

Maintenant que vous avez appris les bases du flux de travail Git, essayez de l'exécuter plusieurs fois par vous-même (voir les instructions).

À ce point de contrôle, vous êtes demandé de prendre des captures d'écran pour chaque étape de la section des instructions, puis de pousser ces captures d'écran vers le dépôt GitHub.

Instructions

1. Créer un dossier appelé learn_git.

```
De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode
$ mkdir Learn_git

De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode
$ |
```

2. Cd (changer de répertoire) dans le dossier learn_git.

```
De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode
$ cd Learn_git/

De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git
$ |
```

3. Créer un fichier appelé third.txt.

```
De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git
$ touch third.txt

De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git
$ |
```

4. Initialiser un dépôt git vide.

```
Dell@DESKTOP-OMGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git
$ git init
Initialized empty Git repository in C:/Users/Dell/Desktop/GoMycode/Learn_git/.git/

Dell@DESKTOP-OMGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |
```

5. Ajouter third.txt à la staging area.

```
Dell@DESKTOP-OMGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git add third.txt

Dell@DESKTOP-OMGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |
```

6. Commiter avec le message "adding third.txt".

```
Dell@DESKTOP-OMGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git commit -m "adding third.txt"
[master (root-commit) 80beb42] adding third.txt
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 third.txt

Dell@DESKTOP-OMGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |
```

7. Vérifiez votre validation avec git log.

```
Dell@DESKTOP-OMGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git log
commit 80beb42b5d3da39a1a1e0631a88efcc4b4277c11 (HEAD -> master)
Author: Ousmane soo <sowbayero14@gmail.com>
Date: Thu Jun 18 11:06:40 2026 +0100

    adding third.txt

Dell@DESKTOP-OMGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |
```

8. Créez un autre fichier appelé fourth.txt.

```
De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ touch fourth.txt

De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |
```

9. Ajoutez fourth.txt à la staging area.

```
De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git add fourth.txt

De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |
```

10. Vérifiez avec le message "adding fourth.txt"

```
De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git log --pretty=oneline
80beb42b5d3da39a1a1e0631a88efcc4b4277c11 (HEAD -> master) adding third.txt

De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git commit -m "adding fourth.txt"
[master 200d794] adding fourth.txt
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 fourth.txt

De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |
```

11. Enlevez le fichier third.txt.

```
De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git rm third.txt
rm 'third.txt'

De11@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ ls
fourth.txt
```

12. Ajoutez cette modification à la staging area. (En utilisant la commande "git add .")

```

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git add .

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |

```

13. Commiter avec le message "removing third.txt".

```

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git commit -m "removing third.txt"
[master b50fbbc] removing third.txt
1 file changed, 0 insertions(+), 0 deletions(-)
delete mode 100644 third.txt

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |

```

14. Vérifiez vos commits en utilisant git log.

```

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git log
commit b50fbbc2d29ee7271cc2e63271a64d4888f20e9a (HEAD -> master)
Author: Ousmane soo <sowbayero14@gmail.com>
Date: Thu Jun 18 12:42:11 2026 +0100

    removing third.txt

commit 200d7944840acf8419c3967a13e69fbbfa753f50
Author: Ousmane soo <sowbayero14@gmail.com>
Date: Thu Jun 18 12:20:23 2026 +0100

    adding fourth.txt

commit 80beb42b5d3da39a1a1e0631a88efcc4b4277c11
Author: Ousmane soo <sowbayero14@gmail.com>
Date: Thu Jun 18 11:06:40 2026 +0100

    adding third.txt

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |

```

15. Changez vos paramètres globaux pour core.pager=cat - vous pouvez en savoir plus ici.

```

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git config --global core.pager cat

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |

```

16. Écrivez la commande appropriée pour lister toutes les configurations globales pour git sur votre machine.

```

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git config --global --list
user.email=sowbayero14@gmail.com
user.name=Ousmane soo
color.ui=auto
core.pager=cat

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ |

```

17. Vous pouvez taper git config --global pour savoir comment faire.

```

De1l@DESKTOP-0MGNLGR MINGW64 ~/Desktop/GoMycode/Learn_git (master)
$ git config --global
usage: git config [<options>]

Config file location
  --[no-]global          use global config file
  --[no-]system          use system config file
  --[no-]local           use repository config file
  --[no-]worktree        use per-worktree config file
  -f, --[no-]file <file>
                        use given config file
  --[no-]blob <blob-id> read config from given blob object

Action
  --[no-]get             get value: name [value-pattern]
  --[no-]get-all        get all values: key [value-pattern]
  --[no-]get-regexp      get values for regexp: name-regex [value-pattern]
  --[no-]get-urlmatch    get value specific for the URL: section[.var] URL
  --[no-]replace-all    replace all matching variables: name value [value-pattern]
  --[no-]add             add a new variable: name value
  --[no-]unset           remove a variable: name [value-pattern]
  --[no-]unset-all      remove all matches: name [value-pattern]
  --[no-]rename-section  rename section: old-name new-name
  --[no-]remove-section  remove a section: name
  -l, --[no-]list        list all
  --[no-]fixed-value     use string equality when comparing values to 'value-pattern'
  -e, --[no-]edit        open an editor
  --[no-]get-color       find the color configured: slot [default]
  --[no-]get-colorbool   find the color setting: slot [stdout-is-tty]

Type
  -t, --[no-]type <type>
                        value is given this type
  --bool                value is "true" or "false"
  --int                 value is decimal number
  --bool-or-int          value is --bool or --int
  --bool-or-str          value is --bool or string
  --path                value is a path (file or directory name)
  --expiry-date          value is an expiry date

Other
  -z, --[no-]null        terminate values with NUL byte
  --[no-]name-only       show variable names only
  --[no-]includes        respect include directives on lookup
  --[no-]show-origin     show origin of config (file, standard input, blob, command line)
  --[no-]show-scope      show scope of config (worktree, local, global, system, command)
  --[no-]default <value>
                        with --get, use default value when missing entry
  --[no-]comment <value>
                        human-readable comment string (# will be prepended as needed)

```

[Git Immersion](#)

Webographie