



Our chance to save the earth,
Outdo with Outdid...

ION HIVE

CHARGE WITH US !



Powered By
Outdid Unified Pvt Ltd



3.5kW AC Charger

**Our chance to save the earth,
Outdo with Outdid...**



TECHNICAL SPECIFICATION

Input power

- Input Voltage: 230 VAC $\pm 20\%$, Single Phase
- Frequency: 50/60 Hz
- Current Ratings: 5A / 10A / 16A
- Connection Type: L, N, and PE (Ground); hardwired via terminal block
- Standby Power Consumption: < 5W

Output power

- Output Voltage: 230V AC, Single Phase
- Output Current: 5A / 10A / 16A
- Frequency: 50/60 Hz

Protection Features

- Upstream Protection: Compliant with local regulatory requirements
- Electrical Protections: Overcurrent (OC), Undervoltage (UV), Overvoltage (OV), Residual Current (RC), Overtemperature (OT), Surge Protection, Short Circuit, Ground Fault, and Plug-Out Protection
- Auto-Recovery from Nuisance Trips: The EVSE automatically resumes charging after minor faults such as OVP, UVP, OTP, or OV—no user intervention needed

Communication

- Network Interfaces: Wi-Fi and Bluetooth Low Energy (BLE)
- Charging Protocols: MQTT and OCPP 1.6J

User Interface & Control

- Status Indicators: Multi-color LEDs for Power, Network, Charging, and System Status
- Control Access: Mobile App and Web Interface
- Remote Configuration: Adjustable Charging Current and Duration via IONHIVE'S App

Key Features

- 3.5 kW Charging via 16A, 3-Pin Socket
- Supports up to 16A at 230V AC
- Built-in Wi-Fi for seamless connectivity
- Wide Operating Voltage Range: 110V AC – 260V AC
- Residual Current Detection: 3–100 mA (AC Leakage Protection)
- Remote Authentication for Start/Stop
- Supported Protocols: MQTT and OCPP 1.6
- Firmware Upgradeable (OTA)
- Ingress Protection: IP65-rated enclosure

Mechanical Specifications

- Enclosure: Customizable based on customer requirements
- Dimensions (W x H x D): 230 x 160 x 80 mm (excluding charging cable, mounting plate, and cable holder)
- Weight: 1 kg (unpackaged)

Charging Interface

- Connector Type: 16A, 3-Pin Socket (3.5 kW Output)

Regulatory Compliance

- Compliant with IEC 61851-1 and IEC 61851-2 standards
- Certification support available upon request

