

Streams

Rupesh Nasre.

OOAIA
January 2020

I/O

- Input stream
 - `istream` `cin`
 - Defaults to keyboard / `stdin`
- Output stream
 - `ostream` `cout`
 - Defaults to console / `stdout`
- Uses header `<iostream>`
- `cin` and `cout` are objects.
 - `>>` and `<<` are overloaded.

```
#include <iostream>

int main() {
    std::string name;
    std::cout << "Enter your name: ";
    std::cin >> name;
    std::cout << "Hello " << name << "!\n";

    return 0;
}
```

cin

- By default, reads whitespace-separated formatted tokens.
 - But be careful with char and string.
- Example stream: **12 17.3 -19**

```
int A, B;  
double X;  
cin >> A; 12  
cin >> X; 17.3  
cin >> B; -19
```

```
int A, B;  
char X;  
cin >> A; 12  
cin >> B; 17  
cin >> X; '.'  
cin >> A; 3
```

```
int A;  
char B, C, D;  
cin >> A; 12  
cin >> B; '1'  
cin >> C; '7'
```

```
string A, B, C;  
cin >> A; "12"  
cin >> B; "17.3"  
cin >> C; "-19"
```

ignore

- cin ignores the leading whitespace.
- One can ignore input until a character of relevance is seen.
 - cin.**ignore**(N, ch); // skip upto N or till ch is seen.
 - Useful for ignoring a line (ch = '\n')

```
cout << "Enter your name: ";  
cin.ignore(2, 'A');
```

```
cin >> name;      // ABCD  
cout << name;     // BCD
```

```
cout << "Enter your name: ";  
cin.ignore(2, 'Z');
```

```
cin >> name;      // ABCD  
cout << name;     // CD
```

cout

- Uses buffered output
 - \n can be printed with **endl**.
 - May not print to screen.
 - To force, use **cout << flush**.
 - **endl** involves **flush**.

```
#include <iostream>

int main() {
    std::string name;
    std::cout << "Enter your name: ";
    std::cin >> name;
    std::cout << "Hello " << name << endl;

    return 0;
}
```

File streams

- `#include <fstream>`
 - `ifstream` and `ofstream`

**What is the
output?**

**What is the
issue?**

stream4.cpp

```
#include <iostream>
#include <fstream>
using namespace std;

int main() {
    ifstream file("stream4.cpp");
    string word;
    while (!file.eof()) {
        file >> word;
        cout << word;
    }

    file.close(); // optional
    return 0;
}
```

```
#include<iostream>#include<fstream>usingnamespacestd;intmain()
{ifstreamfile("stream4.cpp");stringword;while(!file.eof())
{file>>word;cout<<word;}file.close();//optionalreturn0;}}
```

ifstream

- **Issue:** Last line is read twice.
- **Solution:** read precedes eof.

stream4.cpp

```
#include <iostream>
#include <fstream>
using namespace std;

int main() {
    ifstream file("stream4.cpp");
    string word;
    file >> word;
    while (!file.eof()) {
        cout << word;
        file >> word;
    }

    file.close(); // optional
    return 0;
}
```

```
#include<iostream>#include<fstream>usingnamespacestd;intmain()
{ifstreamfile("stream4.cpp");stringword;while(!file.eof())
{file>>word;cout<<word;}file.close();//optionalreturn0;}
```

cat

- What is the output?

```
#include <iostream>
#include <fstream>
using namespace std;

int main() {
    ifstream file("stream4.cpp");
    string line;
    getline(file, line);
    while (!file.eof()) {
        cout << line;
        getline(file, line);
    }

    file.close(); // optional
    return 0;
}
```

```
#include <iostream>#include <fstream>using namespace std;int main() {    ifstream
file("stream4.cpp");    string word;    while (!file.eof()) {        file >> word;        cout << word;
    }    file.close();    // optional    return 0;}
```


cat

- What is the output?

```
#include <iostream>
#include <fstream>
using namespace std;

int main() {
    ifstream file("stream4.cpp");
    string word;
    while (!file.eof()) {
        file >> word;
        cout << word;
    }

    file.close(); // optional
    return 0;
}
```

```
#include <iostream>
#include <fstream>
using namespace std;

int main() {
    ifstream file("stream4.cpp");
    string line;
    getline(file, line);
    while (!file.eof()) {
        cout << line << endl;
        getline(file, line);
    }

    file.close(); // optional
    return 0;
}
```

cp

- a.out <inputfile> <outputfile>

```
#include <iostream>
#include <fstream>
#include <stdlib.h>
using namespace std;

int main(int argc, char *argv[]) {
    ifstream iifile(argv[1]);
    ofstream oofile(argv[2]);
    string line;
    getline(iifile, line);
    while (!iifile.eof()) {
        oofile << line << endl;
        getline(iifile, line);
    }

    return 0;
}
```

cp

- a.out <inputfile> <outputfile>

```
#include <iostream>
#include <fstream>
#include <stdlib.h>
using namespace std;

int main(int argc, char *argv[]) {
    if (argc != 3) {
        cerr << "Usage: " << argv[0] << " <inputfile> <outputfile>" << endl;
        exit(1);
    }
    ifstream iifile(argv[1]);
    ofstream oofile(argv[2]);
    string line;
    getline(iifile, line);
    while (!iifile.eof()) {
        oofile << line << endl;
        getline(iifile, line);
    }

    return 0;
}
```

```
#include <iostream>
#include <fstream>
#include <stdlib.h>
using namespace std;

int main(int argc, char *argv[]) {
    if (argc != 3) {
        cerr << "Usage: " << argv[0] << " <inputfile> <outputfile>" << endl;
        exit(1);
    }
    ifstream iifile(argv[1]);
    if (iifile.fail()) {
        cerr << "File " << argv[1] << " could not be opened." << endl;
        exit(2);
    }
    ofstream oofile(argv[2]);
    string line;
    getline(iifile, line);
    while (!iifile.eof()) {
        oofile << line << endl;
        getline(iifile, line);
    }

    return 0;
}
```

Formatted I/O

data.txt

Name: Roll Number: Marks
John Augustine: CS12D001: 88
Madhu Mutyam: CS11D111: 89
Rupesh Nasre: CS13B000: 25

```
#include <iostream>
#include <fstream>
using namespace std;
```

```
int main() {
    ifstream file("data.txt");
    string name, roll, marks;
```

```
    getline(file, name, ':');
```

```
    while (!file.eof()) {
```

```
        getline(file, roll, ':');
        getline(file, marks, ':');
```

```
        cout << name << ":::" << roll << ":::" << marks << endl;
        getline(file, name, ':');
```

```
    }
```

```
    return 0;
```

```
}
```

Name::: Roll Number::: Marks
John Augustine
CS12D001::: 88
Madhu Mutyam::: CS11D111
89
Rupesh Nasre::: CS13B000::: 25

Formatted I/O

data.txt

Name: Roll Number: Marks
John Augustine: CS12D001: 88
Madhu Mutyam: CS11D111: 89
Rupesh Nasre: CS13B000: 25

Note: getline does not ignore leading whitespace.

```
#include <iostream>
#include <fstream>
using namespace std;

int main() {
    ifstream file("data.txt");
    string name, roll, marks;

    getline(file, name, ':');
    while (!file.eof()) {
        getline(file, roll, ':');
        getline(file, marks);

        cout << name << ":::" << roll << ":::" << marks << endl;
        getline(file, name, ':');
    }
    return 0;
}
```

Name::: Roll Number::: Marks
John Augustine::: CS12D001::: 88
Madhu Mutyam::: CS11D111::: 89
Rupesh Nasre::: CS13B000::: 25

Formatted I/O

Name	Roll Number	Marks
John Augustine	CS12D001	88
Madhu Mutyam	CS11D111	89
Rupesh Nasre	CS13B000	25

```
#include <iostream>
#include <fstream>
#include <iomanip>
using namespace std;

int main() {
    ifstream file("data.txt");
    string name, roll, marks;

    getline(file, name, ':');
    while (!file.eof()) {
        getline(file, roll, ':');
        getline(file, marks);

        cout << setw(20) << name;
        cout << setw(10) << roll;
        cout << setw(10) << marks;
        cout << endl;
        getline(file, name, ':');
    }
    return 0;
}
```

Other functions

- **setprecision**: for floating point values.
- **get**: to read a single character.
- **peek**: to examine a character without removing it from the stream.
- **putback**: add to the stream.

Acknowledgment

- <https://courses.cs.vt.edu/cs1044/Notes/C04.IO.pdf>