

Graph Algorithms - I

CS2800: Design and Analysis of Algorithms

Yadu Vasudev
yadu@cse.iitm.ac.in
IIT Madras

Module plan


1. Graph representations
2. Graph traversals and applications
3. Directed graphs
4. Shortest paths in graphs

Graph representations

Graph: A set of vertices V , and a set of edges $E \subseteq V \times V$

Graphs - basics


Graph: A set of vertices V , and a set of edges $E \subseteq V \times V$



- Transportation networks
- Social networks and the web graph
- Circuits


Graphs - basics

Graph: A set of vertices V , and a set of edges $E \subseteq V \times V$




- Transportation networks
- Social networks and the web graph
- Circuits
- Ubiquitous abstraction for a variety of problems!

Graph representations - adjacency matrices



	1	2	3	4	5	6	7
1	0	1	1	1	0	0	0
2	1	0	1	0	0	0	0
3	1	1	0	0	0	1	0
4	1	0	0	0	1	0	1
5	0	0	0	1	0	1	0
6	0	0	1	0	1	0	1
7	0	0	0	1	0	1	0


Graph representations - adjacency matrices



	1	2	3	4	5	6	7
1	0	1	1	1	0	0	0
2	1	0	1	0	0	0	0
3	1	1	0	0	0	1	0
4	1	0	0	0	1	0	1
5	0	0	0	1	0	1	0
6	0	0	1	0	1	0	1
7	0	0	0	1	0	1	0

- An n vertex graph requires $O(n^2)$ space for the adjacency matrix


Graph representations - adjacency matrices



	1	2	3	4	5	6	7
1	0	1	1	1	0	0	0
2	1	0	1	0	0	0	0
3	1	1	0	0	0	1	0
4	1	0	0	0	1	0	1
5	0	0	0	1	0	1	0
6	0	0	1	0	1	0	1
7	0	0	0	1	0	1	0

- An n vertex graph requires $O(n^2)$ space for the adjacency matrix
- Edge queries can be made in $O(1)$ time


Graph representations - adjacency matrices



	1	2	3	4	5	6	7
1	0	1	1	1	0	0	0
2	1	0	1	0	0	0	0
3	1	1	0	0	0	1	0
4	1	0	0	0	1	0	1
5	0	0	0	1	0	1	0
6	0	0	1	0	1	0	1
7	0	0	0	1	0	1	0

- An n vertex graph requires $O(n^2)$ space for the adjacency matrix
- Edge queries can be made in $O(1)$ time
- Finding all neighbors requires $O(n)$ time



Graph representations - adjacency matrices




	1	2	3	4	5	6	7
1	0	1	1	1	0	0	0
2	1	0	1	0	0	0	0
3	1	1	0	0	0	1	0
4	1	0	0	0	1	0	1
5	0	0	0	1	0	1	0
6	0	0	1	0	1	0	1
7	0	0	0	1	0	1	0

- An n vertex graph requires $O(n^2)$ space for the adjacency matrix
- Edge queries can be made in $O(1)$ time
- Finding all neighbors requires $O(n)$ time
- More useful for representing dense graphs ($|E| = \Omega(n^2)$)

Graph representations - adjacency lists




Graph representations - adjacency lists



- Requires $O(|V| + |E|)$ space to represent a graph
- Checking the existence of edge (u, v) requires time $O(\min\{d(u), d(v)\})$

Graph representations - adjacency lists



- Requires $O(|V| + |E|)$ space to represent a graph
- Checking the existence of edge (u, v) requires time $O(\min\{d(u), d(v)\})$
- Finding all neighbors of u requires $O(d(u))$ time

Graph traversals and applications

Reachability in graphs

Reachability: Given a vertex s , what are the vertices reachable from s via edges of the graph?

Reachability in graphs

Reachability: Given a vertex s , what are the vertices reachable from s via edges of the graph?

- Perhaps the most important primitive of graph operations

Reachability in graphs

Reachability: Given a vertex s , what are the vertices reachable from s via edges of the graph?

- Perhaps the most important primitive of graph operations
- Two important variants:

Reachability in graphs

Reachability: Given a vertex s , what are the vertices reachable from s via edges of the graph?

- Perhaps the most important primitive of graph operations
- Two important variants:
 - Depth-First Search (DFS)
 - Breadth-First Search (BFS)

Reachability in graphs

Reachability: Given a vertex s , what are the vertices reachable from s via edges of the graph?


- Perhaps the most important primitive of graph operations
- Two important variants:
 - Depth-First Search (DFS)
 - Breadth-First Search (BFS)
- Can be used to collect a lot of auxiliary information about the structure of the graph, and
- both BFS and DFS are highly efficient in terms of time and space complexity

Depth-First Search

How do you traverse a maze?


Depth-First Search

How do you traverse a maze?



Depth-First Search


How do you traverse a maze?



- Mark the starting location with a chalk

Depth-First Search


How do you traverse a maze?



- Mark the starting location with a chalk
- Walk along a path until you reach the next junction, mark the junction

Depth-First Search


How do you traverse a maze?



- Mark the starting location with a chalk
- Walk along a path until you reach the next junction, mark the junction
- Keep continuing until you reach your destination or hit a dead-end

Depth-First Search


How do you traverse a maze?



- Mark the starting location with a chalk
- Walk along a path until you reach the next junction, mark the junction
- Keep continuing until you reach your destination or hit a dead-end
- If you hit a dead-end or an already marked junction, retrace your steps to the last marked junction and try out the next path ...

Depth-First Search


How do you traverse a maze?



- Mark the starting location with a chalk
- Walk along a path until you reach the next junction, mark the junction
- Keep continuing until you reach your destination or hit a dead-end
- If you hit a dead-end or an already marked junction, retrace your steps to the last marked junction and try out the next path ...

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
        starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```


Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
        starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
        starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```


Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
        starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```


Depth-First Search

How do you traverse a maze?



RECURSIVEDFS

if v is unmarked then


mark v

```
foreach edge vw do
```

Recursively traverse
starting from v

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
  mark v
  foreach edge vw do
    Recursively traverse
      starting from v
```

Depth-First Search

How do you traverse a maze?




RECURSIVEDFS

```
if v is unmarked then
    mark v
    foreach edge vw do
        Recursively traverse
            starting from v
```

Depth-First Search

How do you traverse a maze?



ITERATIVEDFS

push(s)

while stack is not empty **do**

$v \leftarrow \text{pop}()$

if v is unmarked **then**


mark v

foreach edge vw **do**

push(w)

Depth-First Search

How do you traverse a maze?



ITERATIVEDFS

push(\emptyset, s)

while stack is not empty **do**

 (p, v) \leftarrow pop()

if v is unmarked **then**

 mark v


 parent(v) $\leftarrow p$

foreach edge vw **do**

 push(v, w)

Depth-First Search

How do you traverse a maze?



ITERATIVEDFS

push(\emptyset, s)

while stack is not empty **do**

 (p, v) \leftarrow pop()

if v is unmarked **then**

 mark $v \longrightarrow O(1)/\text{vertex}$

 parent(v) $\leftarrow p$


foreach edge vw **do**

 push(v, w)

$\longrightarrow O(d(v))/\text{vertex}$

Depth-First Search

How do you traverse a maze?



ITERATIVEDFS


```
push( $\emptyset$ , s)
while stack is not empty do
  ( $p, v$ )  $\leftarrow$  pop()
  if  $v$  is unmarked then
    mark  $v$   $\longrightarrow$   $O(1)/\text{vertex}$ 
    parent( $v$ )  $\leftarrow p$ 
    foreach edge  $vw$  do
      push( $v, w$ )
```

$\longrightarrow O(d(v))/\text{vertex}$

Running time $O(|V| + |E|)$ in adjacency list model

Depth-First Search

How do you traverse a maze?



ITERATIVEDFS


```
push( $\emptyset, s$ )  
while stack is not empty do  
  ( $p, v$ )  $\leftarrow$  pop()  
  if  $v$  is unmarked then  
    mark  $v \longrightarrow O(1)/\text{vertex}$   
    parent( $v$ )  $\leftarrow p$   
    foreach edge  $vw$  do  
      push( $v, w$ )
```

$O(d(v))/\text{vertex}$

Running time $O(|V| + |E|)$ in adjacency list model

Question What is the running time in the adjacency matrix model?


Depth-First Search



Lemma: The following statements are true for DFS:

1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Depth-First Search




Lemma: The following statements are true for DFS:

1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Proof of (1): Induction on the length of the shortest path

Depth-First Search




Lemma: The following statements are true for DFS:

1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Proof of (1): Induction on the length of the shortest path

Let $s - u_1 - u_2 - \dots - u - v$ be a shortest path from s to v

Depth-First Search




Lemma: The following statements are true for DFS:

1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Proof of (1): Induction on the length of the shortest path

Let $s - u_1 - u_2 - \dots - u - v$ be a shortest path from s to v

Depth-First Search



Lemma: The following statements are true for DFS:


1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Proof of (1): Induction on the length of the shortest path

Let $s - u_1 - u_2 - \dots - u - v$ be a shortest path from s to v

By the induction hypothesis, u is marked by the DFS

Depth-First Search



Lemma: The following statements are true for DFS:

1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Proof of (1): Induction on the length of the shortest path


Let $s - u_1 - u_2 - \dots - u - v$ be a shortest path from s to v

By the induction hypothesis, u is marked by the DFS

If u is marked, then all the neighbors of u are placed in the stack. Therefore when they are taken out of the stack, either

- They are already marked, or
- They are unmarked and will get marked at that stage

Depth-First Search




Lemma: The following statements are true for DFS:

1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Proof of (2): Induction on the time at which v is marked

Depth-First Search




Lemma: The following statements are true for DES:

1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Proof of (2): Induction on the time at which v is marked

If $w = \text{parent}(v)$, then w is marked before v - There must be a path from w to s and hence from v to s

Depth-First Search



Lemma: The following statements are true for DFS:

1. DFS marks those vertices reachable from s and only those vertices.
2. The set of pairs $(v, \text{parent}(v))$ defines a spanning tree of the component containing s .

Proof of (2): Induction on the time at which v is marked

If $w = \text{parent}(v)$, then w is marked before v - There must be a path from w to s and hence from v to s


Every vertex v has a unique parent (except s that has no parent), and hence the subgraph has $n - 1$ edges \Rightarrow spanning tree

Breadth-First Search

How do you find the shortest path in a maze?

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```


Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  ( $p, v$ )  $\leftarrow$  dequeue()
  if  $v$  is unmarked then
    mark  $v$ 
    parent( $v$ )  $\leftarrow p$ 
    foreach edge  $vw$  do
      enqueue( $v, w$ )
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  ( $p, v$ )  $\leftarrow$  dequeue()
  if  $v$  is unmarked then
    mark  $v$ 
    parent( $v$ )  $\leftarrow p$ 
    foreach edge  $vw$  do
      enqueue( $v, w$ )
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  ( $p, v$ )  $\leftarrow$  dequeue()
  if  $v$  is unmarked then
    mark  $v$ 
    parent( $v$ )  $\leftarrow p$ 
    foreach edge  $vw$  do
      enqueue( $v, w$ )
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  ( $p, v$ )  $\leftarrow$  dequeue()
  if  $v$  is unmarked then
    mark  $v$ 
    parent( $v$ )  $\leftarrow p$ 
    foreach edge  $vw$  do
      enqueue( $v, w$ )
```

Breadth-First Search

How do you find the shortest path in a maze?



BFS

enqueue(\emptyset, s)

```
while queue is not empty do
```

$(p, v) \leftarrow \text{dequeue}()$

if v is unmarked then

mark v


$$\text{parent}(v) \leftarrow p$$

```
foreach edge vw do
```

enqueue(v, w)

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  ( $p, v$ )  $\leftarrow$  dequeue()
  if  $v$  is unmarked then
    mark  $v$ 
    parent( $v$ )  $\leftarrow p$ 
    foreach edge  $vw$  do
      enqueue( $v, w$ )
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

Breadth-First Search

How do you find the shortest path in a maze?




BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```


Breadth-First Search

How do you find the shortest path in a maze?



BFS

```
enqueue( $\emptyset$ , s)
while queue is not empty do
  (p, v)  $\leftarrow$  dequeue()
  if v is unmarked then
    mark v
    parent(v)  $\leftarrow$  p
    foreach edge vw do
      enqueue(v, w)
```

DFS vs BFS




Figure 1: DFS tree




Figure 2: BFS tree

Applications: Connected components

Question: How many connected components are there in the graph?

Applications: Connected components

Question: How many connected components are there in the graph?

- DFS/BFS starting from a vertex s visits those and only those vertices that lie in the same connected component as s

Applications: Connected components

Question: How many connected components are there in the graph?

- DFS/BFS starting from a vertex s visits those and only those vertices that lie in the same connected component as s

DFSALL(G)

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**

DFS(v)

DFS(s)

 push(s)
 while stack is not empty **do**
 $v \leftarrow$ pop()
 if v is unmarked **then**
 mark v

foreach edge vw **do**
 push(w)

Applications: Connected components

Question: How many connected components are there in the graph?

- DFS/BFS starting from a vertex s visits those and only those vertices that lie in the same connected component as s

DFSALL(G)

```
foreach vertex  $v \in G$  do  
    unmark  $v$ 
```

```
 $cc \leftarrow 0$ 
```

```
foreach vertex  $v \in G$  do  
    if  $v$  is unmarked then  
         $cc \leftarrow cc + 1$   
        DFS( $v$ )
```

DFS(s)

```
push( $s$ )
```

```
while stack is not empty do
```

```
     $v \leftarrow \text{pop}()$ 
```

```
    if  $v$  is unmarked then  
        mark  $v$ 
```

```
    foreach edge  $vw$  do  
        push( $w$ )
```

Applications: Connected components

Question: How many connected components are there in the graph?

- DFS/BFS starting from a vertex s visits those and only those vertices that lie in the same connected component as s

DFSALL(G)

```
foreach vertex  $v \in G$  do  
    unmark  $v$ 
```

```
 $cc \leftarrow 0$ 
```

```
foreach vertex  $v \in G$  do  
    if  $v$  is unmarked then  
         $cc \leftarrow cc + 1$   
        DFS( $v$ )
```



unmarked vertex means new component

DFS(s)

```
push( $s$ )
```

```
while stack is not empty do
```

```
     $v \leftarrow \text{pop}()$ 
```

```
    if  $v$  is unmarked then
```

```
        mark  $v$ 
```

```
    foreach edge  $vw$  do
```

```
        push( $w$ )
```

Applications: Connected components

Question: How many connected components are there in the graph?

- DFS/BFS starting from a vertex s visits those and only those vertices that lie in the same connected component as s

DFSALL(G)

```
foreach vertex  $v \in G$  do  
    unmark  $v$ 
```

```
 $cc \leftarrow 0$ 
```

```
foreach vertex  $v \in G$  do  
    if  $v$  is unmarked then  
         $cc \leftarrow cc + 1$   
        DFS( $v$ )
```



unmarked vertex means new component

DFS(s)

```
push( $s$ )
```

```
while stack is not empty do
```

```
     $v \leftarrow \text{pop}()$ 
```

```
    if  $v$  is unmarked then
```

```
        mark  $v$ 
```

```
         $\text{comp}[v] = cc$ 
```

```
        foreach edge  $vw$  do  
            push( $w$ )
```


Applications: Connected components

Question: How many connected components are there in the graph?

- DFS/BFS starting from a vertex s visits those and only those vertices that lie in the same connected component as s

DFSALL(G)

```
foreach vertex  $v \in G$  do  
    unmark  $v$ 
```

```
 $cc \leftarrow 0$ 
```

```
foreach vertex  $v \in G$  do  
    if  $v$  is unmarked then  
         $cc \leftarrow cc + 1$   
        DFS( $v$ )
```

unmarked vertex means new component

DFS(s)

```
push( $s$ )
```

```
while stack is not empty do
```

```
     $v \leftarrow \text{pop}()$ 
```

```
    if  $v$  is unmarked then
```

```
        mark  $v$ 
```

```
         $\text{comp}[v] = cc \longrightarrow$  component label
```


```
        foreach edge  $vw$  do  
            push( $w$ )
```

Directed graphs

Directed graphs: Basics


Directed graphs: Basics

- $G(V, E) - E \subseteq V \times V$: Implicitly assumed a symmetric relation earlier



Directed graphs: Basics


- $G(V, E) - E \subseteq V \times V$: Implicitly assumed a symmetric relation earlier



- If you get pairwise movie preferences for a person, can you rank-order their favourite movies?

Directed graphs: Basics

- $G(V, E) - E \subseteq V \times V$: Implicitly assumed a symmetric relation earlier



- If you get pairwise movie preferences for a person, can you rank-order their favourite movies?
 - Pairwise preferences - directed edges
 - Rank-ordering - Hamiltonian path

DFS in directed graphs: Classification of edges

DFS in directed graphs: Classification of edges

DFSALL(G)

foreach vertex $v \in G$ **do**

 unmark v

foreach vertex $v \in G$ **do**

if v is unmarked **then**

 DFS(v)

DFS(s)

mark s

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**

 parent[w] $\leftarrow s$

 DFS(w)

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**

 unmark v

foreach vertex $v \in G$ **do**

if v is unmarked **then**

 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**

 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

clock \leftarrow clock+1

end[s] \leftarrow clock

return clock

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**
 parent[w] $\leftarrow s$


 clock \leftarrow DFS(w , clock)

clock \leftarrow clock+1

end[s] \leftarrow clock

return clock

start=1



u

unmarked

u

marked, not finished

u

finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**
 parent[w] $\leftarrow s$


 clock \leftarrow DFS(w , clock)

clock \leftarrow clock+1

end[s] \leftarrow clock

return clock

start=1



start=2

u

unmarked

u

marked, not finished

u

finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**


if w is unmarked **then**
 parent[w] $\leftarrow s$




 clock \leftarrow DFS(w , clock)

clock \leftarrow clock+1

end[s] \leftarrow clock

return clock



-  unmarked
-  marked, not finished
-  finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**


if w is unmarked **then**
 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

clock \leftarrow clock+1

end[s] \leftarrow clock

return clock



- u (white circle) unmarked
- u (pink circle) marked, not finished
- u (green circle) finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



- u (white circle) unmarked
- u (pink circle) marked, not finished
- u (green circle) finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



u

unmarked

u

marked, not finished

u

finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



u

unmarked

u

marked, not finished

u

finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



- u (white circle) unmarked
- u (pink circle) marked, not finished
- u (green circle) finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



- u (white circle) unmarked
- u (pink circle) marked, not finished
- u (green circle) finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



- u (pink) unmarked
- u (pink) marked, not finished
- u (green) finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



- u unmarked
- u marked, not finished
- u finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



- u unmarked
- u marked, not finished
- u finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1

 end[s] \leftarrow clock

return clock



- u (white circle) unmarked
- u (pink circle) marked, not finished
- u (green circle) finished

DFS in directed graphs: Classification of edges

DFSALL(G)

clock $\leftarrow 0$

foreach vertex $v \in G$ **do**
 unmark v

foreach vertex $v \in G$ **do**
 if v is unmarked **then**
 DFS(v , clock)

DFS(s , clock)

mark s

clock \leftarrow clock+1

start[s] \leftarrow clock

foreach edge $s \rightarrow w$ **do**

if w is unmarked **then**


 parent[w] $\leftarrow s$

 clock \leftarrow DFS(w , clock)

 clock \leftarrow clock+1


 end[s] \leftarrow clock

return clock




- u unmarked
- u marked, not finished
- u finished

DFS in directed graphs: Classification of edges




DFS in directed graphs: Classification of edges




- **Tree edge:** $\text{start}[s] < \text{start}[t] < \text{end}[t] < \text{end}[s]$, and $\text{DFS}(t)$ is directly called by $\text{DFS}(s)$

DFS in directed graphs: Classification of edges




- **Tree edge:** $\text{start}[s] < \text{start}[t] < \text{end}[t] < \text{end}[s]$, and $\text{DFS}(t)$ is directly called by $\text{DFS}(s)$
- **Forward edge:** $\text{start}[t] < \text{start}[v] < \text{end}[v] < \text{end}[t]$, but $\text{DFS}(v)$ is **not** directly called by $\text{DFS}(t)$

DFS in directed graphs: Classification of edges



- **Tree edge:** $\text{start}[s] < \text{start}[t] < \text{end}[t] < \text{end}[s]$, and $\text{DFS}(t)$ is directly called by $\text{DFS}(s)$
- **Forward edge:** $\text{start}[t] < \text{start}[v] < \text{end}[v] < \text{end}[t]$, but $\text{DFS}(v)$ is **not** directly called by $\text{DFS}(t)$
- **Back edge:** $\text{start}[s] < \text{start}[u] < \text{end}[u] < \text{end}[s]$, and there is a directed path from s to u

DFS in directed graphs: Classification of edges



- **Tree edge:** $\text{start}[s] < \text{start}[t] < \text{end}[t] < \text{end}[s]$, and $\text{DFS}(t)$ is directly called by $\text{DFS}(s)$
- **Forward edge:** $\text{start}[t] < \text{start}[v] < \text{end}[v] < \text{end}[t]$, but $\text{DFS}(v)$ is **not** directly called by $\text{DFS}(t)$
- **Back edge:** $\text{start}[s] < \text{start}[u] < \text{end}[u] < \text{end}[s]$, and there is a directed path from s to u
- **Cross edge:** v is **finished** when $\text{DFS}(w)$ starts - $\text{end}[v] < \text{start}[w]$


Cycles in directed graphs

Cycles in directed graphs

When does a digraph have a cycle?


Cycles in directed graphs

When does a digraph have a cycle?



Cycles in directed graphs


When does a digraph have a cycle?



- There must a back-edge in the DFS traversal

Cycles in directed graphs


When does a digraph have a cycle?



- There must be a back-edge in the DFS traversal
- There is an edge $u \rightarrow v$ such that $\text{end}[u] < \text{end}[v]$

Cycles in directed graphs

When does a digraph have a cycle?



- There must be a back-edge in the DFS traversal
- There is an edge $u \rightarrow v$ such that $end[u] < end[v]$

Exercise: Write the pseudo-code for the $O(|V| + |E|)$ algorithm to check if G is a **DAG** (Directed Acyclic Graph)?

$\text{FIB}(n)$

if $n = 1$ or 2 **then return** 1

return $\text{FIB}(n - 1) + \text{FIB}(n - 2)$


Recursion and DAGs

Dependency digraph

$\text{FIB}(n)$

if $n = 1$ or 2 **then return** 1

return $\text{FIB}(n - 1) + \text{FIB}(n - 2)$




Recursion and DAGs

Dependency digraph

$\text{FIB}(n)$

if $n = 1$ or 2 then return 1

return $\text{FIB}(n - 1) + \text{FIB}(n - 2)$



- Recursive function calls can be simulated by a DFS of the dependency graph – memoization


Recursion and DAGs

Dependency digraph

$\text{FIB}(n)$

if $n = 1$ or 2 then return 1

return $\text{FIB}(n - 1) + \text{FIB}(n - 2)$




- Recursive function calls can be simulated by a DFS of the dependency graph – **memoization**
- What is the order in which the recursive calls are made?

Recursion and DAGs

Dependency digraph

$\text{FIB}(n)$

if $n = 1$ or 2 then return 1
return $\text{FIB}(n - 1) + \text{FIB}(n - 2)$




- Recursive function calls can be simulated by a DFS of the dependency graph – **memoization**
- What is the order in which the recursive calls are made?
 - DFS defines an order on the vertices of the graph

Recursion and DAGs

Dependency digraph

$\text{FIB}(n)$

if $n = 1$ or 2 then return 1
return $\text{FIB}(n - 1) + \text{FIB}(n - 2)$



- Recursive function calls can be simulated by a DFS of the dependency graph – **memoization**
- What is the order in which the recursive calls are made?
 - DFS defines an order on the vertices of the graph
 $\text{FIB}(6) \rightarrow \text{FIB}(5) \rightarrow \text{FIB}(4) \rightarrow \text{FIB}(3) \rightarrow \text{FIB}(2) \rightarrow \text{FIB}(1)$

Topological ordering of DAGs



Topological ordering of DAGs



An ordering $<$ of vertices is said to be a **topological order** if

$$(u, v) \in E \Rightarrow u < v$$

Topological ordering of DAGs



An ordering $<$ of vertices is said to be a **topological order** if

$$(u, v) \in E \Rightarrow u < v$$

Observation: If the digraph contains a cycle, then there is no topological ordering

Topological ordering of DAGs




An ordering $<$ of vertices is said to be a **topological order** if

$$(u, v) \in E \Rightarrow u < v$$

Observation: If the digraph contains a cycle, then there is no topological ordering

Question: Do all DAGs have a topological ordering?

Topological ordering of DAGs




An ordering $<$ of vertices is said to be a **topological order** if

$$(u, v) \in E \Rightarrow u < v$$

Observation: If the digraph contains a cycle, then there is no topological ordering

Question: Do all DAGs have a topological ordering?

Topological ordering of DAGs



An ordering $<$ of vertices is said to be a **topological order** if


$$(u, v) \in E \Rightarrow u < v$$

\searrow
 $\text{end}(u) > \text{end}(v)$

Observation: If the digraph contains a cycle, then there is no topological ordering

Question: Do all DAGs have a topological ordering?

Topological ordering of DAGs



An ordering $<$ of vertices is said to be a **topological order** if

$$(u, v) \in E \Rightarrow u < v$$


\searrow
 $\text{end}(u) > \text{end}(v)$

Observation: If the digraph contains a cycle, then there is no topological ordering

Question: Do all DAGs have a topological ordering?


Theorem: The ordering of vertices in the decreasing order of their DFS end-times is a topological order

Topological ordering of DAGs



Theorem: The ordering of vertices in the decreasing order of their DFS end-times is a topological order


Topological ordering of DAGs



Theorem: The ordering of vertices in the decreasing order of their DFS end-times is a topological order

Proof: Suppose not. Let $(u, v) \in E$ and $\text{end}[u] < \text{end}[v]$.

Topological ordering of DAGs




Theorem: The ordering of vertices in the decreasing order of their DFS end-times is a topological order

Proof: Suppose not. Let $(u, v) \in E$ and $\text{end}[u] < \text{end}[v]$.

Three cases possible about their start times

Topological ordering of DAGs



Theorem: The ordering of vertices in the decreasing order of their DFS end-times is a topological order

Proof: Suppose not. Let $(u, v) \in E$ and $\text{end}[u] < \text{end}[v]$.

Three cases possible about their start times

- $\text{start}[u] < \text{end}[u] < \text{start}[v] < \text{end}[v]$: not possible because if DFS from u starts before v , then it cannot end before the DFS of v since $(u, v) \in E$
- $\text{start}[u] < \text{start}[v] < \text{end}[u] < \text{end}[v]$: not possible for any DFS
- $\text{start}[v] < \text{start}[u] < \text{end}[u] < \text{end}[v]$: path from v to $u \Rightarrow$ there must be a cycle that includes the edge (u, v)

Topological ordering of DAGs

Observation: In a DAG G , if $(u, v) \in E$ then $\text{end}[u] > \text{end}[v]$

Topological ordering of DAGs

Observation: In a DAG G , if $(u, v) \in E$ then $\text{end}[u] > \text{end}[v]$

Observation: Every DAG contains a source (vertex with in-degree=0) and a sink (vertex with out-degree=0)

Topological ordering of DAGs

Observation: In a DAG G , if $(u, v) \in E$ then $\text{end}[u] > \text{end}[v]$

Observation: Every DAG contains a source (vertex with in-degree=0) and a sink (vertex with out-degree=0)

The vertex u with highest $\text{end}[u]$ must be a source, and v with the lowest $\text{end}[v]$ must be a sink.

Topological ordering of DAGs

Observation: In a DAG G , if $(u, v) \in E$ then $\text{end}[u] > \text{end}[v]$

Observation: Every DAG contains a source (vertex with in-degree=0) and a sink (vertex with out-degree=0)

The vertex u with highest $\text{end}[u]$ must be a source, and v with the lowest $\text{end}[v]$ must be a sink.

Algorithm: Find a source, append it to the topological ordering, delete the vertex and its edges, continue ...

Topological ordering of DAGs

Observation: In a DAG G , if $(u, v) \in E$ then $\text{end}[u] > \text{end}[v]$

Observation: Every DAG contains a source (vertex with in-degree=0) and a sink (vertex with out-degree=0)

The vertex u with highest $\text{end}[u]$ must be a source, and v with the lowest $\text{end}[v]$ must be a sink.

Algorithm: Find a source, append it to the topological ordering, delete the vertex and its edges, continue ...

Exercise: Implement this algorithm to run in time $O(|V| + |E|)$

DAGs and the structure of digraphs

DAGs and the structure of digraphs

DFS from v on a digraph covers all vertices u that are reachable from v - $\text{reach}(v)$

DAGs and the structure of digraphs

DFS from v on a digraph covers all vertices u that are reachable from v - $\text{reach}(v)$

- A **strongly connected component** is a maximal subset $V' \subseteq V$ such that for every $u, v \in V'$: $u \in \text{reach}(v)$ and $v \in \text{reach}(u)$
 $\text{scc}(u)$ - strongly connected component containing u

DAGs and the structure of digraphs

DFS from v on a digraph covers all vertices u that are reachable from v - $\text{reach}(v)$

- A **strongly connected component** is a maximal subset $V' \subseteq V$ such that for every $u, v \in V'$: $u \in \text{reach}(v)$ and $v \in \text{reach}(u)$

$\text{scc}(u)$ - strongly connected component containing u

Observation: For every u and v , either

- $\text{scc}(u) = \text{scc}(v)$, or
- $\text{scc}(u) \cap \text{scc}(v) = \emptyset$

DAGs and the structure of digraphs


DFS from v on a digraph covers all vertices u that are reachable from v - $\text{reach}(v)$

- A **strongly connected component** is a maximal subset $V' \subseteq V$ such that for every $u, v \in V'$: $u \in \text{reach}(v)$ and $v \in \text{reach}(u)$

$\text{scc}(u)$ - strongly connected component containing u

Observation: For every u and v , either

- $\text{scc}(u) = \text{scc}(v)$, or
 - $\text{scc}(u) \cap \text{scc}(v) = \emptyset$
- } equivalence relation



DAGs and the structure of digraphs


A **strongly connected component** is a maximal subset $V' \subseteq V$ such that for every $u, v \in V'$: $u \in \text{reach}(v)$ and $v \in \text{reach}(u)$

scc(u) - strongly connected component containing u

DAGs and the structure of digraphs

A **strongly connected component** is a maximal subset $V' \subseteq V$ such that for every $u, v \in V'$: $u \in \text{reach}(v)$ and $v \in \text{reach}(u)$


scc(u) - strongly connected component containing u



DAGs and the structure of digraphs

A **strongly connected component** is a maximal subset $V' \subseteq V$ such that for every $u, v \in V'$: $u \in \text{reach}(v)$ and $v \in \text{reach}(u)$


$scc(u)$ - strongly connected component containing u



DAGs and the structure of digraphs

A **strongly connected component** is a maximal subset $V' \subseteq V$ such that for every $u, v \in V'$: $u \in \text{reach}(v)$ and $v \in \text{reach}(u)$

scc(u) - strongly connected component containing u




Digraph of strongly connected components: **SCC(G)**



DAGs and the structure of digraphs

A **strongly connected component** is a maximal subset $V' \subseteq V$ such that for every $u, v \in V'$: $u \in \text{reach}(v)$ and $v \in \text{reach}(u)$

scc(u) - strongly connected component containing u



Digraph of strongly connected components: **SCC(G)**



Question: Is $\text{SCC}(G)$ always a DAG?

Finding the strongly connected components

Question: Given a $v \in G$, find $\text{scc}(v)$

Finding the strongly connected components


Question: Given a $v \in G$, find $\text{scc}(v)$

- Find the set $\text{reach}(v)$ using DFS

Finding the strongly connected components

Question: Given a $v \in G$, find $\text{scc}(v)$


- Find the set $\text{reach}(v)$ using DFS



Finding the strongly connected components

Question: Given a $v \in G$, find $\text{scc}(v)$

- Find the set $\text{reach}(v)$ using DFS




Finding the strongly connected components

Question: Given a $v \in G$, find $\text{scc}(v)$

- Find the set $\text{reach}(v)$ using DFS

Which of these vertices are in $\text{scc}(v)$?



Finding the strongly connected components


Question: Given a $v \in G$, find $\text{scc}(v)$

- Find the set $\text{reach}(v)$ using DFS

Which of these vertices are in $\text{scc}(v)$?

- All the vertices in the set

$$\text{reach}^{-1}(v) := \{u \mid v \in \text{reach}(u)\}$$



Finding the strongly connected components


Question: Given a $v \in G$, find $\text{scc}(v)$

- Find the set $\text{reach}(v)$ using DFS

Which of these vertices are in $\text{scc}(v)$?

- All the vertices in the set

$$\text{reach}^{-1}(v) := \{u \mid v \in \text{reach}(u)\}$$



How do you find this set?

Finding the strongly connected components

Question: Given a $v \in G$, find $\text{scc}(v)$

- Find the set $\text{reach}(v)$ using DFS

Which of these vertices are in $\text{scc}(v)$?


- All the vertices in the set

$$\text{reach}^{-1}(v) := \{u \mid v \in \text{reach}(u)\}$$

↓

How do you find this set?

$\text{reach}(v)$ in $\text{rev}(G)$



$\text{rev}(G)$

Finding the strongly connected components

Question: Given a $v \in G$, find $\text{scc}(v)$

- Find the set $\text{reach}(v)$ using DFS


Which of these vertices are in $\text{scc}(v)$?

- All the vertices in the set

$$\text{reach}^{-1}(v) := \{u \mid v \in \text{reach}(u)\}$$

How do you find this set?

reach(v) in rev(G)

 $\text{rev}(G)$

$$\text{scc}(v) = \text{reach}(v) \cap \text{reach}^{-1}(v)$$

Finding the strongly connected components

Question: Given a $v \in G$, find $\text{scc}(v)$

- Find the set $\text{reach}(v)$ using DFS

Which of these vertices are in $\text{scc}(v)$?

- All the vertices in the set

$$\text{reach}^{-1}(v) := \{u \mid v \in \text{reach}(u)\}$$


↓

How do you find this set?

$\text{reach}(v)$ in $\text{rev}(G)$


$$\text{scc}(v) = \text{reach}(v) \cap \text{reach}^{-1}(v)$$

Exercise: How do we find $\text{rev}(G)$ in $O(|V| + |E|)$ time?



$\text{rev}(G)$


Finding the strongly connected components



Digraph of strongly connected components: $\text{SCC}(G)$



Finding the strongly connected components




Digraph of strongly connected components: $\text{SCC}(G)$



Question: For which vertices v , do we have $\text{scc}(v) = \text{reach}(v)$?

Finding the strongly connected components




Digraph of strongly connected components: $\text{SCC}(G)$



Question: For which vertices v , do we have $\text{scc}(v) = \text{reach}(v)$?

iff v is a vertex in a sink component of $\text{SCC}(G)$

Finding the strongly connected components



Digraph of strongly connected components: $\text{SCC}(G)$



Question: For which vertices v , do we have $\text{scc}(v) = \text{reach}(v)$?

iff v is a vertex in a sink component of $\text{SCC}(G)$

Algorithm idea:

- Find a vertex v in a sink component of $\text{SCC}(G)$
- Find $\text{reach}(v)$
- Remove it from the graph and continue...


Finding the strongly connected components

Question: How do we find a vertex v in a sink component of $\text{SCC}(G)$?

Finding the strongly connected components

Question: How do we find a vertex v in a sink component of $\text{SCC}(G)$?

A different question: How do you find a vertex v in a source component of $\text{SCC}(G)$?




Digraph of strongly connected components: $\text{SCC}(G)$



Finding the strongly connected components

Question: How do we find a vertex v in a sink component of $\text{SCC}(G)$?

A different question: How do you find a vertex v in a source component of $\text{SCC}(G)$?



Digraph of strongly connected components: $\text{SCC}(G)$



Which vertex v has the largest $\text{end}[v]$ among all the vertices?

Finding the strongly connected components

Theorem: The vertex v with the largest value of $\text{end}[v]$ must lie in a source component of $\text{SCC}(G)$

Finding the strongly connected components

Theorem: The vertex v with the largest value of $\text{end}[v]$ must lie in a source component of $\text{SCC}(G)$



u - vertex in C_1 with largest $\text{end}[]$ value
 v - vertex in C_2 with largest $\text{end}[]$ value,
then

Finding the strongly connected components

Theorem: The vertex v with the largest value of $\text{end}[v]$ must lie in a source component of $\text{SCC}(G)$



u - vertex in C_1 with largest $\text{end}[]$ value
 v - vertex in C_2 with largest $\text{end}[]$ value,
then $\text{end}[u] > \text{end}[v]$

Finding the strongly connected components

Theorem: The vertex v with the largest value of $\text{end}[v]$ must lie in a source component of $\text{SCC}(G)$



u - vertex in C_1 with largest $\text{end}[]$ value
 v - vertex in C_2 with largest $\text{end}[]$ value,
then $\text{end}[u] > \text{end}[v]$

- If DFS visits vertex in C_1 before C_2 , then the first vertex w visited in C_1 has $\text{end}[w]$ greater than all the vertices in C_2

Finding the strongly connected components

Theorem: The vertex v with the largest value of $\text{end}[v]$ must lie in a source component of $\text{SCC}(G)$



u - vertex in C_1 with largest $\text{end}[]$ value
 v - vertex in C_2 with largest $\text{end}[]$ value,
then $\text{end}[u] > \text{end}[v]$

- If DFS visits vertex in C_1 before C_2 , then the first vertex w visited in C_1 has $\text{end}[w]$ greater than all the vertices in C_2
- If DFS visits a vertex in C_2 first, then first vertex w visited in C_1 has $\text{start}[w] > \text{end}$ time of all vertices in C_2

Finding the strongly connected components

But, how do we get a vertex in the sink component?

Finding the strongly connected components

But, how do we get a vertex in the sink component?

- The sink components in $\text{SCC}(G)$ are source components in $\text{rev}(\text{SCC}(G))$

Finding the strongly connected components

But, how do we get a vertex in the sink component?

- The sink components in $\text{SCC}(G)$ are source components in $\text{rev}(\text{SCC}(G))$

Lemma: $\text{rev}(\text{SCC}(G)) = \text{SCC}(\text{rev}(G))$

Finding the strongly connected components

But, how do we get a vertex in the sink component?

- The sink components in $\text{SCC}(G)$ are source components in $\text{rev}(\text{SCC}(G))$

Lemma: $\text{rev}(\text{SCC}(G)) = \text{SCC}(\text{rev}(G))$

Proof sketch:

- A subset $C \subseteq V$ is a strongly connected component of G iff it is a strongly connected component of $\text{rev}(G)$
- $\text{SCC}(G)$ and $\text{SCC}(\text{rev}(G))$ have the same set of vertices
- An edge goes from component C_i to C_j in $\text{rev}(\text{SCC}(G))$ iff an edge goes from C_i to C_j in $\text{rev}(G)$

Finding the strongly connected components

But, how do we get a vertex in the sink component?

- The sink components in $\text{SCC}(G)$ are source components in $\text{rev}(\text{SCC}(G))$

Lemma: $\text{rev}(\text{SCC}(G)) = \text{SCC}(\text{rev}(G))$

Proof sketch:

- A subset $C \subseteq V$ is a strongly connected component of G iff it is a strongly connected component of $\text{rev}(G)$
- $\text{SCC}(G)$ and $\text{SCC}(\text{rev}(G))$ have the same set of vertices
- An edge goes from component C_i to C_j in $\text{rev}(\text{SCC}(G))$ iff an edge goes from C_i to C_j in $\text{rev}(G)$

To obtain the source components of $\text{rev}(\text{SCC}(G))$, it is sufficient to perform DFS on $\text{rev}(G)$

The Kosaraju-Sharir algorithm

The Kosaraju-Sharir algorithm

Phase 1: Perform DFS on $\text{rev}(G)$

DFS(v)

mark v

foreach edge $u \rightarrow w$ **do**

if w is unmarked **then**

 DFS(w)

push(v)

The Kosaraju-Sharir algorithm

Phase 1: Perform DFS on $\text{rev}(G)$

DFS(v)


mark v

foreach edge $u \rightarrow w$ **do**

if w is unmarked **then**

 DFS(w)

push(v)




vertices pushed in the
order of ending times

The Kosaraju-Sharir algorithm

Phase 1: Perform DFS on $\text{rev}(G)$

```
DFS(v)
mark v
foreach edge  $u \rightarrow w$  do
    if  $w$  is unmarked then
        DFS(w)
push(v)
```



vertices pushed in the
order of ending times


Phase 2: Perform DFS in the order of the stack

```
DFS(G)
count  $\leftarrow 1$ 
foreach  $v \in G$  do
    set  $\text{cc}[v] \leftarrow 0$ 
while stack is non-empty do
     $v \leftarrow \text{pop}()$ 
    if  $\text{cc}[v] = 0$  then
        LABELCC( $v$ , count)
        count  $\leftarrow$  count + 1
```

The Kosaraju-Sharir algorithm

Phase 1: Perform DFS on $\text{rev}(G)$

```
DFS(v)
mark v
foreach edge  $u \rightarrow w$  do
    if  $w$  is unmarked then
        DFS(w)
push(v)
```



vertices pushed in the order of ending times

Phase 2: Perform DFS in the order of the stack

```
DFS(G)
count  $\leftarrow 1$ 
foreach  $v \in G$  do
    set  $\text{cc}[v] \leftarrow 0$ 
while stack is non-empty do
     $v \leftarrow \text{pop}()$ 
    if  $\text{cc}[v] = 0$  then
        LABELCC( $v$ , count)
        count  $\leftarrow$  count + 1
```

```
LABELCC( $v$ , count)
 $\text{cc}[v] = \text{count}$ 
foreach edge  $v \rightarrow w$  do
    if  $\text{cc}[w] = 0$  then
        LABELCC( $w$ , count)
```

The Kosaraju-Sharir algorithm

Phase 1: Perform DFS on $\text{rev}(G)$

DFS(v)

mark v


foreach edge $u \rightarrow w$ **do**

if w is unmarked **then**

 DFS(w)

push(v)

vertices pushed in the
order of ending times



- Perform DFS on $\text{rev}(G)$, and order according to end times
- Perform DFS on G in this order and label components
- Total running time: $O(|V| + |E|)$

Phase 2: Perform DFS in the order of the stack

DFS(G)

count $\leftarrow 1$

foreach $v \in G$ **do**

 set $\text{cc}[v] \leftarrow 0$

while stack is non-empty **do**

$v \leftarrow \text{pop}()$

if $\text{cc}[v] = 0$ **then**

 LABELCC(v , count)

 count \leftarrow count + 1

LABELCC(v , count)

$\text{cc}[v] = \text{count}$

foreach edge $v \rightarrow w$ **do**

if $\text{cc}[w] = 0$ **then**

 LABELCC(w , count)

Shortest paths in graphs

Finding shortest paths in graphs

Question: Given a (di)graph G , and two vertices s and t , find the shortest path from s to t in G

Finding shortest paths in graphs

Question: Given a (di)graph G , and two vertices s and t , find the shortest path from s to t in G

- The graphs could be weighted or unweighted - shortest path in terms of edge-weights

Finding shortest paths in graphs

Question: Given a (di)graph G , and two vertices s and t , find the shortest path from s to t in G

- The graphs could be weighted or unweighted - shortest path in terms of edge-weights
- All the algorithms actually solve a more general problem - compute the shortest distances from s to all the other nodes (Single-Source Shortest Path)

Finding shortest paths in graphs

Question: Given a (di)graph G , and two vertices s and t , find the shortest path from s to t in G

- The graphs could be weighted or unweighted - shortest path in terms of edge-weights
- All the algorithms actually solve a more general problem - compute the shortest distances from s to all the other nodes ([Single-Source Shortest Path](#))
- Unweighted case - already seen. But, let's recall...

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

$p[w] \leftarrow v$

 enqueue(w)

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
 $\text{dist}(s) \leftarrow 0$   
 $\text{enqueue}(s)$   
while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
        if  $\text{dist}(w) = \infty$  then  
             $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
             $p[w] \leftarrow v$   
             $\text{enqueue}(w)$ 
```

- Every vertex is inserted in the queue only once

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
 $\text{dist}(s) \leftarrow 0$   
enqueue( $s$ )  
while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
        if  $\text{dist}(w) = \infty$  then  
             $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
             $p[w] \leftarrow v$   
            enqueue( $w$ )
```

- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
 $\text{dist}(s) \leftarrow 0$   
enqueue( $s$ )  
while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
        if  $\text{dist}(w) = \infty$  then  
             $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
             $p[w] \leftarrow v$   
            enqueue( $w$ )
```

- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$


foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

$p[w] \leftarrow v$

 enqueue(w)



- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$


foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

$p[w] \leftarrow v$

 enqueue(w)



- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$


foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

$p[w] \leftarrow v$

 enqueue(w)



- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$


foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

$p[w] \leftarrow v$

 enqueue(w)



- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$


foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

$p[w] \leftarrow v$

 enqueue(w)



- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$


foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

$p[w] \leftarrow v$

 enqueue(w)



- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

SHORTESTPATH(G)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$p[v] \leftarrow \emptyset$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$


foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

$p[w] \leftarrow v$

 enqueue(w)



- Every vertex is inserted in the queue only once
- The value of $\text{dist}(v)$ changes exactly once in the entire run of the algorithm

Unweighted graphs: Breadth-First Search

Theorem: When $\text{SHORTESTPATH}(G)$ ends, $\text{dist}(v)$ is the length of the shortest path from s to v for every $v \in G$

Proof:

```
SHORTESTPATH( $G$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
 $\text{dist}(s) \leftarrow 0$   
enqueue( $s$ )  
while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
        if  $\text{dist}(w) = \infty$  then  
             $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
             $p[w] \leftarrow v$   
            enqueue( $w$ )
```

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
   $\text{dist}(s) \leftarrow 0$   
  enqueue( $s$ )  
  while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
      if  $\text{dist}(w) = \infty$  then  
         $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
         $p[w] \leftarrow v$   
        enqueue( $w$ )
```

Theorem: When $\text{SHORTESTPATH}(G)$ ends, $\text{dist}(v)$ is the length of the shortest path from s to v for every $v \in G$

Proof: For any path $P : s = v_0 \rightarrow v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_t = v$, we will show that $\text{dist}(v_j) \leq j$

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
 $\text{dist}(s) \leftarrow 0$   
 $\text{enqueue}(s)$   
while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
        if  $\text{dist}(w) = \infty$  then  
             $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
             $p[w] \leftarrow v$   
             $\text{enqueue}(w)$ 
```

Theorem: When $\text{SHORTESTPATH}(G)$ ends, $\text{dist}(v)$ is the length of the shortest path from s to v for every $v \in G$

Proof: For any path $P : s = v_0 \rightarrow v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_t = v$, we will show that $\text{dist}(v_j) \leq j$

Proof by induction

- Base case: $\text{dist}(v_0) = \text{dist}(s) = 0$

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
   $\text{dist}(s) \leftarrow 0$   
  enqueue( $s$ )  
  while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
      if  $\text{dist}(w) = \infty$  then  
         $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
         $p[w] \leftarrow v$   
        enqueue( $w$ )
```

Theorem: When $\text{SHORTESTPATH}(G)$ ends, $\text{dist}(v)$ is the length of the shortest path from s to v for every $v \in G$

Proof: For any path $P : s = v_0 \rightarrow v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_t = v$, we will show that $\text{dist}(v_j) \leq j$

Proof by induction

- Base case: $\text{dist}(v_0) = \text{dist}(s) = 0$
- Induction hypothesis: $\text{dist}(v_i) \leq i$ for every $i \leq j - 1$

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
   $\text{dist}(s) \leftarrow 0$   
  enqueue( $s$ )  
  while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
      if  $\text{dist}(w) = \infty$  then  
         $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
         $p[w] \leftarrow v$   
        enqueue( $w$ )
```

Theorem: When $\text{SHORTESTPATH}(G)$ ends, $\text{dist}(v)$ is the length of the shortest path from s to v for every $v \in G$

Proof: For any path $P : s = v_0 \rightarrow v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_t = v$, we will show that $\text{dist}(v_j) \leq j$

Proof by induction

- Base case: $\text{dist}(v_0) = \text{dist}(s) = 0$
- Induction hypothesis: $\text{dist}(v_i) \leq i$ for every $i \leq j - 1$
- Induction step: When v_{j-1} is dequeued, then two things can happen

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
 $\text{dist}(s) \leftarrow 0$   
 $\text{enqueue}(s)$   
while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
        if  $\text{dist}(w) = \infty$  then  
             $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
             $p[w] \leftarrow v$   
             $\text{enqueue}(w)$ 
```

Theorem: When $\text{SHORTESTPATH}(G)$ ends, $\text{dist}(v)$ is the length of the shortest path from s to v for every $v \in G$

Proof: For any path $P : s = v_0 \rightarrow v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_t = v$, we will show that $\text{dist}(v_j) \leq j$

Proof by induction

- Base case: $\text{dist}(v_0) = \text{dist}(s) = 0$
- Induction hypothesis: $\text{dist}(v_i) \leq i$ for every $i \leq j - 1$
- Induction step: When v_{j-1} is dequeued, then two things can happen
 - $\text{dist}(v_j) \leq \text{dist}(v_{j-1}) + 1 = j$, or
 - v_j is enqueued, and $\text{dist}(v_j) \leftarrow \text{dist}(v_{j-1}) + 1 = j$

Unweighted graphs: Breadth-First Search

```
SHORTESTPATH( $G$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
     $p[v] \leftarrow \emptyset$   
 $\text{dist}(s) \leftarrow 0$   
enqueue( $s$ )  
while queue is not empty do  
     $v \leftarrow \text{dequeue}()$   
    foreach edge  $v \rightarrow w$  do  
        if  $\text{dist}(w) = \infty$  then  
             $\text{dist}(w) \leftarrow \text{dist}(v) + 1$   
             $p[w] \leftarrow v$   
            enqueue( $w$ )
```

Theorem: When $\text{SHORTESTPATH}(G)$ ends, $\text{dist}(v)$ is the length of the shortest path from s to v for every $v \in G$

Proof: For any path $P : s = v_0 \rightarrow v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_t = v$, we will show that $\text{dist}(v_j) \leq j$

Proof by induction

- Base case: $\text{dist}(v_0) = \text{dist}(s) = 0$
- Induction hypothesis: $\text{dist}(v_i) \leq i$ for every $i \leq j - 1$
- Induction step: When v_{j-1} is dequeued, then two things can happen
 - $\text{dist}(v_j) \leq \text{dist}(v_{j-1}) + 1 = j$, or
 - v_j is enqueued, and $\text{dist}(v_j) \leftarrow \text{dist}(v_{j-1}) + 1 = j$

$\text{dist}(v)$ must be at most the length of the shortest path from s to v , and $\text{dist}(v)$ is the length of an actual path from s to v

Weighted DAGs


- Only need to compute for vertices v after s in the topological order

Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed


Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed




Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed




Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed




Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed




Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed




Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed



Weighted DAGs


- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed



$$\text{dist}(v) = \min_{(u,v) \in E} \{\text{dist}(u) + w(u,v)\}$$

Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed




$$\text{dist}(v) = \min_{(u,v) \in E} \{\text{dist}(u) + w(u,v)\}$$

What is the dependency digraph?

Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed




$$\text{dist}(v) = \min_{(u,v) \in E} \{\text{dist}(u) + w(u,v)\}$$

- The dependency digraph of the recurrence is $\text{rev}(G)$
- The order in which the recursive solutions are computed corresponds to the topological order of G

Weighted DAGs

- Only need to compute for vertices v after s in the topological order
- Multiple iterations before $\text{dist}(v)$ is correctly computed



SSSP-DAG(G, s)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ in topological order **do**

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

General weighted (di)graphs

Points to remember:

- Graphs cannot contain negative weight cycles
- For now, assume that there are no negative weight edges also

A BFS-based idea

A BFS-based idea



A BFS-based idea




A BFS-based idea



- Replace an edge of weight w with a path of length w with edge weight 1
- Perform BFS on the new graph


A BFS-based idea




- Replace an edge of weight w with a path of length w with edge weight 1
- Perform BFS on the new graph

Question: Does this algorithm compute the shortest paths correctly?


Generalizing the BFS idea



Generalizing the BFS idea




Generalizing the BFS idea



What happens when
edges have weights?


Generalizing the BFS idea



What happens when edges have weights?

- Maintain a set S of vertices whose shortest distances are computed, and expand this set one vertex at a time.

Generalizing the BFS idea




- Maintain a set S of vertices whose shortest distances are computed, and expand this set one vertex at a time.
- For BFS - add a neighbor of a vertex in S
- What should we do for weighted graphs?

Dijkstra's algorithm for SSSP

How do we choose the next vertex to add to the set S ?


Dijkstra's algorithm for SSSP

How do we choose the next vertex to add to the set S ?



Dijkstra's algorithm for SSSP


How do we choose the next vertex to add to the set S ?



Lemma: $\text{dist}(v)$ for the vertex obtained is the shortest distance from s to v .

Dijkstra's algorithm for SSSP

How do we choose the next vertex to add to the set S ?




Lemma: $\text{dist}(v)$ for the vertex obtained is the shortest distance from s to v .

Proof: Suppose not!

Dijkstra's algorithm for SSSP

How do we choose the next vertex to add to the set S ?




Lemma: $\text{dist}(v)$ for the vertex obtained is the shortest distance from s to v .

Proof: Suppose not!

Dijkstra's algorithm for SSSP

How do we choose the next vertex to add to the set S ?




Lemma: $\text{dist}(v)$ for the vertex obtained is the shortest distance from s to v .

Proof: Suppose not!

$$\text{dist}(x) + \text{wt}(x, y) \geq \text{dist}(u) + \text{wt}(u, v) \text{ and } \text{dist}(y, v) \geq 0$$

Dijkstra's algorithm for SSSP

How do we choose the next vertex to add to the set S ?




Lemma: $\text{dist}(v)$ for the vertex obtained is the shortest distance from s to v .

Proof: Suppose not!

$\text{dist}(x) + \text{wt}(x, y) \geq \text{dist}(u) + \text{wt}(u, v)$ and $\text{dist}(y, v) \geq 0$

Question: How do we find the vertex v efficiently?

Dijkstra's algorithm for SSSP



- Choose the v with the smallest $\text{dist}(v) + w(u, v)$ where $u \in S$
- Once a v is chosen, recompute the $\text{dist}(w) + w(u, w)$ values for vertices lying outside $S \cup \{v\}$

need to recompute this
for only neighbors of v

Dijkstra's algorithm for SSSP

SHORTESTPATH(G, s)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

enqueue(s)

while queue is not empty **do**

$v \leftarrow \text{dequeue}()$

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) = \infty$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + 1$

 enqueue(w)

Dijkstra's algorithm for SSSP

```
DIJKSTRA( $G, s$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
   $\text{dist}(s) \leftarrow 0$   
  INSERT( $s, 0$ )  
  while priority queue is not empty do  
     $v \leftarrow \text{EXTRACTMIN}()$   
    foreach edge  $v \rightarrow w$  do  
      if  $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$  then  
         $\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$   
        if  $w$  is in the priority queue then  
          DECREASEKEY( $w, \text{dist}(w)$ )  
        else  
          INSERT( $w, \text{dist}(w)$ )
```

Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ **do**

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty **do**

$v \leftarrow \text{EXTRACTMIN}()$

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)

Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ do

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ do

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty do


$v \leftarrow \text{EXTRACTMIN}()$

 foreach edge $v \rightarrow w$ do

 if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ then

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ **do**

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty **do**


$v \leftarrow \text{EXTRACTMIN}()$

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ do

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ do

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty do


$v \leftarrow \text{EXTRACTMIN}()$

 foreach edge $v \rightarrow w$ do

 if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ then

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ do

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ do

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty do


$v \leftarrow \text{EXTRACTMIN}()$

 foreach edge $v \rightarrow w$ do

 if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ then

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ do

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ do

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty do


$v \leftarrow \text{EXTRACTMIN}()$

 foreach edge $v \rightarrow w$ do

 if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ then

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ do

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ do

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty do


$v \leftarrow \text{EXTRACTMIN}()$

 foreach edge $v \rightarrow w$ do

 if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ then

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ do

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ do

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty do


$v \leftarrow \text{EXTRACTMIN}()$

 foreach edge $v \rightarrow w$ do

 if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ then

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ **do**

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty **do**


$v \leftarrow \text{EXTRACTMIN}()$

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ **do**

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty **do**


$v \leftarrow \text{EXTRACTMIN}()$

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ **do**

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty **do**


$v \leftarrow \text{EXTRACTMIN}()$

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



- Each vertex is inserted in the priority queue, and extracted exactly once

Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ **do**

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ **do**

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty **do**


$v \leftarrow \text{EXTRACTMIN}()$

foreach edge $v \rightarrow w$ **do**

if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ **then**

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



- Each vertex is inserted in the priority queue, and extracted exactly once
- Each edge is relaxed at most once

Dijkstra's algorithm for SSSP

DIJKSTRA(G, s)

foreach $v \in G$ do

$\text{dist}(v) \leftarrow \infty$

$\text{dist}(s) \leftarrow 0$

foreach $v \in G$ do

 INSERT($v, \text{dist}(v)$)

while priority queue is not empty do


$v \leftarrow \text{EXTRACTMIN}()$

 foreach edge $v \rightarrow w$ do

 if $\text{dist}(w) > \text{dist}(v) + \text{wt}(v, w)$ then

$\text{dist}(w) \leftarrow \text{dist}(v) + \text{wt}(v, w)$

 DECREASEKEY($w, \text{dist}(w)$)



- Each vertex is inserted in the priority queue, and extracted exactly once
- Each edge is relaxed at most once

Running time

- $O((|V| + |E|) \log |V|)$ (using binary heaps)
- $O(|V| \log |V| + |E|)$ (using Fibonacci heaps)

SSSP with negative-weight edges

SSSP with negative-weight edges

- Already seen in the case of DAGs

SSSP with negative-weight edges

- Already seen in the case of DAGs
- Dijkstra's algorithm fails when there are negative-weight edges
 - can you explain why?

SSSP with negative-weight edges

- Already seen in the case of DAGs
- Dijkstra's algorithm fails when there are negative-weight edges
 - can you explain why?
- Problem is ill-posed when the graph contains negative-weight cycles
- But, can you identify this situation and fail gracefully?

SSSP with negative-weight edges


Observations

- $\text{dist}(v)$ is always at least as large as the shortest distance to v
- Every edge is relaxed at most once in a run of Dijkstra's algorithm

SSSP with negative-weight edges

Observations


- $\text{dist}(v)$ is always at least as large as the shortest distance to v
- Every edge is relaxed at most once in a run of Dijkstra's algorithm



SSSP with negative-weight edges

Observations


- $\text{dist}(v)$ is always at least as large as the shortest distance to v
- Every edge is relaxed at most once in a run of Dijkstra's algorithm



SSSP with negative-weight edges

Observations


- $\text{dist}(v)$ is always at least as large as the shortest distance to v
- Every edge is relaxed at most once in a run of Dijkstra's algorithm



SSSP with negative-weight edges

Observations

- $\text{dist}(v)$ is always at least as large as the shortest distance to v
- Every edge is relaxed at most once in a run of Dijkstra's algorithm



one more update will set
the distances correctly

The Bellman-Ford algorithm

Recall the recurrence

$$\text{dist}(v) = \min_{(u,v) \in E} \{\text{dist}(u) + w(u, v)\}$$

The Bellman-Ford algorithm

Modified recurrence

$$\text{dist}_{\leq i}(v) = \begin{cases} 0 \\ \infty \end{cases}$$

shortest distance from s to v
by paths with $\leq i$ edges

if $i = 0$ and $v = s$

if $i = 0$ and $v \neq s$

The Bellman-Ford algorithm

Modified recurrence

$$\text{dist}_{\leq i}(v) = \begin{cases} 0 & \text{if } i = 0 \text{ and } v = s \\ \infty & \text{if } i = 0 \text{ and } v \neq s \\ \min \left\{ \begin{array}{l} \text{dist}_{\leq i-1}(v) \\ \min_{(u,v) \in E} \text{dist}_{\leq i-1}(u) + w(u, v) \end{array} \right\} & \text{otherwise} \end{cases}$$

shortest distance from s to v
by paths with $\leq i$ edges

The Bellman-Ford algorithm

Modified recurrence

$$\text{dist}_{\leq i}(v) = \begin{cases} 0 & \text{if } i = 0 \text{ and } v = s \\ \infty & \text{if } i = 0 \text{ and } v \neq s \\ \min \left\{ \begin{array}{l} \text{dist}_{\leq i-1}(v) \\ \min_{(u,v) \in E} \text{dist}_{\leq i-1}(u) + w(u, v) \end{array} \right\} & \text{otherwise} \end{cases}$$

shortest distance from s to v
by paths with $\leq i$ edges

- Have to compute $\text{dist}_{\leq i}(v)$ for $i \leq n - 1$
- In every iteration, **relax all the edges**

if $\text{dist}(v) > \text{dist}(u) + w(u, v)$ **then**
 $\text{dist}(v) = \text{dist}(u) + w(u, v)$

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
   $\text{dist}(s) \leftarrow 0$   
  repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
      if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
         $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
   $\text{dist}(s) \leftarrow 0$   
  repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
      if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
         $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

Lemma: Let $\text{dist}_{\leq i}(v)$ be the distance of the shortest path from s to v using at most i edges. Then, after the i^{th} iteration of the **repeat** loop for every vertex v ,

$$\text{dist}(v) \leq \text{dist}_{\leq i}(v)$$

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
   $\text{dist}(s) \leftarrow 0$   
  repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
      if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
         $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

Lemma: Let $\text{dist}_{\leq i}(v)$ be the distance of the shortest path from s to v using at most i edges. Then, after the i^{th} iteration of the **repeat** loop for every vertex v ,

$$\text{dist}(v) \leq \text{dist}_{\leq i}(v)$$

Proof: Induction on i

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
   $\text{dist}(s) \leftarrow 0$   
  repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
      if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
         $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

Lemma: Let $\text{dist}_{\leq i}(v)$ be the distance of the shortest path from s to v using at most i edges. Then, after the i^{th} iteration of the **repeat** loop for every vertex v ,

$$\text{dist}(v) \leq \text{dist}_{\leq i}(v)$$

Proof: Induction on i

Base case $i = 0$: $\text{dist}(s)$ is set to 0, and the rest to ∞

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
 $\text{dist}(s) \leftarrow 0$   
repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
        if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
             $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

Lemma: Let $\text{dist}_{\leq i}(v)$ be the distance of the shortest path from s to v using at most i edges. Then, after the i^{th} iteration of the **repeat** loop for every vertex v ,

$$\text{dist}(v) \leq \text{dist}_{\leq i}(v)$$

Proof: Induction on i

Induction step $s \rightarrow u_1 \rightarrow \dots u_k \rightarrow v$: shortest path to v of length $\leq i$

must be a
simple path!

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
 $\text{dist}(s) \leftarrow 0$   
repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
        if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
             $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

Lemma: Let $\text{dist}_{\leq i}(v)$ be the distance of the shortest path from s to v using at most i edges. Then, after the i^{th} iteration of the **repeat** loop for every vertex v ,

$$\text{dist}(v) \leq \text{dist}_{\leq i}(v)$$

Proof: Induction on i

Induction step $s \rightarrow u_1 \rightarrow \dots \rightarrow u_k \rightarrow v$: shortest path to v of length $\leq i$

After the $(i - 1)^{\text{st}}$ iteration, $\text{dist}(u_k) \leq \text{dist}_{i-1}(u_k)$

must be a
simple path!

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
   $\text{dist}(s) \leftarrow 0$   
  repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
      if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
         $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

Lemma: Let $\text{dist}_{\leq i}(v)$ be the distance of the shortest path from s to v using at most i edges. Then, after the i^{th} iteration of the **repeat** loop for every vertex v ,

$$\text{dist}(v) \leq \text{dist}_{\leq i}(v)$$

Proof: Induction on i

Induction step $s \rightarrow u_1 \rightarrow \dots u_k \rightarrow v$: shortest path to v of length $\leq i$

After the $(i - 1)^{\text{st}}$ iteration, $\text{dist}(u_k) \leq \text{dist}_{\leq i-1}(u_k)$

After the i^{th} iteration, $\text{dist}(v) \leq \text{dist}(u_k) + \text{wt}(u, v) \leq \text{dist}_{\leq i-1}(u_k) + \text{wt}(u, v) \leq \text{dist}_{\leq i}(v)$

must be a
simple path!

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
   $\text{dist}(s) \leftarrow 0$   
  repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
      if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
         $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

Lemma: Let $\text{dist}_{\leq i}(v)$ be the distance of the shortest path from s to v using at most i edges. Then, after the i^{th} iteration of the **repeat** loop for every vertex v ,

$$\text{dist}(v) \leq \text{dist}_{\leq i}(v)$$

Running time: $O(|V||E|)$

The Bellman-Ford algorithm

```
BELLMANFORD( $G, s$ )  
  foreach  $v \in G$  do  
     $\text{dist}(v) \leftarrow \infty$   
   $\text{dist}(s) \leftarrow 0$   
  repeat  $|V| - 1$  times  
    foreach edge  $u \rightarrow v$  do  
      if  $\text{dist}(v) > \text{dist}(u) + \text{wt}(u, v)$  then  
         $\text{dist}(v) = \text{dist}(u) + \text{wt}(u, v)$ 
```

Lemma: Let $\text{dist}_{\leq i}(v)$ be the distance of the shortest path from s to v using at most i edges. Then, after the i^{th} iteration of the **repeat** loop for every vertex v ,

$$\text{dist}(v) \leq \text{dist}_{\leq i}(v)$$

Running time: $O(|V||E|)$

Question: How do we detect if G has a negative weight cycle?