

Exp8:**Implement SVM/Decision tree classification techniques****a) SVM IN R**

```
# Install and load the e1071 package (if not already installed)
install.packages("e1071")
library(e1071)

# Load the iris dataset
data(iris)

# Inspect the first few rows of the dataset
head(iris)

# Split the data into training (70%) and testing (30%) sets
set.seed(123) # For reproducibility
sample_indices <- sample(1:nrow(iris), 0.7 * nrow(iris))
train_data <- iris[sample_indices, ]
test_data <- iris[-sample_indices, ]

# Fit the SVM model
svm_model <- svm(Species ~ ., data = train_data, kernel = "radial")

# Print the summary of the model
summary(svm_model)

# Predict the test set
predictions <- predict(svm_model, newdata = test_data)

# Evaluate the model's performance
confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)
print(confusion_matrix)

# Calculate accuracy
accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)
cat("Accuracy:", accuracy * 100, "%\n")
```

```
Parameters:  
  SVM-Type:  C-classification  
  SVM-Kernel: radial  
  cost: 1
```

```
Number of Support Vectors: 45
```

```
( 7 18 20 )
```

```
Number of Classes: 3
```

```
Levels:
```

```
setosa versicolor virginica
```

```
> # Predict the test set  
> predictions <- predict(svm_model, newdata = test_data)  
> # Evaluate the model's performance  
> confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)  
> print(confusion_matrix)
```

	Actual		
Predicted	setosa	versicolor	virginica
setosa	14	0	0
versicolor	0	17	0
virginica	0	1	13

```
> # Calculate accuracy  
> accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)  
> cat("Accuracy:", accuracy * 100, "%\n")  
Accuracy: 97.77778 %
```

b) Decision tree in R

```
# Install and load the rpart package (if not already installed)
install.packages("rpart")
library(rpart)

# Load the iris dataset
data(iris)

# Split the data into training (70%) and testing (30%) sets
set.seed(123) # For reproducibility
sample_indices <- sample(1:nrow(iris), 0.7 * nrow(iris))
train_data <- iris[sample_indices, ]
test_data <- iris[-sample_indices, ]

# Fit the Decision Tree model
tree_model <- rpart(Species ~ ., data = train_data, method = "class")

# Print the summary of the model
summary(tree_model)

# Plot the Decision Tree
plot(tree_model)
text(tree_model, pretty = 0)

# Predict the test set
predictions <- predict(tree_model, newdata = test_data, type = "class")

# Evaluate the model's performance
confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)
print(confusion_matrix)
```

```
# Calculate accuracy
```

```
accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)
```

```
cat("Accuracy:", accuracy * 100, "%\n")
```

```
Node number 6: 35 observations
  predicted class=versicolor  expected loss=0.1142857  P(node) =0.3333333
    class counts:    0    31    4
    probabilities: 0.000 0.886 0.114

Node number 7: 34 observations
  predicted class=virginica  expected loss=0.02941176  P(node) =0.3238095
    class counts:    0    1    33
    probabilities: 0.000 0.029 0.971

> # Plot the Decision Tree
> plot(tree_model)
> text(tree_model, pretty = 0)
> # Predict the test set
> predictions <- predict(tree_model, newdata = test_data, type = "class")
> # Evaluate the model's performance
> confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)
> print(confusion_matrix)
      Actual
Predicted setosa versicolor virginica
setosa      14         0         0
versicolor   0        18         1
virginica    0         0        12
> # Calculate accuracy
> accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)
> cat("Accuracy:", accuracy * 100, "%\n")
Accuracy: 97.7778 %
```