

Министерство науки и высшего образования Российской Федерации
НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ
ТОМСКИЙ ГОСУДАРСТВЕННЫЙ УНИВЕРСИТЕТ (НИ ТГУ)
Институт прикладной математики и информатики

ОТЧЕТ ПО ЛАБОРАТОРНОЙ РАБОТЕ
по дисциплине «Системы управления базами данных»

Рекурсивные запросы

Бриц Владислав Олегович

Специалитет, 10.05.01,
Направленность «Компьютерная Безопасность»

Руководитель работы
Старший преподаватель кафедры
теоретических основ информатики

_____ Е.Е. Мокина

подпись

«26» ноября 2022 г.

Автор работы
студент группы № 932025

_____ В.О. Бриц

подпись

«26» ноября 2022 г.

1. Следующий запрос ищет случаи, когда manager_id равен NULL, возвращая корневой узел.
 SELECT employee_id, last_name, department_id, manager_id, salary, hire_date FROM HR.employees
 WHERE manager_id IS NULL;

Worksheet

Query Builder

```
SELECT employee_id, last_name, department_id, manager_id, salary, hire_date
FROM HR.employees WHERE manager_id IS NULL;
```

Query Result x

SQL | All Rows Fetched: 1 in 0,003 seconds

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID	MANAGER_ID	SALARY	HIRE_DATE
1	100 King	90	(null)	24000	17.06.03

2. Следующий запрос возвращает связь узлов с их непосредственными родителями.
 SELECT E.last_name "Employee", M.last_name "Manager" FROM HR.employees E, HR.employees M
 WHERE E.manager_id = M.employee_id;

Worksheet Query Builder	
<pre>SELECT E.last_name "Employee", M.last_name "Manager" FROM HR.employees E, HR.employees M WHERE E.manager_id = M.employee_id;</pre>	
Query Result x All Rows Fetched: 106 in 0,004 seconds	
Employee	Manager
1 Bates	Cambrault
2 Bloom	Cambrault
3 Fox	Cambrault
4 Kumar	Cambrault
5 Ozer	Cambrault
6 Smith	Cambrault
7 Hunold	De Haan

3. Вывести всех сотрудников и их менеджеров.
 SELECT E.last_name "Employee", M.last_name "Manager" FROM HR.employees E LEFT JOIN
 HR.employees M ON E.manager_id = M.employee_id;

Worksheet Query Builder	
<pre>SELECT E.last_name "Employee", M.last_name "Manager" FROM HR.employees E LEFT JOIN HR.employees M ON E.manager_id = M.employee_id;</pre>	
Query Result x All Rows Fetched: 107 in 0,006 seconds	
Employee	Manager
1 Ozer	Cambrault
2 Bloom	Cambrault
3 Fox	Cambrault
4 Smith	Cambrault
5 Bates	Cambrault
6 Kumar	Cambrault
7 Hunold	De Haan

4. Вывести все записи о сотрудниках, у которых нет подчиненных.

SELECT * FROM HR.employees WHERE employee_id NOT IN (SELECT manager_id FROM HR.employees);

Worksheet	Query Builder
<pre>SELECT * FROM HR.employees WHERE employee_id NOT IN (SELECT manager_id FROM HR.employees);</pre>	
Query Result x	
All Rows Fetched: 0 in 0,001 seconds	
EMPLOYEE...	FIRST_NA...
LAST_NAME	EMAIL
PHONE_N...	HIRE_DATE
JOB_ID	SALARY
COMMISS...	MANAGER...
DEPARTM...	

SELECT employee_id, last_name, department_id, manager_id, salary, hire_date FROM HR.employees WHERE employee_id NOT IN (SELECT manager_id FROM HR.employees WHERE manager_id IS NOT NULL);

Worksheet	Query Builder
<pre>SELECT employee_id, last_name, department_id, manager_id, salary, hire_date FROM HR.employees WHERE employee_id NOT IN (SELECT manager_id FROM HR.employees WHERE manager_id IS NOT NULL);</pre>	
Query Result x	
All Rows Fetched: 89 in 0,005 seconds	
EMPLOYEE_ID	LAST_NAME
DEPARTMENT_ID	MANAGER_ID
SALARY	HIRE_DATE
1	198 OConnell
2	199 Grant
3	200 Whalen
4	202 Fay
5	203 Mavris
6	204 Baer
7	206 Gietz

SELECT employee_id, last_name, department_id, manager_id, salary, hire_date FROM HR.employees E WHERE NOT EXISTS (SELECT employee_id FROM HR.employees E1 WHERE E.employee_id = E1.manager_id);

Worksheet	Query Builder
<pre>SELECT employee_id, last_name, department_id, manager_id, salary, hire_date FROM HR.employees E WHERE NOT EXISTS (SELECT employee_id FROM HR.employees E1 WHERE E.employee_id = E1.manager_id);</pre>	
Query Result x	
All Rows Fetched: 89 in 0,003 seconds	
EMPLOYEE_ID	LAST_NAME
DEPARTMENT_ID	MANAGER_ID
SALARY	HIRE_DATE
1	198 OConnell
2	199 Grant
3	200 Whalen
4	202 Fay
5	203 Mavris
6	204 Baer
7	206 Gietz

5. Найти каждого сотрудника вместе с его менеджером.

SELECT last_name, employee_id, manager_id FROM HR.employees START WITH last_name = 'Jones'
CONNECT BY manager_id = PRIOR employee_id;

Worksheet

Query Builder

```
SELECT last_name, employee_id, manager_id FROM HR.employees
START WITH last_name = 'Jones' CONNECT BY manager_id = PRIOR employee_id;
```

Query Result x



SQL | All Rows Fetched: 1 in 0,004 seconds

	LAST_NAME	EMPLOYEE_ID	MANAGER_ID
1	Jones	195	123

7. Найти всех сотрудников и его менеджером, начиная с тех, кто устроился в компанию раньше всех.

SELECT last_name, employee_id, manager_id FROM HR.employees START WITH hire_date = (SELECT MIN(hire_date) FROM HR.employees) CONNECT BY manager_id = PRIOR employee_id;

Worksheet

Query Builder

```
SELECT last_name, employee_id, manager_id FROM HR.employees
START WITH hire_date = (SELECT MIN(hire_date) FROM HR.employees)
CONNECT BY manager_id = PRIOR employee_id;
```

 Query Result x

 | All Rows Fetched: 6 in 0,004 seconds

	LAST_NAME	EMPLOYEE_ID	MANAGER_ID
1	De Haan	102	100
2	Hunold	103	102
3	Ernst	104	103
4	Austin	105	103
5	Pataballa	106	103
6	Lorentz	107	103

8. Найти каждого сотрудника вместе с его менеджером, указав уровень иерархии.

SELECT level,last_name, employee_id, manager_id FROM HR.employees START WITH manager_id IS NULL CONNECT BY manager_id = PRIOR employee_id;

Worksheet

Query Builder

```
SELECT level,last_name, employee_id, manager_id FROM HR.employees
START WITH manager_id IS NULL CONNECT BY manager_id = PRIOR employee_id;
```

Query Result x

SQL | All Rows Fetched: 107 in 0,005 seconds

	LEVEL	LAST_NAME	EMPLOYEE_ID	MANAGER_ID
1	1	King	100	(null)
2	2	Kochhar	101	100
3	3	Greenberg	108	101
4	4	Faviet	109	108
5	4	Chen	110	108
6	4	Sciarra	111	108
7	4	Urman	112	108

9. Найти разницу зарплаты менеджера и его подчиненного.

SELECT E.last_name, E.employee_id, E.manager_id, (SELECT M.salary - E.salary FROM HR.employees M WHERE M.employee_id = E.manager_id) FROM HR.employees E START WITH manager_id IS NULL CONNECT BY manager_id = PRIOR employee_id;

Worksheet		Query Builder	
		<pre>SELECT E.last_name, E.employee_id, E.manager_id, (SELECT M.salary - E.salary FROM HR.employees M WHERE M.employee_id = E.manager_id) FROM HR.employees E START WITH manager_id IS NULL CONNECT BY manager_id = PRIOR employee_id;</pre>	
Query Result		All Rows Fetched: 107 in 0,006 seconds	
LAST_NAME	EMPLOYEE_ID	MANAGER_ID	(SELECT M.SALARY - E.SALARY FROM HR.EMPLOYEES M WHERE M.EMPLOYEE_ID = E.MANAGER_ID)
1 King	100	(null)	(null)
2 Kochhar	101	100	7000
3 Greenberg	108	101	4992
4 Faviet	109	108	3008
5 Chen	110	108	3808

10. Вывести сотрудников в соответствии иерархии должностей.

SELECT level, last_name, first_name FROM HR.employees START WITH manager_id IS NULL CONNECT BY manager_id = PRIOR employee_id ORDER BY level;

Worksheet		Query Builder	
		<pre>SELECT level, last_name, first_name FROM HR.employees START WITH manager_id IS NULL CONNECT BY manager_id = PRIOR employee_id ORDER BY level;</pre>	
Query Result		All Rows Fetched: 107 in 0,005 seconds	
LEVEL	LAST_NAME	FIRST_NAME	
1	1 King	Steven	
2	2 De Haan	Lex	
3	2 Raphaely	Den	
4	2 Weiss	Matthew	
5	2 Fripp	Adam	
6	2 Kaufling	Payam	

11. Найти каждого сотрудника вместе с его менеджером, которые работают в отделах 10, 20 или 30.

SELECT level, last_name, employee_id, manager_id FROM HR.employees WHERE department_id IN (10,20,30) START WITH manager_id IS NULL CONNECT BY manager_id = PRIOR employee_id ORDER BY level;

Worksheet		Query Builder	
		<pre>SELECT level, last_name, employee_id, manager_id FROM HR.employees WHERE department_id IN (10,20,30) START WITH manager_id IS NULL CONNECT BY manager_id = PRIOR employee_id ORDER BY level;</pre>	
Query Result		All Rows Fetched: 9 in 0,004 seconds	
LEVEL	LAST_NAME	EMPLOYEE_ID	MANAGER_ID
1	2 Hartstein	201	100
2	2 Raphaely	114	100
3	3 Baida	116	114
4	3 Fay	202	201
5	3 Himuro	118	114
6	3 Colmenares	119	114
7	3 Khoo	115	114
8	3 Whalen	200	101
9	3 Tobias	117	114