

Package ‘epiforecast’

September 19, 2019

Type Package

Title Tools for forecasting semi-regular seasonal epidemic curves and similar time series

Version 0.0.1

Date 2015-12-09

Author Logan C. Brooks, Sangwon Hyun, David C. Farrow, Aaron Rumack, Ryan J. Tibshirani, Roni Rosenfeld

Maintainer Logan C. Brooks <lcbrooks@cs.cmu.edu>

Imports stats,
utils,
lubridate,
splines,
glmgen,
glmnet,
httr,
Rcpp,
Matrix,
rlist,
Hmisc,
weights,
hexbin,
plotrix,
tibble,
dplyr,
pipeR,
matrixStats,
quantreg,
lpSolve,
parallel,
R.utils,
RCurl,
pbmcapply

Description Tools for forecasting semi-regular seasonal epidemic curves and similar time series. Includes an empirical Bayes approach that forms a prior

by transforming historical curves, a basis regression approach that balances matching observations from the current season and matching historical seasons' measurements for future weeks, and timestep-by-timestep weighted kernel density estimation on backward differences parameterized by both the time series measurements and the current time.

License GPL-2

RoxygenNote 6.1.1

Collate 'RcppExports.R'
'backcasters.R'
'match.R'
'utils.R'
'br.R'
'cv.R'
'cv_apply.R'
'delphi_epidata.R'
'empirical.futures.R'
'empirical.trajectories.R'
'simclass.R'
'ensemble.R'
'namesp.R'
'map_join.R'
'epiproject.R'
'forecast_type.R'
'get_completed_fluview_state_df.R'
'holidays.R'
'weeks.R'
'loaders.R'
'read.R'
'simplify2arrayp.R'
'target_spec.R'
'todo-by-file.R'
'twkde.R'

LinkingTo Rcpp

SystemRequirements

Suggests testthat

R topics documented:

| | |
|-------------------------------|----|
| augmentWeeklyDF | 5 |
| br.sim | 5 |
| br.smoothedCurve | 6 |
| bw.SJnrd0 | 7 |
| c.sim | 8 |
| c.target_forecast | 8 |
| c.uniform_forecast | 9 |
| check.file.contents | 10 |

| | |
|--|----|
| check.list.format | 10 |
| check.table.format | 10 |
| cv.compare | 11 |
| cv.sim | 11 |
| cv_apply | 12 |
| dat.to.matrix | 13 |
| DatesOfSeason | 13 |
| DateToYearWeekWdayDF | 14 |
| dimnames_or_inds | 15 |
| dimnamesnamesp | 15 |
| dimnamesp | 16 |
| dimnamesp_to_dimindices | 17 |
| dimp | 17 |
| downsample_sim | 18 |
| dur | 19 |
| empirical.futures.sim | 19 |
| empirical.trajectories.sim | 20 |
| epi_week_to_model_week | 21 |
| epiweek_Seq | 22 |
| fetchEpidataDF | 22 |
| fetchEpidataFullDat | 24 |
| fetchEpidataHistoryDF | 26 |
| fetchUpdatingResource | 27 |
| firstEpiweekOfUniverse | 27 |
| get.latest.time | 28 |
| get_br_control_list | 28 |
| is_christmas | 29 |
| is_newyear | 30 |
| is_thanksgiving | 30 |
| lastWeekNumber | 31 |
| make_sim_ys_colors | 31 |
| map_join_ | 32 |
| match.arg.else.default | 33 |
| match.dat | 35 |
| match.integer | 36 |
| match.new.dat.sim | 37 |
| match.nonnegative.numeric | 38 |
| match.single.na.or.numeric | 38 |
| match.single.nonna.integer | 39 |
| match.single.nonna.integer.or.null | 39 |
| match.single.nonna.numeric | 40 |
| match.single.wday.w | 41 |
| match.wday.w | 41 |
| mimicPastDF | 42 |
| mimicPastEpidataDF | 42 |
| model_week_to_epi_week | 44 |
| model_week_to_time | 44 |
| named_array_to_name_arrayvecs | 45 |

| | |
|---|----|
| named_arrayvec_to_name_arrayvec | 46 |
| namesp | 46 |
| ndimp | 47 |
| no_join | 47 |
| ons | 48 |
| pht | 48 |
| plot.sim | 49 |
| plot.target_forecast | 49 |
| print.sim | 49 |
| print.target_forecast | 50 |
| pwk | 50 |
| read.from.file | 51 |
| seasonModelWeekDFToYearWeekDF | 51 |
| seasonModelWeekToYearWeekDF | 52 |
| seasonModelWeekWdayDFToDate | 53 |
| seasonModelWeekWdayToDate | 53 |
| seasonOfDate | 54 |
| seasonOfYearWeek | 55 |
| Seq | 55 |
| show.sample.trajectories | 56 |
| table.to.list | 56 |
| target_forecast | 57 |
| target_forecast.sim | 57 |
| time_to_model_week | 58 |
| trimPartialPastSeasons | 58 |
| twkde.markovian.sim | 59 |
| twkde.sim | 60 |
| unite_arraylike | 61 |
| upsample_sim | 62 |
| usa.flu.first.week.of.season | 63 |
| usa_flu_inseason_flags | 64 |
| vector_as_named_array | 64 |
| vector_as_named_array_ | 65 |
| weekConventions | 65 |
| weighted_tabulate | 66 |
| with_dimnames | 66 |
| with_dimnamesnames | 67 |
| yearWeekDFToSeasonModelWeekDF | 68 |
| yearWeekToSeasonModelWeekDF | 68 |
| yearWeekWdayDFToDate | 69 |
| yearWeekWdayListsToDate | 70 |
| yearWeekWdayVecsToDate | 70 |

| | |
|-----------------|---|
| augmentWeeklyDF | <i>Augment df with epiweek/year/week/season/model.week, make weekly, full seasons</i> |
|-----------------|---|

Description

Given a df with either (a) \$epiweek, (b) \$year and \$week, or (c) \$date, fills in (if missing) \$epiweek, \$year, \$week, \$date, \$season, and \$model.week. Fills in missing weekly data from all seasons so that each season in df\$season has all of its model weeks in df\$model.week. Assumes epi week convention.

Usage

```
augmentWeeklyDF(df, first.week.of.season = NULL)
```

Arguments

| | |
|----------------------|---|
| df | data.frame with week numbers and other data |
| first.week.of.season | the first week number in each season or NULL (the default); if NULL, then the first week of the season is assumed to be the week of the first data point. |

Details

Entries in data.frame are assumed without any checks to be sorted and weekly (potentially with some skipped weeks).

| | |
|--------|--|
| br.sim | <i>Function for making forecasts with the basis regression method with output matching the format of distributional forecasting methods.</i> |
|--------|--|

Description

Function for making forecasts with the basis regression method with output matching the format of distributional forecasting methods.

Usage

```
br.sim(full.dat, max.n.sims = 100L, baseline = 0, bootstrap = TRUE,
       control.list = get_br_control_list(), ...)
```

Arguments

| | |
|-----|--|
| ... | arguments to forward to br.smoothedCurve . |
|-----|--|

Details

For the basis regression method, there is a single column per trajectory in `new.dat` containing the smoothed curve outputted by `br.smoothedCurve`, unless `max.n.sims` is non-NULL, in which case, it is a resampling of these smoothed curves.

Value

a `sim` object — a list with two components:

`ys`: a numeric matrix, typically with multiple columns; each column is a different possible trajectory for the current season, with NA's in the input for the current season filled in with random draws from the forecasted distribution, and non-NA's (observed data) filled in with an imagined resampling of noise based on the model (for some models, the non-NA values will remain unchanged).

`weights`: a numeric vector; assigns a weight to each column of `ys`, which is used by methods relying on importance sampling.

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

Examples

```
## National-level ILINet weighted %ILI data for recent seasons, excluding 2009 pandemic:
area.name = "nat"
full.dat = fetchEpidataFullDat("fluview", area.name, "wili",
                              min.points.in.season = 52L,
                              first.week.of.season = 31L,
                              cache.file.prefix=sprintf("fluview_%s_fetch", area.name))
full.dat <- full.dat[names(full.dat)!="S2009"]
## Sample from conditional curve distribution estimate using the above data
## and CDC's 2015 national %wILI onset threshold baseline of 2.1:
sim = br.sim(full.dat, baseline=2.1, max.n.sims=100)
print(sim)
plot(sim, type="lineplot")
```

br.smoothedCurve

Function for making forecasts with the basis regression method

Description

Estimates missing values in `dat.obj[[cur.season]]` by regressing the mean of "pseudo-trajectories" formed from non-NA observations from `dat.obj[[cur.season]]` and "pseudo-observations" formed from `dat.obj[-cur.season]` on a set of basis elements.

Usage

```
br.smoothedCurve(full.dat, dat.obj, cur.season,
  control.list = get.br.control.list())
```

Arguments

| | |
|---------------------------|---|
| <code>full.dat</code> | list of (a) numeric vectors, one per past season, containing historical trajectories, followed by (b) a numeric vector (trajectory), numeric matrix (cbound trajectories), or sim object (list with <code>\$ys</code> a numeric matrix (cbound trajectories) and <code>\$weights</code> a numeric vector (associated weights)), with NA's for all future or missing data points to forecast or infer; currently only supports NA's at future points, not mixed in between non-NA data |
| <code>dat.obj</code> | assumed to be a list, of length equal to number of past seasons. Each item here is itself a list, each component containing a vector of "signals" for that seasons. |
| <code>cur.season</code> | the number of the season to be forecast. Must be in between 1 and the length of <code>dat.obj</code> . |
| <code>control.list</code> | Contains simulation settings. |

Details

First, constructs a pseudo-trajectory for each training trajectory (`dat.obj[-cur.season]`) by shifting the training trajectory so that the maximum of its observations at times where `dat.obj[[cur.season]]` is non-NA aligns more closely with the maximum of `dat.obj[[cur.season]]` (where it is non-NA); the alignment procedure consists of a time shift (so that the partial maximum of the training and test trajectories are the same) and a scale (controlled by `scale.method`, `baseline`, and `max.scale.factor`). The pseudo-trajectory is formed by taking `dat.obj[[cur.season]]` where it is non-NA and the aligned training trajectory where `dat.obj[[cur.season]]` is NA.

Second, the mean of the pseudo-trajectories is regressed on a collection of basis elements to produce a single curve that provides estimates for `dat.obj[[cur.season]]` where it is NA.

Value

a numeric vector containing a smoothed version of the past observations and future "pseudo-observations" (predictions).

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

 bw.SJnrd0

bw.SJ with bw.nrd0 as fallback

Description

At least sometimes when calling `bw.SJ` on backfill updates (`lag.info$residual`), an error is generated ("sample is too sparse to find TD"). `bw.SJnrd0` uses `bw.SJ` if it succeeds, and falls back to `bw.nrd0` if it generates any error.

Usage

`bw.SJnrd0(x)`

Arguments

x numeric vector: the observations

Value

single numeric: the bandwidth selection

| | |
|-------|--|
| c.sim | <i>Add information to a sim object</i> |
|-------|--|

Description

Uses recursive=FALSE and use.names=TRUE when forwarding to the list c method; any attempt to override these values will generate an error.

Usage

```
## S3 method for class 'sim'
c(my.sim, ...)
```

Arguments

my.sim a sim object

... list of components to add to the sim object; must lead to a resulting sim object with components that are all uniquely, nontrivially (!="") named

Value

sim object with the given components appended

| | |
|-------------------|--|
| c.target_forecast | <i>Add information to a target_forecast object</i> |
|-------------------|--|

Description

Uses recursive=FALSE and use.names=TRUE when forwarding to the list c method; any attempt to override these values will generate an error.

Usage

```
## S3 method for class 'target_forecast'
c(target.forecast, ...)
```


Arguments

target_forecast a target_forecast object

... list of components to add to the target_forecast object; must lead to a resulting target_forecast object with components that are all uniquely, nontrivially (!="") named

Value

target_forecast object with the given components appended

c.uniform_forecast *Add information to a uniform_forecast object*

Description

Uses recursive=FALSE and use.names=TRUE when forwarding to the list c method; any attempt to override these values will generate an error.

Usage

```
## S3 method for class 'uniform_forecast'
c(classed.list, ..., recursive = FALSE,
  use.names = TRUE)
```

Arguments

... list of components to add to the uniform_forecast object; must lead to a resulting uniform_forecast object with components that are all uniquely, nontrivially (!="") named

uniform_forecast
a uniform_forecast object

Value

uniform_forecast object with the given components appended

| | |
|---------------------|---|
| check.file.contents | <i>Function to check if a data file is properly formatted (i.e. contains the headers, is filled with numeric values, etc.) Current implementation is very memory-inefficient.</i> |
|---------------------|---|

Description

Function to check if a data file is properly formatted (i.e. contains the headers, is filled with numeric values, etc.) Current implementation is very memory-inefficient.

Usage

```
check.file.contents(filename)
```

Arguments

| | |
|----------|---|
| filename | name of data file with each column equal to each season, with the first (n-1) columns to be, and the n'th column with the current season. |
|----------|---|

| | |
|-------------------|--|
| check.list.format | <i>Performs various checks on full.dat as a list of numeric vectors.</i> |
|-------------------|--|

Description

Performs various checks on full.dat as a list of numeric vectors.

Usage

```
check.list.format(full.dat)
```

| | |
|--------------------|--|
| check.table.format | <i>Performs various checks on full.dat as a table (matrix/data.frame).</i> |
|--------------------|--|

Description

Performs various checks on full.dat as a table (matrix/data.frame).

Usage

```
check.table.format(full.dat)
```

| | |
|------------|-----------------------------------|
| cv.compare | <i>Compare two cv.sim objects</i> |
|------------|-----------------------------------|

Description

Compare two cv.sim objects

Usage

```
cv.compare(cv.sim1, cv.sim2)
```

| | |
|--------|---|
| cv.sim | <i>Class for cv objects; contains (1) control list (2) for each forecasting time and for each left-out season (fold), what are the densities in the 52 by n.grid block of the 2d plane? (3) several things pre-calculated; the prediction scores (negative log-likelihood) for 4 target forecasts. The idea is that, instead of 52 by nsim curves, we can store 52 by n.grid values that store the density estimates, where n.grid can be hundreds, while n.sim may be 10,000's. It should return /all/ quantities required for doing</i> |
|--------|---|

Description

Class for cv objects; contains (1) control list (2) for each forecasting time and for each left-out season (fold), what are the densities in the 52 by n.grid block of the 2d plane? (3) several things pre-calculated; the prediction scores (negative log-likelihood) for 4 target forecasts. The idea is that, instead of 52 by nsim curves, we can store 52 by n.grid values that store the density estimates, where n.grid can be hundreds, while n.sim may be 10,000's. It should return /all/ quantities required for doing

Usage

```
cv.sim()
```

| | |
|----------|--|
| cv_apply | <i>apply-like function applying binary functions on training and test set selections</i> |
|----------|--|

Description

apply-like function applying binary functions on training and test set selections

Usage

```
cv_apply(data, indexer_list, fn, parallel_dim_i = 0L, ...)
```

Arguments

| | |
|--------------|--|
| data | an array |
| indexer_list | <p>a named list with one entry per dimension of data specifying how to select training and test indices for that dimension; for the <i>i</i>th entry:</p> <ul style="list-style-type: none"> • <code>each=NULL</code> slices both training and test data into <code>dim(data)[[i]]</code> pieces by selecting each index along the <i>i</i>th dimension; the corresponding output dimension width of <code>dim(data)[[i]]</code> • <code>all=NULL</code> performs no indexing along the <i>i</i>th dimension for either training or test data; the corresponding output dimension has width 1 and name "all" • <code>smear=relative.indices</code> acts like <code>each=NULL</code>, but instead of each slices corresponding to a single index, allows for nearby indices to be included as well; for the <i>j</i>th slice, includes data for valid indices in <code>j+relative.indices</code> • <code>ablation=NULL</code> acts like <code>each=NULL</code>, but for the <i>j</i>th "slice", excludes, rather than selects, data corresponding to index <i>j</i> • <code>subsets=subset.list</code> indexes both training and test data based on the subsets in <code>subset.list</code>; each entry in <code>subset.list</code> should be a vector of indices (logical, integer, or character) into the <i>i</i>th dimension of data; the output dimension has width <code>length(subset.list)</code> and names <code>names(subset.list)</code> • <code>loo=NULL</code> performs leave-one-out cross-validation indexing: the training set like <code>ablation=NULL</code>, while the test set is indexed like <code>each=NULL</code> • <code>oneahead=test_start_ind</code> slices the test data by taking each index greater than or equal to the specified single <i>integer</i> index <code>test_start_ind</code>; the test data corresponding to index <i>i</i> is paired with training data from indices strictly preceding <i>i</i> • <code>loo_oneahead=oneahead_start_ind</code> slices the test data by each index (similar to <code>each</code>); if the index <i>i</i> is less than the specified single <i>integer</i> index <code>oneahead_start_ind</code>, then it is paired with training data from indices strictly preceding <code>oneahead_start_ind</code>, excluding <i>i</i>; if <i>i</i> \geq <code>oneahead_start_ind</code>, then the training data contains all indices strictly preceding <i>i</i> |
| fn | a function(<code>training.slice</code> , <code>test.slice</code>) returning a scalar, vector, matrix, array, or list, with the same class and fixed structure for all inputs |

Value

an array with dimensionality equal to the sum of the dimensionless of the output of fn and of data

| | |
|---------------|--|
| dat.to.matrix | <i>Numeric matrix of the first n elements of each numeric vector in dat.</i> |
|---------------|--|

Description

A more efficient implementation of `sapply(dat, `[`, seq_len(n))`. Any vectors in `dat` with length less than `n` are extended with `NA_real_`'s at the end.

Usage

```
dat.to.matrix(dat, n)
```

Arguments

| | |
|------------------|---|
| <code>dat</code> | a list of numeric vectors |
| <code>n</code> | a single integer: the number of elements to take from each vector |

Value

a `n-by-length(dat)` numeric matrix

Examples

```
dat = list(11:15, 21:26)
dat.to.matrix(dat, 5) # (5x2: dat[[2]] is cut off)
dat.to.matrix(dat, 6) # (6x2: dat[[1]] is extended with NA_real_)
n = 3
identical(c(n, length(dat)), dim(dat.to.matrix(dat, n)))
```

| | |
|---------------|---|
| DatesOfSeason | <i>Get the first weekday of every week in the given seasons</i> |
|---------------|---|

Description

Get the first weekday of every week in the given seasons

Usage

```
DatesOfSeason(season, first.week, first.wday, owning.wday)
```

Arguments

| | |
|-------------|---|
| season | integer-valued vector: season numbers |
| first.week | integer-valued vector: first week number of each season |
| first.wday | integer-valued vector of weekday numbers: first weekday number in each week |
| owning.wday | integer-valued vector of weekday numbers: weekday that determines the year to which a week will be assigned |

Value

\$length(season)\$-length named list of 52/53-length Date vectors

| | |
|----------------------|---|
| DateToYearWeekWdayDF | <i>Convert dates to a data frame of year-week-wday according to a specified convention.</i> |
|----------------------|---|

Description

Convert dates to a data frame of year-week-wday according to a specified convention.

Usage

```
DateToYearWeekWdayDF(date, first.wday, owning.wday)
```

Arguments

| | |
|-------------|---|
| date | object compatible with as.Date : the dates to convert |
| first.wday | weekday number(s) (0–7, Sunday can be 0 or 7): the weekday that is considered the beginning of the week; typically Sunday or Monday |
| owning.wday | weekday number(s) (0–7, Sunday can be 0 or 7): a week is assigned to a given year if the owning weekday of that week falls in that year; typically first.wday or first.wday+3 |

Value

a data frame (tbl_df) with three columns, \$year, \$week, and \$wday, corresponding to the given dates using the convention specified by first.wday and owning.wday; each wday entry will be %in% 0:6.

| | |
|------------------|--|
| dimnames_or_inds | <i>Get integer or character index sets for each dimension of an object</i> |
|------------------|--|

Description

Favors character-type index sets, using the entries of `dimnamesp` for every dimension with names that are not all empty strings.

Usage

```
dimnames_or_inds(x, invent.scalars = TRUE)
```

Arguments

| | |
|-----------------------------|---|
| <code>x</code> | an array-like object |
| <code>invent.scalars</code> | length-1 non-NA logical; if TRUE, treat unnamed length-1 vector <code>x</code> 's as "scalars" with zero dimensions; if FALSE, treat them as arrays with one dimension of size 1. |

Examples

```
library("pipeR")
array(1:120, 2:5) %>%
  with_dimnames(list(
    "First dimension" = NULL,
    "Second dimension" = rep("", 3),
    "Third dimension" = c("", "", "c", "d"),
    "Fourth dimension" = letters[1:5]
  )) %>%
  dimnames_or_inds()
```

| | |
|-----------------------------|---|
| <code>dimnamesnamesp</code> | <i>Pipe-friendly, robust dimnames names getter, as a character vector of natural length</i> |
|-----------------------------|---|

Description

A pipe-friendly, robustified, more consistent version of `names(dimnames(x))`. Accepts array-like objects, including vectors (although these never have `dimnames` names). Always returns a character vector with length equal to the number of dimensions identified for `x` (never NULL).

Usage

```
dimnamesnamesp(x, invent.scalars = TRUE)
```

Arguments

`x` array-like object

`invent.scalars` length-1 non-NA logical; if TRUE, treat unnamed length-1 vector `x`'s as "scalars" with zero dimensions; if FALSE, treat them as arrays with one dimension of size 1.

Examples

```
library("pipeR")
array(1:24, 2:4) %>%
  with_dimnamesnames(c("a", "", "b")) %>%
  dimnamesnamesp()
array(1:24, 2:4) %>%
  dimnamesnamesp()
array(1:24, 2:4) %>%
  with_dimnames(list(letters[1:2], letters[1:3], NULL)) %>%
  {names(dimnames(.))[[2L]] <- "Second dimension"; .} %>%
  dimnamesnamesp()
dimnamesnamesp(1:5)
dimnamesnamesp(1)
dimnamesnamesp(1, invent.scalars=FALSE)
```

dimnamesp

dimnames, but always as a list of lists with natural lengths

Description

Operates like `dimnames`, but always produces a list of lists with the "natural" lengths. Fixes up cases where the `dimnames` or any element of the `dimnames` would be NULL. Any element of `dimnames` (i.e., vector of names associated with a particular dimension) that would be NULL is replaced with a vector of empty strings.

Usage

```
dimnamesp(x, invent.scalars = TRUE)
```

Arguments

`x` array or array-like object of which to take and format the `dimnames`

`invent.scalars` length-1 non-NA logical; if TRUE, treat unnamed length-1 vector `x`'s as "scalars" with zero dimensions; if FALSE, treat them as arrays with one dimension of size 1.

dimnamesp_to_dimindices

Post-process dimnamesp, changing all-"" dimensions to seq_along's

Description

Post-process dimnamesp, changing all-"" dimensions to seq_along's

Usage

```
dimnamesp_to_dimindices(dnp)
```

Arguments

x object of which to get the dimnames names

invent.scalars length-1 non-NA logical; if TRUE, treat unnamed length-1 vector x's as "scalars" with zero dimensions; if FALSE, treat them as arrays with one dimension of size 1.

Examples

```
## The first two dimensions are re-index with integers; the last two are not:
library("pipeR")
array(1:120, 2:5) %>>%
  with_dimnames(list(
    "First dimension" = NULL,
    "Second dimension" = rep("", 3),
    "Third dimension" = c("", "", "c", "d"),
    "Fourth dimension" = letters[1:5]
  )) %>>%
  dimnamesp() %>>%
  dimnamesp_to_dimindices()
```

dimp

dim, but always outputting integer vector of natural length

Description

dim, but always outputting integer vector of natural length

Usage

```
dimp(x, invent.scalars = TRUE)
```

Arguments

| | |
|-----------------------------|---|
| <code>x</code> | the object |
| <code>invent.scalars</code> | length-1 non-NA logical; if TRUE, treat unnamed length-1 vector <code>x</code> 's as "scalars" with zero dimensions; if FALSE, treat them as arrays with one dimension of size 1. |

| | |
|-----------------------------|---|
| <code>downsample_sim</code> | <i>Resample a sim (if necessary) to get \leq max.n.sims simulated curves</i> |
|-----------------------------|---|

Description

Resample a sim (if necessary) to get \leq max.n.sims simulated curves

Usage

```
downsample_sim(sim.obj, max.n.sims)
```

Arguments

| | |
|-------------------------|---|
| <code>sim.obj</code> | a sim object |
| <code>max.n.sims</code> | a single non-NA non-negative integer; the inclusive upper bound on the number of simulated curves in the result |

Details

Resampling is only performed if the number of simulations needs to change. Resampling is done without replacement to prevent unnecessary reductions in the number of "effective particles".

Value

a sim object with \leq max.n.sims simulated curves; the weights in the result are the same as the weights of the corresponding curves in `sim.obj`, implying that the sum of the weights in the result is less than or equal to the sum of the weights in the result (due to sampling without replacement), similar to reductions in "effective particles" in particle sampling contexts due to resampling.

| | |
|-----|---|
| dur | <i>Calculate the duration of a trajectory</i> |
|-----|---|

Description

Calculate the duration of a trajectory

Usage

```
dur(trajectory, baseline, is.inseason, ...)
```

Arguments

| | |
|-------------|--|
| trajectory | a vector |
| baseline | the onset threshold |
| is.inseason | logical vector length-compatible with trajectory, acting as a mask on possible output values |
| ... | ignored |

Value

a single non-NA integer: the number of indices which are part of the in-season and part of a run of at least three consecutive observations above the onset threshold

| | |
|-----------------------|---|
| empirical.futures.sim | <i>Simulate future in current trajectory with empirical (historical) distribution</i> |
|-----------------------|---|

Description

Simulate future in current trajectory with empirical (historical) distribution

Usage

```
empirical.futures.sim(full.dat, baseline = NA_real_,
  max.n.sims = 2000L)
```

Value

a sim object — a list with two components:

ys: a numeric matrix, typically with multiple columns; each column is a different possible trajectory for the current season, with NA's in the input for the current season filled in with random draws from the forecasted distribution, and non-NA's (observed data) filled in with an imagined resampling of noise based on the model (for some models, the non-NA values will remain unchanged).

weights: a numeric vector; assigns a weight to each column of ys, which is used by methods relying on importance sampling.

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

Examples

```
## National-level ILINet weighted %ILI data for recent seasons, excluding 2009 pandemic:
area.name = "nat"
full.dat = fetchEpidataFullDat("fluview", area.name, "wili",
                               min.points.in.season = 52L,
                               first.week.of.season = 31L,
                               cache.file.prefix=sprintf("fluview_%s_fetch", area.name))
full.dat <- full.dat[names(full.dat)!="S2009"]
## Sample from conditional curve distribution estimate using the above data
## and CDC's 2015 national %wILI onset threshold baseline of 2.1:
sim = empirical.futures.sim(full.dat, baseline=2.1, max.n.sims=100)
print(sim)
plot(sim, type="lineplot")
```

empirical.trajectories.sim

Simulate future in current trajectory with empirical (historical) distribution

Description

Simulate future in current trajectory with empirical (historical) distribution

Usage

```
empirical.trajectories.sim(full.dat, baseline = NA_real_,
                           max.n.sims = 2000L)
```

Value

a sim object — a list with two components:

ys: a numeric matrix, typically with multiple columns; each column is a different possible trajectory for the current season, with NA's in the input for the current season filled in with random draws from the forecasted distribution, and non-NA's (observed data) filled in with an imagined resampling of noise based on the model (for some models, the non-NA values will remain unchanged).

weights: a numeric vector; assigns a weight to each column of **ys**, which is used by methods relying on importance sampling.

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

Examples

```
## National-level ILINet weighted %ILI data for recent seasons, excluding 2009 pandemic:
area.name = "nat"
full.dat = fetchEpidataFullDat("fluview", area.name, "wili",
                               min.points.in.season = 52L,
                               first.week.of.season = 31L,
                               cache.file.prefix=sprintf("fluview_%s_fetch", area.name))
full.dat <- full.dat[names(full.dat)!="S2009"]
## Sample from conditional curve distribution estimate using the above data
## and CDC's 2015 national %wILI onset threshold baseline of 2.1:
sim = empirical.trajectories.sim(full.dat, baseline=2.1, max.n.sims=100)
print(sim)
plot(sim, type="lineplot")
```

epi_week_to_model_week

Convert epi week numbers into model week numbers

Description

Convert epi week numbers into model week numbers

Usage

```
epi_week_to_model_week(epi.week, first.week.of.season, n.weeks.in.season)
```

Arguments

| | |
|-----------------------------------|---|
| <code>epi.week</code> | integer or numeric vector; epi week numbers (wrapper versions of model week numbers in $1..52 + [0,1)$ or $1..53 + [0,1)$) |
| <code>first.week.of.season</code> | epi week number of the first element in a trajectory (i.e., corresponding to time 1L) |
| <code>n.weeks.in.season</code> | 52L or 53L — the length of the indexed trajectory, corresponding to the number of weeks in the first year contained in the season |

Value

integer or numeric vector with same length as `epi.week`; model weeks — epi weeks that don't (necessarily) wrap around to 1 at the start of a new year (after week 52 or 53 of the previous year) but rather wrap around when a season ends, starting back at `first.week.of.season`; values could be integers between `first.week.of.season` to `first.week.of.season+52L` or `first.week.of.season+53L` for integers, or a valid integer value plus a number in the clopen interval $[0,1)$ for numeric vectors

epiweek_Seq

Compute a sequence of epiweeks with the specified range

Description

Uses the rules of [Seq](#); if end.epiweek lies before start.epiweek, an empty sequence will be returned.

Usage

```
epiweek_Seq(from.epiweek, to.epiweek)
```

Arguments

from.epiweek the first epiweek to include in the sequence
to.epiweek the first epiweek to include in the sequence

Value

a sequence of epiweeks

Examples

```
epiweek_Seq(201450L, 201503L)
epiweek_Seq(201550L, 201603L)
epiweek_Seq(201550L, 201203L)
epiweek_Seq(201250L, 201503L)
```

fetchEpidataDF

Fetch & cache [Rhrefhttps://github.com/undefx/delphi-epidata](https://github.com/undefx/delphi-epidata) delphi-epidata data, convert it to a data.frame

Description

Fetch & cache **delphi-epidata** data, convert it to a data.frame

Usage

```
fetchEpidataDF(source, area, lag = NULL, first.week.of.season = NULL,
  first.epiweek = NULL, last.epiweek = NULL,
  cache.file.prefix = NULL, cache.invalidation.period = as.difftime(1L,
  units = "days"), force.cache.invalidation = FALSE,
  ignore.no.results = FALSE, silent = FALSE)
```

Arguments

| | |
|---------------------------|--|
| source | length-1 character vector; name of data source; one of <ul style="list-style-type: none"> • "fluview": U.S. Outpatient Influenza-like Illness Surveillance Network (ILINet) data from CDC FluView reports; weekly, national or by HHS region; updated weekly • "ilinet": Estimates of ILINet data at state level; weekly; static • "gft": Google Flu Trends data • "ght": Google Health Trends data; currently restricted, not supported by this function • "twitter": Twitter data; currently restricted, not supported by this function • "wiki": Wikipedia access log data; currently not supported by this function • "nidss.flu": Taiwan National Infectious Disease Statistics System (NIDSS) outpatient ILI data • "nidss.dengue": Taiwan National Infectious Disease Statistics System (NIDSS) dengue incidence data |
| area | length-1 character vector; name of area; possibilities by source are: <ul style="list-style-type: none"> • "fluview": "hhs1", "hhs2", ..., "hhs10", "nat" • "ilinet": 2-character state abbreviation or "DC" • "gft": listed at https://github.com/undefx/delphi-epidata#gft-parameters • "nidss.flu", "nidss.dengue": one of "nationwide", "central", "eastern", "kaoping", "northern", "southern", "taipei" |
| lag | single integer value or NULL; for supported data sources for which observations for a particular time are revised at later times as more data is received, gives access to some of the older versions of the data. NULL gives the latest revision of the observation. An integer value gives the value for each observation lag weeks after its initial report; the value 0 corresponds to using the initial report for each data point. (This function does not reconstruct what the data looked like at any particular point in the past, but can be used to do so.) |
| first.week.of.season | single integer value giving the week number that seasons start with, or NULL to have seasons start with the week number of the first data point |
| first.epiweek | year-epiweek as string in form "YYYYww" specifying a lower limit on times for which data will be fetched, or NULL to not impose a lower limit |
| last.epiweek | year-epiweek as string in form "YYYYww" specifying an upper limit on times for which data will be fetched, or NULL to not impose an upper limit |
| cache.file.prefix | length-1 character containing filepath prefix for files used to cache data from the delphi-epidata server, or NULL not to cache |
| cache.invalidation.period | single difftime: time duration that must pass from last fetch for a new fetch to be performed instead of reading from the cache; default is one day |
| force.cache.invalidation | single non-NA logical; if TRUE, then the cache.invalidation.period and a fetch will always be performed (the cache will not be read) |

Value

data frame (tbl_df) with \$date, \$year, \$week, and corresponding data (fields differ based on source)

Examples

```
## All fluview data at the national level:
fluview.nat.all.df =
  trimPartialPastSeasons(fetchEpidataDF("fluview", "nat",
    first.week.of.season=21L,
    cache.file.prefix="fluview_nat_allfetch"),
    "wili", min.points.in.season=33L)
## Fluview data at the national level for more recent seasons for which data
## was reported for all weeks (not just those in the influenza season), plus
## the current season:
fluview.nat.recent.df =
  trimPartialPastSeasons(fetchEpidataDF("fluview", "nat",
    first.week.of.season=21L,
    cache.file.prefix="fluview_nat_allfetch"),
    "wili", min.points.in.season=52L)
```

| | |
|---------------------|--|
| fetchEpidataFullDat | <i>Fetch data from delphi-epidata, trim partial seasons, and convert to list of trajectories</i> |
|---------------------|--|

Description

Fetch data from delphi-epidata, trim partial seasons, and convert to list of trajectories

Usage

```
fetchEpidataFullDat(source, area, signal.ind, min.points.in.season = 52L,
  lag = NULL, first.week.of.season = NULL, first.epiweek = NULL,
  last.epiweek = NULL, cache.file.prefix = NULL,
  cache.invalidation.period = as.difftime(1L, units = "days"),
  force.cache.invalidation = FALSE)
```

Arguments

| | |
|--------|---|
| source | length-1 character vector; name of data source; one of <ul style="list-style-type: none"> "fluview": U.S. Outpatient Influenza-like Illness Surveillance Network (ILINet) data from CDC FluView reports; weekly, national or by HHS region; updated weekly "ilinet": Estimates of ILINet data at state level; weekly; static "gft": Google Flu Trends data "ght": Google Health Trends data; currently restricted, not supported by this function |
|--------|---|

| | |
|---------------------------|--|
| | <ul style="list-style-type: none"> • "twitter": Twitter data; currently restricted, not supported by this function • "wiki": Wikipedia access log data; currently not supported by this function • "nidss.flu": Taiwan National Infectious Disease Statistics System (NIDSS) outpatient ILI data • "nidss.dengue": Taiwan National Infectious Disease Statistics System (NIDSS) dengue incidence data |
| area | length-1 character vector; name of area; possibilities by source are: <ul style="list-style-type: none"> • "fluvview": "hhs1", "hhs2", ..., "hhs10", "nat" • "ilinet": 2-character state abbreviation or "DC" • "gft": listed at https://github.com/undefx/delphi-epidata#gft-parameters • "nidss.flu", "nidss.dengue": one of "nationwide", "central", "eastern", "kaoping", "northern", "southern", "taipei" |
| signal.ind | single non-NA character/integer-valued index for column of df |
| min.points.in.season | the minimum number of non-NA values for signal.ind that a season must have in order to be retained; all rows corresponding to seasons containing less observations will be removed from df |
| lag | single integer value or NULL; for supported data sources for which observations for a particular time are revised at later times as more data is received, gives access to some of the older versions of the data. NULL gives the latest revision of the observation. An integer value gives the value for each observation lag weeks after its initial report; the value 0 corresponds to using the initial report for each data point. (This function does not reconstruct what the data looked like at any particular point in the past, but can be used to do so.) |
| first.week.of.season | single integer value giving the week number that seasons start with, or NULL to have seasons start with the week number of the first data point |
| first.epiweek | year-epiweek as string in form "YYYYww" specifying a lower limit on times for which data will be fetched, or NULL to not impose a lower limit |
| last.epiweek | year-epiweek as string in form "YYYYww" specifying an upper limit on times for which data will be fetched, or NULL to not impose an upper limit |
| cache.file.prefix | length-1 character containing filepath prefix for files used to cache data from the delphi-epidata server, or NULL not to cache |
| cache.invalidation.period | single difftime: time duration that must pass from last fetch for a new fetch to be performed instead of reading from the cache; default is one day |
| force.cache.invalidation | single non-NA logical; if TRUE, then the cache.invalidation.period and a fetch will always be performed (the cache will not be read) |

Value

named list of 52/53-length is.numeric vectors; each vector is the trajectory of the given signal for a single season, with NA's used to fill in for missing and future data; the names are of the form

"SYYYY", where YYYY is the first year of the season, e.g., "S2003" corresponds to the 2003–2004 season.

Examples

```
## All fluview data at the national level:
fluview.nat.all.full.dat =
  fetchEpidataFullDat("fluview", "nat", "wili", 33L, first.week.of.season=21L,
                      cache.file.prefix="fluview_nat_allfetch")
## Fluview data at the national level for more recent seasons for which data was
## reported for all weeks (not just those in the influenza season), plus the
## current season:
fluview.nat.recent.full.dat =
  fetchEpidataFullDat("fluview", "nat", "wili", 52L, first.week.of.season=21L,
                      cache.file.prefix="fluview_nat_allfetch")
```

fetchEpidataHistoryDF *Combine current and lagged epidata into a data frame*

Description

Take the epidata data frames for the specified lags plus the current (unlagged) epidata data frame and combine them together into a single data frame (tbl_df). There are two major uses:

- Preparing an epidata.history.df for [mimicPastEpidataDF](#): lags should include all possible lag values that could contain revisions; however, larger lag values may appear in the resulting data frame from the current epidata data frame, indicating that the corresponding data are finalized and there were no non-finalized versions recorded.
- Studying the errors for a set of lags: lags should include all lags of interest; the resulting data frame may include other lags from the current epidata data frame, which should be filtered out; this history data frame should be right-joined with a "ground truth" data frame.

Usage

```
fetchEpidataHistoryDF(source, area, lags, first.week.of.season = NULL,
                      first.epiweek = NULL, last.epiweek = NULL, cache.file.prefix,
                      cache.invalidation.period = as.difftime(1L, units = "days"),
                      force.cache.invalidation = FALSE, ignore.no.results = FALSE,
                      silent = FALSE)
```

See Also

[mimicPastEpidataDF](#)

fetchUpdatingResource *Fetch or read cache of a resource that potentially updates over time*

Description

Fetch or read cache of a resource that potentially updates over time

Usage

```
fetchUpdatingResource(fetch.thunk.fun, check.response.fun,
  cache.file.prefix = NULL, cache.invalidation.period = as.duration(1L,
    units = "days"), force.cache.invalidation = FALSE, silent = FALSE)
```

Arguments

| | |
|---------------------------|---|
| fetch.thunk.fun | a function that takes no arguments that, when called, attempts to fetch the desired resource and returns the response |
| check.response.fun | a function that takes a fetch response as input and either (a) stops if the response indicates an unsuccessful fetch or (b) returns nothing; this prevents invalid fetch responses from being saved to the cache. |
| cache.file.prefix | length-1 character containing a filepath prefix to use when creating files to cache the fetch response, or NULL to disable caching |
| cache.invalidation.period | length-1 duration; the minimum amount of time that must pass between the last cache update and a call to this function for fetch.thunk.fun to be called again rather than using the cache result (unless force.cache.invalidation=TRUE) |
| force.cache.invalidation | TRUE to force a cache update, even if the cache invalidation period has not passed; otherwise FALSE |
| silent | TRUE or FALSE (default); TRUE to disable messages about whether the cache is being used or not, or FALSE to enable these messages |

firstEpiweekOfUniverse

Epiweek before which no data should exist

Description

Assume that the universe was created in 1234 AD EW01, and that no data will be from times before this.

Usage

firstEpiweekOfUniverse

Format

An object of class integer of length 1.

| | |
|-----------------|--|
| get.latest.time | Get index (time) of last non-NA in a vector or other new.dat.sim |
|-----------------|--|

Description

Get index (time) of last non-NA in a vector or other new.dat.sim

Usage

get.latest.time(new.dat.sim)

| | |
|---------------------|-------------------------------|
| get_br_control_list | Generates control list for BR |
|---------------------|-------------------------------|

Description

Generates control list for BR

Usage

```
get_br_control_list(parent = NULL, max.n.sims = 100L, n.out = 53L,
  model = "Basis Regression", max.match.length = NULL, df = 10,
  w = 1, smooth = TRUE, model.noisy = TRUE, baseline = 0,
  basis = "bs", max.scale.factor = 3, cv.rule = c("min", "1se"),
  scale.method = c("none", "max", "last"))
```

Arguments

| | |
|------------|---|
| parent | another BR control list or NULL (default); a control list to base this one off of; arguments unspecified in the function call will be inherited from parent; if parent is NULL, a control list containing default values for all settings is used in its place. |
| max.n.sims | single non-NA integer value or NULL: the number of curves to sample from the inferred distribution |
| n.out | length-1 integer-valued vector; the length of the trajectories to produce in simulations |

| | |
|------------------|---|
| max.match.length | the maximum number of past data points to which the spline is fitted. The default, NULL, indicates to use all past data points when fitting the spline. |
| df | the degrees of freedom for the basis. Default is 10. |
| w | the mixing weight between the two loss terms, as in: $\text{sum over obs times } (y_{\text{obs}} - f)^2 + w * \text{sum over unobs times } (y_{\text{past}} - f)^2$, where y_{obs} is the current season's observed data, y_{past} is the past season's data, suitably transformed, and f is the function to be estimated. |
| smooth | logical; if TRUE, past observations and future "pseudo-observations" (predictions) will be smoothed; if FALSE, the observations and pseudo-observations will be returned unsmoothed. |
| model.noisy | logical; if TRUE and bootstrapping is enabled, will inject noise into future values and pin past observations to the observed values; if FALSE or TRUE but used when bootstrapping is disabled, br.sim will return the "non-noisy" regression curve |
| baseline | the anchoring point used for scaling past season's data; data above the baseline are scaled about the baseline. The default value, NA, indicates to scale about 0 (regardless of sign). |
| basis | type of basis to use. So far only "bs" (B-splines) are implemented. |
| max.scale.factor | single numeric: a limit on the amount of scaling performed by the scaling method: scale factors over max.scale.factor and under $1/\text{max.scale.factor}$ will be clipped. |
| cv.rule | one of "min" or "lse", where "min" gives the usual rule, and "lse" uses the 1-standard-error rule. |
| scale.method | whether and how to scale past seasons to match data from the cur.seasonth trajectory: "none" performs no scaling; "max" scales the maximum of each other season's trajectory — restricted to times which correspond to non-NA values in the cur.seasonth trajectory — so that it matches the maximum of the cur.seasonth trajectory; and "last" performs the same scaling using data at the time corresponding to the latest observation in the cur.seasonth trajectory |

| | |
|--------------|---|
| is_christmas | <i>Test if Date is Christmas Day (vectorized)</i> |
|--------------|---|

Description

Test if Date is Christmas Day (vectorized)

Usage

```
is_christmas(Date)
```

Arguments

| | |
|------|---------------------|
| Date | Date vector to test |
|------|---------------------|

Value

logical vector

| | |
|------------|--|
| is_newyear | <i>Test if Date is (Gregorian) New Year's Day (vectorized)</i> |
|------------|--|

Description

Test if Date is (Gregorian) New Year's Day (vectorized)

Usage

is_newyear(Date)

Arguments

Date Date vector to test

Value

logical vector

| | |
|-----------------|--|
| is_thanksgiving | <i>Test if Date is Thanksgiving Day (vectorized)</i> |
|-----------------|--|

Description

Test if Date is Thanksgiving Day (vectorized)

Usage

is_thanksgiving(Date)

Arguments

Date Date vector to test

Value

logical vector

| | |
|----------------|---|
| lastWeekNumber | <i>The number of weeks assigned to a given year or years.</i> |
|----------------|---|

Description

The length of one input should be evenly divisible by the length of the other.

Usage

```
lastWeekNumber(year, owning.wday)
```

Arguments

| | |
|-------------|---|
| year | integer/NA-valued vector of years |
| owning.wday | integer vector of wday numbers (0–7, 0 and 7 are both Sunday): a week is assigned to a given year based on whether this weekday is contained in that year |

Value

the number of weeks assigned to each year in years

Examples

```
## The number of epi weeks in each year from 1990 to 2020:  
lastWeekNumber(1990:2020, 3)
```

| | |
|--------------------|---|
| make_sim_ys_colors | <i>Make transparent colors according to weights in (0,1).</i> |
|--------------------|---|

Description

Make transparent colors according to weights in (0,1).

Usage

```
make_sim_ys_colors(weights)
```

Arguments

| | |
|---------|--|
| weights | Numeric vector with elements in [0,1]. |
|---------|--|

Value

Character vector containing color codes.

| | |
|-----------|---|
| map_join_ | <i>Map a function over the natural (Cartesian/other) join of array-like objects</i> |
|-----------|---|

Description

Map a function over the natural (Cartesian/other) join of array-like objects

Usage

```
map_join_(f, arraylike.args, elname.mismatch.behavior = c("stop",
  "intersect"), lapply_variant = parallel::mclapply, shuffle = TRUE,
  show.progress = TRUE, cache.prefix = NULL, use.proxy = FALSE)
```

```
map_join(f, ..., elname.mismatch.behavior = c("stop", "intersect"),
  lapply_variant = parallel::mclapply, shuffle = TRUE,
  show.progress = TRUE, cache.prefix = NULL, use.proxy = FALSE)
```

Arguments

| | |
|-----------------------------|---|
| <code>f</code> | the function to map |
| <code>arraylike.args</code> | a list of array-like objects with named dimnames (including "scalars" with <code>ndimp</code> of 0) and/or <code>no_join</code> objects |
| <code>...</code> | array-like objects with named dimnames, converted into an <code>arraylike.args</code> parameter using <code>list(...)</code> |

Details

The function `f` will be called with a number of arguments equal to the number of array-like arguments, with the argument names specified in the `arraylike.args` list; each argument will correspond to an element of one of the `arraylike.args`. `dimnamesnamesp` will be used on each array-like object to determine what indexing colnames it would have if melted; the result will have `dimnamesnamesp` containing all unique `dimnamesnamesp` from each of the arguments. For any two `dimnames` elements of with the same name selected from any of the `arraylike` arguments, either (a) the two should be identical, or (b) at least one should be trivial (NULL or repeated ""'s). Other types of objects can be wrapped in a list of class "no_join" using `no_join` and included in `arraylike.args`; they will be treated as scalars (constants), will not affect the number or naming of dimensions; the corresponding argument fed to `f` is always just the object wrapped inside the `no_join` object. This may be necessary if the same object should be used for all calls to `f` but the object appears to be array-like, to prevent new dimensions from being created or expected.

`map_join` is provided as a potentially more convenient interface, eliminating the need to explicitly form a list of `arraylike` args; it converts the `...` arguments into a list and delegates to `map_join_`

Value

an object of class "array" and mode "list" containing outputs from `f`, or a single output from `f` if all `arraylike.args` are scalars or `no_join`'s

See Also

no_join

Examples

```
library("pipeR")
map_join(`*`, 2L, 3L, lapply_variant=lapply)
map_join(`*`,
  with_dimnamesnames(2:3, "A"),
  with_dimnamesnames(1:3, "B")) %>%
  {mode(.) <- "numeric"; .}
map_join(`*`,
  vector_as_named_array(2:3, "A", letters[1:2]),
  with_dimnamesnames(array(1:6, 2:3), c("A", "B"))) %>%
  {mode(.) <- "numeric"; .}
cache.dir = tempfile()
map_join(`*`,
  vector_as_named_array(2:3, "A", letters[1:2]),
  with_dimnamesnames(1:3, "B"),
  cache.prefix=file.path(cache.dir, "outer_product")) %>%
{mode(.) <- "numeric"; .}
arraylike.args = list(NULL
, A=array(1:24, 2:4) %>%
  {dimnames(.) <- list(DA=paste0("S", 1:2), DB=1:3, DC=1:4); .}
, B=vector_as_named_array_(c(2.0, 2.1), "DA", c("S1", "S2"))
, C=matrix(1:4, 2L, 2L) %>%
  {dimnames(.) <- list(DA=paste0("S", 1:2), DA=paste0("S", 1:2)); .}
, D=142
, E=1:5
, F=vector_as_named_array_(11:14, "DC", 1:4)
, G=c(S1=1, S2=2)
, CP=matrix(1:4, 2L, 2L) %>%
  {dimnames(.) <- list(DA=paste0("S", 1:2), DA=paste0("S", 1:2)); .} %>%
  magrittr::extract(1:2, 2:1)
, FP=vector_as_named_array_(11:15, "DC", 1:5)[c(5, 3, 4, 2, 1)]
)[-1L]
map_join_(list, arraylike.args[c("A", "B", "C", "D", "F")][[DA="S1", DB=1L, DC=1L]]
map_join_(list, arraylike.args[c("A", "B", "C", "D", "F", "CP", "FP")],
  eltname.mismatch.behavior="intersect")[[DA="S1", DB=1L, DC=1L]]
```

match.arg.else.default

match.arg variant replacing unmatched args with choices[[1]], allowing non-character choices

Description

Assumes this usage: parent_fun = function(parent_arg[=parent_choices]) ... match.arg.forgiving(parent_arg) ... (with or without "=parent_choices").

Usage

```
match.arg.else.default(arg, choices)
```

Arguments

| | |
|----------------------|---|
| <code>arg</code> | the argument to match to a choice; should |
| <code>choices</code> | a positive-length vector; if it contains NULL, first choice should be NULL to avoid ambiguity |

Details

If `arg` is NULL, returns `choices[[1]]`.

If `choices` is a character vector, this performs partial matches; otherwise, it checks for `arg`'s that are `all.equal` with `check.attributes=FALSE`.

Value

`arg`, the corresponding match in `choices`, or `choices[[1]]` with a warning (when `arg` fails to match a choice)

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

Examples

```
library(testthat)
## author_header begin
## Copyright (C) 2016 Logan C. Brooks
##
## This file is part of epiforecast. Algorithms included in epiforecast were developed by Logan C. Brooks, David C.
##
## Research reported in this publication was supported by the National Institute Of General Medical Sciences of the
## author_header end
## license_header begin
## epiforecast is free software: you can redistribute it and/or modify
## it under the terms of the GNU General Public License as published by
## the Free Software Foundation, either version 2 of the License, or
## (at your option) any later version.
##
## epiforecast is distributed in the hope that it will be useful,
## but WITHOUT ANY WARRANTY; without even the implied warranty of
## MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
## GNU General Public License for more details.
##
## You should have received a copy of the GNU General Public License
## along with epiforecast. If not, see <http://www.gnu.org/licenses/>.
## license_header end

parent_function = function(ch1=letters[1:5], ch2=c("AAA", "AAB", "BBB"),
```

```

        num1=1:5, int1=6L:10L,
        list1=list(1:2,3:4), list2=list(NULL,"a",c(two=2),1:5)) {
  return (list(
    ch1=match.arg.else.default(ch1),
    ch2=match.arg.else.default(ch2),
    num1=match.arg.else.default(num1),
    int1=match.arg.else.default(int1),
    list1=match.arg.else.default(list1),
    list2=match.arg.else.default(list2)
  ))
}

## Return default on missing:
expect_equal(parent_function(),
  list(ch1="a", ch2="AAA", num1=1, int1=6L, list1=1:2, list2=NULL))

## Return default on NULL:
expect_equal(parent_function(NULL, NULL, NULL, NULL, NULL, NULL),
  list(ch1="a", ch2="AAA", num1=1, int1=6L, list1=1:2, list2=NULL))

## Allow partial matches, all.equal ignoring attributes:
expect_equal(parent_function("b", c(extraneous.name="B"), 3L, 8.00000000001, c(p=3,q=4), 2),
  list(ch1="b", ch2="BBB", num1=3.0, int1=8L, list1=3:4, list2=c(two=2)))

## Return default with warning on mismatched inputs:
expect_equal(suppressWarnings(parent_function("q", "A", "nonnumeric", 11L, 1:4, c("A","B","C"))),
  list(ch1="a", ch2="AAA", num1=1, int1=6L, list1=1:2, list2=NULL))
expect_warning(parent_function("q"))
expect_warning(parent_function("A"))
expect_warning(parent_function(,"nonnumeric"))
expect_warning(parent_function(,,11L))
expect_warning(parent_function(,,,1:4))
expect_warning(parent_function(,,,,c("A","B","C")))

## Produce error on inappropriate inputs:
expect_error(parent_function(3), "length-1 character")
expect_error(parent_function(letters[1:2]), "length-1 character")

## todo produce error on inappropriate =choices=

```

match.dat

Match dat object input

Description

Returns a list of possibly-named numeric-class vectors given a list of possibly-named (is.)numeric vectors as input, or generates an error if the input seems inappropriate.

Usage

```
match.dat(dat)
```

Arguments

dat supposed to be a list of possibly-named numeric vectors

Value

dat as a list of numeric-class vectors

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

| | |
|---------------|-----------------------------------|
| match.integer | <i>Match integer-valued input</i> |
|---------------|-----------------------------------|

Description

Returns a possibly-named integer-class vector version of the input, or produces an error if the input seems inappropriate.

Usage

```
match.integer(inp)
```

Arguments

inp supposed to be a possibly-named numeric object with integer/NA values.

Value

inp as an integer vector

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

| | |
|-------------------|--|
| match.new.dat.sim | <i>Convert trajectory, trajectory matrix, or sim to sim; error otherwise</i> |
|-------------------|--|

Description

*.sim methods should eventually all support sim objects as input for new.dat rather than just single trajectories, but, for the convenience of the user, allow other types of input as well. Specifically, we should accept:

- Trajectory: a numeric vector;
- Trajectory matrix: a numeric matrix with each column a trajectory; and
- Sim: a list with \$ys a #times by #trajectories numeric matrix with #trajectories ≥ 1 and each row either all NA or all non-NA, and \$weights a #trajectories-length numeric matrix with entries all ≥ 0 .

Usage

```
match.new.dat.sim(new.dat.sim)
```

Arguments

new.dat.sim trajectory / trajectory matrix / sim object

Details

This method checks that it receives such an input and outputs a corresponding sim object.

Value

sim object

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

Examples

```
match.new.dat.sim(1:5)
match.new.dat.sim(as.matrix(1:5)[,rep(1,10)]))
match.new.dat.sim(list(ys=as.matrix(1:5)[,rep(1,10)], weights=0:9))
```

```
match.nonnegative.numeric
```

Match all non-negative — within eps — is.numeric input

Description

Returns the input with any nearly-non-negative entries replaced with 0 if the original input is `is.numeric` and all of its entries are within `eps` of being non-negative. Otherwise raises an error.

Usage

```
match.nonnegative.numeric(x, eps = sqrt(.Machine[["double.eps"]]))
```

Arguments

| | |
|------------------|---|
| <code>x</code> | object that <code>is.numeric</code> ; object to check |
| <code>eps</code> | single non-NA non-negative <code>is.numeric</code> ; threshold of tolerance for negative values |

Value

`x` with negative (nearly non-negative) entries replaced with 0 if `x` meets the nearly non-negative criterion; otherwise an error is raised

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

```
match.single.na.or.numeric
```

Match length-1 numeric input

Description

Returns a possibly-named length-1 possibly-NA numeric vector version of the input, or produces an error if the input seems inappropriate.

Usage

```
match.single.na.or.numeric(x)
```

Arguments

| | |
|----------------|---|
| <code>x</code> | supposed to be a possibly-named length-1 numeric object |
|----------------|---|

Value

x as a length-1 numeric vector

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

```
match.single.nonna.integer
```

Match length-1 non-NA integer-valued input

Description

Returns a possibly-named length-1 non-NA integer-class vector version of the input, or produces an error if the input seems inappropriate.

Usage

```
match.single.nonna.integer(n)
```

Arguments

n supposed to be a possibly-named length-1 non-NA integer-valued is.numeric object

Value

n as a length-1 integer-class vector

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

```
match.single.nonna.integer.or.null
```

Match length-1 non-NA integer-valued input or NULL

Description

Returns a possibly-named length-1 non-NA integer-class vector version of the input if non-NULL, NULL if input is NULL, or produces an error if the input seems inappropriate.

Usage

```
match.single.nonna.integer.or.null(n)
```

Arguments

n supposed to be a possibly-named length-1 non-NA integer-valued numeric object or NULL

Value

n as a length-1 integer-class vector

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

match.single.nonna.numeric

Match length-1 non-NA numeric-valued input

Description

Returns a possibly-named length-1 non-NA numeric-class vector version of the input, or produces an error if the input seems inappropriate.

Returns a possibly-named length-1 non-NA numeric-class vector version of the input, or produces an error if the input seems inappropriate.

Usage

match.single.nonna.numeric(x)

match.single.nonna.numeric(x)

Arguments

x supposed to be a possibly-named length-1 non-NA numeric-valued numeric object

x supposed to be a possibly-named length-1 non-NA numeric-valued numeric object

Value

x as a length-1 numeric-class vector

x as a length-1 numeric-class vector

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

| | |
|---------------------|--|
| match.single.wday.w | <i>Returns a possibly-named length-1 integer-class vector of weekday numbers in 0:6 (%w format) given an integer-valued length-1 numeric vector with values in 0:7 (%w or %u format), or throws an error if the input seems inappropriate.</i> |
|---------------------|--|

Description

Returns a possibly-named length-1 integer-class vector of weekday numbers in 0:6 (%w format) given an integer-valued length-1 numeric vector with values in 0:7 (%w or %u format), or throws an error if the input seems inappropriate.

Usage

```
match.single.wday.w(wday)
```

Arguments

| | |
|------|---|
| wday | vector of weekday numbers (each %in% 0:7) |
|------|---|

Value

integer-class %w format weekday numbers

| | |
|--------------|--|
| match.wday.w | <i>Returns a possibly-named integer-class vector of weekday numbers in 0:6 (%w format) given an integer-valued numeric vector with values in 0:7 (%w or %u format), or throws an error if the input seems inappropriate.</i> |
|--------------|--|

Description

Returns a possibly-named integer-class vector of weekday numbers in 0:6 (%w format) given an integer-valued numeric vector with values in 0:7 (%w or %u format), or throws an error if the input seems inappropriate.

Usage

```
match.wday.w(wday)
```

Arguments

| | |
|------|---|
| wday | vector of weekday numbers (each %in% 0:7) |
|------|---|

Value

integer-class %w format weekday numbers

| | |
|-------------|---|
| mimicPastDF | <i>Mimic a past version of a dataset using (partial) history data</i> |
|-------------|---|

Description

Given some potentially partial data about past issues, given by labeling and rbinding together (available sections of available) past issues, mimic what a particular past issue would have looked like. (NA issues are treated as larger than any non-NA issue.)

Usage

```
mimicPastDF(history.df, issue.colname, mimicked.issue,
  time.index.colnames = character(0), time.index.limits = list(),
  nontime.index.colnames = character(0))
```

Arguments

| | |
|------------------------|---|
| history.df | rbound partial past issues |
| issue.colname | name of the column containing issue(label)s, which should have some ordering |
| mimicked.issue | length-1; (label of) issue to mimic |
| time.index.colnames | character vector of colnames containing time indices for observations (should not include issue.colname); used for both filtering and grouping some data |
| time.index.limits | list with length matching that of time.index.colnames; data with time indices above the corresponding limits is filtered out this time.index.limit, using lexicographical ordering when multiple time indices are specified |
| nontime.index.colnames | character vector; names of columns containing any non-time-related observation indices (e.g., locations) |

| | |
|--------------------|---|
| mimicPastEpidataDF | <i>Mimic what fetchEpidataDF would have given in the past</i> |
|--------------------|---|

Description

Attempt to reproduce what fetchEpidataDF would have produced given data through issue forecast.epiweek (i.e., data through the time when the initial report for forecast.epiweek would have been available). Historical data is not always complete. Try the following in order for each observation week: (1) look for data for the report corresponding to the forecast week, (2) look for data in earlier reports (taking the latest report with data), (3) look for data in later reports (taking the earliest report with data). For example, the ILINet (source="fluview") US National (area="nat") historical data skips issue 200352; when forecast.epiweek is chosen as 200352, observations for epiweek 200340 through 200351 are provided by the previous issue, 200351, while the observation

for epiweek 200352 uses data from the *next* issue, 200353. (Observations for earlier seasons also use "future" data from issue 201352, because issue 201352 is special, filling in data for epiweeks missing from all available past issues.) Isolated skipped weeks are uncommon; usually when back-fill data is missing, it is for earlier seasons, during the off-season, or at the beginning of a season; for example, in HHS Region 1 (area="hhs1"), the first recorded issue was 200949, so mimicing any reports from the 2005/2006 season will use finalized data from issue 201352 instead, and mimicing report 200940 will fill in 200940 with data from issue 200949. Similarly, data is missing from the following off-season through issue 201040, inclusive, so mimicing report 201040 will fill in off-season data with finalized data from issue 201352, and the observation for 201040 with data from issue 201041.

Usage

```
mimicPastEpidataDF(epidata.history.df, forecast.epiweek)
```

Arguments

epidata.history.df

output of [fetchEpidataHistoryDF](#); the lags argument fed to these functions should include all lags that could possibly contain revisions.

forecast.epiweek

length-1 integer: issue number to simulate the fetchEpidataDF for; epiweek format is YYYYww

Examples

```
## set up a cache directory:
epidata.cache.dir = "~/epiforecast-cache"
if (!dir.exists(epidata.cache.dir)) {
  dir.create(epidata.cache.dir)
}
## fetch HHS Region 1 ILINet version history, assuming no significant
## revisions past lag 51:
fluvview.area = "hhs1"
epidata.history.df = fetchEpidataHistoryDF(
  "fluvview", fluvview.area, 0:51,
  first.week.of.season = 31L,
  cache.file.prefix=file.path(epidata.cache.dir,paste0("fluvview_",fluvview.area))
)
## Simulate fetchEpidataHistoryDF when issue 201540 (the first ILINet report
## containing data for epiweek 201540) just came out:
mimicPastEpidataDF(epidata.history.df, 201540L)
```

model_week_to_epi_week

Convert model week numbers into epi week numbers

Description

Convert model week numbers into epi week numbers

Usage

```
model_week_to_epi_week(model.week, first.week.of.season, n.weeks.in.season)
```

Arguments

| | |
|----------------------|--|
| model.week | integer or numeric vector; model weeks — epi weeks that don't (necessarily) wrap around to 1 at the start of a new year (after week 52 or 53 of the previous year) but rather wrap around when a season ends, starting back at first.week.of.season; values could be integers between first.week.of.season to first.week.of.season+52L or first.week.of.season+53L for integers, or a valid integer value plus a number in the clopen interval [0,1) for numeric vectors |
| first.week.of.season | epi week number of the first element in a trajectory (i.e., corresponding to time 1L) |
| n.weeks.in.season | 52L or 53L — the length of the indexed trajectory, corresponding to the number of weeks in the first year contained in the season |

Value

integer or numeric vector with same length as model.week; epi week numbers (wrapper versions of model week numbers in 1..52 + [0,1) or 1..53 + [0,1)) corresponding to the given model week numbers

model_week_to_time

Convert model weeks (shifted indices) into times (indices)

Description

Convert model weeks (shifted indices) into times (indices)

Usage

```
model_week_to_time(model.week, first.week.of.season)
```

Arguments

`model.week` integer or numeric vector; model weeks — times shifted forward by `first.week.of.season-1L`

`first.week.of.season` epi week number of the first element in a trajectory (i.e., corresponding to time 1L)

Value

integer or numeric vector with same length as `model.week`; times — integer indices into trajectories containing weekly data, or numeric numbers that could also refer to times between these indices

`named_array_to_name_arrayvecs`

dimnamesp of an array, as a list of named lists

Description

`dimnamesp` of an array, as a list of named lists

Usage

`named_array_to_name_arrayvecs(named.array)`

Examples

```
library("pipeR")
array(1:24, 2:4) %>%
  with_dimnames(list(c("a", "b"),
                     c("c", "d", "e"),
                     c("f", "g", "h", "i")))) %>%
  named_array_to_name_arrayvecs()
array(1:120, 2:5) %>%
  with_dimnames(list("First dimension"=c("a", "b"),
                     "Second dimension"=NULL,
                     c("f", "g", "h", "i"),
                     NULL)) %>%
  named_array_to_name_arrayvecs()
## Some unusual inputs may give surprising output that may not have the exact
## same properties as for more common cases shown above. Behavior on these cases
## likely may change in subsequent versions of this package. In particular,
## behavior for arrays with names assigned to elements of dimnames may be
## surprising and should be considered unstable functionality:
array(1:24, 2:4) %>%
  with_dimnames(list("Unusual dimension"=c(A="a", B="b"),
                     c("c", "d", "e"),
                     c("f", "g", "h", "i")))) %>%
  named_array_to_name_arrayvecs()
```

`named_arrayvec_to_name_arrayvec`

Names of a 1-D array, as a character array with the same dimnames(names)

Description

Given a 1-D array or other object with non-NULL names, turn it into a 1-D character array with values given by the input's names, and the same dimnames as the input (if any), including the names of the dimnames. Objects are converted to arrays first for more consistent behavior (e.g., vectors can have names but not dimnames; converting to an array gives dimnames equal to `list(names(vec))`).

Usage

`named_arrayvec_to_name_arrayvec(arrayvec)`

Examples

```
library("pipeR")
array(1:5, 5) %>>%
  with_dimnames(list(letters[1:5])) %>>%
  with_dimnamesnames("Only dimension") %>>%
  named_arrayvec_to_name_arrayvec()
array(1:5, 5) %>>%
  with_dimnames(list(letters[1:5])) %>>%
  named_arrayvec_to_name_arrayvec()
## Conversion to arrays is attempted for non-array inputs, e.g., the two
## expressions below should be exchangeable:
stats::setNames(1:5, letters[1:5]) %>>%
  as.array() %>>%
  named_arrayvec_to_name_arrayvec()
stats::setNames(1:5, letters[1:5]) %>>%
  named_arrayvec_to_name_arrayvec()
```

`namesp`

names, but always outputting character vector of natural length

Description

If object does not have names, outputs a vector of empty strings of matching length instead of NULL.

Usage

`namesp(x)`

Arguments

| | |
|-----------------------------|---|
| <code>x</code> | the object |
| <code>invent.scalars</code> | length-1 non-NA logical; if TRUE, treat unnamed length-1 vector <code>x</code> 's as "scalars" with zero dimensions; if FALSE, treat them as arrays with one dimension of size 1. |

| | |
|--------------------|---|
| <code>ndimp</code> | <i>The number of dimensions of an object; length of <code>dimp</code></i> |
|--------------------|---|

Description

The number of dimensions of an object; length of `dimp`

Usage

```
ndimp(x, invent.scalars = TRUE)
```

Arguments

| | |
|-----------------------------|---|
| <code>x</code> | the object |
| <code>invent.scalars</code> | length-1 non-NA logical; if TRUE, treat unnamed length-1 vector <code>x</code> 's as "scalars" with zero dimensions; if FALSE, treat them as arrays with one dimension of size 1. |

| | |
|----------------------|---|
| <code>no_join</code> | <i>Mark an array-like or other argument to be used like a constant/scalar in map_join</i> |
|----------------------|---|

Description

Mark an array-like or other argument to be used like a constant/scalar in [map_join](#)

Usage

```
no_join(x)
```

Arguments

| | |
|----------------|----------------------|
| <code>x</code> | the argument to mark |
|----------------|----------------------|

Value

an object of class "map_join" wrapping `x`

Examples

```
map_join(`+`, with_dimnamesnames(1:3,"A"), with_dimnamesnames(1:3,"A"))
map_join(`+`, with_dimnamesnames(1:3,"A"), no_join(with_dimnamesnames(1:3,"A")))
```

| | |
|-----|--|
| ons | <i>Calculate the onset of a trajectory (post-rounding)</i> |
|-----|--|

Description

Calculate the onset of a trajectory (post-rounding)

Usage

```
ons(trajectory, baseline, is.inseason, ...)
```

Arguments

| | |
|-------------|--|
| trajectory | a vector |
| baseline | the onset threshold |
| is.inseason | logical vector length-compatible with trajectory, acting as a mask on possible output values |
| ... | ignored |

Value

the first index which is part of the in-season and is part of a run of consecutive observations above the onset threshold that lasts at least for two additional indices

| | |
|-----|--|
| pht | <i>Calculate the peak height of a trajectory</i> |
|-----|--|

Description

Calculate the peak height of a trajectory

Usage

```
pht(trajectory, is.inseason = rep_len(TRUE, length(trajectory)), ...)
```

Arguments

| | |
|-------------|---|
| trajectory | a vector |
| is.inseason | logical vector length-compatible with trajectory, |
| ... | ignored |

Value

a scalar — the maximum value of the vector

| | |
|----------|--|
| plot.sim | <i>Plotting function for "sim" class</i> |
|----------|--|

Description

Plotting function for "sim" class

Usage

```
## S3 method for class 'sim'
plot(mysim, ylab = "Disease Intensity", xlab = "Time",
     lty = 1, nplot = min(100, ncol(mysim$ys)), type = c("lineplot",
     "density", "hexagonal"), overlay = FALSE, ...)
```

| | |
|----------------------|--|
| plot.target_forecast | <i>plot method for target_forecast objects</i> |
|----------------------|--|

Description

plot method for target_forecast objects

Usage

```
## S3 method for class 'target_forecast'
plot(x, add = FALSE, ...)
```

Arguments

| | |
|-----|--|
| x | target_forecast object |
| add | logical, length 1, non-NA: whether to plot on top of the currently active plot (vs. creating a new plot) |

| | |
|-----------|--|
| print.sim | <i>Printing function for "sim" class</i> |
|-----------|--|

Description

Printing function for "sim" class

Usage

```
## S3 method for class 'sim'
print(x, verbose = TRUE, ...)
```

Arguments

| | |
|---|---|
| x | Output from running an OO.sim() function. |
|---|---|

```
print.target_forecast Print a forecast object
```

Description

Print a forecast object

Usage

```
## S3 method for class 'target_forecast'
print(x, sig.digit = 2L, ...)
```

Arguments

x output of a forecast method

```
pwk                      Calculate the peak week(s) in a vector of weekly observations
```

Description

Calculate the peak week(s) in a vector of weekly observations

Usage

```
pwk(trajjectory, is.inseason = rep_len(TRUE, length(trajjectory)), ...)
```

Arguments

trajjectory a vector of weekly observations
 is.inseason logical vector length-compatible with trajjectory,
 ... ignored

Value

integer vector, typically of length 1; indices of elements that are \geq all other elements

| | |
|----------------|--|
| read.from.file | <i>Function that reads from a csv file</i> |
|----------------|--|

Description

Function that reads from a csv file

Usage

```
read.from.file(filename)
```

Arguments

| | |
|----------|---|
| filename | name of data file with each column equal to each season, with the first (n-1) columns to be, and the n'th column with the current season. |
|----------|---|

```
seasonModelWeekDFToYearWeekDF
```

Convert season-model.week in data.frame to year-week

Description

Like [yearWeekDFToSeasonModelWeekDF](#), but in opposite direction.

Usage

```
seasonModelWeekDFToYearWeekDF(seasonModelWeek, first.week, owning.wday)
```

Arguments

| | |
|-----------------|---|
| seasonModelWeek | data.frame (or other list) with columns \$season: integer-valued vector: season numbers \$model.week: integer-valued vector: model week numbers |
| first.week | integer-valued vector: week number that the seasons start on |
| owning.wday | integer-valued vector of weekday numbers: weekday that determines the year to which a week will be assigned |

Value

data.frame with two columns giving the corresponding year-week breakdown:

\$year: integer-class vector: years

\$week: integer-class vector: week numbers

Examples

```

dates = as.Date("2015-01-01")+seq.int(0L, 1000L, 7L)
ywwd = DateToYearWeekWdayDF(dates, 0L, 3L) # epi week convention
dates.duplicate1 = yearWeekWdayDFToDate(ywwd, 0L, 3L)
identical(dates, dates.duplicate1)
smw = yearWeekDFToSeasonModelWeekDF(ywwd, 21L, 3L) # seasons starting on week number 21
yw = seasonModelWeekDFToYearWeekDF(smw, 21L, 3L)
identical(ywwd[,c("year", "week")], yw)
dates.duplicate2 = seasonModelWeekWdayDFToDate(cbind(smw, wday=ywwd$wday), 21L, 0L, 3L)
identical(dates, dates.duplicate2)

```

```
seasonModelWeekToYearWeekDF
```

Convert season-model.week to year-week

Description

Like [yearWeekToSeasonModelWeekDF](#), but in opposite direction.

Usage

```
seasonModelWeekToYearWeekDF(season, model.week, first.week, owning.wday)
```

Arguments

| | |
|-------------|---|
| season | integer-valued vector: season numbers |
| model.week | integer-valued vector: model week numbers |
| first.week | integer-valued vector: week number that the seasons start on |
| owning.wday | integer-valued vector of weekday numbers: weekday that determines the year to which a week will be assigned |

Value

data.frame with two columns giving the corresponding year-week breakdown:

\$year: integer-class vector: years

\$week: integer-class vector: week numbers

seasonModelWeekWdayDFToDate

Convert season-model.week-wday data.frame to Date

Description

Convert season-model.week-wday data.frame to Date

Usage

```
seasonModelWeekWdayDFToDate(seasonModelWeekWday, first.week, first.wday,  
    owning.wday, error.on.wrap = TRUE)
```

Arguments

seasonModelWeekWday

data.frame with \$season, model.week, and wday columns

| | |
|------------|-----------------------------|
| first.week | first week number of season |
|------------|-----------------------------|

| | |
|------------|------------------------------|
| first.wday | first weekday number of week |
|------------|------------------------------|

| | |
|-------------|---|
| owning.wday | integer-valued vector of weekday numbers: weekday that determines the year to which a week will be assigned |
|-------------|---|

| | |
|----------------------------|---|
| <code>error.on.wrap</code> | TRUE or FALSE: if TRUE, an error is generated if a given week falls outside the range of possible week numbers for the corresponding year (i.e., if it is nonpositive or greater than the number of weeks assigned to the corresponding year in year); if FALSE, the week number will wrap around to future or previous years (e.g., week 0 of 1997 will be considered the last week of 1996) |
|----------------------------|---|

Value

Date vector with the corresponding dates

seasonModelWeekWdayToDate

Convert season-model.week-wday to Date

Description

Convert season-model.week-wday to Date

Usage

```
seasonModelWeekWdayToDate(season, model.week, wday, first.week, first.wday,
  owning.wday, error.on.wrap = TRUE)
```

Arguments

| | |
|---------------|---|
| season | season number |
| model.week | model week number |
| wday | weekday number |
| first.week | first week number of season |
| first.wday | first weekday number of week |
| owning.wday | integer-valued vector of weekday numbers: weekday that determines the year to which a week will be assigned |
| error.on.wrap | TRUE or FALSE: if TRUE, an error is generated if a given week falls outside the range of possible week numbers for the corresponding year (i.e., if it is nonpositive or greater than the number of weeks assigned to the corresponding year in year); if FALSE, the week number will wrap around to future or previous years (e.g., week 0 of 1997 will be considered the last week of 1996) |

Value

Date vector with the corresponding dates

| | |
|--------------|--|
| seasonOfDate | <i>Get the season number associated with a particular date</i> |
|--------------|--|

Description

Seasons are 52/53-week-long time spans that start with a particular week number (from 1 to 52); years are a special case that start with week 1. Seasons contain weeks from two consecutive years except in the case that the season starts with week 1, in which case it coincides exactly with a single year. Seasons are numbered by the first distinct year from which they take weeks, and labeled with an "S" prefix; for example, a season containing weeks from 2015 and 2016 would be numbered 2015 and labeled "S2015". This function gives the season number associated with the dates.

Usage

```
seasonOfDate(date, first.week, first.wday, owning.wday)
```

Arguments

| | |
|-------------|---|
| date | object convertible to Date |
| first.week | the week on which each season should start |
| first.wday | weekday number(s) (0–7, Sunday can be 0 or 7): the weekday that is considered the beginning of the week; typically Sunday or Monday |
| owning.wday | weekday number(s) (0–7, Sunday can be 0 or 7): a week is assigned to a given year if the owning weekday of that week falls in that year; typically first.wday or first.wday+3 |

Value

named integer-valued vector: season numbers associated with the inputted weeks with names giving the season labels

| | |
|------------------|---|
| seasonOfYearWeek | <i>Get the season number associated with a particular year and week</i> |
|------------------|---|

Description

Seasons are 52/53-week-long time spans that start with a particular week number (from 1 to 52); years are a special case that start with week 1. Seasons contain weeks from two consecutive years except in the case that the season starts with week 1, in which case it coincides exactly with a single year. Each season ends the week before the next season (with the same starting week) begins. Seasons are numbered by the first distinct year from which they take weeks, and labeled with an "S" prefix; for example, a season containing weeks from 2015 and 2016 would be numbered 2015 and labeled "S2015". This function gives the season number associated with the inputted weeks specified as year-week combinations.

Usage

seasonOfYearWeek(year, week, first.week)

Arguments

| | |
|------------|---|
| year | integer-valued vector: year in which the weeks fall |
| week | integer-valued vector: associated week numbers (each %in% 1:53) |
| first.week | the week on which each season should start |

Value

named integer-valued vector: season numbers associated with the inputted weeks with names giving the season labels

| | |
|-----|---|
| Seq | <i>A seq variant that produces a 0-length vector when !(from <= to).</i> |
|-----|---|

Description

A seq variant that produces a 0-length vector when !(from <= to).

Usage

Seq(from, to, ...)

Arguments

| | |
|------|---|
| from | starting number (or other object compatible with seq) |
| to | ending number (or other object compatible with seq) |
| ... | arguments to forward to seq |

```
show.sample.trajectories
```

Showing sample trajectories of ys.

Description

Showing sample trajectories of ys.

Usage

```
show.sample.trajectories(ys, n.shown.rows = 100L, n.shown.cols = 100L)
```

Arguments

| | |
|--------------|--|
| ys | A matrix whose columns contain simulated curves. |
| n.shown.rows | How many observations per curve to show. |
| n.shown.cols | How many curves to show. |

```
table.to.list
```

Function to change full.dat from table to list.

Description

Function to change full.dat from table to list.

Usage

```
table.to.list(full.dat)
```

| | |
|-----------------|---|
| target_forecast | <i>Forecast distribution of targets such as peak height from model fits</i> |
|-----------------|---|

Description

This S3 method generates forecasts of various targets (e.g., peak height of a trajectory) derived from some type of model fit. For example, the fit model could be a collection of simulations of the trajectory, and this method will calculate the desired target for each simulation and aggregate these results into a distributional forecast. Refer to the appropriate S3 implementation for a given model fit for additional details.

Usage

```
target_forecast(fit.model, ...)
```

Arguments

| | |
|-----------|---|
| fit.model | the fit model (trajectory forecast, simulations, regression fit, etc.), on which to base the target forecasts |
|-----------|---|

See Also

[target_forecast.sim](#)

| | |
|---------------------|---|
| target_forecast.sim | <i>Forecast a target (peak height, etc.) using a sim object</i> |
|---------------------|---|

Description

Forecast a target (peak height, etc.) using a sim object

Usage

```
## S3 method for class 'sim'
target_forecast(mysim, target = c("pwk", "pht", "ons",
  "dur"), target.name = target, target.fun = target,
  target_trajectory_preprocessor = function(trajectory) trajectory,
  target.spec = NULL, target_value_formatter = identity,
  target.multival.behavior = c("random.val", "closest.to.pred.val"),
  compute.estimates = TRUE, hist.bins = NULL, ...)
```

Arguments

| | |
|-------|---|
| mysim | Output from running an OO.sim() function. |
|-------|---|

| | |
|--------------------|---|
| time_to_model_week | <i>Convert times (indices) into model weeks (shifted indices)</i> |
|--------------------|---|

Description

Convert times (indices) into model weeks (shifted indices)

Usage

```
time_to_model_week(time, first.week.of.season)
```

Arguments

| | |
|----------------------|--|
| time | integer or numeric vector; integer indices into trajectories containing weekly data, or numeric numbers that could also refer to times between these indices |
| first.week.of.season | epi week number of the first element in a trajectory (i.e., corresponding to time 1L) |

Value

integer or numeric vector with same length as time; model weeks — times shifted forward by first.week.of.season-1L — corresponding to time

| | |
|------------------------|--|
| trimPartialPastSeasons | <i>Trims incomplete past seasons from a data.frame</i> |
|------------------------|--|

Description

Removes rows from df corresponding to "past" seasons (i.e., all but the last season in df) for which df has less than min.points.in.season non-missing entries in df[[signal.ind]].

Usage

```
trimPartialPastSeasons(df, signal.ind, min.points.in.season)
```

Arguments

| | |
|----------------------|--|
| df | data frame with columns df\$season, and df[[signal.ind]] |
| signal.ind | single non-NA character/integer-valued index for column of df |
| min.points.in.season | the minimum number of non-NA values for signal.ind that a season must have in order to be retained; all rows corresponding to seasons containing less observations will be removed from df |

| | |
|---------------------|---|
| twkde.markovian.sim | <i>Time-parameterized kernel density estimation sim method, Markovian version</i> |
|---------------------|---|

Description

Function for making forecasts with the basic time-parameterized kernel density estimation method. This method estimates `diff(new.dat)[t-1]` (used to produce `dat[t]`) for a trajectory `new.dat` based on weighted kernel density estimation using values of `dat` at the corresponding time of season (a Markov process). The weights are based on `new.dat[t-1]` and the corresponding values in `dat`; the weighting function is a Gaussian kernel with width determined by `bw.SJnrD0`.

Usage

```
twkde.markovian.sim(full.dat, baseline = NA_real_, max.n.sims = 1000L)
```

Value

a sim object — a list with two components:

`ys`: a numeric matrix, typically with multiple columns; each column is a different possible trajectory for the current season, with NA's in the input for the current season filled in with random draws from the forecasted distribution, and non-NA's (observed data) filled in with an imagined resampling of noise based on the model (for some models, the non-NA values will remain unchanged).

`weights`: a numeric vector; assigns a weight to each column of `ys`, which is used by methods relying on importance sampling.

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

Examples

```
## National-level ILINet weighted %ILI data for recent seasons, excluding 2009 pandemic:
area.name = "nat"
full.dat = fetchEpidataFullDat("fluview", area.name, "wili",
                               min.points.in.season = 52L,
                               first.week.of.season = 31L,
                               cache.file.prefix=sprintf("fluview_%s_fetch", area.name))
full.dat <- full.dat[names(full.dat)!="S2009"]
## Sample from conditional curve distribution estimate using the above data
## and CDC's 2015 national %wILI onset threshold baseline of 2.1:
sim = twkde.markovian.sim(full.dat, baseline=2.1, max.n.sims=100)
print(sim)
plot(sim, type="lineplot")
```

twkde.sim

Time-parameterized kernel density estimation sim method with heuristic adjustments

Description

Function for making forecasts with the time-parameterized kernel density estimation method with tweaks. This method estimates `diff(new.dat)` based on weighted kernel density estimation. Weights are based on the time of season and four functions of `new.dat`: (a) the last observed value in `new.dat`, (b) the sum of observed values in `new.dat`, (c) an exponential moving average of the observed values in `new.dat`, and (d) an exponential moving average of the changes in observed values in `new.dat` (i.e., in `diff(new.dat)`). The weighting function is separable, and consists of two components: a highly weighted "base" weighting function and a lowly weighted boxcar weighting function. The base weighting function is the product of an integral Laplacian kernel with respect to time of season, and Gaussian kernels with respect to the four `new.dat`-based components (with bandwidths selected by the [bw.SJnrd0](#) method, and relative weighting controlled by `tradeoff.weights`). Each time a difference is drawn, simulating `diff(new.dat)[t-1]`, the corresponding result for `new.dat[t]` is linearly mixed with a randomly selected value from historical curves around that time.

Usage

```
twkde.sim(full.dat, baseline = NA_real_, max.n.sims = 1000L,
  decay.factor = 0.7, diff.decay.factor = 0.5,
  max.shifts = c(rep(10L, 10L), 10:1, rep(0L, 3L), 1:10, rep(10L, 20L)),
  shift.decay.factor = 0.7, tradeoff.weights = c(0.5, 0.25, 0.25, 0.5))
```

Arguments

| | |
|---------------------------------|---|
| <code>decay.factor</code> | decay factor for the exponential moving average of covariate. |
| <code>diff.decay.factor</code> | decay factor for the exponential moving average of differences covariate. |
| <code>max.shifts</code> | numeric vector with length matching the trajectory length in <code>new.dat.sim</code> ; specifies the width of the time-of-season kernel as a function of the time of season. |
| <code>shift.decay.factor</code> | decay factor for the time-of-season Laplacian kernel component. |
| <code>tradeoff.weights</code> | log-scale weighting factors for the four non-time-based kernel components (last observed value, sum of observed values, exponential moving average of values, exponential moving average of differences). |

Value

a sim object — a list with two components:

`ys`: a numeric matrix, typically with multiple columns; each column is a different possible trajectory for the current season, with NA's in the input for the current season filled in with random draws from the forecasted distribution, and non-NA's (observed data) filled in with an imagined resampling of noise based on the model (for some models, the non-NA values will remain unchanged).

`weights`: a numeric vector; assigns a weight to each column of `ys`, which is used by methods relying on importance sampling.

Author(s)

Logan C. Brooks, David C. Farrow, Sangwon Hyun, Ryan J. Tibshirani, Roni Rosenfeld

Examples

```
## National-level ILINet weighted %ILI data for recent seasons, excluding 2009 pandemic:
area.name = "nat"
full.dat = fetchEpidataFullDat("fluview", area.name, "wili",
                               min.points.in.season = 52L,
                               first.week.of.season = 31L,
                               cache.file.prefix=sprintf("fluview_%s_fetch", area.name))
full.dat <- full.dat[names(full.dat)!="S2009"]
## Sample from conditional curve distribution estimate using the above data
## and CDC's 2015 national %wILI onset threshold baseline of 2.1:
sim = twkde.sim(full.dat, baseline=2.1, max.n.sims=100)
print(sim)
plot(sim, type="lineplot")
```

| | |
|-----------------|---|
| unite_arraylike | <i>Reshape arraylike into fewer but larger dimensions and/or permute (and optionally rename) dimensions; like tidy::unite on arrays using R.utils::wrap.array</i> |
|-----------------|---|

Description

Collapses specified array(like) object dimensions together to produce an array with fewer but larger dimensions and an equal number of entries; indices of each collapsed dimension refers to a Cartesian product over the indices of the dimensions it was made from. This operation should be similar or equivalent to melting the array, calling `tidy::unite`, and casting back into an array.

Usage

```
unite_arraylike(arraylike, dnn.sets, sep = ".")
```

Arguments

| | |
|-----------|---|
| arraylike | the arraylike object to reshape; must have the <code>dimnames</code> names referred to in <code>{dnn.sets}</code> |
|-----------|---|

| | |
|----------|---|
| dnn.sets | a list of character vectors; each character vector specifies some dimensions to unite in the array; ordering within each vector determines the ordering of indices in the resulting collapsed dimension (as in <code>R.utils::wrap.array</code>); ordering between the vectors determines the ordering of the collapsed dimensions in the result; names of vector entries (e.g., <code>names(dnn.sets[[1]])</code>) are ignored; <code>names(dnn.sets)</code> , if specified and nonblank, override automatic names of the collapsed dimensions |
| sep | length-1 character vector; string used to combine dimnames for collapsed dimensions, as well as automatic dimnames names for collapsed dimensions |

Details

Collapsed/united dimensions are ordered after all untouched dimensions. To tweak the ordering or use this function to simply permute dimensions, individual dimnames names can be included as their own singleton "sets" in `dnn.sets`.

Examples

```
arraylike = array(1:2^5, rep(2,5))
dimnames(arraylike) <-
  list(A=c("a1","a2"), B=c("b1","b2"), C=c("c1","c2"),
       D=c("d1","d2"), E=c("e1","e2"))
)
## Collapsing A&B, C&D:
dimnames(unite_arraylike(arraylike, list(c("A","B"), c("C","D"))))
## Adjusting `sep` changes resulting dimnames and dimnames names:
dimnames(unite_arraylike(arraylike, list(c("A","B"), c("C","D")), sep="__"))
## Result dimnames names can be manually specified:
names(dimnames(unite_arraylike(arraylike, list(c("A","B"), DVD=c("C","D")), sep="__"))
## Singleton sets can be used to permute dimensions, optionally renaming
## them (changing the dimnames names):
##   Place dimension A at end:
names(dimnames(unite_arraylike(arraylike, list("A"))))
##   Permute all dims:
names(dimnames(unite_arraylike(arraylike, list("E","D","C","B","A"))))
##   Place some dimensions at end and rename one:
names(dimnames(unite_arraylike(arraylike, list("A","EEE"="E"))))
## Collapsing and permuting are actually the same operation and can be mixed:
names(dimnames(unite_arraylike(arraylike, list(c("C","D"),"A","EEE"="E"))))
```

upsample_sim

Resample a sim (if necessary) to get \geq min.n.sims simulated curves

Description

Resample a sim (if necessary) to get \geq min.n.sims simulated curves

Usage

```
upsample_sim(sim.obj, min.n.sims, inflate.weights)
```

Arguments

| | |
|-----------------|--|
| sim.obj | a sim object |
| inflate.weights | a single non-NA logical; TRUE indicated that the weights be inflated proportionally with the increase in the number of simulations; FALSE indicates that the total weight should be preserved instead. |
| max.n.sims | a single non-NA non-negative integer; the inclusive lower bound on the number of simulated curves in the result |

Details

Resampling is only performed if the number of simulations needs to change. Any resampling is (necessarily) done with replacement.

Value

a sim object with \geq min.n.sims simulated curves; the sum of weights in the result will equal the sum of the results in the input.

```
usa.flu.first.week.of.season
```

First epi week in weekly USA flu-related trajectories used by some methods

Description

First epi week in weekly USA flu-related trajectories used by some methods

Usage

```
usa.flu.first.week.of.season
```

Format

An object of class integer of length 1.

```
usa_flu_inseason_flags
```

Get logical marking in-season times in a USA flu-related trajectory

Description

Given that a trajectory starts with the epi week `usa.flu.first.week.of.season` and is `n.weeks.in.season` long, marks parts of the trajectory that are part of the USA flu "in-season" (epi week 40 of the first year of a season to epi week 20 of the following year)

Usage

```
usa_flu_inseason_flags(n.weeks.in.season)
```

Arguments

`n.weeks.in.season`

52L or 53L; the number of weeks in the first year of a season

Value

logical vector of length equal to `n.weeks.in.season`; entries are TRUE at times corresponding to weeks that are part of the in-season, and FALSE otherwise (i.e., in the off-season)

```
vector_as_named_array
```

Convert vector to 1-D array with non-NULL names & named dimnames

Description

Convert vector to 1-D array with non-NULL names & named dimnames

Usage

```
vector_as_named_array(vector, dimension.name = NULL,
  entry.names = NULL)
```

Arguments

`vector` the vector to convert

`dimension.name` length-1 character vector or NULL (default); if the former, then the `names(dimnames(output))[[1]]` will be this value; otherwise, `names(dimnames(output))[[1]]` will be set using nonstandard evaluation to grab the expression provided for the vector argument and convert it to a string @param `entry.names` character vector (expected to be of same length as `vector`) or NULL; if the former, the names of the output are set to this value; if the latter, the names of the output are set to a character

vector of the same length: vector itself if it is an unnamed character vector, or namesp(vector) otherwise.

| | | | | |
|------------------------|-----------------------|---------------|---------|----|
| vector_as_named_array_ | Standard-evaluation, | no-NULL-input | version | of |
| | vector_as_named_array | | | |

Description

Standard-evaluation, no-NULL-input version of vector_as_named_array

Usage

vector_as_named_array(vector, dimension.name, entry.names)

| | |
|-----------------|--|
| weekConventions | first.wday and owning.wday for some week numbering conventions |
|-----------------|--|

Description

Covers four common week numbering conventions:

- "epi": Epidemiological weeks or "epi weeks": weeks begin on Sunday, and are assigned to years based on what year the majority of days fall in (i.e., what year Wednesday falls in)
- "iso": ISO 8601 weeks: weeks begin on Monday, and are assigned to years based on what year the majority of days fall in (i.e., what year Thursday falls in)
- "usa": USA convention: weeks begin on Sunday, and are assigned to years based on what year Sunday falls in
- "uk": UK convention: weeks begin on Monday, and are assigned to years based on what year Monday falls in

Usage

weekConventions

Format

An object of class matrix with 2 rows and 4 columns.

Details

There are two rows, named "first.wday" and "owning.wday". There are four columns, corresponding to the four conventions above.

| | |
|-------------------|---|
| weighted_tabulate | <i>Weighted, more nbins-restrictive version of base::tabulate</i> |
|-------------------|---|

Description

Weighted, more nbins-restrictive version of base::tabulate

Usage

```
weighted_tabulate(bin, nbins, w)
```

Arguments

| | |
|-------|--|
| bin | integer-compatible vector; entries must be non-NA and between 1 and nbins; these indices denote entries in the result vector to which the corresponding weights in w should be added |
| nbins | single non-NA, non-negative integer; length of the vector to return |
| w | numeric-compatible vector of the same length as bin; weights corresponding to the indices in bin |

Value

numeric vector of length nbins; the *i*th entry is like `sum(w[bin==i])`, but with a naive summation algorithm

| | |
|---------------|--|
| with_dimnames | <i>Pipe-friendly, robust way of setting dimnames(object)</i> |
|---------------|--|

Description

Pipe-friendly, robust way of setting dimnames(object)

Usage

```
with_dimnames(arraylike, dimnames)
```

Examples

```
library("pipeR")
array(1:24, 2:4) %>%
  with_dimnames(list(c("a", "b"),
                    c("c", "d", "e"),
                    c("f", "g", "h", "i")))
## Two ways of setting named dimnames:
array(1:24, 2:4) %>%
  with_dimnames(list("First dimension"=c("a", "b"),
```

```

        "Second dimension"=c("c","d","e"),
        "Third dimension"=c("f","g","h","i"))
array(1:24, 2:4) %>%
  with_dimnames(list(c("a","b"),
                    c("c","d","e"),
                    c("f","g","h","i")) %>%
    with_dimnamesnames(c("First dimension", "Second dimension", "Third dimension"))
## Vectors are converted to arrays by with_dimnames:
(1:5) %>% with_dimnames(list(letters[1:5]))
(1:5) %>% with_dimnames(list("Only dimension" = letters[1:5]))

```

| | |
|--------------------|---|
| with_dimnamesnames | <i>Pipe-friendly, robust way of setting names(dimnames(object))</i> |
|--------------------|---|

Description

Pipe-friendly, robust way of setting names(dimnames(object))

Usage

```
with_dimnamesnames(arraylike, dimnamesnames)
```

Examples

```

library("pipeR")
array(1:24, 2:4) %>%
  with_dimnames(list(c("a","b"),
                    c("c","d","e"),
                    c("f","g","h","i")) %>%
    with_dimnamesnames(c("First dimension", "Second dimension", "Third dimension"))
## Edge case with null dimnames is handled:
array(1:24, 2:4) %>%
  with_dimnamesnames(c("First dimension", "Second dimension", "Third dimension"))
matrix(1:6, 2,3) %>%
  with_dimnamesnames(c("First dimension", "Second dimension"))
## Vectors are converted to arrays by with_dimnamesnames; the dimnames names
## are set properly whether or not the vector is already has names, but the
## print function will not show the dimnames names for the result if the
## vector was originally unnamed:
from.named.vector = c(a=1,b=2) %>% with_dimnamesnames("Only dimension")
class(from.named.vector) # "array"
print(from.named.vector) # shows dimnames names
names(dimnames(from.named.vector)) # "Only dimension"
from.unnamed.vector = c(1,2) %>% with_dimnamesnames("Only dimension")
class(from.unnamed.vector) # "array"
print(from.unnamed.vector) # doesn't show dimnames names
names(dimnames(from.unnamed.vector)) # "Only dimension"

```

yearWeekDFToSeasonModelWeekDF

Convert year-week in a data.frame to season-model.week

Description

Delegates to [yearWeekToSeasonModelWeekDF](#).

Usage

```
yearWeekDFToSeasonModelWeekDF(yearWeek, first.week, owning.wday)
```

Arguments

| | |
|-------------|--|
| yearWeek | data.frame (or other list) with columns \$year and \$week: \$year integer-valued vector: year from the year-week numbering \$week integer-valued vector: week from the year-week numbering |
| first.week | integer-valued vector: week number that the seasons start on |
| owning.wday | integer-valued vector of weekday numbers: weekday that determines the year to which a week will be assigned |

Value

data.frame with two columns giving the corresponding season-model.week breakdown:
\$season: integer-class vector: season numbers
\$model.week: integer-class vector: model week numbers

yearWeekToSeasonModelWeekDF

Convert year-week to season-model.week

Description

Seasons starting with a week number n other than 1 contain week numbers n to 52/53 from the season's first year and 1 to $n-1$ of the season's second year. Sometimes we would like a numbering of weeks within a season that coincides with the week number when possible, but does not have a jump down from 52/53 to 1. Model weeks fulfill this purpose: they begin with the starting week of a season and increase by 1 for each subsequent week; they coincide with week numbers in the starting year, and are 52/53 plus the week number in the second year.

Usage

```
yearWeekToSeasonModelWeekDF(year, week, first.week, owning.wday)
```

Arguments

| | |
|-------------|---|
| year | integer-valued vector: year from the year-week numbering |
| week | integer-valued vector: week from the year-week numbering |
| first.week | integer-valued vector: week number that the seasons start on |
| owning.wday | integer-valued vector of weekday numbers: weekday that determines the year to which a week will be assigned |

Value

a data frame (tbl_df) with two columns giving the corresponding season-model.week breakdown:
 \$season: integer-class vector: season numbers
 \$model.week: integer-class vector: model week numbers

| | |
|----------------------|--|
| yearWeekWdayDFToDate | <i>Convert a structure containing year, week, and weekday numbers into the corresponding dates under a specified week numbering convention. Reverses DateToYearWeekWdayDF.</i> |
|----------------------|--|

Description

Convert a structure containing year, week, and weekday numbers into the corresponding dates under a specified week numbering convention. Reverses [DateToYearWeekWdayDF](#).

Usage

```
yearWeekWdayDFToDate(ywwd, first.wday, owning.wday, error.on.wrap = TRUE)
```

Arguments

| | |
|---------------|---|
| ywwd | data frame with columns \$year, \$week, and \$wday containing the year, week, and weekday numbers respectively (weekday numbers are 0–7; Sunday can be inputted either as 0 or as 7) |
| first.wday | wday number corresponding to the first weekday of any week |
| owning.wday | wday number; a week is assigned to a given year if the owning weekday of that week falls in the given year |
| error.on.wrap | TRUE or FALSE: if TRUE, an error is generated if a given week falls outside the range of possible week numbers for the corresponding year (i.e., if it is nonpositive or greater than the number of weeks assigned to the corresponding year in year); if FALSE, the week number will wrap around to future or previous years (e.g., week 0 of 1997 will be considered the last week of 1996) |

Value

a Date vector: the dates corresponding to the year-week-wdays and week numbering convention

yearWeekWdayListsToDate

Like [yearWeekWdayDFToDate](#), but allows parameters to be provided in several (is.)list structures and vectors.

Description

Like [yearWeekWdayDFToDate](#), but allows parameters to be provided in several (is.)list structures and vectors.

Usage

```
yearWeekWdayListsToDate(...)
```

Arguments

... vectors and (is.)lists to feed to [yearWeekWdayVecsToDate](#); each entry in a list (e.g., column in a data.frame) is treated as a vector. Names can be provided by the names attribute of list arguments or optional parameter names for the vector arguments. (With no names, parameters of [yearWeekWdayVecsToDate](#) are matched sequentially.):

- year integer-valued vector: the year numbers
- week integer-valued vector: the week numbers
- wday integer-valued vector: the wday numbers (0–7, either 0 or 7 can be used for Sunday)
- first.wday wday number of the first day of each week
- owning.wday if the owning weekday of a week falls in a particular year, the entire week is assigned to that year
- error.on.wrap if TRUE, throws errors when week numbers do not fall in the specified years; when FALSE, wraps them around into other years

Value

the corresponding dates

yearWeekWdayVecsToDate

Like [yearWeekWdayDFToDate](#), but with each column of ywwd provided as separate parameters.

Description

Like [yearWeekWdayDFToDate](#), but with each column of ywwd provided as separate parameters.

Usage

```
yearWeekWdayVecsToDate(year, week, wday, first.wday, owning.wday,  
  error.on.wrap = TRUE)
```

Arguments

| | |
|----------------------------|---|
| <code>year</code> | integer-valued vector: the year numbers |
| <code>week</code> | integer-valued vector: the week numbers |
| <code>wday</code> | integer-valued vector: the wday numbers (0–7, either 0 or 7 can be used for Sunday) |
| <code>first.wday</code> | wday number of the first day of each week |
| <code>owning.wday</code> | if the owning weekday of a week falls in a particular year, the entire week is assigned to that year |
| <code>error.on.wrap</code> | if TRUE, throws errors when week numbers do not fall in the specified years; when FALSE, wraps them around into other years |

Value

the corresponding dates

Index

*Topic **datasets**

- firstEpiweekOfUniverse, 27
- usa.flu.first.week.of.season, 63
- weekConventions, 65

- as.Date, 14
- augmentWeeklyDF, 5

- br.sim, 5
- br.smoothedCurve, 5, 6, 6
- bw.SJnrð0, 7, 60

- c.sim, 8
- c.target_forecast, 8
- c.uniform_forecast, 9
- check.file.contents, 10
- check.list.format, 10
- check.table.format, 10
- cv.compare, 11
- cv.sim, 11
- cv.apply, 12

- dat.to.matrix, 13
- DatesOfSeason, 13
- DateToYearWeekWdayDF, 14, 69
- dimnames_or_inds, 15
- dimnamesnamesp, 15, 32
- dimnamesp, 16
- dimnamesp_to_dimindices, 17
- dimp, 17
- downsample_sim, 18
- dur, 19

- empirical.futures.sim, 19
- empirical.trajectories.sim, 20
- epi_week_to_model_week, 21
- epiweek_Seq, 22

- fetchEpidataDF, 22, 42
- fetchEpidataFullDat, 24
- fetchEpidataHistoryDF, 26, 43

- fetchUpdatingResource, 27
- firstEpiweekOfUniverse, 27

- get.latest.time, 28
- get_br_control_list, 28

- is_christmas, 29
- is_newyear, 30
- is_thanksgiving, 30

- lastWeekNumber, 31

- make_sim_ys_colors, 31
- map_join, 47
- map_join(map_join_), 32
- map_join_, 32
- match.arg.else.default, 33
- match.dat, 35
- match.integer, 36
- match.new.dat.sim, 37
- match.nonnegative.numeric, 38
- match.single.na.or.numeric, 38
- match.single.nonna.integer, 39
- match.single.nonna.integer.or.null, 39
- match.single.nonna.numeric, 40
- match.single.wday.w, 41
- match.wday.w, 41
- mimicPastDF, 42
- mimicPastEpidataDF, 26, 42
- model_week_to_epi_week, 44
- model_week_to_time, 44

- named_array_to_name_arrayvecs, 45
- named_arrayvec_to_name_arrayvec, 46
- namesp, 46
- ndimp, 32, 47
- no_join, 32, 47

- ons, 48

- pht, 48

`plot.sim`, 49
`plot.target_forecast`, 49
`print.sim`, 49
`print.target_forecast`, 50
`pwk`, 50

`read.from.file`, 51

`seasonModelWeekDFToYearWeekDF`, 51
`seasonModelWeekToYearWeekDF`, 52
`seasonModelWeekWdayDFToDate`, 53
`seasonModelWeekWdayToDate`, 53
`seasonOfDate`, 54
`seasonOfYearWeek`, 55
`Seq`, 22, 55
`show.sample.trajectories`, 56

`table.to.list`, 56
`target_forecast`, 57
`target_forecast.sim`, 57, 57
`time_to_model_week`, 58
`trimPartialPastSeasons`, 58
`twkde.markovian.sim`, 59
`twkde.sim`, 60

`unite_arraylike`, 61
`upsample_sim`, 62
`usa.flu.first.week.of.season`, 63, 64
`usa_flu_inseason_flags`, 64

`vector_as_named_array`, 64
`vector_as_named_array_`, 65

`weekConventions`, 65
`weighted_tabulate`, 66
`with_dimnames`, 66
`with_dimnamesnames`, 67

`yearWeekDFToSeasonModelWeekDF`, 51, 68
`yearWeekToSeasonModelWeekDF`, 52, 68, 68
`yearWeekWdayDFToDate`, 69, 70
`yearWeekWdayListsToDate`, 70
`yearWeekWdayVecsToDate`, 70, 70