


# Lecture Notes for **Machine Learning in Python**



Professor Eric Larson  
**Logistic Regression**

# Lecture Notes for **Machine Learning in Python**



## Professor Eric Larson **Optimization Techniques for Logistic Regression**

# Class Logistics and Agenda

- Logistic: grading!
- Agenda
  - Finish Logistic Regression
  - Numerical Optimization Techniques
    - Types of Optimization
    - Programming the Optimization
- **Whirlwind Lecture Alert**
  - Get an intuition, program it, maybe you don't follow every mathematical concept in lecture
  - But you know how to approach it outside lecture

# Class Overview, by topic

Table Data  
Visualization

Numpy, Pandas, Seaborn  
Overviews with some in-depth discussion

Dimension  
Reduction and  
Image Processing

Scikit-learn, Scikit Image,  
Intuition only, Some mathematics

Linear and  
Logistic  
Regression

Numpy, Recreate API for Scikit-learn  
Detailed mathematics for simple optimization  
***intuition for advanced optimization***

Neural Networks  
and Back Prop.

Numpy  
Detailed mathematics for NN operations

Wide and Deep  
Networks

Convolutional  
Networks

Recurrent  
Networks

Keras, Tensorflow  
Intuition, Detailed implement.

Ethics in  
Language Models

ConceptNet  
Case studies

# Review

$$\underbrace{w_j}_{\text{new value}} \leftarrow \underbrace{w_j}_{\text{old value}} + \underbrace{\frac{\eta}{M} \sum_{i=1}^M (y^{(i)} - g(\mathbf{w}^T \mathbf{x}^{(i)})) x_j^{(i)}}_{\text{gradient}}$$

now  $\mathbf{x}$ ,  $\mathbf{w}$  are vectors

$$\underbrace{\mathbf{w}}_{\text{new vect}} \leftarrow \underbrace{\mathbf{w}}_{\text{old vect}} + \frac{\eta}{M} \sum_{i=1}^M (y^{(i)} - g(\mathbf{w}^T \mathbf{x}^{(i)})) \cdot \mathbf{x}^{(i)}$$

$$\mathbf{w} \leftarrow \mathbf{w} + \eta \cdot \text{mean}(\mathbf{y}_{diff} \odot \mathbf{X})_{columns}$$

$$\mathbf{y}_{diff} = \begin{bmatrix} y^{(1)} - g(\mathbf{w}^T \mathbf{x}^{(1)}) \\ y^{(2)} - g(\mathbf{w}^T \mathbf{x}^{(2)}) \\ \vdots \\ y^{(M)} - g(\mathbf{w}^T \mathbf{x}^{(M)}) \end{bmatrix} = \begin{bmatrix} y_{diff}^{(1)} \\ y_{diff}^{(2)} \\ \vdots \\ y_{diff}^{(M)} \end{bmatrix}$$

$$\mathbf{w} \leftarrow \mathbf{w} + \eta \cdot \text{mean} \left( \begin{bmatrix} y_{diff}^{(1)} \\ y_{diff}^{(2)} \\ \vdots \\ y_{diff}^{(M)} \end{bmatrix} \odot \begin{bmatrix} \leftarrow \mathbf{x}^{(1)} \rightarrow \\ \leftarrow \mathbf{x}^{(2)} \rightarrow \\ \vdots \\ \leftarrow \mathbf{x}^{(M)} \rightarrow \end{bmatrix} \right)_{columns}$$

$$\mathbf{w} \leftarrow \mathbf{w} + \eta \cdot \text{mean} \left( \begin{bmatrix} (\leftarrow \mathbf{x}^{(1)} \rightarrow) \cdot y_{diff}^{(1)} \\ (\leftarrow \mathbf{x}^{(2)} \rightarrow) \cdot y_{diff}^{(2)} \\ \vdots \\ (\leftarrow \mathbf{x}^{(M)} \rightarrow) \cdot y_{diff}^{(M)} \end{bmatrix} \right)_{columns}$$

## 05. Logistic Regression.ipynb

### **“Finish”**

Programming

Vectorization

Regularization

Multi-class extension



### **Other Tutorials:**

<http://blog.yhat.com/posts/logistic-regression-python-rodeo.html>

[http://scikit-learn.org/stable/auto\\_examples/linear\\_model/plot\\_iris\\_logistic.html](http://scikit-learn.org/stable/auto_examples/linear_model/plot_iris_logistic.html)

# Demo Lecture

## 06. Optimization



# Scratch Paper



# Back Up Slides

# Last time

$$p(y^{(i)} = 1 \mid x^{(i)}, w) = \frac{1}{1 + \exp(w^T x^{(i)})}$$


$$l(w) = \sum_i (y^{(i)} \ln[g(w^T x^{(i)})] + (1 - y^{(i)}) (\ln[1 - g(w^T x^{(i)})]))$$

$$\underbrace{w_j}_{\text{new value}} \leftarrow \underbrace{w_j}_{\text{old value}} + \underbrace{\eta \sum_{i=1}^M (y^{(i)} - g(x^{(i)})) x_j^{(i)}}_{\text{gradient}}$$

$$w \leftarrow w + \eta \sum_{i=1}^M (y^{(i)} - g(x^{(i)})) x^{(i)}$$

$$w \leftarrow w + \eta \left[ \underbrace{\nabla l(w)_{\text{old}}}_{\text{old gradient}} - C \cdot 2w \right]$$

```
def _get_gradient(self, X, y):  
    # programming \sum_i (yi - g(xi)) xi  
    gradient = np.zeros(self.w_.shape) # set  
    for (xi, yi) in zip(X, y):  
        # the actual update inside of sum  
        gradi = (yi - self.predict_proba(xi,  
        # reshape to be column vector and add  
        gradient += gradi.reshape(self.w_.sh  
  
    return gradient/float(len(y))
```




# Optimization: gradient descent

- What we know thus far:

$$\underbrace{w_j}_{\text{new value}} \leftarrow \underbrace{w_j}_{\text{old value}} + \underbrace{\eta \left[ \left( \sum_{i=1}^M (y^{(i)} - g(x^{(i)})) x_j^{(i)} \right) - C \cdot 2w_j \right]}_{\nabla l(w)}$$

$$w \leftarrow w + \eta \nabla l(w)$$




# Line Search: a better method

- Line search in direction of gradient:

$$w \leftarrow w + \eta \nabla l(w)$$

$$w \leftarrow w + \underbrace{\eta}_{\text{best step?}} \nabla l(w)$$



# Revisiting the Gradient

- How much computation is required (for gradient)?

$$\sum_{i=1}^M (y^{(i)} - \hat{y}^{(i)})x^{(i)} - 2C \cdot w$$

M = number of instances

N = number of features

**Self Test: How many multiplies  
per gradient calculation?**

- A.  $M \cdot N + 1$  multiplications
- B.  $(M + 1) \cdot N$  multiplications
- C.  $2N$  multiplications
- D.  $2N - M$  multiplications

# Stochastic Methods

- How much computation is required (for gradient)?

$$\sum_{i=1}^M (y^{(i)} - \hat{y}^{(i)})x^{(i)} - 2C \cdot w$$

**Per iteration:**


(M+1)\*N multiplications  
2M add/subtract

$$w \leftarrow w + \underbrace{\eta \left( (y^{(i)} - \hat{y}^{(i)})x^{(i)} - 2C \cdot w \right)}_{\text{approx. gradient}},$$

$i$  chosen at random

**Per iteration:**

N+1 multiplications  
1 add/subtract



Gradient Descent (with line search)

Stochastic Gradient Descent

Hessian

Quasi-Newton Methods

Multi-processing






# For Next Lecture

- ▣ **Next time:** SVMs via in class assignment
- ▣ **Next Next time:** Neural Networks



# Can we do better than the gradient?

- Assume function is quadratic:



function of one variable:

$$w \leftarrow w - \underbrace{\left[ \frac{\partial^2}{\partial w} l(w) \right]^{-1}}_{\text{inverse 2nd deriv}} \underbrace{\frac{\partial}{\partial w} l(w)}_{\text{derivative}}$$

will solve in one step!

what is the second order derivative  
for a multivariate function?

$$\nabla^2 l(w) = \mathbf{H}[l(w)]$$

# The Hessian

- Assume function is quadratic:

function of one variable:

$$\mathbf{H}[l(w)] = \begin{bmatrix} \frac{\partial^2}{\partial w_1} l(w) & \frac{\partial}{\partial w_1} \frac{\partial}{\partial w_2} l(w) & \dots & \frac{\partial}{\partial w_1} \frac{\partial}{\partial w_N} l(w) \\ \frac{\partial}{\partial w_2} \frac{\partial}{\partial w_1} l(w) & \frac{\partial^2}{\partial w_2} l(w) & \dots & \frac{\partial}{\partial w_2} \frac{\partial}{\partial w_N} l(w) \\ \vdots & \vdots & \ddots & \vdots \\ \frac{\partial}{\partial w_N} \frac{\partial}{\partial w_1} l(w) & \frac{\partial}{\partial w_N} \frac{\partial}{\partial w_2} l(w) & \dots & \frac{\partial^2}{\partial w_N} l(w) \end{bmatrix}$$




$$\nabla^2 l(w) = \mathbf{H}[l(w)]$$

# The Newton Update Method

- Assume function is quadratic (in high dimensions):


$$w \leftarrow w - \underbrace{\left[ \frac{\partial^2}{\partial w} l(w) \right]^{-1}}_{\text{inverse 2nd deriv}} \underbrace{\frac{\partial}{\partial w} l(w)}_{\text{derivative}}$$

$$w \leftarrow w + \eta \cdot \underbrace{\mathbf{H}[l(w)]^{-1}}_{\text{inverse Hessian}} \cdot \underbrace{\nabla l(w)}_{\text{gradient}}$$



*Is. Newton*

I do not know what I may appear to the world, but to myself I seem to have been only like a boy playing on the sea-shore, and diverting myself in now and then finding a smoother pebble or a prettier shell than ordinary, whilst the great ocean of truth lay all undiscovered before me.



I do not know what I may appear to the world, but to myself I seem to have been only like a boy playing on the sea-shore, and diverting myself in now and then finding a smoother pebble or a prettier shell than ordinary, whilst the great ocean of truth lay all undiscovered before me.

*Is. Newton*

$$\frac{\partial}{\partial w_j} l(w) = \sum_i (y^{(i)} - g(x^{(i)})) x_j^{(i)}$$

↓ PLUG IN

$$H[k,j] = \frac{\partial}{\partial w_k} \frac{\partial}{\partial w_j} l = \frac{\partial}{\partial w_k} \left( \sum_i (y^{(i)} - g(x^{(i)})) x_j^{(i)} \right)$$

$$= \sum_i \frac{\partial}{\partial w_k} y^{(i)} x_j^{(i)} - \frac{\partial}{\partial w_k} g(x^{(i)}) x_j^{(i)}$$

← LEFT OVER TERM

$$= - \sum_i \frac{\partial}{\partial w_k} g(x^{(i)}) x_j^{(i)}$$

Already know  $\frac{\partial}{\partial w_k} g(w^T x^{(i)})$  side calculation

$$= g(x^{(i)}) (1 - g(x^{(i)})) \frac{\partial}{\partial w_k} (w^T x^{(i)})$$

$$= g(x^{(i)}) (1 - g(x^{(i)})) x_k^{(i)}$$

← PLUG IN

$$\therefore = - \sum_i g(x^{(i)}) (1 - g(x^{(i)})) x_k^{(i)} x_j^{(i)}$$

← THAT'S THE HESSIAN!

$$H(k,j) =$$

This is a valid equation for the Hessian, but we want to represent it using linear algebra

$$= - \sum_i g(x^{(i)}) (1 - g(x^{(i)})) x_k^{(i)} x_j^{(i)}$$

↑ SIGMOID

3D LINEAR ALG

# The Hessian for Logistic Regression

- The hessian is easy to calculate from the gradient for logistic regression

$$w \leftarrow w + \eta \cdot \underbrace{\mathbf{H}[l(w)]^{-1}}_{\text{inverse Hessian}} \cdot \underbrace{\nabla l(w)}_{\text{gradient}}$$

$$\mathbf{H}_{j,k}[l(w)] = - \sum_{i=1}^M g(x^{(i)})(1 - g(x^{(i)})) x_k^{(i)} x_j^{(i)}$$

$$\underbrace{\sum_{i=1}^M (y^{(i)} - \hat{y}^{(i)}) x_j^{(i)}}_{\text{gradient}}$$

$$\mathbf{H}[l(w)] = X^T \cdot \text{diag}[g(x^{(i)})(1 - g(x^{(i)}))] \cdot X$$

$$X * y_{diff}$$

$$w \leftarrow w + \eta [X^T \cdot \text{diag}[g(x^{(i)})(1 - g(x^{(i)}))] \cdot X]^{-1} \cdot X * y_{diff}$$



Newton's method



# Problems with Newton's Method

- **Quadratic** isn't always a great assumption:
  - ▣ highly dependent on starting point
    - ▣ jumps can get **really random!**
  - ▣ near saddle points, inverse hessian **unstable**
  - ▣ hessian **not** always **invertible**...
    - ▣ or invertible with correct numerical precision

# The solution: quasi Newton methods

- In general:
  - ▣ **approximate** the **Hessian** with something numerically sound and efficiently invertible
  - ▣ **back off to gradient** descent when the approximate hessian is **not stable**
  - ▣ use **momentum** to update approximate hessian
- ▣ **A popular approach:** use Broyden-Fletcher-Goldfarb-Shanno (BFGS)
  - ▣ which you can look up if you are interested ...

[https://en.wikipedia.org/wiki/Broyden-Fletcher-Goldfarb-Shanno\\_algorithm](https://en.wikipedia.org/wiki/Broyden-Fletcher-Goldfarb-Shanno_algorithm)

# BFGS

$$\mathbf{H}_0 = \mathbf{I} \quad \text{init}$$

$$p_k = -\mathbf{H}_k^{-1} \nabla l(w_k) \quad \text{get update direction}$$

$$\text{find next } w \quad w_{k+1} \leftarrow w_k + \eta \cdot p_k$$

$$\text{get scaled direction} \quad s_k = \eta \cdot p_k$$

$$v_k = \nabla l(w_{k+1}) - \nabla l(w_k) \quad \text{approx gradient change}$$

$$\mathbf{H}_{k+1} = \mathbf{H}_k + \underbrace{\frac{v_k v_k^T}{v_k^T s_k}}_{\text{approx. Hessian}} - \underbrace{\frac{\mathbf{H}_k s_k s_k^T \mathbf{H}_k}{s_k^T \mathbf{H}_k s_k}}_{\text{momentum}} \quad \text{update Hessian and inverse Hessian approx}$$

$$\mathbf{H}_{k+1}^{-1} = \mathbf{H}_k^{-1} + \frac{(s_k^T v_k + \mathbf{H}_k^{-1})(s_k s_k^T)}{(s_k^T v_k)^2} - \frac{\mathbf{H}_k^{-1} v_k s_k^T + s_k v_k^T \mathbf{H}_k^{-1}}{s_k^T v_k}$$

$$k = k + 1 \quad \text{increment } k \text{ and repeat}$$

invertibility of  $\mathbf{H}$  well defined / only matrix operations

BFGS (if time)  
parallelization

