

# Model Repair and Conformance Checking of Time-Aware Models

Shubh Sharma<sup>1,2</sup>, and Thomas Chatain<sup>2</sup>

<sup>1</sup>Chennai Mathematical Institute, <sup>2</sup>LSV, ENS Paris-Saclay

---

## Abstract

The subject of this paper is to implement model repair for timed models, that is, process models that consider both the sequence of events in a process as well as the timestamps at which each event is recorded. Time aware process mining is a growing subfield of research, and as tools that seek to discover timing related properties in the process develop, so does the need for conformance checking techniques that give insightful quality measure, for the purpose of this paper, we use alignments as witness for the model being unfit, we then give algorithms improving the models

---

**Keywords** Time Petri Nets, Model Repair, Conformance Checking

## 1. Introduction

### 1.a. Process Mining and Model Repair

*Process Mining* is a family of techniques used to analyze event data in order to understand and improve the system. It studies the system through their event logs and seeks to extract meaningful ways to model the underlying process to understand the system better or to predict its future behaviour (Aalst, 2016).

The first step: *discovery*, in process mining is the discovery of a model one expects to model the system through techniques like machine learning. But the unexplainability of the approaches that ML takes naturally makes one question if the produced model approximates the target system well enough.

This is where *Conformance Checking* comes in. Conformance Checking is a set of techniques used to compare a *process model* with an event log and rate it over some parameters like:

- **Fitness** : Does the model exhibit the behaviours specified in the logs?
- **Precision** : Does the model deviate a lot from the behavior specified in the logs?
- **Generalization** : Does the model correctly predict behavior of the system outside the given logs?
- **Simplicity** : Is the model the simplest model that describes the log accurately?

Once we measure how well the model conforms to the given set of logs, we move to the next step that is *enhancement*: where an existing process model is extended or improved using information about the actual process record in some event log.

Another important part of Process Mining is Performance Analysis where the goal is to analyze and improve the execution of the model to use less time and resources and improve its performance data.

*Model Repair* is a special case of **Enhancement** that deals with improving the model to more accurately fit any discrepancies due to events in the system that happen after the model has been constructed. The improvement metrics are usually one of the 4 mentioned above, this paper focuses on the fitness of the model.

### 1.b. Time Aware Models

Process Models are represented by formal objects. Petri-Nets offer a graphical means to represent concurrent systems and a formal semantics for their execution. The setup is similar to the one in (Chatain & Rino, 2022) where an event is represented by a letter from a finite alphabet (a set of possible discrete events). Logs are represented by the set of timed words over the alphabet, which is a list of events along with the timestamps on which the event occurred. The notion of distance between words, which will give our conformance metric, will be similar to the Levenshtein's edit distance where we find the quickest way to go from one timed-word to another using a given set of edit actions.

We will be using Time Petri Nets, which are a variant of Petri Nets that can check the duration it takes to fire a transition once it's enabled, restricting the set of timed-words it accepts, this can be used to construct relationships and constraints between events and the timestamps at which they can be taken as seen in the logs.

## 2. Preliminaries

### 2.a. Time Petri Nets

We represent an event as pairs  $(a, t)$  where  $a \in \Sigma$  is the action and  $t$  denotes the time at which the action was taken.

**Definition 1:** A *timed trace* is a sequence  $\gamma \in (\Sigma \times \mathbb{R}^+)^*$  of timed events, seen as a timed word.

We will often ignore the untimed part of the word, i.e. project it on to the time component leaving a word in  $(\mathbb{R}^+)^*$ .

The Process Model we use here is a Time Petri Net.

**Definition 2:** A *Labelled Timed Petri Net* (or TPN) is a tuple  $\mathcal{N} = \langle P, T, F, SI, \Sigma, \lambda, M_0, M_f \rangle$  where

- $P$  and  $T$  are disjoint sets of places and transitions respectively.
- $F \subseteq (P \times T) \cup (T \times P)$  is the flow relation.
- $SI : T \rightarrow \mathbb{I}$  is the static interval function,  $SI(t) = (st(t), en(t))$  where
  - $st(t)$  is the smallest valid time interval from the enabling of  $t$  to its firing.
  - $en(t)$  is the largest valid time interval from the enabling of  $t$  to its firing.
- $\lambda : T \rightarrow \Sigma$  is a labelling function for the transition with actions from the action set  $\Sigma$
- $M_0$  and  $M_f : P \rightarrow \mathbb{N}$  are the initial and final markings.

Given a transition  $t \in T$  we define

- The Pre-set of  $t$  from as  $\bullet t = \{p \in P \mid (p, t) \in F\}$
- The Post-set as  $t^\bullet = \{p \in P \mid (t, p) \in F\}$  (we define pre-set and post-set if places similarly).
- We say that a transition  $t$  is enabled at a marking  $M$  if  $\forall p \in \bullet t, M(p) > 0$
- The set of all enabled transitions in  $M$  is given by  $Enabled(M) = \{t \in T \mid t \text{ is enabled in } M\}$ .

**Definition 3:** The *state* (or *configuration*) of a TPN  $\mathcal{N} = \langle P, T, F, SI, \Sigma, \lambda, M_0, M_f \rangle$  is a pair  $S = (M, I)$  where  $M$  is a marking and  $I : \text{Enabled}(M) \rightarrow \mathbb{R}^+$  is the clock function keeping track of the time since each transition was enabled. We set the initial state to be  $(M_0, \mathbf{0})$  where  $\mathbf{0}$  is the zero-function.

A transition  $t$  is said to be **fireable** after a delay  $\theta$  from a state  $S = (M, I)$  if  $t$  is enabled in  $M$  and  $I(t) + \theta \in SI(t)$

The update to the marking and time function are defined below:

**Definition 4: (Firing Rule)** When a transition  $t$  fires after a delay  $\theta$  from state  $S = (M, I)$ , the new state  $S' = (M', I')$  is given as follows:


$$M' = (M \setminus \bullet t) \cup t \bullet$$

$$I'(t) = \begin{cases} I(t) + \theta & \text{If } t \in \text{Enabled}(M') \\ 0 & \text{If } t \in \text{Enabled}(M') \text{ and } t \notin \text{Enabled}(M) \\ \text{Undefined} & \text{Otherwise} \end{cases}$$

This is also denoted as  $S[t]S'$

A valid execution of the model starts at the initial marking  $M_0$ , fires a sequence of transitions and ends at the final marking  $M_f$ .

**Example 1:** Consider the following example of a Time Petri Net  $N$ :



One possible execution of  $N$  would be for the firing sequence

$$w = (a, 1)(b, 2)(d, 3)(e, 4)(f, 5)$$

The initial marking only has  $a$  enabled and firing  $a$  moves the token to places that enable  $b, c, d$  and  $e$ . Then transition  $b$  at time 2 is fired, which puts a token in one of the places consumed by transition  $f$ . at time 3,  $d$  is fired followed by  $e$  at 4 and now  $f$  is enabled and is fired after a second of wait.

Now we can define the language of the Time Petri Net as follows

**Definition 5:** A word  $w = a_0 a_1 \dots a_n \in \Sigma^*$  is in the *language of the Labelled Time Petri Net*  $\mathcal{L}(\mathcal{N})$  if there is a fireable sequence of transitions  $(t_0, t_1 \dots t_n)$  such that  $\lambda(t_0, t_1 \dots t_n) = w$  and if the sequence of transitions is taken from the initial state  $M_0$ , it will end at the final transition  $M_f$ .

$$(M_0, \mathbf{0})[t_0 t_1 \dots t_n](M_f, I)$$

## 2.b. Helper Definitions

To help with defining some of the things that will be used further, we will use **causal nets** which are like unfoldings of a Petri Net that will make definitions and procedures about walking through the Petri Net easier.

**Definition 6:** A *Causal Net*  $CN := \langle B, E, G \rangle$  is a finitary, acyclic net where

$$\forall b \in B : |b^\bullet| \leq 1 \wedge |\bullet b| \leq 1$$

This definition reads as “A Petri net where each place has at most 1 in-transition and at most 1 out-transition”. We can also think of this as taking the original petri net and everytime we see a state with multiple out-transitions we copy the state and the net constructed till now once for each transition, we do the same for out-transitions.

Once we construct a Causal Net for a Petri Net we need to connect the execution of the Causal Net with that of the Petri Net. This will be done using a homomorphism.

**Definition 7:** A mapping  $p : B \cup E \rightarrow P \cup T$  is a *homomorphism* if:

- $\forall e \in E, p(e^\bullet) = p(e)^\bullet$
- $\forall e \in E, p(\bullet e) = \bullet p(e)$
- $M_{0(\text{causal net})} = p(M_{0(\text{Petri net})})$

We will use a Causal Net and a homomorphism together as

**Definition 8:** A *Causal Process* of a Time Petri Net  $\mathcal{N}$  is a pair  $(CN, p)$  where  $CN$  is a causal net and  $p$  is a homomorphism from  $CN$  to  $\mathcal{N}$ .

Using  $p$ , the elements of  $CN$  are identified with their corresponding elements in  $\mathcal{N}$ . As a result, any run in the Causal Process corresponds uniquely to an untimed run in a Timed Petri Net. To also associate time stamps with our Causal Process we define

**Definition 9:** A *Timing Function*  $\tau : E \rightarrow \mathbb{R}^+$  is a function from events of a causal process into time values.

## 2.c. Conformance Metric

Conformance Checking tries to measure how well a process model mimics the system, some of the metrics used for that are defined below.

**Definition 10:** Given a process model  $\mathcal{N}$  and a log  $L$  we define the *fitness* of  $\mathcal{N}$  with respect to  $L$  as

$$\text{fitness}(\mathcal{N}, L) = 1 - \max_{\sigma \in L} \text{dist}^*(\sigma, \mathcal{L}(\mathcal{N}))$$

Here  $\text{dist}^*$  is some normalized distance between traces, some options are defined later.

The fitness of the model is high if all of the observed behaviors in the logs are closely captured by the model.

**Definition 11:** Given a process model  $\mathcal{N}$  and a log  $L$  we define the *precision* of  $\mathcal{N}$  with respect to  $L$  as

$$\text{precision}(\mathcal{N}, L) = 1 - \max_{w \in \mathcal{L}(\mathcal{N})} \text{dist}^*(L, w)$$

We have that the precision of the model is high if it does not exhibit behavior that deviates too much from the observed logs.

### 3. Conformance Checking and Model Repair in Timed Setting

The Problem of Model Repair is, given an event log, a process model and some budget, compute the edits that can be made to the model under the budget to improve the conformance of the model to the system by some metric. If we let a Time Petri Net be our process model and fitness be our conformance metric then the problem can be stated as :

#### Model Repair of Time Petri Net (General)

Given a process  $\mathcal{N}$  denoted by a Time Petri Net, a log  $L$  and a budget  $\beta$ , we wish to find an edit of the  $\mathcal{N} \rightarrow \mathcal{N}'$  that can be implemented under the given budget constraint and optimally increases the fitness.

The two ways in which the model can be imperfect fitness is to have traces in the log such that

- $\text{Untime}(L) \not\subseteq \text{Untime}(\mathcal{L}(\mathcal{N}))$ , i.e there are traces where the sequence of events is not captured by  $\mathcal{N}$
- There exists a trace whose untimed version is in the language, but the timestamps do not match with any word in the language of  $\mathcal{N}$

**Example 2:** Consider the Process Model in [Example 1](#) and consider the the following observed traces.

- $\sigma_1 = (a, 0)(a, 1)(b, 2)(d, 3), (e, 3)(f, 5)$ 
  - Clearly, there is no trace in the process model that has more than 1  $a$ , which means the structure of the model itself needs to be updated by adding/removing states and transitions.
- $\sigma_2 = (a, 1)(b, 1)(d, 3)(e, 4)(f, 5)$ 
  - The sequence of transitions in  $\sigma_2$  can happen in the model but for transition  $b$  we need to wait for at least 1 unit. Changing the timestamp for that transition to 2 gives a trace that has a run in the petri net.
- $\sigma_3 = (a, 1)(d, 1)(d, 2)(e, 4)(f, 5)$ 
  - This trace is also not possible in the model as transition  $b$  or  $c$  must be fired to enable transition  $f$ . This can be fixed by relabelling transition  $b$  or  $c$ .

In the untimed setting, this problem is viewed as minimizing cost over a series of edit moves which are either insertions or deletions to the model. For the timed case there are two aspects that need to be improved, which are mentioned above. This problem has been studied for the untimed case, but the timed settings is more complex.

Also, in practice, a large set of malfunctionings can be modeled as temporal anomalies (a slowing down of a conveyor belt speed due to wear, a shorter duration of a work phase due to an incorrect handling of the operator, a causal change in a timer duration, etc.) and the problem is a pre-requisite for the general case of dealing with all kinds of errors. In this paper we will be focusing on the purely timed version of the model repair problem. i.e where the only anomalies that are fixed are temporal ones (All traces that are not in the language of the model will have an issue similar to  $\sigma_2$  in [Example 2](#))

#### Model Repair of Time Petri Nets (Purely Timed)

Given a process  $\mathcal{N}$  denoted by a Time Petri Net, a log  $L$  and a budget  $\beta$ , we wish to find an edit of the  $\mathcal{N} \rightarrow \mathcal{N}'$  that can be implemented under the given budget constraint and optimally increases the fitness. We also have the constraint that  $\forall \sigma \in L, \text{UnTime}(\sigma)$  gives a valid causal process for  $\mathcal{N}$ .

To properly formalize the problem we need definitions for editing out petri net and conformance for which we need to define out distance functions.

#### 3.a. Edits and Distances

Our notion of distance is similar to that of Levenstein's edit distance where we are given a set of edit actions and we try to go from one trace to another in the shortest way, representing in some sense how different 2 traces are, there are 2 options that are considered usually

**Definition 12: (Stamp Edit)** Given a timing function  $\gamma : E \rightarrow \mathbb{R}^+$ , we define the a stamp move as:

$$\forall x \in \mathbb{R}, e \in E : \text{stamp}(x, e)(\gamma) = \gamma' \text{ where}$$

$$\forall e' \in E : \gamma'(e) = \begin{cases} \gamma(e') + x & e' = e \\ \gamma(e') & \text{otherwise} \end{cases}$$

i.e we edit the timestamp at which a particular transition ( $e$ ) was taken by  $x$ . These edits only affect a single transition, and can represent a reading error in the model which needs to be corrected without affecting the other timestamps.

Another natural edit move to consider is :

**Definition 13: (Delay Edit)** Given a timing function  $\gamma : E \rightarrow \mathbb{R}^+$ , we define the a delay move as:

$$\forall x \in \mathbb{R}, e \in E : \text{stamp}(x, e)(\gamma) = \gamma' \text{ where}$$

$$\forall e' \in E : \gamma'(e) = \begin{cases} \gamma(e') + x & e' \geq_G e \\ \gamma(e') & \text{otherwise} \end{cases}$$

Here the relation  $\geq_G$  can be thought of as a causal one, i.e if  $e$  must happen for  $e'$  to happen then  $e \leq_G e'$ .

Intuitively, this edit represents a change in the duration one waits before taking a transition, this is why timestamps of all subsequent transitions are also changed by the same amount.

Using these 2 distance we can define our notion of distance. We assign a cost to each edit move say for both delay and stamp edits we say that the cost of an edit is the same as the change  $x$ , using that we can define the following 3 definitions:

**Definition 14:** (*Stamp Only Distance  $d_t$* ) Given any two timing functions  $\tau_1, \tau_2$  over the same causal process  $(CN, p)$ , we define the stamp distance as

$$d_t(\tau_1, \tau_2) = \min\{\text{cost}(m) \mid m \in \text{Stamp}^*, m(\tau_1) = \tau_2\}$$

**Definition 15:** (*Delay Only Distance  $d_\theta$* ) Given any two timing functions  $\tau_1, \tau_2$  over the same causal process  $(CN, p)$ , we define the stamp distance as

$$d_\theta(\tau_1, \tau_2) = \min\{\text{cost}(m) \mid m \in \text{Delay}^*, m(\tau_1) = \tau_2\}$$

**Definition 16:** (*Mixed Moves Distance  $d_N$* ) Given any two timing functions  $\tau_1, \tau_2$  over the same causal process  $(CN, p)$ , we define the stamp distance as

$$d_N(\tau_1, \tau_2) = \min\{\text{cost}(m) \mid m \in (\text{Stamp} \cup \text{Delay})^*, m(\tau_1) = \tau_2\}$$

## 4. Results


### 4.a. Sequential Petri Nets and Delay-Only Distance

We first focus our attention to a restricted version of problem where:

- The model in question will be a **Sequential Time Petri Net**, which means that, there is a dedicated start state and a dedicated end state, and each transition, connects one state, to one other state in a way that the underlying graph looks like a line graph, which the start and end states acting as the two ends of the graph.
- The problem is restricted to a **Purely Timed Problem**, which means that the sequence of transitions represent the sequence of events in the system correctly, but the timestamps might not be accurate.
- The metric for measure which will be used is going to be **Delay-Only Distance** (Definition 15)
- For the edits to the model, we cost  $x$  unit of the budget whenever any bound of a time range of a transition is changed by  $x$ .
- The conformance metric used is *fitness* but here we define it as  $-(\max_{\sigma \in L} \text{dist}_\theta(\sigma, \mathcal{L}(\mathcal{N})))$  which can be easily converted to the normalized distance used in the original definition.
- Another thing to note is that a Sequential Petri Net is isomorphic to its Causal Net, hence we will not make a distinction between the two here.

**Example 3:** We start with a simple example and informally go over the procedure

Consider the following Time Petri Net  $\mathcal{N}$



We are also given the following log

$$L = \left\{ \begin{array}{l} [(a, 1) (b, 5) (c, 9)], \\ [(a, 0) (b, 5) (c, 7)] \end{array} \right\}$$

And we are given the budget  $\beta = 2$ .

Our goal is to edit the model by making a change of at most  $\beta = 2$  to the boundaries of the transitions in order to minimize the distance of the logs from the model. The Procedure will go as follows:


- The transitions only keep track of the delay that is done to trigger them, so it will be easier to look at traces with wait times before the previous transitions rather than the next one, so we construct the following

$$F = \left\{ \begin{array}{l} [(a, 1) (b, 4) (c, 4)], \\ [(a, 0) (b, 5) (c, 2)] \end{array} \right\}$$

And now it is easier to see that neither of the traces have a corresponding run in  $N$ , also, the distance of each transition is now easy to compute, for both the transitions it's 3. So the fitness is  $-3$  and we need to reduce the distance of the model from each of the traces to improve the fitness of  $N$ .


Trace 1 takes transition  $b$  and  $c$  too late, where as Trace 2 takes transition  $b$  late and takes transition  $a$  too early. This means that increasing the upper bound of transition  $b$  reduce the distance of both traces, and hence will be optimal, so we spend our budget on  $b$ .

After spending 1 unit of budget though the model changes to



And now trace 1 takes the transition  $b$  at the correct time. If we continue to spend out budget entirely on  $b$  then we will not reduce the distance of trace 1 from the model anymore and hence will not change the fitness of the model.

So we need to rethink our distribution of the budget. We need to reduce the distance of both the traces from the model, hence we need to spend budget in a way that improves fitness. One way to do it optimally would be to split our leftover budget evenly between transition  $b$  and  $c$ . And finally ending with the following model.



Now we can stop as we have consumed all our budget and the distance of each trace from the model is 1.5.

Note that this is not the only optimal solution, reducing the lower bound of transition  $a$  instead of increasing the upper bound  $b$  in step to also leads to the same improvement in fitness.



#### 4.a.i. Reduction to simpler cases:

Note that the only 2 kinds of edits one would want to make to the petri net are:

- increasing the upper bound of a transition
- decreasing a lower bound of a transition

This is because these are precisely the edits that would increase the size of the language of the petri net, and other edits make the language of the petri-net strictly smaller.

We now try to reduce the petri-net in a way that we would only have to deal with 1 type of edit.

We restrict the input set of petri nets to those which in which the static interval function is the constant function  $x \mapsto [0, 0]$ .

Given a Sequential Time Petri-net  $\mathcal{N}$  and a trace  $\tau$  on it we can reduce it to a Sequential Time Petri-net  $\mathcal{N}'$  with the above definition in the following:

- If the original set of transitions was  $T$  then let  $T' = \{t_{\text{start}} \mid t \in T\} \cup \{t_{\text{end}} \mid t \in T\}$
- Given places  $p_i$  and  $p_{i+1}$  and a transition  $t_i$  such that  $\bullet t_i = \{p_i\}$  and  $t_i^\bullet = \{p_{i+1}\}$  we make states  $q_i, q'_i, q_{i+1}$  such that
  - $\bullet t_{i,\text{start}} = \{q_i\}$
  - $t_{i,\text{start}}^\bullet = \{q'_i\}$
  - $\bullet t_{i,\text{end}} = \{q'_i\}$
  - $t_{i,\text{end}}^\bullet = \{q_{i+1}\}$


This procedure takes in each transition and copies it, one copy for the start boundry of the transition, and one for the end.

Given a flow function  $f$  for  $\mathcal{N}$ , we can define  $f'$  for  $\mathcal{N}'$  as follows:

- If  $f = f_1 f_2 \dots f_n$  we let  $f' = f'_{1,\text{start}} f'_{1,\text{end}} f'_{2,\text{start}} \dots f'_{n,\text{end}}$ , note that  $|f'| = 2 |f|$ .
- If  $t_i = \langle \text{st}_i, \text{en}_i \rangle$  then
  - If  $f_i < \text{st}_i$  we let  $f'_{i,\text{start}} = \text{st}_i - f_i$  and  $f'_{i,\text{end}} = 0$
  - If  $f_i > \text{en}_i$  we let  $f'_{i,\text{start}} = 0$  and  $f'_{i,\text{end}} = f_i - \text{en}_i$
  - otherwise we let  $f'_{i,\text{start}} = f'_{i,\text{end}} = 0$

**Example 4:** Consider the Petri Net  $N$  and the flow functions  $F$  on them.

Using the above construction we get the following  $N'$



And we can rewrite the set of flow functions as

$$F = \left\{ \begin{bmatrix} 0 & 0 & 0 & 1 & 0 & 2 \\ 1 & 0 & 0 & 2 & 0 & 0 \end{bmatrix} \right\}$$

Note: I am omitting the labelling of the transitions as they are not relevant here.

This conversion intuitively changes the petri net so that one can treat different boundaries of transitions as different transitions, taking a transition too early or too late will translate to taking the first transition too late or taking the second transition too late, which matches our goal of having just 1 kind of edit.

**Theorem 1:** Given a Petri Net  $\mathcal{N}$  and a log  $\mathcal{L}$  and it's corresponding net and log in the restricted case  $\mathcal{N}'$  and  $\mathcal{L}'$ , for each edit of cost  $c$  that takes creates  $\mathcal{M}$  from  $\mathcal{N}$ , there is an edit of cost  $c$  that creates  $\mathcal{M}'$  from  $\mathcal{N}'$  such that

- $\mathcal{M}'$  is the restricted version of  $\mathcal{M}$  which can also be constructed using the methods defined above
- For any net  $N$  and log  $L$ , it's restricted version  $N'$  with  $L'$  has the same fitness as  $N$

Hence solving model repair for this restricted class, solves it for general sequential petri nets too.

Note: This can be made more efficient by only considering transitions for boundaries that matter. i.e, for an upper bound if a transition is taken too late in a trace, or for a lower bound if a transition is taken too early in a trace. This is especially easy to notice in petri-nets produced by editing the above restricted nets, apart from the first reduction, all other reductions either decrease the number of states or keep it the same.

This reduction will be assumed for [Section 4.a.ii](#), [Section 4.a.iii](#) and [Section 4.a.iv](#).

#### 4.a.ii. The $\text{unfit}$ function:

Given an a petri net  $\mathcal{N}$  with  $n$  transitions, any edit, must increase the upper bound of a transition by some amount, so we can represent an edit by an  $n$  dimesional vector, precisely the amount by which each upperbound of a transition is increased, formally, for any edit that takes a petri net  $\mathcal{N}$  to a petri net  $\mathcal{N}'$ , one can represent it as the vector  $v$  such that  $v(i) = \mathcal{N}'(i)_{\text{end}} - \mathcal{N}(i)_{\text{end}}$ . Where  $\mathcal{N}(i)_{\text{end}}$  is the upper bound of the static interval of the  $i^{\text{th}}$  transition of net  $\mathcal{N}$ .

Now the space  $(\mathbb{R}^+)^n$  can be mapped to the space of the petri nets that can be creating by editing a given starting petri net  $\mathcal{N}$ .

This lets us define the  $\text{unfit} : (\mathbb{R}^+)^n \rightarrow \mathbb{R}$  function. The input of the function is a vector, which represents an edit to the original petri net  $\mathcal{N}$  and the output of the function is the negation of the fitness of the net obtained after the edit.

The following helper function  $d' : \mathbb{R} \times \mathbb{R} \rightarrow \mathbb{R}$  will be useful:  $d'(a, b) = \max(0, b - a)$

First we define the  $\text{unfit}$  function for the case where there is just 1 trace in the log. Let the trace be  $\tau$  and it's flow function be  $f$ . Here the  $\text{unfit}$  function is the same as the distance function.

For each transition  $t_i$  of the petri net, we define  $d_i(\vec{a}, \vec{b}) = d'(\vec{a}(i), \vec{b}(i))$ . Where  $\vec{a}(i)$  is the  $i^{\text{th}}$  component of  $\vec{a}$ .

Now that we have defined it for each component we let  $D(\vec{a}, \vec{b}) = \sum_{i=1}^n d_i(\vec{a}, \vec{b})$


**Theorem 2:** Given a vector  $\vec{a}$  representing an edit on the petri net  $\mathcal{N}$  producing  $\mathcal{N}'$  and a flow function  $f$  in  $\mathcal{F}'$ ,  $D(a, f)$  is precisely  $\text{dist}_\theta$  between the edited net and  $f$ .

**Definition 17:** Given a net  $\mathcal{N}$  with constant  $[0, 0]$  static interval functions for all transitions and a log  $\mathcal{L}$ , the  $\text{unfit}$  function can be defined as follows.

$$\text{unfit}_{(\mathcal{N}, \mathcal{L})}(a) = \max_{f \in \mathcal{F}'} D(a, f) \quad (1)$$

**Corollary 3:**  $\text{unfit}_{(\mathcal{N}, \mathcal{L})}(a)$  is negation of the fitness of  $\mathcal{N}$  with respect to  $\mathcal{L}$ .

**Example 5:** Consider the following net  $\mathcal{N}$  with 2 transitions



And the following set of flow functions for it

$$F = \left\{ \begin{array}{l} f_1 = [2 \quad 0], \\ f_2 = [0 \quad 2], \\ f_3 = [1.5 \quad 1.5], \end{array} \right\}$$

And the following are the graphs of the unfit functions




Image 1: unfit function for  $f_1$




Image 2: unfit function for  $f_2$




Image 3: unfit function for  $f_3$




Image 4: unfit function for the entire problem

#### 4.a.iii. Gradient Descent:

**Theorem 4:** Some properties of the unfit functions:

The unfit functions turns out to have a ton of nice properties.

- The function  $d_i$  is continuous and a piecewise function, linear in each part.
- It is also a convex function.
- Since unfit us just multiple  $d_i$  functions combined using  $\max$  and summation. which means it's also continuous, piecewise linear, and a convex function.
- Also the domain of the function in general is  $(R^+)^n$ , but it can be restricted to all vectors such that the sum of their components ( $p_1$  norm)  $\leq \beta$  to give the problem a budget. In their scenarios the input space is a convex set.

These properties make it really good for gradient descent. Hence we will choose that as our strategy to solve the problem, it also precisely matches an intuitive direct strategy of finding the way to distribute the budgets to make changes optimal locally.

Gradient Descent is a greedy mathematical optimization techniques that involves starting at a point in the input space and moving in the opposite direction of the gradient(in the direction where the function decreases at the highest rate), until a local minimum is reached.

For our case picking Gradient Descent is a good option because:

- The function is piecewise linear, which means each part the gradient is constant and can be computed easily using linear programming.
- The function is convex with a convex set as it's input space, which means that there is only 1 set of global minima which is also convex and no other critical point.
- The input space can be bounded. If the fitness of the model is  $-k$  then the we can bound the input space to all vectors whose  $p_1$  norm is less than  $k * |L|$ . This is also a closed set, hence compact, which means the points that evaluate the global minima are in the set.

Therefore we can give the following algorithm for computing the model repair problem

- We start at the point 0
- At every step we find the direction of steepest descent and we keep moving in that direction:
  - Consume the entire budget
  - A new trace becomes a trace with maximum distance from the net
  - Some trace with maximum distance from net has a transition which is taken at a time delay accepted by the edited petri net.
- Whenever we reach such a point, we do recompute the gradient and keep repeating this and the previous step.
- We stop when the budget runs out or when the model becomes fit.

#### 4.a.iv. Computing the Solution:

We have defined our unfit function as the maximum of the distances of the log traces from the model. Let  $\mathcal{F}_{\max}$  be the set of flow functions with maximum distance from  $\mathcal{N}$ .

We now use linear programming to both compute the direction of steepest descent and the amount of budget to be spent in it before a recomputation is required.

We will be using the following list of variables.

- For every  $t$  in the set of transitions of the petri net (denoted by  $T$ ), we have a variable  $b_t$  holding the budget assigned to  $t$ .
- For every  $f$  in  $\mathcal{F}$  we have  $\text{imp}_f$  denoting the reduction in distance of  $f$  from  $\mathcal{N}$  because of the edit.
- $\text{improvement}$ , holding the total change in the fitness of the model, hence our goal will be to maximize this.
- $\text{spend}$ , holding the total amount of budget spent.

The following constants will be helpful in writing the equations

- We let  $\vec{a} = 0$
- $\beta$ , which is the total budget available
- $\text{un-fitness} = \text{unfit}_{(\mathcal{N}, \mathcal{L})}(\vec{a})$
- For each  $f \in \mathcal{F}$  we have  $d_f = D(\vec{a}, f)$ , that is the distance of  $f$  from  $\mathcal{N}$
- for each  $f \in \mathcal{F}$ , we let  $d_{f,i} = f_i$
- For each  $f \in \mathcal{F}$  and  $t$  in  $T$  we have  $\text{affects}_{t,f}$  which is
  - 0 if  $t$  is the  $i^{\text{th}}$  transitions and  $d_i(\vec{a}, f) = 0$
  - 1 otherwise

The goal of linear program is

$$\text{Maximize}(\text{improvement}) \quad (2)$$

Under the constraints:

- We do not spend more than the total budget:

$$\text{spend} \leq \beta \quad (3)$$

- Improvement in a flow function is the total budget assigned to the transitions which affect it, for each  $f \in \mathcal{F}$  we have

$$\text{imp}_f = \sum_{t \in T} b_t \times \text{affects}_{t,f} \quad (4)$$

- Total improvement is the least improvement of all of the flow functions in  $\mathcal{F}_{\max}$ , so for each  $f \in \mathcal{F}_{\max}$

$$\text{improvement} \leq \text{imp}_f \quad (5)$$

- Computing the total amount of budget spent

$$\text{spend} = \sum_{t \in T} b_t \quad (6)$$

The variables  $b_t$  can be used to compute the direction of steepest descent, but we also add the following constraint to calculate the largest “step size” after which we need to do recomputation.

- We need to recompute when a new flow function needs to be added to  $\mathcal{F}_{\max}$  so for all  $f \in \mathcal{F}$

$$\text{un-fitness} - \text{improvement} \geq d_f - \text{imp}_f \quad (7)$$

- We need to recompute each time the effects variables become outdated, so for all  $i \in [1 \dots n]$  let  $t_i$  be the  $i^{\text{th}}$  transition and for all  $f \in \mathcal{F}$  we have

$$b_{t_i} \leq d_{f,i} \quad (8)$$

Once we get values of  $b_{t_i}$  after solving the linear program, we get  $\tilde{a}(i) = b_{t_i}$  where  $t_i$  is the  $i^{\text{th}}$  transition. We also set  $\beta := \beta - \text{spend}$ . After fixing those 2, we recompute all the other constants and do the linear programming again till we consume the entire budget or un-fitness becomes 0.

#### 4.a.v. Time Complexity:

The algorithm one local change using linear programming and repeating again and again till the budget is consumed or the model becomes fit.

For the linear programming, given a petri net with  $n$  transition, and a log with size  $l$  we have to compute  $2ln + l + 3$  constants, which is  $O(ln)$  time. Then we solve a linear programming problem with  $n + l + 2$  variables and  $3ln + 2l + 2$  constraints which can be computed in polynomial time ((Cohen et al., 2018)).

Now with all the budgets for  $\mathcal{N}$  computed, we can edit the petri net to get  $\mathcal{N}'$  which has the highest possible fitness that can be achieved under the budget constraint  $\beta$ .

## References

- Aalst, W. van der. (2016). *Process Mining: Data Science in Action* (2nd ed.). Springer Publishing Company, Incorporated.
- Chatain, T., & Rino, N. (2022). Timed Alignments. *2022 4th International Conference on Process Mining (ICPM)*, 0, 112–119. <https://doi.org/10.1109/ICPM57379.2022.9980687>
- Cohen, M. B., Lee, Y. T., & Song, Z. (2018). Solving Linear Programs in the Current Matrix Multiplication Time. *Corr.* <http://arxiv.org/abs/1810.07896>