

```
// ===== File 1/66: DelegationApp/App/AppContainer.swift =====
import Foundation
import SwiftUI

@MainActor
final class AppContainer: ObservableObject {
    let taskService: TaskService
    let chatService: ChatService
    let profileService: ProfileService
    let announcementService: AnnouncementService
    let authService: AuthService

    // ВАЖНО: lazy – чтобы инициализация SessionStore произошла уже на MainActor
    lazy var session: SessionStore = SessionStore(auth: authService)

    init(
        taskService: TaskService,
        chatService: ChatService,
        profileService: ProfileService,
        announcementService: AnnouncementService,
        authService: AuthService
    ) {
        self.taskService = taskService
        self.chatService = chatService
        self.profileService = profileService
        self.announcementService = announcementService
        self.authService = authService
    }
}

extension AppContainer {
    @MainActor
    static let preview = AppContainer(
        taskService: MockTaskService(),
        chatService: MockChatService(),
        profileService: MockProfileService(),
        announcementService: MockAnnouncementService(),
        authService: NetworkAuthService()
    )
}
```

```
// ===== File 2/66: DelegationApp/App/AppRouter.swift =====
import SwiftUI

struct AppRouter: View {
    @EnvironmentObject var container: AppContainer

    var body: some View {
        rootView()
            .environmentObject(container)
            .environmentObject(container.session)
    }
}

struct RootView: View {
    @EnvironmentObject var container: AppContainer
    @EnvironmentObject var session: SessionStore

    var body: some View {
        Group {
            if !AppConfig.authEnabled {
                MainTabView()
            } else {
                if session.isRestoring {
                    VStack(spacing: 12) {
                        ProgressView()
                    }
                }
            }
        }
    }
}
```

```

        Text("Проверяем сессию...")
            .font(.system(size: 14))
    }
} else {
    if session.isAuthenticated {
        MainTabView()
    } else {
        AuthScreen()
    }
}
}
}
}
}

private struct MainTabView: View {
    @EnvironmentObject var container: AppContainer
    @EnvironmentObject var session: SessionStore
    @State private var tab: AppTab = .map

    var body: some View {
        ZStack { contentView }
            .safeAreaInset(edge: .bottom) {
                LiquidTabBar(selection: $tab)
                    .padding(.horizontal, 16)
                    .padding(.bottom, 8)
            }
            .tint(Theme.ColorToken.turquoise)
    }
}

@ViewBuilder
private var contentView: some View {
    switch tab {
    case .map:
        NavigationStack {
            MapScreen(
                vm: .init(
                    service: container.taskService,
                    announcementService: container.announcementService,
                    searchService: AddressSearchService()
                ),
                mapMode: MapDisplayConfig.defaultMode()
            )
        }

    case .route:
        NavigationStack {
            RouteScreen(vm: .init(service: container.taskService))
        }

    case .ads:
        NavigationStack {
            MyAdsScreen(
                vm: .init(
                    service: container.announcementService,
                    session: session
                )
            )
        }

    case .chats:
        NavigationStack {
            ChatsScreen(vm: .init(service: container.chatService))
        }

    case .profile:
        NavigationStack {
            ProfileScreen(vm: .init(service: container.profileService))
        }
    }
}

```

```

        .toolbar {
            if AppConfig.authEnabled {
                Button("Logout") { session.logout() }
            }
        }
    }
}
}
}
}
}

```

// ===== File 3/66: DelegationApp/App/DelegationApp.swift =====

```

import SwiftUI
import YandexMapsMobile

@main
struct DelegationApp: App {
    @StateObject private var container = AppContainer.preview

    init() {
        YMKMapKit.setApiKey("df3f9145-2080-42b7-9b91-b879c34236bb")
        YMKMapKit.sharedInstance()
    }

    var body: some Scene {
        WindowGroup {
            rootView()
                .environmentObject(container)
                .environmentObject(container.session) // <- БОТ ЭТО ВАЖНО
        }
    }
}

```

// ===== File 4/66: DelegationApp/App/YandexMapView.swift =====

```

/// Обёртка над YMKMapView для использования в SwiftUI.
///
/// Важно: в превью мы не создаём нативную карту вообще,
/// чтобы не падал SwiftUI Preview.

```

```

import SwiftUI
import YandexMapsMobile

struct YandexMapView: UIViewRepresentable {
    @Binding var centerPoint: YMKPoint?
    let pins: [YMKPoint]

    final class Coordinator {
        var mapView: YMKMapView?
        var centerPlacemark: YMKPlacemarkMapObject?
        var pinPlacemarks: [YMKPlacemarkMapObject] = []
    }

    func makeCoordinator() -> Coordinator { Coordinator() }

    func makeUIView(context: Context) -> UIView {
        let container = UIView()
        container.backgroundColor = .clear

        YandexMapConfigurator.configureIfNeeded()

        guard let mapView = makeNativeMapView() else {
            return container
        }
        mapView.translatesAutoresizingMaskIntoConstraints = false
    }
}

```

```

        container.addSubview(mapView)
        NSLayoutConstraint.activate([
            mapView.topAnchor.constraint(equalTo: container.topAnchor),
            mapView.bottomAnchor.constraint(equalTo: container.bottomAnchor),
            mapView.leadingAnchor.constraint(equalTo: container.leadingAnchor),
            mapView.trailingAnchor.constraint(equalTo: container.trailingAnchor),
        ])

        context.coordinator.mapView = mapView

        let startPoint = centerPoint ?? YMKPoint(latitude: 55.751244, longitude: 37.618423)
        applyState(on: mapView, coordinator: context.coordinator, center: startPoint, pins: pins)

        return container
    }

    func updateUIView(_ uiView: UIView, context: Context) {
        guard let mapView = context.coordinator.mapView else { return }

        let target = centerPoint ?? YMKPoint(latitude: 55.751244, longitude: 37.618423)
        applyState(on: mapView, coordinator: context.coordinator, center: target, pins: pins)
    }

    private func makeNativeMapView() -> YMKMapView? {
        #if targetEnvironment(simulator)
            // For Apple Silicon simulators MapKit recommends Vulkan-backed view.
            return YMKMapView(frame: .zero, vulkanPreferred: true)
        #else
            return YMKMapView(frame: .zero)
        #endif
    }

    private func applyState(
        on mapView: YMKMapView,
        coordinator: Coordinator,
        center: YMKPoint,
        pins: [YMKPoint]
    ) {
        let map = mapView.mapWindow.map

        // Камера
        let position = YMKCameraPosition(target: center, zoom: 14, azimuth: 0, tilt: 0)
        let animation = YMKAnimation(type: .smooth, duration: 0.8)
        map.move(with: position, animation: animation, cameraCallback: nil)

        let mapObjects = map.mapObjects

        // Маркер центра (поиск)
        if let old = coordinator.centerPlacemark {
            mapObjects.remove(with: old)
        }
        coordinator.centerPlacemark = mapObjects.addPlacemark(with: center)

        // Пины объявлений
        for old in coordinator.pinPlacemarks {
            mapObjects.remove(with: old)
        }
        coordinator.pinPlacemarks.removeAll()

        for p in pins {
            let pm = mapObjects.addPlacemark(with: p)
            coordinator.pinPlacemarks.append(pm)
        }
    }
}

```

```

// ===== File 5/66: DelegationApp/Core/Components/FilterChip.swift =====
import SwiftUI

/// Универсальный чип-фильтр.
/// Поддерживает два режима:
/// 1) Binding<Bool> – чип сам переключает состояние.
/// 2) Bool + action – состояние вычисляется снаружи, чип только вызывает action.
struct FilterChip: View {
    let title: String

    // Внутри всегда есть Binding, но во "внешнем" режиме он будет .constant(...)
    @Binding private var isSelected: Bool

    // Нужно ли самому делать toggle()
    private let togglesSelection: Bool

    // Доп. действие при тапе (например, выбрать фильтр)
    private let action: (() -> Void)?

    // MARK: - Init (Binding mode)
    init(
        title: String,
        isSelected: Binding<Bool>,
        action: (() -> Void)? = nil
    ) {
        self.title = title
        self._isSelected = isSelected
        self.togglesSelection = true
        self.action = action
    }

    // MARK: - Init (Computed Bool mode)
    init(
        title: String,
        isSelected: Bool,
        action: @escaping () -> Void
    ) {
        self.title = title
        self._isSelected = .constant(isSelected)
        self.togglesSelection = false
        self.action = action
    }

    var body: some View {
        Button {
            if togglesSelection {
                isSelected.toggle()
            }
            action?()
        } label: {
            Text(title)
                .font(.system(size: 14, weight: .semibold))
                .foregroundColor(isSelected ? Color.white : Color.primary)
                .padding(.vertical, 8)
                .padding(.horizontal, 12)
                .background(
                    Capsule()
                        .fill(isSelected ? Theme.ColorToken.turquoise : Color.white.opacity(0.7))
                )
                .overlay(
                    Capsule()
                        .stroke(Theme.ColorToken.turquoise.opacity(0.3), lineWidth: 1)
                )
        }
        .buttonStyle(.plain)
        .shadow(color: Color.black.opacity(0.05), radius: 4, x: 0, y: 2)
    }
}

```

```
// ===== File 6/66: DelegationApp/Core/Components/FloatingPlusButton.swift =====
//
// FloatingPlusButton.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//
```

```
import SwiftUI
```

```
struct FloatingPlusButton: View {
    var action: () -> Void
    var body: some View {
        Button(action: action) {
            Image(systemName: "plus")
                .font(.system(size: 24, weight: .bold))
                .foregroundColor(Color.white)
                .frame(width: 64, height: 64)
                .background(Circle().fill(Theme.ColorToken.turquoise))
                .softCardShadow()
        }
        .buttonStyle(.plain)
        .accessibilityLabel("Создать")
    }
}
```

```
// ===== File 7/66: DelegationApp/Core/Components/LiquidTabBar.swift =====
import SwiftUI
```

```
/// Прозрачный TabBar в стиле iOS 26 / Telegram
/// с «жидким» индикатором, который плавно переезжает между иконками.
```

```
struct LiquidTabBar: View {
    @Binding var selection: AppTab
    var badges: [AppTab: Int] = [:]

    @Namespace private var indicatorNamespace

    // Размеры – их теперь легко править
    private let barCornerRadius: CGFloat = 26
    private let barHeight: CGFloat = 74
    private let bubbleSize: CGFloat = 54

    var body: some View {
        HStack(spacing: 10) {
            ForEach(AppTab.allCases) { tab in
                tabButton(for: tab)
            }
        }
        .padding(.horizontal, 14)
        .frame(height: barHeight)
        .background(
            RoundedRectangle(cornerRadius: barCornerRadius, style: .continuous)
                .fill(.ultraThinMaterial) // стекло
                .overlay(
                    RoundedRectangle(cornerRadius: barCornerRadius, style: .continuous)
                        .stroke(Color.white.opacity(0.15), lineWidth: 1)
                )
                .shadow(color: Color.black.opacity(0.10),
                    radius: 22,
                    x: 0,
                    y: 10)
        )
    }
    // Плавный переезд «капли» между иконками
}
```

```

        .animation(
            .spring(response: 0.45,
                    dampingFraction: 0.85,
                    blendDuration: 0.25),
            value: selection
        )
    }

// MARK: - Одна кнопка таба

private func tabButton(for tab: AppTab) -> some View {
    Button {
        if selection != tab {
            selection = tab
        }
    } label: {
        ZStack {
            // «Liquid Glass» пузырёк под выбранной иконкой
            if selection == tab {
                Circle()
                    .fill(.ultraThinMaterial)
                    .overlay(
                        Circle()
                            .stroke(Color.white.opacity(0.45), lineWidth: 1)
                    )
                    .shadow(color: Color.black.opacity(0.20),
                            radius: 14,
                            x: 0,
                            y: 8)
                    .matchedGeometryEffect(id: "LIQUID_INDICATOR",
                                           in: indicatorNamespace)
                    .frame(width: bubbleSize, height: bubbleSize)
                    .transition(.opacity)
            }

            VStack(spacing: 4) {
                Image(systemName: tab.iconName(selected: selection == tab))
                    .font(.system(size: 18, weight: .semibold)) // иконка немного меньше
                    .foregroundColor(
                        selection == tab
                        ? Theme.ColorToken.turquoise
                        : Theme.ColorToken.textSecondary
                    )
                    .scaleEffect(selection == tab ? 1.08 : 1.0)
                    .frame(height: 20)

                Text(tab.title)
                    .font(.system(size: 11, weight: .semibold)) // текст поменьше
                    .foregroundColor(
                        selection == tab
                        ? Theme.ColorToken.turquoise
                        : Theme.ColorToken.textSecondary
                    )
                    .lineLimit(1) // всегда в одну строку
                    .minimumScaleFactor(0.7) // «Объявления» сжимается, но не переносится
            }
            .frame(maxWidth: .infinity)
        }
    }
    .buttonStyle(.plain)
    .frame(maxWidth: .infinity)
    .overlay(alignment: .topTrailing) {
        // Красный бейдж (например, на профиле «2»)
        if let count = badges[tab], count > 0 {
            Text("\(count)")
                .font(.system(size: 11, weight: .bold))
                .padding(5)
        }
    }
}

```

```

        .background(
            Circle()
                .fill(Color.red)
        )
        .foregroundColor(.white)
        .offset(x: 8, y: -10)
    }
}
}
}
}

```

// ===== File 8/66: DelegationApp/Core/Components/PriceTag.swift =====

```

//
// PriceTag.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

```

```
import SwiftUI
```

```

struct PriceTag: View {
    let price: Int
    let eta: Int
    var isHighlighted: Bool = false

    var body: some View {
        VStack(spacing: 4) {
            Text("\(price) ")
                .font(.system(size: 16, weight: .semibold))
            Text("\(eta) мин")
                .font(.system(size: 12, weight: .regular))
                .foregroundColor(Theme.ColorToken.textSecondary)
        }
        .padding(.horizontal, 16)
        .padding(.vertical, 10)
        .background(
            RoundedRectangle(cornerRadius: Theme.Radius.l, style: .continuous)
                .fill(Theme.ColorToken.white)
                .overlay(
                    RoundedRectangle(cornerRadius: Theme.Radius.l)
                        .stroke(isHighlighted ? Theme.ColorToken.turquoise : Color.clear, lineWidth: 2)
                )
        )
        .softCardShadow()
    }
}

```

// ===== File 9/66: DelegationApp/Core/Components/StarsView.swift =====

```

//
// StarsView.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

```

```
import SwiftUI
```

```

struct StarsView: View {
    let rating: Double
    let max: Int = 5

    var body: some View {
        HStack(spacing: 4) {

```

```

        ForEach(0.. $\max$ , id: \.self) { idx in
            let filled = rating >= Double(idx + 1) - 0.001
            Image(systemName: filled ? "star.fill" : "star")
                .foregroundColor(filled ? Theme.ColorToken.peach : Theme.ColorToken.textSecondary)
        }
    }
}

```

```

// ===== File 10/66: DelegationApp/Core/Config/AppConfig.swift =====
//
// AppConfig.swift
// iCuno test
//
// Created by maftuna murtazaeva on 22.01.2026.
//

```

```
import Foundation
```

```
enum AppConfig {
```

```

    // =====
    // DEV-ПЕРЕКЛЮЧАТЕЛЬ АВТОРИЗАЦИИ
    // =====
    // Хочешь разрабатывать приложение БЕЗ регистрации/логина?
    // Просто поставь false, и приложение будет сразу пускать внутрь.
    //
    // Когда будешь полноценно тестировать – верни true.
    static let authEnabled: Bool = {
        #if DEBUG
            return false // <-- МЕНЯЕШЬ ТУТ: false = без авторизации
        #else
            return true
        #endif
    }()

    // =====
    // BASE URL ДЛЯ API
    // =====
    // ВАЖНО:
    // - В симуляторе iOS часто можно ходить на 127.0.0.1 (это Mac).
    // - На РЕАЛЬНОМ iPhone 127.0.0.1 = сам iPhone, поэтому бэкэнд "на маке" не доступен.
    //
    // Правильный вариант для iPhone: http://<IP_твоего_Mac_в_WiFi>:8000
    // Например: http://192.168.1.10:8000
    static let apiBaseUrl: URL = {
        // Если захочешь – можешь положить API_BASE_URL в Info.plist,
        // тогда здесь подхватится автоматически (удобно для разных конфигов).
        if let s = Bundle.main.object(forKey: "API_BASE_URL") as? String,
            !s.isEmpty,
            let url = URL(string: s) {
            return url
        }

        let fallback: String
        #if targetEnvironment(simulator)
            fallback = "http://127.0.0.1:8000"
        #else
            // !!! Поменяй на IP твоего Mac (в той же сети Wi-Fi)
            fallback = "http://192.168.1.10:8000"
        #endif

        guard let url = URL(string: fallback) else {
            preconditionFailure("Invalid API base URL fallback: \(fallback)")
        }
        return url
    }()

```

```
    }()  
}
```

```
// ===== File 11/66: DelegationApp/Core/Models/AdModels.swift =====  
//  
// AdModels.swift  
// iCuno test  
//  
// Создано для экрана объявлений.  
//
```

```
import Foundation
```

```
/// Модель объявления. Пока используется только для мок-данных  
/// на экране "Мои объявления".
```

```
struct AdItem: Identifiable {  
    let id: UUID = .init()  
    let title: String  
    let priceDescription: String  
    let isExpired: Bool  
    let views: Int  
    let responses: Int  
    let favorites: Int  
}
```

```
// ===== File 12/66: DelegationApp/Core/Models/AnnouncementModels.swift =====  
//  
// AnnouncementModels.swift  
// iCuno test  
//  
// Created by maftuna murtazaeva on 18.02.2026.  
//
```

```
import Foundation
```

```
// MARK: - Network models
```

```
struct AnnouncementDTO: Codable, Identifiable {  
    let id: String  
    let user_id: String  
    let category: String  
    let title: String  
    let status: String  
    let data: [String: JSONValue]  
    let created_at: String  
}
```

```
struct CreateAnnouncementRequest: Codable {  
    let category: String  
    let title: String  
    let status: String  
    let data: [String: JSONValue]  
  
    init(category: String, title: String, status: String = "active", data: [String: JSONValue]) {  
        self.category = category  
        self.title = title  
        self.status = status  
        self.data = data  
    }  
}
```

```
// ===== File 13/66: DelegationApp/Core/Models/AppTab.swift =====
```

```

import SwiftUI

/// Вкладки нижнего TabBar
enum AppTab: Int, CaseIterable, Identifiable {
    case map
    case route
    case ads
    case chats
    case profile

    var id: Int { rawValue }

    /// Текст под иконкой
    var title: String {
        switch self {
            case .map:      return "Карта"
            case .route:    return "Маршрут"
            case .ads:      return "Объявления"
            case .chats:    return "Чаты"
            case .profile:  return "Профиль"
        }
    }

    /// Названия системных иконок (для выбранного/не выбранного состояния)
    func iconName(selected: Bool) -> String {
        switch self {
            case .map:
                return selected ? "map.fill" : "map"

            case .route:
                // Ваша «ветка маршрута»
                return "point.topleft.down.curvedto.point.bottomright.up"

            case .ads:
                return selected
                    ? "rectangle.stack.badge.plus.fill"
                    : "rectangle.stack.badge.plus"

            case .chats:
                return selected
                    ? "bubble.left.and.bubble.right.fill"
                    : "bubble.left.and.bubble.right"

            case .profile:
                return selected ? "person.circle.fill" : "person.circle"
        }
    }
}

```

```

// ===== File 14/66: DelegationApp/Core/Models/AuthModels.swift =====
import Foundation

```

```

struct RegisterRequest: Codable {
    let email: String
    let password: String
}

```

```

struct LoginRequest: Codable {
    let email: String
    let password: String
}

```

```

struct TokenResponse: Codable {
    let access_token: String
    let token_type: String? // <-- стало optional (чтобы не падало при декоде)
}

```

```
struct MeResponse: Codable {
    let id: String
    let email: String
    let role: String
}
```

```
// ===== File 15/66: DelegationApp/Core/Models/ChatModels.swift =====
import Foundation
```

```
struct ChatPreview: Identifiable {
    let id: UUID = .init()
    let initials: String
    let name: String
    let lastMessage: String
    let time: String
    let unreadCount: Int
}
```

```
// ===== File 16/66: DelegationApp/Core/Models/JSONValue+Numbers.swift =====
//
// JSONValue+Numbers.swift
// iCuno test
//
// Created by maftuna murtazaeva on 25.02.2026.
//
```

```
import Foundation
```

```
extension JSONValue {
    var doubleValue: Double? {
        switch self {
            case .double(let d): return d
            case .int(let i): return Double(i)
            case .string(let s): return Double(s)
            default: return nil
        }
    }

    var objectValue: [String: JSONValue]? {
        if case .object(let o) = self { return o }
        return nil
    }
}
```

```
// ===== File 17/66: DelegationApp/Core/Models/JSONValue.swift =====
//
// JSONValue.swift
// iCuno test
//
// Created by maftuna murtazaeva on 18.02.2026.
//
```

```
import Foundation
```

```
/// Универсальный тип для передачи "любого" JSON (строка/число/булев/массив/объект/null).
/// Нужен, чтобы сохранять форму объявления в БД без жёсткой схемы на iOS.
enum JSONValue: Codable, Equatable {
    case string(String)
    case int(Int)
    case double(Double)
    case bool(Bool)
```

```

case object([String: JSONValue])
case array([JSONValue])
case null

init(from decoder: Decoder) throws {
    let c = try decoder.singleValueContainer()

    if c.decodeNil() {
        self = .null
        return
    }
    if let b = try? c.decode(Bool.self) {
        self = .bool(b)
        return
    }
    if let i = try? c.decode(Int.self) {
        self = .int(i)
        return
    }
    if let d = try? c.decode(Double.self) {
        self = .double(d)
        return
    }
    if let s = try? c.decode(String.self) {
        self = .string(s)
        return
    }
    if let o = try? c.decode([String: JSONValue].self) {
        self = .object(o)
        return
    }
    if let a = try? c.decode([JSONValue].self) {
        self = .array(a)
        return
    }

    throw DecodingError.dataCorruptedError(in: c, debugDescription: "Unsupported JSON value")
}

func encode(to encoder: Encoder) throws {
    var c = encoder.singleValueContainer()
    switch self {
    case .string(let s): try c.encode(s)
    case .int(let i): try c.encode(i)
    case .double(let d): try c.encode(d)
    case .bool(let b): try c.encode(b)
    case .object(let o): try c.encode(o)
    case .array(let a): try c.encode(a)
    case .null: try c.encodeNil()
    }
}

extension JSONValue {
    var stringValue: String? {
        if case .string(let s) = self { return s }
        return nil
    }
    var intValue: Int? {
        if case .int(let i) = self { return i }
        return nil
    }
    var boolValue: Bool? {
        if case .bool(let b) = self { return b }
        return nil
    }
}

```

```
// ===== File 18/66: DelegationApp/Core/Models/ProfileModels.swift =====
//
// ProfileModels.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//
```

```
import Foundation
```

```
struct Profile {
    let name: String
    let phone: String
    let rating: Double
    let completed: Int
    let cancelled: Int
}
```

```
struct Review: Identifiable {
    let id: UUID = .init()
    let authorInitial: String
    let authorName: String
    let text: String
    let ago: String
    let stars: Int
}
```

```
// ===== File 19/66: DelegationApp/Core/Models/TaskModels.swift =====
//
// TaskModels.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//
```

```
import Foundation
```

```
struct TaskItem: Identifiable {
    let id: UUID = .init()
    let title: String
    let price: Int //
    let etaMinutes: Int // мин
    let distanceKm: Double
}
```

```
// ===== File 20/66: DelegationApp/Core/Services/AnnouncementService.swift =====
//
// AnnouncementService.swift
// iCuno test
//
// Created by maftuna murtazaeva on 18.02.2026.
//
```

```
import Foundation
```

```
protocol AnnouncementService {
    func createAnnouncement(token: String, request: CreateAnnouncementRequest) async throws -> AnnouncementDTO
    func myAnnouncements(token: String) async throws -> [AnnouncementDTO]

    // Для карты: публичные активные объявления (без токена)
    func publicAnnouncements() async throws -> [AnnouncementDTO]
}
```

```

final class NetworkAnnouncementService: AnnouncementService {
    private let api: APIClient

    init(api: APIClient = APIClient()) {
        self.api = api
    }

    func createAnnouncement(token: String, request: CreateAnnouncementRequest) async throws -> AnnouncementDTO
{
    try await api.request(.createAnnouncement, body: request, token: token)
}

    func myAnnouncements(token: String) async throws -> [AnnouncementDTO] {
        try await api.request(.myAnnouncements, token: token)
    }

    func publicAnnouncements() async throws -> [AnnouncementDTO] {
        try await api.request(.publicAnnouncements)
    }
}

final class MockAnnouncementService: AnnouncementService {
    func createAnnouncement(token: String, request: CreateAnnouncementRequest) async throws -> AnnouncementDTO
{
    let now = ISO8601DateFormatter().string(from: Date())
    return AnnouncementDTO(
        id: UUID().uuidString,
        user_id: "dev",
        category: request.category,
        title: request.title,
        status: request.status,
        data: request.data,
        created_at: now
    )
}

    func myAnnouncements(token: String) async throws -> [AnnouncementDTO] {
        let now = ISO8601DateFormatter().string(from: Date())
        return [
            AnnouncementDTO(
                id: UUID().uuidString,
                user_id: "dev",
                category: "delivery",
                title: "Доставка по пути: забрать посылку",
                status: "active",
                data: [
                    "pickup_address": .string("Москва, Красная площадь"),
                    "point": .object(["lat": .double(55.75393), "lon": .double(37.620795)])
                ],
                created_at: now
            )
        ]
    }

    func publicAnnouncements() async throws -> [AnnouncementDTO] {
        // Для превью/моков можно вернуть то же самое
        try await myAnnouncements(token: "DEV_TOKEN")
    }
}

// ===== File 21/66: DelegationApp/Core/Services/AuthService.swift =====
//
// AuthService.swift
// iCuno test
//

```

```
// Created by maftuna murtazaeva on 21.01.2026.  
//
```

```
import Foundation
```

```
protocol AuthService {  
    func register(email: String, password: String) async throws -> TokenResponse  
    func login(email: String, password: String) async throws -> TokenResponse  
    func me(token: String) async throws -> MeResponse  
}  
  
final class NetworkAuthService: AuthService {  
    private let api: APIClient  
  
    init(api: APIClient = APIClient()) {  
        self.api = api  
    }  
  
    func register(email: String, password: String) async throws -> TokenResponse {  
        let req = RegisterRequest(email: email, password: password)  
        return try await api.request(.register, body: req)  
    }  
  
    func login(email: String, password: String) async throws -> TokenResponse {  
        let req = LoginRequest(email: email, password: password)  
        return try await api.request(.login, body: req)  
    }  
  
    func me(token: String) async throws -> MeResponse {  
        return try await api.request(.me, token: token)  
    }  
}
```

```
// ===== File 22/66: DelegationApp/Core/Services/ChatService.swift =====  
//  
// ChatService.swift  
// iCuno test  
//  
// Created by maftuna murtazaeva on 07.11.2025.  
//
```

```
import Foundation
```

```
protocol ChatService {  
    func loadChats() -> [ChatPreview]  
}
```

```
// ===== File 23/66: DelegationApp/Core/Services/Mock/MockAnnouncementService.swift =====
```

```
////  
//// MockAnnouncementService.swift  
//// iCuno test  
////  
//// Created by maftuna murtazaeva on 18.02.2026.  
////  
//  
//import Foundation  
//  
//final class MockAnnouncementService: AnnouncementService {  
//    func createAnnouncement(token: String, request: CreateAnnouncementRequest) async throws ->  
//    AnnouncementDTO {  
//        let now = ISO8601DateFormatter().string(from: Date())  
//        return AnnouncementDTO(  
//            id: UUID().uuidString,  
//            user_id: "dev",  
//
```

```

//      category: request.category,
//      title: request.title,
//      status: request.status,
//      data: request.data,
//      created_at: now
//    )
//  }
//
//  func myAnnouncements(token: String) async throws -> [AnnouncementDTO] {
//      let now = ISO8601DateFormatter().string(from: Date())
//      return [
//          AnnouncementDTO(
//              id: UUID().uuidString,
//              user_id: "dev",
//              category: "delivery",
//              title: "Доставка по пути: забрать посылку",
//              status: "active",
//              data: ["budget": .int(300)],
//              created_at: now
//          ),
//          AnnouncementDTO(
//              id: UUID().uuidString,
//              user_id: "dev",
//              category: "help",
//              title: "Помощь с мелким поручением",
//              status: "draft",
//              data: [:],
//              created_at: now
//          )
//      ]
//  }
//}

```

```

// ===== File 24/66: DelegationApp/Core/Services/Mock/MockChatService.swift =====
import Foundation

```

```

final class MockChatService: ChatService {
    func loadChats() -> [ChatPreview] {
        [
            .init(initials: "С", name: "Саша", lastMessage: "Ман сасилдок", time: "14:30", unreadCount: 1),
            .init(initials: "П", name: "Павел", lastMessage: "Посылку доставил", time: "Вчера", unreadCount:
0)
        ]
    }
}

```

```

// ===== File 25/66: DelegationApp/Core/Services/Mock/MockProfileService.swift =====
//
// MockProfileService.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

```

```

import Foundation

final class MockProfileService: ProfileService {
    func loadProfile() -> Profile {
        .init(name: "Алексей Иванов",
            phone: "+7 999 123-45-67",
            rating: 4.9,
            completed: 127,
            cancelled: 3)
    }
}

```

```

func loadReviews() -> [Review] {
    [
        .init(authorInitial: "М", authorName: "Мария К.",
            text: "Отличный исполнитель! Всё сделал быстро и качественно. Рекомендую!",
            ago: "2 дня назад", stars: 5),
        .init(authorInitial: "Д", authorName: "Дмитрий С.",
            text: "Очень доволен! Приехал раньше срока, всё аккуратно.",
            ago: "неделю назад", stars: 5)
    ]
}
}

```

```

// ===== File 26/66: DelegationApp/Core/Services/Mock/MockTaskService.swift =====
//
// MockTaskService.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

```

```

import Foundation

final class MockTaskService: TaskService {
    func loadNearbyTasks() -> [TaskItem] {
        [
            .init(title: "Купить молоко", price: 200, etaMinutes: 14, distanceKm: 1.1),
            .init(title: "Забрать посылку", price: 400, etaMinutes: 10, distanceKm: 2.0),
            .init(title: "Доставить цветы", price: 500, etaMinutes: 18, distanceKm: 3.5),
            .init(title: "Помочь донести", price: 250, etaMinutes: 7, distanceKm: 0.6)
        ]
    }
    func loadRouteTasks() -> [TaskItem] {
        [
            .init(title: "Подхватить письмо", price: 350, etaMinutes: 8, distanceKm: 0.9),
            .init(title: "Купить кофе", price: 150, etaMinutes: 12, distanceKm: 0.5)
        ]
    }
}

```

```

// ===== File 27/66: DelegationApp/Core/Services/Networking/APIClient.swift =====
import Foundation

```

```

struct APIClient {

    struct APIError: LocalizedError {
        let statusCode: Int
        let message: String
        var errorDescription: String? {
            message.isEmpty ? "HTTP \(statusCode)" : message
        }
    }

    // FastAPI error: {"detail": "..."} или {"detail":[{"loc":..., "msg":...}]}
    private struct FastAPIError: Decodable {
        let detail: Detail

        enum Detail: Decodable {
            case string(String)
            case validation([ValidationItem])
            case unknown

            init(from decoder: Decoder) throws {
                let container = try decoder.singleValueContainer()
                if let str = try? container.decode(String.self) {

```

```

        self = .string(str)
        return
    }
    if let arr = try? container.decode([ValidationItem].self) {
        self = .validation(arr)
        return
    }
    self = .unknown
}

}

struct ValidationItem: Decodable {
    let loc: [String]?
    let msg: String?
    let type: String?
}

var humanMessage: String {
    switch detail {
    case .string(let s):
        return s
    case .validation(let items):
        let msgs = items.compactMap { $0.msg }
        if msgs.isEmpty { return "Некорректные данные" }
        let joined = msgs.joined(separator: "\n")
        if joined.contains("value is not a valid email address") {
            return "Неверный email. Пример: name@mail.com"
        }
        return joined
    case .unknown:
        return "Ошибка запроса"
    }
}
}

// Используем свою сессию (таймауты!)
private let session: URLSession

init() {
    let config = URLSessionConfiguration.default
    config.timeoutIntervalForRequest = 8 // быстро падаем, а не "вечная загрузка"
    config.timeoutIntervalForResource = 15
    self.session = URLSession(configuration: config)
}

func request<T: Decodable, B: Encodable>(
    _ endpoint: APIEndpoint,
    body: B? = nil,
    token: String? = nil
) async throws -> T {

    var req = URLRequest(url: endpoint.url)
    req.httpMethod = endpoint.method.rawValue
    req.setValue("application/json", forHTTPHeaderField: "Content-Type")

    if let token {
        req.setValue("Bearer \(token)", forHTTPHeaderField: "Authorization")
    }

    if let body {
        req.httpBody = try JSONEncoder().encode(body)
    }

    do {
        let (data, response) = try await session.data(for: req)

        guard let http = response as? HTTPURLResponse else {
            throw APIError(statusCode: -1, message: "Нет HTTP ответа")
        }
    }
}

```

```

    }

    if (200..<300).contains(http.statusCode) {
        return try JSONDecoder().decode(T.self, from: data)
    }

    // пробуем красиво распарсить FastAPI error
    if let apiErr = try? JSONDecoder().decode(FastAPIError.self, from: data) {
        throw APIError(statusCode: http.statusCode, message: apiErr.humanMessage)
    }

    let raw = String(data: data, encoding: .utf8) ?? ""
    throw APIError(statusCode: http.statusCode, message: raw)

} catch let e as URLError {
    // Человеческая ошибка сети (например, если baseUrl не доступен с iPhone)
    throw APIError(statusCode: -1, message: "Сеть недоступна: \(e.localizedDescription)")
}
}

// Удобно для GET без body
func request<T: Decodable>(
    _ endpoint: APIEndpoint,
    token: String? = nil
) async throws -> T {
    try await request(endpoint, body: Optional<Int>.none, token: token)
}
}

```

```

// ===== File 28/66: DelegationApp/Core/Services/Networking/AddressSearchService.swift =====
// AddressSearchService.swift
// iCuno test / DelegationApp

```

```

import Foundation
import YandexMapsMobile

final class AddressSearchService {

    private let searchManager: YMKSearchManager?
    private var searchSession: YMKSearchSession?
    private let isEnabled: Bool

    init() {
        // // В превью отключаем сервис.
        // if RuntimeEnvironment.isPreview {
        //     self.searchManager = nil
        //     self.isEnabled = false
        //     return
        // }

        YandexMapConfigurator.configureIfNeeded()

        let managerType: YMKSearchManagerType = .combined
        let search = YMKSearch.sharedInstance()
        self.searchManager = search?.createSearchManager(with: managerType)
        self.isEnabled = (self.searchManager != nil)
    }

    func searchAddress(
        _ text: String,
        completion: @escaping (YMKPoint?) -> Void
    ) {
        let trimmed = text.trimmingCharacters(in: .whitespacesAndNewlines)
        guard !trimmed.isEmpty else {
            completion(nil)
            return
        }
    }
}

```

```

    }

    // В превью просто ничего не ищем.
    guard isEnabled, let searchManager else {
        completion(nil)
        return
    }

    let bbox = YMKBoundingBox(
        southWest: YMKPoint(latitude: -85.0, longitude: -180.0),
        northEast: YMKPoint(latitude: 85.0, longitude: 180.0)
    )
    let geometry = YMKGeometry(boundingBox: bbox)

    let options = YMKSearchOptions()
    options.geometry = true

    searchSession = searchManager.submit(
        withText: trimmed,
        geometry: geometry,
        searchOptions: options
    ) { [weak self] response, error in
        defer { self?.searchSession = nil }

        if let error {
            print("Search error: \(error)")
            completion(nil)
            return
        }

        guard
            let collection = response?.collection,
            let firstItem = collection.children.first,
            let obj = firstItem.obj,
            let point = obj.geometry.first?.point
        else {
            completion(nil)
            return
        }

        completion(point)
    }
}

// ===== File 29/66: DelegationApp/Core/Services/Networking/Endpoints.swift =====
import Foundation

enum Endpoints {
    static let baseUrl: URL = AppConfig.apiBaseUrl
}

enum HTTPMethod: String {
    case GET, POST
}

enum APIEndpoint {
    case register
    case login
    case me

    // Announcements (Ads)
    case createAnnouncement
    case myAnnouncements
    case publicAnnouncements

```

```

var path: String {
    switch self {
        case .register: return "auth/register"
        case .login: return "auth/login"
        case .me: return "me"

        case .createAnnouncement: return "announcements"
        case .myAnnouncements: return "announcements/me"
        case .publicAnnouncements: return "announcements/public"
    }
}

var method: HTTPMethod {
    switch self {
        case .register, .login, .createAnnouncement:
            return .POST
        case .me, .myAnnouncements, .publicAnnouncements:
            return .GET
    }
}

var url: URL {
    Endpoints.baseURL.appendingPathComponent(path)
}
}

// ===== File 30/66: DelegationApp/Core/Services/ProfileService.swift =====
//
// ProfileService.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

import Foundation

protocol ProfileService {
    func loadProfile() -> Profile
    func loadReviews() -> [Review]
}

// ===== File 31/66: DelegationApp/Core/Services/SessionStore.swift =====
import Foundation
import Security

@MainActor
final class SessionStore: ObservableObject {

    // MARK: - Published state
    @Published private(set) var token: String?
    @Published private(set) var me: MeResponse?
    @Published var errorText: String?
    @Published private(set) var isRestoring: Bool = true
    @Published private(set) var isBusy: Bool = false

    // MARK: - Private
    private let auth: AuthService
    private let keychainKey = "icuno.jwt.access_token"

    // MARK: - Init
    init(auth: AuthService) {
        self.auth = auth
    }

```

```

// =====
// DEV: если авторизация выключена –
// сразу пускаем внутрь и НИЧЕГО не проверяем
// =====
if !AppConfig.authEnabled {
    self.token = "DEV_TOKEN"
    self.me = MeResponse(id: "dev", email: "dev@local", role: "user")
    self.isRestoring = false
    return
}

// Читаем токен при старте
self.token = Keychain.readString(key: keychainKey)

// При запуске – пробуем восстановить (НО без “вечной” блокировки UI)
Task { await self.restoreSession() }

}

// MARK: - Computed
var isAuthorized: Bool { token != nil }

// MARK: - Public actions

/// Восстановление сессии при старте приложения.
/// ВАЖНО: UI не должен “висеть” пока сеть думает.
func restoreSession() async {
    // Сразу снимаем экран “Проверяем сессию...”
    isRestoring = false

    guard token != nil else { return }

    // Проверку токена делаем отдельной задачей (не блокируем rootView)
    Task { [weak self] in
        guard let self else { return }
        await self.validateTokenInBackground()
    }
}

func register(email: String, password: String) async {
    await runAuthFlow(email: email, password: password) {
        let t = try await auth.register(email: email, password: password)
        setTokenAndStore(t.access_token)
        try await loadMe()
    }
}

func login(email: String, password: String) async {
    await runAuthFlow(email: email, password: password) {
        let t = try await auth.login(email: email, password: password)
        setTokenAndStore(t.access_token)
        try await loadMe()
    }
}

func loadMe() async throws {
    guard let token else {
        throw NSError(domain: "SessionStore", code: 0,
            userInfo: [NSLocalizedStringKey: "Нет токена"])
    }
    let profile = try await auth.me(token: token)
    self.me = profile
}

func logout() {
    clearSession()
}

```

```

// MARK: - Background validation

private func validateTokenInBackground() async {
    guard token != nil else { return }

    do {
        // Если сервер недоступен (например, baseUrl не тот) – не выкидываем сразу пользователя,
        // а просто показываем ошибку, чтобы не было бесконечной загрузки.
        // try await withTimeout(seconds: 5) {
        //     try await loadMe()
        // }
        try await withTimeout(seconds: 5) {
            try await self.loadMe()
        }

    } catch is TimeoutError {
        self.errorText = "Не удалось проверить сессию (таймаут). Проверь API Base URL."
    } catch {
        // Если токен реально невалиден/просрочен – чистим
        clearSession()
        self.errorText = error.localizedDescription
    }
}

// MARK: - Helpers

private func runAuthFlow(
    email: String,
    password: String,
    action: () async throws -> Void
) async {
    errorText = nil

    let trimmedEmail = email.trimmingCharacters(in: .whitespacesAndNewlines)
    let trimmedPass = password.trimmingCharacters(in: .whitespacesAndNewlines)

    guard !trimmedEmail.isEmpty, !trimmedPass.isEmpty else {
        errorText = "Заполни email и пароль"
        return
    }

    isBusy = true
    defer { isBusy = false }

    do {
        try await action()
    } catch {
        errorText = error.localizedDescription
    }
}

private func setTokenAndStore(_ value: String) {
    token = value
    Keychain.saveString(value, key: keychainKey)
}

private func clearSession() {
    token = nil
    me = nil
    Keychain.delete(key: keychainKey)
}

// MARK: - Timeout helper

private struct TimeoutError: LocalizedError {
    var errorDescription: String? { "Таймаут" }
}

```

```

private func withTimeout<T>(
    seconds: Double,
    operation: @escaping @Sendable () async throws -> T
) async throws -> T {
    try await withThrowingTaskGroup(of: T.self) { group in
        group.addTask {
            try await operation()
        }
        // group.addTask {
        //     try await Task.sleep(nanoseconds: UInt64(seconds * 1_000_000_000))
        //     throw TimeoutError()
        // }

        group.addTask { [seconds] in
            try await Task.sleep(nanoseconds: UInt64(seconds * 1_000_000_000))
            throw Self.TimeoutError()
        }

        guard let result = try await group.next() else {
            group.cancelAll()
            throw TimeoutError()
        }
        group.cancelAll()
        return result
    }
}

enum Keychain {

    static func saveString(_ value: String, key: String) {
        guard let data = value.data(using: .utf8) else { return }

        // 1) Сначала удаляем старое значение (если было)
        delete(key: key)

        // 2) Создаём запись
        let query: [String: Any] = [
            kSecClass as String: kSecClassGenericPassword,
            kSecAttrAccount as String: key,
            kSecValueData as String: data,
            // можно добавить доступность, чтобы работало предсказуемо

            kSecAttrAccessible as String: kSecAttrAccessibleAfterFirstUnlock
        ]

        SecItemAdd(query as CFDictionary, nil)
    }

    static func readString(key: String) -> String? {
        let query: [String: Any] = [
            kSecClass as String: kSecClassGenericPassword,
            kSecAttrAccount as String: key,
            kSecReturnData as String: true,
            kSecMatchLimit as String: kSecMatchLimitOne
        ]

        var item: AnyObject?
        let status = SecItemCopyMatching(query as CFDictionary, &item)

        guard status == errSecSuccess,
              let data = item as? Data,
              let str = String(data: data, encoding: .utf8)
        else {
            return nil
        }
    }
}

```

```

        return str
    }

    static func delete(key: String) {
        let query: [String: Any] = [
            kSecClass as String: kSecClassGenericPassword,
            kSecAttrAccount as String: key
        ]

        SecItemDelete(query as CFDictionary)
    }
}

// ===== File 32/66: DelegationApp/Core/Services/TaskService.swift =====
//
// TaskService.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

import Foundation

protocol TaskService {
    func loadNearbyTasks() -> [TaskItem]
    func loadRouteTasks() -> [TaskItem]
}

// ===== File 33/66: DelegationApp/Core/Theme/Theme.swift =====
//
// Theme.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

import SwiftUI

enum Theme {
    enum ColorToken {
        static let turquoise = Color.hex("#3CC8C4")
        static let white = Color.hex("#FFFFFF")
        static let milk = Color.hex("#F7F3E9")
        static let peach = Color.hex("#FFC9A6")
        static let textPrimary = Color.black.opacity(0.9)
        static let textSecondary = Color.black.opacity(0.6)
        static let shadow = Color.black.opacity(0.08)
    }

    enum Radius {
        static let s: CGFloat = 10
        static let m: CGFloat = 16
        static let l: CGFloat = 24
        static let xl: CGFloat = 28
    }

    enum Spacing {
        static let xs: CGFloat = 6
        static let s: CGFloat = 8
        static let m: CGFloat = 12
        static let l: CGFloat = 16
        static let xl: CGFloat = 20
        static let xxl: CGFloat = 24
    }
}

```

```

enum Shadow {
    static let soft = ShadowStyle(radius: 16, y: 8, opacity: 0.10)
    struct ShadowStyle {
        let radius: CGFloat
        let y: CGFloat
        let opacity: Double
    }
}

extension View {
    /// Мягкая карточная тень под iOS
    func softCardShadow() -> some View {
        shadow(color: Theme.ColorToken.shadow, radius: Theme.Shadow.soft.radius, x: 0, y: Theme.Shadow.soft.y)
    }
}

```

```

// ===== File 34/66: DelegationApp/Core/Utils/Extentions/Color+Hex.swift =====
//
// Color+Hex.swift
// iCuno test
//
// Created by maftuna murtazaeva on 08.11.2025.
//

```

```

import SwiftUI

extension Color {
    static func hex(_ hex: String) -> Color {
        let hex = hex.trimmingCharacters(in: CharacterSet.alphanumerics.inverted)
        var int: UInt64 = 0; Scanner(string: hex).scanHexInt64(&int)
        let a, r, g, b: UInt64
        switch hex.count {
            case 3: (a,r,g,b) = (255, (int >> 8) * 17, (int >> 4 & 0xF) * 17, (int & 0xF) * 17)
            case 6: (a,r,g,b) = (255, int >> 16, int >> 8 & 0xFF, int & 0xFF)
            case 8: (a,r,g,b) = (int >> 24, int >> 16 & 0xFF, int >> 8 & 0xFF, int & 0xFF)
            default: (a,r,g,b) = (255,0,0,0)
        }
        return Color(.sRGB,
                    red: Double(r)/255, green: Double(g)/255,
                    blue: Double(b)/255, opacity: Double(a)/255)
    }
}

```

```

// ===== File 35/66: DelegationApp/Features/Ads/AdsView/AdsScreen.swift =====
import SwiftUI

```

```

/// Экран "Мои объявления".
struct MyAdsScreen: View {
    @StateObject private var vm: MyAdsViewModel
    @State private var selectedFilter: AdsFilter = .active
    @State private var showNewAdSheet: Bool = false

    init(vm: MyAdsViewModel) {
        _vm = StateObject(wrappedValue: vm)
    }

    var body: some View {
        ZStack(alignment: .bottom) {
            content
            newAdButton
        }
        .navigationTitle("Мои объявления")
    }
}

```

```

.navigationBarTitleDisplayMode(.inline)
.background(Theme.ColorToken.milk.ignoresSafeArea())
.task { await vm.reload() }
.refreshable { await vm.reload() }
.sheet(isPresented: $showNewAdSheet) {
    CreateAdFlowHost(
        service: vm.service,
        session: vm.session
    ) { _ in
        Task { await vm.reload() }
    }
}
.alert(
    "Ошибка",
    isPresented: Binding(
        get: { vm.errorText != nil },
        set: { _ in vm.errorText = nil }
    )
) {
    Button("Ок", role: .cancel) {}
} message: {
    Text(vm.errorText ?? "")
}
}

private var content: some View {
    ScrollView {
        VStack(alignment: .leading, spacing: Theme.Spacing.l) {
            summarySection
            filtersSection
            listSection
        }
        .padding(.horizontal, Theme.Spacing.l)
        .padding(.top, Theme.Spacing.l)
        .padding(.bottom, 100)
    }
}

private var summarySection: some View {
    VStack(alignment: .leading, spacing: 10) {
        Text("Статистика")
            .font(.system(size: 18, weight: .bold))
        HStack(spacing: 12) {
            StatPill(title: "Активные", value: vm.activeCount)
            StatPill(title: "Черновики", value: vm.draftCount)
            StatPill(title: "Архив", value: vm.archivedCount)
        }
    }
    .padding(Theme.Spacing.l)
    .background(
        RoundedRectangle(cornerRadius: Theme.Radius.l, style: .continuous)
            .fill(Color.white.opacity(0.6))
    )
    .softCardShadow()
}

private var filtersSection: some View {
    ScrollView(.horizontal, showsIndicators: false) {
        HStack(spacing: 10) {
            ForEach(AdsFilter.allCases) { f in
                FilterChip(
                    title: "\(f.rawValue) \(count(for: f))",
                    isSelected: selectedFilter == f
                ) {
                    selectedFilter = f
                }
            }
        }
    }
}

```

```

        .padding(.vertical, 2)
    }
}

private func count(for filter: AdsFilter) -> Int {
    switch filter {
    case .active: return vm.activeCount
    case .drafts: return vm.draftCount
    case .archived: return vm.archivedCount
    }
}

private var listSection: some View {
    Group {
        if vm.isLoading && vm.items.isEmpty {
            VStack(spacing: 12) {
                ProgressView()
                Text("Загружаем объявления...")
                    .foregroundColor(.secondary)
            }
            .frame(maxWidth: .infinity)
            .padding(.top, 30)
        } else {
            let list = vm.filteredItems(for: selectedFilter)

            if list.isEmpty {
                EmptyState()
            } else {
                VStack(spacing: 12) {
                    ForEach(list) { item in
                        AnnouncementCard(item: item)
                    }
                }
            }
        }
    }
}

private var newAdButton: some View {
    Button {
        showNewAdSheet = true
    } label: {
        HStack(spacing: 10) {
            Image(systemName: "plus.circle.fill")
                .font(.system(size: 18, weight: .bold))
            Text("Новое объявление")
                .font(.system(size: 16, weight: .bold))
        }
        .foregroundColor(.white)
        .padding(.vertical, 14)
        .frame(maxWidth: .infinity)
        .background(
            RoundedRectangle(cornerRadius: Theme.Radius.l, style: .continuous)
                .fill(Theme.ColorToken.turquoise)
        )
        .softCardShadow()
    }
    .padding(.horizontal, Theme.Spacing.l)
    .padding(.bottom, 90)
}

// MARK: - UI bits

private struct StatPill: View {
    let title: String
    let value: Int

```

```

var body: some View {
    VStack(alignment: .leading, spacing: 4) {
        Text(title)
            .font(.system(size: 12, weight: .semibold))
            .foregroundColor(.secondary)
        Text("\(value)")
            .font(.system(size: 18, weight: .bold))
    }
    .padding(.vertical, 10)
    .padding(.horizontal, 12)
    .background(
        RoundedRectangle(cornerRadius: 14, style: .continuous)
            .fill(Theme.ColorToken.milk.opacity(0.65))
    )
}

}

//private struct FilterChip: View {
//    let title: String
//    let isSelected: Bool
//    let tap: () -> Void
//
//    var body: some View {
//        Button(action: tap) {
//            Text(title)
//                .font(.system(size: 14, weight: .semibold))
//                .foregroundColor(isSelected ? .white : .primary)
//                .padding(.vertical, 8)
//                .padding(.horizontal, 12)
//                .background(
//                    RoundedRectangle(cornerRadius: 14, style: .continuous)
//                        .fill(isSelected ? Theme.ColorToken.turquoise : Color.white.opacity(0.55))
//                )
//                .overlay(
//                    RoundedRectangle(cornerRadius: 14, style: .continuous)
//                        .stroke(Theme.ColorToken.turquoise.opacity(0.25), lineWidth: 1)
//                )
//            }
//        .buttonStyle(.plain)
//    }
//}

private struct AnnouncementCard: View {
    let item: AnnouncementDTO

    var body: some View {
        VStack(alignment: .leading, spacing: 10) {
            HStack(alignment: .top) {
                VStack(alignment: .leading, spacing: 6) {
                    Text(item.title)
                        .font(.system(size: 16, weight: .bold))
                        .foregroundColor(.primary)

                    Text(categorySubtitle(item.category))
                        .font(.system(size: 13, weight: .semibold))
                        .foregroundColor(.secondary)
                }

                Spacer()

                StatusBadge(status: item.status)
            }
        }
        .padding(Theme.Spacing.l)
        .background(
            RoundedRectangle(cornerRadius: Theme.Radius.l, style: .continuous)
                .fill(Color.white.opacity(0.6))
        )
    }
}

```

```

        )
        .softCardShadow()
    }

    private func categorySubtitle(_ raw: String) -> String {
        switch raw {
        case "delivery": return "Доставка и поручения"
        case "help": return "Помощь"
        default: return raw
        }
    }
}

private struct StatusBadge: View {
    let status: String

    var body: some View {
        Text(title)
            .font(.system(size: 12, weight: .bold))
            .foregroundColor(.white)
            .padding(.vertical, 6)
            .padding(.horizontal, 10)
            .background(Capsule().fill(color))
    }

    private var title: String {
        switch status {
        case "draft": return "Черновик"
        case "archived": return "Архив"
        default: return "Активно"
        }
    }

    private var color: Color {
        switch status {
        case "draft": return Color.gray.opacity(0.75)
        case "archived": return Color.black.opacity(0.65)
        default: return Theme.ColorToken.turquoise
        }
    }
}

private struct EmptyState: View {
    var body: some View {
        VStack(spacing: 10) {
            Image(systemName: "doc.text.magnifyingglass")
                .font(.system(size: 34, weight: .bold))
                .foregroundColor(.secondary)
            Text("Здесь пока пусто")
                .font(.system(size: 16, weight: .bold))
            Text("Создайте первое объявление — оно появится в списке.")
                .font(.system(size: 14, weight: .medium))
                .foregroundColor(.secondary)
                .multilineTextAlignment(.center)
                .padding(.horizontal, 24)
        }
        .frame(maxWidth: .infinity)
        .padding(.top, 30)
    }
}

// ===== File 36/66: DelegationApp/Features/Ads/AdView/NewAdCategoryScreen.swift =====
import SwiftUI

struct NewAdCategoryScreen: View {
    @ObservedObject var draft: CreateAdDraft

```

```

let onClose: () -> Void
let onFinish: (AnnouncementDTO) -> Void

private let accent = Theme.ColorToken.turquoise

var body: some View {
    ScrollView {
        VStack(alignment: .leading, spacing: 16) {
            header

            VStack(spacing: 16) {
                NavigationLink {
                    NewDeliveryAdFormScreen(
                        draft: draft,
                        accent: accent,
                        onFinish: onFinish
                    )
                    .onAppear { draft.category = .delivery }
                } label: {
                    CategoryCard(
                        title: CreateAdDraft.Category.delivery.title,
                        subtitle: CreateAdDraft.Category.delivery.subtitle,
                        systemImage: "shippingbox.fill",
                        tint: accent
                    )
                }
                .buttonStyle(.plain)

                NavigationLink {
                    NewHelpAdFormScreen(
                        draft: draft,
                        accent: accent,
                        onFinish: onFinish
                    )
                    .onAppear { draft.category = .help }
                } label: {
                    CategoryCard(
                        title: CreateAdDraft.Category.help.title,
                        subtitle: CreateAdDraft.Category.help.subtitle,
                        systemImage: "hands.sparkles.fill",
                        tint: accent
                    )
                }
                .buttonStyle(.plain)
            }
        }
        .padding(.horizontal, 20)
        .padding(.top, 12)
        .padding(.bottom, 24)
    }
    .navigationBarBackButtonHidden(true)
    .toolbar {
        ToolbarItem(placement: .topBarLeading) {
            Button(action: onClose) {
                Image(systemName: "xmark")
                    .font(.system(size: 16, weight: .bold))
                    .foregroundColor(.primary)
                    .padding(8)
                    .background(Circle().fill(Color.white.opacity(0.65)))
            }
        }
    }
}

private var header: some View {
    VStack(alignment: .leading, spacing: 6) {
        Text("Новое объявление")
        .font(.system(size: 28, weight: .bold))
    }
}

```

```

        Text("Выберите тип объявления")
            .font(.system(size: 16, weight: .medium))
            .foregroundColor(.secondary)
    }
}

// MARK: - Category Card

private struct CategoryCard: View {
    let title: String
    let subtitle: String
    let systemImage: String
    let tint: Color

    var body: some View {
        HStack(alignment: .top, spacing: 14) {
            ZStack {
                RoundedRectangle(cornerRadius: 14, style: .continuous)
                    .fill(tint.opacity(0.18))
                Image(systemName: systemImage)
                    .font(.system(size: 20, weight: .bold))
                    .foregroundColor(tint)
            }
            .frame(width: 54, height: 54)

            VStack(alignment: .leading, spacing: 6) {
                Text(title)
                    .font(.system(size: 18, weight: .bold))
                    .foregroundColor(.primary)
                Text(subtitle)
                    .font(.system(size: 14, weight: .medium))
                    .foregroundColor(.secondary)
            }

            Spacer()

            Image(systemName: "chevron.right")
                .font(.system(size: 14, weight: .semibold))
                .foregroundColor(Color.secondary)
        }
        .padding(16)
        .background(
            RoundedRectangle(cornerRadius: 18, style: .continuous)
                .fill(Color.white.opacity(0.6))
        )
        .overlay(
            RoundedRectangle(cornerRadius: 18, style: .continuous)
                .stroke(tint.opacity(0.18), lineWidth: 1)
        )
    }
}

// ===== File 37/66: DelegationApp/Features/Ads/CreateAdFlow/AdAudienceScreen.swift =====
//
// AdAudienceScreen.swift
// iCuno test
//
// Created by maftuna murtazaeva on 18.02.2026.
//

import SwiftUI

struct AdAudienceScreen: View {
    @EnvironmentObject private var vm: CreateAdFlowViewModel

```

```

@ObservedObject var draft: CreateAdDraft
let accent: Color
let onFinish: (AnnouncementDTO) -> Void

@State private var showError: Bool = false
@State private var errorText: String = ""

var body: some View {
    VStack(spacing: 0) {
        ScrollView {
            VStack(alignment: .leading, spacing: 16) {
                titleBlock
                optionsCard
                statusHint
            }
            .padding(20)
            .padding(.top, 6)
        }

        CreateAdBottomButton(
            title: vm.isSubmitting ? "Публикуем..." : "Опубликовать",
            accent: accent
        ) {
            Task {
                let created = await vm.submit(draft: draft)
                if let created {
                    onFinish(created)
                } else if let txt = vm.errorText {
                    errorText = txt
                    showError = true
                } else {
                    errorText = "Не удалось опубликовать"
                    showError = true
                }
            }
        }
        .disabled(vm.isSubmitting)
    }
    .navigationBarBackButtonHidden(true)
    .toolbar { backToolbar }
    .alert("Ошибка", isPresented: $showError) {
        Button("Ок", role: .cancel) {}
    } message: {
        Text(errorText)
    }
}

private var titleBlock: some View {
    VStack(alignment: .leading, spacing: 6) {
        Text("Кому показывать объявление")
            .font(.system(size: 28, weight: .bold))
        Text("Выберите аудиторию (можно поменять позже).")
            .font(.system(size: 15, weight: .medium))
            .foregroundColor(.secondary)
    }
}

private var optionsCard: some View {
    CreateAdSectionCard(
        title: "Аудитория",
        subtitle: nil,
        accent: accent
    ) {
        VStack(alignment: .leading, spacing: 10) {
            ForEach(CreateAdDraft.Audience.allCases) { a in
                AudienceRow(title: a.title, isSelected: draft.audience == a) {
                    draft.audience = a
                }
            }
        }
    }
}

```

```

        }
    }
}

private var statusHint: some View {
    CreateAdSectionCard(
        title: "Статус",
        subtitle: "Сейчас публикуем как активное объявление. Черновики добавим позже.",
        accent: accent
    ) {
        Text("После публикации объявление появится в разделе \"Мои объявления\".")
            .font(.system(size: 14, weight: .medium))
            .foregroundColor(.secondary)
    }
}

private var backToolbar: some ToolbarContent {
    ToolbarItem(placement: .topBarLeading) {
        CreateAdBackButton()
    }
}

private struct AudienceRow: View {
    let title: String
    let isSelected: Bool
    let tap: () -> Void

    var body: some View {
        Button(action: tap) {
            HStack(spacing: 10) {
                Image(systemName: isSelected ? "checkmark.circle.fill" : "circle")
                    .foregroundColor(isSelected ? Theme.ColorToken.turquoise : Color.secondary)
                Text(title)
                    .font(.system(size: 16, weight: .semibold))
                    .foregroundColor(.primary)
                Spacer()
            }
            .padding(.vertical, 6)
        }
        .buttonStyle(.plain)
    }
}

```

```

// ===== File 38/66: DelegationApp/Features/Ads/CreateAdFlow/AdContactScreen.swift =====
//
//  AdContactScreen.swift
//  iCuno test
//
//  Created by maftuna murtazaeva on 18.02.2026.
//

```

```

import SwiftUI

struct AdContactScreen: View {
    @ObservedObject var draft: CreateAdDraft
    let accent: Color
    let onFinish: (AnnouncementDTO) -> Void

    @State private var goAudience: Bool = false

    var body: some View {
        VStack(spacing: 0) {
            ScrollView {
                VStack(alignment: .leading, spacing: CreateAdUI.Spacing.l) {

```

```

Text("Как с вами связаться")
    .font(.system(size: 28, weight: .bold))
    .padding(.top, 6)

CreateAdSectionCard(
    title: "Контакты",
    subtitle: "Можно оставить пустым и заполнить позже в профиле – пока MVP.",
    accent: accent
) {
    CreateAdTextField(
        label: "Имя",
        placeholder: "Введите имя",
        text: $draft.contactName
    )
    CreateAdTextField(
        label: "Телефон",
        placeholder: "+7 ...",
        text: $draft.contactPhone,
        keyboard: .phonePad
    )
}

CreateAdSectionCard(
    title: "Предпочтительный способ связи",
    subtitle: nil,
    accent: accent
) {
    Picker("", selection: $draft.contactMethod) {
        ForEach(CreateAdDraft.ContactMethod.allCases) { m in
            Text(m.title).tag(m)
        }
    }
    .pickerStyle(.segmented)
}

CreateAdSectionCard(
    title: "Каналы (позже)",
    subtitle: "Например: Telegram/WhatsApp – добавишь позже.",
    accent: accent
) {
    Text("Пока оставляем как точку расширения.")
        .font(.system(size: 14, weight: .medium))
        .foregroundColor(.secondary)
}

}
.padding(.horizontal, 20)
.padding(.bottom, 24)
}

CreateAdBottomButton(title: "Продолжить", accent: accent) {
    goAudience = true
}
}

.navigationBarBackButtonHidden(true)
.toolbar { backToolbar }
.navigationDestination(isPresented: $goAudience) {
    AdAudienceScreen(
        draft: draft,
        accent: accent,
        onFinish: onFinish
    )
}
}

private var backToolbar: some ToolbarContent {
    ToolbarItem(placement: .topBarLeading) {
        CreateAdBackButton()
    }
}

```

```
}  
}
```

```
// ===== File 39/66: DelegationApp/Features/Ads/CreateAdFlow/CreateAdBackButton.swift =====  
//  
// CreateAdBackButton.swift  
// iCuno test  
//  
// Created by maftuna murtazaeva on 18.02.2026.  
//
```

```
import SwiftUI
```

```
/// Единая кнопка "Назад" для create-flow, чтобы не дублировать код по экранам.
```

```
struct CreateAdBackButton: View {  
    @Environment(\.dismiss) private var dismiss  
  
    var body: some View {  
        Button(action: { dismiss() }) {  
            Image(systemName: "chevron.left")  
                .font(.system(size: 16, weight: .bold))  
                .foregroundColor(.primary)  
                .padding(8)  
                .background(Circle().fill(Color.white.opacity(0.65)))  
        }  
    }  
}
```

```
// ===== File 40/66: DelegationApp/Features/Ads/CreateAdFlow/CreateAdFlowHost.swift =====  
//  
// CreateAdFlowHost.swift  
// iCuno test  
//  
// Created by maftuna murtazaeva on 18.02.2026.  
//
```

```
import SwiftUI
```

```
struct CreateAdFlowHost: View {  
    @Environment(\.dismiss) private var dismiss  
  
    @StateObject private var draft = CreateAdDraft()  
    @StateObject private var vm: CreateAdFlowViewModel  
  
    let onCreate: (AnnouncementDTO) -> Void  
  
    init(  
        service: AnnouncementService,  
        session: SessionStore,  
        onCreate: @escaping (AnnouncementDTO) -> Void  
    ) {  
        _vm = StateObject(wrappedValue: CreateAdFlowViewModel(service: service, session: session))  
        self.onCreate = onCreate  
    }  
  
    var body: some View {  
        NavigationStack {  
            NewAdCategoryScreen(  
                draft: draft,  
                onClose: { dismiss() },  
                onFinish: { created in  
                    onCreate(created)  
                    dismiss()  
                }  
            )  
        }  
    }  
}
```

```

        )
    }
    .environmentObject(vm)
    .background(Theme.ColorToken.milk.ignoresSafeArea())
}
}

```

```

// ===== File 41/66: DelegationApp/Features/Ads/CreateAdFlow/NewDeliveryAdFormScreen.swift =====
//
// NewDeliveryAdFormScreen.swift
// iCuno test
//
// Created by maftuna murtazaeva on 18.02.2026.
//

```

```
import SwiftUI
```

```

struct NewDeliveryAdFormScreen: View {
    @ObservedObject var draft: CreateAdDraft
    let accent: Color
    let onFinish: (AnnouncementDTO) -> Void

    @State private var goContact: Bool = false
    @State private var showValidationAlert: Bool = false
    @State private var validationText: String = ""

    var body: some View {
        ScrollView {
            VStack(alignment: .leading, spacing: CreateAdUI.Spacing.l) {
                header

                CreateAdSectionCard(
                    title: "Основное",
                    subtitle: "Коротко опишите задачу и бюджет (опционально).",
                    accent: accent
                ) {
                    CreateAdTextField(
                        label: "Название",
                        placeholder: "Например: Забрать посылку и привезти",
                        text: $draft.title
                    )

                    CreateAdValueField(
                        label: "Бюджет (опционально)",
                        placeholder: "0",
                        trailing: "",
                        text: $draft.budget
                    )
                }

                CreateAdSectionCard(
                    title: "Маршрут",
                    subtitle: "Откуда и куда нужно доставить.",
                    accent: accent
                ) {
                    CreateAdTextField(
                        label: "Адрес забора",
                        placeholder: "Введите адрес",
                        text: $draft.pickupAddress
                    )

                    CreateAdTextField(
                        label: "Адрес доставки",
                        placeholder: "Введите адрес",
                        text: $draft.dropoffAddress
                    )
                }
            }
        }
    }
}

```

```

    }

    CreateAdSectionCard(
        title: "Время",
        subtitle: "Когда можно выполнить поручение.",
        accent: accent
    ) {
        DatePicker("Начало", selection: $draft.startDate, displayedComponents: [.date,
.hourAndMinute])
        .font(.system(size: 16, weight: .semibold))

        CreateAdToggleRow(title: "Указать время окончания", isOn: $draft.hasEndTime)

        if draft.hasEndTime {
            DatePicker("Окончание", selection: $draft.endDate, displayedComponents: [.date,
.hourAndMinute])
            .font(.system(size: 16, weight: .semibold))
        }
    }

    CreateAdSectionCard(
        title: "Габариты (опционально)",
        subtitle: "Если важно – укажите размеры.",
        accent: accent
    ) {
        HStack(spacing: 12) {
            CreateAdTextField(label: "Длина", placeholder: "см", text: $draft.cargoLength,
keyboard: .decimalPad)
            CreateAdTextField(label: "Ширина", placeholder: "см", text: $draft.cargoWidth,
keyboard: .decimalPad)
            CreateAdTextField(label: "Высота", placeholder: "см", text: $draft.cargoHeight,
keyboard: .decimalPad)
        }
    }

    CreateAdSectionCard(
        title: "Подъём (опционально)",
        subtitle: "Если нужно поднять/спустить груз.",
        accent: accent
    ) {
        CreateAdTextField(label: "Этаж", placeholder: "Например: 5", text: $draft.floor, keyboard:
.numberPad)

        CreateAdToggleRow(title: "Есть лифт", isOn: $draft.hasElevator)
        CreateAdToggleRow(title: "Нужен грузчик", isOn: $draft.needLoader)
    }

    CreateAdSectionCard(
        title: "Описание",
        subtitle: "Любые детали, которые помогут исполнителю.",
        accent: accent
    ) {
        CreateAdTextArea(
            label: "Комментарий",
            placeholder: "Например: позвонить за 10 минут до приезда...",
            text: $draft.notes
        )
    }

    // Заглушка под медиа – оставляем "задел", но без логики загрузки
    CreateAdSectionCard(
        title: "Фото и видео (позже)",
        subtitle: "Пока без загрузки. Оставлено как точка расширения.",
        accent: accent
    ) {
        Text("Подключишь PhotosPicker + upload в Worker/Service.")
        .font(.system(size: 14, weight: .medium))
        .foregroundColor(.secondary)
    }
}

```

```

        }
        .padding(.horizontal, 20)
        .padding(.top, 10)
        .padding(.bottom, 24)
    }
    .navigationBarBackButtonHidden(true)
    .toolbar { backToolbar }
    .navigationDestination(isPresented: $goContact) {
        AdContactScreen(
            draft: draft,
            accent: accent,
            onFinish: onFinish
        )
    }
    .alert("Проверьте данные", isPresented: $showValidationAlert) {
        Button("Ок", role: .cancel) {}
    } message: {
        Text(validationText)
    }
    .safeAreaInset(edge: .bottom) {
        CreateAdBottomButton(title: "Продолжить", accent: accent) {
            let res = draft.validateForCurrentStep()
            if res.ok {
                goContact = true
            } else {
                validationText = res.message
                showValidationAlert = true
            }
        }
    }
}

private var header: some View {
    Text("Доставка и поручения")
        .font(.system(size: 28, weight: .bold))
        .padding(.top, 6)
}

private var backToolbar: some ToolbarContent {
    ToolbarItem(placement: .topBarLeading) {
        CreateAdBackButton()
    }
}
}

```

```

// ===== File 42/66: DelegationApp/Features/Ads/CreateAdFlow/NewHelpAdFormScreen.swift =====
//
// NewHelpAdFormScreen.swift
// iCuno test
//
// Created by maftuna murtazaeva on 18.02.2026.
//

```

```

import SwiftUI

struct NewHelpAdFormScreen: View {
    @ObservedObject var draft: CreateAdDraft
    let accent: Color
    let onFinish: (AnnouncementDTO) -> Void

    @State private var goContact: Bool = false
    @State private var showValidationAlert: Bool = false
    @State private var validationText: String = ""

    var body: some View {
        ScrollView {

```

```

VStack(alignment: .leading, spacing: CreateAdUI.Spacing.l) {
    header

    CreateAdSectionCard(
        title: "Основное",
        subtitle: "Коротко опишите задачу и бюджет (опционально).",
        accent: accent
    ) {
        CreateAdTextField(
            label: "Название",
            placeholder: "Например: Помочь донести сумки",
            text: $draft.title
        )

        CreateAdValueField(
            label: "Бюджет (опционально)",
            placeholder: "0",
            trailing: "",
            text: $draft.budget
        )
    }

    CreateAdSectionCard(
        title: "Адрес",
        subtitle: "Где нужна помощь.",
        accent: accent
    ) {
        CreateAdTextField(
            label: "Адрес",
            placeholder: "Введите адрес",
            text: $draft.helpAddress
        )
    }

    CreateAdSectionCard(
        title: "Время",
        subtitle: "Когда можно выполнить поручение.",
        accent: accent
    ) {
        DatePicker("Начало", selection: $draft.startDate, displayedComponents: [.date,
.hourAndMinute])
        .font(.system(size: 16, weight: .semibold))

        CreateAdToggleRow(title: "Указать время окончания", isOn: $draft.hasEndTime)

        if draft.hasEndTime {
            DatePicker("Окончание", selection: $draft.endDate, displayedComponents: [.date,
.hourAndMinute])
            .font(.system(size: 16, weight: .semibold))
        }
    }

    CreateAdSectionCard(
        title: "Описание",
        subtitle: "Любые детали, которые помогут исполнителю.",
        accent: accent
    ) {
        CreateAdTextArea(
            label: "Комментарий",
            placeholder: "Например: работа на 30 минут, перчатки не нужны...",
            text: $draft.notes
        )
    }

    CreateAdSectionCard(
        title: "Фото и видео (позже)",
        subtitle: "Пока без загрузки. Оставлено как точка расширения.",
        accent: accent
    )

```

```

        ) {
            Text("Подключишь PhotosPicker + upload в Worker/Service.")
                .font(.system(size: 14, weight: .medium))
                .foregroundColor(.secondary)
        }
    }
    .padding(.horizontal, 20)
    .padding(.top, 10)
    .padding(.bottom, 24)
}
.navigationBarBackButtonHidden(true)
.toolbar { backToolbar }
.navigationDestination(isPresented: $goContact) {
    AdContactScreen(
        draft: draft,
        accent: accent,
        onFinish: onFinish
    )
}
.alert("Проверьте данные", isPresented: $showValidationAlert) {
    Button("Ок", role: .cancel) {}
} message: {
    Text(validationText)
}
.safeAreaInset(edge: .bottom) {
    CreateAdBottomButton(title: "Продолжить", accent: accent) {
        let res = draft.validateForCurrentStep()
        if res.ok {
            goContact = true
        } else {
            validationText = res.message
            showValidationAlert = true
        }
    }
}
}

private var header: some View {
    Text("Помощь")
        .font(.system(size: 28, weight: .bold))
        .padding(.top, 6)
}

private var backToolbar: some ToolbarContent {
    ToolbarItem(placement: .topBarLeading) {
        CreateAdBackButton()
    }
}
}
}

```

```

// ===== File 43/66: DelegationApp/Features/Ads/CreateAdUI/CreateAdUI.swift =====
//
// CreateAdUI.swift
// iCuno test
//
// Created by maftuna murtazaeva on 18.02.2026.
//

```

```

import SwiftUI
import UIKit

```

```

enum CreateAdUI {
    enum Spacing {
        static let xs: CGFloat = 8
        static let s: CGFloat = 12
        static let m: CGFloat = 16
    }
}

```

```

        static let l: CGFloat = 20
    }

    enum Radius {
        static let card: CGFloat = 18
    }

    enum Palette {
        static let turquoise = Theme.ColorToken.turquoise
        static let beige = Theme.ColorToken.milk
    }
}

// MARK: - Section Card

struct CreateAdSectionCard<Content: View>: View {
    let title: String
    let subtitle: String?
    let accent: Color
    @ViewBuilder let content: Content

    var body: some View {
        VStack(alignment: .leading, spacing: CreateAdUI.Spacing.m) {
            VStack(alignment: .leading, spacing: 6) {
                Text(title)
                    .font(.system(size: 18, weight: .bold))

                if let subtitle {
                    Text(subtitle)
                        .font(.system(size: 14, weight: .medium))
                        .foregroundColor(.secondary)
                }
            }

            content
        }
        .padding(CreateAdUI.Spacing.l)
        .background(
            RoundedRectangle(cornerRadius: CreateAdUI.Radius.card, style: .continuous)
                .fill(Color.white.opacity(0.55))
        )
        .overlay(
            RoundedRectangle(cornerRadius: CreateAdUI.Radius.card, style: .continuous)
                .stroke(accent.opacity(0.25), lineWidth: 1)
        )
    }
}

// MARK: - Fields

struct CreateAdTextField: View {
    let label: String
    let placeholder: String
    @Binding var text: String
    var keyboard: UIKeyboardType = .default

    var body: some View {
        VStack(alignment: .leading, spacing: 6) {
            Text(label)
                .font(.system(size: 12, weight: .semibold))
                .foregroundColor(.secondary)

            TextField(placeholder, text: $text)
                .keyboardType(keyboard)
                .textInputAutocapitalization(.sentences)
                .font(.system(size: 16, weight: .semibold))
                .padding(.vertical, 10)
        }
    }
}

```

```

        Divider().opacity(0.35)
    }
}

struct CreateAdValueField: View {
    let label: String
    let placeholder: String
    let trailing: String
    @Binding var text: String

    var body: some View {
        VStack(alignment: .leading, spacing: 6) {
            Text(label)
                .font(.system(size: 12, weight: .semibold))
                .foregroundColor(.secondary)

            HStack(spacing: 8) {
                TextField(placeholder, text: $text)
                    .keyboardType(.decimalPad)
                    .font(.system(size: 16, weight: .semibold))

                Spacer(minLength: 0)

                Text(trailing)
                    .font(.system(size: 14, weight: .semibold))
                    .foregroundColor(.secondary)
            }
            .padding(.vertical, 10)

            Divider().opacity(0.35)
        }
    }
}

struct CreateAdToggleRow: View {
    let title: String
    @Binding var isOn: Bool

    var body: some View {
        HStack {
            Text(title)
                .font(.system(size: 16, weight: .semibold))
            Spacer()
            Toggle("", isOn: $isOn)
                .labelsHidden()
        }
        .padding(.vertical, 6)
    }
}

struct CreateAdTextArea: View {
    let label: String
    let placeholder: String
    @Binding var text: String

    var body: some View {
        VStack(alignment: .leading, spacing: 6) {
            Text(label)
                .font(.system(size: 12, weight: .semibold))
                .foregroundColor(.secondary)

            ZStack(alignment: .topLeading) {
                if text.isEmpty {
                    Text(placeholder)
                        .foregroundColor(Color.secondary.opacity(0.8))
                        .padding(.top, 10)
                        .padding(.leading, 4)
                }
            }
        }
    }
}

```

```

        }

        TextEditor(text: $text)
            .frame(minHeight: 110)
            .scrollContentBackground(.hidden)
            .font(.system(size: 16, weight: .regular))
        }
        .padding(.vertical, 6)

        Divider().opacity(0.35)
    }
}

// MARK: - Bottom Button

struct CreateAdBottomButton: View {
    let title: String
    let accent: Color
    let action: () -> Void

    var body: some View {
        Button(action: action) {
            Text(title)
                .font(.system(size: 16, weight: .bold))
                .foregroundColor(.white)
                .frame(maxWidth: .infinity)
                .padding(.vertical, 16)
                .background(
                    RoundedRectangle(cornerRadius: 16, style: .continuous)
                    .fill(accent)
                )
                .shadow(color: accent.opacity(0.25), radius: 12, x: 0, y: 6)
        }
        .padding(.horizontal, 20)
        .padding(.vertical, 12)
        .background(.ultraThinMaterial)
    }
}

```

```

// ===== File 44/66: DelegationApp/Features/Ads/Model/CreateAdDraft.swift =====
//
// CreateAdDraft.swift
// iCuno test
//
// Created by maftuna murtazaeva on 18.02.2026.
//

```

```
import Foundation
```

```
@MainActor
```

```
final class CreateAdDraft: ObservableObject {

    enum Category: String, CaseIterable, Identifiable {
        case delivery = "delivery"
        case help = "help"
        var id: String { rawValue }

        var title: String {
            switch self {
            case .delivery: return "Доставка и поручения"
            case .help: return "Помощь"
            }
        }

        var subtitle: String {

```

```

        switch self {
        case .delivery: return "Посылки, покупки, курьерские услуги"
        case .help: return "Помощь руками, поддержка, бытовые задачи"
        }
    }
}

enum ContactMethod: String, CaseIterable, Identifiable {
    case callsAndMessages = "calls_and_messages"
    case messagesOnly = "messages_only"
    case callsOnly = "calls_only"
    var id: String { rawValue }

    var title: String {
        switch self {
        case .callsAndMessages: return "Звонки и сообщения"
        case .messagesOnly: return "Только сообщения"
        case .callsOnly: return "Только звонки"
        }
    }
}

enum Audience: String, CaseIterable, Identifiable {
    case individuals = "individuals"
    case business = "business"
    case both = "both"
    var id: String { rawValue }

    var title: String {
        switch self {
        case .individuals: return "Частные лица"
        case .business: return "Бизнес"
        case .both: return "Частные лица и бизнес"
        }
    }
}

// MARK: - Common
@Published var category: Category?
@Published var title: String = ""
@Published var budget: String = ""

// MARK: - Delivery fields
@Published var pickupAddress: String = ""
@Published var dropoffAddress: String = ""
@Published var startDate: Date = .now
@Published var hasEndTime: Bool = false
@Published var endDate: Date = .now

@Published var cargoLength: String = ""
@Published var cargoWidth: String = ""
@Published var cargoHeight: String = ""

@Published var floor: String = ""
@Published var hasElevator: Bool = true
@Published var needLoader: Bool = false

// MARK: - Help fields
@Published var helpAddress: String = ""

// MARK: - Notes + future hooks
@Published var notes: String = ""
/// Заглушка под будущую загрузку фото/видео (позже: PhotosPicker / upload).
@Published var mediaLocalIdentifiers: [String] = []
/// Заглушка под будущую обработку текста/фото моделями.
@Published var aiHints: [String] = []

// MARK: - Contacts

```

```

@Published var contactName: String = ""
@Published var contactPhone: String = ""
@Published var contactMethod: ContactMethod = .callsAndMessages

// MARK: - Audience
@Published var audience: Audience = .both

// MARK: - Validation
func validateForCurrentStep() -> (ok: Bool, message: String) {
    guard let category else { return (false, "Выберите категорию") }
    guard !title.trimmingCharacters(in: .whitespacesAndNewlines).isEmpty else {
        return (false, "Заполните название объявления")
    }
    switch category {
    case .delivery:
        if pickupAddress.trimmingCharacters(in: .whitespacesAndNewlines).isEmpty {
            return (false, "Укажите адрес забора")
        }
        if dropoffAddress.trimmingCharacters(in: .whitespacesAndNewlines).isEmpty {
            return (false, "Укажите адрес доставки")
        }
    case .help:
        if helpAddress.trimmingCharacters(in: .whitespacesAndNewlines).isEmpty {
            return (false, "Укажите адрес")
        }
    }
    return (true, "")
}

// MARK: - Mapping to request
func toCreateRequest() -> CreateAnnouncementRequest {
    let iso = ISO8601DateFormatter()

    var data: [String: JSONValue] = [:]

    data["category"] = .string(category?.rawValue ?? "")
    data["budget"] = budget.isEmpty ? .null : .string(budget)

    data["contact_name"] = contactName.isEmpty ? .null : .string(contactName)
    data["contact_phone"] = contactPhone.isEmpty ? .null : .string(contactPhone)
    data["contact_method"] = .string(contactMethod.rawValue)

    data["audience"] = .string(audience.rawValue)

    data["notes"] = notes.isEmpty ? .null : .string(notes)
    data["media_local_identifiers"] = .array(mediaLocalIdentifiers.map { .string($0) })
    data["ai_hints"] = .array(aiHints.map { .string($0) })

    if let category {
        switch category {
        case .delivery:
            data["pickup_address"] = .string(pickupAddress)
            data["dropoff_address"] = .string(dropoffAddress)
            data["start_at"] = .string(iso.string(from: startDate))
            data["has_end_time"] = .bool(hasEndTime)
            data["end_at"] = hasEndTime ? .string(iso.string(from: endDate)) : .null

            data["cargo_length"] = cargoLength.isEmpty ? .null : .string(cargoLength)
            data["cargo_width"] = cargoWidth.isEmpty ? .null : .string(cargoWidth)
            data["cargo_height"] = cargoHeight.isEmpty ? .null : .string(cargoHeight)

            data["floor"] = floor.isEmpty ? .null : .string(floor)
            data["has_elevator"] = .bool(hasElevator)
            data["need_loader"] = .bool(needLoader)

        case .help:
            data["address"] = .string(helpAddress)
            data["start_at"] = .string(iso.string(from: startDate))
        }
    }
}

```

```

        data["has_end_time"] = .bool(hasEndTime)
        data["end_at"] = hasEndTime ? .string(iso.string(from: endDate)) : .null
    }
}

let categoryRaw = category?.rawValue ?? "unknown"
return CreateAnnouncementRequest(
    category: categoryRaw,
    title: title,
    status: "active",
    data: data
)
}
}

```

```

// ===== File 45/66: DelegationApp/Features/Ads/ViewModel/CreateAdFlowViewModel.swift =====
//
// CreateAdFlowViewModel.swift
// iCuno test
//
// Created by maftuna murtazaeva on 18.02.2026.
//

```

```
import Foundation
```

```
@MainActor
```

```
final class CreateAdFlowViewModel: ObservableObject {
```

```
    @Published var isSubmitting: Bool = false
```

```
    @Published var errorText: String?
```

```
    private let service: AnnouncementService
```

```
    private let session: SessionStore
```

```
    init(service: AnnouncementService, session: SessionStore) {
```

```
        self.service = service
```

```
        self.session = session
```

```
    }
```

```
    func submit(draft: CreateAdDraft) async -> AnnouncementDTO? {
```

```
        guard let token = session.token else {
```

```
            errorText = "Нет токена сессии"
```

```
            return nil
```

```
        }
```

```
        isSubmitting = true
```

```
        defer { isSubmitting = false }
```

```
        do {
```

```
            let req = draft.toCreateRequest()
```

```
            let created = try await service.createAnnouncement(token: token, request: req)
```

```
            return created
```

```
        } catch {
```

```
            errorText = error.localizedDescription
```

```
            return nil
```

```
        }
```

```
    }
```

```
}
```

```

// ===== File 46/66: DelegationApp/Features/Ads/ViewModel/MyAdsViewModel.swift =====
//

```

```

// MyAdsViewModel.swift
// iCuno test
//

```

```

// Created by maftuna murtazaeva on 18.02.2026.

```

```

//

import Foundation

@MainActor
final class MyAdsViewModel: ObservableObject {
    @Published var isLoading: Bool = false
    @Published var errorText: String?
    @Published private(set) var items: [AnnouncementDTO] = []

    let service: AnnouncementService
    let session: SessionStore

    init(service: AnnouncementService, session: SessionStore) {
        self.service = service
        self.session = session
    }

    func reload() async {
        guard let token = session.token else {
            errorText = "Нет токена сессии"
            return
        }

        isLoading = true
        defer { isLoading = false }

        do {
            items = try await service.myAnnouncements(token: token)
        } catch {
            errorText = error.localizedDescription
        }
    }

    // MARK: - Derived counts
    var activeCount: Int { items.filter { $0.status == "active" }.count }
    var draftCount: Int { items.filter { $0.status == "draft" }.count }
    var archivedCount: Int { items.filter { $0.status == "archived" }.count }

    func filteredItems(for filter: AdsFilter) -> [AnnouncementDTO] {
        switch filter {
        case .active:
            return items.filter { $0.status == "active" }
        case .drafts:
            return items.filter { $0.status == "draft" }
        case .archived:
            return items.filter { $0.status == "archived" }
        }
    }
}

enum AdsFilter: String, CaseIterable, Identifiable {
    case active = "Активные"
    case drafts = "Черновики"
    case archived = "Архив"

    var id: String { rawValue }
}

// ===== File 47/66: DelegationApp/Features/Auth/AuthScreen.swift =====
import SwiftUI

struct AuthScreen: View {
    @EnvironmentObject var container: AppContainer

    @State private var email: String = ""

```

```

@State private var password: String = ""
@State private var isLoginMode: Bool = false

var body: some View {
    VStack(spacing: 16) {
        Text(isLoginMode ? "Вход" : "Регистрация")
            .font(.system(size: 24, weight: .bold))

        TextField("Email (например: name@mail.com)", text: $email)
            .keyboardType(.emailAddress)
            .textInputAutocapitalization(.never)
            .autocorrectionDisabled(true)
            .textFieldStyle(.roundedBorder)

        SecureField("Пароль", text: $password)
            .textFieldStyle(.roundedBorder)

        if let err = container.session.errorText {
            Text(err)
                .foregroundColor(.red)
                .font(.system(size: 13))
                .multilineTextAlignment(.center)
        }

        Button {
            Task {
                if isLoginMode {
                    await container.session.login(email: email, password: password)
                } else {
                    await container.session.register(email: email, password: password)
                }
            }
        } label: {
            HStack(spacing: 10) {
                if container.session.isBusy {
                    ProgressView()
                }
                Text(isLoginMode ? "Войти" : "Создать аккаунт")
            }
        }
        .buttonStyle(.borderedProminent)
        .disabled(container.session.isBusy)

        Button {
            isLoginMode.toggle()
            container.session.errorText = nil
        } label: {
            Text(isLoginMode ? "Нет аккаунта? Зарегистрироваться" : "Уже есть аккаунт? Войти")
                .font(.system(size: 14))
        }
    }
    .padding()
}

```

```

// ===== File 48/66: DelegationApp/Features/Chats/View/ChatsScreen.swift =====
import SwiftUI

```

```

struct ChatsScreen: View {
    @StateObject var vm: ChatsViewModel
    init(vm: ChatService) { _vm = StateObject(wrappedValue: .init(service: vm)) }
    init(vm: ChatsViewModel) { _vm = StateObject(wrappedValue: vm) }

    var body: some View {
        List {

```

```

        ForEach(vm.chats) { chat in
            HStack(spacing: 12) {
                Circle()
                    .fill(LinearGradient(colors: [Theme.ColorToken.turquoise, Theme.ColorToken.peach],
                        startPoint: .topLeading, endPoint: .bottomTrailing))
                    .frame(width: 44, height: 44)
                    .overlay(Text(chat.initials).foregroundColor(.white).font(.system(size: 17, weight:
.bold)))

                VStack(alignment: .leading, spacing: 4) {
                    HStack {
                        Text(chat.name).font(.system(size: 16, weight: .semibold))
                        Spacer()
                        Text(chat.time).foregroundColor(Theme.ColorToken.textSecondary).font(.system(size:
13))
                    }
                    Text(chat.lastMessage)
                        .foregroundColor(Theme.ColorToken.textSecondary)
                        .lineLimit(1)
                        .font(.system(size: 14))
                }
                if chat.unreadCount > 0 {
                    Text("\(chat.unreadCount)")
                        .font(.system(size: 12, weight: .bold))
                        .padding(.vertical, 4).padding(.horizontal, 8)
                        .background(Capsule().fill(Theme.ColorToken.turquoise))
                        .foregroundColor(.white)
                }
            }
            .listRowBackground(Theme.ColorToken.white)
        }
        .scrollContentBackground(.hidden)
        .background(Theme.ColorToken.milk)
        .navigationTitle("Сообщения")
    }
}

##Preview {
    // ChatsScreen(
    //     vm: ChatsViewModel(service: MockChatService())
    // )
}

// ===== File 49/66: DelegationApp/Features/Chats/ViewModel/ChatsViewModel.swift =====
import Foundation

final class ChatsViewModel: ObservableObject {
    @Published var chats: [ChatPreview] = []

    private let service: ChatService
    init(service: ChatService) {
        self.service = service
        self.chats = service.loadChats()
    }
}

// ===== File 50/66: DelegationApp/Features/Chats.swift =====
//
// Chats.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

```

```
// ===== File 51/66: DelegationApp/Features/Map/MapScreen/MapScreen.swift =====
import SwiftUI

struct MapScreen: View {
    @StateObject private var vm: MapViewModel
    private let mapMode: MapDisplayMode

    init(
        vm: MapViewModel,
        mapMode: MapDisplayMode = MapDisplayConfig.defaultMode()
    ) {
        _vm = StateObject(wrappedValue: vm)
        self.mapMode = mapMode
    }

    var body: some View {
        ZStack(alignment: .top) {
            mapArea

            VStack(spacing: 5) {
                Spacer().frame(height: 50)
                searchBar
                errorLabel
                chipsRow
                Spacer()
            }
            .padding(.horizontal, 16)
            .padding(.top, 8)
            .ignoresSafeArea()
        }
        .task {
            await vm.reloadPins()
        }
    }

    private var searchBar: some View {
        HStack(spacing: 8) {
            Image(systemName: "magnifyingglass")
                .foregroundColor(Theme.ColorToken.textSecondary)

            TextField("Введите адрес", text: $vm.searchText, onCommit: vm.performSearch)
                .textFieldStyle(.plain)

            if !vm.searchText.isEmpty {
                Button {
                    vm.searchText = ""
                } label: {
                    Image(systemName: "xmark.circle.fill")
                        .foregroundColor(Theme.ColorToken.textSecondary)
                        .imageScale(.medium)
                }
            }

            Button(action: vm.performSearch) {
                Text("Найти")
                    .font(.system(size: 15, weight: .semibold))
            }
        }
        .padding(.horizontal, 12)
        .padding(.vertical, 10)
        .background(.ultraThinMaterial)
        .clipShape(RoundedRectangle(cornerRadius: 16, style: .continuous))
        .softCardShadow()
    }
}
```

```

private var errorLabel: some View {
    Group {
        if let message = vm.errorMessage {
            Text(message)
                .font(.caption)
                .foregroundColor(.red)
                .frame(maxWidth: .infinity, alignment: .leading)
        }
    }
}

private var chipsRow: some View {
    ScrollView(.horizontal, showsIndicators: false) {
        HStack(spacing: Theme.Spacing.m) {
            ForEach(vm.chips, id: \.self) { chip in
                FilterChip(
                    title: chip,
                    isSelected: Binding(
                        get: { vm.selected.contains(chip) },
                        set: { isOn in
                            if isOn { vm.selected.insert(chip) }
                            else { vm.selected.remove(chip) }
                        }
                    )
                )
            }
        }
    }
}

private var mapArea: some View {
    MapCanvasView(centerPoint: $vm.centerPoint, pins: vm.pins, mode: mapMode)
        .ignoresSafeArea(edges: .top)
}

}

// ===== File 52/66: DelegationApp/Features/Map/MapViewModel/MapViewModel.swift =====
import SwiftUI
import YandexMapsMobile
import Foundation

enum MapDisplayMode {
    case real
    case placeholder
}

enum MapDisplayConfig {
    static func defaultMode() -> MapDisplayMode {
        #if DEBUG
            return .real
        #else
            return .real
        #endif
    }
}

struct MapCanvasView: View {
    @Binding var centerPoint: YMKPoint?
    let pins: [YMKPoint]
    let mode: MapDisplayMode

    var body: some View {
        Group {
            switch mode {
                case .real:

```

```

        YandexMapView(centerPoint: $centerPoint, pins: pins)
    case .placeholder:
        Rectangle()
            .fill(Theme.ColorToken.milk)
            .overlay(
                VStack(spacing: 8) {
                    Image(systemName: "map")
                        .font(.system(size: 32))
                        .foregroundColor(Theme.ColorToken.textSecondary)
                    Text("Map placeholder")
                        .font(.system(size: 14, weight: .medium))
                        .foregroundColor(Theme.ColorToken.textSecondary)
                }
            )
    }
}
}
}
}
}

```

@MainActor

```

final class MapViewModel: ObservableObject {
    // MARK: - Фильтры
    @Published var chips: [String] = [
        "Купить", "Доставить", "Забрать",
        "Помочь", "Перенести", "Другое"
    ]
    @Published var selected: Set<String> = []

    // MARK: - Моковые задачи (пока оставляем)
    @Published var tasks: [TaskItem] = []

    // MARK: - Объявления на карте
    @Published private(set) var announcements: [AnnouncementDTO] = []
    @Published var pins: [YMKPoint] = []

    // MARK: - Поиск и карта
    @Published var searchText: String = ""
    @Published var centerPoint: YMKPoint?
    @Published var errorMessage: String?

    private let service: TaskService
    private let announcementService: AnnouncementService
    private let searchService: AddressSearchService

    init(
        service: TaskService,
        announcementService: AnnouncementService,
        searchService: AddressSearchService = AddressSearchService()
    ) {
        self.service = service
        self.announcementService = announcementService
        self.searchService = searchService

        self.tasks = service.loadNearbyTasks()
        self.centerPoint = YMKPoint(latitude: 55.751244, longitude: 37.618423)
    }

    func toggle(_ chip: String) {
        if selected.contains(chip) { selected.remove(chip) }
        else { selected.insert(chip) }
    }

    func performSearch() {
        let query = searchText.trimmingCharacters(in: .whitespacesAndNewlines)
        guard !query.isEmpty else {
            errorMessage = nil
            return
        }
    }
}

```

```

        searchService.searchAddress(query) { [weak self] point in
            DispatchQueue.main.async {
                guard let self else { return }
                if let point {
                    self.centerPoint = point
                    self.errorMessage = nil
                } else {
                    self.errorMessage = "Адрес не найден"
                }
            }
        }
    }

    func reloadPins() async {
        do {
            let list = try await announcementService.publicAnnouncements()
            self.announcements = list
            self.pins = list.compactMap { Self.extractPoint(from: $0) }
        } catch {
            self.errorMessage = error.localizedDescription
        }
    }

    private static func extractPoint(from a: AnnouncementDTO) -> YMKPoint? {
        guard let pointVal = a.data["point"]?.objectValue else { return nil }
        guard
            let lat = pointVal["lat"]?.doubleValue,
            let lon = pointVal["lon"]?.doubleValue
        else { return nil }

        return YMKPoint(latitude: lat, longitude: lon)
    }
}

// ===== File 53/66: DelegationApp/Features/Profile/View/ProfileEditScreen.swift =====
////
//// ProfileEditScreen.swift
//// iCuno test
////
//// Created by maftuna murtazaeva on 23.01.2026.
////
//
//import SwiftUI
//import PhotosUI
//import Foundation
//
//struct UserSettingsView: View {
//    @State private var selectedItem: PhotosPickerItem? = nil
//    @State private var showAgePicker = false
//    @State private var selectedImage: UIImage? = nil
//
//    var body: some View {
//        VStack {
//            HStack { Spacer(); saveButton }
//            ScrollView {
//
//                profileImage
//
//                nicknameSection
//                randomNameButton.padding(.bottom, 20)
//
//                bioSection.padding(.bottom, 20)
//                ageSection.padding(.bottom, 20)
//
//            }
//        }
//    }

```

```

//         genderPicker.padding(.bottom, 20)
//         Spacer()
//     }
// }
//// .onAppear { viewModel.onAppear() }
//// .alert("Сохранено!", isPresented: $viewModel.showSaveBanner) {
////     Button("OK", role: .cancel) {}
//// }
//// .sheet(isPresented: $showAgePicker) { agePicker }
// }
//
// private var saveButton: some View {
//     Button("Сохранить") { }
//     .foregroundColor(.red)
//     .padding(.horizontal, 25)
// }
//
//
// var genderPicker: some View {
//     VStack(alignment: .leading) {
//         Text("Ваш пол: Мужской")
//         Text("Укажите свой пол для анкеты")
//         .font(.footnote)
//
//         Picker("", selection: Binding(
//             get: { viewModel.gender },
//             set: { viewModel.genderSelected($0) }
//         )) {
//             ForEach(Gender1.allCases) { g in
//                 Text(g.rawValue).tag(g)
//             }
//         }
//         .pickerStyle(.segmented)
//     }
//     .padding(.horizontal, 25)
// }
//
// var profileImage: some View {
//     VStack {
//         if let image = viewModel.image {
//             Image(uiImage: image)
//                 .resizable()
//                 .frame(width: 130, height: 130)
//                 .cornerRadius(65)
//                 .padding(.top, 25)
//         } else {
//             Text("Изображение не выбрано")
//                 .foregroundColor(.gray)
//                 .padding()
//         }
//
//         PhotosPicker(
//             selection: $selectedItem,
//             matching: .images,
//             photoLibrary: .shared()
//         ) {
//             Text("Изменить фотографию")
//                 .foregroundColor(Color(.label))
//         }
//         .onChange(of: selectedItem) { newItem in
//             Task {
//                 await viewModel.handleImageSelection(newItem)
//             }
//         }
//     }
//     .padding()
// }
//

```

```

//
// private var nicknameSection: some View {
//     VStack(alignment: .leading) {
//         Text("Никнейм: \(viewModel.name)")
//         Text("Никнейм будет отображён в анкете")
//         .font(.footnote)
//         TextField("Введите никнейм...",
//             text: Binding(get: { viewModel.name },
//                 set: viewModel.nameChanged))
//         .textFieldStyle(.roundedBorder)
//         .overlay(RoundedRectangle(cornerRadius: 20)
//             .stroke(Color(.label).opacity(0.4), lineWidth: 1))
//     }
//     .padding(.horizontal, 25)
// }
// private var randomNameButton: some View {
//     Button("СЛУЧАЙНЫЙ НИКНЕЙМ") { viewModel.nicknameTapped() }
//     .frame(maxWidth: .infinity)
//     .padding(.vertical, 10)
//     .background(Color(.systemGroupedBackground))
//     .cornerRadius(20)
//     .overlay(RoundedRectangle(cornerRadius: 20)
//         .stroke(Color(.label).opacity(0.4), lineWidth: 1))
//     .padding(.horizontal, 25)
//     .foregroundColor(Color(.label))
// }
//
// private var bioSection: some View {
//     VStack(alignment: .leading) {
//         Text("О себе")
//         Text("Напиши пару слов о себе, чтобы заинтересовать собеседника")
//         .font(.footnote)
//         TextField("О себе",
//             text: Binding(get: { viewModel.bio },
//                 set: viewModel.bioChanged))
//         .textFieldStyle(.roundedBorder)
//         .overlay(RoundedRectangle(cornerRadius: 20)
//             .stroke(Color(.label).opacity(0.4), lineWidth: 1))
//     }
//     .padding(.horizontal, 25)
// }
//
// private var ageSection: some View {
//     VStack(alignment: .leading) {
//         Text("Ваш возраст: \(viewModel.age)")
//         Text("Укажите свой возраст для анкеты")
//         .font(.footnote)
//         Button("УКАЖИТЕ ВОЗРАСТ") { showAgePicker = true }
//         .frame(maxWidth: .infinity)
//         .padding(.vertical, 10)
//         .background(Color(.systemGroupedBackground))
//         .cornerRadius(20)
//         .overlay(RoundedRectangle(cornerRadius: 20)
//             .stroke(Color(.label).opacity(0.4), lineWidth: 1))
//         .foregroundColor(Color(.label))
//     }
//     .padding(.horizontal, 25)
// }
//
// private var agePicker: some View {
//     VStack(spacing: 0) {
//         Text("Выберите ваш возраст")
//         .font(.headline)
//         .padding()
//         .frame(maxWidth: .infinity)
//         .background(Color(.systemGray6))

```

```
//      Divider()
//      Picker("Возраст", selection: Binding(
//          get: { viewModel.age },
//          set: viewModel.ageSelected
//      )) {
//          ForEach(10..<100, id: \.self) { Text("\($0)").tag($0) }
//      }
//      .pickerStyle(.wheel)
//      .labelsHidden()
//      .frame(height: 150)
//      Divider()
//      Button("OK") { showAgePicker = false }
//          .frame(maxWidth: .infinity)
//  }
//  .background(Color(.systemBackground))
//  .cornerRadius(16).padding()
//
//  }
//}
//
//
//
/////#Preview {
/////     UserSettingsModule.build()
/////}
```

```
// ===== File 54/66: DelegationApp/Features/Profile/View/ProfileScreen.swift =====
import SwiftUI
```

```

struct ProfileScreen: View {
    @StateObject var vm: ProfileViewModel
    init(vm: ProfileViewModel) { _vm = StateObject(wrappedValue: vm) }

    var body: some View {
        ScrollView {
            VStack(spacing: Theme.Spacing.l) {
                header
                settings
                support
                reviews
            }
            .padding(.bottom, 32)
        }
        .background(Theme.ColorToken.milk)
        .navigationTitle("Профиль")
        .toolbar(.hidden, for: .navigationBar)
    }

    private var header: some View {
        VStack(alignment: .leading, spacing: 12) {
            HStack(alignment: .center, spacing: 14) {
                Circle().fill(Theme.ColorToken.milk).frame(width: 56, height: 56)
                    .overlay(Image(systemName: "person.fill").font(.system(size:
26)).foregroundColor(Theme.ColorToken.turquoise))

                VStack(alignment: .leading, spacing: 6) {
                    Text(vm.profile.name).font(.system(size: 20, weight: .semibold))
                    Text(vm.profile.phone).foregroundColor(Theme.ColorToken.textSecondary)
                        .font(.system(size: 14))
                }
                Spacer()
                Text("ID")
                    .font(.system(size: 13, weight: .bold))
            }
        }
    }
}

```

```

                .padding(.vertical, 6).padding(.horizontal, 10)
                .background(RoundedRectangle(cornerRadius: 10).fill(Theme.ColorToken.peach.opacity(0.3)))
            }

            HStack(spacing: 28) {
                VStack(alignment: .leading) {
                    HStack(spacing: 6) {
                        Image(systemName: "star.fill").foregroundColor(Theme.ColorToken.peach)
                        Text("\(vm.profile.rating, specifier: "%.1f")")
                            .font(.system(size: 16, weight: .semibold))
                    }
                    Text("Рейтинг").foregroundColor(Theme.ColorToken.textSecondary).font(.system(size: 12))
                }
                VStack(alignment: .leading) {
                    Text("\(vm.profile.completed)").font(.system(size: 16, weight: .semibold))
                    Text("Выполнено").foregroundColor(Theme.ColorToken.textSecondary).font(.system(size: 12))
                }
                VStack(alignment: .leading) {
                    Text("\(vm.profile.cancelled)").font(.system(size: 16, weight: .semibold))
                    Text("Отменено").foregroundColor(Theme.ColorToken.textSecondary).font(.system(size: 12))
                }
                Spacer()
            }
        }
        .padding()

        .background(LinearGradient(colors: [Theme.ColorToken.turquoise.opacity(0.85),
Theme.ColorToken.turquoise],
                                startPoint: .topLeading, endPoint: .bottomTrailing))
        .foregroundColor(.white)
        .clipShape(RoundedRectangle(cornerRadius: Theme.Radius.xl, style: .continuous))
        .padding(.horizontal)
        .padding(.top, 12)
        .softCardShadow()
    }

    private var settings: some View {
        SectionBox(title: "Настройки") {
            ToggleRow(title: "Тёмная тема", isOn: $vm.darkMode)
            NavRow(title: "Уведомления")
            NavRow(title: "Платежи и выплаты")
        }
    }

    private var support: some View {
        SectionBox(title: "Поддержка") {
            NavRow(title: "Помощь")
            NavRow(title: "Правила и условия")
        }
    }

    private var reviews: some View {
        SectionBox(title: "Отзывы") {
            ForEach(vm.reviews) { r in
                HStack(alignment: .top, spacing: 12) {
                    Circle().fill(Theme.ColorToken.milk).frame(width: 40, height: 40)
                        .overlay(Text(r.authorInitial).font(.system(size: 16, weight: .bold)))
                    VStack(alignment: .leading, spacing: 6) {
                        HStack {
                            Text(r.authorName).font(.system(size: 15, weight: .semibold))
                            StarsView(rating: Double(r.stars))
                            Spacer()
                        }
                        Text(r.text).font(.system(size: 14)).fixedSize(horizontal: false, vertical: true)
                        Text(r.ago).font(.system(size: 12)).foregroundColor(Theme.ColorToken.textSecondary)
                    }
                    Spacer(minLength: 0)
                }
            }
        }
        .padding(.vertical, 8)
    }

```

```

        .padding(.horizontal, 8)
    }
    Button("Посмотреть все отзывы") { }
        .font(.system(size: 15, weight: .semibold))
        .frame(maxWidth: .infinity, alignment: .leading)
        .padding(.top, 6)
        .tint(Theme.ColorToken.turquoise)
        .padding()
    }
}

private struct SectionBox<Content: View>: View {
    let title: String
    @ViewBuilder var content: Content

    var body: some View {
        VStack(alignment: .leading, spacing: 8) {
            Text(title).font(.system(size: 12, weight: .bold))
                .foregroundColor(Theme.ColorToken.textSecondary)
                .padding(.horizontal)
            VStack(spacing: 0) { content }
                .background(RoundedRectangle(cornerRadius: Theme.Radius.l).fill(Theme.ColorToken.white))
                .softCardShadow()
                .padding(.horizontal)
        }
        .padding(.top, 4)
    }
}

private struct ToggleRow: View {
    let title: String
    @Binding var isOn: Bool
    var body: some View {
        HStack {
            Label(title, systemImage: "moon.fill")
                .labelStyle(.titleAndIcon)
            Spacer()
            Toggle("", isOn: $isOn).labelsHidden()
        }
        .padding()
        .background(Color.clear)
    }
}

private struct NavRow: View {
    let title: String
    var body: some View {
        HStack {
            Text(title)
            Spacer()
            Image(systemName: "chevron.right").foregroundColor(Theme.ColorToken.textSecondary)
        }
        .padding()
    }
}

// #Preview {
//     let service = MockProfileService()
//     let vm = ProfileViewModel(service: service)
//     ProfileScreen(vm: vm)
// }

// @StateObject var vm: ProfileViewModel
// init(vm: ProfileViewModel) { _vm = StateObject(wrappedValue: vm) }
```

```
// ===== File 55/66: DelegationApp/Features/Profile/ViewModel/ProfileViewModel.swift =====
```

```
import Foundation
```

```
final class ProfileViewModel: ObservableObject {
    @Published var profile: Profile
    @Published var reviews: [Review]
    @Published var darkMode: Bool = false

    private let service: ProfileService
    init(service: ProfileService) {
        self.service = service
        self.profile = service.loadProfile()
        self.reviews = service.loadReviews()
    }
}
```

```
// ===== File 56/66: DelegationApp/Features/Route/View/RouteScreen.swift =====
```

```
import SwiftUI
```

```
enum PreviewData {
    static let container = AppContainer.preview

    static let chatsVM = ChatsViewModel(service: MockChatService())
    static let mapVM = MapViewModel(
        service: MockTaskService(),
        announcementService: MockAnnouncementService()
    )
    static let routeVM = RouteViewModel(service: MockTaskService())
    static let profileVM = ProfileViewModel(service: MockProfileService())
}
```

```
struct RouteScreen: View {
    @StateObject var vm: RouteViewModel
    init(vm: RouteViewModel) { _vm = StateObject(wrappedValue: vm) }

    var body: some View {
        ScrollView {
            VStack(spacing: Theme.Spacing.l) {
                VStack(spacing: Theme.Spacing.m) {
                    RouteRow(symbol: "a.circle.fill", text: vm.pointA)
                    RouteRow(symbol: "b.circle.fill", text: vm.pointB)
                    RouteRow(symbol: "clock.fill", text: vm.time)
                }
                .padding()
                .background(RoundedRectangle(cornerRadius: Theme.Radius.l)
                    .fill(Theme.ColorToken.white))
                .softCardShadow()
                .padding(.horizontal)

                HStack {
                    Image(systemName: "arrow.forward.circle")
                    Text("45 мин · 12.5 км")
                        .font(.system(size: 16, weight: .semibold))
                    Spacer()
                    Capsule()
                        .fill(Theme.ColorToken.milk)
                        .frame(width: 36, height: 28)
                        .overlay(Text("\(vm.tasks.count)").font(.system(size: 15, weight: .semibold)))
                }
                .padding()
                .background(RoundedRectangle(cornerRadius: Theme.Radius.l)
                    .fill(Theme.ColorToken.white))
                .softCardShadow()
                .padding(.horizontal)
            }
        }
    }
}
```

```

        // Карта заглушка
        RoundedRectangle(cornerRadius: Theme.Radius.l)
            .fill(Theme.ColorToken.milk)
            .frame(height: 220)
            .overlay(Text("Карта с маршрутом").foregroundColor(Theme.ColorToken.textSecondary))
            .padding(.horizontal)

        VStack(alignment: .leading, spacing: Theme.Spacing.m) {
            Text("Задания по пути")
                .font(.system(size: 18, weight: .semibold))
            ForEach(vm.tasks) { t in
                HStack {
                    VStack(alignment: .leading, spacing: 4) {
                        Text(t.title).font(.system(size: 16, weight: .semibold))
                        Text("~\\(t.distanceKm, specifier: "%.1f") км • \\(t.etaMinutes) мин")
                            .foregroundColor(Theme.ColorToken.textSecondary)
                            .font(.system(size: 13))
                    }
                    Spacer()
                    PriceTag(price: t.price, eta: t.etaMinutes)
                }
                .padding()
            }
            .background(RoundedRectangle(cornerRadius:
Theme.Radius.m).fill(Theme.ColorToken.white))
            .softCardShadow()
        }
        .padding(.horizontal)
        .padding(.bottom, 24)
    }
}
.navigationTitle("Маршрут")
}
}

private struct RouteRow: View {
    let symbol: String
    let text: String
    var body: some View {
        HStack(spacing: 12) {
            Image(systemName: symbol)
                .foregroundColor(Theme.ColorToken.turquoise)
            Text(text)
            Spacer()
        }
        .font(.system(size: 16))
    }
}

// #Preview("RouteScreen") {
//     NavigationStack {
//         RouteScreen(vm: PreviewData.routeVM)
//     }
//     .preferredColorScheme(.light)
// }

// ===== File 57/66: DelegationApp/Features/Route/View/RouteView.swift =====
////
//// RouteView.swift
//// iCuno test
////
//// RootView с таббаром.
////
//

```

```

//import SwiftUI
//
//struct RootView: View {
//    @EnvironmentObject var container: AppContainer
//    @State private var selectedTab = 0
//
//    var body: some View {
//        TabView(selection: $selectedTab) {
//
//            // Вкладка "Карта"
//            NavigationStack {
//                MapScreen(vm: .init(service: container.taskService), mapMode: .placeholder)
//            }
//            .tabItem {
//                Label("Карта", systemImage: "map")
//            }
//            .tag(0)
//
//            // Вкладка "Маршрут"
//            NavigationStack {
//                RouteScreen(vm: .init(service: container.taskService))
//            }
//            .tabItem {
//                Label("Маршрут", systemImage: "point.topleft.down.curvedto.point.bottomright.up")
//            }
//            .tag(1)
//
//            // Новая вкладка "Объявления"
//            NavigationStack {
//                MyAdsScreen()
//            }
//            .tabItem {
//                Label("Объявления", systemImage: "rectangle.stack.badge.plus")
//            }
//            .tag(2)
//
//            // Вкладка "Чаты"
//            NavigationStack {
//                ChatsScreen(vm: .init(service: container.chatService))
//            }
//            .tabItem {
//                Label("Чаты", systemImage: "bubble.left.and.bubble.right")
//            }
//            .tag(3)
//
//            // Вкладка "Профиль"
//            NavigationStack {
//                ProfileScreen(vm: .init(service: container.profileService))
//            }
//            .tabItem {
//                Label("Профиль", systemImage: "person.circle")
//            }
//            .tag(4)
//        }
//        .background(Color.black)
//        .ignoresSafeArea()
//        .tint(Theme.ColorToken.turquoise)
//        .cornerRadius(20)
//
//        .background(.ultraThinMaterial)
//        .clipShape(RoundedRectangle(cornerRadius: 16, style: .continuous))
//        .softCardShadow()
//    }
//}
//
//import SwiftUI
//

```

```

//// MARK: - RootView с кастомным «Liquid Glass» TabBar
//struct RootView: View {
//    @EnvironmentObject var container: AppContainer
//
//    // Текущая вкладка
//    @State private var selection: AppTab = .map
//
//    // При желании можно показать бейджи, как на скрине (пример: на профиле "2")
//    private let badges: [AppTab: Int] = [.profile: 2]
//
//    var body: some View {
//        ZStack(alignment: .bottom) {
//            // Контент – позади, движется сам по себе.
//            content
//                .transition(.identity)
//
//            // Полупрозрачный «стеклянный» TabBar, закреплённый снизу
//            LiquidTabBar(selection: $selection, badges: badges)
//                .padding(.horizontal, 16)
//                .padding(.bottom, 12)
//                .allowsHitTesting(true)
//        }
//        .ignoresSafeArea(edges: .bottom)
//        .tint(Theme.ColorToken.turquoise)
//    }
//
//    // MARK: - Контент по вкладкам
//    @ViewBuilder
//    private var content: some View {
//        switch selection {
//            case .map:
//                NavigationStack {
//                    MapScreen(
//                        vm: MapViewModel(
//                            service: container.taskService,
//                            searchService: AddressSearchService()
//                        )
//                    )
//                }
//
//            case .route:
//                NavigationStack {
//                    RouteScreen(vm: RouteViewModel(service: container.taskService))
//                }
//
//            case .ads:
//                NavigationStack {
//                    MyAdsScreen()
//                }
//
//            case .chats:
//                NavigationStack {
//                    ChatsScreen(vm: ChatsViewModel(service: container.chatService))
//                }
//
//            case .profile:
//                NavigationStack {
//                    ProfileScreen(vm: ProfileViewModel(service: container.profileService))
//                }
//        }
//    }
//}

//import SwiftUI
//
//////// Главный контейнер приложения с кастомным «стеклянным» TabBar
//struct RootView: View {
//    @EnvironmentObject var container: AppContainer

```

```

//
//    /// Текущая выбранная вкладка
//    @State private var selection: AppTab = .map
//
//    /// Пример бейджа на профиле (красный кружок «2»)
//    private let badges: [AppTab: Int] = [.profile: 2]
//
//    var body: some View {
//        ZStack(alignment: .bottom) {
//            // Контент под TabBar – карта и остальные экраны
//            tabContent
//                .ignoresSafeArea() // фон двигается под таббаром
//
//            // Кастомный «Liquid Glass» TabBar
//            LiquidTabBar(selection: $selection, badges: badges)
//                .padding(.horizontal, 16)
//                .padding(.bottom, 4) // бар чуть выше, не «прилипает» к home-индикатору
//        }
//        .background(Theme.ColorToken.milk) // фон, если вдруг нет карты
//        .tint(Theme.ColorToken.turquoise)
//    }
//
//    // MARK: - Контент для каждой вкладки
//
//    @ViewBuilder
//    private var tabContent: some View {
//        switch selection {
//        case .map:
//            NavigationStack {
//                MapScreen(
//                    vm: .init(
//                        service: container.taskService,
//                        searchService: AddressSearchService()
//                    ), mapMode: .real
//                )
//            }
//
//        case .route:
//            NavigationStack {
//                RouteScreen(vm: .init(service: container.taskService))
//            }
//
//        case .ads:
//            NavigationStack {
//                MyAdsScreen()
//            }
//
//        case .chats:
//            NavigationStack {
//                ChatsScreen(vm: .init(service: container.chatService))
//            }
//
//        case .profile:
//            NavigationStack {
//                ProfileScreen(vm: .init(service: container.profileService))
//            }
//        }
//    }
//}

//import SwiftUI
//
//struct RootView: View {
//    @EnvironmentObject var container: AppContainer
//
//    var body: some View {

```

```

//      if container.session.isAuthenticated {
//          MainTabView()
//      } else {
//          AuthScreen()
//      }
//  }
//}
//
//private struct MainTabView: View {
//    @EnvironmentObject var container: AppContainer
//    @State private var selectedTab = 0
//
//    var body: some View {
//        TabView(selection: $selectedTab) {
//            NavigationStack {
//                MapScreen(vm: .init(service: container.taskService))
//            }
//            .tabItem { Label("Капра", systemImage: "map") }
//            .tag(0)
//
//            NavigationStack {
//                RouteScreen(vm: .init(service: container.taskService))
//            }
//            .tabItem { Label("Маршрут", systemImage: "point.topleft.down.curvedto.point.bottomright.up") }
//            .tag(1)
//
//            NavigationStack {
//                ChatsScreen(vm: .init(service: container.chatService))
//            }
//            .tabItem { Label("Чат", systemImage: "bubble.left.and.bubble.right") }
//            .tag(2)
//
//            NavigationStack {
//                ProfileScreen(vm: .init(service: container.profileService))
//                .toolbar {
//                    Button("Logout") { container.session.logout() }
//                }
//            }
//            .tabItem { Label("Профиль", systemImage: "person.circle") }
//            .tag(3)
//        }
//        .tint(Theme.ColorToken.turquoise)
//    }
//}

```

```

// ===== File 58/66: DelegationApp/Features/Route/ViewModel/RouteViewModel.swift =====
import Foundation

```

```

final class RouteViewModel: ObservableObject {
    @Published var pointA: String = "Пушкинская площадь"
    @Published var pointB: String = "Станция МЦК Площадь Гагарина"
    @Published var time: String = "17:00"
    @Published var tasks: [TaskItem] = []

    private let service: TaskService
    init(service: TaskService) {
        self.service = service
        self.tasks = service.loadRouteTasks()
    }
}

```

```

// ===== File 59/66: DelegationApp/Features/Untitled.swift =====
//import SwiftUI
//

```

```
//extension Color {
//    static func hex(_ hex: String) -> Color {
//        let hex = hex.trimmingCharacters(in: CharacterSet.alphanumerics.inverted)
//        var int: UInt64 = 0; Scanner(string: hex).scanHexInt64(&int)
//        let a, r, g, b: UInt64
//        switch hex.count {
//        case 3: (a,r,g,b) = (255, (int >> 8) * 17, (int >> 4 & 0xF) * 17, (int & 0xF) * 17)
//        case 6: (a,r,g,b) = (255, int >> 16, int >> 8 & 0xFF, int & 0xFF)
//        case 8: (a,r,g,b) = (int >> 24, int >> 16 & 0xFF, int >> 8 & 0xFF, int & 0xFF)
//        default:(a,r,g,b) = (255,0,0,0)
//        }
//        return Color(.sRGB,
//            red: Double(r)/255, green: Double(g)/255,
//            blue: Double(b)/255, opacity: Double(a)/255)
//    }
//}
```

```
// ===== File 60/66: DelegationApp/Others/YandexMapConfigurator.swift =====
import YandexMapsMobile
```

```
/// Централизованная настройка Yandex MapKit.
enum YandexMapConfigurator {
    private static var isConfigured = false

    static func configureIfNeeded() {
        // В SwiftUI Preview вообще не инициализируем SDK.
        if RuntimeEnvironment.isPreview { return }
        guard !isConfigured else { return }

        // сюда твой реальный ключ
        YMKMapKit.setApiKey("df3f9145-2080-42b7-9b91-b879c34236bb")
        YMKMapKit.sharedInstance()
        isConfigured = true
    }
}
```

```
// ===== File 61/66: DelegationApp/RootView.swift =====
//import SwiftUI
//
//struct RootView: View {
//    /// DI-контейнер с сервисами
//    @EnvironmentObject var container: AppContainer
//    @State private var selected = 0
//
//    var body: some View {
//        TabView(selection: $selected) {
//
//            // ? Вкладка КАРТА
//            NavigationStack {
//                MapScreen(vm: MapViewModel(service: container.taskService))
//            }
//            .tabItem {
//                Label("Карта", systemImage: "map")
//            }
//            .tag(0)
//
//            // ? Вкладка МАРШРУТ
//            NavigationStack {
//                RouteScreen(vm: RouteViewModel(service: container.taskService))
//            }
//            .tabItem {
//                Label("Маршрут", systemImage: "point.topleft.down.curvedto.point.bottomright.up")
//            }
//            .tag(1)
//        }
//    }
//}
```

```

//
//      // ? Вкладка ЧАТЫ
//      NavigationStack {
//          ChatsScreen(vm: container.chatService)
//      }
//      .tabItem {
//          Label("Чаты", systemImage: "bubble.left.and.bubble.right")
//      }
//      .tag(2)
//
//      // ? Вкладка ПРОФИЛЬ
//      NavigationStack {
//          ProfileScreen(vm: ProfileViewModel(service: container.profileService))
//      }
//      .tabItem {
//          Label("Профиль", systemImage: "person")
//      }
//      .tag(3)
//      }
//      .tint(Theme.ColorToken.turquoise)
//      .background(Theme.ColorToken.milk)
//  }
//}
////
////#Preview {
////    RootView()
////    .environmentObject(AppContainer.preview)
////}

```

```

// ===== File 62/66: iCuno test/ContentView.swift =====
//
// ContentView.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

```

```

// ===== File 63/66: iCuno test/iCuno_testApp.swift =====
//
// iCuno_testApp.swift
// iCuno test
//
// Created by maftuna murtazaeva on 07.11.2025.
//

```

```

//import SwiftUI
//
//@main
//struct iCuno_testApp: App {
//    var body: some Scene {
//        WindowGroup {
//            ContentView()
//        }
//    }
//}

```

```

// ===== File 64/66: iCuno testTests/iCuno_testTests.swift =====
//

```

```

// iCuno_testTests.swift
// iCuno testTests
//
// Created by maftuna murtazaeva on 07.11.2025.
//

import XCTest
@testable import iCuno_test

final class iCuno_testTests: XCTestCase {

    override func setUpWithError() throws {
        // Put setup code here. This method is called before the invocation of each test method in the class.
    }

    override func tearDownWithError() throws {
        // Put teardown code here. This method is called after the invocation of each test method in the
class.
    }

    func testExample() throws {
        // This is an example of a functional test case.
        // Use XCTAssert and related functions to verify your tests produce the correct results.
        // Any test you write for XCTest can be annotated as throws and async.
        // Mark your test throws to produce an unexpected failure when your test encounters an uncaught error.
        // Mark your test async to allow awaiting for asynchronous code to complete. Check the results with
assertions afterwards.
    }

    func testPerformanceExample() throws {
        // This is an example of a performance test case.
        self.measure {
            // Put the code you want to measure the time of here.
        }
    }

}

```

```

// ===== File 65/66: iCuno testUITests/iCuno_testUITests.swift =====
//
// iCuno_testUITests.swift
// iCuno testUITests
//
// Created by maftuna murtazaeva on 07.11.2025.
//

import XCTest

final class iCuno_testUITests: XCTestCase {

    override func setUpWithError() throws {
        // Put setup code here. This method is called before the invocation of each test method in the class.

        // In UI tests it is usually best to stop immediately when a failure occurs.
        continueAfterFailure = false

        // In UI tests it's important to set the initial state - such as interface orientation - required for
your tests before they run. The setUp method is a good place to do this.
    }

    override func tearDownWithError() throws {
        // Put teardown code here. This method is called after the invocation of each test method in the
class.
    }

    @MainActor

```

```

func testExample() throws {
    // UI tests must launch the application that they test.
    let app = XCUIApplication()
    app.launch()

    // Use XCTAssert and related functions to verify your tests produce the correct results.
}

@MainActor
func testLaunchPerformance() throws {
    // This measures how long it takes to launch your application.
    measure(metrics: [XCTApplicationLaunchMetric()]) {
        XCUIApplication().launch()
    }
}
}

```

```

// ===== File 66/66: iCuno testUITests/iCuno_testUITestsLaunchTests.swift =====
//
// iCuno_testUITestsLaunchTests.swift
// iCuno testUITests
//
// Created by maftuna murtazaeva on 07.11.2025.
//

```

```

import XCTest

```

```

final class iCuno_testUITestsLaunchTests: XCTestCase {

    override class var runsForEachTargetApplicationUIConfiguration: Bool {
        true
    }

    override func setUpWithError() throws {
        continueAfterFailure = false
    }

    @MainActor
    func testLaunch() throws {
        let app = XCUIApplication()
        app.launch()

        // Insert steps here to perform after app launch but before taking a screenshot,
        // such as logging into a test account or navigating somewhere in the app

        let attachment = XCTAttachment(screenshot: app.screenshot())
        attachment.name = "Launch Screen"
        attachment.lifetime = .keepAlways
        add(attachment)
    }
}

```