



NOTES:

1. ALL ARTWORK PATTERNS ARE VIEWED FROM THE TOP.
2. PLATING FINISH METHOD SHALL BE HASL
3. SOLDER MASK OVER BARE COPPER (SMOBC) SHALL BE ON BOTH SIDES.
4. MASK COLOUR IS GREEN AND TYPE IS LPI
5. BOARD THICKNESS IS 1.6 MM
6. COPPER THICKNESS
FOR OUTER LAYERS IS 35 MICRONS
FOR INNER LAYERS IS 35 MICRONS
7. PCB MATERIAL IS FR4
8. STACKUP SPECIFICATIONS IS AS FOLLOWS
9. SIGNAL TRACE WIDTH 7 MILS POWER TRACEWIDTH 20 MILS (MIN 8 MILS)
10. IF VIA IN PAD (VIP) SHOULD BE FILLED AND PLATED WITH PLANNER

DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	10.0	+3.0/-3.0	PLATED	78
▪	11.799	+3.0/-3.0	PLATED	16

62.992 MILS
(1.6 MM)

LAYER 1-TOP

LAYER 2-BOT

STACKUP INFO

