

There's a newer version of Bootstrap!

[View on GitHub](#)

# Options

Quickly customize Bootstrap with built-in variables to easily toggle global CSS preferences for controlling style and behavior.



Your new development career awaits. Check out the latest listings.


ads via Carbon

Customize Bootstrap with our built-in custom variables file and easily toggle global CSS preferences with new `$enable-*` Sass variables. Override a variable's value and recompile with `npm run test` as needed.

You can find and customize these variables for key global options in Bootstrap's `scss/_variables.scss` file.

Variable	Values	Description
<code>\$spacer</code>	<code>1rem</code> (default), or any value <code>&gt; 0</code>	Specifies the default spacer value to programmatically generate our <a href="#">spacer utilities</a> .
<code>\$enable-rounded</code>	<code>true</code> (default) or <code>false</code>	Enables predefined <code>border-radius</code> styles on various components.
<code>\$enable-shadows</code>	<code>true</code> or <code>false</code> (default)	Enables predefined decorative <code>box-shadow</code> styles on various components. Does not affect <code>box-shadows</code> used for focus states.
<code>\$enable-gradients</code>	<code>true</code> or <code>false</code> (default)	Enables predefined gradients via <code>background-image</code> styles on various components.

Variable	Values	Description
<code>\$enable-transitions</code>	<code>true</code> (default) or <code>false</code>	Enables predefined <code>transitions</code> on various components.
<code>\$enable-reduced-motion</code>	<code>true</code> (default) or <code>false</code>	Enables the <a href="#">prefers-reduced-motion media query</a> , which suppresses certain animations/transitions based on the users' browser/operating system preferences.
<code>\$enable-grid-classes</code>	<code>true</code> (default) or <code>false</code>	Enables the generation of CSS classes for the grid system (e.g. <code>.row</code> , <code>.col-md-1</code> , etc.).
<code>\$enable-caret</code>	<code>true</code> (default) or <code>false</code>	Enables pseudo element caret on <code>.dropdown-toggle</code> .
<code>\$enable-button-pointers</code>	<code>true</code> (default) or <code>false</code>	Add "hand" cursor to non-disabled button elements.
<code>\$enable-rfs</code>	<code>true</code> (default) or <code>false</code>	Globally enables <a href="#">RFS</a> .
<code>\$enable-validation-icons</code>	<code>true</code> (default) or <code>false</code>	Enables <code>background-image</code> icons within textual inputs and some custom forms for validation states.
<code>\$enable-negative-margins</code>	<code>true</code> or <code>false</code> (default)	Enables the generation of <a href="#">negative margin utilities</a> .
<code>\$enable-deprecation-messages</code>	<code>true</code> (default) or <code>false</code>	Set to <code>false</code> to hide warnings when using any of the deprecated mixins and functions that are planned to be removed in <code>v6</code> .
<code>\$enable-important-utilities</code>	<code>true</code> (default) or <code>false</code>	Enables the <code>!important</code> suffix in utility classes.



Designed and built with all the love in the world by the Bootstrap team with the help of our contributors.

Code licensed MIT, docs CC BY 3.0.

Currently v5.0.2.

Analytics by Fathom.

Links

Guides

[Home](#)

[Docs](#)

[Examples](#)

[Themes](#)

[Blog](#)

[Swag Store](#)

## Projects

[Bootstrap 5](#)

[Bootstrap 4](#)

[Icons](#)

[RFS](#)

[npm starter](#)

[Getting started](#)

[Starter template](#)

[Webpack](#)

[Parcel](#)

## Community

[Issues](#)

[Discussions](#)

[Corporate sponsors](#)

[Open Collective](#)

[Stack Overflow](#)