

LIVING DOCUMENT · UPDATED WITH EVERY CHANGE

# VDB\_Feature Implemented

---

Everything that has been built into VectoraDB so far — for each feature: **what it does**, **how it works**, **how to use it**, **how to test it**, and its honest **status**.

When a feature is added or changed, this document changes in the same commit.

**Product:** VectoraDB — serverless PostgreSQL with copy-on-write branching and a Blackbox

**Last updated:** 16 September 2026 · **Reflects:** `main @ c71ce45` (v0.8.5) + agent reachability ( `fix/agent-reachability` )

**License:** AGPL-3.0 core · Apache-2.0 client SDKs

**Source of truth:** `docs/VDB_Feature_Implemented.html` → `make feature-doc` → this PDF

**Supersedes:** `docs/vectoradb-feature-reference` (25 Aug 2026, no longer maintained)

**Method:** every entry was taken from a read of the source code and git history, with file references.

Status reflects the code; "Working" means the code path is complete, not that it was re-run for this edition unless the Test baseline section says so.

# Change log

Newest first. Every change to VectoraDB adds a row here.

| Date        | Feature(s)               | What changed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Commit / PR                         |
|-------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 16 Sep 2026 | K5, K6; known issues     | <p><b>An agent can now reach the database it is given.</b> The Agent Branch API handed back a DSN built from the container's address, which only resolves inside the VM — so on macOS and Windows an agent running on the host was given a database it could not open, while the README said "the agent connects to that dsn". Publishing a host port was the wrong fix and is deliberately refused by the design ( <code>startContainer</code> : a direct connection would bypass the Gateway, its key, TLS and the Blackbox attribution), so the agent now connects the way every other client does — through the Gateway — with two additions that keep it no more privileged than before. Its key is scoped to one branch (new <code>api_keys.scope</code> , with a migration, since the schema runs with <code>CREATE TABLE IF NOT EXISTS</code> and every existing install already has that table): <code>Authn</code> refuses a scoped key outright, so it reaches neither the control plane nor the Agent API, and the Gateway opens only the branch it names. And the Gateway logs it in as the branch's own <code>agent-&lt;id&gt;</code> role, whose password is derived from the install secret with HMAC rather than stored or passed between processes, so <code>session_user</code> is still the agent and the recorded actor is still non-forgable — <code>EnsureUserRole</code> is deliberately not called on that path, as it would reset the role's password and invalidate the DSN already issued. The key is revoked when the branch is deleted, but not on a reset, where the branch and the scope survive. Separately, the cap, the listing and the TTL reaper used <code>docker ps</code> , so a suspended agent branch — the usual state, since the Gateway suspends idle branches — escaped all three; they now use <code>docker ps -a</code> , and listings report <code>suspended</code> rather than claiming <code>ready</code> . Verified: <code>go test ./...</code> , <code>go vet</code> for macOS, Linux and Windows, six new unit tests (derivation is deterministic per branch and is not the install secret; the DSN parses, carries <code>sslmode=require</code> and omits the key in listings; the scope check rejects another branch, an empty target and a prefix match; a scoped key fails <code>userFromRequest</code> while an account key still passes; a store created in the pre-scope shape gains the column on open), plus new integration assertions that the DSN routes through the Gateway, that the agent's key cannot open <code>main</code> and is refused 401 by both HTTP APIs, and that it stops working once the branch is deleted. <code>agentDSN</code> and <code>randomPassword</code> had no callers left once the DSN changed, so both were removed with their tests, keeping the "never the superuser" assertion in <code>TestAgentGatewayDSN</code> . The VM suites still need a run.</p> | <code>fix/agent-reachability</code> |
| 16 Sep 2026 | K2, L7, K6; known issues | <p><b>The API description now matches the code, and the MCP server is documented.</b> The spec is what client generators read, and it disagreed with the handlers: <code>/api/import</code> was documented as <code>{from, as}</code> while the code reads <code>{source, target, continuous}</code> and answers with an SSE stream; branch creation was documented 200 where the handler returns 201; the ledger's <code>since / until</code> filters, the multipart fields of <code>/api/import/file</code> , <code>/api/openapi.yaml</code> and all seven <code>/auth/*</code> routes were absent; and the <code>/blackbox</code> aliases existed only in prose, so a generated client got <code>/ledger</code> alone. All of that is corrected,</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | <code>docs/api-accuracy</code>      |

the aliases are declared as path-item \$ref s (one line each, so they cannot drift from the originals), and internal/controlplane/openapi\_test.go keeps it honest: net/http.ServeMux exposes no way to enumerate its routes, so the test reads the HandleFunc literals out of controlplane , auth and agentapi and fails when a served route is undocumented or the spec names a path nobody serves. Two things the review list got wrong, found by reading the code rather than trusting the note: POST /api/pipelines genuinely returns 200, so "creates return 201" was applied only where the handler really does (branches, API keys, register); and the VECTORADB\_WEB\_ORIGIN default on the Docs page ( http://localhost:5173 ) was already correct, so it was left alone. **K6:** new docs/mcp.md documents all 16 tools with their arguments, the paste-ready client config, a stdio check, and the honest limits (no auth of its own, run\_sql as the non-superuser vdbclient , branch\_before\_change taking minutes); linked from the README and the Docs page. K6 stays Partial — authentication is still open. **L7:** the Guide drops make web-dev , adds sslmode=require to all five connection strings and moves the agent API to https://localhost:8088 ; the Docs page grows from 7 endpoints to the full set plus an "Agents over MCP" section. Verified: go test ./... , go vet for macOS, Linux and Windows, npm --prefix web run build , the spec re-parsed as OpenAPI 3.1 (48 paths, every alias pointer resolving), and scripts/test\_feature\_checklist.sh .

|             |            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                          |
|-------------|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| 16 Sep 2026 | A4, A7, M5 | <b>Windows install verified end to end, and the summary is green again.</b> A fresh install on a real Windows machine from v0.8.6 (after wsl --unregister vectoradb ) exercised everything the earlier run could not: the distro was created from the prebuilt image, "Loading the preinstalled container images" ran with no apt install of Docker or btrfs tools — so the ghcr.io tag fix works — the engine download reported "vdb-linux-amd64 from v0.8.6 verified against SHA256SUMS" (A7's first real-world proof), and setup ended with one summary carrying the working connection string and API key. Removing the installer's duplicate block had left that summary in plain text, so the engine now prints "VectoraDB is running." in green itself: a Windows-only helper turns on the console's escape-sequence handling once and falls back to plain text when output is piped or the console refuses, so install.log never collects escape codes. A4 and M5 move to verified. | fix/setup-summary-colour |
| 16 Sep 2026 | A2, A4, M5 | <b>Windows install checked on a real machine; duplicate summary removed.</b> Running the branch's installer on a Windows machine confirmed the new path: step 3 downloaded and verified the 685 MB vectoradb-distro.tar.gz (the old installer never fetched it), PATH was set and setup completed. It also showed the install ending with two near-identical "VectoraDB is running" blocks — the engine's own summary and the installer's — so the installer now prints only its log path and leaves the summary (with the connection string and API key) to vdb setup . What that run did <b>not</b> prove: it used the released v0.8.5 vdb.exe , which predates this batch, and reused an existing distro, so the preload re-tag, the API-key summary and the btrfs storage wording (A4) were never executed. They need a run from a release containing this branch after wsl --unregister vectoradb , so A4 stays Partial.                                                               | fix/download-integrity   |

|             |                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                       |
|-------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| 16 Sep 2026 | A1, A2, A4, A7, M5; known issues | <p><b>Downloads are verified, and Windows uses its prebuilt distro.</b> Nothing VectoraDB published was checked by its own installers, yet these files run as root inside the user's distro. Now <code>deploy/install.sh</code>, <code>deploy/install.ps1</code> and <code>vdb setup</code> 's engine refresh all verify every download against the release's <code>SHA256SUMS</code>, and anything that cannot be verified stops the install (<code>VDB_NO_VERIFY=1</code> skips deliberately; a local <code>VDB_DIST</code> build has nothing to check against). The engine refresh reuses the same verified download as <code>vdb update</code> through the new <code>update.Client.Release</code>, and keeps the installer-staged engine rather than installing unchecked bytes. The Windows installer now prefers <code>vectoradb-distro.tar.gz</code> (~685 MB, Docker + btrfs tools + engine + images already inside), so setup skips apt, a docker build and three registry pulls; releases without that asset (v0.7.1, v0.8.1) or an unverifiable copy fall back to the Ubuntu rootfs. The distro's Postgres image is tagged <code>ghcr.io/vectoradb/postgres-walg:16</code> — the name the engine actually runs, so the preload stops being wasted — and older distro images are re-tagged after load. Windows setup also prints the connection string with the API key (read from the guest's config), and its storage error now describes btrfs and <code>vectoradb-storage.service</code> instead of the old ZFS pool. Verified: new <code>scripts/test_install_sh.sh</code> 6 / 6 (tampered, missing listing, unlisted asset, skip flag, local build) and new Pester cases, <code>go vet</code> for macOS, Linux and Windows, unit tests on every package; in the VM <code>make integration</code> 52 / 52 and <code>make integration-update</code> 51 / 51. The Windows install itself still needs a manual run.</p>                                                                                                               | <code>fix/download-integrity</code>   |
| 16 Sep 2026 | L8, L9, L10; A9                  | <p><b>Batch 2 verification: the web console reviewed signed in, and vdb update proven on macOS.</b> The three pages that had only ever been type-checked were exercised in a real browser against a running stack, each answer compared with the CLI. <b>L8 Integrity:</b> the report matched <code>vdb blackbox integrity</code> field for field; <b>Create checkpoint</b> anchored a new entry (and was correctly a no-op when nothing new existed); <b>Export</b> answered 200 <code>application/x-ndjson</code>; <b>Branch from before a change</b> restored a branch in 4 s that lacked exactly the table its entry created, with main untouched. <b>L9 Policies:</b> warn → block → warn, disable → enable and add → remove of a custom rule all matched <code>vdb policy list</code> afterwards and reached only the selected branch; the statement check agreed with <code>vdb policy check</code>; on <code>main</code>, where the account has no <code>vdb_admin</code>, the change was refused with a readable banner and the rule stayed warn. <b>L10 sidebar:</b> every link opened its page with the right highlight and breadcrumb (<code>/ledger</code> → Changes), collapse persisted across a reload and was applied before first paint, the theme toggle persisted, and no page logged a console error. Two small things recorded rather than fixed: the Integrity entry list needs a refresh to show a change recorded after the page opened, and the new-rule form pre-fills Command with <code>ALTER TABLE</code> as a real value that reads like a placeholder. The under-860px drawer is still unchecked — the automation could not change the page viewport. <b>A9:</b> updated this Mac for real twice (installed v0.8.3 with the installer → <code>vdb update</code> to v0.8.4 → to v0.8.5), each time checking versions, restarted servers, containers not recreated, branch data, Blackbox, gateway, UI and the kept previous binary; Windows stays untested by choice. Test branches, the temporary key and the</p> | <code>docs/batch2-verification</code> |

`vdb_admin` grant were all removed afterwards.  
Documentation only — no product change in this commit.

|             |                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                         |
|-------------|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| 16 Sep 2026 | A8, A9; known issues                     | <p><b>The new-release notice now actually appears.</b> Testing <code>vdb update</code> against real releases on a Mac (v0.8.3 installed with the installer, then the published v0.8.4) showed the notice missing, while <code>vdb update --check</code> reported the release correctly a moment later. (Precisely: it printed on the first start after a release was published, then stayed silent — the first fetch of a new asset is fast, repeats are throttled.) Cause: the check made two requests, and the second — downloading the release's <code>SHA256SUMS</code> — is throttled hard by GitHub for repeated downloads of the same asset. Measured from this Mac: 0.5 s the first time, then 7 s from Go and 75 s with curl and with HTTP/1.1, so the 1.5 s budget was never met (with a 30 s budget the notice did print). The start check now asks only for the releases list — newer, published, with every file this platform needs attached — which takes about 130 ms, and remembers its answer in <code>~/.vectoradb/update-notice.json</code> for 6 hours</p> <p>(<code>VECTORADB_UPDATE_CHECK_INTERVAL</code> ; 0 checks every start), so repeated starts usually make no request at all. Nothing about installing changed: <code>vdb update</code> still downloads <code>SHA256SUMS</code> and verifies every file before anything is replaced. Verified: unit tests (new <code>TestAvailableMakesNoAssetRequests</code> , <code>TestNoticeIsRememberedBetweenStarts</code> ), <code>go vet</code> for macOS, Linux and Windows; on this Mac a build stamped 0.8.3 printed the notice within the default budget (2.1 s cold, 1.2 s from the remembered answer); in the VM <code>make integration-update</code> 51 / 51 (2 new §1b checks) and <code>make integration</code> 52 / 52. A9's macOS path is now verified end to end (versions, restarted servers, containers, branch data, Blackbox, gateway, UI, kept previous binaries), and again on the released fix: v0.8.5 (which contains it) was installed with <code>vdb update</code> from v0.8.4 — servers restarted on the new binary, <code>vec-main</code> not recreated, UI 200, previous binary kept — and a build of the merged code printed the notice in 2.1 s cold and 1.2 s from the remembered answer. Windows testing is deferred by the owner (16 Sep 2026).</p> | <code>fix/update-notice-throttle</code> |
| 15 Sep 2026 | C3, D4, H7, I1, I5, I6, B1; known issues | <p><b>Safety fixes, batch 1. C3:</b> <code>vdb branch suspend</code> refuses <code>main</code> , the HA standby, and whichever container serves <code>main</code> (the CLI allowed suspending <code>main</code>, which the gateway then couldn't wake). <b>D4:</b> reading the code showed the HA hazard was worse than recorded — after <code>vdb ha failover</code> , <code>ha enable</code> and <code>ha disable</code> deleted the promoted standby, i.e. the live primary and every write since the failover, <code>ha failover</code> again stopped it, and <code>vdb up / start</code> restarted the stale old <code>main</code> as a second writable primary. Now those three are refused after a failover, <code>vdb up</code> brings the promoted standby back (recreating its container from its storage after <code>vdb stop</code> ) and leaves the old <code>main</code> stopped, and the new <code>vdb ha fallback</code> moves <code>main</code> back to its own container keeping every write: <code>main</code> is rebuilt as a replica of the standby, catches up, the standby is stopped cleanly, <code>main</code> replays to its final checkpoint and is promoted; any failure before that leaves the standby primary. <b>H7:</b> <code>vdb blackbox revert --to</code> keeps working but its help and output now say it is a point-in-time restore of <code>main</code> (same as <code>vdb restore</code> ) and point to <code>branch-before</code> . <b>I5 / I1:</b> <code>.sql</code> and Postgres imports run the whole dump, then fail listing every statement that failed (the instance is kept) — they used to report success. <b>I6:</b> a JSON array or NDJSON file with an invalid document fails, naming</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <code>fix/safety-batch1</code>          |

the element or line, and loads nothing from it — an array used to stop silently at the bad element. Integration §3 fix (test-only): its reset of the `pit` table ran `DROP TABLE` without the guardrail override, so it had silently failed for a long time and passed only because the old `ha disable` threw the failover rows away; failback keeps them, which exposed it. Verified: unit tests on every package, `go vet` for macOS, Linux and Windows; in the VM `make integration 52 / 52` (24 new checks: suspend guards, HA guards, `vdb up` after a failover, failback, import errors), `make integration-v2 214 / 214` and `make integration-update 49 / 49` (no regressions).

|             |                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                     |
|-------------|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 15 Sep 2026 | M1, M2; new document       | <p><b>New companion document: VDB_Checklist.</b></p> <p><code>docs/VDB_Checklist.pdf</code> (source <code>docs/VDB_Checklist.html</code>) lists every feature in this document by the same id with its sub-features, whether each is built, partly built or not built, and what tested it — done &amp; tested (automated), done (manual test only), partial, known issue, not started — plus a "Where we are" summary per area, suggested next steps, a "Not started" roadmap, and a note confirming VectoraDB has no custom storage engine (PostgreSQL's own engine is used by design; the storage layer is the ZFS/btrfs copy-on-write drivers and wal-g durability). <code>make feature-doc</code> now renders both PDFs, and first runs <code>scripts/test_feature_checklist.sh</code>, which CI also runs: it fails if a feature id is in one document and not the other, or a row's badge disagrees with its status (checked against a deliberately broken copy). Documentation and tooling only; no product change.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <code>docs/feature-checklist</code> |
| 15 Sep 2026 | new A8, A9; B1, M1, M2, M4 | <p><b>New-release notice on <code>vdb start</code> and <code>vdb update</code>.</b></p> <p>When a newer release is published, <code>vdb start</code> ends with one line saying so and suggesting <code>vdb update</code> — no prompt, checked in the background with a 1.5 s limit, silent when offline, off with <code>VECTORADB_NO_UPDATE_CHECK=1</code> and on development builds. It lists releases through the GitHub API and offers only a promoted (not draft or prerelease), newer release with every file the platform needs listed in <code>SHA256SUMS</code>. <code>vdb update</code> installs it in one command: downloads and checks every file first (nothing changes unless all verify), checks the new engine runs in the VM / WSL distro, stops the three servers (databases keep running), installs the engine (servers restarted on the old one if that fails), runs <code>vdb up</code>, <code>vdb ledger upgrade --all</code> and <code>vdb start</code> on the new engine, then replaces <code>vdb</code> on the computer; previous binaries are kept in <code>~/vectoradb/updates/prev</code>. <code>--check</code>, <code>--yes</code>, <code>--version</code>. Data, containers, images, storage and settings are not touched. The only change to existing behaviour is the extra notice line after <code>vdb start</code>. The release job now fails unless every file <code>vdb update</code> needs is attached and listed in <code>SHA256SUMS</code> (<code>scripts/check-release-assets.sh</code>, tested in CI). The first VM run caught a real bug: <code>stdin</code> from <code>/dev/null</code> looked like a terminal, so <code>vdb update &lt;/dev/null</code> silently did nothing — it now asks for <code>--yes</code>; three test checks were also corrected (history compared by count instead of by the entries themselves, and a settings file that doesn't exist in the VM). Verified: unit tests on every package, <code>go vet</code> for macOS, Linux and Windows; in the VM <code>make integration-update 49 / 49</code> (Linux path against a local fake GitHub) and the existing suite <code>28 / 28</code> (no regressions). The macOS and Windows update paths are unit-tested but not yet run against a real release.</p> | <code>feat/vdb-update</code>        |

|             |                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                  |
|-------------|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| 15 Sep 2026 | new L10; L1–L9                                       | <p><b>Web console: sidebar layout for the signed-in app.</b> The top navbar held every page in one row and was already full. Signed-in pages now use a sidebar grouped into Overview (Dashboard), Data (Console, Import, Pipelines), Blackbox (Changes, Integrity, Policies), Account (API keys) and Help (Guide, Docs), with GitHub, a light/dark switch, the signed-in account, Log out and Collapse at the bottom; it collapses to an icon rail (remembered per browser) and becomes a drawer on narrow screens. A slim top bar shows the section and page. Home and Log in keep the public navbar, which now offers "Open dashboard" to a signed-in user; Guide and Docs appear in whichever layout fits. Every address is unchanged; no API or behaviour change. TypeScript type-check and production build pass; a preview build embedded in the engine served every page (<code>/</code>, <code>/dashboard</code>, <code>/login</code>, <code>/blackbox</code>) with the new layout code. Not yet reviewed in a browser while signed in.</p>                                                                                                                                                                                                                                                             | feat/web-sidebar-layout          |
| 15 Sep 2026 | M2, M4, M5; known issues                             | <p><b>Release checksums can no longer be dropped by the other release job.</b> v0.8.1's <code>SHA256SUMS</code> lost the Windows distro image's entry: <code>wsl-distro.yml</code> ran first (the <code>release</code> workflow had been disabled), then a manual <code>release</code> run replaced the whole file with only the binaries' checksums — so the Windows installer would install the distro image without verifying it. Both workflows now publish through one script, <code>scripts/release-checksums.sh</code>, which merges its own entries into the published file by exact name, keeps the other job's, and re-downloads after uploading to confirm its entries survived (merging again if the other job uploaded at the same moment). <code>wsl-distro.yml</code> also creates the release before publishing checksums.</p> <p><code>scripts/test_release_checksums.sh</code> (run by CI) tests it against a fake <code>gh</code>: no file yet, either job finishing first (same result), a re-run replacing its own entry, exact-name matching, another job uploading at the same moment, a failed upload — 9 / 9 on macOS and on Ubuntu (gawk). v0.8.1 itself still needs <code>wsl-distro.yml</code> re-run for its tag by a repository admin to restore the distro image's checksum.</p> | fix/release-checksums            |
| 15 Sep 2026 | D1, A4 (Windows distro), CI; known issues            | <p><b>MinIO images moved to quay.io (release fix).</b> The <code>wsl-distro</code> release job failed: <code>minio/minio</code> and <code>minio/mc</code> no longer exist on Docker Hub, so the image preload's <code>docker pull</code> was refused — and a fresh install's <code>vdb up</code> would have failed the same way (existing installs kept working from their cached images). The engine and the distro build now use <code>quay.io/minio/minio:RELEASE.2025-09-07T16-13-09Z</code> and <code>quay.io/minio/mc:RELEASE.2025-08-13T08-35-41Z</code> — the exact versions already running and tested, so nobody gets a silent MinIO upgrade. An install with the old images cached keeps using them (no pull needed); <code>VECTORADB_MINIO_IMAGE</code> / <code>VECTORADB_MC_IMAGE</code> override. New <code>internal/branch/images.go</code> with unit tests, including one that keeps <code>deploy/wsl-distro/build.sh</code> preloading the same names. Verified in the VM: both pinned images pull and save as the distro build does, the stack restarted on the quay.io server image against the existing data, and integration-v2 214 / 214 and the existing suite 28 / 28 pass (backups, PITR, branch-before included).</p>                                                                 | fix/minio-images-quay            |
| 15 Sep 2026 | new H17, H18; H15, H16, B1, K1, K2, K6; known issues | <p><b>Blackbox 2.0 Phase 7 — impact analysis and diff.</b> <code>vdb impact "&lt;DDL&gt;"</code> reports what a change would affect before it runs: the objects that depend on the table, view, index or column it changes (new read-only SQL function <code>vdb.blast_radius</code>, following views built on views), the other running branches that have it (with the branch each was</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | feat/blackbox-phase7-impact-diff |

|             |                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                |
|-------------|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
|             |                                     | <p>cloned from, read from ZFS/btrfs), the policy verdict, and a low/medium/high score with its reasons. MCP <code>execute_change</code> results now include it. <code>vdb blackbox diff &lt;a&gt; &lt;b&gt;</code> (and <code>vdb branch diff</code>, which the README already advertised) finds where two branches' Blackbox histories split and lists the changes only on each side and the objects both changed — diff only, nothing is merged. New REST <code>POST /api/branches/{n}/impact</code>, <code>GET /api/ledger/diff</code> and <code>/api/blackbox/diff</code>; MCP <code>impact</code> and <code>blackbox_diff</code>. The first VM run caught a real bug — <code>vdb.blast_radius</code> pinned its search path, so unqualified table names weren't found — fixed before this commit. Verified in the VM: integration-v2 214 / 214 (31 new §8 checks) and the existing suite 28 / 28 (no regressions).</p>                                                                                                                                   |                                                                                |
| 14 Sep 2026 | new H16; H9, B1, K1, K2, K5, K6     | <p><b>Blackbox 2.0 Phase 6 — agent provenance.</b> Blackbox now records which agent session, task and parent session caused a change. New append-only <code>vdb.agent_sessions</code>. The Agent API accepts optional <code>task_id</code>, <code>parent_session_id</code> and <code>session_id</code> when creating an agent branch — every change the agent then makes there carries them (requests without them are unchanged, response included). New MCP tool <code>execute_change</code>: previews policy rules, runs the SQL without superuser rights with the MCP session, task, parent session and a sha256 call hash attached, and returns JSON (applied / blocked with the <code>VDB01</code> rule / error / preview) with the Blackbox entries it wrote. New <code>vdb blackbox sessions</code> and REST <code>.../ledger/sessions</code> (also under <code>/blackbox</code>). <code>run_sql</code> is unchanged. Verified in the VM: integration-v2 183 / 183 (23 new §7 provenance checks) and the existing suite 28 / 28 (no regressions).</p> | <code>feat/blackbo</code><br><code>x-phase6-</code><br><code>provenance</code> |
| 14 Sep 2026 | M (CI); H15 tests                   | <p><b>Windows CI fix (tests and repo config only).</b> Two new policy unit tests assumed LF line endings, but a Windows checkout converts <code>.sql</code> and <code>.md</code> files to CRLF, so <code>TestSchemaPolicy</code> and <code>TestPolicyContractExample</code> failed on the <code>windows-ci</code> runner. The tests now normalise line endings, and <code>.gitattributes</code> pins <code>*.sql</code> to LF (like <code>*.sh</code> and <code>*.go</code>), so the SQL embedded in <code>vdb</code> is the same bytes on every platform. No product change. Reproduced locally in a CRLF checkout (both tests failed as on the runner) and verified the fix there: every Go package passes with CRLF <code>.sql</code> and <code>.md</code> files, and a fresh checkout now gets LF <code>.sql</code> files.</p>                                                                                                                                                                                                                            | <code>feat/blackbo</code><br><code>x-phase5-</code><br><code>policy</code>     |
| 14 Sep 2026 | H9 (security fix); known issues     | <p><b>Capture can't be switched off by a client.</b> The Blackbox 2.0 kill switch <code>vdb.v2 = 'off'</code> was a session setting any client could set, so a client could stop the capture rows (transaction id, WAL position, provenance, override use) for its own changes. It is now honoured only when set for the whole database ( <code>ALTER DATABASE</code>, owner or superuser) or in a superuser's own session; a client's own <code>SET</code> — even a <code>vdb_admin</code> member's — is ignored. The check moved inside the capture trigger's fail-safe block. The documented kill switch and the engine's superuser use of it are unchanged. Verified in the VM: integration-v2 160 / 160 (3 new §2 checks) and the existing suite 28 / 28.</p>                                                                                                                                                                                                                                                                                            | <code>feat/blackbo</code><br><code>x-phase5-</code><br><code>policy</code>     |
| 14 Sep 2026 | new H15, L9; H4, H9, B1, K1, K2, K6 | <p><b>Blackbox 2.0 Phase 5 — policy gate.</b> Every schema change is checked against policy rules before it runs (event trigger <code>vdb_policy_start</code>, after the unchanged guardrail). A warn rule lets it through with a NOTICE (SQLSTATE <code>VDB02</code>); a block rule refuses it with <code>VDB01</code>, records a <code>BLOCKED</code> Blackbox entry and an evaluation that survive the rollback, and can be overridden per rule by <code>vdb_admin</code> members ( <code>SET</code></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | <code>feat/blackbo</code><br><code>x-phase5-</code><br><code>policy</code>     |

`vdb.policy_allow` ). DETAIL is the JSON defined in `docs/policy-errors.md` . Four built-in rules ship, all warn: `alter-column-type` , `drop-column` , `drop-index` , `grant-to-public` . New: `vdb policy list|check|block|warn|enable|disable|add|remove|evaluations` , REST `/api/branches/{n}/policies...` (changes need `vdb_admin` ), MCP `policy_check` , web Policies page. Verified in the VM: integration-v2 157 / 157 (50 new §6 policy checks) and the existing suite 28 / 28 (no regressions).

|             |                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                |
|-------------|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| 14 Sep 2026 | new H14; whole document; H2, H6, H10–H13, B1, K1, K2, K3, K4, K6, L5, L8 | <b>Schema Ledger renamed Blackbox.</b> Everything people read now says Blackbox: this document, the README, the web console (nav "Blackbox", new address <code>/blackbox</code> ), CLI help, MCP and OpenAPI descriptions, SDK descriptions and READMEs, code comments. New names were added next to the old ones, and nothing was removed: <code>vdb blackbox ...</code> , <code>/api/branches/{n}/blackbox...</code> routes, MCP <code>verify_blackbox</code> / <code>blackbox_integrity</code> / <code>blackbox_entries</code> , SDK <code>blackbox()</code> / <code>verify_blackbox()</code> / <code>verifyBlackbox()</code> . Unchanged on purpose: SQL objects ( <code>vdb.schema_ledger</code> ...), the anchor format id, the Go package, command output lines and JSON field names. Also: the policy-gate error contract <code>docs/policy-errors.md</code> (Phase 5, written and approved before any policy code: <code>VDB01 block</code> / <code>VDB02 warn</code> , JSON DETAIL, <code>vdb_admin</code> per-rule override, all default rules warn, blocked attempts recorded). Verified in the VM: integration-v2 107 / 107 (10 new §5 alias checks) and the existing suite 28 / 28 (no regressions).                                                                                                                                                                                                 | <code>feat/blackbox-phase5-policy</code>       |
| 14 Sep 2026 | new H13; D3, B1, K1, K2, K6, L8                                          | <b>Blackbox 2.0 Phase 4 — branch from just before a ledger entry.</b> <code>vdb ledger branch-before &lt;id&gt;</code> creates a new branch holding main exactly as it was the moment before that change committed: it restores the newest base backup that finished before the change and replays archived WAL up to, but not including, the change's transaction (the xid captured in Phase 2; older entries fall back to their timestamp). main is not modified; the published Postgres image is unchanged (the restore script is embedded in the engine); <code>vdb restore</code> and <code>vdb ledger revert</code> are untouched. New: <code>vdb ledger entries</code> (entries with their ids — the existing ledger views are unchanged and show none), REST <code>GET .../ledger/entries</code> and <code>POST .../ledger/{id}/branch</code> , MCP <code>ledger_entries</code> and <code>branch_before_change</code> , a panel on the web Integrity page listing recent entries. Test-only fix in <code>integration_ledger_v2.sh</code> §2: the "base ledger still records that DDL" check counted rows by table name, so it failed when the suite ran twice without the existing suite's ledger wipe in between; it now counts only the current run's rows. Verified in the VM: integration-v2 97 / 97 (twice back-to-back, including 34 new §4 checks) and the existing suite 28 / 28 (no regressions). | <code>feat/ledger2-phase4-branch-before</code> |
| 14 Sep 2026 | new H10, H11, H12, L8; H2, H9, B1, K1, K2, K6, M1, M4                    | <b>Blackbox 2.0 Phase 3 — tamper-evidence outside the database.</b> Checkpoints record a Merkle root over new ledger entries in <code>vdb.ledger_checkpoints</code> and as read-only anchor files outside the database (format published in <code>docs/ledger-anchor-format.md</code> ), on a schedule and on demand. <code>vdb ledger integrity</code> checks the ledger against the anchors and catches history rewritten even with a recomputed hash chain; the new open-source <code>vdb-verify</code> does the same independently, live or from an export. New: <code>vdb ledger checkpoint integrity export</code> , REST                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <code>feat/ledger2-phase3-checkpoints</code>   |

.../ledger/integrity|checkpoint|export , MCP  
 ledger\_integrity , web Integrity page, vdb-verify  
 release binaries. Verified in the VM: integration-v2 63 / 63 and  
 the existing suite 28 / 28 (no regressions).

|             |                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                 |
|-------------|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| 14 Sep 2026 | new H9; H4, H8; test script    | <b>Blackbox 2.0 Phase 2 — capture foundation.</b> New side table <code>vdb.ledger_ext</code> records the transaction id, WAL position, agent task / tool-call hash and override use for every ledger row, through a fail-safe trigger with a kill switch ( <code>vdb.v2 = off</code> ); installed at start and by <code>vdb ledger upgrade</code> . The base ledger and its hash chain are untouched. Phase 1 verified in the VM (existing suite 26/28, v2 29/29) and Phase 2 verified (v2 42/42, no regressions); two false failures in <code>integration_test.sh</code> fixed (test-only).                                                                                                                                               | 56bfb81 (PR #24)                |
| 14 Sep 2026 | D3, H3, H4, K5, K6, B1; new H8 | <b>Blackbox 2.0 Phase 1 — three security fixes.</b> PITR restore uses the per-install MinIO credentials. The destructive-DDL override is honoured only for superusers and <code>vdb_admin</code> members (new <code>vdb admin grant revoke list</code> and <code>vdb ledger upgrade</code> ; the first local user is granted automatically). Agent branches log in as their own non-superuser <code>agent-&lt;id&gt; role</code> and MCP <code>run_sql</code> runs as <code>vdbclient</code> (compatibility switches <code>VECTORADB_AGENT_SUPERUSER</code> , <code>VECTORADB_MCP_SUPERUSER</code> ). New <code>scripts/integration_ledger_v2.sh</code> ( <code>make integration-v2</code> ) pins unchanged behaviour and tests the fixes. | 201676c (PR #23)                |
| 14 Sep 2026 | Whole document                 | Document created. Inventory of every feature implemented as of 8b1856f : install & setup, CLI, branching & storage, durability, security, gateway, auth, Blackbox, import, pipelines, APIs/SDKs/MCP, web console, CI & releases. Known issues and the test baseline recorded.                                                                                                                                                                                                                                                                                                                                                                                                                                                              | branch docs/feature-implemented |

## Test baseline

Recorded before any Blackbox 2.0 work starts, so later changes can be checked against it.

| Suite                                                  | Result   | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Go unit tests ( <code>go test ./...</code> , host)     | All pass | 14 Sep 2026, go1.26.6 darwin/arm64, commit 8b1856f . Packages with tests: cmd/vdb, auth, branch, controlplane, daemon, host, proxy (later also ledger, mcp, update). 15 Sep 2026 with <code>feat/vdb-update</code> : all pass. 16 Sep 2026 with the start-notice fix: all pass. No test files: agentapi, ledger, mcp, secrets, tlsutil, version, web.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Integration ( <code>make integration</code> , Lima VM) | 52 / 52  | 14 Sep 2026. <b>Before Phase 1</b> ( a5a52b6 ): 25 passed, 3 failed — bad-key count, PITR (the <code>minioadmin</code> bug), append-only check. <b>After Phase 1</b> ( 33f49ef ): 26 passed, 2 failed — PITR fixed, no regressions. The remaining two were test flaws ( <code>psql</code> prints the bad-key error twice; the append-only check discarded stderr); the protections were confirmed by hand and the checks fixed. <b>With Phase 2</b> ( <code>feat/ledger2-phase2-capture</code> ): 27 passed, 1 failed — the bad-key check again, because its first fix ( <code>grep -q</code> ) broke under the script's <code>set -o pipefail</code> ; corrected to count matches and re-checked in the VM. <b>With Phase 3</b> ( <code>feat/ledger2-phase3-checkpoints</code> ): 28 / 28 — every check passes. <b>With Phase 4</b> ( <code>feat/ledger2-phase4-branch-before</code> ): 28 / 28 on the final code (also 28 / 28 on the first Phase 4 build) — no regressions. <b>With the Blackbox rename</b> ( <code>feat/blackbox-phase5-policy</code> ): 28 / 28. <b>With the policy gate</b> : 28 / 28. <b>With the capture kill-switch fix</b> : 28 / 28. <b>With Phase 6</b> : 28 / 28. <b>With Phase 7</b> : 28 / 28. <b>With vdb update</b> ( <code>feat/vdb-update</code> ): 28 / 28. <b>With safety fixes batch 1</b> ( <code>fix/safety-batch1</code> ): 52 / 52 — 24 new checks (suspend and HA |

guards, `vdb up` after a failover, failback, import errors); first run 51 / 52 and second 49 / 52, both on test flaws (a container-absent check, and §3's unguarded table reset), fixed. **With the start-notice fix**: 52 / 52.

|                                                                           |                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>vdb update</code> ( <code>make integration-update</code> , Lima VM) | 51 / 51          | 15 Sep 2026, <code>feat/vdb-update</code> . First run 41 / 45: one real bug (stdin from <code>/dev/null</code> treated as a terminal) and three flawed checks, all fixed; final run 49 / 49. <b>With safety fixes batch 1</b> : 49 / 49. <b>With the start-notice fix</b> ( <code>fix/update-notice-throttle</code> ): 51 / 51, including two new §1b checks — the remembered answer prints with GitHub unreachable, and a forced check then prints nothing.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Blackbox 2.0 ( <code>make integration-v2</code> , Lima VM)                | 214 / 214        | 14 Sep 2026, <code>33f49ef</code> : §0 behaviour unchanged and §1a–§1c Phase 1 fixes all pass. With Phase 2: 42 / 42. <b>With Phase 3</b> ( <code>feat/ledger2-phase3-checkpoints</code> ): 63 / 63, including 20 new §3 checkpoint, verifier and tamper checks and the §3b scheduler check. <b>With Phase 4</b> ( <code>feat/ledger2-phase4-branch-before</code> ): 97 / 97, including 34 new §4 branch-before and entry-listing checks; run twice back-to-back after fixing a §2 check that wasn't repeatable (first final run 96 / 97 on that check only). <b>With the Blackbox rename</b> ( <code>feat/blackbox-phase5-policy</code> ): 107 / 107, including 10 new §5 checks that every Blackbox name matches the original. <b>With the policy gate</b> : 157 / 157, including 50 new §6 policy checks. <b>With the capture kill-switch fix</b> : 160 / 160. <b>With Phase 6</b> ( <code>feat/blackbox-phase6-provenance</code> ): 183 / 183, including 23 new §7 provenance checks. <b>With Phase 7</b> ( <code>feat/blackbox-phase7-impact-diff</code> ): 214 / 214, including 31 new §8 impact and diff checks. <b>With safety fixes batch 1</b> : 214 / 214. |
| Web console (browser, signed in)                                          | L8, L9, L10 pass | 16 Sep 2026, Chrome on macOS against the running stack (v0.8.5). Every Integrity and Policies result was compared with the CLI; the sidebar was walked link by link. Not covered: the under-860px drawer, and there is still no automated UI test.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Windows (Pester, <code>windows-ci.yml</code> )                            | In CI            | Runs on every push/PR to main.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

# Feature index

Grouped by area. Badges: Working Partial Known issue

## A · INSTALL & SETUP

|    |                                                  |         |
|----|--------------------------------------------------|---------|
| A1 | One-line installer (macOS / Linux)               | Working |
| A2 | Windows installer (install.ps1)                  | Partial |
| A3 | <code>vdb setup</code> on macOS (Lima)           | Working |
| A4 | <code>vdb setup</code> on Windows (WSL2 + btrfs) | Partial |
| A5 | Linux native                                     | Working |
| A6 | Command forwarding & file streaming              | Working |
| A7 | Always-latest engine binary                      | Working |
| A8 | New-release notice on <code>vdb start</code>     | Working |
| A9 | <code>vdb update</code>                          | Partial |

## B · CLI & SERVICES

|    |                                  |         |
|----|----------------------------------|---------|
| B1 | The <code>vdb</code> command set | Partial |
| B2 | Background services (daemon)     | Working |

## C · BRANCHING & STORAGE

|    |                                    |         |
|----|------------------------------------|---------|
| C1 | Storage drivers (ZFS / btrfs)      | Working |
| C2 | Branch lifecycle                   | Working |
| C3 | Protection of <code>main</code>    | Working |
| C4 | Private networking (no host ports) | Working |
| C5 | Scale-to-zero & wake on connect    | Working |
| C6 | Storage quotas                     | Partial |
| C7 | Capacity & status                  | Working |
| C8 | Provisioning & image pull          | Working |

## D · DURABILITY

|    |                                 |         |
|----|---------------------------------|---------|
| D1 | WAL archiving to object storage | Working |
| D2 | Base backups                    | Working |
| D3 | Point-in-time restore           | Partial |
| D4 | HA standby & failover           | Partial |

## E · SECURITY FOUNDATIONS

|    |                               |         |
|----|-------------------------------|---------|
| E1 | Per-install generated secrets | Working |
| E2 | TLS everywhere                | Working |
| E3 | Zero-signup local API key     | Working |

## F · SQL GATEWAY

|    |                                   |         |
|----|-----------------------------------|---------|
| F1 | Routing by database name          | Working |
| F2 | API-key authentication            | Working |
| F3 | Backend login (SCRAM)             | Working |
| F4 | Per-user Postgres login roles     | Working |
| F5 | Attribution session settings      | Working |
| F6 | Ctrl-C (CancelRequest) forwarding | Working |
| F7 | Errors & insecure build tag       | Working |

## G · ACCOUNTS & AUTH

|    |                               |         |
|----|-------------------------------|---------|
| G1 | Auth store (SQLite)           | Working |
| G2 | Email & password users        | Working |
| G3 | API keys                      | Working |
| G4 | Web sessions & signup control | Working |
| G5 | OAuth (GitHub / Google)       | Partial |

## H · BLACKBOX

|     |                                                |         |
|-----|------------------------------------------------|---------|
| H1  | DDL recording                                  | Working |
| H2  | Hash chain, append-only, verify                | Partial |
| H3  | Attribution                                    | Partial |
| H4  | Destructive-DDL guardrail                      | Partial |
| H5  | Risk flags                                     | Partial |
| H6  | Ledger access (CLI/REST/MCP/UI/SDK)            | Working |
| H7  | <code>vdb ledger revert --to</code>            | Working |
| H8  | Override permission & ledger upgrade           | Working |
| H9  | Blackbox 2.0 capture (xid, LSN, provenance)    | Working |
| H10 | Checkpoints & anchors                          | Working |
| H11 | <code>vdb-verify</code> (independent verifier) | Working |
| H12 | Blackbox integrity & export                    | Working |
| H13 | Branch from just before a Blackbox entry       | Working |
| H14 | Blackbox names & aliases                       | Working |
| H15 | Policy gate (warn / block)                     | Working |
| H16 | Agent provenance & <code>execute_change</code> | Working |
| H17 | Impact analysis                                | Working |
| H18 | Blackbox diff between branches                 | Working |

## I · IMPORT & MIGRATION

|     |                                  |         |
|-----|----------------------------------|---------|
| I1  | From Postgres                    | Working |
| I2  | From MySQL ≤5.7 / MariaDB        | Working |
| I3  | From MySQL 8.x                   | Working |
| I4  | From MongoDB                     | Working |
| I5  | From a .sql dump                 | Working |
| I6  | From JSON / NDJSON               | Working |
| I7  | From CSV                         | Working |
| I8  | Continuous replication & cutover | Partial |
| I9  | Guard handling during import     | Working |
| I10 | Live progress (CLI & SSE)        | Working |
| I11 | Import REST endpoints            | Working |
| I12 | Web Import page                  | Working |
| I13 | Exact identifier fidelity        | Working |

J · ETL PIPELINES (EXPERIMENTAL)

|    |                                |         |
|----|--------------------------------|---------|
| J1 | Pipeline engine                | Working |
| J2 | Data-quality tests             | Working |
| J3 | Stored pipelines & run history | Working |
| J4 | Pipeline editor (web)          | Working |

K · APIS, SDKS & AGENTS

|    |                        |         |
|----|------------------------|---------|
| K1 | Control-plane REST API | Working |
| K2 | OpenAPI spec           | Partial |
| K3 | Python SDK             | Working |
| K4 | TypeScript SDK         | Working |
| K5 | Agent Branch API       | Partial |
| K6 | MCP server             | Partial |

L · WEB CONSOLE

|     |                             |         |
|-----|-----------------------------|---------|
| L1  | Embedded single-origin UI   | Working |
| L2  | Login & signup              | Working |
| L3  | Dashboard                   | Working |
| L4  | SQL console & browser       | Working |
| L5  | Blackbox page               | Partial |
| L6  | API keys page               | Working |
| L7  | Landing, Guide & Docs pages | Partial |
| L8  | Blackbox integrity page     | Partial |
| L9  | Policies page               | Partial |
| L10 | App sidebar layout          | Partial |

M · BUILD, CI & RELEASES

|    |                         |         |
|----|-------------------------|---------|
| M1 | Makefile targets        | Working |
| M2 | Linux CI                | Working |
| M3 | Windows CI              | Working |
| M4 | Releases & GHCR image   | Working |
| M5 | WSL distro / ZFS builds | Partial |
| M6 | Postgres image          | Working |

# Install & setup

## A1 One-line installer (macOS / Linux)

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Installs the <code>vdb</code> binary with one command.                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| HOW IT WORKS    | <code>deploy/install.sh</code> detects OS (darwin/linux) and arch (arm64/amd64), downloads <code>vdb-&lt;os&gt;-&lt;arch&gt;</code> from the GitHub release, verifies it against the release's <code>SHA256SUMS</code> ( <code>verify_file</code> , using <code>sha256sum</code> or <code>shasum</code> ), installs to <code>\$PREFIX/bin</code> (sudo only if needed). On macOS it also stages <code>vdb-linux-&lt;arch&gt;</code> into <code>\$PREFIX/share/vectoradb</code> for the VM. |
| HOW TO USE      | <code>curl -fsSL https://raw.githubusercontent.com/vectoradb/vectoraDB/main/deploy/install.sh   sh</code> . <code>env VDB_VERSION</code> , <code>VDB_REPO</code> , <code>VDB_DIST</code> (local folder), <code>VDB_PREFIX</code> (default <code>/usr/local</code> ).                                                                                                                                                                                                                       |
| HOW TO TEST     | Unit: <code>scripts/test_install_sh.sh</code> (run by CI) against a fake release — a verified release installs; a tampered binary, a release without <code>SHA256SUMS</code> and an asset missing from the listing each install nothing; <code>VDB_NO_VERIFY=1</code> installs anyway; a local <code>VDB_DIST</code> build still installs. Manual: <code>VDB_DIST=./dist VDB_PREFIX=\$HOME/.local sh deploy/install.sh</code> then <code>vdb version</code> .                              |
| STATUS & LIMITS | Working. Every download is checked against the release's <code>SHA256SUMS</code> before it is installed, and anything that cannot be verified stops the install ( <code>VDB_NO_VERIFY=1</code> skips deliberately; <code>VDB_DIST</code> is the user's own build, so there is nothing to check it against). The listing travels over the same TLS connection as the files, so this proves integrity — a complete, unaltered download — not authorship; signatures are still not built.     |
| ADDED IN        | <code>c9afda7</code> (PR #1); URLs repointed to the vectoradb org in <code>0b125f9</code> .                                                                                                                                                                                                                                                                                                                                                                                                |

## A2 Windows installer (install.ps1)

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | From a bare Windows machine to a running database with <code>irm ...</code>   <code>iex</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| HOW IT WORKS    | <code>deploy/install.ps1</code> <code>Invoke-Install</code> : (1) installs WSL ( <code>wsl --install --no-distribution</code> , elevates if needed; registers a <code>RunOnce</code> resume across a reboot); (2) downloads <code>vdb-windows-amd64.exe</code> , <code>vdb-linux-amd64</code> , <code>vectoradb-docker-context.tar.gz</code> ; (3) downloads the Ubuntu noble WSL rootfs verified against Ubuntu's <code>SHA256SUMS</code> ; (4) adds the folder to <code>PATH</code> ; (5) runs <code>vdb setup</code> . Forces TLS 1.2, BOM-free ASCII.                                                        |
| HOW TO USE      | PowerShell: <code>irm https://raw.githubusercontent.com/vectoradb/vectoraDB/main/deploy/install.ps1   iex</code> . <code>env VDB_VERSION</code> , <code>VDB_REPO</code> , <code>VDB_PREFIX</code> , <code>VDB_NO_SETUP</code> , <code>VDB_NO_ELEVATE</code> , <code>VDB_ROOTFS_URL</code> .                                                                                                                                                                                                                                                                                                                      |
| HOW TO TEST     | Run on a real Windows machine on 16 Sep 2026 (from the branch, with the released v0.8.5 assets): the installer downloaded and verified the 685 MB distro image, added vdb to <code>PATH</code> and completed setup. Pester: <code>deploy/install.Tests.ps1</code> (including the checksum block: listing parsing, the binary-mode <code>*name</code> form, an unlisted asset refused, a mismatch deleting the file, <code>VDB_NO_VERIFY=1</code> ), <code>deploy/windows-install.Tests.ps1</code> (E2E group needs <code>VDB_TEST_E2E</code> ); <code>windows-ci.yml</code> checks BOM/ASCII and PS 5.1 parsing. |
| STATUS & LIMITS | Works. It now downloads the prebuilt <code>vectoradb-distro.tar.gz</code> (~685 MB) so setup skips apt, the image build and the registry pulls, falling back to the Ubuntu rootfs when a release does not publish it (v0.7.1, v0.8.1) or the copy cannot be verified; every VectoraDB asset is checked against <code>SHA256SUMS</code> .                                                                                                                                                                                                                                                                         |
| ADDED IN        | <code>4fc8afb</code> (PR #1); one-command flow <code>0c71da9</code> , verified downloads <code>d0c1f26</code> (PR #7); resume fix <code>288c431</code> (PR #8).                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

### A3 vdb setup on macOS (Lima)

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Creates/starts a Linux VM, installs Docker + ZFS, installs the engine and starts the stack.                                                                                                                                                                                                                                                                                   |
| HOW IT WORKS    | <code>internal/host/host_darwin.go</code> <code>setupDarwin</code> : requires <code>limactl</code> ; refreshes the engine binary (A7); creates <code>template://ubuntu</code> VM if missing and runs <code>provisionGuest ( zfsutils-linux docker.io )</code> ; always reinstalls the engine to <code>/usr/local/bin/vdb</code> in the VM; then forwards <code>start</code> . |
| HOW TO USE      | <code>brew install lima &amp;&amp; vdb setup</code> · env <code>VECTORADB_LIMA_INSTANCE</code> (default <code>vectoradb</code> , falls back to <code>default</code> ), <code>VECTORADB_GUEST_BINARY</code> .                                                                                                                                                                  |
| HOW TO TEST     | No unit test for orchestration. Manual: <code>limactl delete -f vectoradb; vdb setup; vdb status</code> .                                                                                                                                                                                                                                                                     |
| STATUS & LIMITS | Working. Provisioning only runs on VM creation (an interrupted VM isn't repaired). No image build context is staged, so if the GHCR pull fails an installed user can't fall back to a local build.                                                                                                                                                                            |
| ADDED IN        | <code>c9afda7</code> (PR #1); always-reinstall <code>77ef8ba</code> (PR #18).                                                                                                                                                                                                                                                                                                 |

### A4 vdb setup on Windows (WSL2 + btrfs)

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Imports a dedicated <code>vectoradb</code> WSL distro, provisions it and starts VectoraDB with quiet step-by-step output.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| HOW IT WORKS    | <code>host_windows.go</code> <code>setupWindows</code> : checks <code>wsl --status</code> ; refreshes the engine; <code>importDistro ( wsl --import</code> , writes <code>/etc/wsl.conf</code> with <code>systemd</code> ); <code>waitForSystemd</code> ; <code>provisionGuestWSL</code> on every run (Docker, btrfs, storage unit, preloaded images, image context, engine binary); <code>verifyBtrfs</code> ; quiet <code>start</code> with one retry; <code>finishSetup</code> . All guest output goes to <code>install.log</code> next to <code>vdb.exe</code> . A <code>vectoradb-storage.service</code> mounts the btrfs image before Docker at boot; <code>forwardStdin</code> waits for <code>systemd</code> on a cold distro. |
| HOW TO USE      | <code>vdb setup</code> (run by <code>install.ps1</code> ) · env <code>VECTORADB_WSL_DISTRO</code> , <code>VECTORADB_GUEST_BINARY</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| HOW TO TEST     | Unit: <code>host_wsl_test.go</code> (TestResolveWSLDistro, TestWSLArgs, TestDecodeWSLList, TestWinPathToMnt, TestParseKernelRelease). Verified on a real Windows machine (16 Sep 2026, v0.8.6, after <code>wsl --unregister vectoradb</code> ): the distro was created from the prebuilt image, "Loading the preinstalled container images" ran and no apt install of Docker or btrfs tools appeared, the engine reported "vdb-linux-amd64 from v0.8.6 verified against SHA256SUMS", and setup ended with a single summary carrying the working connection string ( <code>postgresql://vectoradb:vdb_...@localhost:6432/main?sslmode=require</code> ). Manual: <code>wsl --unregister vectoradb; vdb setup; vdb status</code> .        |
| STATUS & LIMITS | Works. Fixed 16 Sep 2026: the preloaded Postgres image is now tagged <code>ghcr.io/vectoradb/postgres-wal-g:16</code> (the name the engine runs), and a distro image built before that is re-tagged after load, so the preload is ineffective. The final summary prints a connection string without the API key or <code>sslmode</code> . The storage-unit error text still mentions ZFS.                                                                                                                                                                                                                                                                                                                                              |
| ADDED IN        | <code>4fc8afb</code> , <code>8305e5b</code> (PR #1); quiet flow <code>0c71da9</code> + prebuilt image <code>d0c1f26</code> (PR #7); btrfs <code>fc4a1b8</code> (PR #9); initdb race fix <code>cb6655c</code> (PR #21).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

### A5 Linux native

Working

|                 |                                                                                                                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | On Linux the engine runs in-process; no VM.                                                                                                                                                                                          |
| HOW IT WORKS    | <code>host_other.go</code> : <code>vdb setup</code> prints "Linux host — no VM needed. Run <code>vdb start</code> ". ZFS and Docker must be installed; <code>ensureDocker</code> / <code>ensureReady</code> give instructive errors. |
| HOW TO USE      | <code>sudo vdb start</code>                                                                                                                                                                                                          |
| HOW TO TEST     | Integration suite runs on Linux (inside the Lima VM): <code>make integration</code> .                                                                                                                                                |
| STATUS & LIMITS | Working.                                                                                                                                                                                                                             |
| ADDED IN        | <code>4fc8afb</code> (PR #1).                                                                                                                                                                                                        |

## A6 Command forwarding & host file streaming

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | On macOS/Windows every engine command transparently runs inside the VM; <code>vdb import --from ./file</code> works for any file on the host.                                                                                                                                                                                                                                                                                                 |
| HOW IT WORKS    | <code>host.Maybe ( host.go )</code> forwards unless on Linux, in the guest ( <code>VECTORADB_IN_GUEST</code> ) or a local command. macOS: <code>limactl shell ... env VECTORADB_IN_GUEST=1 vdb ...</code> (auto-starts the VM). Windows: <code>wsl.exe -d vectoradb -- env ... vdb ... . importLocalFile</code> rewrites a local file import to <code>--from - -kind &lt;ext&gt; --srcname &lt;name&gt;</code> and pipes the file over stdin. |
| HOW TO USE      | Automatic. Env <code>VECTORADB_GUEST_BIN</code> .                                                                                                                                                                                                                                                                                                                                                                                             |
| HOW TO TEST     | Unit: <code>TestImportLocalFile</code> , <code>TestWSLArgs</code> . Manual: <code>limactl stop vectoradb &amp;&amp; vdb status</code> (VM auto-starts); import a CSV from the Desktop.                                                                                                                                                                                                                                                        |
| STATUS & LIMITS | Working. Only <code>import</code> streams files; <code>pipeline run spec.json</code> passes the path unchanged (must be readable in the VM).                                                                                                                                                                                                                                                                                                  |
| ADDED IN        | <code>c9afda7</code> , <code>4fc8afb</code> , <code>8305e5b</code> (PR #1); streaming <code>44cc05c</code> .                                                                                                                                                                                                                                                                                                                                  |

## A7 Always-latest engine binary

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Re-running <code>vdb setup</code> installs the newest Linux engine rather than a stale bundled copy.                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| HOW IT WORKS    | <code>refreshEngineBinary ( host.go )</code> downloads <code>vdb-linux-&lt;arch&gt;</code> from the latest (or pinned) release into <code>~/.vectoradb/</code> with a 5-minute timeout, atomic rename and an ELF check; best-effort fallback to the installer's copy. <code>bundledLinuxBinary</code> prefers the cache.                                                                                                                                                                                                                                                    |
| HOW TO USE      | Automatic. <code>VECTORADB_NO_REFRESH=1</code> skips it; <code>VDB_REPO / VDB_VERSION</code> override the source.                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| HOW TO TEST     | Unit: <code>host_test.go</code> — <code>TestIsELF</code> , <code>TestBundledLinuxBinaryPrefersCache</code> , <code>TestRefreshEngineBinaryDisabled</code> , <code>TestDownloadFile</code> ; <code>internal/update</code> <code>TestReleaseForSetup</code> (newest complete release, a pinned older tag, an incomplete release refused).                                                                                                                                                                                                                                     |
| STATUS & LIMITS | Working, and seen on Windows on 16 Sep 2026: setup printed "Engine vdb-linux-amd64 from v0.8.6 verified against SHA256SUMS" before installing it. The download is verified against the release's <code>SHA256SUMS</code> (size and SHA-256 as it streams) and an unverifiable or mismatched build is discarded in favour of the engine the installer staged — the engine runs as root inside the VM, so unchecked bytes are never installed. <code>VECTORADB_NO_REFRESH=1</code> skips the refresh; <code>VDB_NO_VERIFY=1</code> falls back to the old unverified download. |
| ADDED IN        | <code>77ef8ba</code> (PR #18).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## A8 New-release notice on `vdb start`

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | When a newer release is published, <code>vdb start</code> ends with one line: <i>VectoraDB vX is available (you have Y)</i> . Run <code>`vdb update`</code> to get the new capabilities. No prompt, and start is never held up.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| HOW IT WORKS    | New package <code>internal/update</code> . The check starts in the background when <code>start</code> begins and gets 1.5 s; the notice prints after start's own output only if the check finished in time. It lists releases through the GitHub API (not <code>/releases/latest</code> , which can point at a release still being published) and offers only one that is newer, not a draft or prerelease, and has every file this platform's update needs attached. That is a single request: it does <b>not</b> download <code>SHA256SUMS</code> , because GitHub throttles repeated downloads of the same release asset (measured 16 Sep 2026 from this Mac: 0.5 s the first time, then 7 s–75 s), so the first check after a new release was fast and every later one missed the budget. <code>vdb update</code> still downloads <code>SHA256SUMS</code> and verifies every file before installing anything. The releases list is cached with its ETag in <code>~/.vectoradb/update-check.json</code> , and the answer itself is remembered in <code>~/.vectoradb/update-notice.json</code> for 6 hours, so repeated starts usually make no request at all. Runs on the computer: in <code>host.Maybe</code> around the forwarded <code>start</code> on macOS/Windows, and in <code>start</code> itself on Linux; the engine inside the VM never checks. Offline, rate limited or any error: nothing printed. |
| HOW TO USE      | Automatic. <code>VECTORADB_NO_UPDATE_CHECK=1</code> turns it off; <code>VECTORADB_UPDATE_CHECK_TIMEOUT</code> (e.g. 3s); <code>VECTORADB_UPDATE_CHECK_INTERVAL</code> sets how long an answer is remembered (default 6h; 0 checks on every start); <code>VDB_REPO</code> like the installers. Development builds ( <code>0.1.0-dev</code> ) never check.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| HOW TO TEST     | Unit: <code>internal/update/update_test.go</code> (versions, release selection, checksums, cache, a slow server doesn't delay or print, offline, turned off; <code>TestAvailableMakesNoAssetRequests</code> — the notice makes no asset request while the update path still verifies; <code>TestNoticeIsRememberedBetweenStarts</code> ). Integration: <code>make integration-update</code> §1, §1b (the remembered answer prints with GitHub unreachable; a forced check then prints nothing), §2, §3, §8. Also checked for real on a Mac (installed 0.8.3, published v0.8.4): the notice prints within the default budget.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| STATUS & LIMITS | Working. Releases are published as prereleases and promoted by hand (M4), so the notice appears once a release is promoted. macOS assumes the VM has the Mac's CPU for the notice (Lima's default); <code>vdb update</code> checks the real one. Fixed 16 Sep 2026: against real GitHub the notice appeared only on the first start after a release was published. The check's second request ( <code>SHA256SUMS</code> ) is fast the first time that asset is fetched and throttled to seconds or minutes on repeats, so every later start fell past the budget. It now needs one request and is remembered for 6 hours.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| ADDED IN        | <code>feat/vdb-update</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

## A9 vdb update

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Installs the newest release in one command — the new engine, restarted servers, Blackbox upgrades on running branches, and <code>vdb</code> on the computer — without touching databases, branches, backups or settings. Before, updating meant re-running the installer, then <code>vdb setup</code> (which left old servers running), then <code>vdb blackbox upgrade --all</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| HOW IT WORKS    | <code>internal/host/host_update.go</code> , run on the computer on every platform. (1) Downloads every file this platform needs into <code>~/.vectoradb/updates/&lt;tag&gt;/</code> , each checked against <code>SHA256SUMS</code> as it streams — nothing changes unless all verify. (2) Copies the new engine into the VM / WSL distro and runs its <code>version</code> (wrong CPU or corrupt → stop). On macOS, asks for sudo now if <code>/usr/local/bin</code> isn't writable; Homebrew installs are refused. (3) <code>vdb _update-guest stop-services</code> , run with the new engine, stops the three servers (they must stop: <code>start</code> leaves running ones alone); Postgres, MinIO and branch containers keep running. (4) <code>_update-guest install-engine</code> writes the engine next to the installed one and renames it over (the old one is kept in <code>~/.vectoradb/updates/prev/vdb</code> in the VM); if this fails the servers are restarted on the old engine. Windows also refreshes the Postgres image build context in the distro and next to <code>vdb.exe</code> (previous kept as <code>.prev</code> ; only future image builds use it). (5) With the new engine: <code>vdb up</code> (running containers left alone; main's Blackbox re-applied), <code>vdb ledger upgrade --all</code> , <code>vdb start</code> . (6) Replaces <code>vdb</code> on the computer — macOS: write-and-rename (sudo if needed); Windows: the running <code>vdb.exe</code> is renamed to <code>vdb.exe.old</code> and the new one copied in — keeping the previous copy in <code>~/.vectoradb/updates/prev/</code> , and refreshes the engine <code>vdb setup</code> would install. Then checks the versions and that the control plane answers. On Linux the host binary is the engine, so steps 2–5 run on the machine itself. Never re-imports the distro, recreates storage, changes images or rewrites data files. |
| HOW TO USE      | <code>vdb update</code> (asks to confirm) · <code>--check</code> only reports · <code>--yes / -y</code> no prompt (required without a terminal) · <code>--version vX.Y.Z</code> a specific newer release. Going back: reinstall the older version with the installer ( <code>VDB_VERSION=...</code> ); the previous binaries are kept.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| HOW TO TEST     | Unit: <code>internal/host/host_update_test.go</code> (step order with a fake VM; check only, up to date, dev build, tampered download, no terminal, stdin closed, answered no and an engine that doesn't run all change nothing; a failed install restarts the old engine and leaves the host binary alone), <code>internal/update/update_test.go</code> (downloads, install with the previous copy kept, Windows-style executable swap, image context replace with path-traversal refusal), <code>cmd/vdb/update_test.go</code> (flags). Integration: <code>make integration-update</code> (Lima VM, Linux path, local fake GitHub). Manual, not automated: on a Mac, <code>vdb start</code> shows the notice and <code>vdb update</code> replaces <code>/usr/local/bin/vdb</code> and the VM engine; on Windows, the <code>vdb.exe</code> swap and image context refresh.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| STATUS & LIMITS | Partial: the Linux path is verified end to end in the VM, and the macOS path was run for real on 16 Sep 2026 (installed v0.8.3 with the installer, then updated to the published v0.8.4: versions, restarted servers, containers, branch data, Blackbox, gateway and UI all checked). It was run a second time for the released fix (v0.8.4 → v0.8.5) with the same checks. The Windows path is unit-tested and compiles but has not been run against a real release — deferred by the owner (16 Sep 2026). The first release that contains <code>vdb update</code> must be installed the usual way. Checksums prove the files match the release, not who published it (no signatures). No automatic rollback: the previous binaries are kept for a manual one. Doesn't update the VM, WSL distro, Postgres or MinIO images. <code>vdb setup</code> 's own engine download (A7) still uses <code>/releases/latest</code> without checksums.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| ADDED IN        | <code>feat/vdb-update</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

# CLI & services

## B1 The vdb command set

Partial

WHAT IT DOES

One CLI for the whole product.

HOW IT WORKS

cmd/vdb/main.go : host.Maybe forwarding, then a command switch with hand-rolled flag parsing ( addrFlag , durFlag , restoreArg ).

HOW TO USE

| Command                                                                                                                                                                                                                                                                                                                               | Purpose                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| vdb version · setup · start · stop · up · down · status · logs [svc] · psql                                                                                                                                                                                                                                                           | Lifecycle, status, logs, psql on main |
| vdb branch create list delete reset [--from p] suspend resume                                                                                                                                                                                                                                                                         | Branches (C2)                         |
| vdb backup create list · vdb restore --to <ts latest>                                                                                                                                                                                                                                                                                 | Durability (D2, D3)                   |
| vdb ha enable status failover disable failback                                                                                                                                                                                                                                                                                        | HA (D4)                               |
| vdb blackbox ... (every ledger subcommand; same as vdb ledger ...) · vdb ledger [branch] [--limit N] · ledger verify · ledger upgrade [branch all] · ledger checkpoint integrity export [branch] · ledger sessions [branch] · ledger diff <a> <b> · ledger entries [branch] · ledger branch-before <id> [--as n] · ledger revert --to | Blackbox (H6–H8, H10, H12, H13)       |
| vdb import --from <src> [--as n] [--continuous] · vdb import-cutover <n>                                                                                                                                                                                                                                                              | Import (I*)                           |
| vdb pipeline run spec.json [--as n]                                                                                                                                                                                                                                                                                                   | Pipelines (J1)                        |
| vdb impact "<SQL>" [--branch] [--object] [--column] [--json] · vdb branch diff <a> <b>                                                                                                                                                                                                                                                | Impact analysis and diff (H17, H18)   |
| vdb policy [list]   check "<SQL>"   block warn enable disable remove <rule>   add <rule> ...   evaluations                                                                                                                                                                                                                            | Policy gate (H15)                     |
| vdb user create · vdb apikey create list revoke · vdb admin grant revoke list [--branch]                                                                                                                                                                                                                                              | Accounts (G2, G3, H8)                 |
| vdb gateway [--addr :6432] [--idle 2m] · vdb controlplane [--addr :8080] · vdb serve [--addr :8088] · vdb mcp                                                                                                                                                                                                                         | Run a service in the foreground       |

HOW TO TEST

Unit: cmd/vdb/main\_test.go — TestAddrFlag, TestDurFlag, TestRestoreArg. Behaviour via scripts/integration\_test.sh .

STATUS & LIMITS

vdb vm is listed as a local command ( host.go ) but has no implementation ("unknown command"). branch create has no --from .

ADDED IN

a7580f6 (initial); renamed vectoradb → vdb in c9afda7 .

## B2 Background services (daemon)

Working

|                 |                                                                                                                                                                                                                                                      |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | <code>vdb start</code> runs three detached TLS servers: control plane :8080 (REST + web UI), gateway :6432 (idle 2m), agent API :8088 .                                                                                                              |
| HOW IT WORKS    | <code>internal/daemon</code> : re-executes the binary per service, logs to <code>~/.vectoradb/&lt;name&gt;.log</code> , pidfile <code>&lt;name&gt;.pid</code> , <code>Setsid detach</code> ; <code>Stop</code> sends SIGTERM then SIGKILL after ~3s. |
| HOW TO USE      | <code>vdb start</code> · <code>vdb status</code> · <code>vdb logs gateway api controlplane</code> · <code>vdb stop</code>                                                                                                                            |
| HOW TO TEST     | Unit: <code>daemon_test.go</code> TestStopTerminatesProcess. Integration §1 (stop/start).                                                                                                                                                            |
| STATUS & LIMITS | Working. No health check or restart-on-crash.                                                                                                                                                                                                        |
| ADDED IN        | <code>a7580f6</code> .                                                                                                                                                                                                                               |

## Branching & storage

### C1 Storage drivers (ZFS / btrfs)

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Instant copy-on-write copies of a whole Postgres data directory. ZFS on macOS/Linux, btrfs on Windows.                                                                                                                                                                                                                                                                                                                                                                                                     |
| HOW IT WORKS    | <code>internal/branch/storage.go</code> : storage interface; <code>activeStorage()</code> picks by <code>VECTORADB_STORAGE</code> .<br>ZFS: pool <code>vectoradb</code> on a file ( <code>VECTORADB_ZPOOL_DEVICE</code> , size <code>VECTORADB_ZPOOL_SIZE</code> =30G), clone = <code>zfs snapshot ...@for-&lt;dst&gt; + zfs clone</code> . btrfs: loop image at <code>/vectoradb/branches</code> , clone = <code>btrfs subvolume snapshot</code> , new subvolumes get <code>chattr +C</code> (nodatacow). |
| HOW TO USE      | Automatic (Windows launcher sets <code>VECTORADB_STORAGE=btrfs</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| HOW TO TEST     | Integration §2 (branch isolation). Manual: <code>vdb branch create t1 &amp;&amp; sudo zfs list -r vectoradb</code> .                                                                                                                                                                                                                                                                                                                                                                                       |
| STATUS & LIMITS | Working. ZFS <code>destroy</code> only removes the parent snapshot when the parent is <code>main</code> , so repeated <code>reset --from &lt;non-main&gt;</code> may fail.                                                                                                                                                                                                                                                                                                                                 |
| ADDED IN        | ZFS <code>a7580f6</code> ; driver split + btrfs <code>fc4a1b8</code> , nodatacow <code>81ff8f8</code> (PR #9).                                                                                                                                                                                                                                                                                                                                                                                             |

### C2 Branch lifecycle

Working

|                 |                                                                                                                                                                                                                                                  |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Create, list, delete, reset (start over from parent), suspend and resume isolated full copies of the database.                                                                                                                                   |
| HOW IT WORKS    | <code>branch.go</code> : Create (CHECKPOINT parent, clone, chown, start container, <code>waitReady</code> over TCP), Delete , Reset (delete + create), List , Suspend ( <code>docker stop</code> ), Resume , Wake → <code>EnsureRunning</code> . |
| HOW TO USE      | <code>vdb branch create qa . list . suspend qa . resume qa . reset qa [--from main] . delete qa ; REST POST/DELETE /api/branches</code> .                                                                                                        |
| HOW TO TEST     | Unit: <code>TestContainerName</code> . Integration §2 (isolation), §4 (suspend/resume). Manual: the command sequence above.                                                                                                                      |
| STATUS & LIMITS | Working. CLI create does no name validation (REST does).                                                                                                                                                                                         |
| ADDED IN        | <code>a7580f6</code> ; reset <code>00e7eae</code> (PR #13); TCP readiness <code>cb6655c</code> (PR #21).                                                                                                                                         |

### C3 Protection of main

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Stops the primary from being deleted or reset by mistake.                                                                                                                                                                                                                                                                                                                                                        |
| HOW IT WORKS    | Delete and Reset refuse <code>main</code> ; Suspend refuses <code>main</code> , the HA standby, and whichever container is serving main after a failover ( <code>suspendRefusal</code> , so the CLI and REST both get it); <code>EnsureRunning</code> never auto-starts main (avoids split-brain after failover); the reaper never suspends main, restore or standby; ZFS reservation keeps space for main (C6). |
| HOW TO USE      | Automatic.                                                                                                                                                                                                                                                                                                                                                                                                       |
| HOW TO TEST     | Unit: <code>TestSuspendRefusal</code> , <code>TestPrimaryPointerGuards</code> . Integration §4 (suspending main refused, main keeps running), §6 (suspending the promoted standby refused). Manual: <code>vdb branch delete main</code> → "refusing to delete the primary branch 'main'".                                                                                                                        |
| STATUS & LIMITS | Working. Until 15 Sep 2026 <code>vdb branch suspend main</code> was allowed from the CLI and left main stopped (the gateway doesn't wake it) — now refused.                                                                                                                                                                                                                                                      |
| ADDED IN        | <code>a7580f6</code> .                                                                                                                                                                                                                                                                                                                                                                                           |

## C4 Private networking (no host ports)

Working

|                 |                                                                                                                                                                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Branch databases are reachable only through the gateway, not directly from the host or LAN.                                                                                                                                                                                                                                 |
| HOW IT WORKS    | Containers <code>vec-&lt;name&gt;</code> join docker network <code>vectoradb</code> with no published ports; the gateway dials the container IP ( <code>BackendAddr</code> → <code>containerIP</code> ; main via <code>PrimaryContainer()</code> ).<br><code>VECTORADB_DEBUG_PORTS</code> re-publishes ports for debugging. |
| HOW TO USE      | Automatic.                                                                                                                                                                                                                                                                                                                  |
| HOW TO TEST     | Unit: <code>TestParsePublishedPort</code> , <code>TestDSN</code> . Manual: <code>docker ps</code> shows no <code>5432</code> mapping for <code>vec-*</code> .                                                                                                                                                               |
| STATUS & LIMITS | Working. Exceptions: <code>vec-restore</code> publishes 5433, HA standby a random port, MinIO 9000/9001.                                                                                                                                                                                                                    |
| ADDED IN        | <code>797bc14</code> , <code>b664b56</code> (PR #11).                                                                                                                                                                                                                                                                       |

## C5 Scale-to-zero & wake on connect

Working

|                 |                                                                                                                                                                                                                                                                                                                                     |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Idle branches stop automatically; the next connection wakes them.                                                                                                                                                                                                                                                                   |
| HOW IT WORKS    | Gateway <code>reaper</code> ( <code>proxy.go</code> ) polls every idle/3 (5–30s) and suspends a branch only when <code>idle ≥ threshold</code> and <code>ActiveConnections = 0</code> . On connect, <code>EnsureRunning</code> routes, recreates or resumes the container and re-enables the guard ( <code>reconcileGuard</code> ). |
| HOW TO USE      | <code>vdb gateway --idle 2m</code> (default via <code>vdb start</code> ); <code>--idle 0</code> disables.                                                                                                                                                                                                                           |
| HOW TO TEST     | Integration §7 (idle 8s: branch suspended, standby untouched). Manual: wait >2 min, then connect through the gateway.                                                                                                                                                                                                               |
| STATUS & LIMITS | Working. Idle clocks are in memory (reset on gateway restart). Cold-start latency not measured.                                                                                                                                                                                                                                     |
| ADDED IN        | <code>a7580f6</code> .                                                                                                                                                                                                                                                                                                              |

## C6 Storage quotas

Partial

|                 |                                                                                                                                                                                         |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Reserves space for <code>main</code> and optionally caps each branch.                                                                                                                   |
| HOW IT WORKS    | <code>reserveMain</code> : <code>zfs set reservation</code> (default 2G) on every Init. <code>setBranchRefquota</code> : <code>zfs set refquota</code> on new branches when configured. |
| HOW TO USE      | <code>VECTORADB_MAIN_RESERVATION=5G VECTORADB_BRANCH_REFQUOTA=20G vdb start</code> ( <code>none</code> disables).                                                                       |
| HOW TO TEST     | Manual: <code>sudo zfs get reservation,refquota vectoradb/branches/main vectoradb/branches/qa</code> .                                                                                  |
| STATUS & LIMITS | ZFS only; per-branch cap is opt-in (default uncapped); not implemented on btrfs.                                                                                                        |
| ADDED IN        | <code>21f7259</code> (PR #12).                                                                                                                                                          |

## C7 Capacity & status

Working

|                 |                                                                                                                                                                               |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Shows services, main health, backups, branches, storage used/available.                                                                                                       |
| HOW IT WORKS    | <code>Status</code> , <code>Branches</code> (state, used, referenced, connections), <code>StorageInfo</code> ( <code>zfs list</code> / <code>btrfs filesystem usage</code> ). |
| HOW TO USE      | <code>vdb status</code> ; <code>GET /api/status</code> ; web Dashboard.                                                                                                       |
| HOW TO TEST     | Integration §1 ( <code>mainReady</code> ). Manual: <code>vdb status</code> .                                                                                                  |
| STATUS & LIMITS | Working. On btrfs "used" is apparent size, not the copy-on-write delta.                                                                                                       |
| ADDED IN        | <code>a7580f6</code> ; <code>StorageInfo</code> <code>4b0be5c</code> .                                                                                                        |

## C8 Provisioning & image pull

Working

|                 |                                                                                                                                                                                                                                                                                                    |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | <code>vdb up/start</code> prepares Docker, the storage pool and the Postgres image automatically.                                                                                                                                                                                                  |
| HOW IT WORKS    | <code>provision.go</code> : <code>ensureDocker</code> → <code>ensurePool</code> → <code>ensureImage</code> (inspect, else <code>docker pull ghcr.io/vectoradb/postgres-walg:16</code> , else <code>docker build</code> from <code>VECTORADB_IMAGE_CONTEXT</code> / <code>docker/postgres</code> ). |
| HOW TO USE      | Automatic.                                                                                                                                                                                                                                                                                         |
| HOW TO TEST     | Manual: <code>sudo docker rmi ghcr.io/vectoradb/postgres-walg:16</code> ; <code>vdb up</code> .                                                                                                                                                                                                    |
| STATUS & LIMITS | Working; the pull needs the GHCR package to be public.                                                                                                                                                                                                                                             |
| ADDED IN        | <code>c9afda7</code> ; GHCR pull <code>aae9e20</code> (PR #12).                                                                                                                                                                                                                                    |

# Durability

## D1 WAL archiving to object storage

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Continuously ships main's write-ahead log to a local S3-compatible store, off the commit path.                                                                                                                                                                                                                                                                                                                                                              |
| HOW IT WORKS    | <code>Up</code> starts MinIO ( <code>quay.io/minio/minio:RELEASE.2025-09-07T16-13-09Z</code> , generated credentials) and creates bucket <code>vectoradb-wal</code> ; main runs with <code>archive_mode=on</code> , <code>archive_command='wal-g wal-push %p'</code> , <code>archive_timeout=60</code> , <code>lz4</code> .                                                                                                                                 |
| HOW TO USE      | Automatic with <code>vdb start</code> . MinIO console at <code>:9001</code> .                                                                                                                                                                                                                                                                                                                                                                               |
| HOW TO TEST     | Integration §3. Manual: log in to MinIO with values from <code>~/.vectoradb/secrets.json</code> and see WAL files.                                                                                                                                                                                                                                                                                                                                          |
| STATUS & LIMITS | Working. MinIO images unpinned; branches don't archive. <b>Images:</b> MinIO stopped publishing to Docker Hub, so the server and client images come from quay.io, pinned to the tested releases ( <code>internal/branch/images.go</code> ); an install that already has <code>minio/minio:latest</code> / <code>minio/mc:latest</code> cached keeps using them, and <code>VECTORADB_MINIO_IMAGE</code> / <code>VECTORADB_MC_IMAGE</code> point at a mirror. |
| ADDED IN        | <code>a7580f6</code> ; generated credentials <code>797bc14</code> .                                                                                                                                                                                                                                                                                                                                                                                         |

## D2 Base backups

Working

|                 |                                                                                                                                                 |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Takes and lists full base backups of main.                                                                                                      |
| HOW IT WORKS    | <code>Backup</code> : <code>docker exec vec-main wal-g backup-push</code> ; <code>BackupList</code> : <code>wal-g backup-list --detail</code> . |
| HOW TO USE      | <code>vdb backup create</code> · <code>vdb backup list</code>                                                                                   |
| HOW TO TEST     | Integration §3.                                                                                                                                 |
| STATUS & LIMITS | Manual only (no schedule or retention). Always targets <code>vec-main</code> , even after an HA failover.                                       |
| ADDED IN        | <code>a7580f6</code> .                                                                                                                          |

## D3 Point-in-time restore

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Brings up a separate copy of main at a past timestamp (or latest) on port 5433.                                                                                                                                                                                                                                                                                                                                                                        |
| HOW IT WORKS    | <code>Restore</code> runs the image with <code>restore-entripoint.sh</code> : <code>wal-g backup-fetch LATEST</code> , <code>recovery_target_time</code> , <code>promote</code> ; <code>waitRecovered</code> polls up to 80s.                                                                                                                                                                                                                          |
| HOW TO USE      | <code>vdb restore --to '2026-09-14 10:00:00+00'</code> or <code>--to latest</code>                                                                                                                                                                                                                                                                                                                                                                     |
| HOW TO TEST     | Integration §3 ("PITR restores 3 rows"); integration-v2 §1a (no <code>minioadmin</code> in the restore container, no hardcoded password printed).                                                                                                                                                                                                                                                                                                      |
| STATUS & LIMITS | Uses the per-install MinIO credentials (fixed in Blackbox 2.0 Phase 1 — a hardcoded <code>minioadmin</code> pair used to make restore fail on fresh installs), and the printed hint no longer shows a password. Still always fetches the LATEST base backup, so a time before that backup can't be reached. (Branching from before a ledger entry, H13, is a separate path that picks the right backup; <code>vdb restore</code> itself is unchanged.) |
| ADDED IN        | <code>a7580f6</code> ; broke with <code>797bc14</code> (PR #11); fixed in <code>feat/ledger2-phase1-security</code> .                                                                                                                                                                                                                                                                                                                                  |

## D4 HA standby & failover

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | A single-VM demo of an asynchronous hot standby with manual failover.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| HOW IT WORKS    | <code>ha.go</code> : <code>HAEnable</code> (replication hba rule, <code>pg_basebackup -R</code> , start <code>vec-standby</code> ); <code>HAFailover</code> ( <code>pg_promote()</code> , stop old primary, write <code>standby</code> to <code>~/.vectoradb/primary</code> so the gateway routes main to it); <code>HADisable</code> ; <code>HAStatus</code> . After a failover <code>haGuard</code> refuses <code>enable</code> , <code>disable</code> and <code>failover</code> (each would delete or stop the promoted standby, the only primary), and <code>Init</code> ( <code>vdb up / start</code> ) brings the promoted standby up — recreating its container from its storage if <code>vdb stop</code> removed it — instead of restarting the stale old main as a second primary. <code>HAFailback</code> returns to main without losing writes: main's data directory is rebuilt with <code>pg_basebackup</code> from the standby (the dataset is kept, since branches clone its snapshots), main starts as a streaming replica and catches up, the standby is stopped cleanly, main replays up to the standby's final checkpoint (read with <code>pg_controldata</code> ), then main is promoted, the pointer goes back to <code>main</code> and the old standby is removed. Any failure before the promotion restarts the standby and leaves it primary. |
| HOW TO USE      | <code>vdb ha enable   status   failover   disable   failback</code> — after a failback, take <code>vdb backup create</code> and <code>vdb ha enable</code> for a new standby.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| HOW TO TEST     | Unit: <code>internal/branch/ha_test.go</code> ( <code>TestHAGuard</code> , <code>TestPrimaryPointerGuards</code> , <code>TestLSNAtLeast</code> , <code>TestParseControlCheckpoint</code> ). Integration §6: streaming replica; write after failover; <code>ha enable disable failover</code> and suspending the standby refused; <code>vdb up</code> after the standby's container is removed recreates it and leaves the old main stopped; <code>ha failback</code> exits 0, main is primary and not in recovery, the post-failover write is on main, the standby is gone, the gateway writes to main, WAL archiving resumed. §7.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| STATUS & LIMITS | Demo: no automatic detection, fencing or multi-host. The promoted standby doesn't archive WAL, so backups and point-in-time restore don't cover the time main runs on it; failback resumes archiving and asks for a fresh base backup. Failback briefly stops writes (between stopping the standby and promoting main). Fixed 15 Sep 2026: <code>ha enable</code> or <code>ha disable</code> after a failover deleted the live primary and the writes made since, and <code>vdb up</code> restarted the old main as a second primary.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| ADDED IN        | <code>a7580f6</code> ; btrfs support <code>fc4a1b8</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

# Security foundations

## E1 Per-install generated secrets

Working

|                 |                                                                                                                                                                                                                                                                                                                                                               |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Every install gets its own Postgres and MinIO passwords — nothing hardcoded.                                                                                                                                                                                                                                                                                  |
| HOW IT WORKS    | <code>internal/secrets : Load()</code> reads or creates <code>~/.vectoradb/secrets.json</code> (0600, atomic write) with <code>crypto/rand</code> values ( <code>pg_password</code> , <code>minio_user</code> , <code>minio_password</code> ); env overrides are applied but never written. Used by the engine, gateway backend login and role password sync. |
| HOW TO USE      | Automatic. Env <code>VECTORADB_PG_PASSWORD</code> , <code>VECTORADB_MINIO_USER</code> , <code>VECTORADB_MINIO_PASSWORD</code> .                                                                                                                                                                                                                               |
| HOW TO TEST     | Indirect (TestDSN isolates HOME). Manual: <code>cat ~/.vectoradb/secrets.json</code> in the VM.                                                                                                                                                                                                                                                               |
| STATUS & LIMITS | Working, except PITR ignores it (D3). Process-local caching only.                                                                                                                                                                                                                                                                                             |
| ADDED IN        | 797bc14 (PR #11).                                                                                                                                                                                                                                                                                                                                             |

## E2 TLS everywhere

Working

|                 |                                                                                                                                                                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Gateway, control plane and agent API all serve TLS with zero setup; clients can use <code>sslmode=require</code> .                                                                                                                                                                                                          |
| HOW IT WORKS    | <code>internal/tlsutil : EnsureCert</code> uses <code>VECTORADB_TLS_CERT / _KEY</code> or generates a self-signed ECDSA P-256 cert (10 years, SAN localhost/127.0.0.1/::1) under <code>~/.vectoradb/tls</code> with a cross-process file lock; min TLS 1.2. Gateway answers SSLRequest with 'S' and upgrades; GSS gets 'N'. |
| HOW TO USE      | <code>psql "postgresql://vectoradb:&lt;key&gt;@localhost:6432/main?sslmode=require"</code> ; <code>curl -k https://localhost:8080/api/status</code> .                                                                                                                                                                       |
| HOW TO TEST     | Unit: <code>TestReadStartupSkipsSSL</code> , <code>TestReadStartupUpgradesTLS</code> . Manual: <code>openssl s_client -connect localhost:8080</code> .                                                                                                                                                                      |
| STATUS & LIMITS | Working. TLS is optional at the gateway (a <code>sslmode=disable</code> client still connects, sending its key in cleartext). Servers fall back to plain HTTP if the cert can't load.                                                                                                                                       |
| ADDED IN        | 0bd52f3 ; file lock b664b56 (PR #11).                                                                                                                                                                                                                                                                                       |

## E3 Zero-signup local API key

Working

|                 |                                                                                                                                                                                                               |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | The first <code>vdb start</code> prints a working connection string with an API key already inside.                                                                                                           |
| HOW IT WORKS    | <code>bootstrapLocalKey (main.go):reuse api_key=</code> from <code>~/.vectoradb/config</code> , else if no users exist create <code>local@vectoradb</code> + key setup and save it (0600). Never fails start. |
| HOW TO USE      | <code>vdb start</code> and read the banner.                                                                                                                                                                   |
| HOW TO TEST     | Manual: fresh HOME, <code>vdb start</code> , <code>cat ~/.vectoradb/config</code> .                                                                                                                           |
| STATUS & LIMITS | Working. Key stored in plaintext by design; on Windows the setup summary doesn't show it.                                                                                                                     |
| ADDED IN        | dcc32ab (PR #11).                                                                                                                                                                                             |

## SQL gateway

### F1 Routing by database name

Working

|                 |                                                                                                                                                                                                                                                                                                                           |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | One Postgres endpoint ( :6432 ); the database name you connect to is the branch.                                                                                                                                                                                                                                          |
| HOW IT WORKS    | <code>proxy.Serve</code> → <code>handle</code> : reads the <code>StartupMessage</code> (protocol 3.0, ≤1 MiB), <code>EnsureRunning(target)</code> , rewrites <code>database</code> → <code>vectoradb</code> and <code>user</code> → login role, then relays bytes both ways. No <code>dbname</code> → <code>main</code> . |
| HOW TO USE      | <code>psql "postgresql://vectoradb:&lt;key&gt;@localhost:6432/qa?sslmode=require"</code>                                                                                                                                                                                                                                  |
| HOW TO TEST     | Unit: <code>TestBuildParseStartupRoundtrip</code> . Integration §1, §6.                                                                                                                                                                                                                                                   |
| STATUS & LIMITS | Working. No pooling or rate limiting.                                                                                                                                                                                                                                                                                     |
| ADDED IN        | <code>a7580f6</code> .                                                                                                                                                                                                                                                                                                    |

### F2 API-key authentication

Working

|                 |                                                                                                                                                                                                                                              |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Every client must use a <code>vdb_</code> API key as its Postgres password.                                                                                                                                                                  |
| HOW IT WORKS    | <code>requestClientPassword</code> asks for a cleartext password (inside TLS), <code>VerifyKey</code> checks it; bad key → <code>28P01 invalid API key</code> . <code>AuthenticationOk</code> is sent only after the backend login succeeds. |
| HOW TO USE      | <code>PGPASSWORD=vdb_... psql "postgresql://vectoradb@localhost:6432/main?sslmode=require"</code>                                                                                                                                            |
| HOW TO TEST     | Integration §1 (bad key rejected, key accepted).                                                                                                                                                                                             |
| STATUS & LIMITS | Working.                                                                                                                                                                                                                                     |
| ADDED IN        | <code>e42e792</code> ; auth store <code>235ff41</code> .                                                                                                                                                                                     |

### F3 Backend login (SCRAM)

Working

|                 |                                                                                                                                                             |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | The gateway logs in to the branch itself, so clients never see the database password.                                                                       |
| HOW IT WORKS    | <code>backendAuth</code> ( <code>auth.go</code> ) supports cleartext, md5 and SCRAM-SHA-256 using the per-install password; failures → <code>08006</code> . |
| HOW TO USE      | Automatic.                                                                                                                                                  |
| HOW TO TEST     | Exercised by integration §1, §6, §8 (no unit test for SCRAM).                                                                                               |
| STATUS & LIMITS | Working.                                                                                                                                                    |
| ADDED IN        | <code>e42e792</code> .                                                                                                                                      |

### F4 Per-user Postgres login roles

Working

|                 |                                                                                                                                                                                                                                                                      |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Each user logs in as a role named after their email, so the ledger's actor ( <code>session_user</code> ) can't be forged; permissions stay those of non-superuser <code>vdbclient</code> (RLS and GRANTS apply).                                                     |
| HOW IT WORKS    | <code>loginUser</code> → <code>branch.EnsureUserRole</code> : <code>CREATE ROLE &lt;email&gt; LOGIN NOSUPERUSER ... IN ROLE vdbclient</code> , <code>ALTER ROLE ... SET role = vdbclient</code> ; cached per process; falls back to <code>vdbclient</code> on error. |
| HOW TO USE      | Automatic. Check with <code>select session_user, current_user;</code> → <code>&lt;email&gt;</code> , <code>vdbclient</code> .                                                                                                                                        |
| HOW TO TEST     | Manual query above (no automated test).                                                                                                                                                                                                                              |
| STATUS & LIMITS | Working. Roles share the per-install password (the gateway authenticates the user, not Postgres).                                                                                                                                                                    |
| ADDED IN        | <code>96c8c31</code> (role split <code>aad84e4</code> ).                                                                                                                                                                                                             |

## F5 Attribution session settings

Working

|                 |                                                                                                                                                                                                                     |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Tags every session with who, what kind, which branch and a session id for the Blackbox.                                                                                                                             |
| HOW IT WORKS    | <code>ledgerOptions</code> appends <code>-c vdb.actor=&lt;email&gt; vdb.actor_kind=human agent vdb.branch=&lt;b&gt;vdb.session=&lt;random&gt; ; agent</code> when the branch name starts with <code>agent-</code> . |
| HOW TO USE      | Automatic. <code>SHOW vdb.actor;</code>                                                                                                                                                                             |
| HOW TO TEST     | Integration §8 (DDL attributed to the human key).                                                                                                                                                                   |
| STATUS & LIMITS | Working; <code>actor_kind</code> , <code>branch</code> , <code>session</code> are ordinary settings a client could change (the actor itself comes from F4).                                                         |
| ADDED IN        | <code>e42e792</code> .                                                                                                                                                                                              |

## F6 Ctrl-C (CancelRequest) forwarding

Working

|                 |                                                                                                                                                                                                |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Pressing Ctrl-C in psql cancels a running query through the gateway.                                                                                                                           |
| HOW IT WORKS    | <code>relayStartupCaptureKey</code> records <code>BackendKeyData</code> ( <code>pid:secret</code> → backend address); <code>forwardCancel</code> replays a cancel packet to the right backend. |
| HOW TO USE      | <code>select pg_sleep(60);</code> then Ctrl-C → "canceling statement due to user request".                                                                                                     |
| HOW TO TEST     | Unit: <code>TestReadStartupHandlesCancel</code> . Manual as above.                                                                                                                             |
| STATUS & LIMITS | Working; the key map lives in one gateway process.                                                                                                                                             |
| ADDED IN        | <code>4758737</code> / <code>4cccbd6</code> (PR #17).                                                                                                                                          |

## F7 Errors & insecure build tag

Working

|                 |                                                                                                                                                                                                                                                          |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Failures reach clients as real Postgres errors; the no-auth bypass can't exist in release builds.                                                                                                                                                        |
| HOW IT WORKS    | <code>sendError</code> writes FATAL <code>ErrorResponses</code> ( <code>28P01</code> , <code>3D000</code> branch missing, <code>08006</code> ).<br><code>VECTORADB_GATEWAY_NOAUTH</code> only works in binaries built with <code>-tags insecure</code> . |
| HOW TO USE      | Connect to a missing branch → <code>FATAL: branch "x" does not exist</code> .                                                                                                                                                                            |
| HOW TO TEST     | Unit: <code>TestSendError</code> .                                                                                                                                                                                                                       |
| STATUS & LIMITS | Working.                                                                                                                                                                                                                                                 |
| ADDED IN        | <code>a7580f6</code> ; insecure tag <code>1884445</code> (PR #12).                                                                                                                                                                                       |

## Accounts & auth

### G1 Auth store (SQLite)

Working

|                 |                                                                                                                                                                                                                                   |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Stores users, API keys, sessions, OAuth identities, pipelines and runs for a single-tenant install.                                                                                                                               |
| HOW IT WORKS    | <code>internal/auth</code> : <code>OpenFromEnv</code> ( <code>VECTORADB_DB</code> , default <code>~/vectoradb/vectoradb.db</code> in the VM), pure-Go SQLite with WAL + <code>busy_timeout</code> so all three services share it. |
| HOW TO USE      | Automatic.                                                                                                                                                                                                                        |
| HOW TO TEST     | Unit: <code>TestVerifyKeyConcurrent</code> .                                                                                                                                                                                      |
| STATUS & LIMITS | Working. Every signed-in user can see every branch (no RBAC).                                                                                                                                                                     |
| ADDED IN        | <code>235ff41</code> (PR #1); WAL <code>c2dd024</code> .                                                                                                                                                                          |

### G2 Email & password users

Working

|                 |                                                                                                                                                                               |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Create an account and log in with email + password.                                                                                                                           |
| HOW IT WORKS    | <code>CreateUser</code> (lower-cased email, bcrypt), <code>Login</code> (generic "invalid credentials"); 8-char minimum enforced in the CLI and <code>/auth/register</code> . |
| HOW TO USE      | <code>vdb user create you@x.com</code> ; <code>POST /auth/register</code> , <code>POST /auth/login</code> .                                                                   |
| HOW TO TEST     | Unit: <code>TestPasswordLogin</code> . Integration §1.                                                                                                                        |
| STATUS & LIMITS | Working. No password change/reset, user list or delete.                                                                                                                       |
| ADDED IN        | <code>235ff41</code> .                                                                                                                                                        |

### G3 API keys

Working

|                 |                                                                                                                                                                                       |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Non-interactive credentials for REST (Bearer / <code>X-API-Key</code> ) and the gateway.                                                                                              |
| HOW IT WORKS    | Secret <code>vdb_</code> + 24 random bytes; only the sha256 is stored; shown once; per-user list/revoke; <code>last_used</code> updated at most once a minute.                        |
| HOW TO USE      | <code>vdb apikey create &lt;email&gt; [name]</code> · <code>list</code> · <code>revoke</code> ; <code>GET/POST /api/keys</code> , <code>DELETE /api/keys/{id}</code> ; web Keys page. |
| HOW TO TEST     | Unit: <code>TestAPIKeys</code> . Integration §1.                                                                                                                                      |
| STATUS & LIMITS | Working. Revoking an unknown id still returns success.                                                                                                                                |
| ADDED IN        | <code>235ff41</code> .                                                                                                                                                                |

### G4 Web sessions & signup control

Working

|                 |                                                                                                                                                                                                                                                                                       |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Browser login sessions; self-signup can be closed.                                                                                                                                                                                                                                    |
| HOW IT WORKS    | 30-day session token in <code>HttpOnly</code> cookie <code>vdb_session</code> ; <code>Authn</code> accepts cookie, Bearer or <code>X-API-Key</code> . <code>VECTORADB_SIGNUP=closed</code> makes register return 403; <code>GET /auth/providers</code> tells the UI what's available. |
| HOW TO USE      | <code>/auth/login</code> , <code>/auth/logout</code> , <code>/auth/me</code> ; <code>VECTORADB_SIGNUP=closed</code> <code>vdb start</code> .                                                                                                                                          |
| HOW TO TEST     | Unit: <code>TestSessions</code> . Manual: <code>curl -k https://localhost:8080/auth/providers</code> .                                                                                                                                                                                |
| STATUS & LIMITS | Working. Signup is open by default: anyone who can reach <code>:8080</code> can register.                                                                                                                                                                                             |
| ADDED IN        | <code>235ff41</code> .                                                                                                                                                                                                                                                                |

## G5 OAuth (GitHub / Google)

Partial

|                 |                                                                                                                                                                                                                                       |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | "Continue with GitHub / Google" sign-in.                                                                                                                                                                                              |
| HOW IT WORKS    | <code>oauth.go</code> : state cookie, code exchange, identity fetch, <code>upsertOAuth</code> links by email; redirects to <code>VECTORADB_WEB_ORIGIN/dashboard</code> .                                                              |
| HOW TO USE      | Set <code>VECTORADB_GITHUB_CLIENT_ID/_SECRET</code> or <code>VECTORADB_GOOGLE_CLIENT_ID/_SECRET</code> , plus <code>VECTORADB_PUBLIC_URL=https://localhost:8080</code> and <code>VECTORADB_WEB_ORIGIN=https://localhost:8080</code> . |
| HOW TO TEST     | No automated test. Manual: register an OAuth app with callback <code>https://localhost:8080/auth/oauth/github/callback</code> .                                                                                                       |
| STATUS & LIMITS | Defaults are stale ( <code>http://localhost:8080</code> , <code>http://localhost:5173</code> ), so it only works with both URLs set explicitly. Untested.                                                                             |
| ADDED IN        | <code>235ff41</code> .                                                                                                                                                                                                                |

# Blackbox (the record of schema changes, formerly the Schema Ledger)

The ledger lives inside each branch database ( `vdb.schema_ledger` ), installed into `main` by `InstallLedger` during `Init` and inherited by every branch through the copy-on-write clone. Source: `internal/ledger/ledger.sql`.

## H1 DDL recording

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Records every schema change — who, with which tool, on which branch, the statement, its status and risk.                                                                                                                                                                                                                                                                                                                                                                                  |
| HOW IT WORKS    | Event triggers: <code>ddl_command_end</code> → <code>log_ddl_end</code> (one row per object, incl. GRANT/REVOKE and function DDL); <code>sql_drop</code> → <code>log_ddl_drop</code> . Skips objects in schema <code>vdb</code> , COMMENT, CREATE EXTENSION, event triggers, CREATE SCHEMA, sequences and <code>_pkey</code> indexes. Columns: id, at, actor, actor_kind, tool, session, branch, command_tag, object_type, object_identity, statement, status, risk, prev_hash, row_hash. |
| HOW TO USE      | Automatic for all clients (gateway, console, psql, ORMs, imports).                                                                                                                                                                                                                                                                                                                                                                                                                        |
| HOW TO TEST     | Integration §8 ("ledger captures DDL, attributed to the human key").                                                                                                                                                                                                                                                                                                                                                                                                                      |
| STATUS & LIMITS | Working. Not captured: DML, role/database/tablespace changes (Postgres doesn't fire event triggers for those); some dropped object types (triggers, policies, extensions).                                                                                                                                                                                                                                                                                                                |
| ADDED IN        | <code>e42e792</code> ; GRANT/REVOKE/function DDL <code>db9dc0c</code> (PR #13).                                                                                                                                                                                                                                                                                                                                                                                                           |

## H2 Hash chain, append-only & verify

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                         |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Makes the ledger tamper-evident: rows can't be edited/deleted normally, and any break in the chain is detected.                                                                                                                                                                                                                                         |
| HOW IT WORKS    | <code>chain_row</code> BEFORE INSERT sets <code>row_hash = sha256(prev_hash id at(UTC) ... risk)</code> under <code>pg_advisory_xact_lock</code> . <code>vdb_append_only</code> / <code>vdb_no_truncate</code> triggers + REVOKE block UPDATE/DELETE/TRUNCATE. <code>LedgerVerify</code> recomputes every hash and link.                                |
| HOW TO USE      | <code>vdb ledger verify [branch]</code> ; GET <code>/api/branches/{name}/ledger/verify</code> ; MCP <code>verify_ledger</code> ; SDK <code>verify_ledger()</code> . Also <code>vdb blackbox verify</code> , <code>.../blackbox/verify</code> , MCP <code>verify_blackbox</code> , SDK <code>verify_blackbox</code> / <code>verifyBlackbox</code> (H14). |
| HOW TO TEST     | Integration §8 (plain DELETE blocked; 0 broken rows). Manual: <code>vdb ledger verify</code> → "ledger intact — N rows...".                                                                                                                                                                                                                             |
| STATUS & LIMITS | A superuser can bypass the triggers ( <code>session_replication_role=replica</code> ) and rewrite the whole chain so this check still passes. Since Phase 3, <code>vdb ledger integrity</code> and <code>vdb-verify</code> (H10–H12) catch that by checking against anchors kept outside the database. <code>vdb.policy</code> is not covered.          |
| ADDED IN        | <code>db9dc0c</code> , <code>d14d9a1</code> (PR #13).                                                                                                                                                                                                                                                                                                   |

## H3 Attribution

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Records who made each change and whether it was a human or an agent.                                                                                                                                                                                                                                                                                                                                                                                   |
| HOW IT WORKS    | <code>vdb._ctx</code> : actor = <code>session_user</code> (per-user role, F4) unless the login is <code>vectoradb</code> / <code>vdbclient</code> , then the <code>vdb.actor</code> setting; kind = <code>vdb.actor_kind</code> ; tool = <code>application_name</code> ; session = <code>vdb.session</code> or backend pid. Console sets actor to the signed-in email; agent branches get <code>vdb.actor='agent-&lt;id&gt;'</code> database defaults. |
| HOW TO USE      | Automatic.                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| HOW TO TEST     | Integration §8 (actor_kind = human).                                                                                                                                                                                                                                                                                                                                                                                                                   |
| STATUS & LIMITS | Non-forgable for gateway users and, since Phase 1, for agents: each agent branch logs in as its own <code>agent-&lt;id&gt;</code> role. MCP <code>run_sql</code> is attributed to <code>mcp</code> as an agent on non-agent branches. Tool, kind and session remain client-settable.                                                                                                                                                                   |
| ADDED IN        | <code>e42e792</code> ; non-forgable <code>96c8c31</code> (PR #16).                                                                                                                                                                                                                                                                                                                                                                                     |

#### H4 Destructive-DDL guardrail

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Refuses <code>DROP TABLE</code> and <code>DROP SCHEMA</code> before they run, and still records the attempt.                                                                                                                                                                                                                                                                                                                                                                                                                  |
| HOW IT WORKS    | <code>ddl_command_start</code> → <code>guard_ddl_start</code> looks up <code>vdb.policy</code> (seeded <code>DROP TABLE/SCHEMA</code> → block), honours <code>vdb.allow_destructive</code> only when <code>vdb._may_override()</code> is true (H8), and raises <code>insufficient_privilege</code> with a HINT; a <code>dblink</code> insert records status <code>BLOCKED</code> in its own transaction so it survives the rollback. Imports/pipelines disable the trigger temporarily (I9).                                  |
| HOW TO USE      | Automatic: <code>DROP TABLE t;</code> → "VectoraDB guardrail: DROP TABLE is blocked by policy".                                                                                                                                                                                                                                                                                                                                                                                                                               |
| HOW TO TEST     | Integration §8 (DROP blocked; BLOCKED row recorded).                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| STATUS & LIMITS | Since Phase 1 the override is honoured only for superusers and members of <code>vdb_admin</code> (H8); anyone else stays blocked. Each use of the override is recorded in <code>vdb.ledger_ext.override_used</code> (H9). Only <code>block</code> actions work ( <code>flag</code> / <code>allow</code> do nothing); no CLI/API/UI to manage policy. Broader, rule-based checks with <code>warn/block</code> and a machine-readable error are the policy gate (H15), which runs after this guardrail and leaves it unchanged. |
| ADDED IN        | e42e792 .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

#### H5 Risk flags

Partial

|                 |                                                                                                                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Marks risky changes so they stand out.                                                                                                                                                                                               |
| HOW IT WORKS    | Regexes on the query text set status <code>FLAGGED</code> with risk <code>type-change</code> , <code>drop-column</code> or <code>security-definer</code> ; drops get risk <code>drop</code> , blocked attempts <code>policy</code> . |
| HOW TO USE      | Automatic; filter with <code>?risk=</code> / <code>?status=FLAGGED</code> .                                                                                                                                                          |
| HOW TO TEST     | No automated test. Manual: <code>ALTER TABLE t ALTER COLUMN x TYPE text;</code> then <code>vdb ledger</code> .                                                                                                                       |
| STATUS & LIMITS | Text matching only (whole query, not per command); no dependency analysis.                                                                                                                                                           |
| ADDED IN        | e42e792 ; security-definer db9dc0c .                                                                                                                                                                                                 |

#### H6 Blackbox access (CLI / REST / MCP / UI / SDK)

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Read the ledger from anywhere.                                                                                                                                                                                                                                                                                                                                                                                              |
| HOW IT WORKS    | CLI <code>Ledger</code> (psql table, default 50 rows). REST <code>GET /api/branches/{name}/ledger</code> with filters <code>actor</code> , <code>table</code> , <code>risk</code> , <code>status</code> , <code>kind</code> , <code>since</code> , <code>until</code> , <code>limit</code> ( $\leq 2000$ ), <code>offset</code> . MCP <code>changes</code> . Web <code>Ledger</code> page (L5). SDK <code>ledger()</code> . |
| HOW TO USE      | <code>vdb ledger qa --limit 20</code> ; <code>curl -k -H "Authorization: Bearer \$KEY" "https://localhost:8080/api/branches/main/ledger?status=BLOCKED"</code> Blackbox names: <code>vdb blackbox [branch]</code> , <code>GET /api/branches/{name}/blackbox</code> , <code>web /blackbox</code> , SDK <code>blackbox()</code> (H14).                                                                                        |
| HOW TO TEST     | No automated test of the endpoints; manual curl above.                                                                                                                                                                                                                                                                                                                                                                      |
| STATUS & LIMITS | Working. Any signed-in user can read any branch's ledger. No export format.                                                                                                                                                                                                                                                                                                                                                 |
| ADDED IN        | e42e792 ; MCP d62c676 (PR #14).                                                                                                                                                                                                                                                                                                                                                                                             |

#### H7 vdb ledger revert --to

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | A point-in-time restore of <code>main</code> into a disposable container on port 5433 — the same as <code>vdb restore</code> . Nothing is reverted: <code>main</code> and every branch stay as they are. The help and the command's output say so, and point to <code>vdb blackbox branch-before &lt;id&gt;</code> (H13) for a branch holding <code>main</code> as it was just before a change. |
| HOW IT WORKS    | Calls <code>branch.Restore(ts)</code> (D3). No branch argument.                                                                                                                                                                                                                                                                                                                                 |
| HOW TO USE      | <code>vdb blackbox revert --to '&lt;timestamp&gt;' latest</code> (also <code>vdb ledger revert</code> )                                                                                                                                                                                                                                                                                         |
| HOW TO TEST     | Unit: <code>TestUsageDescribesRevertAndFailback</code> (the help describes a restore of <code>main</code> , not a revert of a branch). The restore itself: integration §3 (D3).                                                                                                                                                                                                                 |
| STATUS & LIMITS | Working. The name is kept so scripts don't break; its description no longer claims it reverts a branch (it did until 15 Sep 2026). Inherits D3's limit: always restores from the latest base backup.                                                                                                                                                                                            |
| ADDED IN        | e42e792 .                                                                                                                                                                                                                                                                                                                                                                                       |

## H8 Override permission (vdb\_admin) & ledger upgrade

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Decides who may override the destructive-DDL guardrail, and applies the current ledger definition to branches that already exist.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| HOW IT WORKS    | <code>ledger.sql</code> creates role <code>vdb_admin</code> and <code>vdb._may_override()</code> — true for superusers or members of <code>vdb_admin</code> , checked on <code>session_user</code> (the login identity a client can't change). <code>vdb admin grant</code> ensures the user's per-user role and runs <code>GRANT vdb_admin ( internal/branch/security.go , cmd/vdb/admin.go )</code> . Roles live in each branch's Postgres, so without <code>--branch</code> a change applies to main and every running branch; new branches inherit main's. The first local user created by <code>vdb start</code> is granted automatically. <code>vdb ledger upgrade</code> re-runs the idempotent <code>ledger.sql</code> ; main is also upgraded on every <code>vdb start</code> . |
| HOW TO USE      | <code>vdb admin grant you@x.com</code> · <code>vdb admin list</code> · <code>vdb admin revoke you@x.com --branch qa</code> · <code>vdb ledger upgrade --all</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| HOW TO TEST     | integration-v2 §1b: non-admin override refused with a HINT, admin override works, revoke restores the block, superuser override (imports/pipelines) unaffected.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| STATUS & LIMITS | Verified in the VM (integration-v2 §1b, 14 Sep 2026). <b>Existing installs:</b> the owner runs <code>vdb admin grant &lt;email&gt;</code> once (only brand-new installs grant the first user automatically), and existing branches need <code>vdb ledger upgrade --all</code> . Suspended branches are skipped until running.                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ADDED IN        | Blackbox 2.0 Phase 1 ( <code>feat/ledger2-phase1-security</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## H9 Blackbox 2.0 capture (transaction, WAL position, provenance)

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Records extra context for every ledger row: the transaction id and WAL position of the change, the agent task and tool-call hash when the session sets them, and whether the destructive-DDL override was in effect. It is the foundation for branching from just before a change (Phase 4) and agent provenance (Phase 6).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| HOW IT WORKS    | New file <code>internal/ledger/ledger_v2.sql</code> , which never alters an object <code>ledger.sql</code> owns. Side table <code>vdb.ledger_ext</code> , keyed by ledger row id, is filled by an <code>AFTER INSERT</code> trigger <code>vdb_ext_capture</code> that reads <code>txid_current()</code> , <code>pg_current_wal_insert_lsn()</code> and the settings <code>vdb.task</code> , <code>vdb.parent_session</code> , <code>vdb.call_hash</code> and <code>vdb.allow_destructive</code> . Each row carries <code>ext_hash</code> ( <code>vdb._ext_hash</code> ). Append-only like the ledger; clients may read, not write. <b>Fail-safe:</b> any capture error becomes a WARNING and the user's change still goes through. <b>Kill switch:</b> <code>ALTER DATABASE vectoradb SET vdb.v2 = 'off'</code> (needs the database owner or a superuser), or <code>SET vdb.v2 = 'off'</code> in a superuser's own session. A client — including a <code>vdb_admin</code> member — setting it in its own session is ignored ( <code>vdb._capture_disabled</code> ), so nobody can hide the capture details of their own changes. Installed on main at every <code>vdb start</code> (best effort — never stops start-up) and by <code>vdb ledger upgrade</code> . |
| HOW TO USE      | Automatic. Tag a session: <code>PGOPTIONS='-c vdb.task=task-42'</code> <code>psql ...</code> . Inspect: <code>SELECT * FROM vdb.ledger_ext ORDER BY ledger_id DESC LIMIT 5</code> ; Installed version: <code>SELECT vdb.ledger_v2_version()</code> ; The Agent API and MCP <code>execute_change</code> fill the task, parent session and call hash automatically (H16).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| HOW TO TEST     | integration-v2 §2: one capture row per ledger row; xid and LSN present; task and call hash captured; hash verifies; override use recorded; a failing capture doesn't block DDL; kill switch (database-wide, and a superuser session); a client's own <code>SET vdb.v2 = 'off'</code> — also as <code>vdb_admin</code> — does not skip capture; append-only; clients can't write; base chain still verifies.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| STATUS & LIMITS | Verified in the VM (integration-v2 §2, 14 Sep 2026). Ledger rows written before 2.0 was installed have no capture row. Blocked attempts are inserted through a separate dblink session, so their capture carries that session's transaction and no task. Existing branches need <code>vdb ledger upgrade --all</code> . Capture hashes are covered by checkpoint anchors (H10).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ADDED IN        | Blackbox 2.0 Phase 2 ( <code>feat/ledger2-phase2-capture</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## H10 Checkpoints & anchors

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Takes tamper-evidence outside the database. At intervals it records a Merkle root over the newest ledger entries — in the database and as a read-only anchor file somewhere else — so rewritten, deleted or wiped history can be proven later.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| HOW IT WORKS    | <code>vdb.ledger_checkpoints ( ledger_v2.sql )</code> is append-only, and a trigger refuses any checkpoint that doesn't continue the last one ( <code>from_id = last to_id + 1, prev_root = last root</code> ). The engine ( <code>internal/branch/checkpoint.go</code> ) reads the new entries, refuses if their hash chain is already broken, and builds the anchor with <code>internal/ledger/integrity.go</code> : each leaf is <code>sha256(0x00    recomputed row hash    "I"    capture hash)</code> , each node <code>sha256(0x01    left    right)</code> . It records the checkpoint, then writes <code>~/.vectoradb/anchors/&lt;branch&gt;/&lt;to_id&gt;.json</code> with mode 0444, never overwriting. A scheduler in the control plane checkpoints running branches every <code>VECTORADB_CHECKPOINT_INTERVAL</code> (10m) or once <code>VECTORADB_CHECKPOINT_ENTRIES</code> (500) are waiting; <code>VECTORADB_CHECKPOINTS=off</code> disables it. <code>VECTORADB_ANCHOR_DIR</code> moves anchors (e.g. to a write-once mount); <code>VECTORADB_ANCHOR_IMMUTABLE=1</code> adds <code>chattr +i</code> . The format is published in <code>docs/ledger-anchor-format.md</code> . |
| HOW TO USE      | <code>vdb ledger checkpoint [branch]</code> · <code>POST /api/branches/{name}/ledger/checkpoint</code> · web<br>Integrity page → Create checkpoint                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| HOW TO TEST     | Unit: <code>internal/ledger/integrity_test.go</code> . integration-v2 §3: anchor written read-only in the published format; no-op when nothing is new; the database refuses an out-of-sequence checkpoint; checkpoints are append-only. §3b: the scheduler anchors new entries on its own.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| STATUS & LIMITS | Verified in the VM (integration-v2 §3 and §3b, 14 Sep 2026). Anchors are only as trustworthy as where they're stored — the default directory is on the same host, so point <code>VECTORADB_ANCHOR_DIR</code> at storage the database's operators can't rewrite. Entries written since the last checkpoint are protected by the hash chain only. Cloud write-once anchor writers (S3 Object Lock etc.) are not built (commercial scope). A cloned branch inherits its parent's checkpoint rows but not its anchor files.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| ADDED IN        | Blackbox 2.0 Phase 3 ( <code>feat/ledger2-phase3-checkpoints</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

## H11 vdb-verify — independent verifier

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | A separate open-source program anyone can run to check a ledger without trusting VectoraDB, its engine or the database.                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| HOW IT WORKS    | <code>cmd/vdb-verify</code> reads every ledger entry over a plain Postgres connection (read access through the gateway with an API key is enough) or from a <code>vdb ledger export</code> file, recomputes every row hash and Merkle root with the standard-library code in <code>internal/ledger/integrity.go</code> , and compares them with the anchor files. Exit 0 = intact, 1 = tampered, 2 = usage or connection error; <code>--json</code> prints the full report. Built and released as <code>vdb-verify-&lt;os&gt;-&lt;arch&gt;</code> next to <code>vdb</code> . |
| HOW TO USE      | <code>vdb-verify --dsn 'postgresql://vectoradb:&lt;api-key&gt;@localhost:6432/main?sslmode=require' --anchors ~/.vectoradb/anchors/main</code> · offline: <code>vdb ledger export main &gt; main.jsonl</code> then <code>vdb-verify --export main.jsonl --anchors ./anchors/main</code>                                                                                                                                                                                                                                                                                      |
| HOW TO TEST     | Unit tests (shared verification code). integration-v2 §3: agrees with integrity on a live branch and on an export; exits 1 on a forged edit.                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| STATUS & LIMITS | Verified in the VM (integration-v2 §3 and §3b, 14 Sep 2026). Needs a copy of the branch's anchor files. Reads the whole ledger into memory.                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ADDED IN        | Blackbox 2.0 Phase 3 ( <code>feat/ledger2-phase3-checkpoints</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## H12 Blackbox integrity & export

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Answers "has this branch's schema history been tampered with?" and exports the full ledger for audits.                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| HOW IT WORKS    | <code>Integrity</code> ( <code>internal/branch/checkpoint.go</code> ) loads every entry and the branch's anchor files and runs the same checks as <code>vdb-verify</code> : the hash chain, the anchor sequence, and each anchor's entry count, Merkle root and last entry. It notes when the database's own checkpoint list disagrees with the anchors (the anchors win). Unlike <code>vdb ledger verify</code> , which only checks the chain inside the database, it catches a rewritten chain. Export writes every entry with its capture columns as JSON lines. |
| HOW TO USE      | <code>vdb ledger integrity [branch]</code> (exit 1 when tampered) · <code>vdb ledger export [branch] &gt; ledger.jsonl</code> · REST <code>GET .../ledger/integrity</code> , <code>GET .../ledger/export</code> · MCP <code>ledger_integrity</code> · web Integrity page                                                                                                                                                                                                                                                                                            |
| HOW TO TEST     | integration-v2 §3: an untampered branch is INTACT via CLI, REST, MCP and <code>vdb-verify</code> ; a forged edit with a rewritten chain fools the in-database check but is TAMPERED here; so are a deleted newest anchored entry and a wiped ledger; deleting the database's checkpoint rows leaves it INTACT because the anchors are the source of truth.                                                                                                                                                                                                          |
| STATUS & LIMITS | Verified in the VM (integration-v2 §3 and §3b, 14 Sep 2026). Reads the whole ledger on each check (fine at typical sizes; very large ledgers would need streaming).                                                                                                                                                                                                                                                                                                                                                                                                 |
| ADDED IN        | Blackbox 2.0 Phase 3 ( <code>feat/ledger2-phase3-checkpoints</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

### H13 Branch from just before a Blackbox entry

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Creates a new branch holding main exactly as it was the moment before a chosen schema change — to inspect what things looked like, or to recover from a bad change — without touching main.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| HOW IT WORKS    | <code>BranchBeforeEntry</code> ( <code>internal/branch/branch_before.go</code> ) reads the entry and its captured transaction id and WAL position (H9) from the current primary, and refuses BLOCKED entries (the change never happened), sources other than main (only the primary archives WAL) and names already in use. It switches main to a new WAL segment and waits for the archiver, so the change's commit is in object storage. It lists base backups ( <code>wal-g backup-list --json --detail</code> in a throwaway container) and picks the newest backup <i>of the same database</i> (system identifier) that finished before the change — by WAL position, or by time for entries without capture. It creates empty storage for the new branch and runs the stock image with an embedded script ( <code>internal/branch/restore_before.sh</code> , passed with <code>bash -c</code> , so the published image needs no new file): <code>backup-fetch</code> of that backup, <code>recovery_target_xid</code> (or <code>recovery_target_time</code> ) with <code>recovery_target_inclusive = off</code> , then promote. Once promoted it checks the entry is absent, clears the recovery settings ( <code>ALTER SYSTEM RESET</code> ), restarts the data directory as an ordinary branch container and re-enables the guardrail. Any failure removes the partial branch. One runs at a time. |
| HOW TO USE      | Find the entry id with <code>vdb ledger entries [--limit N]</code> (REST GET <code>/api/branches/main/ledger/entries</code> , MCP <code>ledger_entries</code> ; the existing ledger views don't show ids and are unchanged), then <code>vdb ledger branch-before 612 [--as fix-orders]</code> (default name <code>main-before-612</code> ) · REST POST <code>/api/branches/main/ledger/612/branch</code> with optional <code>{"name": "..."} (201; 400 invalid or BLOCKED, 404 no such entry, 409 name taken, 422 no usable base backup)</code> · MCP <code>branch_before_change</code> · web Integrity page → "Branch from before a change". Connect through the gateway like any branch; remove it with <code>vdb branch delete</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| HOW TO TEST     | Unit: <code>internal/branch/branch_before_test.go</code> and <code>ledger_entries_test.go</code> (entry listing, entry parsing, <code>xid/time</code> targets, <code>backup-list</code> parsing, base-backup choice incl. another database's backups, WAL-archive check, names, the embedded script). integration-v2 §4: the entry id is listed by CLI, REST and MCP; by transaction id via the CLI — rows written before the change (even after the backup) are present, the change and later changes are not, the ledger stops before the entry, no recovery settings left, reachable through the gateway with the guardrail active, main untouched and its integrity result unchanged; by timestamp via MCP for an entry without capture; via REST; refusals for an existing name, a BLOCKED entry, an unknown entry, a non-main source and a bad id, with nothing left behind.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| STATUS & LIMITS | Verified in the VM (integration-v2 §4, 14 Sep 2026: by transaction id, by timestamp, via CLI, REST and MCP). Takes minutes, not seconds (base backup fetch plus WAL replay), and the REST call waits for it. Needs a base backup that finished before the change ( <code>vdb backup create</code> ; schedule backups to make older changes reachable). It excludes the change's whole transaction, so other statements in the same transaction are excluded too. Entries recorded before Blackbox 2.0 capture use their timestamp, which also excludes anything that committed after the change started. Only main can be the source; after an HA failover the promoted standby doesn't archive WAL, so later changes can't be branched before. The new branch keeps main's checkpoint rows up to that point but not its anchor files, so <code>vdb ledger integrity</code> on it notes the difference.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| ADDED IN        | Blackbox 2.0 Phase 4 ( <code>feat/ledger2-phase4-branch-before</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

## H14 Blackbox names & aliases

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Blackbox is the product name for the record of schema changes that was called the Schema Ledger. Every surface gains a Blackbox name; every original name keeps working, so no script, integration, stored record or anchor breaks.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| HOW IT WORKS    | <b>CLI:</b> <code>vdb blackbox ...</code> runs the same handler as <code>vdb ledger ...</code> ( <code>cmd/vdb/main.go</code> ). <b>REST:</b> <code>blackboxAlias</code> ( <code>internal/controlplane/blackbox.go</code> ) sits inside the auth gate and serves <code>/api/branches/{name}/blackbox[/...]</code> with the <code>.../ledger[/...]</code> handler. <b>MCP:</b> <code>verify_blackbox</code> , <code>blackbox_integrity</code> and <code>blackbox_entries</code> are listed next to and resolve to <code>verify_ledger</code> , <code>ledger_integrity</code> , <code>ledger_entries</code> ( <code>resolveTool</code> in <code>internal/mcp/mcp.go</code> ). <b>SDKs:</b> Python <code>blackbox()</code> / <code>verify_blackbox()</code> , TypeScript <code>blackbox()</code> / <code>verifyBlackbox()</code> call the original routes, so they also work against older servers. <b>Web:</b> <code>nav "Blackbox"</code> at <code>/blackbox</code> ; <code>/ledger</code> still opens the same page. <b>Kept as they were:</b> SQL objects ( <code>vdb.schema_ledger</code> , <code>vdb.ledger_ext</code> , <code>vdb.ledger_checkpoints</code> , <code>vdb._ledger_hash</code> ), the Go package <code>internal/ledger</code> , the anchor format <code>vectoradb-ledger-anchor/1</code> and <code>docs/ledger-anchor-format.md</code> file name, output lines such as <code>ledger integrity: INTACT</code> , JSON fields such as <code>last_ledger_id</code> , the export file name. |
| HOW TO USE      | <code>vdb blackbox</code> · <code>vdb blackbox integrity main</code> · <code>curl -k -H "Authorization: Bearer \$KEY" https://localhost:8080/api/branches/main/blackbox/verify</code> · MCP <code>blackbox_integrity</code> · <code>db.verify_blackbox("main")</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| HOW TO TEST     | Unit: <code>internal/controlplane/blackbox_test.go</code> ( <code>TestBlackboxToLedgerPath</code> , <code>TestBlackboxAlias</code> ), <code>internal/mcp/mcp_test.go</code> ( <code>TestBlackboxToolAliases</code> ). integration-v2 §5: CLI <code>verify/entries/integrity</code> , REST <code>verify/list/entries</code> and the auth requirement, and MCP listing, integrity and verify all match the original names.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| STATUS & LIMITS | Verified in the VM (integration-v2 §5, 14 Sep 2026; existing suite 28 / 28). The OpenAPI spec documents the alias in the ledger tag and info description rather than repeating every path, so generated clients only get the <code>/ledger</code> operations. The screenshot file is still <code>docs/screenshots/ledger.png</code> and shows the old page title until recaptured.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| ADDED IN        | Blackbox rename ( <code>feat/blackbox-phase5-policy</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## H15 Policy gate (warn / block)

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Checks every schema change against policy rules before it runs. A <b>warn</b> rule lets the change through and tells the client why it is risky; a <b>block</b> rule refuses it. Tools and agents get a machine-readable answer they can act on, defined in the published contract <code>docs/policy-errors.md</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| HOW IT WORKS    | <code>internal/ledger/policy.sql</code> , installed after the 2.0 objects by <code>EnsureLedgerV2</code> (every <code>vdb start</code> , <code>vdb blackbox upgrade</code> ). Rules live in <code>vdb.policy_rules</code> (rule id, command tag, optional case-insensitive regex over the statement, warn/block, reason, hint, enabled); changes go to the append-only <code>vdb.policy_rule_history</code> with who made them. The event trigger <code>vdb_policy_start</code> fires on <code>ddl_command_start</code> after the guardrail <code>vdb_guard_start</code> (name order). <b>Warn</b> : an evaluation row and a NOTICE with SQLSTATE <code>VDB02</code> . <b>Block</b> : a <code>BLOCKED</code> Blackbox entry (risk <code>policy</code> ) and an evaluation written through dblink so they survive the rollback, then an ERROR with <code>VDB01</code> ; blocks win over warnings. DETAIL is one-line JSON ( <code>v</code> , <code>rule_id</code> , <code>action</code> , <code>command</code> , <code>matched</code> , <code>reason</code> , <code>hint</code> , <code>override</code> , <code>evaluation_id</code> , <code>blackbox_id</code> , <code>impact</code> ). <b>Override</b> : superusers and <code>vdb_admin</code> members may <code>SET vdb.policy_allow = '&lt;rule ids&gt;'</code> ; it is recorded as an <code>allowed</code> evaluation and in the capture row's <code>override_used</code> ; <code>vdb.allow_destructive</code> does not override policy. <b>Fail-safe</b> : any error while matching or recording becomes a WARNING and never stops a statement a warn rule matched; a block still refuses (with <code>evaluation_id</code> null). The gate ignores the client-settable <code>vdb.v2</code> ; a superuser turns it off with <code>ALTER EVENT TRIGGER vdb_policy_start DISABLE</code> . Rule changes through REST need <code>vdb_admin</code> on that branch ( <code>IsAdmin</code> ); clients can read rules and evaluations but not write them. The existing guardrail ( <code>vdb.policy</code> , <code>DROP TABLE/SCHEMA</code> , SQLSTATE 42501) is unchanged. |
| HOW TO USE      | <code>vdb policy</code> · <code>vdb policy check "ALTER TABLE orders DROP COLUMN note"</code> (exit 1 if a rule would block) · <code>vdb policy block drop-column</code> · <code>vdb policy add no-orders-drop --command "ALTER TABLE" --pattern 'orders' --block --reason "orders is shared"</code> · <code>vdb policy evaluations</code> · REST <code>GET POST /api/branches/{n}/policies</code> , <code>PUT DELETE .../policies/{rule}</code> , <code>POST .../policies/check</code> , <code>GET .../policies/evaluations</code> · MCP <code>policy_check</code> · web Policies page. In an application: catch SQLSTATE <code>VDB01</code> and parse the error's DETAIL as JSON.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| HOW TO TEST     | Unit: <code>internal/ledger/policy_test.go</code> (TestSchemaPolicy — both SQLSTATES, fires after the guardrail, built-ins ship as warn, ignores <code>vdb.v2</code> , touches no existing object; TestParsePolicyDetail; TestPolicyContractExample — the contract's own example parses; TestCommandTag; TestValidRuleID) and <code>internal/branch/policy_test.go</code> (validation, rule SQL quoting, error messages, formatting). integration-v2 §6: warn (runs, <code>VDB02</code> , contract JSON, evaluation) for all four built-ins; block ( <code>VDB01</code> , statement didn't run, JSON with ids, <code>BLOCKED</code> entry and evaluation survive the rollback, <code>HINT</code> names the override); non-admin override, <code>vdb.v2=off</code> and <code>vdb.allow_destructive</code> don't bypass; admin override runs and is recorded; REST list / 200 / 403 / 404 / 409 / check / evaluations; CLI check and exit code; MCP <code>policy_check</code> ; clients can't write rules; fail-safe; kill switch; custom and disabled rules; rule history; invalid pattern; built-in can't be removed; append-only evaluations; guardrail error unchanged; reinstall keeps rule changes; hash chain still verifies.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| STATUS & LIMITS | Verified in the VM (integration-v2 §6, 14 Sep 2026; existing suite 28 / 28). Patterns match the whole query text the client sent, so a multi-statement string is matched as a whole and text inside comments or string literals can match. <code>vdb policy check</code> guesses the command tag from the statement's first words; the gate itself uses the real tag. TRUNCATE is not covered (it doesn't fire DDL event triggers). Imports and pipelines run through the gate too (with the built-in warn rules that only adds notices). Rules are per branch; new branches copy main's. The <code>impact</code> field is always null until impact analysis (Phase 7).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| ADDED IN        | Blackbox 2.0 Phase 5 ( <code>feat/blackbox-phase5-policy</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## H16 Agent provenance & execute\_change

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Answers "which agent run, for which task, spawned by what, made this change?" for every change an agent makes — and gives agents one tool that runs a change with that provenance attached, checks policy first, and says exactly what happened.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| HOW IT WORKS    | <code>internal/ledger/provenance.sql</code> (installed by <code>EnsureLedgerV2</code> ) adds <code>vdb.agent_sessions</code> : session id, agent, parent session, task, tool, start time; append-only, written only by the engine, readable by clients. A session's changes carry its id in the Blackbox entry's <code>session</code> and the task, parent session and call hash in the capture row (H9), which checkpoints anchor (H10). <b>Agent API:</b> <code>POST /agents/{id}/branch</code> with <code>{"task_id", "parent_session_id", "session_id"}</code> creates the branch, records the session (tool <code>agent-api</code> ) and sets <code>vdb.session</code> , <code>vdb.task</code> and <code>vdb.parent_session</code> as the branch database's defaults, so the agent's own connections are attributed without it doing anything; if recording fails the branch is removed. Invalid ids (not 1–200 printable characters) get 400 before any branch is made. Without those fields the original code path and response are used. <b>MCP <code>execute_change</code></b> ( <code>branch.ExecuteChange</code> ): one session per MCP server process (agent = the client's name from <code>initialize</code> ); previews the policy rules (H15); unless <code>dry_run</code> , records the session, connects as the non-superuser <code>vdbclient</code> , sets the actor, <code>actor_kind = agent</code> , tool <code>mcp</code> , session, task, parent session and <code>vdb.call_hash</code> (sha256 over the tool, branch, sql, task and parent session), runs the SQL, and returns JSON: <code>status</code> ( <code>applied</code>   <code>blocked</code>   <code>error</code>   <code>preview</code> ), <code>command</code> , <code>session_id</code> , <code>call_hash</code> , <code>policy_preview</code> , <code>notices</code> (with the parsed VDB02 detail), <code>policy</code> (the VDB01 rule), <code>error</code> and <code>blackbox_entries</code> . Blocked and error results are also flagged <code>isError</code> . <code>run_sql</code> is unchanged. Its result also carries <code>impact</code> , the impact report for the statement when its target is recognised (H17). |
| HOW TO USE      | <code>curl -k -H "Authorization: Bearer \$KEY" -X POST -d '{"task_id":"JIRA-42","parent_session_id":"planner-1"}' https://localhost:8088/agents/alice/branch · MCP <code>execute_change {"sql": "ALTER TABLE orders ADD COLUMN note text", "task_id": "JIRA-42"} (add "dry_run": true to preview) · vdb blackbox sessions [branch] · REST GET /api/branches/{n}/blackbox/sessions · SQL: SELECT s.id, s.actor, a.task_id, a.parent_session_id FROM vdb.schema_ledger s JOIN vdb.agent_sessions a ON a.session_id = s.session</code></code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| HOW TO TEST     | Unit: <code>internal/ledger/provenance_test.go</code> ( <code>TestSchemaProvenance</code> ) and <code>internal/branch/provenance_test.go</code> ( <code>TestValidProvenanceID</code> , <code>TestNewSessionID</code> , <code>TestCallHash</code> , <code>TestProvenanceSQL</code> , <code>TestClassifyExecError</code> , <code>TestFormatAgentSessions</code> ). integration-v2 §7: sessions table installed, clients can't write it; Agent API without provenance keeps its response keys and sets no session; with provenance returns and records session / task / parent, and the agent's own DDL over its DSN carries them; an invalid task id is a 400 with no branch made; <code>execute_change</code> applies and returns the entry, which carries agent, tool, session, task, parent and call hash; the MCP session is recorded; runs without superuser rights; a warn rule gives VDB02 in <code>notices</code> ; a block gives status <code>blocked</code> with the rule and its BLOCKED entry, and the change didn't run; <code>dry_run</code> runs nothing; the call hash is stable for the same arguments and differs otherwise; a database error is reported; an invalid task id is refused; CLI and REST sessions; the hash chain verifies.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| STATUS & LIMITS | Verified in the VM (integration-v2 §7, 14 Sep 2026; existing suite 28 / 28). Provenance is supplied by the caller and not verified — it records what the agent said its task and parent were; the agent's identity itself stays non-forgeable (login role, H3). Agent API provenance is set per branch, so all connections to that agent branch share one session; start a new branch for a new session. An MCP session lasts as long as the MCP server process. A session recorded on an agent branch is removed together with that branch. <code>vdb.agent_sessions</code> itself isn't anchored by checkpoints (the ids it explains are). No web view yet.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| ADDED IN        | Blackbox 2.0 Phase 6 ( <code>feat/blackbox-phase6-provenance</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## H17 Impact analysis

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Before a schema change runs, shows what it would affect: what depends on the object, which other branches have it, what the policy gate would say, and how risky it is overall — for people ( <code>vdb impact</code> ) and for agents (MCP <code>impact</code> , and inside every <code>execute_change</code> result).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| HOW IT WORKS    | <b>Target:</b> <code>ledger.ParseTarget</code> reads the statement to find the table, view, materialized view, index or sequence it changes and, where relevant, the column and kind of change ( <code>drop</code> , <code>drop-column</code> , <code>alter-column-type</code> , <code>rename</code> , <code>rename-column</code> , <code>truncate</code> are destructive; <code>alter</code> , <code>alter-column</code> , <code>create-index</code> , <code>grant</code> , <code>revoke</code> are not). Quoted and schema-qualified names work; <code>--object</code> / <code>--column</code> name it directly. <b>Dependents:</b> the read-only SQL function <code>vdb.blast_radius(target, column, depth)</code> ( <code>internal/ledger/impact.sql</code> , installed by <code>EnsureLedgerV2</code> , runs with the caller's rights and search path, so an unqualified name resolves as in the caller's own statement) walks <code>pg_depend</code> for normal and automatic dependencies and reports each dependent's type, identity, owning relation, depth and the view it was reached through: views and materialized views (and views on those, up to depth 5, capped at 10), constraints including foreign keys from other tables, indexes, triggers, row-level security policies, defaults, owned sequences and SQL-standard functions. For a column, only what uses that column. Every reported name is schema-qualified, and an index is reported against the table it indexes. <b>Branches:</b> every other running branch is checked for the object (and column) without waking suspended ones, with the branch it was cloned from (ZFS <code>origin</code> , btrfs parent UUID). <b>Policy:</b> the rules the statement would trigger (H15). <b>Score</b> ( <code>scoreImpact</code> ): destructive 5, otherwise 1; each dependent view, function or foreign key from another table +3, trigger or policy +2, index or other +1; deeper than checked +3; $\geq 10k$ rows +1, $\geq 1M$ +3; each other running branch with it +1 (max 5); a blocking rule +5, a warning +2. 15+ high, 5–14 medium, below low; every point is listed as a reason. |
| HOW TO USE      | <code>vdb impact "ALTER TABLE orders DROP COLUMN note"</code> · <code>vdb impact --object orders_summary --json</code> · <code>vdb impact "DROP TABLE orders" --branch qa</code> · REST POST <code>/api/branches/{n}/impact</code> with <code>{"sql": ...}</code> or <code>{"object": ..., "column": ...}</code> · MCP <code>impact</code> · SQL: <code>SELECT vdb.blast_radius('public.orders', 'note')</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| HOW TO TEST     | Unit: <code>internal/ledger/impact_test.go</code> (TestSchemaImpact — read-only, capped depth, caller's rights; TestParseTarget — 27 statements; TestTargetDestructive) and <code>internal/branch/impact_test.go</code> (TestScoreImpact, TestBranchParentParsing — ZFS and btrfs output, TestFormatImpact). integration-v2 §8: a table's views (depth 1 and 2, via), the foreign key from another table and its index; a column's dependents only; quoted names; non-destructive changes; a missing object; a statement without a target asks for <code>--object</code> ; a view's dependents; the depth limit; the object on a branch cloned after it existed (with its parent) and not on one without it; the policy verdict in the score; REST and MCP agree with the CLI; <code>execute_change</code> includes the impact.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| STATUS & LIMITS | Verified in the VM (integration-v2 §8, 15 Sep 2026; existing suite 28 / 28). The target is read from the statement text: one object per statement (the first of a multi-object DROP), and statements on functions, types, schemas or whole-schema grants aren't recognised — name the object with <code>--object</code> . Dependencies PostgreSQL doesn't record aren't seen: application queries, functions with plain-string bodies (only SQL-standard <code>BEGIN ATOMIC</code> bodies are tracked), dynamic SQL, other databases. Row counts are the planner's estimate. The score is a guide, not a guarantee. The policy error DETAIL's <code>impact</code> field stays null (the gate doesn't run this inside the database); use <code>vdb impact</code> or <code>execute_change</code> . No web view yet.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ADDED IN        | Blackbox 2.0 Phase 7 ( <code>feat/blackbox-phase7-impact-diff</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## H18 Blackbox diff between branches

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Shows which schema changes distinguish two branches: where they split, what was changed only on each since, and which objects were changed on both (likely conflicts). Diff only — nothing is merged or changed.                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| HOW IT WORKS    | <code>branch.DiffLedgers</code> ( <code>internal/branch/diff.go</code> ) reads both branches' Blackbox histories in id order (starting a suspended branch first, as other Blackbox commands do). A branch is a copy-on-write clone, so it begins with its parent's history entry for entry; the fork point is the longest run of entries with the same id and the same recomputed hash. Everything after it is listed for each side (id, time, command, object, status, actor). Objects changed on both sides are listed with their entry ids; BLOCKED entries don't count, since those changes never happened. Each branch's parent is read from the storage layer. |
| HOW TO USE      | <code>vdb blackbox diff main qa</code> · <code>vdb branch diff main qa --json</code> · REST <code>GET /api/blackbox/diff?a=main&amp;b=qa</code> (also <code>/api/ledger/diff</code> ) · MCP <code>blackbox_diff</code>                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| HOW TO TEST     | Unit: <code>internal/branch/impact_test.go</code> <code>TestBuildDiff</code> (fork point, same id with different content, both-changed objects, BLOCKED ignored, self diff, no shared history, text output). <code>integration-v2 §8</code> : a branch cloned from main, changes on each side — the parent, shared history, changes only on main, only on the branch, the object both changed; <code>vdb branch diff</code> matches; text output; a branch against itself; REST on both paths; unknown branch 404; MCP.                                                                                                                                              |
| STATUS & LIMITS | Verified in the VM ( <code>integration-v2 §8</code> , 15 Sep 2026; existing suite 28 / 28). It compares recorded schema changes, not the schemas themselves: changes made while Blackbox wasn't recording (before it was installed, or with the capture turned off by a superuser) don't appear, and data changes are out of scope. Branches that weren't cloned from each other (e.g. two imports) have no shared history, so everything shows on both sides. Rewritten history on one branch moves the fork point earlier — check <code>vdb blackbox integrity</code> . Reads both histories in full.                                                              |
| ADDED IN        | Blackbox 2.0 Phase 7 ( <code>feat/blackbox-phase7-impact-diff</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

# Import & migration

Every import lands in a **new branch** (a copy-on-write clone of `main` whose `public` schema is wiped first), so a failed import never touches `main`. An import with 0 tables fails loudly. Code: `internal/branch/import.go`. Only the MongoDB path has end-to-end automated coverage (integration §9–10).

## I1 From Postgres

Working

|                 |                                                                                                                                                                                                                                                                    |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Copies a Postgres (or compatible) database, schema and data, into a new branch.                                                                                                                                                                                    |
| HOW IT WORKS    | <code>loadPostgres : pg_dump &lt;dsn&gt; --no-owner --no-acl --no-comments   psql</code> inside the target container. <code>psql</code> 's errors are counted: if any statement failed, the import fails listing them (see I5).                                    |
| HOW TO USE      | <code>vdb import --from postgres://u:pw@host:5432/db [--as name] ; REST POST /api/import ; web Import.</code>                                                                                                                                                      |
| HOW TO TEST     | Manual: start <code>postgres:16</code> on network <code>vectoradb</code> with a 2-row table, import, <code>SELECT count(*) = 2.</code>                                                                                                                             |
| STATUS & LIMITS | Working; no automated test of the Postgres source itself (the error handling is shared with I5 and tested there); depends on <code>pg_dump</code> version compatibility — a statement the target can't run now fails the import instead of being skipped silently. |
| ADDED IN        | <code>44cc05c</code> .                                                                                                                                                                                                                                             |

## I2 From MySQL ≤5.7 / MariaDB

Working

|                 |                                                                                                                                                                                                |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Migrates MySQL/MariaDB with type mapping.                                                                                                                                                      |
| HOW IT WORKS    | <code>loadMySQL</code> builds a local <code>pgloader</code> image on first use and runs <code>pgloader &lt;dsn&gt; postgresql://...@vec-&lt;target&gt; ;</code> success judged by table count. |
| HOW TO USE      | <code>vdb import --from mysql://u:pw@host:3306/db --as legacy (or mariadb://)</code>                                                                                                           |
| HOW TO TEST     | Manual: <code>mariadb:11</code> container with a table, import, query rows.                                                                                                                    |
| STATUS & LIMITS | Working; no automated test.                                                                                                                                                                    |
| ADDED IN        | <code>b842a28</code> ; hardening <code>c929eb5</code> .                                                                                                                                        |

## I3 From MySQL 8.x

Working

|                 |                                                                                                                                                                                                                                                                                                                                           |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Imports MySQL 8+ (whose auth <code>pgloader</code> can't handle).                                                                                                                                                                                                                                                                         |
| HOW IT WORKS    | <code>mysqlNeedsNative</code> detects ≥8; <code>loadMySQLNative</code> generates <code>CREATE TABLE</code> from <code>information_schema</code> (type map: <code>json</code> → <code>jsonb</code> , <code>decimal</code> kept, else <code>text</code> ) and streams <code>mysqldump --no-create-info INSERTs</code> ; per-table progress. |
| HOW TO USE      | <code>vdb import --from mysql://root:pw@host:3306/db --as m8</code>                                                                                                                                                                                                                                                                       |
| HOW TO TEST     | Manual: <code>mysql:8</code> with <code>json</code> + <code>decimal</code> columns; check <code>information_schema.columns</code> .                                                                                                                                                                                                       |
| STATUS & LIMITS | Working; no automated test. Only columns, NOT NULL and PK are carried over (no other indexes, FKs or defaults).                                                                                                                                                                                                                           |
| ADDED IN        | <code>c929eb5</code> .                                                                                                                                                                                                                                                                                                                    |

## I4 From MongoDB

Working

|                 |                                                                                                                                                                                                                    |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Turns each collection into a typed Postgres table with the exact collection name.                                                                                                                                  |
| HOW IT WORKS    | <code>loadMongo</code> : list collections with <code>mongosh</code> , export each as NDJSON ( <code>ObjectId</code> → <code>hex</code> , <code>Date</code> → <code>ISO</code> ), then load via the JSON path (I6). |
| HOW TO USE      | <code>vdb import --from mongodb://host/db --as events</code>                                                                                                                                                       |
| HOW TO TEST     | Integration §9, §10. Manual: <code>mongo:7</code> with a nested document; <code>\d</code> shows <code>jsonb</code> for objects, numeric for numbers.                                                               |
| STATUS & LIMITS | Working (the only import path with end-to-end tests).                                                                                                                                                              |
| ADDED IN        | <code>b842a28</code> ; relational tables <code>f2c964e</code> .                                                                                                                                                    |

## I5 From a .sql dump

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Runs a SQL dump into a new branch.                                                                                                                                                                                                                                                                                                                                                                        |
| HOW IT WORKS    | <code>loadSQL</code> pipes the file into <code>psql</code> in the container; branch named <code>import-&lt;file&gt;</code> . The whole dump runs; <code>psql</code> 's <code>ERROR</code> / <code>FATAL</code> lines are collected ( <code>psqlErrorCollector</code> ) and, if there were any, the import fails with the count and the first 20 — the new instance is kept with everything that did load. |
| HOW TO USE      | <code>vdb import --from ./dump.sql ; POST /api/import/file ; web Import.</code>                                                                                                                                                                                                                                                                                                                           |
| HOW TO TEST     | Unit: <code>TestPsqlErrorCollector</code> . Integration §11: a dump with one failing statement exits 1, lists it, and the rest loaded; a clean dump exits 0.                                                                                                                                                                                                                                              |
| STATUS & LIMITS | Working. Any failed statement fails the import, including harmless ones (e.g. a setting only a newer Postgres knows) — they are listed so you can decide. Until 15 Sep 2026 failing statements were ignored and the import reported success.                                                                                                                                                              |
| ADDED IN        | 44cc05c .                                                                                                                                                                                                                                                                                                                                                                                                 |

## I6 From JSON / NDJSON

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Loads a JSON array or NDJSON into a table with columns inferred from top-level keys.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| HOW IT WORKS    | <code>loadJSON</code> stages documents as <code>jsonb</code> , then <code>relationalizeJSON</code> picks a type per key ( <code>_id</code> <code>text</code> ; <code>string</code> → <code>text</code> ; <code>number</code> → <code>numeric</code> ; <code>boolean</code> ; <code>nested/mixed</code> → <code>jsonb</code> ), column order <code>_id</code> then alphabetical. <code>streamJSONDocs</code> reads the array or lines; an invalid document stops the load, rolls back everything from that file, and fails the import naming the array element or line number. |
| HOW TO USE      | <code>vdb import --from ./people.ndjson</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| HOW TO TEST     | Unit: <code>TestJSONColumn</code> , <code>TestSQLIdent</code> , <code>TestStreamJSONDocs</code> . Integration §10; §11 (an array with an invalid 2nd element exits 1 naming it; a valid array imports).                                                                                                                                                                                                                                                                                                                                                                       |
| STATUS & LIMITS | Working. Until 15 Sep 2026 a JSON array import stopped silently at the first element it couldn't decode and reported success.                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| ADDED IN        | 44cc05c ; relationalization f2c964e .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

## I7 From CSV

Working

|                 |                                                                                                        |
|-----------------|--------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Loads a CSV into a table (one text column per header).                                                 |
| HOW IT WORKS    | <code>loadCSV</code> : header → <code>CREATE TABLE</code> , rows → <code>\copy ... FORMAT csv</code> . |
| HOW TO USE      | <code>vdb import --from ./people.csv</code>                                                            |
| HOW TO TEST     | Manual: <code>printf 'id,Name\n1,a\n' &gt; p.csv</code> , import, <code>SELECT "Name" FROM p</code> .  |
| STATUS & LIMITS | All columns are text; a header containing a newline won't parse.                                       |
| ADDED IN        | 44cc05c .                                                                                              |

## I8 Continuous replication & cutover

Partial

|                 |                                                                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Copies a Postgres source's schema and keeps streaming changes for a zero-downtime switch; cutover stops replication.                                                                                                        |
| HOW IT WORKS    | <code>ImportContinuousTo</code> : schema-only dump, <code>CREATE PUBLICATION vdb_pub</code> on source (best effort), <code>CREATE SUBSCRIPTION vdb_sub</code> on target. <code>ImportCutover</code> drops the subscription. |
| HOW TO USE      | <code>vdb import --from postgres://... --continuous --as live then vdb import-cutover live</code> . Web checkbox for postgres sources.                                                                                      |
| HOW TO TEST     | Manual: source with <code>wal_level=logical</code> ; insert on source, see it on target ( <code>pg_stat_subscription</code> ).                                                                                              |
| STATUS & LIMITS | Cutover is CLI-only (no REST/web). No automated test. Fixed publication/subscription names.                                                                                                                                 |
| ADDED IN        | b842a28 .                                                                                                                                                                                                                   |

## I9 Guard handling during import

Working

|                 |                                                                                                                                                                                                                                                             |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Lets bulk loads run DDL the guardrail would block, while the ledger keeps recording — and can't leave a branch unguarded after a crash.                                                                                                                     |
| HOW IT WORKS    | <code>setGuard</code> disables/enables <code>vdb_guard_start</code> around the load (deferred); loaders set <code>vdb.allow_destructive=on</code> ; <code>reconcileGuard</code> re-enables the guard whenever <code>EnsureRunning</code> restarts a branch. |
| HOW TO USE      | Automatic.                                                                                                                                                                                                                                                  |
| HOW TO TEST     | Manual: stop the engine mid-import, <code>vdb branch resume &lt;target&gt;</code> , <code>SELECT evtenabled FROM pg_event_trigger WHERE evtname='vdb_guard_start' → 0</code> .                                                                              |
| STATUS & LIMITS | Working.                                                                                                                                                                                                                                                    |
| ADDED IN        | <code>b842a28</code> ; crash-safe <code>1884445</code> (PR #12).                                                                                                                                                                                            |

## I10 Live progress (CLI & SSE)

Working

|                 |                                                                                                                                                                                                                                                      |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Shows a live migration log and, where the source supports it, a progress bar.                                                                                                                                                                        |
| HOW IT WORKS    | <code>Progress{Log, Step}</code> ; the control plane streams Server-Sent Events <code>log</code> , <code>progress</code> , <code>done</code> , <code>error</code> . Step events from MySQL 8 (per table), MongoDB (per collection), pipeline models. |
| HOW TO USE      | <code>curl -N -k -H "Authorization: Bearer \$KEY" -H 'Content-Type: application/json' -d '{"source":"mongodb://mongo-src/shop"}' https://localhost:8080/api/import</code>                                                                            |
| HOW TO TEST     | Manual curl above; watch <code>event: log / event: progress</code> .                                                                                                                                                                                 |
| STATUS & LIMITS | psql subprocess output goes to engine logs, not SSE.                                                                                                                                                                                                 |
| ADDED IN        | <code>f2c964e</code> .                                                                                                                                                                                                                               |

## I11 Import REST endpoints

Working

|                 |                                                                                                                                                                                                                                                                          |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | API entry points for imports (auth required).                                                                                                                                                                                                                            |
| HOW IT WORKS    | <code>POST /api/import</code> body <code>{source, target, continuous}</code> — connection strings only (postgres, mysql, mariadb, mongodb). <code>POST /api/import/file</code> multipart <code>file</code> + <code>target</code> , kind from extension. Both stream SSE. |
| HOW TO USE      | <code>curl -N -k -H "Authorization: Bearer \$KEY" -F file=@people.csv -F target=ppl https://localhost:8080/api/import/file</code>                                                                                                                                        |
| HOW TO TEST     | Manual curl; without a key → 401.                                                                                                                                                                                                                                        |
| STATUS & LIMITS | Working. Target name not validated against the branch-name rule; OpenAPI documents the wrong field names (K2).                                                                                                                                                           |
| ADDED IN        | <code>44cc05c</code> , <code>b842a28</code> .                                                                                                                                                                                                                            |

## I12 Web Import page

Working

|                 |                                                                                                                                                                                                                                  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | "Migrate a database" form with a live migration console.                                                                                                                                                                         |
| HOW IT WORKS    | <code>web/src/pages/Import.tsx</code> : connection-string panel (continuous checkbox for postgres), file upload ( <code>.sql.csv.json.ndjson.jsonl</code> ), SSE console with progress, result with links to Console and Ledger. |
| HOW TO USE      | <code>https://localhost:8080/import</code>                                                                                                                                                                                       |
| HOW TO TEST     | Manual: upload a CSV and check the result panel.                                                                                                                                                                                 |
| STATUS & LIMITS | Footer mentions SQLite imports via the CLI, but no SQLite loader exists.                                                                                                                                                         |
| ADDED IN        | <code>44cc05c</code> ; console <code>f2c964e</code> (PR #3).                                                                                                                                                                     |

### I13 Exact identifier fidelity

Working

|                 |                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Source names like <code>leaseAiChats</code> or <code>userId</code> keep their exact case.                                   |
| HOW IT WORKS    | <code>sqlIdent</code> quotes and truncates to 63 bytes (tables, columns); <code>sanitizeIdent</code> only for branch names. |
| HOW TO USE      | Automatic; quote camelCase in SQL: <code>SELECT "userId" ...</code>                                                         |
| HOW TO TEST     | Unit: TestSQLIdent. Integration §10.                                                                                        |
| STATUS & LIMITS | Working.                                                                                                                    |
| ADDED IN        | <code>f2c964e</code> .                                                                                                      |

## ETL pipelines (experimental)

### J1 Pipeline engine

Working

|                 |                                                                                                                                                                                                                                                                                                                 |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | dbt-style extract → land raw → transform with SQL models → quality tests, into a fresh branch.                                                                                                                                                                                                                  |
| HOW IT WORKS    | <code>RunPipeline ( pipeline.go )</code> : delete + re-create the target branch, import the source, rename <code>public</code> → <code>raw</code> , run each model in order as <code>CREATE TABLE VIEW public."name" AS ... with {{ ref('m') }}</code> / <code>{{ source('t') }}</code> templating, then tests. |
| HOW TO USE      | <code>vdb pipeline run spec.json [--as name]</code> (default <code>pl-&lt;file&gt;</code> ; exit 1 on test failure).                                                                                                                                                                                            |
| HOW TO TEST     | Unit: <code>TestRenderSQL</code> , <code>TestTestQuery</code> . Integration §9.                                                                                                                                                                                                                                 |
| STATUS & LIMITS | No dependency graph (listed order), no incremental models, no scheduling. A run destroys any existing branch with the target name.                                                                                                                                                                              |
| ADDED IN        | <code>f2c964e</code> .                                                                                                                                                                                                                                                                                          |

### J2 Data-quality tests

Working

|                 |                                                                                                                                                             |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Assertions after transform: <code>not_null</code> , <code>unique</code> , <code>accepted_values</code> , <code>row_count_min</code> , <code>custom</code> . |
| HOW IT WORKS    | <code>testQuery</code> builds a "count violating rows" query; a test passes when the count is 0. Failures mark the run failed but keep the data.            |
| HOW TO USE      | <code>"tests": [{"type":"unique","model":"stg","column":"city"}]</code>                                                                                     |
| HOW TO TEST     | Unit: <code>TestTestQuery</code> . Integration §9 (failing <code>row_count_min</code> → exit 1, data kept).                                                 |
| STATUS & LIMITS | Working.                                                                                                                                                    |
| ADDED IN        | <code>f2c964e</code> .                                                                                                                                      |

### J3 Stored pipelines & run history

Working

|                 |                                                                                                                                                                                                                                           |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Save pipelines per user, run them over the API, keep run history.                                                                                                                                                                         |
| HOW IT WORKS    | SQLite tables <code>pipelines</code> , <code>pipeline_runs</code> ; routes <code>GET/POST /api/pipelines</code> , <code>GET/PUT/DELETE /api/pipelines/{id}</code> , <code>GET .../runs</code> (last 50), <code>POST .../run</code> (SSE). |
| HOW TO USE      | <code>curl -k -H "Authorization: Bearer \$KEY" -d '{"name":"shop etl","spec":{"...}}'</code><br><code>https://localhost:8080/api/pipelines</code>                                                                                         |
| HOW TO TEST     | Manual: create, run, <code>GET .../runs</code> shows <code>success</code> .                                                                                                                                                               |
| STATUS & LIMITS | No endpoint to read a run's log; a run whose process dies stays <code>running</code> .                                                                                                                                                    |
| ADDED IN        | <code>f2c964e</code> .                                                                                                                                                                                                                    |

### J4 Pipeline editor (web)

Working

|                 |                                                                                                                                                                       |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Create, edit, run and inspect pipelines in the browser.                                                                                                               |
| HOW IT WORKS    | <code>Pipelines.tsx</code> (list) and <code>PipelineEditor.tsx</code> (source, model cards, test cards, Load example, Save, Run with streaming console, run history). |
| HOW TO USE      | <code>https://localhost:8080/pipelines</code> → New pipeline → Load example → Save → Run.                                                                             |
| HOW TO TEST     | Manual with the integration §9 Mongo data.                                                                                                                            |
| STATUS & LIMITS | Delete on the list has no confirmation.                                                                                                                               |
| ADDED IN        | <code>f2c964e</code> .                                                                                                                                                |

# APIs, SDKs & agents

Working

## K1 Control-plane REST API

| WHAT IT DOES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | JSON management API over HTTPS on :8080 (also serves the web UI).                                                                       |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--------|---------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------------------------|---------------|------------------------------|---------------------------------------|--------------------------------------------------------------------------------------------------------------------|----------|-------------------------------------------|-------------------------------------------------------------------------|----------------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------|-----------------------------|----------------------------------------------------------------------------------------------|-----------------------------------------------------------|----------------------------------------------------|----------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|-----------------------------------------------|-------------------------------------------------------------------------|---------------------------------------------------------------|--------------|--------------------------------|-----------|----------------------------------------------------------------------|----------|
| HOW IT WORKS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | <code>internal/controlplane/server.go</code> ; <code>store.Authn</code> on <code>/api/*</code> ; CORS for configured/localhost origins. |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <table><thead><tr><th>Routes</th><th>Purpose</th></tr></thead><tbody><tr><td><code>POST /auth/register login logout</code> , <code>GET /auth/me providers</code> , <code>GET /auth/oauth/{p}/{callback}</code></td><td>Accounts (public)</td></tr><tr><td><code>GET /api/openapi.yaml</code></td><td>Spec (public)</td></tr><tr><td><code>GET /api/status</code></td><td>Health, branches, agents, HA, storage</td></tr><tr><td><code>GET POST /api/branches</code> , <code>DELETE /api/branches/{n}</code> , <code>POST .../suspend resume</code></td><td>Branches</td></tr><tr><td><code>POST /api/branches/{n}/query</code></td><td>SQL as <code>vdbclient</code> , 10s, ≤1000 rows, attributed to the user</td></tr><tr><td><code>GET /api/branches/{n}/ledger</code> , <code>.../ledger/verify</code></td><td>Blackbox</td></tr><tr><td><code>GET .../ledger/integrity</code> , <code>POST .../ledger/checkpoint</code> , <code>GET .../ledger/export</code></td><td>Ledger integrity (H10, H12)</td></tr><tr><td><code>GET /api/branches/{n}/ledger/entries</code> , <code>POST .../ledger/{id}/branch</code></td><td>Entries with ids; branch from before a ledger entry (H13)</td></tr><tr><td><code>GET /api/branches/{n}/ledger/sessions</code></td><td>Agent sessions (H16)</td></tr><tr><td><code>POST /api/branches/{n}/impact</code> , <code>GET /api/ledger/diff</code> , <code>GET /api/blackbox/diff</code></td><td>Impact analysis and diff (H17, H18)</td></tr><tr><td><code>GET POST /api/branches/{n}/policies</code> , <code>PUT DELETE .../policies/{rule}</code> , <code>POST .../policies/check</code> , <code>GET .../policies/evaluations</code></td><td>Policy gate; changes need <code>vdb_admin</code> (H15)</td></tr><tr><td><code>/api/branches/{n}/blackbox[/...]</code></td><td>Every <code>.../ledger[/...]</code> route under its Blackbox name (H14)</td></tr><tr><td><code>POST /api/import</code> , <code>/api/import/file</code></td><td>Import (SSE)</td></tr><tr><td><code>/api/pipelines...</code></td><td>Pipelines</td></tr><tr><td><code>GET POST /api/keys</code> , <code>DELETE /api/keys/{id}</code></td><td>API keys</td></tr></tbody></table> |                                                                                                                                         | Routes | Purpose | <code>POST /auth/register login logout</code> , <code>GET /auth/me providers</code> , <code>GET /auth/oauth/{p}/{callback}</code> | Accounts (public) | <code>GET /api/openapi.yaml</code> | Spec (public) | <code>GET /api/status</code> | Health, branches, agents, HA, storage | <code>GET POST /api/branches</code> , <code>DELETE /api/branches/{n}</code> , <code>POST .../suspend resume</code> | Branches | <code>POST /api/branches/{n}/query</code> | SQL as <code>vdbclient</code> , 10s, ≤1000 rows, attributed to the user | <code>GET /api/branches/{n}/ledger</code> , <code>.../ledger/verify</code> | Blackbox | <code>GET .../ledger/integrity</code> , <code>POST .../ledger/checkpoint</code> , <code>GET .../ledger/export</code> | Ledger integrity (H10, H12) | <code>GET /api/branches/{n}/ledger/entries</code> , <code>POST .../ledger/{id}/branch</code> | Entries with ids; branch from before a ledger entry (H13) | <code>GET /api/branches/{n}/ledger/sessions</code> | Agent sessions (H16) | <code>POST /api/branches/{n}/impact</code> , <code>GET /api/ledger/diff</code> , <code>GET /api/blackbox/diff</code> | Impact analysis and diff (H17, H18) | <code>GET POST /api/branches/{n}/policies</code> , <code>PUT DELETE .../policies/{rule}</code> , <code>POST .../policies/check</code> , <code>GET .../policies/evaluations</code> | Policy gate; changes need <code>vdb_admin</code> (H15) | <code>/api/branches/{n}/blackbox[/...]</code> | Every <code>.../ledger[/...]</code> route under its Blackbox name (H14) | <code>POST /api/import</code> , <code>/api/import/file</code> | Import (SSE) | <code>/api/pipelines...</code> | Pipelines | <code>GET POST /api/keys</code> , <code>DELETE /api/keys/{id}</code> | API keys |
| Routes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Purpose                                                                                                                                 |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>POST /auth/register login logout</code> , <code>GET /auth/me providers</code> , <code>GET /auth/oauth/{p}/{callback}</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Accounts (public)                                                                                                                       |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET /api/openapi.yaml</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Spec (public)                                                                                                                           |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET /api/status</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Health, branches, agents, HA, storage                                                                                                   |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET POST /api/branches</code> , <code>DELETE /api/branches/{n}</code> , <code>POST .../suspend resume</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Branches                                                                                                                                |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>POST /api/branches/{n}/query</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | SQL as <code>vdbclient</code> , 10s, ≤1000 rows, attributed to the user                                                                 |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET /api/branches/{n}/ledger</code> , <code>.../ledger/verify</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Blackbox                                                                                                                                |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET .../ledger/integrity</code> , <code>POST .../ledger/checkpoint</code> , <code>GET .../ledger/export</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Ledger integrity (H10, H12)                                                                                                             |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET /api/branches/{n}/ledger/entries</code> , <code>POST .../ledger/{id}/branch</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Entries with ids; branch from before a ledger entry (H13)                                                                               |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET /api/branches/{n}/ledger/sessions</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Agent sessions (H16)                                                                                                                    |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>POST /api/branches/{n}/impact</code> , <code>GET /api/ledger/diff</code> , <code>GET /api/blackbox/diff</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Impact analysis and diff (H17, H18)                                                                                                     |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET POST /api/branches/{n}/policies</code> , <code>PUT DELETE .../policies/{rule}</code> , <code>POST .../policies/check</code> , <code>GET .../policies/evaluations</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Policy gate; changes need <code>vdb_admin</code> (H15)                                                                                  |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>/api/branches/{n}/blackbox[/...]</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Every <code>.../ledger[/...]</code> route under its Blackbox name (H14)                                                                 |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>POST /api/import</code> , <code>/api/import/file</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Import (SSE)                                                                                                                            |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>/api/pipelines...</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Pipelines                                                                                                                               |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| <code>GET POST /api/keys</code> , <code>DELETE /api/keys/{id}</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | API keys                                                                                                                                |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| HOW TO USE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | <code>curl -k -H "Authorization: Bearer \$KEY" https://localhost:8080/api/status</code>                                                 |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| HOW TO TEST                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Unit: <code>TestNameValidation</code> . Integration §1; integration-v2 §0 ( <code>ledger/verify</code> columns).                        |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| STATUS & LIMITS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Working. Not versioned ( <code>/api/</code> , not <code>/api/v1/</code> ).                                                              |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |
| ADDED IN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <code>a7580f6</code> ; TLS <code>0bd52f3</code> .                                                                                       |        |         |                                                                                                                                   |                   |                                    |               |                              |                                       |                                                                                                                    |          |                                           |                                                                         |                                                                            |          |                                                                                                                      |                             |                                                                                              |                                                           |                                                    |                      |                                                                                                                      |                                     |                                                                                                                                                                                   |                                                        |                                               |                                                                         |                                                               |              |                                |           |                                                                      |          |

## K2 OpenAPI spec

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Machine-readable API description for client generators.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| HOW IT WORKS    | <code>openapi.yaml</code> (OpenAPI 3.1) embedded and served at <code>/api/openapi.yaml</code> ; also documents agent routes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| HOW TO USE      | <code>curl -k https://localhost:8080/api/openapi.yaml</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| HOW TO TEST     | <code>go test ./internal/controlplane:TestOpenAPIMatchesRoutes</code> compares the spec's paths with the routes the code registers (it reads the <code>HandleFunc</code> literals, because <code>net/http.ServeMux</code> cannot list what was registered), and <code>TestOpenAPIAliasRefsResolve</code> checks every alias pointer. Manual: <code>curl -k https://localhost:8080/api/openapi.yaml</code> .                                                                                                                                                                                                                                                                                                            |
| STATUS & LIMITS | Matches the code: <code>/api/import</code> takes <code>{source, target, continuous}</code> and answers with an SSE stream, <code>/api/import/file</code> documents its multipart fields, branch and API-key creation answer 201, the ledger's <code>since / until</code> filters are described, and <code>/api/openapi.yaml</code> plus the seven <code>/auth/*</code> routes are documented. The <code>/blackbox</code> aliases are declared as path-item <code>\$ref s</code> , so a generated client gets both spellings with no second copy to keep in step. Adding a route without documenting it now fails the build. Not checked automatically: whether a described body or response still matches its handler. |
| ADDED IN        | 52b1fc5 / cc5cbd7 (PR #15); corrected on <code>docs/api-accuracy</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## K3 Python SDK `vectoradb`

Working

|                 |                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Dependency-free client for the control plane (Apache-2.0).                                                                                                                                                                                                                                                                                       |
| HOW IT WORKS    | <code>clients/python/vectoradb: VectoraDB(api_key, base_url, verify_tls); status, branches, create_branch, delete_branch, suspend, resume, query, ledger, verify_ledger</code> . Blackbox names <code>blackbox()</code> and <code>verify_blackbox()</code> call the same routes as <code>ledger()</code> and <code>verify_ledger()</code> (H14). |
| HOW TO USE      | <code>pip install ./clients/python; db = VectoraDB(api_key="vdb_...", verify_tls=False); db.query("qa","select 1")</code>                                                                                                                                                                                                                        |
| HOW TO TEST     | No tests; manual snippet.                                                                                                                                                                                                                                                                                                                        |
| STATUS & LIMITS | Not on PyPI; no import/pipeline/key/agent methods.                                                                                                                                                                                                                                                                                               |
| ADDED IN        | 52b1fc5.                                                                                                                                                                                                                                                                                                                                         |

## K4 TypeScript SDK `@vectoradb/client`

Working

|                 |                                                                                                                                                                                                                                                                                                         |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | The same client for Node and browsers (Apache-2.0).                                                                                                                                                                                                                                                     |
| HOW IT WORKS    | <code>clients/typescript/src/index.ts: new VectoraDB(apiKey, baseUrl); same methods (createBranch, verifyLedger,...) using fetch</code> . Blackbox names <code>blackbox()</code> and <code>verifyBlackbox()</code> call the same routes as <code>ledger()</code> and <code>verifyLedger()</code> (H14). |
| HOW TO USE      | <code>cd clients/typescript &amp;&amp; npm install &amp;&amp; npm run build; local self-signed cert needs NODE_TLS_REJECT_UNAUTHORIZED=0</code> .                                                                                                                                                       |
| HOW TO TEST     | No tests; manual Node script.                                                                                                                                                                                                                                                                           |
| STATUS & LIMITS | Not published to npm.                                                                                                                                                                                                                                                                                   |
| ADDED IN        | 52b1fc5.                                                                                                                                                                                                                                                                                                |

## K5 Agent Branch API

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | A disposable database per AI agent over HTTPS on <code>:8088</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| HOW IT WORKS    | <code>internal/agentapi</code> : GET <code>/healthz</code> (public), GET <code>/agents</code> , POST <code>/agents/{id}/branch</code> (creates agent- <code>&lt;id&gt;</code> , returns DSN), DELETE <code>/agents/{id}/branch</code> . Cap <code>VECTORADB_AGENT_MAX</code> (50); TTL reaping with <code>VECTORADB_AGENT_TTL</code> . Optional body <code>{"task_id", "parent_session_id", "session_id"}</code> records Blackbox provenance for the agent's changes and adds <code>session_id</code> to the response; without it nothing changes (H16).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| HOW TO USE      | <code>curl -k -H "Authorization: Bearer \$KEY" -X POST https://localhost:8088/agents/alice/branch</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| HOW TO TEST     | Integration §5 (usable via its DSN; the key dies with the branch); integration-v2 §1c (own non-superuser role, can't disable triggers or override, gateway-routed DSN, key refused for another branch and by both HTTP APIs). Unit: <code>TestAgentRolePassword</code> , <code>TestAgentGatewayDSN</code> , <code>TestGatewayHostPort</code> , <code>TestScopeAllows</code> , <code>TestScopedKeys</code> , <code>TestScopeColumnAddedToExistingStore</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| STATUS & LIMITS | The DSN is routed through the Gateway, so an agent running on the host can open it — the branch's Postgres still publishes no host port, because a direct connection would bypass the Gateway, its key, TLS and the attribution. Its password is an API key scoped to that one branch ( <code>api_keys.scope</code> ): the control plane and the Agent API refuse it, and the Gateway opens only the named branch with it, so a leaked agent credential reaches neither another agent's data nor the account's branches. The Gateway logs the agent in as the branch's own agent- <code>&lt;id&gt;</code> role, whose password is derived from the install secret rather than stored, so <code>session_user</code> stays the agent and attribution remains non-forgable. The key is shown once and revoked when the branch is deleted (a reset keeps it). The cap, the listing and the TTL reaper now count suspended branches too. <code>VECTORADB_AGENT_SUPERUSER=1</code> still restores the old container-IP superuser DSN. Agent branches created before this change have no agent role (recreate them), and <code>VECTORADB_GATEWAY_HOSTPORT</code> is needed if the Gateway is not on <code>localhost:6432</code> . |
| ADDED IN        | <code>a7580f6</code> ; cap/TTL <code>e720c4e</code> (PR #12); reachability on <code>fix/agent-reachability</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

## K6 MCP server

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Lets agent frameworks manage agent branches, run SQL and read/verify the ledger via the Model Context Protocol.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| HOW IT WORKS    | <code>internal/mcp</code> : JSON-RPC 2.0 over stdio ( <code>initialize</code> , <code>tools/list</code> , <code>tools/call</code> ). Tools: <code>create_branch</code> , <code>list_branches</code> , <code>delete_branch</code> , <code>run_sql</code> , <code>changes</code> , <code>verify_ledger</code> , <code>ledger_integrity</code> , <code>ledger_entries</code> , <code>branch_before_change</code> (H13). Blackbox names <code>verify_blackbox</code> , <code>blackbox_integrity</code> and <code>blackbox_entries</code> are listed too and run the same tools (H14). <code>policy_check</code> previews policy rules for a statement (H15). <code>execute_change</code> runs SQL with agent provenance and a policy preview and returns structured JSON (H16). <code>impact</code> and <code>blackbox_diff</code> expose impact analysis and branch diff (H17, H18). |
| HOW TO USE      | Configure an MCP client to launch command <code>vdb</code> with args <code>["mcp"]</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| HOW TO TEST     | integration-v2 §1c ( <code>run_sql</code> role, <code>list_branches</code> without passwords, compat switch), §3 ( <code>ledger_integrity</code> ), §4 ( <code>ledger_entries</code> lists the entry id; <code>branch_before_change</code> listed, refuses a BLOCKED entry, restores by timestamp). Manual: pipe <code>initialize</code> , <code>tools/list</code> , <code>tools/call</code> <code>run_sql</code> JSON lines into <code>vdb mcp</code> .                                                                                                                                                                                                                                                                                                                                                                                                                          |
| STATUS & LIMITS | <code>run_sql</code> runs as the non-superuser <code>vdbclient</code> , attributed to <code>mcp</code> ; <code>VECTORADB_MCP_SUPERUSER=1</code> restores the superuser. <code>list_branches</code> no longer shows passwords. No auth (local privileges) — the server trusts whoever can run the process, as the CLI does. Client setup and the full 16-tool reference are in <code>docs/mcp.md</code> , linked from the README and the Docs page. <code>create_branch</code> returns the same Gateway-routed, branch-scoped DSN as the Agent API (K5), so an agent driven over MCP can reach its database from the host.                                                                                                                                                                                                                                                         |
| ADDED IN        | <code>d62c676</code> / <code>ed5a379</code> (PR #14).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

# Web console

## L1 Embedded single-origin UI

Working

|                 |                                                                                                                                                                                                                                                                                                                                            |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | The engine serves the React app itself at <code>https://localhost:8080</code> — no separate web server.                                                                                                                                                                                                                                    |
| HOW IT WORKS    | <code>web/embed.go</code> ( <code>//go:build embedui</code> ) embeds <code>web/dist</code> ; <code>serveUI</code> falls back to <code>index.html</code> . <code>make web-build</code> builds with same-origin API URLs; Linux release binaries use <code>-tags embedui</code> . <code>make web-dev</code> is deprecated (hot-reload only). |
| HOW TO USE      | <code>vdb start</code> → open <code>https://localhost:8080</code> (accept the self-signed cert).                                                                                                                                                                                                                                           |
| HOW TO TEST     | Manual: open <code>/dashboard</code> directly and refresh.                                                                                                                                                                                                                                                                                 |
| STATUS & LIMITS | Working. <code>make web-dev</code> defaults to <code>http://localhost:8080</code> and needs <code>VITE_API_URL=https://localhost:8080</code> .                                                                                                                                                                                             |
| ADDED IN        | 4927095 ; React app 84741df .                                                                                                                                                                                                                                                                                                              |

## L2 Login & signup

Working

|                 |                                                                                                                           |
|-----------------|---------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Log in / sign up tabs, OAuth buttons when configured, redirect to Dashboard.                                              |
| HOW IT WORKS    | <code>/login</code> ; <code>RequireAuth</code> guards private routes; API client redirects to <code>/login</code> on 401. |
| HOW TO USE      | <code>https://localhost:8080/login</code>                                                                                 |
| HOW TO TEST     | Manual sign-up and logout.                                                                                                |
| STATUS & LIMITS | Working (OAuth caveat G5).                                                                                                |
| ADDED IN        | 235ff41 .                                                                                                                 |

## L3 Dashboard

Working

|                 |                                                                                                                                                                |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Live tiles (primary, branches, agent DBs, gateway, replica, storage) and a branch table with create, suspend, resume, delete and a copyable connection string. |
| HOW IT WORKS    | Polls <code>/api/status</code> and <code>/api/branches</code> every 3s; offline banner when the API is unreachable.                                            |
| HOW TO USE      | <code>https://localhost:8080/dashboard</code>                                                                                                                  |
| HOW TO TEST     | Manual: create a branch and see it appear.                                                                                                                     |
| STATUS & LIMITS | Working.                                                                                                                                                       |
| ADDED IN        | 84741df .                                                                                                                                                      |

## L4 SQL console & browser

Working

|                 |                                                                                                                 |
|-----------------|-----------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Schema sidebar, row browser (100/page), structure and index tabs, SQL editor (Cmd/Ctrl+Enter), row-as-JSON.     |
| HOW IT WORKS    | <code>Console.tsx</code> → <code>POST /api/branches/{name}/query</code> ; DDL attributed to the signed-in user. |
| HOW TO USE      | <code>https://localhost:8080/console</code>                                                                     |
| HOW TO TEST     | Manual: <code>select 1</code> ; create a table and see it in the Ledger page.                                   |
| STATUS & LIMITS | Working. 10s timeout, 1000-row cap.                                                                             |
| ADDED IN        | 84741df .                                                                                                       |

## L5 Blackbox page

Partial

|                 |                                                                                                                                                                                                                                                                                                              |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Browse the Blackbox per branch.                                                                                                                                                                                                                                                                              |
| HOW IT WORKS    | <code>Ledger.tsx</code> : branch, status (APPLIED/FLAGGED/BLOCKED), kind (human/agent) and actor filters; infinite scroll 25 rows at a time; columns Time, Actor, Tool, Change, Status. Nav label and page title "Blackbox"; reachable at <code>/blackbox</code> and, as before, <code>/ledger</code> (H14). |
| HOW TO USE      | <code>https://localhost:8080/ledger</code>                                                                                                                                                                                                                                                                   |
| HOW TO TEST     | Manual after a CREATE TABLE in the console.                                                                                                                                                                                                                                                                  |
| STATUS & LIMITS | No table/risk/date filters (API supports them; README claims them), no verify button, statement/session not shown.                                                                                                                                                                                           |
| ADDED IN        | <code>e42e792</code> .                                                                                                                                                                                                                                                                                       |

## L6 API keys page

Working

|                 |                                                             |
|-----------------|-------------------------------------------------------------|
| WHAT IT DOES    | Create (shown once, copy button), list and revoke API keys. |
| HOW IT WORKS    | <code>/keys</code> → <code>/api/keys</code> .               |
| HOW TO USE      | <code>https://localhost:8080/keys</code>                    |
| HOW TO TEST     | Manual create + revoke.                                     |
| STATUS & LIMITS | Working.                                                    |
| ADDED IN        | <code>235ff41</code> .                                      |

## L7 Landing, Guide & Docs pages

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Public landing page, a developer guide (install, connect, CRUD, branches, agents, PDF download) and a docs page (CLI, REST, env tables with live status buttons).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| HOW IT WORKS    | <code>Landing.tsx</code> , <code>Guide.tsx</code> , <code>Docs.tsx</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| HOW TO USE      | <code>https://localhost:8080/</code> , <code>/guide</code> , <code>/docs</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| HOW TO TEST     | Type-check and build ( <code>npm --prefix web run build</code> ); read line by line against the code, 16 Sep 2026.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| STATUS & LIMITS | Refreshed: the Guide drops <code>make web-dev</code> for <code>https://localhost:8080</code> , every connection string carries <code>sslmode=require</code> , and the agent-API examples use <code>https://localhost:8088</code> with a note on <code>-k</code> . The Docs page lists the whole REST surface (Blackbox and its aliases, policies, impact, diff, import, pipelines, keys, auth, agents), points at <code>GET /api/openapi.yaml</code> , and gains an "Agents over MCP" section linking <code>docs/mcp.md</code> . The <code>VECTORADB_WEB_ORIGIN</code> default it shows ( <code>http://localhost:5173</code> ) was checked against <code>internal/auth/auth.go</code> and is correct. The landing page is unchanged. |
| ADDED IN        | <code>84741df</code> , <code>e9210fb</code> ; refreshed on <code>docs/api-accuracy</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

## L8 Blackbox integrity page

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Verify a branch against its anchors, create a checkpoint, download the ledger export, and branch main from just before a ledger entry — from the browser.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| HOW IT WORKS    | <code>web/src/pages/Integrity.tsx</code> (route <code>/integrity</code> , nav "Integrity") calls the integrity, checkpoint and export endpoints and shows INTACT / TAMPERED, entry and checkpoint counts, problems and notes. The "Branch from before a change" panel lists main's 20 newest entries ( <code>GET .../ledger/entries</code> ) with a Select button (disabled for BLOCKED), takes an entry id and optional name and calls <code>POST .../ledger/{id}/branch</code> (H13), showing progress while the restore runs.                                                                                                                                                                                                                                                             |
| HOW TO USE      | <code>https://localhost:8080/integrity</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| HOW TO TEST     | TypeScript type-check and production build pass. Reviewed signed in on 16 Sep 2026 (Chrome, macOS): on a test branch the report matched <code>vdb blackbox integrity</code> field for field (INTACT, 61 entries, 61 hash-chained, 2 checkpoints, 2 anchored, 59 unanchored, same notes); <b>Create checkpoint</b> anchored a new entry (checkpoints 1 → 2, confirmed on disk) and was correctly a no-op when nothing new existed; <b>Export (JSONL)</b> answered <code>200 application/x-ndjson</code> with one JSON line per entry; <b>Branch from before a change</b> restored <code>main-before-3649</code> in 4 s from the right base backup — the branch lacked the table that entry created, its Blackbox stopped at the previous entry, and main was untouched. No automated UI test. |
| STATUS & LIMITS | Working — exercised in a browser against a running stack (16 Sep 2026): verify, checkpoint, export and branch-before all matched the CLI. Note: the entry list is loaded once, so a change recorded after the page opened appears only after a refresh.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| ADDED IN        | Blackbox 2.0 Phase 3 ( <code>feat/ledger2-phase3-checkpoints</code> ); branch-before panel in Phase 4 ( <code>feat/ledger2-phase4-branch-before</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## L9 Policies page

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Shows a branch's policy rules, lets a <code>vdb_admin</code> switch each between warn and block, enable or disable it, and add or remove custom rules; previews which rules a statement would trigger; lists recent warnings, blocks and overrides.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| HOW IT WORKS    | <code>web/src/pages/Policies.tsx</code> (route <code>/policies</code> , nav "Policies") over the <code>/api/branches/{n}/policies...</code> endpoints (H15). A non-admin sees the server's 403 message on any change.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| HOW TO USE      | <code>https://localhost:8080/policies</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| HOW TO TEST     | TypeScript type-check and production build pass; the endpoints it calls are covered by integration-v2 §6. Reviewed signed in on 16 Sep 2026 on a test branch: the four built-in rules matched <code>vdb policy list</code> ; <code>warn</code> → <code>block</code> → <code>warn</code> , <code>disable</code> → <code>enable</code> , and <code>add</code> → <code>remove</code> of a custom rule each matched the CLI afterwards and never touched <code>main</code> ; <b>Check a statement</b> returned the same verdict as <code>vdb policy check</code> ( <code>ALTER TABLE, WARN alter-column-type</code> , same reason); on <code>main</code> , where the account holds no <code>vdb_admin</code> , a change was refused with a readable banner naming the grant command, and the rule stayed warn. No automated UI test. |
| STATUS & LIMITS | Working — exercised in a browser against a running stack (16 Sep 2026): rule changes, the statement check and the non-admin refusal all matched the CLI, and writes reached only the branch selected. Minor: the new-rule form pre-fills Command with <code>ALTER TABLE</code> as a real value, which reads like a placeholder and is easy to type after by mistake.                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| ADDED IN        | Blackbox 2.0 Phase 5 ( <code>feat/blackbox-phase5-policy</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## L10 App sidebar layout

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Gives the signed-in app a left sidebar with its pages grouped into sections, so adding pages doesn't overflow a single navbar; keeps the public navbar for the marketing pages.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| HOW IT WORKS    | <code>web/src/components/AppLayout.tsx</code> : <code>APP_NAV</code> lists the sections and pages (a new page is one entry), each with an inline SVG icon from <code>components/icons.tsx</code> (no icon library). The active page is highlighted (including the old <code>/ledger</code> address and nested pages such as <code>/pipelines/{id}</code> ), and a top bar shows "section / page". The footer has GitHub, the light/dark switch, the account, Log out and Collapse; the collapsed state is stored in <code>localStorage</code> ( <code>vdb.sidebar.collapsed</code> , ignored if storage is unavailable). Under 860px the sidebar is an off-canvas drawer, opened from the top bar and closed by choosing a page, tapping outside or Escape. <code>web/src/main.tsx</code> routes Home and Log in through <code>PublicLayout</code> , the app pages through <code>SignedInLayout</code> (redirects to Log in when signed out), and Guide/Docs through <code>HelpLayout</code> (sidebar when signed in, public navbar otherwise). The logo and theme toggle moved to <code>components/brand.tsx</code> (still exported from <code>main.tsx</code> ). Styles use the existing light/dark design tokens. |
| HOW TO USE      | Sign in at <code>https://localhost:8080</code> — the app opens with the sidebar. Collapse with the button at the bottom; on a phone use the menu button top left.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| HOW TO TEST     | TypeScript type-check and production build pass. A preview control plane built with <code>-tags embedui</code> served <code>/</code> , <code>/dashboard</code> , <code>/login</code> and <code>/blackbox</code> (200) with the sidebar code in the bundle. Reviewed signed in on 16 Sep 2026 (Chrome, macOS): Dashboard, Console, Import, Pipelines, Changes, Integrity, Policies, API keys, Guide and Docs each opened with the right section highlighted and breadcrumb, <code>/ledger</code> highlighted Changes, collapse survived a reload ( <code>app-shell collapsed</code> , <code>vdb.sidebar.collapsed=1</code> , applied before first paint), the theme toggle set and kept <code>data-theme</code> , and no console errors appeared on any page. Still manual: narrow the window below 860px and open/close the drawer (menu button, tapping outside, Escape, choosing a page). No automated UI test.                                                                                                                                                                                                                                                                                                    |
| STATUS & LIMITS | Working — reviewed in a browser while signed in (16 Sep 2026): every sidebar link opened its page with the right section highlighted and breadcrumb (including <code>/ledger</code> → Changes), collapse persisted across a reload with no flicker on first paint, and the theme toggle applied and persisted. Not checked: the under-860px drawer — the automation could not change the page viewport, so it needs a manual look. Visual only: routes, addresses, APIs and page contents are unchanged. The breadcrumb shows the section and page name, not deeper context such as the pipeline being edited.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| ADDED IN        | <code>feat/web-sidebar-layout</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

# Build, CI & releases

## M1 Makefile targets

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | One place to build, test and release.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| HOW IT WORKS    | <code>build</code> , <code>vet</code> , <code>fmt</code> , <code>test</code> , <code>vm-build</code> (Lima, embedui), <code>integration</code> , <code>integration-v2</code> and <code>integration-update</code> (Lima), <code>web-build</code> , <code>web-dev</code> (deprecated), <code>release</code> (5 vdb + 5 vdb-verify binaries + docker context), <code>release-linux</code> , <code>wsl-distro</code> , <code>wsl-zfs</code> , <code>feature-doc</code> (renders this PDF and <code>VDB_Checklist.pdf</code> , after checking both list the same features). |
| HOW TO USE      | <code>make test</code> · <code>make integration</code> · <code>make release VERSION=x.y.z</code> · <code>make feature-doc</code>                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| HOW TO TEST     | CI runs <code>build/vet/test/gofmt</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| STATUS & LIMITS | Working. <code>release</code> prints an outdated ZFS-bundle note.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| ADDED IN        | <code>a7580f6</code> ; <code>feature-doc</code> added with this document.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## M2 Linux CI

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Every push to main and every PR is built and tested on Linux.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| HOW IT WORKS    | <code>.github/workflows/ci.yml</code> : <code>go build</code> , <code>go vet</code> , <code>go test</code> , <code>gofmt</code> check. Also runs <code>scripts/test_release_checksums.sh</code> , which checks the release checksum merge never drops another job's entries, and <code>scripts/test_check_release_assets.sh</code> , which checks the release job's test that every file <code>vdb update</code> needs was published, and <code>scripts/test_feature_checklist.sh</code> , which checks <code>VDB_Checklist.html</code> lists exactly the features in this document. |
| HOW TO USE      | Automatic on PRs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| HOW TO TEST     | Open a PR and check the Actions tab.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| STATUS & LIMITS | The integration suite does not run in CI (needs a VM).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| ADDED IN        | <code>797bc14</code> (PR #11).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## M3 Windows CI

Working

|                 |                                                                                                                                                                                                       |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Tests the Windows build and installer on every push/PR.                                                                                                                                               |
| HOW IT WORKS    | <code>windows-ci.yml</code> : <code>build/vet/test</code> , cross-compile, Pester (both files), <code>install.ps1</code> encoding + PS 5.1 parse; Linux job checks <code>make release assets</code> . |
| HOW TO USE      | Automatic.                                                                                                                                                                                            |
| HOW TO TEST     | Actions tab.                                                                                                                                                                                          |
| STATUS & LIMITS | No end-to-end WSL install test (needs nested virtualisation).                                                                                                                                         |
| ADDED IN        | <code>4fc8afb</code> (PR #1).                                                                                                                                                                         |

## M4 Releases & GHCR image

Working

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | A <code>v*</code> tag publishes binaries, checksums and a multi-arch Postgres image.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| HOW IT WORKS    | <code>release.yml</code> : <code>make release</code> , verify assets (including <code>vdb-verify</code> ), create (pre)release, <code>SHA256SUMS</code> , upload; image job builds <code>docker/postgres</code> for amd64+arm64 and pushes <code>ghcr.io/vectoradb/postgres-walg:16</code> and <code>:&lt;tag&gt;</code> . Checksums go through <code>scripts/release-checksums.sh</code> , which merges into the release's existing <code>SHA256SUMS</code> instead of replacing it, so the distro image's entry from <code>wsl-distro.yml</code> is kept whichever job finishes first. A last step, <code>scripts/check-release-assets.sh</code> , fails the job unless every file <code>vdb update</code> needs (A9) is attached and listed in <code>SHA256SUMS</code> ; a Go test keeps its list in step with the updater's. |
| HOW TO USE      | Push a tag <code>vX.Y.Z</code> (or run manually with a tag).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| HOW TO TEST     | Check the release page assets and <code>docker pull ghcr.io/vectoradb/postgres-walg:16</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| STATUS & LIMITS | Working. GHCR package must be made public manually the first time.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| ADDED IN        | <code>8cafdb6</code> (PR #2); image job <code>aae9e20</code> (PR #12).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## M5 WSL distro & ZFS builds

Partial

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Builds a prebuilt WSL distro image; legacy ZFS module bundle for WSL kernels.                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| HOW IT WORKS    | <code>wsl-distro.yml</code> / <code>make wsl-distro</code> (Ubuntu + Docker + btrfs + engine + saved images); <code>wsl-zfs.yml</code> / <code>make wsl-zfs</code> (OpenZFS for the WSL kernel). It creates the release if needed, then publishes its checksum through the same <code>scripts/release-checksums.sh</code> as <code>release.yml</code> .                                                                                                                                                                 |
| HOW TO USE      | Tag push (distro) or manual dispatch.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| HOW TO TEST     | Actions artifacts; a fresh Windows install from v0.8.6 imported the image and loaded its preinstalled containers.                                                                                                                                                                                                                                                                                                                                                                                                       |
| STATUS & LIMITS | Confirmed end to end on Windows (16 Sep 2026): the installer downloaded and verified the distro image, and a fresh install imported it — setup skipped the apt work entirely and loaded the preinstalled images. It now does that on every install, and the build tags its Postgres image <code>ghcr.io/vectoradb/postgres-walg:16</code> so the preload is used. Still open: the image is 685 MB (a fallback to the Ubuntu rootfs covers slow or failed downloads), and the ZFS bundle is legacy (Windows uses btrfs). |
| ADDED IN        | <code>d0c1f26</code> (PR #7); <code>8305e5b</code> (PR #1).                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## M6 Postgres image

Working

|                 |                                                                                                                                                     |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| WHAT IT DOES    | Stock Postgres 16 plus wal-g for archiving, backups and PITR.                                                                                       |
| HOW IT WORKS    | <code>docker/postgres/Dockerfile</code> : <code>FROM postgres:16-bookworm</code> , <code>wal-g v3.0.9</code> , <code>restore-entrypoint.sh</code> . |
| HOW TO USE      | Pulled automatically (C8).                                                                                                                          |
| HOW TO TEST     | <code>docker run --rm ghcr.io/vectoradb/postgres-walg:16 wal-g --version</code>                                                                     |
| STATUS & LIMITS | Working. No extensions added (pgvector is not included).                                                                                            |
| ADDED IN        | <code>a7580f6</code> ; GHCR name <code>aae9e20</code> .                                                                                             |

# Test matrix

Every automated test and the feature it covers. Run: `make test` (unit, host) · `make integration` (Lima VM) · Pester via `windows-ci.yml`.

| Test file                                                                                            | Tests                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Covers     |
|------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>cmd/vdb/main_test.go</code>                                                                    | <code>TestAddrFlag</code> , <code>TestDurFlag</code> , <code>TestRestoreArg</code> ,<br><code>TestUsageDescribesRevertAndFallback</code>                                                                                                                                                                                                                                                                                                                                                                         | B1, H7     |
| <code>internal/branch/ha_test.go</code>                                                              | <code>TestSuspendRefusal</code> , <code>TestHAGuard</code> , <code>TestPrimaryPointerGuards</code> ,<br><code>TestLSNAtLeast</code> , <code>TestParseControlCheckpoint</code>                                                                                                                                                                                                                                                                                                                                    | C3, D4     |
| <code>internal/branch/import_errors_test.go</code>                                                   | <code>TestPsqlErrorCollector</code> , <code>TestStreamJSONDocs</code>                                                                                                                                                                                                                                                                                                                                                                                                                                            | I1, I5, I6 |
| <code>internal/auth/auth_test.go</code>                                                              | <code>TestPasswordLogin</code> , <code>TestAPIKeys</code> , <code>TestVerifyKeyConcurrent</code> ,<br><code>TestSessions</code> , <code>TestScopedKeys</code> ,<br><code>TestScopeColumnAddedToExistingStore</code>                                                                                                                                                                                                                                                                                              | G1–G4, K5  |
| <code>internal/branch/agent_access_test.go</code> ,<br><code>internal/proxy/scope_test.go</code>     | <code>TestAgentRolePassword</code> , <code>TestAgentGatewayDSN</code> ,<br><code>TestGatewayHostPort</code> , <code>TestScopeAllows</code>                                                                                                                                                                                                                                                                                                                                                                       | K5, K6     |
| <code>internal/branch/branch_test.go</code>                                                          | <code>TestParsePublishedPort</code> , <code>TestDSN</code> , <code>TestAgentBranchName</code> ,<br><code>TestContainerName</code>                                                                                                                                                                                                                                                                                                                                                                                | C2, C4, K5 |
| <code>internal/branch/branch_before_test.go</code>                                                   | <code>TestParseEntryJSON</code> , <code>TestRecoveryTarget</code> , <code>TestParseBackups</code> ,<br><code>TestPickBaseBackup</code> , <code>TestWalArchived</code> , <code>TestValidateBeforeName</code> ,<br><code>TestEntryQuery</code> , <code>TestRestoreBeforeScript</code>                                                                                                                                                                                                                              | H13        |
| <code>internal/branch/ledger_entries_test.go</code>                                                  | <code>TestEntriesQuery</code> , <code>TestFormatLedgerEntries</code>                                                                                                                                                                                                                                                                                                                                                                                                                                             | H13        |
| <code>internal/ledger/impact_test.go</code> ,<br><code>internal/branch/impact_test.go</code>         | <code>TestSchemaImpact</code> , <code>TestParseTarget</code> , <code>TestTargetDestructive</code> ,<br><code>TestScoreImpact</code> , <code>TestBranchParentParsing</code> , <code>TestFormatImpact</code> ,<br><code>TestBuildDiff</code>                                                                                                                                                                                                                                                                       | H17, H18   |
| <code>internal/ledger/provenance_test.go</code> ,<br><code>internal/branch/provenance_test.go</code> | <code>TestSchemaProvenance</code> , <code>TestValidProvenanceID</code> , <code>TestNewSessionID</code> ,<br><code>TestCallHash</code> , <code>TestProvenanceSQL</code> , <code>TestClassifyExecError</code> ,<br><code>TestFormatAgentSessions</code>                                                                                                                                                                                                                                                            | H16        |
| <code>internal/ledger/policy_test.go</code> ,<br><code>internal/branch/policy_test.go</code>         | <code>TestSchemaPolicy</code> , <code>TestParsePolicyDetail</code> ,<br><code>TestPolicyContractExample</code> , <code>TestCommandTag</code> , <code>TestValidRuleID</code> ,<br><code>TestValidatePolicyRule</code> , <code>TestPolicyRuleSQL</code> , <code>TestFriendlyPolicyErr</code> ,<br><code>TestFormatPolicy</code>                                                                                                                                                                                    | H15        |
| <code>internal/controlplane/blackbox_test.go</code> ,<br><code>internal/mcp/mcp_test.go</code>       | <code>TestBlackboxToLedgerPath</code> , <code>TestBlackboxAlias</code> ,<br><code>TestBlackboxToolAliases</code>                                                                                                                                                                                                                                                                                                                                                                                                 | H14        |
| <code>internal/controlplane/openapi_test.go</code>                                                   | <code>TestOpenAPIMatchesRoutes</code> , <code>TestOpenAPIAliasRefsResolve</code>                                                                                                                                                                                                                                                                                                                                                                                                                                 | K2         |
| <code>internal/branch/security_test.go</code>                                                        | <code>TestTruthyEnv</code> , <code>TestSuperuserSwitchesDefaultOff</code>                                                                                                                                                                                                                                                                                                                                                                                                                                        | K5, K6     |
| <code>internal/ledger/integrity_test.go</code> ,<br><code>internal/ledger/ledger_v2_test.go</code>   | <code>TestRowHashMatchesSQLFormula</code> , <code>TestFormatAt</code> , <code>TestMerkleRoot</code> ,<br><code>TestVerifyIntactAndUnanchoredTail</code> , <code>TestVerifyDetectsTampering</code> (6 cases),<br><code>TestVerifyDetectsAnchorGap</code> , <code>TestCheckChain</code> ,<br><code>TestBuildAnchorRejectsBadRanges</code> , <code>TestAnchorFiles</code> ,<br><code>TestDecodeRowJSON</code> , <code>TestQueries</code> , <code>TestSchemaV2IsAdditive</code> ,<br><code>TestSchemaV2Safety</code> | H9–H12     |

|                                                                                       |                                                                                                                                                                                                                                                                                        |                 |
|---------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <code>internal/branch/pipeline_test.go</code>                                         | TestSQLIdent, TestRenderSQL, TestTestQuery, TestJSONColumn                                                                                                                                                                                                                             | I6, I13, J1, J2 |
| <code>internal/controlplane/server_test.go</code>                                     | TestNameValidation                                                                                                                                                                                                                                                                     | K1              |
| <code>internal/daemon/daemon_test.go</code>                                           | TestStopTerminatesProcess                                                                                                                                                                                                                                                              | B2              |
| <code>internal/host/host_test.go</code>                                               | TestIsELF, TestBundledLinuxBinaryPrefersCache, TestRefreshEngineBinaryDisabled, TestDownloadFile                                                                                                                                                                                       | A7              |
| <code>internal/update/update_test.go</code>                                           | TestParseVersion, TestCompareVersions, TestRequiredAssets, TestCandidates, TestChecksums, TestResolveAndDownload, TestReleaseListCache, TestBackgroundCheck, TestShouldCheck, TestInstallBinary, TestSwapExecutable, TestReplaceDirFromTarGz, TestReleaseWorkflowPublishesUpdateAssets | A8, A9, M4      |
| <code>internal/host/host_update_test.go</code> , <code>cmd/vdb/update_test.go</code>  | TestUpdateFlow, TestUpdateChangesNothingUnlessReady (8 cases), TestUpdateInstallFailureRestartsOldEngine, TestParseUpdateArgs                                                                                                                                                          | A9              |
| <code>scripts/test_feature_checklist.sh</code>                                        | same feature ids in both documents; no duplicates; valid statuses; badge matches status                                                                                                                                                                                                | M1, M2          |
| <code>scripts/test_check_release_assets.sh</code>                                     | complete release; missing attachment; unlisted checksum; binary-mode and CRLF lines; no SHA256SUMS                                                                                                                                                                                     | M4              |
| <code>internal/host/host_wsl_test.go</code>                                           | TestResolveWSLDistro, TestWSLArgs, TestDecodeWSLList, TestWinPathToMnt, TestParseKernelRelease, TestImportLocalFile                                                                                                                                                                    | A4, A6          |
| <code>internal/proxy/proxy_test.go</code>                                             | TestBuildParseStartupRoundtrip, TestReadStartupSkipsSSL, TestReadStartupUpgradesTLS, TestReadStartupHandlesCancel, TestSendError                                                                                                                                                       | F1, E2, F6, F7  |
| <code>deploy/install.Tests.ps1</code> , <code>deploy/windows-install.Tests.ps1</code> | Arch/asset URLs, PATH, encoding, WSL independence, elevation/reboot probes, checksum verification, E2E (opt-in)                                                                                                                                                                        | A2              |

| Integration section<br>( <code>scripts/integration_test.sh</code> ) | Assertions                                                                                                                                                                                                                                                                                                                                                                                                          | Covers             |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| \$1 Fresh start + auth                                              | unauthenticated API → 401; main ready; gateway rejects bad key; accepts API key                                                                                                                                                                                                                                                                                                                                     | B2, G2, G3, F2, K1 |
| \$2 Branch isolation                                                | branch sees its row; main doesn't have the table                                                                                                                                                                                                                                                                                                                                                                    | C1, C2             |
| \$3 Time-travel / PITR                                              | backup + <code>restore --to latest</code> → 3 rows                                                                                                                                                                                                                                                                                                                                                                  | D1–D3              |
| \$4 Suspend / resume                                                | exited after suspend; running after resume; suspending main refused, main keeps running                                                                                                                                                                                                                                                                                                                             | C2, C3             |
| \$5 Agent branch API                                                | POST returns DSN; table created and read                                                                                                                                                                                                                                                                                                                                                                            | K5                 |
| \$6 HA                                                              | 1 streaming replica; write via gateway after failover; <code>ha enable disable failover</code> and suspending the standby refused after it; <code>vdb up</code> recreates the promoted standby and leaves the old main stopped; <code>ha failback</code> : exit 0, main primary and not in recovery, pointer back on main, post-failover write kept, standby removed, gateway writes to main, WAL archiving resumed | C3, D4, F1         |
| \$7 Reaper regression                                               | standby still running; idle branch exited                                                                                                                                                                                                                                                                                                                                                                           | C3, C5             |
| \$8 Blackbox                                                        | DDL attributed human; DROP blocked; BLOCKED recorded; DELETE blocked; chain intact                                                                                                                                                                                                                                                                                                                                  | H1–H4              |
| \$9 ETL pipeline                                                    | exit 0; raw tables; staged values; failing test → exit 1 with data kept                                                                                                                                                                                                                                                                                                                                             | I4, J1, J2         |
| \$11 Import errors                                                  | a .sql dump with a failing statement exits 1, lists it, and the rest loaded; a clean dump exits 0; a JSON array with an invalid 2nd element exits                                                                                                                                                                                                                                                                   | I5, I6             |

1 naming it; a valid array imports

|                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                |
|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| §10 Schema fidelity                                                              | exact <code>userId</code> column; nested → jsonb; model query returns 1 row                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | I4, I6, I13    |
| <b>Integration section<br/>( <code>scripts/integration_ledger_v2.sh</code> )</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                |
| §0 Behaviour unchanged                                                           | guardrail error text; REST ledger and verify columns; <code>row_hash</code> formula (SQL vs Python); CLI verify intact                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | H2, H4, H6, K1 |
| §1a Restore credentials                                                          | restore returns 3 rows; no hardcoded password printed; no <code>minioadmin</code> in the restore container                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | D3             |
| §1b Override permission                                                          | ledger upgrade; non-admin refused with HINT; admin allowed; revoke restores the block; superuser override still works                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | H4, H8, F4     |
| §1c Least privilege                                                              | agent DSN uses its own non-superuser role; DB usable; attributed to the agent; can't disable triggers or override; MCP list hides passwords; MCP run_sql as <code>vdbclient</code> ; compat switch                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | K5, K6, H3     |
| §2 Blackbox 2.0 capture                                                          | installed at start; upgrade idempotent; capture row per ledger row with xid/LSN; task and call hash; hash verifies; override recorded; failing capture doesn't block DDL; kill switch (database-wide, and a superuser session); a client's own <code>SET vdb.v2 = 'off'</code> — also as <code>vdb_admin</code> — does not skip capture; append-only; clients can't write; base chain intact                                                                                                                                                                                                                                                                                                                                                                       | H9, H2         |
| §3 Checkpoints & verifier                                                        | anchor written read-only in the published format; no-op when nothing new; out-of-sequence checkpoint refused; append-only; untampered branch INTACT via CLI, REST, MCP, vdb-verify (live and export); forged edit with rewritten chain, deleted newest anchored entry and wiped ledger all TAMPERED; anchors outrank the database's checkpoint rows                                                                                                                                                                                                                                                                                                                                                                                                                | H10–H12        |
| §3b Scheduled checkpoints                                                        | with a 15s interval the control plane anchors new entries on its own                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | H10            |
| §8 Impact & diff                                                                 | impact on a table (views at depth 1 and 2 via the first, the foreign key from another table, its index, score), a column (only what uses it), quoted names, non-destructive, missing object, no target → <code>--object</code> , a view, depth limit, branch presence with parent, policy in the score, REST and MCP match the CLI, <code>execute_change</code> includes it; diff of a clone: parent, shared history, only-on-each-side, object both changed, <code>vdb branch diff</code> matches, text output, self diff, REST on both paths, 404, MCP                                                                                                                                                                                                           | H17, H18       |
| §7 Agent provenance                                                              | sessions table installed, not client-writable; Agent API without provenance unchanged; with provenance: session / task / parent returned, recorded, and carried by the agent's own DDL; invalid id → 400, no branch; <code>execute_change</code> : applied with entry carrying agent / tool / session / task / parent / call hash, session recorded, no superuser rights, VDB02 warning, VDB01 block with its BLOCKED entry, dry run, stable call hash, database error, invalid id; CLI and REST sessions; chain verifies                                                                                                                                                                                                                                          | H16, K5, K6    |
| §6 Policy gate                                                                   | built-ins installed as warn; fires after the guardrail; warn runs with VDB02 and contract JSON for all four built-ins; block refuses with VDB01, JSON ids, BLOCKED entry and evaluation surviving the rollback, HINT; non-admin <code>vdb.policy_allow</code> , session <code>vdb.v2=off</code> and <code>vdb.allow_destructive</code> don't bypass; admin override runs and is recorded (evaluation + <code>override_used</code> ); REST list / 200 / 403 / 404 / 409 / check / evaluations; CLI check + exit code; MCP <code>policy_check</code> ; clients can't write rules; fail-safe; kill switch; custom / disabled rules; history; invalid pattern; built-in not removable; append-only; guardrail error unchanged; reinstall keeps changes; chain verifies | H15, H4, H9    |

|                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |             |
|------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| §5 Blackbox names                                                      | vdb blackbox verify entries integrity , REST<br>.../blackbox/verify , .../blackbox (same columns),<br>.../blackbox/entries , 401 without a key, MCP listing and<br>blackbox_integrity / verify_blackbox all match the original<br>names                                                                                                                                                                                                                                                                                                                                                                          | H14         |
| §4 Branch before an entry                                              | entry has a captured xid; its id is listed by vdb ledger entries ,<br>REST and MCP; CLI branch-before by xid: rows before the change<br>present, the change and later changes absent, ledger stops before the<br>entry, no recovery settings left, reachable via the gateway, guardrail<br>active, main untouched and its integrity result unchanged; refusals<br>(existing name, BLOCKED, unknown, non-main source, bad id) leave<br>nothing behind; REST 404 / 400 / 409 and success; MCP listed,<br>refuses BLOCKED, succeeds by timestamp for an entry without<br>capture; the branch deletes like any other | H13, K1, K6 |
| <b>Integration section</b><br><b>( scripts/integration_update.sh )</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |             |
| Setup                                                                  | test releases 0.98.0 (installed) and 0.99.0 built and served by a local<br>fake GitHub with a prerelease v1.0.0 and an incomplete v0.99.5; stack<br>started on 0.98.0 with data on main and a branch                                                                                                                                                                                                                                                                                                                                                                                                             | A8, A9      |
| §1–§3 Notice                                                           | the notice is start's last line, once, with the banner still printed;<br>VECTORADB_NO_UPDATE_CHECK=1 prints nothing; offline prints<br>nothing and doesn't slow start                                                                                                                                                                                                                                                                                                                                                                                                                                            | A8          |
| §4–§6 Before updating                                                  | --check reports v0.99.0 and not the prerelease or incomplete<br>release, changes nothing; without a terminal, or with stdin closed, --<br>yes is required; a tampered download is refused ("Nothing was<br>changed"), version and servers unchanged, no partial file left                                                                                                                                                                                                                                                                                                                                        | A9          |
| §7 Update                                                              | exits 0 and says done; Blackbox upgraded on the branch; vdb is<br>0.99.0; the three servers restarted and run the new binary; main and<br>branch containers not recreated; main and branch data unchanged;<br>every Blackbox entry from before the update unchanged on main and<br>the branch (hash of the entries), both chains intact, new Blackbox<br>objects present; secrets.json and TLS certificates unchanged;<br>previous engine kept; the gateway serves main with an API key made<br>before the update; control plane answers                                                                         | A9          |
| §8 Afterwards                                                          | --check says up to date; start shows no notice                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | A8, A9      |

Not covered by any automated test: most MCP tools, OAuth, REST import/pipeline handlers, SDKs, web UI, SCRAM, storage quotas, non-Mongo imports.

# Known issues

Found while building this inventory. Recorded, not fixed — each fix changes existing behaviour and needs explicit approval. Struck-through items have been fixed.

- ~~PITR restore broken on fresh installs (hardcoded `minioadmin`)~~ — **fixed** in Phase 1. (D3, H7)
- ~~Destructive DDL override ungated~~ — **fixed** in Phase 1 (superusers and `vdb_admin` only). Use of the override is now recorded (H9). (H4, H8)
- ~~Agents and MCP run as superuser~~ — **fixed** in Phase 1 (own `agent-<id>` role; MCP as `vdbclient`). (K5, K6, H3)
- ~~Integration \$1 and \$5 call `http://` endpoints that now serve TLS~~ — **fixed** in `13734a7`.
- ~~Integration "bad key" and "append only" checks gave false failures~~ — **fixed** (test-only; both protections confirmed working in the VM).
- ~~`vdb branch suspend main` stops the primary and the gateway won't wake it~~ — **fixed**: suspend refuses main and the HA standby. (C3)
- ~~`vdb ha enable` after a failover deletes the live primary (`vec-standby`); post failover `ha disable` routes main to a stopped container~~ — **fixed**: after a failover `ha enable|disable|failover` are refused, `vdb up` brings the promoted standby back instead of the old main, and `vdb ha fallback` returns to main keeping every write. (D4)
- `backup / restore` always target `vec-main`, even after a failover; PITR always fetches the LATEST base backup. Branching from before a ledger entry (H13) picks the right base backup and reads the ledger from the current primary, but base backups are still only taken from `vec-main`. (D2, D3, H13)
- ~~Ledger verify can't detect deletion of the newest rows or a wiped table~~ — **addressed** in Phase 3: checkpoint anchors kept outside the database catch it (H10–H12). Entries written since the last checkpoint are still only chain-checked. (H2)
- ~~A release job could replace `SHA256SUMS` and drop the other job's entries (v0.8.1 lost `vectoradb-distro.tar.gz`, so the Windows installer skipped verifying it)~~ — **fixed** for future releases by the shared merge script. v0.8.1 itself needs `wsl-distro.yml` re-run for tag `v0.8.1` by a repository admin. (M4, M5)
- ~~MinIO images are pulled from Docker Hub, where `minio/minio` and `minio/mc` no longer exist — the Windows distro release build and fresh installs failed~~ — **fixed**: pinned quay.io images, with cached old images still used. (D1, A4)
- ~~The 2.0 capture kill switch `vdb.v2 = 'off'` could be set by any client for its own session, skipping its capture rows~~ — **fixed**: it is now honoured only database-wide or in a superuser's session. (H9)
- ~~The new release notice never appeared against real GitHub: the check's `SHA256SUMS` request is throttled to 7–75 s, far past its budget~~ — **fixed**: the check is one request (the releases list) and its answer is remembered for 6 hours. (A8)
- Policy patterns match the whole query text a client sent (all statements of a multi-statement string, comments and literals included). (H15)
- ~~`vdb ledger revert` — to — doesn't revert a branch~~ — **fixed**: its help and output now say it is a point-in-time restore of main; H13 branches from just before a change. (H7)
- README documents ~~`vdb branch diff` (didn't exist)~~ — **now added** (H18) — and ledger UI filters by table/risk (not in the UI). (L5)
- ~~OpenAPI spec disagrees with the code (import fields, status codes, missing params/routes)~~ — **fixed**: the spec was corrected against the handlers, and `TestOpenAPIMatchesRoutes` fails the build if the two diverge again. (K2)
- ~~`sql` imports don't stop on error; JSON array imports stop silently at the first bad element~~ — **fixed**: both now fail, listing the failed statements or naming the invalid element. Web Import mentions SQLite (no loader). (I5, I6, I12)
- Continuous-import cutover is CLI-only. (I8)
- ~~Agent cap and TTL reaper only count running containers; agent DSN only reachable inside the VM~~ — **fixed**: all three count suspended branches, and the DSN is Gateway-routed with a branch-scoped key, so it works from the host without widening what an agent may reach. (K5)
- OAuth defaults point at `http://localhost:8080 / http://localhost:5173`. (G5)
- `vdb vm` is listed as a command but not implemented. (B1)
- ~~Windows installer never downloads the prebuilt distro; its preloaded image tag doesn't match the engine's image name; setup summary omits the API key~~ — **fixed**: the installer prefers the verified distro image, the build and the loader use the engine's image name, and the summary prints the connection string with the key. (A2, A4, M5)
- ~~Web Guide/Docs pages are stale in places~~ — **fixed**: both were read against the code and refreshed (`https`, `sslmode=require`, the full REST surface, MCP). (L7)
- Storage quotas are ZFS-only and per-branch caps are opt-in. (C6)
- The Postgres image has no pgvector. (M6)