





CAD FILE:



Technical Data  
Material:  
Contact material:Brass  
Plating:Gold Flash  
Insulator material:Black polyester UL94V-0  
Standard:6T+30%G,F

Electrical:  
Current rating:3Amps/contact max.  
Contact resistance: $\leq 20\text{m}\Omega$ /contact  
Insulation resistance: $\geq 1000\text{M}\Omega$  at V=100V  
Withstanding voltage:550V AC/minute

Mechanical:  
Soldering temperature:+260°C, 4s max  
UNSPECIFIED TOLERANCE:  $\pm 0.20$



### PCB Layout

$$A = 2.54 * \frac{n}{2} + 0.40 \pm 0.35$$

$$B = 2.54 * \frac{n}{2} - 2.54 \pm 0.20$$

Pin Number=2~80

APPROVALS		DATE	DEALON® ELECTRONICS CO.,LTD					
DRAWN	CHEKED	G.M.Chen	2015/7/17	TITLE:	DW254N-22-XX-85			
				CONNECTOR				
APPROVALS				PART NO.	UNIT: mm	SCALE: 1:1	SHEET 1 OF 1	
NEW				30~40	±0.30	ANGLE		
				10~30	±0.20			
				5~10	±0.15			
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	DRAWING NO.	PROJ. ○
				~ 5	±0.10			