

# Reporting API Documentation

---

## CHANGE LOGS

Date	Description	Version
2015-09-23	Initial Release	1.1
2015-11-10	Add sub merchant update and delete methods	1.2

---

## TABLE OF CONTENTS

Change logs .....	1
Table of contents .....	2
Introduction .....	4
Method Overview .....	6
Merchant login .....	7
Transaction report .....	35
Transaction query .....	37
Get transaction .....	43
Get client .....	47

---

# INTRODUCTION

The Reporting API gives you access to most of the report data in PSP. With the Reporting API you can :

- Build custom dashboards to display PSP API data.
- Save time by automating complex reporting tasks.

## 1. Requirement

To begin using the API, you should have received your API Key. The API Key “apiKey” has to be added in the parameters of every request.

## 2. Security

The API uses a secured and encrypted communication over the HTTPS protocol. This protocol uses a layer called SSL encryption that ensures the integrity and the confidentiality of all data transmitted over the TCP/IP network layer. The security is provided by an authentication certificate issued from an approved third party authority.

Following the discovery of a security flaw in SSLv2-3, TLS must be used to call the API.

The security is increased by a second process in order to increase the safety of the services. All the request are logged on the our side. This allows us to track and send you alerts when suspicious behaviors are detected.

---

### 3. How it works

## METHODS OVERVIEW

Interface	Description
<b>/api/v3/merchant/user/login</b>	Login with email and password.
<b>/api/v3/transactions/report</b>	Request for list of transaction.
<b>/api/v3/transaction/list</b>	Request for list of transaction.
<b>/api/v3/transaction</b>	Request for all information of transaction.
<b>/api/v3/client</b>	Request for information of client.

---

## MERCHANT LOGIN

**LIVE URL** : <https://reporting.rpd pymnt.com/api/v3/merchant/user/login>

**TEST URL** : <https://sandbox-reporting.rpd pymnt.com/api/v3/merchant/user/login>

### Post parameters

Parameter name	Details	Example	Type	Mandatory
<b>email</b>	Email address of merchant user.	merchant@test.com	Char(128)	✓
<b>password</b>	Password	12345	Char(32)	✓

✓ Only one parameter is required.

### Response parameters

Parameter name	Details	Example	Type	Always there
<b>token</b>	JWT token.	eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluliwi	Text	
<b>status</b>	The API request status.	APPROVED	Char(64)	

### Request (Post parameter)

```
{
  email : "merchant@test.com"
  password : "123*-+"
}
```

## Successful Response

```
{
  token : "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGFudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluIiwibWVyY2hhbnRJZCI6MSwic3ViTWVyY2hhbnRJZHMlOiJ0eXAiOiJKV1QiLCJ0aW1lc3RhbXAiOiJ0eXNDQzODk0ODB9.zPxVu4fkRqIy1uG2f03X2RbxiI4otK_HG7M4MMTB298",
  status : "APPROVED"
}
```

The parameter 'token' in response is important, because token is required.

**Token is valid for 10 minutes.**

---

## TRANSACTION REPORT

**LIVE URL** : <https://reporting.rpdpymnt.com/api/v3/transactions/report>

**TEST URL** : <https://sandbox-reporting.rpdpymnt.com/api/v3/transactions/report>

### Post parameters

Parameter name	Details	Example	Type	Mandatory
<b>fromDate</b>	Start date	YYYY-MM-DD	Date	✓
<b>toDate</b>	Finish date.	YYYY-MM-DD	Date	✓
<b>merchant</b>	The merchant identifier.	1	Int	
<b>acquirer</b>	The acquirer identifier.	2	Int	

### Header parameters

Parameter name	Details	Example	Type	Mandatory
<b>Authorization</b>	JWT token generated in merchant login.	eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGFudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluliw	Text	✓

✓ Only one parameter is required.

### Response parameters

Parameter name		Details	Example	Type	Always there
<b>status</b>		The API request status.	APPROVED	Char(64)	
<b>response</b>	<b>count</b>	Quantity transaction	283	Int	
	<b>total</b>	Total amount	28300	Int	
	<b>currency</b>	Original currency	USD	Char(3)	



---

## Request

### Post parameters

```
{
  fromDate : "2015-07-01",
  toDate : "2015-10-01",
  merchant : 1,
  acquirer : 1,
}
```

### Header parameters

```
{
  Authorization : "eyJ0eXAI0iJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGFudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluIiwibWVzY2hhbnRJZCI6MSwic3ViTWVyYy1uG2f03X2RbxiI4otK_HG7M4MMTB298"
}
```

## Successful Response

```
{
  status : "APPROVED",
  response : [
    {
      count : 283,
      total : 28300,
      currency : "USD"
    },
    {
      count : 280,
      total : 1636515,
      currency : "EUR"
    }
  ]
}
```

## TRANSACTION QUERY

**LIVE URL** : <https://reporting.rpdymnt.com/api/v3/transaction/list>

**TEST URL** : <https://sandbox-reporting.rpdymnt.com/api/v3/transaction/list>

### Post parameters

Parameter name	Details	Example	Type	Mandatory
<b>fromDate</b>	Start Date	YYYY-MM-DD	Date	
<b>toDate</b>	Finish Date	YYYY-MM-DD	Date	
<b>status</b>	The API request status.	APPROVED	Char(64)	
<b>operation</b>	Request operation	3D	Char(64)	
<b>merchantId</b>	The merchant identifier.	1	Int	
<b>acquirerId</b>	The acquirer identifier.	2	Int	
<b>paymentMethod</b>	The payment method	CREDITCARD	Char(32)	
<b>errorCode</b>	Error Code	Invalid Card	Char(256)	
<b>filterField</b>	Search by special field	Customer Email	Char(128)	
<b>filterValue</b>	Value of field.	xxxx@test.com.tr	Char(256)	
<b>page</b>	Number of page	1	Int	

### Header parameters

Parameter name	Details	Example	Type	Mandatory
<b>Authorization</b>	JWT token generated in merchant login.	eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGFnZVZzZXJJZCI6MSwicm9sZSI6ImFkbWluliw	Text	✓

✓ Only one parameter is required.

---

## Response parameters

Parameter name		Details	Example	Type	Always there
per_page		Number of transaction for page.	50	Int	
current_page		Current page number	2	Int	
next_page_url		Url of next page	<a href="https://reporting.rpdpymnt.com/api/v3/transaction/list/?page=3">https://reporting.rpdpymnt.com/api/v3/transaction/list/?page=3</a>	Char(256)	
prev_page_url		Url of precedent page	<a href="https://reporting.rpdpymnt.com/api/v3/transaction/list/?page=1">https://reporting.rpdpymnt.com/api/v3/transaction/list/?page=1</a>	Char(256)	
from		Index number	50	Int	
to		Index number	100	Int	
data	fx	FX information	originalAmount, originalCurrency	Array	
	customerInfo	Customer Info	email, billingFirstName	Array	
	merchant	Merchant Info	name, id	Array	
	ipn	Ipn received	received	Array	
	transaction	Transaction Info	referenceNo,status	Array	
	acquirer	Acquirer Info	id,name	Array	
	refundable	Check if can refund the transaction.	true	Boolean	

---

## Request Parameters Details

**status** : { "APPROVED", "WAITING", "DECLINED", "ERROR" }

**operation** : { "DIRECT", "REFUND", "3D", "3DAUTH", "STORED" }

**paymentMethod** : { "CREDITCARD", "CUP", "IDEAL", "GIROPAY", "MISTERCASH", "STORED",  
"PAYTOCARD", "CEPBANK", "CITADEL" }

**errorCode** : { "Do not honor", "Invalid Transaction", "Invalid Card", "Not sufficient funds", "Incorrect PIN",  
"Invalid country association", "Currency not allowed", "3-D Secure Transport Error", "Transaction not  
permitted to cardholder" }

**filterField** : { "Transaction UUID", "Customer Email", "Reference No", "Custom Data", "Card PAN" }

## Request

### Post parameters

{ }

OR

```
{  
    fromDate : "2015-07-01",  
    toDate : "2015-10-01",  
}
```

OR

```
{  
    fromDate : "2015-07-01",  
    toDate : "2015-10-01",  
    merchant : 1,  
    acquirer : 1,  
}
```

---

OR

```
{
  "fromDate" : "2015-07-01",
  "toDate" : "2015-10-01",
  "merchantId" : 1,
  "acquirerId" : 1,
  "status" : "APPROVED",
  "operation" : "DIRECT",
  "paymentMethod" : "CREDITCARD",
  "filterField" : "Reference No",
  "filterValue" : "1-1568845-56",
  "page" : 1
}
```

OR

```
{
  "status" : "DECLINED",
  "operation" : "3D",
  "errorCode" : "Invalid Transaction"
}
```

#### Header parameters

```
{
  "Authorization" : "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGFudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluIiwibWVzY2hhbnRJZCI6MSwic3ViTWVyY2hhbnRJZHMltdLCJ0aw1lc3RhbXAiOiJE0NDQzODk4ODB9.zPxVu4fky1uG2f03X2RbxiI4otK_HG7M4MMTB298"
}
```

---

## Successful Response

```
{
  per_page : 50,
  current_page : 1,
  next_page_url :
  "http://reporting.rpdpymnt.com/api/v3/transaction/list/?page=2",
  prev_page_url : null,
  from : 1,
  to : 50,
  data : [{
    fx : {
      merchant : {
        originalAmount : 5,
        originalCurrency : "EUR"
      }
    },
    customerInfo : {
      number : "448574XXXXXX3395",
      email : "aykut.aras@bumin.com.tr",
      billingFirstName : "Aykut",
      billingLastName : "Aras"
    },
    merchant : {
      id : 3,
      name : "Dev-Merchant"
    },
    ipn : { received : true },
  ]
}
```

---

```

transaction :{
  merchant :{
    referenceNo : "api_560a4a9314208",
    status : "APPROVED",
    operation : "3DAUTH",
    message : "Auth3D is APPROVED",
    created_at : "2015-09-29 08:24:42",
    transactionId : "2827-1443515082-3"
  },
  acquirer :{
    id : 12,
    name : "Mergen Bank",
    code : "MB",
    type : "CREDITCARD"
  },
  refundable : true
},
{ fx :{ merchant :{ originalAmount : 100, originalCurrency : "EUR" }...},
{ fx :{ merchant :{ originalAmount : 100, originalCurrency : "EUR" }...},
.....
.....
.....
.....
}

```

---

## GET TRANSACTION

**LIVE URL** : <https://reporting.rpd pymnt.com/api/v3/transaction>

**TEST URL** : <https://sandbox-reporting.rpd pymnt.com/api/v3/transaction>

### Post parameters

Parameter name	Details	Example	Type	Mandatory
<b>transactionId</b>	Our unique transaction identifier.	529-1438673740-2	Char(32)	✓

### Header parameters

Parameter name	Details	Example	Type	Mandatory
<b>Authorization</b>	JWT token generated in merchant login.	eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGFudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluliw	Text	✓

✓ Only one parameter is required.

### Response parameters

Parameter name	Details	Example	Type	Always there
<b>fx</b>	FX information	originalAmount, originalCurrency	Array	
<b>customerInfo</b>	Customer Info	email, billingFirstName	Array	
<b>acquirerTransactions</b>	Acquirer Transaction Info	name of acquirer, code	Array	
<b>merchant</b>	Merchant Info	name, id	Array	
<b>merchantTransactions</b>	Merchant Transaction Info	referenceNo,status	Array	



---

## Request

### Post parameters

```
{
  transactionId : "1-1444392550-1"
}
```

### Header parameters

```
{
  Authorization : "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGFudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluIiwibWVyY2hhbnRJZCI6MSwic3ViTWVyY2hhbnRJZHMltdLCJ0aw1lc3RhbXAiOiJlNDQzODk4ODB9.zPxVu4fky1uG2f03X2RbxiI4otK_HG7M4MMTB298"
}
```

## Successful Response

```
{
  fx : {
    merchant : {
      originalAmount : 100,
      originalCurrency : "EUR"
    }
  },
  customerInfo : {
    id : 1,
    created_at : "2015-10-09 12:09:10",
    updated_at : "2015-10-09 12:09:10",
    deleted_at : null,
    number : "401288XXXXXX1881",
    expiryMonth : "6",
    expiryYear : "2017",
    startMonth : null,
  }
}
```

---

```
startYear : null,  
issueNumber : null,  
email : "michael@gmail.com",  
birthday : "1986-03-20 12:09:10",  
gender : null,  
billingTitle : null,  
billingFirstName : "Michael",  
billingLastName : "Kara",  
billingCompany : null,  
billingAddress1 : "test address",  
billingAddress2 : null,  
billingCity : "Antalya",  
billingPostcode : "07070",  
billingState : null,  
billingCountry : "TR",  
billingPhone : null,  
billingFax : null,  
shippingTitle : null,  
shippingFirstName : "Michael",  
shippingLastName : "Kara",  
shippingCompany : null,  
shippingAddress1 : "test address",  
shippingAddress2 : null,  
shippingCity : "Antalya",  
shippingPostcode : "07070",  
shippingState : null,  
shippingCountry : "TR",  
shippingPhone : null,
```

---

```
        shippingFax : null
    },
    merchant :{
        name : "Dev-Merchant"
    },
    transaction :{
        merchant :{
            referenceNo : "reference_5617ae66281ee",
            merchantId : 1,
            status : "WAITING",
            channel : "API",
            customData : null,
            chainId : "5617ae666b4cb",
            agentInfoId : 1,
            operation : "DIRECT",
            fxTransactionId : 1,
            updated_at : "2015-10-09 12:09:12",
            created_at : "2015-10-09 12:09:10",
            id : 1,
            acquirerTransactionId : 1,
            code : "00",
            message : "Waiting",
            transactionId : "1-1444392550-1",
            agent :{ id : 1, customerIp : "192.168.1.2",
                    customerUserAgent : "Agent", merchantIp : "127.0.0.1",...}
        }
    }
}
```

---

---

## GET CLIENT

**LIVE URL** : <https://reporting.rpd pymnt.com/api/v3/client>

**TEST URL** : <https://sandbox-reporting.rpd pymnt.com/api/v3/client>

### Post parameters

Parameter name	Details	Example	Type	Mandatory
<b>transactionId</b>	Our unique transaction identifier.	529-1438673740-2	Char(32)	✓

### Header parameters

Parameter name	Details	Example	Type	Mandatory
<b>Authorization</b>	JWT token generated in merchant login.	eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluliw	Text	✓

✓ Only one parameter is required.

### Response parameters

Parameter name	Details	Example	Type	Always there
<b>customerInfo</b>	Customer Info	email, billingFirstName	Array	

---

## Request

### Post parameters

```
{
  transactionId : "1-1444392550-1"
}
```

### Header parameters

```
{
  Authorization : "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJtZXJjaGFudFVzZXJJZCI6MSwicm9sZSI6ImFkbWluIiwibWVyY2hhbnRJZCI6MSwic3ViTWVyY2hhbnRJZHMltdLCJ0aW1lc3RhbXAiOiJlNDQzODk4ODB9.zPxVu4fky1uG2f03X2RbxiI4otK_HG7M4MMTB298"
}
```

## Successful Response

```
{
  customerInfo :{
    id : 1,
    created_at : "2015-10-09 12:09:10",
    updated_at : "2015-10-09 12:09:10",
    deleted_at : null,
    number : "401288XXXXXX1881",
    expiryMonth : "6",
    expiryYear : "2017",
    startMonth : null,
    startYear : null,
    issueNumber : null,
    email : "michael@gmail.com",
    birthday : "1986-03-20 12:09:10",
    gender : null,
    billingTitle : null,
  }
}
```

---

```
    billingFirstName : "Michael",
    billingLastName  : "Kara",
    billingCompany   : null,
    billingAddress1  : "test address",
    billingAddress2  : null,
    billingCity      : "Antalya",
    billingPostcode  : "07070",
    billingState     : null,
    billingCountry   : "TR",
    billingPhone     : null,
    billingFax       : null,
    shippingTitle    : null,
    shippingFirstName : "Michael",
    shippingLastName  : "Kara",
    shippingCompany   : null,
    shippingAddress1  : "test address",
    shippingAddress2  : null,
    shippingCity      : "Antalya",
    shippingPostcode  : "07070",
    shippingState     : null,
    shippingCountry   : "TR",
    shippingPhone     : null,
    shippingFax       : null
  }
}
```