

DIS Police DB System Tech Manual

Contents

1. Purpose & Basic requirements
2. Database
3. Files and Directories
4. How it works

1. Purpose & Basic requirements

1. Purpose :

This system was designed to provide an end-to-end system that will allow police officers to record and retrieve information about vehicles, people and traffic incidents.

Any officer who has an ID can login and use this system.

Also, there is an administrator who can manage accounts, add fines to any incidents or modify offence types in accordance with relevant laws.

2. Database : Mysql

3. Web page files : PHP(with JQuery 3.5.1(included in script folder), awesomefont)

2. Database

1. Server name & Username / PW : psxsm27 / Crystal!41
2. Schema name : psxsm27
3. Mysql version : 6.3


2. Database – tables info (types and relationships on the next page)

1. **People** : (PK)People_ID, People_name, People_address, People_licence – Personal records
2. **Vehicle** : (PK)Vehicle_ID, Vehicle_type, Vehicle_colour, Vehicle_licence – Vehicle records
3. **Ownership** : (FK)People_ID, (FK)Vehicle_ID – Vehicle ownership
4. **Offence** : (PK)Offence_ID, Offence_description, Offence_maxFine, Offence_maxPoints – Offence types and penalties
5. **Incident** : (PK)Incident_ID, (FK)Vehicle_ID, (FK)People_ID, (FK)Offence_ID, Incident_date, Incident_report – Incident records
6. **Fines** : (PK)Fine_ID, (FK)Incident_ID, Fine_amount, Fine_points – Fine records
7. **Users** : (PK)Users_ID, Users_name, Users_password – DB Web user accounts

- (PK)ID is auto-increment value in all tables.


- Tables connected to each other by FKs are on update & delete cascade,
so if any change occurs on one side, it will be reflected on the other.

2. Database – structure and input types (\sql\ERD.mwb)



1. People can own one or more vehicles
2. Ownership table reflects the ownership
3. For some vehicles, the owner might be unknown
4. There are some people who don't have any vehicle (It has not yet been identified or might actually be)

2. Database – structure and input types (\sql\ERD.mwb)



5. An incident involves one person and one vehicle
6. The involved vehicle may not be in possession of the involved person
7. In some cases, involved vehicle or person might be unknown
8. An incident is related to an offence
9. An incident will be fined by admin after it is reported by an officer
10. Users include user accounts

2. Database – Queries (\sql\queries.txt)

- The query file is in the sql folder together with ERD file. (sql : queries.txt, ERD: ERD.mwb)
- Some initial records will be inserted by insert queries.
- It will drop the tables with the same name first, so be sure to backup all the important data first!
- Queries order : drop previous table -> create new table -> insert records -> specify primary keys
-> set primary keys auto increment -> add foreign key relationships

3. Files and directories - Outline

1. Folders are categorised for each function

(people, vehicle, **incident -> report**, offence, fines, **manage account -> account**)

2. Each category(folder) includes three functions (search/insert and edit/ delete)

3. **Search function file name = folder name**

4. Search function files are the first pages of each category

5. Each file name starts with the first letter of the folder name and underline (Report -> starts with r_)

6. Insert and edit files named as **“ins_edit”** or **“ins”** if there is no edit function (People -> p_ins_edit)

7. Delete files named as **“delete”** (Fines -> f_delete)

3. Files and directories - Outline

8. Logo on the upper left corner is in images folder
9. CSS file “styles.css” is in css folder
10. The CSS file also follows the naming rules of files on the previous page (5.)
11. Connection configure file (dbcon.php), log in/out file (login.php and logout.php), Home file (main.php), and change password file (change_password.php) is in the root folder

3. Files and directories – PHP files

root : login, logout, change_password, main, dbcon

account: account, a_insert, a_delete

finer: finer, f_ins_edit, f_delete

offence: offence, off_ins_edit, off_delete

people: people, p_ins_edit, p_delete

report: report, r_ins_edit, r_delete

vehicle: vehicle, v_ins_edit, v_delete

3. Files and directories – Other files

root: accounts.txt

css: [CSS] styles.css

images: logo.jpg

script: jquery-3.5.1.min.js

sql: ERD.mwb, queries.txt

4. How it works

- Each php file is organised in the following order
 1. Session start, require dbcon.php, check the user is still logged-on
 2. Initialize post variables and error messages
 3. post variables and queries
 4. Javascript functions
 5. HTML (Search, Insert or Edit forms)
- For each input values, pattern, maxlength were used to prevent any user error
- For user convenience, input title, placeholder and oninvalid were used

4-1. How it works (login.php)



Login

Please fill in your ID and password to login.

Login.php is the first page of this system.

If the user is already logged in, he will be redirected to the main page.

```
// Check if the user is already logged in, if yes then redirect him to Main page
if (isset($_SESSION["loggedin"]) && $_SESSION["loggedin"] === true) {
    header("location: main.php");
    exit;
}
```

login.php

On the other hand, if someone tries to open other pages without logging in, he will be redirected to this page.

```
// Check if the user is logged in, if not then redirect to login page
if (!isset($_SESSION["loggedin"]) || $_SESSION["loggedin"] !== true) {
    header("location: ../login.php");
    exit;
}
```

The other pages

4-1. How it works (login.php)



DIS Police DB System

Login

Please fill in your ID and password to login.

Login

```
"SELECT * FROM Users WHERE Users_name = '$Users_name'";  
$correct_password = $row["Users_password"];
```

```
$Users_password == $correct_password  
-> login and redirect to main.php  
$_SESSION["loggedin"] = true;  
$_SESSION["Users_name"] = $Users_name;
```



```
if (strcasecmp($Users_name, "haskins") == 0) {  
    $_SESSION["isadmin"] = true;}
```

If \$Users_name or \$Users_password is empty after trimming, it will display error messages on the screen

Please enter username.

Please enter your password.

4-2. How it works (main.php)



Change password button
(href change_password.php),
Log out button
(href logout.php)

4-3. How it works (change_password.php)



DIS Police DB System

Hello, Regan.

[Change password](#)

[Log out](#)

Home

People

Vehicle

Report

Offence

Fines

Change Password

Please fill out this form to change your password.

New Password

Enter new password 6-10 characters without spaces

Confirm Password

Please input your password again to confirm

[Submit](#)

[Cancel](#)

```
$Users_name = $_SESSION["Users_name"];
```

```
If $new_password == $confirm_password
```

```
-> $sql = "UPDATE Users SET Users_password = '$new_password'
WHERE Users_name = '$Users_name'";
```

4-4. How it works (people.php)



DIS Police DB System

Hello, Regan.

[Change password](#)

[Log out](#)

Home

People

Vehicle

Report

Offence

Fines

Search or Update Personal Record

Name Enter search keyword or just press search button

href p_ins_edit.php

$\$p_category$

$\$p_search$

Non-case-sensitive,
partial search available

```
$sql = "SELECT * FROM People WHERE " . $p_category . " LIKE \"%\" . $p_search . "%\"  
LIMIT $start_from, $per_page_record;";
```

pagination

Set $\$per_page_record$ as appropriate
The search form includes $\$page$ as a hidden input

```
if (isset($_POST["page"])) { $page = $_POST["page"]; } else { $page = 1; }  
$start_from = ($page - 1) * $per_page_record;
```

4-4. How it works (people.php)



DIS Police DB System

Hello, Regan.

[Change password](#)

[Log out](#)

Home

People

Vehicle

Report

Offence

Fines

Search or Update Personal Record

Name Enter search keyword or just press search button

[href p_delete.php](#)

[p_ins_edit.php](#)

Name	Address	Licence	Delete	Edit
James Smith	23 Barnsdale Road, Leicester	SMITH92LDOFJJ829	Delete	Edit
Jennifer Allen	46 Bramcote Drive, Nottingham	ALLEN88K23KLR9B3	Delete	Edit
John Myers	323 Derby Road, Nottingham	MYERS99JDW8REWL3	Delete	Edit
James Smith	26 Devonshire Avenue, Nottingham	SMITHR004JFS20TR	Delete	Edit
Terry Brown	7 Clarke Rd, Nottingham	BROWND3PJJ39DLFG	Delete	Edit
Mary Adams	38 Thurman St, Nottingham	ADAMSH9O3JRHH107	Delete	Edit
Neil Becker	6 Fairfax Close, Nottingham	BECKE88UPR840F9R	Delete	Edit
Angela Smith	30 Avenue Road, Grantham	SMITH222LE9FJ5DS	Delete	Edit
Morgan Wilson	4 Redwood Court, Bottesford	WILSON25EF0SA2FW	Delete	Edit
Frankie Watts	Cornerstone House, Glandwr	WATTS523WB1JE0SF	Delete	Edit

Search result table

1 2 Next

Button onclick = script function `page_move()`;
It submits the form again with different page numbers

4-4. How it works (p_delete.php)

people.php


```
function confirmDelete(ID)
window.location.href = "p_delete.php?People_ID=".concat(ID)
```

GET method, each button contains each record's People_ID

```
<td><button onclick='confirmDelete(".$row["People_ID"].")'>
Delete</button></td>
```

p_delete.php

```
$People_ID=$_REQUEST['People_ID'];
$sql = "DELETE FROM People WHERE People_ID=".$People_ID."";
```



Licence		
SMITH92LDOFJJ829	Delete	Edit
ALLEN88K23KLR9B3	Delete	Edit
MYERS99JDW6REWL3	Delete	Edit
SMITHR004JFS20TR	Delete	Edit
BROWND3PJ39DLFG	Delete	Edit
ADAMSH903JRHH107	Delete	Edit
BECKE88UPR840F9R	Delete	Edit
SMITH222LE9FJ5DS	Delete	Edit
WILSON25EF0SA2FW	Delete	Edit
WATTS523WB1JE0SF	Delete	Edit

4-4. How it works (p_ins_edit.php) - Insert



DIS Police DB System

Hello, Regan.

[Change password](#)

[Log out](#)

Home

People

Vehicle

Report

Offence

Fines

Insert New Personal Record

Name

Address

Licence

[Submit](#)

[Cancel](#)

```
$Status = 0; // insert(0), edit(1)
```

```
$People_name;
```

```
$People_address;
```

```
$People_licence;
```

```
// check if the People_licence is already in the database
```

```
$sql=
```

```
"SELECT * FROM People WHERE People_licence = '$People_licence'";
```

```
// If not,
```

```
$sql =
```

```
"INSERT INTO People (People_name,People_address,People_licence)
VALUES ('$People_name','$People_address','$People_licence')";
```

4-4. How it works (p_ins_edit.php) - Edit

people.php

```
function Edit(ID)
window.location.href = "p_ins_edit.php?People_ID=".concat(ID).
concat("&&Status=1")
```


GET method, send selected ID and status=1

p_ins_edit.php

```
if (isset($_GET["People_ID"]) && $_GET["Status"] == 1)
    $Edit_people_ID = $_GET["People_ID"];
    $Status = $_GET["Status"];

    $sql = "SELECT * FROM People WHERE People_ID = '$Edit_people_ID'";
    $People_name = $row['People_name'];
    $People_address = $row['People_address'];
    $People_licence = $row['People_licence'];
```

Using the Select query, get previous input values to edit
and input them on the edit form



Licence		
SMITH92LDOFJJ829	Delete	Edit
ALLEN88K23KLR9B3	Delete	Edit
MYERS99JDW8REW3	Delete	Edit
SMITHR004JFS20TR	Delete	Edit
BROWND3PJ39DLFG	Delete	Edit
ADAMSH903JRHH107	Delete	Edit
BECKE88UPR840F9R	Delete	Edit
SMITH222LE9FJ5DS	Delete	Edit
WILSON25EF0SA2FW	Delete	Edit
WATTS523WB1JE0SF	Delete	Edit

4-4. How it works (p_ins_edit.php) - Edit



DIS Police DB System

Hello, Regan.

Change password Log out

- Home
- People
- Vehicle
- Report
- Offence
- Fines

Update Personal Record

Name

Address

Licence

Update Cancel

2. Store Post values edited
`$People_name` , `$People_address` , `$People_licence` , `$Edit_people_ID`

3. Update table using query
`$sql = "UPDATE People SET People_name = '$People_name',
People_address = '$People_address',
People_licence = '$People_licence'
WHERE People_ID = '$Edit_people_ID'";`

1. At first, as mentioned on the previous page, there will be previous input values



DIS Police DB System

Hello, Regan.


Change password Log out

- Home
- People
- Vehicle
- Report
- Offence
- Fines

Search or Update Personal Record

Name	Address	Licence	Delete	Edit
James Smith	23 Barnsdale Road, Leicester	SMITH92LDOFJJ829	Delete	Edit
Jennifer Allen	46 Bramcote Drive, Nottingham	ALLEN88K23KLR9B3	Delete	Edit
John Myers	323 Derby Road, Nottingham	MYERS99JDW8REW13	Delete	Edit
James Smith	26 Devonshire Avenue, Nottingham	SMITHR004JFS20TR	Delete	Edit
Terry Brown	7 Clarke Rd, Nottingham	BROWND3PJ39DLFG	Delete	Edit
Mary Adams	38 Thurman St, Nottingham	ADAMSH903JRH107	Delete	Edit
Neil Becker	6 Fairfax Close, Nottingham	BECKE88UPR840F9R	Delete	Edit
Angela Smith	30 Avenue Road, Grantham	SMITH222LE9FJ5DS	Delete	Edit
Morgan Wilson	4 Redwood Court, Bottesford	WILSON29EF0SA2FW	Delete	Edit
Frankie Watts	Cornerstone House, Glandwr	WATT5523WB1JE0SF	Delete	Edit

4-5. How it works (vehicle.php)



4-5. How it works (vehicle.php)



DIS Police DB System

Hello, Regan.

[Change password](#)

[Log out](#)

Home

People

Vehicle

Report

Offence

Fines

Search or Update Vehicle Record

Vehicle licence Enter search keyword or just press search button

[href v_delete.php](#)

[v_ins_edit.php](#)

Type	Colour	Vehicle licence	Owner name	Owner licence	Delete	Edit
Ford Fiesta	Blue	LB15AJL	John Myers	MYERS99JDW8REWL3	Delete	Edit
Ferrari 458	Red	MY64PRE	Angela Smith	SMITH222LE9FJ5DS	Delete	Edit
Vauxhall Astra	Silver	FD65WPQ	James Smith	SMITHR004JFS20TR	Delete	Edit
Honda Civic	Green	FJ17AUG	Jennifer Allen	ALLEN88K23KLR9B3	Delete	Edit
Toyota Prius	Silver	FP16KKE	James Smith	SMITHR004JFS20TR	Delete	Edit
Ford Mondeo	Black	FP66KLM			Delete	Edit
Ford Focus	White	DJ14SLE	Terry Brown	BROWND3PJJ39DLFG	Delete	Edit
Nissan Pulsar	Red	NY64KWD			Delete	Edit
Renault Scenic	Silver	BC16OEA	Neil Becker	BECKE88UPR840F9R	Delete	Edit
Ford Focus	Black	FS346FA	James Smith	SMITH92LDOFJJ829	Delete	Edit

Search result table

1 2 Next

Button onclick = script function `page_move()`;
It submits the form again with different page numbers

4-4. How it works (v_delete.php)

vehicle.php


```
function confirmDelete(ID)
window.location.href = "v_delete.php?Vehicle_ID=".concat(ID)
```

GET method, each button contains each record's Vehicle_ID

```
<td><button onclick='confirmDelete(".$row["Vehicle_ID"].")'>
Delete</button></td>
```

v_delete.php

```
$Vehicle_ID=$_REQUEST['Vehicle_ID'];
$sql = "DELETE FROM Vehicle WHERE Vehicle_ID=".$Vehicle_ID."";
```



Owner licence		
MYERS99JDW8REWL3	Delete	Edit
SMITH222LE9FJ5DS	Delete	Edit
SMITHR004JFS20TR	Delete	Edit
ALLEN88K23KLR9B3	Delete	Edit
SMITHR004JFS20TR	Delete	Edit
	Delete	Edit
BROWND3PJ39DLFG	Delete	Edit
	Delete	Edit
BECKE88UPR840F9R	Delete	Edit
SMITH92LDOFJJ829	Delete	Edit

4-5. How it works (v_ins_edit.php) - Insert



DIS Police DB System

Hello, Regan.

[Change password](#)

[Log out](#)

Home

People

Vehicle

Report

Offence

Fines

Insert New Vehicle Record

1. Input vehicle info

Type

Colour

Vehicle licence

`$Vehicle_type;`
`$Vehicle_colour;`
`$Vehicle_licence;`

2. Choose owner status

- ☐ Person already in the database
- ☐ Person not in the database
- ☐ Unknown

`$P_status =`
`$_POST['p_radio_btn'];`
`value :`
`"existing_owner" or`
`"new_owner" or`
`"unknown"`

Onclick Javascript
`contentsview();`
It shows the appropriate
form for each `$P_status`

[Submit](#)

[Cancel](#)

4-5. How it works (v_ins_edit.php) – Insert [Existing owner]

`$Ex_p_licence`, if the owner selected on 3., it will be automatically filled out.
Not used "readonly" attribute to make it "required", use `preventDefault()`;
`$(".readonly").keydown(function(e) {e.preventDefault();});`

Insert New Vehicle Record

1. Input vehicle info

Type

BMW 320d

Colour

White

Vehicle licence

CEF24XV

`$Vehicle_type;`
`$Vehicle_colour;`
`$Vehicle_licence;`

2. Choose owner status

Selected Owner Licence

SMITH92LDOFJJ829

- ☒ Person already in the database
☐ Person not in the database
☐ Unknown

`$P_status = "existing_owner"`

`contentsview();`

3. Search & Select existing owner

Name Enter search keyword or just press search

Name	Address	Licence	Select
James Smith	23 Darnsdale Road, Leicester	SMITH92LDOFJJ829	<input checked="" type="radio"/>
Jennifer Allen	46 Bramcote Drive, Nottingham	ALLEN88K23KLR9B3	<input type="radio"/>
John Myers	323 Derby Road, Nottingham	MYERS99JDW8REWL3	<input type="radio"/>
James Smith	26 Devonshire Avenue, Nottingham	SMITHR004JFS20TR	<input type="radio"/>
Terry Brown	7 Clarke Rd, Nottingham	BROWND3PJ39DLFG	<input type="radio"/>

1 2 3 Next

`function Select(Selected_p_ID, Selected_p_licence)`
`$Ex_people_ID = Selected_p_ID;`
`$Ex_p_licence = Selected_p_licence;`

Submit

Cancel

The owner search form works in the same way as people search

Home

People

Vehicle

Report

Offence

Fines

4-5. How it works (v_ins_edit.php) – Insert [Existing owner]

[Home](#)
[People](#)
[Vehicle](#)
[Report](#)
[Offence](#)
[Fines](#)

Insert New Vehicle Record

1. Input vehicle info

Type
BMW 320d

Colour
White

Vehicle licence
CEF24XV

2. Choose owner status

Selected Owner Licence
SMITH92LDOFJJ829

☒ Person already in the database
☐ Person not in the database
☐ Unknown

3. Search & Select existing owner

Name

Enter search keyword or just press search

Q

Name	Address	Licence	Select
James Smith	23 Barnsdale Road, Leicester	SMITH92LDOFJJ829	<input checked="" type="radio"/>
Jennifer Allen	4	K23KLR9B3	<input type="radio"/>
John Myers	323 Derby Road, Nottingham	MYERS99JDW8REW3	<input type="radio"/>
James Smith	26 Devonshire Avenue, Nottingham	SMITHR004JFS20TR	<input type="radio"/>
Terry Brown	7 Clarke Rd, Nottingham	BROWND3PJ39DLFG	<input type="radio"/>

1 2 3 Next

Submit

Cancel

\$Ex_p_licence

contentsview();

\$P_status = "existing_owner"

Select(); \$Ex_people_ID;

\$Vehicle_type;
\$Vehicle_colour;
\$Vehicle_licence;

This search form onSubmit="SaveInput();" It temporarily saves all input values in sessionStorage when pressing the search button.

4-5. How it works (v_ins_edit.php) – Insert [Existing owner]

```
// Check if the same vehicle licence number is already in the database
$select_query = "SELECT * FROM Vehicle WHERE Vehicle_licence = '$Vehicle_licence'";

// If not, use transaction to prevent any situation where only part of them executed.
if ($P_status == "existing_owner")

    Try { mysqli_autocommit($conn, false);

        $sql1 = "INSERT INTO Vehicle (Vehicle_type,Vehicle_colour,Vehicle_licence) VALUES
            ('$Vehicle_type','$Vehicle_colour','$Vehicle_licence')";

        $Vehicle_ID = mysqli_insert_id($conn); // Get the Vehicle_ID inserted by $sql1
        $sql2 = "INSERT INTO Ownership VALUES ('$Ex_people_ID', '$Vehicle_ID')";

        mysqli_commit($conn);

    } Catch () {...}

// So, there will be both new vehicle record and new ownership record.
```

4-5. How it works (v_ins_edit.php) – Insert [New owner]

Home

People

Vehicle

Report

Offence

Fines

Insert New Vehicle Record

1. Input vehicle info

Type

BMW 320d

Colour

White

Vehicle licence

CEF24XV

2. Choose owner status

☐ Person already in the database

☒ Person not in the database

☐ Unknown

\$Vehicle_type;

\$Vehicle_colour;

\$Vehicle_licence;

3. Input info of new owner

Name

Enter name (letters and spaces)

Address

Enter address

Licence

Enter 16-digit licence (letters and numbers without spaces)

Submit

Cancel

\$P_status = "new_owner"

contentsview();

\$People_name; \$People_address; \$People_licence;

4-5. How it works (v_ins_edit.php) – Insert [New owner]

```
if ($P_status == "new_owner")

// Check if the personal licence number is already in the database
$select_query = "SELECT * FROM People WHERE People_licence = '$People_licence'";

// If not, transaction to prevent any situation where only part of these queries executed.
Try { mysqli_autocommit($conn, false);

// Insert into People
$sql1 = "INSERT INTO People (People_name,People_address,People_licence)
VALUES ('$People_name','$People_address','$People_licence')";
$People_ID = mysqli_insert_id($conn); // Get inserted people_ID
// Insert into Vehicle
$sql2 = "INSERT INTO Vehicle (Vehicle_type,Vehicle_colour,Vehicle_licence)
VALUES ('$Vehicle_type','$Vehicle_colour','$Vehicle_licence')";
$Vehicle_ID = mysqli_insert_id($conn); // Get inserted Vehicle_ID
// Insert into Ownership
$sql3 = "INSERT INTO Ownership VALUES ('$People_ID', '$Vehicle_ID')";

mysqli_commit($conn);

} Catch () {...}
// So, there will be new vehicle record, people record, and ownership record.
```


4-5. How it works (v_ins_edit.php) – Insert [Owner unknown]



DIS Police DB System

Hello, Regan.

[Change password](#)

[Log out](#)

Home

People

Vehicle

Report

Offence

Fines

Insert New Vehicle Record

1. Input vehicle info

Type

BMW 320d

Colour

White

Vehicle licence

CEF24XV

```
$Vehicle_type;  
$Vehicle_colour;  
$Vehicle_licence;
```

2. Choose owner status

☐ Person already in the database

☐ Person not in the database

☒ Unknown

```
$P_status = "unknown"
```

```
contentsview();
```

```
// Insert into Vehicle
```

```
$sql = "INSERT INTO Vehicle (Vehicle_type,Vehicle_colour,Vehicle_licence)  
VALUES ('$Vehicle_type','$Vehicle_colour','$Vehicle_licence');";
```

```
// Only a new vehicle record will be inserted
```

[Submit](#)

[Cancel](#)

4-5. How it works (v_ins_edit.php) - Edit

Vehicle.php


```
function Edit(ID)
window.location.href = "v_ins_edit.php?Vehicle_ID=".concat(ID).
concat("&&Status=1")
```

GET method, send selected ID and status=1

v_ins_edit.php

```
if (isset($_GET["Vehicle_ID"]) && $_GET["Status"] == 1)
// get the chosen vehicle ID & status,
// and then set up edit form with previous values
$Edit_vehicle_ID = $_GET["Vehicle_ID"];
$Status = $_GET["Status"];
$sql = "SELECT * FROM Vehicle NATURAL LEFT JOIN Ownership
NATURAL LEFT JOIN People WHERE Vehicle_ID = '$Edit_vehicle_ID'";
$Vehicle_type = $row['Vehicle_type'];
$Vehicle_colour = $row['Vehicle_colour'];
$Vehicle_licence = $row['Vehicle_licence'];
$Ex_people_ID = $row['People_ID'];

// set the owner status based on the previous value
if ($Ex_people_ID == "") -> $P_status = "unknown";
else -> $P_status = "existing_owner"; $Ex_p_licence = $row['People_licence'];
```



Owner licence		
MYERS99JDW8REWL3	Delete	Edit
SMITH222LE9FJ5DS	Delete	Edit
SMITHR004JFS20TR	Delete	Edit
ALLEN88K23KLR9B3	Delete	Edit
SMITHR004JFS20TR	Delete	Edit
	Delete	Edit
BROWND3PJ39DLFG	Delete	Edit
	Delete	Edit
BECKE88UPR840F9R	Delete	Edit
SMITH92LDOFJJ829	Delete	Edit

4-5. How it works (v_ins_edit.php) - Edit

The edit form mechanism is the same as the people page.

There will be previous values with radio buttons selected, and users can edit them.

```
// Check if the updated licence number is already in the database and it is not the previous one
```

```
$Select_query = "SELECT * FROM Vehicle WHERE Vehicle_licence = '$Vehicle_licence'";
```

```
$row = mysqli_fetch_assoc($Select_result);
```

```
$Vehicle_ID = $row['Vehicle_ID'];
```

```
if ($Edit_vehicle_ID != $Vehicle_ID)
```

```
// If not, update
```

```
$Status == 1 and existing_owner
```

```
// Use transaction to prevent any situation where only part of them updated
```

```
Try { mysqli_autocommit($conn, false);
```

```
// Update vehicle record
```

```
$sql1 = "UPDATE Vehicle SET Vehicle_type = '$Vehicle_type', Vehicle_colour = '$Vehicle_colour',
```

```
Vehicle_licence = '$Vehicle_licence' WHERE Vehicle_ID = '$Edit_vehicle_ID'";
```

```
// Check if the vehicle was owned by someone else
```

```
// If so, update the ownership record
```

```
$sql2 = "UPDATE Ownership SET People_ID = '$Ex_people_ID' WHERE Vehicle_ID = '$Edit_vehicle_ID'";
```

```
// If not, insert new ownership record
```

```
$sql2 = "INSERT INTO Ownership VALUES ('$Ex_people_ID', '$Edit_vehicle_ID');";
```

```
mysqli_commit($conn);
```

```
} Catch () {...}
```

4-5. How it works (v_ins_edit.php) - Edit

```
$Status == 1 and new_owner
    // Use transaction to prevent any situation where only part of them updated
Try { mysqli_autocommit($conn, false);

    // check if the People_licence is already in the database
    $Select_query = "SELECT * FROM People WHERE People_licence = '$People_licence'";
    // If not, insert into people
    $sql1 = "INSERT INTO People (People_name,People_address,People_licence)
            VALUES ('$People_name','$People_address','$People_licence')";
    $People_ID = mysqli_insert_id($conn);

    // update vehicle
    $sql2 = "UPDATE Vehicle SET Vehicle_type = '$Vehicle_type', Vehicle_colour = '$Vehicle_colour',
            Vehicle_licence = '$Vehicle_licence' WHERE Vehicle_ID = '$Edit_vehicle_ID'";

    // Check if the vehicle was owned by someone else
    $Select_query = "SELECT * FROM Ownership WHERE Vehicle_ID = '$Edit_vehicle_ID'";
    // if so, update the ownership
    $sql3 = "UPDATE Ownership SET People_ID = '$People_ID' WHERE Vehicle_ID = '$Edit_vehicle_ID'";
    // if not, insert new ownership record
    $sql3 = "INSERT INTO Ownership VALUES ('$People_ID', '$Edit_vehicle_ID')";

    mysqli_commit($conn); } Catch () {...}
```

4-5. How it works (v_ins_edit.php) - Edit

```
$Status == 1 and unknown
    // Use transaction to prevent any situation where only part of them updated
    Try { mysqli_autocommit($conn, false);

        // Update vehicle record
        $sql1 = "UPDATE Vehicle SET Vehicle_type = '$Vehicle_type', Vehicle_colour = '$Vehicle_colour',
                Vehicle_licence = '$Vehicle_licence' WHERE Vehicle_ID = '$Edit_vehicle_ID'";

        // Delete the previous ownership record of the vehicle
        $sql2 = "DELETE FROM Ownership WHERE Vehicle_ID = '$Edit_vehicle_ID'";

        mysqli_commit($conn);

    } Catch () {...}
```

4-6. How it works (report.php)



Home

People

Vehicle

Report

Offence

Fines

Search or Update Incident Record

Offence type - All

\$R_category_2

From mm/dd/yyyy To mm/dd/yyyy

\$From, \$To

Incident ID Enter search keyword or just press search button

href r_ins_edit.php

Incident ID	Date	Personal name	Personal licence	Vehicle licence	Offence type	Report	Vehicle type	Vehicle colour	Delete	Edit
1	2017-12-01	James Smith	SMITHR004JFS20TR	FP16KKE	Speeding	40mph in a 30 limit	Toyota Prius	Silver	Delete	Edit
2	2017-11-01	Angela Smith	SMITH222LE9FJ5DS	MY64PRE	Illegal parking	Double parked	Ferrari 458	Red	Delete	Edit
3	2017-09-17	James Smith	SMITHR004JFS20TR	FD65WPQ	Speeding	110mph on motorway	Vauxhall Astra	Silver	Delete	Edit
4	2017-08-22	Jennifer Allen	ALLEN88K23KLR9B3	FJ17AUG	Cycling on pavement	Failure to stop at a red light - travelling 25mph	Honda Civic	Green	Delete	Edit
5	2017-10-17	James Smith	SMITHR004JFS20TR	FD65WPQ	Seat belt offence	Not wearing a seatbelt on the M1	Vauxhall Astra	Silver	Delete	Edit

r_ins_edit.php

href r_delete.php

\$R_category

\$R_search

1

Search result table

Button onclick = script function page_move();
It submits the form again with different page numbers

4-6. How it works (report.php)

```
// If Offence_type All
// Natural left join to search involved person and vehicle info together
if ($R_category_2 == 'All')
$sql = "SELECT * FROM Incident NATURAL LEFT JOIN Vehicle NATURAL LEFT JOIN People
        NATURAL LEFT JOIN Offence // LEFT JOIN to include offence type, involved person and vehicle
        WHERE " . $R_category . " LIKE \"%\" . $R_search . \"%\" // for non-case-sensitive and partial search
        AND Incident_date BETWEEN '$From' AND '$To' ORDER BY Incident_ID ASC // From and To date
        LIMIT $start_from, $per_page_record;"; // Pagination

// Else if certain offence_type is selected
// Natural left join to search involved person and vehicle info together
$R_sql_1 = "SELECT * FROM Incident NATURAL LEFT JOIN Vehicle NATURAL LEFT JOIN People
        NATURAL LEFT JOIN Offence
        WHERE " . $R_category . " LIKE \"%\" . $R_search . \"%\"
        AND Incident_date BETWEEN '$From' AND '$To'
        AND Offence_description = '$R_category_2' ORDER BY Incident_ID ASC // Offence_type
        LIMIT $start_from, $per_page_record;";

// if To date is not specified, then it will be set today's date
if ($_POST['to'] != '' && $_POST['to'] != null) {
    $To = $_POST['to'];
} else {
    $To = date("Y-m-d");
}
```

4-6. How it works (r_delete.php)

report.php


```
function confirmDelete(ID)
window.location.href = "r_delete.php?Incident_ID=".concat(ID)
```

GET method, each button contains each record's Incident_ID

```
<td><button onclick='confirmDelete(".$row["Incident_ID"].")'>
Delete</button></td>
```

r_delete.php

```
$Incident_ID=$_REQUEST['Incident_ID'];
$sql = "DELETE FROM Incident WHERE Incident_ID=".$Incident_ID."";
```



Report	Vehicle type	Vehicle colour		
0mph in a 30 limit	Toyota Prius	Silver	Delete	Edit
Double parked	Ferrari 458	Red	Delete	Edit
0mph on motorway	Vauxhall Astra	Silver	Delete	Edit
at a red light - travelling 25mph	Honda Civic	Green	Delete	Edit
ing a seatbelt on the M1	Vauxhall Astra	Silver	Delete	Edit

4-6. How it works (r_ins_edit.php) - Insert

\$Incident_date, \$Incident_report, \$Offence_description

Insert New Incident Record

1. Input basic info

Incident date

mm/dd/yyyy



Incident description

Enter description

Offence type

Speeding



2. Person involved

Selected person Licence:

SMITH92LDOFJJ829

☒ Person already in the database ☐ Person not in the database ☐ Unknown Person

`contentsView();`

2.2. Search & Select existing person

Name

Enter search keyword or just press search



`select();`

Name	Address	Personal licence	Select
James Smith	23 Barnsdale Road, Leicester	SMITH92LDOFJJ829	<input checked="" type="radio"/>
Jennifer Allen	46 Bramcote Drive, Nottingham	ALLEN88K23KLR9B3	<input type="radio"/>
John Myers	323 Derby Road, Nottingham	MYERS99JDW8REWL3	<input type="radio"/>
James Smith	26 Devonshire Avenue, Nottingham	SMITHR004JFS20TR	<input type="radio"/>
Terry Brown	7 Clarke Rd, Nottingham	BROWND3PJJ39DLFG	<input type="radio"/>

1

2

3

Next

3. Vehicle involved

☐ Vehicle already in the database ☒ Vehicle not in the database ☐ Unknown Vehicle

`contentsView();`

3.2. Input info of new vehicle

Type

Enter Type

Colour

Enter colour without special characters

Vehicle Licence

Enter 7-digit vehicle licence (letters and numbers)

Submit

Cancel

This page follows the same mechanism as the vehicle page

4-6. How it works (r_ins_edit.php) - Insert

```
// existing person
// existing vehicle
// insert into incident with chosen people ID and vehicle ID
$sql = "INSERT INTO Incident
      (Vehicle_ID, People_ID, Incident_date, Incident_report, Offence_ID) VALUES
      ('$Ex_vehicle_ID', '$Ex_people_ID', '$Incident_date', '$Incident_report', '$Offence_ID');"

// new vehicle
// Check if the same vehicle licence number is already in the database
$select_query = "SELECT * FROM Vehicle WHERE Vehicle_licence = '$Vehicle_licence'";

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);
    // Insert into Vehicle
    $V_ins_query = "INSERT INTO Vehicle (Vehicle_type,Vehicle_colour,Vehicle_licence) VALUES
    ('$Vehicle_type','$Vehicle_colour','$Vehicle_licence');"
    // Get the inserted vehicle ID
    $Vehicle_ID = mysqli_insert_id($conn);
    // Insert into Incident
    $sql = "INSERT INTO Incident (Vehicle_ID, People_ID, Incident_date, Incident_report, Offence_ID)
    VALUES ('$Vehicle_ID', '$Ex_people_ID', '$Incident_date', '$Incident_report', '$Offence_ID');"

    mysqli_commit($conn);

} Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Insert

```
// existing person
// unknown vehicle
// insert into incident with chosen people ID
$sql = "INSERT INTO Incident (People_ID, Incident_date, Incident_report, Offence_ID) VALUES
      ($Ex_people_ID, '$Incident_date', '$Incident_report', '$Offence_ID')";

// new person
// existing vehicle
// check if the People_licence is already in the database
$Select_query = "SELECT * FROM People WHERE People_licence = '$People_licence'";

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);
    // Insert into People
    $P_ins_query = "INSERT INTO People (People_name, People_address, People_licence)
                  VALUES ('$People_name', '$People_address', '$People_licence')";
    // Get the inserted People ID
    $People_ID = mysqli_insert_id($conn);

    // Insert into Incident
    $sql = "INSERT INTO Incident (Vehicle_ID, People_ID, Incident_date, Incident_report, Offence_ID)
          VALUES ('$Ex_vehicle_ID', '$People_ID', '$Incident_date', '$Incident_report', '$Offence_ID')";

    mysqli_commit($conn); } Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Insert

```
// new person
// new vehicle
// Check if the People_licence is already in the database
$select_query = "SELECT * FROM People WHERE People_licence = '$People_licence'";

// Check if the same vehicle licence number is already in the database
$select_query = "SELECT * FROM Vehicle WHERE Vehicle_licence = '$Vehicle_licence'";

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);
    // Insert into People
    $P_ins_query = "INSERT INTO People (People_name,People_address,People_licence)
        VALUES ('$People_name','$People_address','$People_licence')";
    // Get the inserted People ID
    $People_ID = mysqli_insert_id($conn);
    // Insert into Vehicle
    $V_ins_query = "INSERT INTO Vehicle (Vehicle_type,Vehicle_colour,Vehicle_licence) VALUES
        ('$Vehicle_type','$Vehicle_colour','$Vehicle_licence')";
    // Get the inserted Vehicle ID
    $Vehicle_ID = mysqli_insert_id($conn);

    // Insert into Incident
    $sql = "INSERT INTO Incident (Vehicle_ID, People_ID, Incident_date, Incident_report, Offence_ID)
        VALUES ('$Vehicle_ID', '$People_ID', '$Incident_date', '$Incident_report', '$Offence_ID')";

    mysqli_commit($conn); } Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Insert

```
// new person
// unknown vehicle
// check if the People_licence is already in the database
$select_query = "SELECT * FROM People WHERE People_licence = '$People_licence'";

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);

    // Insert into People
    $P_ins_query = "INSERT INTO People (People_name,People_address,People_licence)
                    VALUES ('$People_name','$People_address','$People_licence')";
    // Get the inserted People ID
    $People_ID = mysqli_insert_id($conn);

    // Insert into Incident
    $sql = "INSERT INTO Incident (People_ID, Incident_date, Incident_report, Offence_ID) VALUES
            ('$People_ID', '$Incident_date', '$Incident_report', '$Offence_ID')";

    mysqli_commit($conn); } Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Insert

```
// unknown person
// existing vehicle
// Insert into Incident
$sql = "INSERT INTO Incident (Vehicle_ID, Incident_date, Incident_report, Offence_ID) VALUES
      ('$Ex_vehicle_ID', '$Incident_date', '$Incident_report', '$Offence_ID');"

// new vehicle
// Check if the same vehicle licence number is already in the database
$select_query = "SELECT * FROM Vehicle WHERE Vehicle_licence = '$Vehicle_licence'";

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);

    // Insert into Vehicle
    $V_ins_query = "INSERT INTO Vehicle (Vehicle_type,Vehicle_colour,Vehicle_licence) VALUES
                  ('$Vehicle_type','$Vehicle_colour','$Vehicle_licence');"
    // Get the inserted Vehicle ID
    $Vehicle_ID = mysqli_insert_id($conn);

    // Insert into Incident
    $sql = "INSERT INTO Incident (Vehicle_ID, Incident_date, Incident_report, Offence_ID) VALUES
          ('$Vehicle_ID', '$Incident_date', '$Incident_report', '$Offence_ID');"

    mysqli_commit($conn); } Catch ( ) {...}
```

4-6. How it works (r_ins_edit.php) - Insert

```
// unknown person
// unknown vehicle
// Insert into Incident
$sql = "INSERT INTO Incident (Incident_date, Incident_report, Offence_ID) VALUES
      ('$Incident_date', '$Incident_report', '$Offence_ID');";
```

4-6. How it works (r_ins_edit.php) - Edit

Report.php

```
function Edit(ID)
window.location.href = "r_ins_edit.php?Incident_ID=".concat(ID).
concat("&&Status=1")
```

GET method, send selected ID and status=1


r_ins_edit.php

```
if (isset($_GET["Incident_ID"]) && $_GET["Status"] == 1)
```

```
// Get chosen Incident ID and status
```

```
$Edit_incident_ID = $_GET["Incident_ID"];
```

```
$Status = $_GET["Status"];
```



Report	Vehicle type	Vehicle colour	Delete	Edit
0mph in a 30 limit	Toyota Prius	Silver	Delete	Edit
Double parked	Ferrari 458	Red	Delete	Edit
0mph on motorway	Vauxhall Astra	Silver	Delete	Edit
at a red light - travelling 25mph	Honda Civic	Green	Delete	Edit
ing a seatbelt on the M1	Vauxhall Astra	Silver	Delete	Edit

4-6. How it works (r_ins_edit.php) - Edit

r_ins_edit.php

```
// find other values using the Incident ID
```

```
$Select_query = "SELECT * FROM Incident NATURAL LEFT JOIN Vehicle NATURAL LEFT JOIN People  
NATURAL LEFT JOIN Offence WHERE Incident_ID = '$Edit_incident_ID'";
```

```
// get previous vehicle status
```

```
$Ex_vehicle_ID = $row['Vehicle_ID'];  
if ($Ex_vehicle_ID == "") { $V_status = "unknown_vehicle";  
} else {  
    $V_status = "existing_vehicle";  
    $Ex_v_licence = $row['Vehicle_licence'];  
}
```

```
// get previous people status
```

```
$Ex_people_ID = $row['People_ID'];  
if ($Ex_people_ID == "") {  
    $P_status = "unknown_person";  
} else {  
    $P_status = "existing_person";  
    $Ex_p_licence = $row['People_licence'];  
}
```

```
// get other previous information
```

```
$Incident_date = $row['Incident_date'];  
$Incident_report = $row['Incident_report'];  
$Offence_ID = $row['Offence_ID'];  
$Offence_description = $row['Offence_description'];
```

4-6. How it works (r_ins_edit.php) - Edit

The edit form mechanism is the same as the people page.
There will be previous values with radio buttons selected, and users can edit them.
(All queries the same as insert have been omitted.)

```
// existing person
// existing vehicle
// Update incident with chosen people ID and vehicle ID
$sql = "UPDATE Incident SET Vehicle_ID = '$Ex_vehicle_ID', People_ID = '$Ex_people_ID',
      Incident_date = '$Incident_date', Incident_report = '$Incident_report',
      Offence_ID = '$Offence_ID' WHERE Incident_ID = '$Edit_incident_ID'";

// new vehicle
// Check if the same vehicle licence number is already in the database
// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);
    // Insert into Vehicle
    // Get the inserted vehicle ID
    // Update Incident
    $sql = "UPDATE Incident SET Vehicle_ID = '$Vehicle_ID', People_ID = '$Ex_people_ID',
          Incident_date = '$Incident_date', Incident_report = '$Incident_report',
          Offence_ID = '$Offence_ID' WHERE Incident_ID = '$Edit_incident_ID'";

    mysqli_commit($conn);

} Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Edit

```
// existing person
// unknown vehicle
// Update incident with chosen people ID
$sql = "UPDATE Incident SET Vehicle_ID = NULL, People_ID = '$Ex_people_ID',
    Incident_date = '$Incident_date', Incident_report = '$Incident_report',
    Offence_ID = '$Offence_ID' WHERE Incident_ID = '$Edit_incident_ID'";

// new person
// existing vehicle
// check if the People_licence is already in the database

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);
    // Insert into People
    // Get the inserted People ID
    // Update Incident
    $sql = "UPDATE Incident SET Vehicle_ID = '$Ex_vehicle_ID', People_ID = '$People_ID',
        Incident_date = '$Incident_date', Incident_report = '$Incident_report',
        Offence_ID = '$Offence_ID' WHERE Incident_ID = '$Edit_incident_ID'";

    mysqli_commit($conn); } Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Edit

```
// new person
// new vehicle
// Check if the People_licence is already in the database
// Check if the same vehicle licence number is already in the database

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);
    // Insert into People
    // Get the inserted People ID
    // Insert into Vehicle
    // Get the inserted Vehicle ID
    // Update Incident
    $sql = "UPDATE Incident SET Vehicle_ID = '$Vehicle_ID', People_ID = '$People_ID',
        Incident_date = '$Incident_date', Incident_report = '$Incident_report',
        Offence_ID = '$Offence_ID' WHERE Incident_ID = '$Edit_incident_ID'";

    mysqli_commit($conn); } Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Edit

```
// new person
// unknown vehicle
// check if the People_licence is already in the database

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);

    // Insert into People
    // Get the inserted People ID
    // Update Incident
    $sql = "UPDATE Incident SET Vehicle_ID = NULL,
        People_ID = '$People_ID', Incident_date = '$Incident_date',
        Incident_report = '$Incident_report', Offence_ID = '$Offence_ID'
        WHERE Incident_ID = '$Edit_incident_ID'";

    mysqli_commit($conn); } Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Edit

```
// unknown person
// existing vehicle
// Update Incident
$sql = "UPDATE Incident SET Vehicle_ID = '$Ex_vehicle_ID', People_ID = NULL,
    Incident_date = '$Incident_date', Incident_report = '$Incident_report',
    Offence_ID = '$Offence_ID' WHERE Incident_ID = '$Edit_incident_ID'";

// new vehicle
// Check if the same vehicle licence number is already in the database

// If not, use transaction to insert data into tables
try { mysqli_autocommit($conn, false);

    // Insert into Vehicle
    // Get the inserted Vehicle ID
    // Update Incident
    $sql = "UPDATE Incident SET Vehicle_ID = '$Vehicle_ID', People_ID = NULL,
        Incident_date = '$Incident_date', Incident_report = '$Incident_report',
        Offence_ID = '$Offence_ID' WHERE Incident_ID = '$Edit_incident_ID'";

    mysqli_commit($conn); } Catch () {...}
```

4-6. How it works (r_ins_edit.php) - Edit

```
// unknown person
// unknown vehicle
// Update Incident
$sql = "UPDATE Incident SET Vehicle_ID = NULL, People_ID = NULL,
    Incident_date = '$Incident_date', Incident_report = '$Incident_report',
    Offence_ID = '$Offence_ID' WHERE Incident_ID = '$Edit_incident_ID'";
```

4-7. How it works (offence.php)

Home

People

Vehicle

Report

Offence

Fines

Manage account

List of Offence

Warning: Any kinds of modifications to the offence type record must be made in accordance with the law. Also, any related fine or report records will be affected.

Max Fine: To

Max Point: To

Offence description ▾

description

Max Fine

Max Points

Speeding 33

1000

3

Delete

Edit

Speeding on a motorway

2500

6

Delete

Edit

Seat belt offence

500

0

Delete

Edit

Illegal parking

500

0

Delete

Edit

Drink driving

10000

11

Delete

Edit

Driving without a licence

10000

0

Delete

Edit

Traffic light offences

1000

3

Delete

Edit

Cycling on pavement

500

0

Delete

Edit

1

2

Next

\$O_category

\$O_search

\$min, \$max

\$p_min, \$p_max

href off_ins_edit.php

href off_delete.php

off_ins_edit.php

Search result table

Button onclick = script function page_move(); It submits the form again with different page numbers

4-7. How it works (offence.php)

```
// Select query
$sql_2 = "SELECT * FROM Offence
        WHERE " . $O_category . " LIKE \"%\" . $O_search . "%\" AND
        Offence_maxFine BETWEEN '$Min' AND '$Max'
        AND Offence_maxPoints BETWEEN '$P_min' AND '$P_max'
        ORDER BY Offence_ID ASC LIMIT $start_from, $per_page_record;";

// if Max or P_Max is not specified, then it will be set the maximum float value
if ($_POST['max'] != '' && $_POST['max'] != null) {
    $Max = $_POST['max'];
} else {
    // $Max = PHP_FLOAT_MAX; if PHP 7.2+
    $Max = 1.7976931348623E+308;
}

if ($_POST['p_max'] != '' && $_POST['p_max'] != null) {
    $P_max = $_POST['p_max'];
} else {
    // $P_max = PHP_FLOAT_MAX; if PHP 7.2+
    $P_max = 1.7976931348623E+308;
}
```

4-7. How it works (off_delete.php)

offence.php

```
function confirmDelete(ID)
window.location.href = "off_delete.php?Offence_ID=".concat(ID)
```

GET method, each button contains each record's Offence_ID

```
<td><button onclick='confirmDelete("$.row["Offence_ID"].")'>
Delete</button></td>
```

off_delete.php

```
$Offence_ID=$_REQUEST['Offence_ID'];
$sql = "DELETE FROM Offence WHERE Offence_ID=".$Offence_ID."";
```



A red arrow originates from the 'Delete' button in the first row of the table, points to the `Offence_ID` parameter in the SQL query, and then points to the `Offence_ID` parameter in the `confirmDelete` function call in the PHP code.

Max Points		
3	Delete	Edit
6	Delete	Edit
0	Delete	Edit
0	Delete	Edit
11	Delete	Edit
0	Delete	Edit
3	Delete	Edit
0	Delete	Edit

4-7. How it works (off_ins_edit.php) - Insert



DIS Police DB System

[Admin] Hello, haskins.

[Change password](#)

[Log out](#)

Home

People

Vehicle

Report

Offence

Fines

Manage
account

Insert New Offence

Description

← \$Offence_description

Max fine

← \$Offence_maxFine

Max points

← \$Offence_maxPoints

// check if the offence_description is already in the database

```
$Select_query = "SELECT * FROM Offence WHERE Offence_description = '$Offence_description'";
```

// If not, insert into Offence

```
$sql = "INSERT INTO Offence (Offence_description,Offence_maxFine,Offence_maxPoints)  
VALUES ('$Offence_description','$Offence_maxFine','$Offence_maxPoints')";
```

4-7. How it works (off_ins_edit.php) - Edit

offence.php

```
function Edit(ID)
window.location.href = "off_ins_edit.php?Offence_ID=".concat(ID).
concat("&&Status=1")
```

GET method, send selected ID and status=1

off_ins_edit.php

```
if (isset($_GET["Offence_ID"]) && $_GET["Status"] == 1)
```

```
// Get chosen Offence ID and status
```

```
$Edit_Offence_ID = $_GET["Offence_ID"];
```

```
$Status = $_GET["Status"];
```

```
// Get other previous input values
```

```
$Select_query = "SELECT * FROM Offence WHERE
                  Offence_ID = '$Edit_Offence_ID'";
```


```
$Offence_description = $row['Offence_description'];
```

```
$Offence_maxFine = $row['Offence_maxFine'];
```

```
$Offence_maxPoints = $row['Offence_maxPoints'];
```

```
// Update Offence with new input values
```

```
$sql = "UPDATE Offence SET Offence_description = '$Offence_description', Offence_maxFine = '$Offence_maxFine',
Offence_maxPoints = '$Offence_maxPoints' WHERE Offence_ID = '$Edit_Offence_ID'";
```



Report	Vehicle type	Vehicle colour		
0mph in a 30 limit	Toyota Prius	Silver	Delete	Edit
Double parked	Ferrari 458	Red	Delete	Edit
0mph on motorway	Vauxhall Astra	Silver	Delete	Edit
at a red light - travelling 25mph	Honda Civic	Green	Delete	Edit
ing a seatbelt on the M1	Vauxhall Astra	Silver	Delete	Edit

4-8. How it works (fines.php)

Home

People

Vehicle

Report

Offence

Fines

Search or Update Fine Record

From

To

Fine amount:

To

Fine Point:

To

Fine ID

▼

Enter search keyword or just press search button

Q

new

Fine ID	Fine amount	Fine points	Personal licence	Vehicle licence	Incident ID	Incident Date	Offence type	Max fine	Max points		
1	1000	3	SMITHR004JFS20TR	FD65WPQ	3	2017-09-17	Speeding 33	1000	3	Delete	Edit
2	50	0	SMITH222LE9FJ5DS	MY64PRE	2	2017-11-01	Illegal parking	500	0	Delete	Edit

\$F_category

\$F_search

1

Search result table

Button onclick = script function page_move();
It submits the form again with different page numbers

\$From, \$To

\$Min, \$Max

\$P_min, \$P_max

href f_ins_edit.php

href f_delete.php

f_ins_edit.php

4-8. How it works (fines.php)

```
// Select query
// Natural left join to search fined incident and involved person and vehicle together
$sql_2 = "SELECT * FROM Fines NATURAL LEFT JOIN Incident NATURAL LEFT JOIN People
        NATURAL LEFT JOIN Vehicle NATURAL LEFT JOIN Offence
        where " . $F_category . " LIKE \"%\" . $F_search . \"%\" // Partial search
        AND Incident_date BETWEEN '$From' AND '$To'
        AND Fine_amount BETWEEN '$Min' AND '$Max'
        AND Fine_points BETWEEN '$P_min' AND '$P_max'
        ORDER BY Fine_ID ASC LIMIT $start_from, $per_page_record;"; // Pagination

// if Max or P_max is not specified, then it will be set the maximum float value
if ($_POST['max'] != '' && $_POST['max'] != null) {
    $Max = $_POST['max'];
} else {
    // $Max = PHP_FLOAT_MAX; if PHP 7.2+
    $Max = 1.7976931348623E+308;
}

// $P_max -> same

// if To date is not specified, then it will be set today's date
if ($_POST['to'] != '' && $_POST['to'] != null) {
    $To = $_POST['to'];
} else {
    $To = date("Y-m-d");
}
```

4-8. How it works (f_delete.php)

fines.php


```
function confirmDelete(ID)
window.location.href = "f_delete.php?Fine_ID=".concat(ID)
```

GET method, each button contains each record's Fine_ID

```
<td><button onclick='confirmDelete("$.row["Fine_ID"].")'>
Delete</button></td>
```

f_delete.php

```
$Fine_ID=$_REQUEST['Fine_ID'];
$sql = "DELETE FROM Fines WHERE Fine_ID=".$Fine_ID."";
```



ence type	Max fine	Max points		
eeding 33	1000	3	Delete	Edit
jal parking	500	0	Delete	Edit

4-8. How it works (f_ins_edit.php) - Insert

These values will be inserted automatically

Insert New Fine Record

1. Search and Choose Report data

Offence type - All

From To

Incident ID Enter search keyword or just press search

Incident ID	Date	Personal licence	Vehicle licence	Offence type	Select
1	2017-12-01	SMITHR004JFS20TR	FP16KKE	Speeding	<input checked="" type="radio"/>
2	2017-11-01	SMITH222LE9FJ5DS	MY64PRE	Illegal parking	<input type="radio"/>
3	2017-09-17	SMITHR004JFS20TR	FD65WPQ	Speeding	<input type="radio"/>
4	2017-08-22	ALLEN88K23KLR9B3	FJ17AUG	Cycling on pavement	<input type="radio"/>
5	2017-10-17	SMITHR004JFS20TR	FD65WPQ	Seat belt offence	<input type="radio"/>

select();

2. Input basic info

Selected Incident ID ← **\$Incident_ID**

Max fine amount ← **\$Max_amount**

Fine amount ← **\$Fine_amount**

Max fine points ← **\$Max_points**

Fine points ← **\$Fine_points**

If $\$Fine_amount \leq \Max_amount and $\$Fine_points \leq \Max_points ,
(values can't be negative by input pattern)

```
$sql = "INSERT INTO Fines (Fine_amount, Fine_points, Incident_ID)
VALUES ('$Fine_amount', '$Fine_points', '$Incident_ID')";
```


4-8. How it works (f_ins_edit.php) - Edit

fines.php

```
function Edit(ID)
window.location.href = "f_ins_edit.php?Fine_ID=".concat(ID).
concat("&&Status=1")
```

GET method, send selected ID and status=1

f_ins_edit.php

```
if (isset($_GET["Fine_ID"]) && $_GET["Status"] == 1)
```

// Get chosen Fine ID and status

```
$Edit_fine_ID = $_GET["Fine_ID"];
$Status = $_GET["Status"];
```

// Get other previous input values

```
$Select_query = "SELECT * FROM Fines NATURAL LEFT JOIN Incident NATURAL LEFT JOIN Offence
                WHERE Fine_ID = '$Edit_fine_ID'";
```

```
$Fine_amount = trim($row['Fine_amount']);
```

```
$Fine_points = trim($row['Fine_points']);
```


```
$Max_amount = $row['Offence_maxFine'];
```

```
$Max_points = $row['Offence_maxPoints'];
```

```
$Incident_ID = $row['Incident_ID'];
```

// Update Fines with new input values

```
$sql = "UPDATE Fines SET Fine_amount = '$Fine_amount', Fine_points = '$Fine_points',
        Incident_ID = '$Incident_ID' WHERE Fine_ID = '$Edit_fine_ID'";
```



Offence type	Max fine	Max points	Delete	Edit
Bedding 30	1000	3	Delete	Edit
Legal parking	500	0	Delete	Edit

4-9. How it works (accounts.php)



DIS Police DB System

[Admin] Hello, haskins.

Change password

Log out

Home

People

Vehicle

Report

Search or Create Accounts

Enter account name or just press search button



new

href a_insert.php

href a_delete.php

Account name	
haskins	
Regan	Delete
Carter	Delete

`$A_search`

1

Button onclick = script function `page_move()`;
It submits the form again with different page numbers

Search result table

```
$sql = "SELECT * FROM Users where Users_name LIKE \"%" . $A_search . "%\"";
```

4-9. How it works (a_delete.php)

accounts.php


```
function confirmDelete(ID)
window.location.href = "a_delete.php?Users_ID=".concat(ID)
```

GET method, each button contains each record's Users_ID

```
<td><button onclick='confirmDelete("$.row["Users_ID"].")'>
Delete</button></td>
```

a_delete.php

```
$Users_ID=$_REQUEST['Users_ID'];
$sql = "DELETE FROM Users WHERE Users_ID=".$Users_ID."";
```



A diagram with a red arrow pointing from the 'Delete' button of the first row in the table to the 'a_delete.php' code block.

ence type	Max fine	Max points		
eeding 33	1000	3	Delete	Edit
jal parking	500	0	Delete	Edit

4-9. How it works (a_insert.php) - Insert

The image shows a web application interface for creating an account. On the left is a dark blue sidebar with white text links: Home, People, Vehicle, Report, Offence, and Fines. The main content area has a light blue header bar. Below it, the title 'Create an account' is followed by the instruction 'Please fill this form to create an account.' The form contains three input fields: 'Username' with placeholder text 'Enter Username using letters and numbers', 'Password' with placeholder text 'Enter password 6-10 characters without spaces', and 'Confirm Password' with placeholder text 'Please input your password again to confirm'. To the right of each input field is a red arrow pointing left to a PHP variable: '\$Users_name' for Username, '\$Users_password' for Password, and '\$Confirm_Users_password' for Confirm Password. At the bottom of the form are two buttons: a blue 'Submit' button and a black 'Cancel' button. A red arrow points upwards from the text block below to the 'Submit' button.

Home
People
Vehicle
Report
Offence
Fines

Create an account
Please fill this form to create an account.

Username
Enter Username using letters and numbers ← `$Users_name`

Password
Enter password 6-10 characters without spaces ← `$Users_password`

Confirm Password
Please input your password again to confirm ← `$Confirm_Users_password`

Submit Cancel

If `$Users_password` = `$Confirm_Users_password`,

```
$Ins_query = "INSERT INTO Users (Users_name, Users_password)
              VALUES ('$Users_name', '$Users_password')";
```

That's all!