

# **Reliable Response Notification Database**

Build 152

Date 2005-07-15 12:38:52

# 1. Overview

Other
-------


## 2. DataTypes

Constant Types		
Name	Domain	DataD equiv
tinyint		
smallint		
mediumint		
int		
bigint		
float		
double		
decimal		
date		
datetime		
time		
year		
tinytext		
mediumtext		
text		
longtext		
tinyblob		
mediumblob		
blob		
longblob		
enum('a', 'b')		
set('a', 'b')		
int2		int
bool		boolean
INTEGER		
BYTEA		
timestamp		timestamp


Variable Types			
Name	Size	Domain	DataD equiv
<b>float</b>	n/a	n/a	n/a
float(4,2)	4,2		
<b>double</b>	n/a	n/a	n/a
double(8,4)	8,4		
<b>decimal</b>	n/a	n/a	n/a
salary	9,2		
<b>timestamp</b>	n/a	n/a	n/a
yy	2		
yy-mm	4		
yy-mm-dd	6		
yyyy-mm-dd	8		
yy-mm-dd-hh-mm	10		
yy-mm-dd-hh-mm-ss	12		
yyyy-mm-dd-hh-mm-ss	14		
<b>char</b>	n/a	n/a	n/a
char	1		
bool	1		
bit	1		
<b>varchar</b>	n/a	n/a	n/a
varchar-255	255		
uuidvarchar	64		varchar
255varchar	255		varchar
largemessage	2048		BLOB
VARCHAR8000	8000		
VARCHAR80	80		
VARCHAR95	95		
VARCHAR1	1		
VARCHAR16	16		
VARCHAR120	120		

Variable Types			
Name	Size	Domain	DataD equiv
VARCHAR128	128		
VARCHAR40	40		
VARCHAR8	8		
<b>VARBINARY</b>	n/a	n/a	n/a
VARBINARY65535	65535		
<b>BIT</b>	n/a	n/a	n/a
BIT1	1		
<b>BINARY</b>	n/a	n/a	n/a
BINARY-1	-1		

### 3. ER Views

ER View	Description
	

## 4. Reliable ERD



## 1. member

<i>member</i>		
PK	uuid	uuidvarchar
N	type	int
A	firstname	255varchar
A	lastname	255varchar
A	email	255varchar
A	description	255varchar
A	cached	bool

**Used tables**

member

## 4.2. membergroup

<i>membergroup</i>		
PK	uuid	member(uuid)
N	membertype	int2
A	category	255varchar

**Used tables**

membergroup

## 4.3. authentication

<i>authentication</i>		
PK	member	member(uuid)
N	passphrase	255varchar
U	userinfo	255varchar
U	resetkey	uuidvarchar
A	resettime	timestamp

**Used tables**

authentication

## 4.4. authorizationinfo

<i>authorizationinfo</i>		
PK	member	member(uuid)
N	role	255varchar



**Used tables**

authorizationinfo

## 4.5. device

<i>device</i>		
PK	uuid	uuidvarchar
FK	type	devicetype(uuid)
FK	member	member(uuid)

**Used tables**

device

## 4.6. devicetype

<i>devicetype</i>		
PK	uuid	uuidvarchar
A	name	255varchar
N	classname	255varchar

**Used tables**

devicetype

## 4.7. userinformation

<i>userinformation</i>		
FK	member	member(uuid)
A	name	255varchar
A	value	255varchar

**Used tables**

userinformation

## 4.8. membership

<i>membership</i>		
PK	uuid	uuidvarchar
FK	child	member(uuid)
FK	parent	membergroup(uuid)
N	childorder	int
A	priority	int

**Used tables**

membership

## 4.9. escalationgroup

<i>escalationgroup</i>		
PK	membership	membership(uuid)
N	escalationtime	int2
N	numattempts	int2

**Used tables**

escalationgroup

## 4.10. notification

**Used tables**

notification

<i><b>notification</b></i>		
PK	uuid	uuidvarchar
FK	recipient	member(uuid)
A	time	timestamp
FK	confirmedby	member(uuid)
A	subject	255varchar
A	requiresconfirmation	bool
A	status	255varchar
FK	parent	notification(uuid)
A	owner	255varchar
A	senderclass	varchar-255
A	senderinfo1	varchar-255
A	senderinfo2	varchar-255
A	senderinfo3	varchar-255
A	senderinfo4	varchar-255
A	senderinfo5	varchar-255
A	senderinfo6	varchar-255
A	senderinfo7	varchar-255
A	senderinfo8	varchar-255
A	senderinfo9	varchar-255
A	senderinfo10	varchar-255

## 4.11. notificationoptions

<i><b>notificationoptions</b></i>		
FK	notification	notification(uuid)
N	optionname	255varchar

### Used tables

notificationoptions

## 4.12. devicesetting

<i><b>devicesetting</b></i>		
FK	device	device(uuid)
N	name	255varchar
A	value	255varchar
A	isrequired	char

**Used tables**

devicesetting

## 4.13. schedule

<i>schedule</i>		
PK	uuid	uuidvarchar
A	name	255varchar

**Used tables**

schedule

## 4.14. escalationlog

<i>escalationlog</i>		
FK	notification	notification(uuid)
FK	memberto	member(uuid)
FK	memberfrom	member(uuid)
A	passed	bool
A	time	timestamp

**Used tables**

escalationlog

## 4.15. qrtz\_blob\_triggers

<i>qrtz_blob_triggers</i>		
PK	trigger_name	qrtz_triggers(trigger_name)
PK	trigger_group	qrtz_triggers(trigger_group)
A	blob_data	BYTEA

**Used tables**

qrtz\_blob\_triggers

## 4.16. qrtz\_calendars

qrtz_calendars		
PK	calendar_name	VARCHAR80
N	calendar	BYTEA

**Used tables**

qrtz\_calendars

## 4.17. qrtz\_cron\_triggers

qrtz_cron_triggers		
PK	trigger_name	qrtz_triggers(trigger_name)
PK	trigger_group	qrtz_triggers(trigger_group)
N	cron_expression	VARCHAR80
A	time_zone_id	VARCHAR80

**Used tables**

qrtz\_cron\_triggers

## 4.18. qrtz\_fired\_triggers

**Used tables**

qrtz\_fired\_triggers

## 4.19. qrtz\_job\_details

<i>qrtz_fired_triggers</i>		
PK	entry_id	VARCHAR95
N	trigger_name	VARCHAR80
N	trigger_group	VARCHAR80
N	is_volatile	VARCHAR1
N	instance_name	VARCHAR80
N	fired_time	bigint
N	state	VARCHAR16
A	job_name	VARCHAR80
A	job_group	VARCHAR80
A	is_stateful	VARCHAR1
A	requests_recovery	VARCHAR1

<i>qrtz_job_details</i>		
PK	job_name	VARCHAR80
PK	job_group	VARCHAR80
A	description	VARCHAR120
N	job_class_name	VARCHAR128
N	is_durable	VARCHAR1
N	is_volatile	VARCHAR1
N	is_stateful	VARCHAR1
N	requests_recovery	VARCHAR1
A	job_data	BYTEA

#### Used tables

qrtz\_job\_details

## 4.20. qrtz\_job\_listeners

<i>qrtz_job_listeners</i>		
PK	job_name	qrtz_job_details(job_name)
PK	job_group	qrtz_job_details(job_group)
PK	job_listener	VARCHAR80

**Used tables**

qrtz\_job\_listeners

## 4.21. qrtz\_locks

<i>qrtz_locks</i>		
PK	lock_name	VARCHAR40

**Used tables**

qrtz\_locks

## 4.22. qrtz\_paused\_trigger\_grps

<i>qrtz_paused_trigger_grps</i>		
PK	trigger_group	VARCHAR80

**Used tables**

qrtz\_paused\_trigger\_grps

## 4.23. qrtz\_scheduler\_state

<i>qrtz_scheduler_state</i>		
PK	instance_name	VARCHAR80
N	last_checkin_time	bigint
N	checkin_interval	bigint
A	recoverer	VARCHAR80

**Used tables**

qrtz\_scheduler\_state

## 4.24. `qrtz_simple_triggers`

<i>qrtz_simple_triggers</i>		
PK	trigger_name	qrtz_triggers(trigger_name)
PK	trigger_group	qrtz_triggers(trigger_group)
N	repeat_count	bigint
N	repeat_interval	bigint
N	times_triggered	bigint

### Used tables

qrtz\_simple\_triggers

## 4.25. `qrtz_trigger_listeners`

<i>qrtz_trigger_listeners</i>		
PK	trigger_name	qrtz_triggers(trigger_name)
PK	trigger_group	qrtz_triggers(trigger_group)
PK	trigger_listener	VARCHAR80

### Used tables

qrtz\_trigger\_listeners

## 4.26. `qrtz_triggers`

### Used tables

qrtz\_triggers

## 4.27. `notificationmessages`



<i>qrtz_triggers</i>		
PK	trigger_name	VARCHAR80
PK	trigger_group	VARCHAR80
FK	job_name	qrtz_job_details(job_name)
FK	job_group	qrtz_job_details(job_group)
N	is_volatile	VARCHAR1
A	description	VARCHAR120
A	next_fire_time	bigint
A	prev_fire_time	bigint
N	trigger_state	VARCHAR16
N	trigger_type	VARCHAR8
N	start_time	bigint
A	end_time	bigint
A	calendar_name	VARCHAR80
A	misfire_instr	smallint

<i>notificationmessages</i>		
FK	notification	notification(uuid)
A	message	BYTEA
A	addedby	255varchar
A	addledon	timestamp

#### Used tables

notificationmessages

## 4.28. notificationprovider

<i>notificationprovider</i>		
PK	uuid	uuidvarchar
FK	notification	notification(uuid)
A	classname	varchar-255
A	status	255varchar

**Used tables**

notificationprovider

## 4.29. notificationproviderinfo

<i>notificationproviderinfo</i>		
FK	provider	notificationprovider(uuid)
A	name	varchar-255
A	value	varchar-255

**Used tables**

notificationproviderinfo

## 4.30. priority

<i>priority</i>		
PK	uuid	uuidvarchar
FK	member	member(uuid)
A	prioritynumber	int
FK	device	device(uuid)

**Used tables**

priority

## 4.31. priorityschedule

<i>priorityschedule</i>		
PK	uuid	uuidvarchar
FK	priority	priority(uuid)
FK	schedule	schedule(uuid)

Used tables

priorityschedule

4.32. uuid

uuid		
A	generic	int
A	member	int
A	notification	int
A	device	int

Used tables

uuid

## 5. Reliable Response Notification Database

This is the main database for Reliable Response Notification

### 1. authentication

This stores a mapping between the user's login name, the actual user object, and the hashed passphrase

Field Summary		
Name	Type	Description
passphrase	255varchar	
<b>member</b>	member(uuid)	
userinfo	255varchar	
resetkey	uuidvarchar	
resettime	timestamp	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
passphrase	varchar(255)	-		-	x	-	-	-	-	-	-	-	-
<b>member</b>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
userinfo	varchar(255)	-		x	-	-	-	-	-	-	-	-	-
resetkey	varchar(64)	-		x	-	-	-	-	-	-	-	-	-
resettime	timestamp	-		-	-	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
member	member(uuid)	NO ACTION	CASCADE

## 5.2. authorizationinfo

This stores which groups a user is in.

Field Summary		
Name	Type	Description
<i>member</i>	member(uuid)	
role	255varchar	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Autolnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>member</i>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
role	varchar(255)	-		-	x	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
member	member(uuid)	NO ACTION	CASCADE

## 5.3. device

### See Also

devicesetting  
priority

Field Summary		
Name	Type	Description
<i>type</i>	devicetype(uuid)	

<i>member</i>	member(uuid)	
<b>uuid</b>	uuidvarchar	

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>type</i>	varchar(64)	-		-	x	-	-	-	-	-	-	-	-
<i>member</i>	varchar(64)	-		-	-	-	-	-	-	-	x	-	-
<b>uuid</b>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-

## Foreign Keys

Name	Import	On Update	On Delete
<i>type</i>	devicetype(uuid)	NO ACTION	CASCADE
<i>member</i>	member(uuid)	NO ACTION	CASCADE

## 5.4. devicesetting

### Field Summary

Name	Type	Description
<i>device</i>	device(uuid)	
<i>name</i>	255varchar	
<i>value</i>	255varchar	
<i>isrequired</i>	char	

### Sql Summary

Name	Type	PrK	Def	Unq	Not	Aut	Bin	UnS	Zero	MUn	Idx1	Udx	Idx1
------	------	-----	-----	-----	-----	-----	-----	-----	------	-----	------	-----	------

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Autoincr	Bin	Unsigned	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>device</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
name	varchar(255)	-		-	x	-	-	-	-	-	-	-	-
value	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
isrequired	char(1)	-		-	-	-	-	-	-	-	-	-	-

## Foreign Keys

Name	Import	On Update	On Delete
device	device(uuid)	NO ACTION	CASCADE

## 5.5. devicetype

See Also  
device

## Field Summary

Name	Type	Description
<b>uuid</b>	uuidvarchar	
name	255varchar	
classname	255varchar	

## Sql Summary

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Autoincr	Bin	Unsigned	Zero Fill	MUnq	Idx1	Udx1	Idx1
uuid	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
name	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
classname	varchar(255)	-		-	x	-	-	-	-	-	-	-	-

## 5.6. errorlog

Field Summary		
Name	Type	Description
uuid	uuidvarchar	
errorlevel	int	
message	255varchar	
time	date	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Autoincr	Bin	Unsigned	Zero Fill	MUnq	Idx1	Udx1	Idx1
uuid	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
errorlevel	int	-		-	-	-	-	-	-	-	-	-	-
message	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
time	date	-		-	-	-	-	-	-	-	-	-	-



## 5.7. escalationgroup

Field Summary		
Name	Type	Description
<b>membership</b>	membership(uuid)	
escalationtime	int2	
numattempts	int2	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<b>membership</b>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
escalationtime	int2	-	15	-	x	-	-	-	-	-	-	-	-
numattempts	int2	-		-	x	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
membership	membership(uuid)	NO ACTION	CASCADE

## 5.8. escalationlog

Field Summary		
Name	Type	Description

<i>notification</i>	notification(uuid)	
<i>memberto</i>	member(uuid)	
<i>memberfrom</i>	member(uuid)	
<i>passed</i>	bool	
<i>time</i>	timestamp	

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
<i>notification</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
<i>memberto</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
<i>memberfrom</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
<i>passed</i>	bool	-		-	-	-	-	-	-	-	-	-	-
<i>time</i>	timestamp	-		-	-	-	-	-	-	-	-	-	-

## Foreign Keys

Name	Import	On Update	On Delete
notification	notification(uuid)	NO ACTION	CASCADE
memberto	member(uuid)	NO ACTION	CASCADE
memberfrom	member(uuid)	NO ACTION	CASCADE

## 5.9. loginlog

## Field Summary

Name	Type	Description
uuid	uuidvarchar	
time	date	
succeeded	char	
username	255varchar	
originatingaddress	varchar-255	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
uuid	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
time	date	-		-	x	-	-	-	-	-	-	-	-
succeeded	char(1)	-		-	x	-	-	-	-	-	-	-	-
username	varchar(255)	-		-	x	-	-	-	-	-	-	-	-
originatingaddress	varchar(255)	-		-	-	-	-	-	-	-	-	-	-

## 5.10. member

This is the basic user management table. It stored the UUID for every user and group in the system.

Used by `net.reliableresponse.notification.usermgmt.*`, `net.reliableresponse.notification.broker.UserMgmtBroker` and `net.reliableresponse.notification.broker.GroupMgmtBroker`

### See Also

- authentication
- authorizationinfo
- device
- escalationlog
- membergroup
- membership

notification  
priority  
userinformation

## Field Summary

Name	Type	Description
uuid	uuidvarchar	
type	int	
firstname	255varchar	
lastname	255varchar	
email	255varchar	
description	255varchar	
cached	bool	

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Autoincr	Bin	Unsigned	Zero Fill	MUnq	Idx1	Udx1	Idx1
uuid	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
type	int	-		-	x	-	-	-	-	-	-	-	-
firstname	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
lastname	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
email	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
description	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
cached	bool	-	'N'	-	-	-	-	-	-	-	-	-	-

## 5.11. membergroup

This is the group table. I don't call it "group" because this is a reserved word in some databases (MySQL for example).

**See Also**

membership

Field Summary		
Name	Type	Description
<i>uuid</i>	member(uuid)	
membertype	int2	
category	255varchar	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Autolncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>uuid</i>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
membertype	int2	-		-	x	-	-	-	-	-	-	-	-
category	varchar(255)	-		-	-	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
uuid	member(uuid)	NO ACTION	CASCADE

## 5.12. membership

**See Also**

escalationgroup

Field Summary		
Name	Type	Description

<i>child</i>	member(uuid)	
<i>parent</i>	membergroup(uuid)	
<b>uuid</b>	uuidvarchar	
childorder	int	
priority	int	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Autoincr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>child</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
<i>parent</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
<b>uuid</b>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
childorder	int	-		-	x	-	-	-	-	-	-	-	-
priority	int	-		-	-	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
child	member(uuid)	NO ACTION	CASCADE
parent	membergroup(uuid)	NO ACTION	CASCADE

## 5.13. notification

### See Also

[escalationlog](#)  
[notification](#)  
[notificationmessages](#)  
[notificationoptions](#)  
[notificationprovider](#)

Field Summary		
Name	Type	Description
<b>uuid</b>	uuidvarchar	
<i>recipient</i>	member(uuid)	
time	timestamp	
<i>confirmedby</i>	member(uuid)	
subject	255varchar	
requiresconfirmation	bool	
status	255varchar	
<i>parent</i>	notification(uuid)	
owner	255varchar	
senderclass	varchar-255	
senderinfo1	varchar-255	
senderinfo2	varchar-255	
senderinfo3	varchar-255	
senderinfo4	varchar-255	
senderinfo5	varchar-255	
senderinfo6	varchar-255	
senderinfo7	varchar-255	
senderinfo8	varchar-255	
senderinfo9	varchar-255	
senderinfo10	varchar-255	

Sql Summary														
Name	Type	PrKey	Def	Unq	Not N	Autoincr	Bin	Unsigned	Zero Fill	MUnq	Idx1	Udx1	Idx1	
<b>uuid</b>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-	-
<i>recipient</i>	varchar(64)	-		-	x	-	-	-	-	-	-	-	-	-
time	timestamp	-		-	-	-	-	-	-	-	-	-	-	-

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Autoincr	Bin	Unsigned	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>confirmedby</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
subject	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
requiresconfirmation	bool	-		-	-	-	-	-	-	-	-	-	-
status	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
<i>parent</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
owner	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderclass	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo1	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo2	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo3	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo4	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo5	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo6	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo7	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo8	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo9	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
senderinfo10	varchar(255)	-		-	-	-	-	-	-	-	-	-	-

## Foreign Keys

Name	Import	On Update	On Delete
recipient	member(uuid)	NO ACTION	CASCADE
confirmedby	member(uuid)	NO ACTION	CASCADE
parent	notification(uuid)	NO ACTION	CASCADE



## 5.14. notificationmessages

Field Summary		
Name	Type	Description
<i>notification</i>	notification(uuid)	
message	BYTEA	
addedby	255varchar	
addedon	timestamp	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
<i>notification</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
message	BYTEA	-		-	-	-	-	-	-	-	-	-	-
addedby	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
addedon	timestamp	-		-	-	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
notification	notification(uuid)	NO ACTION	CASCADE

## 5.15. notificationoptions

Field Summary		
Name	Type	Description
<i>notification</i>	notification(uuid)	
optionname	255varchar	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>notification</i>	varchar(64)	-		-	x	-	-	-	-	-	-	-	-
optionname	varchar(255)	-		-	x	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
notification	notification(uuid)	CASCADE	CASCADE

## 5.16. notificationprovider

### See Also

[notificationproviderinfo](#)

Field Summary		
Name	Type	Description
<i>notification</i>	notification(uuid)	

<b>uuid</b>	uuidvarchar	
classname	varchar-255	
status	255varchar	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Autolnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>notification</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
<b>uuid</b>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
classname	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
status	varchar(255)	-		-	-	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
notification	notification(uuid)	NO ACTION	CASCADE

## 5.17. notificationproviderinfo

Field Summary		
Name	Type	Description
<i>provider</i>	notificationprovider(uuid)	
name	varchar-255	
value	varchar-255	

Sql Summary													
Name	Type	PrK	Def	Unq	Not	Aut	Bin	UnS	Zero	MUn	Idx1	Udx	Idx1

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>provider</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
name	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
value	varchar(255)	-		-	-	-	-	-	-	-	-	-	-

## Foreign Keys

Name	Import	On Update	On Delete
provider	notificationprovider(uuid)	NO ACTION	CASCADE

## 5.18. priority

### See Also

priorityschedule

## Field Summary

Name	Type	Description
<b>uuid</b>	uuidvarchar	
<i>member</i>	member(uuid)	
prioritynumber	int	
<i>device</i>	device(uuid)	

## Sql Summary

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<b>uuid</b>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
<i>member</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
prioritynumber	int	-		-	-	-	-	-	-	-	-	-	-
<i>device</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-

**Foreign Keys**

Name	Import	On Update	On Delete
member	member(uuid)	NO ACTION	CASCADE
device	device(uuid)	NO ACTION	CASCADE

**5.19. priorityschedule****Field Summary**

Name	Type	Description
<i>priority</i>	priority(uuid)	
<i>schedule</i>	schedule(uuid)	
<b>uuid</b>	uuidvarchar	

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
------	------	-------	-----	-----	-------	-----------	-----	--------	-----------	------	------	------	------

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>priority</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
<i>schedule</i>	varchar(64)	-		-	-	-	-	-	-	-	-	-	-
<b>uuid</b>	varchar(64)	x		-	-	-	-	-	-	-	-	-	-

**Foreign Keys**

Name	Import	On Update	On Delete
priority	priority(uuid)	NO ACTION	CASCADE
schedule	schedule(uuid)	NO ACTION	CASCADE

**5.20. qrtz\_blob\_triggers****Field Summary**

Name	Type	Description
<b><i>trigger_name</i></b>	qrtz_triggers(trigger_name)	
<b><i>trigger_group</i></b>	qrtz_triggers(trigger_group)	
blob_data	BYTEA	

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
------	------	-------	-----	-----	-------	-----------	-----	--------	-----------	------	------	------	------

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>trigger_name</i>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<i>trigger_group</i>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
blob_data	BYTEA	-		-	-	-	-	-	-	-	-	-	-

**Foreign Keys**

Name	Import	On Update	On Delete
trigger_name	qrtz_triggers(trigger_name)	NO ACTION	NO ACTION
trigger_group	qrtz_triggers(trigger_group)	NO ACTION	NO ACTION

**5.21. qrtz\_calendars****Field Summary**

Name	Type	Description
calendar_name	VARCHAR80	
calendar	BYTEA	

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<b>calendar_name</b>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
calendar	BYTEA	-		-	x	-	-	-	-	-	-	-	-

**5.22. qrtz\_cron\_triggers****Field Summary**

Name	Type	Description
<b>trigger_name</b>	qrtz_triggers(trigger_name)	
<b>trigger_group</b>	qrtz_triggers(trigger_group)	
cron_expression	VARCHAR80	
time_zone_id	VARCHAR80	

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<b>trigger_name</b>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<b>trigger_group</b>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
cron_expression	varchar(80)	-		-	x	-	-	-	-	-	-	-	-
time_zone_id	varchar(80)	-		-	-	-	-	-	-	-	-	-	-



## Foreign Keys

Name	Import	On Update	On Delete
trigger_name	qrtz_triggers(trigger_name)	NO ACTION	NO ACTION
trigger_group	qrtz_triggers(trigger_group)	NO ACTION	NO ACTION

## 5.23. qrtz\_fired\_triggers

### Field Summary

Name	Type	Description
entry_id	VARCHAR95	
trigger_name	VARCHAR80	
trigger_group	VARCHAR80	
is_volatile	VARCHAR1	
instance_name	VARCHAR80	
fired_time	bigint	
state	VARCHAR16	
job_name	VARCHAR80	
job_group	VARCHAR80	
is_stateful	VARCHAR1	
requests_recovery	VARCHAR1	

### Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
entry_id	varchar(95)	x		-	-	-	-	-	-	-	-	-	-

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
trigger_name	varchar(80)	-		-	x	-	-	-	-	-	-	-	-
trigger_group	varchar(80)	-		-	x	-	-	-	-	-	-	-	-
is_volatile	varchar(1)	-		-	x	-	-	-	-	-	-	-	-
instance_name	varchar(80)	-		-	x	-	-	-	-	-	-	-	-
fired_time	bigint	-		-	x	-	-	-	-	-	-	-	-
state	varchar(16)	-		-	x	-	-	-	-	-	-	-	-
job_name	varchar(80)	-		-	-	-	-	-	-	-	-	-	-
job_group	varchar(80)	-		-	-	-	-	-	-	-	-	-	-
is_stateful	varchar(1)	-		-	-	-	-	-	-	-	-	-	-
requests_recovery	varchar(1)	-		-	-	-	-	-	-	-	-	-	-

## 5.24. qrtz\_job\_details

### See Also

qrtz\_job\_listeners

qrtz\_triggers

Field Summary		
Name	Type	Description
job_name	VARCHAR80	
job_group	VARCHAR80	
description	VARCHAR120	
job_class_name	VARCHAR128	
is_durable	VARCHAR1	
is_volatile	VARCHAR1	
is_stateful	VARCHAR1	

requests_recovery	VARCHAR1	
job_data	BYTEA	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
job_name	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
job_group	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
description	varchar(120)	-		-	-	-	-	-	-	-	-	-	-
job_class_name	varchar(128)	-		-	x	-	-	-	-	-	-	-	-
is_durable	varchar(1)	-		-	x	-	-	-	-	-	-	-	-
is_volatile	varchar(1)	-		-	x	-	-	-	-	-	-	-	-
is_stateful	varchar(1)	-		-	x	-	-	-	-	-	-	-	-
requests_recovery	varchar(1)	-		-	x	-	-	-	-	-	-	-	-
job_data	BYTEA	-		-	-	-	-	-	-	-	-	-	-

## 5.25. qrtz\_job\_listeners

Field Summary		
Name	Type	Description
job_name	qrtz_job_details(job_name)	
job_group	qrtz_job_details(job_group)	
job_listener	VARCHAR80	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
<i>job_name</i>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<i>job_group</i>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<i>job_listener</i>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-

Foreign Keys			
Name	Import	On Update	On Delete
job_name	qrtz_job_details(job_name)	NO ACTION	NO ACTION
job_group	qrtz_job_details(job_group)	NO ACTION	NO ACTION

## 5.26. qrtz\_locks

Field Summary		
Name	Type	Description
lock_name	VARCHAR40	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
lock_name	varchar(40)	x		-	-	-	-	-	-	-	-	-	-

## 5.27. qrtz\_paused\_trigger\_grps

Field Summary		
Name	Type	Description
trigger_group	VARCHAR80	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
trigger_group	varchar(80)	x		-	-	-	-	-	-	-	-	-	-

## 5.28. qrtz\_scheduler\_state

Field Summary		
Name	Type	Description
instance_name	VARCHAR80	
last_checkin_time	bigint	
checkin_interval	bigint	
recoverer	VARCHAR80	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut olnc	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
<b>instance_name</b>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
last_checkin_time	bigint	-		-	x	-	-	-	-	-	-	-	-
checkin_interval	bigint	-		-	x	-	-	-	-	-	-	-	-
recoverer	varchar(80)	-		-	-	-	-	-	-	-	-	-	-

**5.29. qrtz\_simple\_triggers****Field Summary**

Name	Type	Description
<b>trigger_name</b>	qrtz_triggers(trigger_name)	
<b>trigger_group</b>	qrtz_triggers(trigger_group)	
repeat_count	bigint	
repeat_interval	bigint	
times_triggered	bigint	

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnS ign	Zero Fill	MUn q	Idx1	Udx 1	Idx1
<b>trigger_name</b>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<b>trigger_group</b>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
repeat_count	bigint	-		-	x	-	-	-	-	-	-	-	-
repeat_interval	bigint	-		-	x	-	-	-	-	-	-	-	-

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
times_triggered	bigint	-		-	x	-	-	-	-	-	-	-	-

**Foreign Keys**

Name	Import	On Update	On Delete
trigger_name	qrtz_triggers(trigger_name)	NO ACTION	NO ACTION
trigger_group	qrtz_triggers(trigger_group)	NO ACTION	NO ACTION

**5.30. qrtz\_trigger\_listeners****Field Summary**

Name	Type	Description
<i>trigger_name</i>	qrtz_triggers(trigger_name)	
<i>trigger_group</i>	qrtz_triggers(trigger_group)	
trigger_listener	VARCHAR80	

**Sql Summary**

Name	Type	PrKey	Def	Unq	Not N	Aut olnc	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
------	------	-------	-----	-----	-------	----------	-----	--------	-----------	------	------	------	------

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Aut olnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>trigger_name</i>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<i>trigger_group</i>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<i>trigger_listener</i>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-

## Foreign Keys

Name	Import	On Update	On Delete
trigger_name	qrtz_triggers(trigger_name)	NO ACTION	NO ACTION
trigger_group	qrtz_triggers(trigger_group)	NO ACTION	NO ACTION

## 5.31. qrtz\_triggers

### See Also

[qrtz\\_blob\\_triggers](#)  
[qrtz\\_cron\\_triggers](#)  
[qrtz\\_simple\\_triggers](#)  
[qrtz\\_trigger\\_listeners](#)

## Field Summary

Name	Type	Description
<i>trigger_name</i>	VARCHAR80	
<i>trigger_group</i>	VARCHAR80	
<i>job_name</i>	qrtz_job_details(job_name)	
<i>job_group</i>	qrtz_job_details(job_group)	



is_volatile	VARCHAR1	
description	VARCHAR120	
next_fire_time	bigint	
prev_fire_time	bigint	
trigger_state	VARCHAR16	
trigger_type	VARCHAR8	
start_time	bigint	
end_time	bigint	
calendar_name	VARCHAR80	
misfire_instr	smallint	

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Autolncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<b>trigger_name</b>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<b>trigger_group</b>	varchar(80)	x		-	-	-	-	-	-	-	-	-	-
<i>job_name</i>	varchar(80)	-		-	x	-	-	-	-	-	-	-	-
<i>job_group</i>	varchar(80)	-		-	x	-	-	-	-	-	-	-	-
is_volatile	varchar(1)	-		-	x	-	-	-	-	-	-	-	-
description	varchar(120)	-		-	-	-	-	-	-	-	-	-	-
next_fire_time	bigint	-		-	-	-	-	-	-	-	-	-	-
prev_fire_time	bigint	-		-	-	-	-	-	-	-	-	-	-
trigger_state	varchar(16)	-		-	x	-	-	-	-	-	-	-	-
trigger_type	varchar(8)	-		-	x	-	-	-	-	-	-	-	-
start_time	bigint	-		-	x	-	-	-	-	-	-	-	-
end_time	bigint	-		-	-	-	-	-	-	-	-	-	-
calendar_name	varchar(80)	-		-	-	-	-	-	-	-	-	-	-
misfire_instr	smallint	-		-	-	-	-	-	-	-	-	-	-

## Foreign Keys

Name	Import	On Update	On Delete
job_name	qrtz_job_details(job_name)	NO ACTION	NO ACTION
job_group	qrtz_job_details(job_group)	NO ACTION	NO ACTION

## 5.32. schedule

### See Also

priorityschedule

Field Summary		
Name	Type	Description
uuid	uuidvarchar	
name	255varchar	This maps to the type of schedule entry

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Autolnc r	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
uuid	varchar(64)	x		-	-	-	-	-	-	-	-	-	-
name	varchar(255)	-		-	-	-	-	-	-	-	-	-	-

## 5.33. userinformation

Field Summary		
Name	Type	Description
member	member(uuid)	
name	255varchar	
value	255varchar	

## Sql Summary

Name	Type	PrKey	Def	Unq	Not N	Autolncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
<i>member</i>	varchar(64)	-		-	x	-	-	-	-	-	-	-	-
name	varchar(255)	-		-	-	-	-	-	-	-	-	-	-
value	varchar(255)	-		-	-	-	-	-	-	-	-	-	-

## Foreign Keys

Name	Import	On Update	On Delete
member	member(uuid)	NO ACTION	CASCADE

## 5.34. uuid\_seq

### Attribs

Increment	1
Min value	1
Max value	9999999
Start	1
Cache	
Cycle	-
Order	-

## 5.35. member\_uuid\_seq

Attribs	
Increment	1
Min value	1
Max value	9999999
Start	1
Cache	
Cycle	-
Order	-

## 5.36. notification\_uuid\_seq

Attribs	
Increment	1
Min value	1
Max value	9999999
Start	1
Cache	
Cycle	-
Order	-

## 5.37. device\_uuid\_seq

Attribs	
Increment	1
Min value	1
Max value	9999999
Start	1
Cache	
Cycle	-
Order	-

## 5.38. uuid

This is used for MySQL only, since MySQL doesn't really support sequences.

Field Summary		
Name	Type	Description
generic	int	
member	int	
notification	int	
device	int	

Sql Summary													
Name	Type	PrKey	Def	Unq	Not N	Aut oIncr	Bin	UnSign	Zero Fill	MUnq	Idx1	Udx1	Idx1
generic	int	-	1	-	-	-	-	-	-	-	-	-	-
member	int	-	1	-	-	-	-	-	-	-	-	-	-
notification	int	-	1	-	-	-	-	-	-	-	-	-	-
device	int	-	1	-	-	-	-	-	-	-	-	-	-