```
[root@ip-172-31-8-63 ~]# docker network ls
NETWORK ID     NAME      DRIVER    SCOPE
a047b5308b31   bridge    bridge    local
7c214f275ac9   host      host      local
90ba46fea43a   none      null      local
[root@ip-172-31-8-63 ~]# docker run -itd --name k1 alpine
docker: Error response from daemon: Conflict. The container name "/k1" is already in use by container "f9e859a7878c22098ccad92f1c92f7e653e816d029685769080313 7bd3362d25". You have to remove (or rename) that cont
ainer to be able to reuse that name.
See 'docker run --help'.
[root@ip-172-31-8-63 ~]# docker run -itd --name k2 alpine
915aa3e8b2ed0086ac1044e9e0efcade91af60e86b7a146ccda1879822214 0ed
[root@ip-172-31-8-63 ~]# docker inspect k2
[
    {
        "Id": "915aa3e8b2ed0086ac1044e9e0efcade91af60e86b7a146ccda1879822214 0ed",
        "Created": "2026-10-18T08:13:19.796590691Z",
        "Path": "/bin/sh",
        "Args": [],
        "State": {
            "Status": "running",
            "Running": true,
            "Paused": false,
            "Restarting": false,
            "OOMKilled": false,
            "Dead": false,
            "Pid": 28730,
            "ExitCode": 0,
            "Error": "",
            "StartedAt": "2026-10-18T08:13:20.121156318Z",
            "FinishedAt": "0001-01-01T00:00:00Z"
        },
        "Image": "sha256:320994c3b997e2ec6433f717f153e108023c5bec8fefa8d76b83451d16d05ea8",
        "ResolvConfPath": "/var/lib/docker/containers/915aa3e8b2ed0086ac1044e9e0efcade91af60e86b7a146ccda1879822214 0ed/resolv.conf",
        "HostnamePath": "/var/lib/docker/containers/915aa3e8b2ed0086ac1044e9e0efcade91af60e86b7a146ccda1879822214 0ed/hostname",
        "HostsPath": "/var/lib/docker/containers/915aa3e8b2ed0086ac1044e9e0efcade91af60e86b7a146ccda1879822214 0ed/hosts",
        "LogPath": "/var/lib/docker/containers/915aa3e8b2ed0086ac1044e9e0efcade91af60e86b7a146ccda1879822214 0ed/915aa3e8b2ed0086ac1044e9e0efcade91af60e86b7a146ccda1879822214 0ed-json.log",
        "Name": "/k2",
        "RestartCount": 0,
        "Driver": "overlay2",
        "Platform": "linux",
        "MountLabel": "",
        "ProcessLabel": "",
        "AppArmorProfile": "",
        "ExecIDs": null,
        "HostConfig": {
            "Binds": null,
            "ContainerIDFile": "",
            "LogConfig": {
                "Type": "json-file",
                "Config": {}
            },
            "NetworkMode": "default",
            "PortBindings": {},
            "RestartPolicy": {
                "Name": "no",
                "MaximumRetryCount": 0
            },
            "AutoRemove": false,
```

```
[root@ip-172-31-8-63 ~]# docker exec -it k1 sh
Error response from daemon: container f9e859a7878c22098ccad92f1c92f7e653e816d029685769080313 7bd3362425 is not running
[root@ip-172-31-8-63 ~]# docker run -itd --name k3 alpine
463127d2da7392e2a6516d58956867ea89d8f03c4c4b391b4c43f4f93b1c5
[root@ip-172-31-8-63 ~]# docker exec -it k3 sh
/ # ping 172.17.0.1
sh: 172.17.0.2: not found
/ # ping 172.17.0.2
^C

/ # ping 172.17.0.2
PING 172.17.0.2 (172.17.0.2): 56 data bytes
64 bytes from 172.17.0.2: seq=0 ttl=127 time=0.130 ms
64 bytes from 172.17.0.2: seq=1 ttl=127 time=0.070 ms
64 bytes from 172.17.0.2: seq=2 ttl=127 time=0.072 ms
64 bytes from 172.17.0.2: seq=3 ttl=127 time=0.072 ms
64 bytes from 172.17.0.2: seq=4 ttl=127 time=0.069 ms
64 bytes from 172.17.0.2: seq=5 ttl=127 time=0.070 ms
64 bytes from 172.17.0.2: seq=6 ttl=127 time=0.066 ms
64 bytes from 172.17.0.2: seq=7 ttl=127 time=0.067 ms
64 bytes from 172.17.0.2: seq=8 ttl=127 time=0.070 ms
^C
--- 172.17.0.2 ping statistics ---
9 packets transmitted, 9 packets received, 0% packet loss
round-trip min/avg/max = 0.066/0.076/0.130 ms
/ # ping k2
ping: bad address 'k2'
/ # exit
[root@ip-172-31-8-63 ~]# docker network create --driver bridge varshitha_net
663ce8f9b5d68818223a9dc34e9700d14a07455f6d8947eccf4abda1c6108133
[root@ip-172-31-8-63 ~]# docker network ls
NETWORK ID     NAME           DRIVER    SCOPE
a047b5308b31   bridge         bridge    local
663ce8f9b568   varshitha_net  bridge    local
7c214f723ac9   host           host      local
90b46f1ea452   none           null      local
[root@ip-172-31-8-63 ~]# docker run -itd --name A1 --network varshitha_net alpine
f97d3d9ed1bf2f6330622D5212cbe1a8ee88fff07026854175403e1b3d589d1
[root@ip-172-31-8-63 ~]# docker run -itd --name A2 --network varshitha_net alpine
70302b94e38ad19eda95a0c19bf66ac668d4443359013c4ceb4fe8b492c4e274d
[root@ip-172-31-8-63 ~]#  docker exec -it A1 sh
/ # ping A2
PING A2 (172.18.0.3): 56 data bytes
64 bytes from 172.18.0.3: seq=0 ttl=127 time=0.137 ms
64 bytes from 172.18.0.3: seq=1 ttl=127 time=0.074 ms
64 bytes from 172.18.0.3: seq=2 ttl=127 time=0.109 ms
64 bytes from 172.18.0.3: seq=3 ttl=127 time=0.072 ms
64 bytes from 172.18.0.3: seq=4 ttl=127 time=0.074 ms
^C
--- A2 ping statistics ---
6 packets transmitted, 6 packets received, 0% packet loss
round-trip min/avg/max = 0.072/0.090/0.137 ms
/ # exit
[root@ip-172-31-8-63 ~]#
```