03 — Application Flow

Product: EventPilot — The Living Plan

1. Navigation model

Single-page planning workspace:

- Start / Event Setup
- Plan Workspace

- Budget - Timeline - Vendor Checklist - Ideas

- Change Review (drawer or dedicated panel)
- Settings / Reset Demo (lightweight)

2. Primary flow

```
START
  |
  v
Choose event type
  |
  v
Enter date, guest count, budget, currency, priorities
  |
  +---- invalid input ----> Inline validation ----> Correct input
  |
  v
Create plan / Load sample plan
  |
  v
PLAN WORKSPACE
  |------ Budget
  |------ Timeline
  |------ Vendor checklist
  |------ Personalized ideas
  |
  v
Change a supported constraint
(guest count / event date / total budget)
  |
  v
Recalculate deterministic values
  |
  v
Create proposed change set
  |
  v
Review before / after / reason / assumptions
  |                          |
  v                          v
Accept selected changes    Reject changes
  |                          |
  v                          v
Commit accepted changes    Keep original values
  \                          /
   \                        /
    v                      v
Updated plan remains editable
```

3. Screen states

Start / setup

- Empty state with clear call to action.
- Event type selector.
- Date, guest count, budget, currency and priorities.

- Inline errors and example values.
- “Try sample plan” path that does not require an API key.

Plan workspace

- Event title/date/guest count/budget summary.
- Four clearly labeled sections.
- Provenance labels for estimates and confirmed-by-user values.
- Clear over-budget status and task status.
- Loading, empty, error and success states.

Change review

For each change show:

- Item and field affected.
- Before value and proposed value.
- Reason and assumptions.
- Impact on budget or schedule.
- Accept / Reject controls.
- Locked items indicated and not silently modified.

AI unavailable

- Keep the current plan usable.
- Show a non-blocking explanation.
- Offer template suggestions / retry action.
- Do not clear or duplicate user data.

4. Accessibility requirements

- Logical heading hierarchy and landmarks.
- Keyboard-operable tabs and controls.
- Visible focus indicator.
- Every form control has a label.
- Errors are announced and linked to fields.
- Do not communicate status by color alone.
- Respect reduced-motion preference.
- Dialog/drawer traps and restores focus correctly if used.

5. Mobile behavior

- Stack plan sections vertically.
- Keep key budget and date summary visible without horizontal scrolling.
- Change review becomes a full-width panel or dialog.
- Buttons have adequate touch targets.

- Tables convert to stacked rows/cards when needed.

6. Error paths

- Invalid form input: inline correction.
- AI timeout/rate limit: preserve plan and offer fallback.
- Invalid AI schema: reject response and use fallback.
- Dependency cycle: show which tasks cause conflict.
- Storage failure: show warning and allow session-only use.
- Reset: confirm destructive reset and then show empty/sample state.

7. Demo script (90–120 seconds)

1. Start from sample wedding/birthday plan.
2. Show budget, timeline, vendor checklist and ideas.
3. Change guest count.
4. Show deterministic budget impact and before/after changes.
5. Reject one suggestion and accept another.
6. Demonstrate locked item remains unchanged.
7. Briefly show provenance labels and fallback if AI is unavailable.