
Computer and
Informatics
Engineering
Projects

SOFTWARE DEFINED NETWORKS MONITORING SYSTEM

universidade de aveiro  **deti** departamento de eletrónica, telecomunicações e informática

Afonso Cardoso	88964
David Araújo	93444
Diogo Dias	85085
Guilherme Craveiro	103574
João Machado	89119
Vasco Santos	98391

December 2022

State of the Art

Monitoring
&

Inband Network Telemetry

“P4-powered” SDN monitoring is mainly academic.

All monitoring solutions with P4 is based on the implementation of INT

Some of the work focus on what type of metrics to collect

What is not seen is the implementation of a proprietary header type.

Expected Use & Results

Deployment on **new** network or **existing ones**.

Use **simultaneously** with other SDN **controllers** or as a **standalone** solution.

Observer role over a network.

Autonomous **reactive** topology **reconfiguration**.



Requirement elicitation



Sources for these requirements came from:

- ✓ Study of similar implementations;
 - ✓ Brainstorming sessions;
 - ✓ Task Analysis;
 - ✓ Domain Analysis;
-

Functional Requirements

Management

- ❑ **Device** - Add and remove network devices.
- ❑ **Network Entities** - subdivisions like vlans or subnets are treated as entities.
- ❑ **Users** - The network can have multiple admins.

Measurements

- ❑ **Configurability** - user can set its own set of metrics.
- ❑ **Sample size** - can be set per device or has an globally measure value.

Atomicity

- ❑ **Network devices** - devices should require little no initial configuration.
- ❑ **Metrics** - metrics should be device independent.

Non-Functional Requirements

Capacity

- ❑ **Bandwidth** - stable width.
- ❑ **Response** - agent number or environment agnostic.
- ❑ **Size** - usable for a large number of agents

Reliability

- ❑ **Stability** - links do not disconnect.
- ❑ **Solidity** - lost of packs is minimized.

Availability

- ❑ **Access** - user access individuality.
- ❑ **Grouping** - device organization by common qualities.
- ❑ **Device type** - device agnostic.
- ❑ **Topologies** - topology structure agnostic

Non-Functional Requirements

Security

- ❑ **Privacy** - Guarantee data privacy.
- ❑ **Protection** - Ensuring the data is not compromised.


Usability

- ❑ **Customization** - Create a group of rules to simplify common operations.
- ❑ **Multi-Task** - Access multiple networks.
- ❑ **Multi-User** - Network accessible by multiple users.


Use Cases

Interaction only has one actor, the **system administrator**, which in production environments can have multiple **roles**.

In production, a network can have **multiple administrators**.



Personas




Name	Diana Silva	Age	27
Job	Network Engineer	Location	Braga
Context Challenges &	The company where she currently works deals with a variety of projects at a given time. It wants to begin transitioning to virtualized services, but doing so “in-house”, so they tasked Diana with developing a network structure for the upcoming virtualized environment.		
Goals	Diana need to keep a close eye on the network of services, but not only that, she needs a solution that actively alerts her to whatever parameter she defines and that she can define to react to certain events.		


Personas



Name	Diogo Ferreira	Age	34
Job	SOC Analyst	Location	Aveiro
Context Challenges &	Diogo works as part of a “blue team” for the security division of his company, one of his task is to monitor the impact of different types of traffic, the time periods during the day with large bandwidth demands , detect and act upon attacks like <i>DDOS</i> or even perform some vulnerability isolation .		
Goals	Diogo needs a solution that enables him to automate some of this tasks in his company’s virtual networks. He needs a system that not only detects but also is capable of reconfigure routes (or even vlans) when certain types of traffic are detected .		




System Architecture



Entity Diagram

System Mockup

Metric visualization & Device management



Overview of the network

The screenshot displays the ReactiveSDN web application interface. The browser's address bar shows the URL `http://localhost:8080/`. The application has a blue header bar with the title "ReactiveSDN" and a hamburger menu icon on the left. A vertical sidebar on the left contains icons for a user profile, Alerts, Topology, and Editor. The main content area is titled "Topology" and "Devices". Under the "Devices" section, there are tabs for "Routers", "L3 Switches", and "+ New Category". Below these tabs is a "+ New Device" button. The device list includes "Marketing" and "Secretary", each with a "Configure" link. The "Marketing" device details are expanded, showing its name, addresses, and host count.

Name	Marketing
Addresses	20.56.89.124 14:2d:27:e4:36:0f Subnet Seniors
Hosts	8 List all

Topology and network devices listing