





INJECTOR'S MEASURED TO TAKE MAX 1A EACH WHEN OPEN VNLD5160TR-E should be fine HARLEY uses 2N06L35




IGNITION



Harley Uses:


https://www.mouser.de/ProductDetail/onsemi/FGB3040G2-F085C?qs=2WXlatMagcHzMRj1hscbYQ%3D%3D
ISL9V3040D3ST should work though

PURGE & VVT SOLENOIDS



TODO: PURGE AND VVT SOLENOIDS NOT MEASURED YET AT ALL

COOLANT FAN & PUMP



COOLANT FAN PULLS AROUND 4A WHEN CONSTANT 100%, INITIALLY PULLING UP TO 8A FOR GETTING SPINNING

HARLEY USES: HUFA76429D3

POSSIBLE: https://www.digikey.de/de/products/detail/onsemi/HUF76629D3ST/4553106
AND: https://www.digikey.de/de/products/detail/diodes-incorporated/DMN6040SK3-13/8545933
Weytronik: https://www.digikey.de/de/products/detail/vishay-siliconix/SISS54DN-T1-GE3/14004251?s=N4IgTCBcDaIMoEk5wKwBYAiA5EBdAvkA

H2OS Heaters are PWM Controlled and max out at about 0.9 Amps at room temperature, then reducing with heat coming. VNLD5160TR-E should work. Will test

HD uses https://www.vishay.com/docs/71506/sq4946aey.pdf



CCFC: Harley uses 2N06L35
TODO: Does this part really make sense?

