SL-LINE | SL-CLASSIC

Safety storage cabinets for the storage of aggressive and non-flammable hazardous materials in working areas according to TRGS 510, DGUV-I 213-850, Ordinance on Hazardous Substances

1

Robust construction and longevity
Tall cabinet with body made of powder-coated sheet steel and interior space made of melamine resin and flame retardant special plates. Under bench cabinets completely made of melamine resin and flame retardant special plates.



2

Safe, separate storage
Acids and alkalis can be stored safe and separately. Two hermetically divided storage compartments, vertical or horizontal dividing wall. Integrated aeration and venting system, corrosion resistance of the metal-free air ducts.



3

Cylinder lock
Door lockable with cylinder lock, the cabinets can be integrated by the customer into an existing locking system.



4

Ventilation
Integrated air ducts ready for connection (DN 75) to a technical exhaust system can be used for the extraction of hazardous materials vapours. The potential formation of harmful vapours is safely prevented.



5

Pull-out shelves
Equipped with pull-out shelves incl. highly resistant sumps made of plastic. The pulled-out shelf provides a quick overview of all stored hazardous substances. In case of leakage the tray can be easily removed and quickly emptied and cleaned.



6

Separately lockable storage box
(Optionally available) for hydrofluoric acid including corrosion-resistant polypropylene sump



7

Interior equipment
Optionally available with PE tray shelves (V = 33 L) or bottom collecting sumps (V = 68 L) as storage levels for bulk packs.





- **GS-tested** (document EK5/AK4 09-10, ProdSG)

- Conformity in accordance with the requirements of **EN 16121** and **16122**
- Requirements and test methods for safety, strength, durability and stability.

- **Excellent products with special manufacturer warranty**
- Extended **manufacturer warranty of up to 5 years** in combination with the asecos BASICPlus tariff
- Further information from page 512





Model SL.196.120.MV
Order No. 30606-001-30608



Model SL.196.120.MV
Order No. 30606-001-37224

Technical data

External dimensions W x D x H	mm	1200 x 605 x 1970
Internal dimensions W x D x H	mm	all compartments: 485 x 570 x 1869
Weight without interior equip.	kg	215
Extraction air	DN	75
Air change **30 times**	m³/h	31
Diff. pressure (air change **30 times**)	Pa	10

Main features

Highly resistant surfaces

Optionally with separate storage box for hydrofluoric acid

You will find technical drawings and adjustment heights for these cabinet models from page 318

Model	Information / equipment	Colour	Order No.
SL.196.120.MV	without interior equipment, with vertical dividing wall	light grey RAL 7035	30606-001
		laboratory white (sim. RAL 9016)	30606-005

Interior equipment packages (can only be ordered in combination with the cabinet)	Material	Order No.
Left: 4x pull-out shelf with plastic sump (V=11.0L) Right: 4x pull-out shelf with plastic sump (V=11.0L)	panel melamine resin-coated/PP grey	30607
Left: 6x pull-out shelf with plastic sump (V=11.0L) Right: 6x pull-out shelf with plastic sump (V=11.0L)	panel melamine resin-coated/PP grey	30608
Left: 4x pull-out shelf with plastic sump (V=11.0L), 1x storage box for hydrofluoric acid (V=7.0L) Right: 4x pull-out shelf with plastic sump (V=11.0L)	panel melamine resin-coated/PP grey, panel melamine resin-coated/PE grey	37223
Left: 4x pull-out shelf (V=11.0L), 1x storage box for hydrofluoric acid (V=7.0L) Right: 5x pull-out shelf (V=11.0L)	panel melamine resin-coated/PP grey, panel melamine resin-coated/PE grey	37224
Left: 5x pull-out shelf (V=11.0L), 1x storage box for hydrofluoric acid (V=7.0L) Right: 6x pull-out shelf (V=11.0L)	panel melamine resin-coated/PP grey, panel melamine resin-coated/PE grey	37225

Interior equipment	Material	W x D x H (mm)	1)	2)	3)	Order No.
Sump pallet with grid	PE	454 x 538 x 314*	70.00	68.00	61.82	30611
Sump pallet on shelf with grid	PE	427 x 541 x 167*	70.00	33.50	30.45	30610
Pull-out shelf with plastic sump	panel melamine resin-coated/PP grey	407 x 468 x 80*	25.00	11.00	10.00	30609
Document holder DIN A5	polystyrene					30793

Accessories	Order No.
Extraction unit without exhaust air monitoring	14218

* usable storage space W x D (mm)
1) load capacity (kg), 2) retention capacity (ltr.), 3) maximum container volume in the cabinet (ltr.)



Model SL.196.060.MH
Order No. 30612-001-30615



Model SL.196.060.MH
Order No. 30612-005-37218

Technical data

External dimensions W x D x H	mm	597 x 603 x 1965
Internal dimensions W x D x H	mm	top: 485 x 570 x 914 bottom: 485 x 570 x 833
Weight without interior equip.	kg	136
Extraction air	DN	75
Air change **30 times**	m³/h	14
Diff. pressure (air change **30 times**)	Pa	4

Main features

- Highly resistant surfaces
- Optionally with separate storage box for hydrofluoric acid

You will find technical drawings and adjustment heights for these cabinet models from page 318

SL-SLX-LINE

Model	Information / equipment	Colour	Order No.
SL.196.060.MH	without interior equipment, left hinged, with horizontal dividing wall	light grey RAL 7035	30612-001
		laboratory white (sim. RAL 9016)	30612-005
SL.196.060.MH.R	without interior equipment, right hinged, with horizontal dividing wall	light grey RAL 7035	30613-001
		laboratory white (sim. RAL 9016)	30613-005

Interior equipment packages (can only be ordered in combination with the cabinet)	Material	Order No.	
		Door hinge: left	right
Top: 2x pull-out shelf with plastic sump (V=11.0L) Bottom: 2x pull-out shelf with plastic sump (V=11.0L)	panel melamine resin-coated/PP grey	30614	30614
Top: 3x pull-out shelf with plastic sump (V=11.0L) Bottom: 3x pull-out shelf with plastic sump (V=11.0L)	panel melamine resin-coated/PP grey	30615	30615
Top: 1x pull-out shelf (V=11.0L), 1x storage box for hydrofluoric acid (V=7.0L) Bottom: 2x pull-out shelf (V=11.0L)	panel melamine resin-coated/PP grey, panel melamine resin-coated/PE grey	37217	37220
Top: 1x pull-out shelf (V=11.0L), 1x storage box for hydrofluoric acid (V=7.0L) Bottom: 3x pull-out shelf (V=11.0L)	panel melamine resin-coated/PP grey, panel melamine resin-coated/PE grey	37218	37221
Top: 2x pull-out shelf (V=11.0L), 1x storage box for hydrofluoric acid (V=7.0L) Bottom: 3x pull-out shelf (V=11.0L)	panel melamine resin-coated/PP grey, panel melamine resin-coated/PE grey	37219	37222

Interior equipment	Material	W x D x H (mm)	1)	2)	3)	Order No.
Sump pallet with grid	PE	454 x 538 x 314*	70.00	68.00	61.82	30611
Sump pallet on shelf with grid	PE	427 x 541 x 167*	70.00	33.50	30.45	30610
Pull-out shelf with plastic sump	panel melamine resin-coated/PP grey	407 x 468 x 80*	25.00	11.00	10.00	30609

Accessories	Order No.
Extraction unit without exhaust air monitoring	14218

* usable storage space W x D (mm)
1) load capacity (kg), 2) retention capacity (ltr.), 3) maximum container volume in the cabinet (ltr.)