

Fan
CE compliant: CE ⟨Ex⟩ II 2/2G Ex h IIB T3 Gb X, explosion-proof, extraction from: EX-Zone 2, including shock absorber

Order No. 5794



Fan
CE compliant: CE ⟨Ex⟩ II 3/_G Ex h IIB T3 Gc X, explosion-proof, extraction from: EX-Zone 2 / installation: outside any EX-ZONE, including shock absorber

Order No. 5793

Fans – powerful and safe ventilation of safety storage cabinets

- Housing and impeller made of polypropylene
- Sealed against gas emission
- Connecting fitting DN 75
- Protection class IP 55
- Air flow 60-250 m³/h
- Total pressure 240-175 Pa
- Incl. PA/GFK console

Technical data		**EH.VE.5793**
External dimensions W x D x H	mm	275 x 225 x 312
Nominal voltage	V	230
Frequency	Hz	50
Max. current consumption	A	4.5
Noise level (approx.)	dB	45.0
Speed	rpm	2850
Weight	kg	4.2

Technical data		**EH.VE.5794**
External dimensions W x D x H	mm	335 x 225 x 312
Nominal voltage	V	3x400
Frequency	Hz	50
Max. current consumption	A	2.9
Noise level (approx.)	dB	45.0
Speed	rpm	2760
Weight	kg	4.8



Hose clamp made from chrome steel, diameter 70—90 mm

Order No. 5797



Butterfly damper made from polyethylene, inner diameter 75 mm

Order No. 5798



Flexible extraction hose made from plastic, inner diameter 75 mm

Order No. 1434



Motor protection switch suitable for fans

Order No. 5799

Model	Order No.
Fan EH.VE.5793	5793
Fan EH.VE.5794	5794

Accessories	Order No.
Motor protection switch suitable for fans	5799
Protective housing for motor protection switch	5803
Flexible extraction hose made from plastic, inner diameter 75 mm	1434
T-piece made from PVC, inner diameter 75 mm	8681
Butterfly damper made from polyethylene, inner diameter 75 mm	5798
Hose clamp made from chrome steel, diameter 70—90 mm	5797