

Programm:

```
prane_partheev1@PARTHEEV: X + v
GNU nano 8.7.1 skill7.c
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main() {
    pid_t pid = fork();

    if (pid == 0) {
        execlp("ls", "ls", NULL);
        perror("exec");
    } else {
        int status;
        waitpid(pid, &status, 0);

        if (WIFEXITED(status))
            printf("Child exited with status %d\n", WEXITSTATUS(status));
    }

    return 0;
}
```

OUTPUT:

```
prane_partheev1@PARTHEEV:~$ ./skill7
EX1      childpid      fork_exec.c      linuxcommand.c   pcPID.c          pratical3.c      skill2.c          skill5.c          username.c
IDprocess childpid.c      hello            multiplechild    practical-1       practical4       skill3            skill6            wait1
IDprocess.c example.txt    hello.c          multiplechild.c  practical-1.c    practical4.c     skill3.c          skill6.c          wait1.c
ParentChild fork          hello.c.save     parentwait       practical-2       processid        skill4            skill7            wait2
ParentChild.c fork.c          hello.c.save.1   parentwait.c     practical-2.c    processid.c     skill4.c          skill7.c          wait2.c
a.out    fork_exec      linuxcommand     pcPID            practical3        skill2           skill5            username          waste.c
Child exited with status 0
```