

Programm:

```
GNU nano 8.7.1
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <sys/wait.h>

int main() {
    pid_t pid = fork();

    if (pid == 0) {
        int fd = open("output.txt",
                     O_WRONLY | O_CREAT | O_TRUNC,
                     0644);

        dup2(fd, STDOUT_FILENO);
        close(fd);

        execlp("ls", "ls", "-l", NULL);
        perror("exec");
    } else {
        wait(NULL);
    }

    return 0;
}
```

OUTPUT:

```
prane_partheev1@PARTHEEV:~$ nano skill13.c
prane_partheev1@PARTHEEV:~$ gcc skill13.c -o skill13
prane_partheev1@PARTHEEV:~$ ./skill13
prane_partheev1@PARTHEEV:~$ ls
13.c          childpid.c  hello.c      parentwait  pratical3   skill11     skill2     skill6     username
EX1           error.txt  hello.c.save parentwait.c pratical3.c skill11.c   skill2.c   skill6.c   username.c
IDprocess     example.txt hello.c.save.1 pcPID       pratical4   skill12.c   skill3.c   skill7.c   wait1
IDprocess.c   fork       linuxcommand pcPID.c     pratical4.c skill12.c   skill3.c   skill7.c   wait1.c
ParentChild   fork.c     linuxcommand.c pratical-1  processid   skill13     skill4     skill8     wait2
ParentChild.c fork_exec  multiplechild pratical-1.c processid.c skill13.c   skill4.c   skill8.c   wait2.c
a.out         fork_exec.c multiplechild.c pratical-2  skill10     skill14     skill5     skill9     waste.c
childpid      hello     output.txt  pratical-2.c skill10.c   skill14.c   skill5.c   skill9.c
```