

Programm:

```
prane_partheev1@PARTHEEV: x + v
GNU nano 8.7.1
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <sys/wait.h>

int main() {
    pid_t pid = fork();

    if (pid == 0) {
        int fd = open("error.txt",
                     O_WRONLY | O_CREAT | O_APPEND,
                     0644);

        dup2(fd, STDERR_FILENO);
        close(fd);

        execlp("ls", "ls", "invalid_file", NULL);
        perror("exec");
    } else {
        wait(NULL);
    }

    return 0;
}
```

OUTPUT:

```
prane_partheev1@PARTHEEV:~$ nano skill14.c
prane_partheev1@PARTHEEV:~$ gcc skill14.c -o skill14
prane_partheev1@PARTHEEV:~$ ./skill14
prane_partheev1@PARTHEEV:~$ ls
13.c          childpid.c  hello.c          parentwait      pratical3      skill11        skill2        skill6        username
EX1           error.txt   hello.c.save     parentwait.c    pratical3.c    skill11.c     skill2.c     skill6.c     username.c
IDprocess     example.txt hello.c.save.1   pcPID           pratical4      skill12.c     skill3.c     skill7.c     wait1
ParentChild   fork.c      linuxcommand     pcPID.c         pratical4.c    skill12.c     skill3.c     skill7.c     wait1.c
ParentChild.c fork_exec   multiplechild    pratical-1      processid      skill13.c     skill4.c     skill8.c     wait2.c
a.out         fork_exec.c multiplechild.c  pratical-1.c    processid.c    skill13.c     skill4.c     skill8.c     wait2.c
childpid      hello      output.txt       pratical-2      skill10        skill14        skill5        skill9        waste.c
prane_partheev1@PARTHEEV:~$
```