

## 25 Advanced C Function Challenges - Explained

### 1. What happens when a C function returns a local array? Why?

- Local arrays are stored in stack memory. When a function returns, its stack frame is destroyed. Returning a pointer to that local array leads to undefined behavior.
- Fix: Use static storage or dynamically allocated memory (malloc).

### 2. How would you pass a function as a parameter to another function in C?

- Use function pointers. Example:

```
int add(int a, int b) { return a + b; }
void operate(int x, int y, int (*func)(int, int)) {
    printf("%d", func(x, y));
}
```

### 3. Difference between inline and static in function declarations:

- inline: Suggests the compiler to insert the function code at the call site.
- static: Limits the visibility of the function or variable to the current file.

### 4. Function declaration, definition, and prototype:

- Declaration: Introduces the function (e.g., `int func();`).
- Definition: Provides the body of the function.
- Prototype: Declaration with parameter types.

### 5. Effect of using static:

- Inside a function: variable retains value across calls.
- Outside a function: limits visibility to the file (internal linkage).

### 6. What is tail-call optimization and does C support it?

- Tail recursion: last action of a function is a recursive call.
- C supports TCO depending on compiler (e.g., GCC with `-O2`).

### 7. What happens if you call a function before its prototype is defined?

- In C89: assumes `int` return type.
- In C99+: compiler error due to implicit declaration.

### 8. Variadic function to return max of integers:

```
int maxOf(int count, ...) {
    va_list args;
    va_start(args, count);
    int max = va_arg(args, int);
    for (int i = 1; i < count; i++) {
        int val = va_arg(args, int);
        if (val > max) max = val;
    }
    va_end(args);
}
```

## 25 Advanced C Function Challenges - Explained

```
    return max;
}
```

**9. Compiler can't enforce type safety in variadic functions. Arguments are read by `va_arg` without type info.**

### 10. `va_list`, `va_start`, `va_arg`:

- `va_list`: holds the list.
- `va_start`: initializes it.
- `va_arg`: extracts the next argument.

### 11. Calling variadic function with fewer arguments:

- Causes undefined behavior: function reads more arguments than passed.

### 12. Passing float to variadic function:

- float is promoted to double. Always use `va_arg(args, double)`.

### 13. Simulate anonymous functions:

- Use function pointers or GCC's `lambda` macro:  

```
#define LAMBDA(return_type, body) ({ return_type __fn__ body __fn__; })
```

### 14. Function pointer array for arithmetic:

```
int (*ops[4])(int, int) = {add, sub, mul, divide};
ops[0](a, b); // calls add
```

### 15. Function pointer from different files:

- Must not be static.
- Use `extern` in header file.

### 16. Function pointer to void returning func with `(int, char*)`:

```
void (*fp)(int, char*) = myFunc;
```

### 17. Dynamically switch behavior at runtime:

```
void (*handler)();
if (mode == 1) handler = printA;
else handler = printB;
```

### 18. Maximum depth of recursion:

- Based on stack size. Use ``ulimit -s`` and frame size estimate.

## 25 Advanced C Function Challenges - Explained

### 19. Convert recursion to iteration:

- Use explicit stack data structure to mimic call stack.

### 20. Mutual recursion:

```
void A(); void B();  
void A() { B(); }  
void B() { A(); }
```

### 21. Tail recursion:

```
int tailFact(int n, int acc) {  
    if (n == 0) return acc;  
    return tailFact(n-1, n*acc);  
}
```

### 22. Real-world recursive problems:

- Tree traversal, graph DFS, backtracking, divide & conquer algorithms.

### 23. Recursive variadic function parsing (simulate):

- Use structs to nest calls:  
sum(1, sum(2, 3), 4) => represented with node trees.

### 24. Command parser with function pointers:

```
if (strcmp(cmd, "add") == 0) fn = add;
```

### 25. Function pointers and recursion can cause stack overflows:

- Especially with deep/indirect recursion. Always include base cases.