

Table of Contents

M	I3UA Management - SCTP	1
	Create SCTP Server	1
	Destroy SCTP Server	2
	Start SCTP Server	2
	Stop SCTP Server	3
	Show SCTP Server	3
	Create SCTP Association	4
	Destroy SCTP Association	4
	Show SCTP Association	5
M	I3UA Management	5
	Create AS	6
	Destroy AS	7
	Show AS	7
	Create ASP	8
	Destroy ASP	8
	Show ASP	9
	Start ASP	9
	Stop ASP	. 10
	Add ASP to AS	. 10
	Remove ASP from AS	. 11
	Add Route.	. 11
	Remove Route	. 12
	Chay Pouto	12

M3UA stack is also responsible to manage the SCTP Associations.

M3UA Management - SCTP

M3UA - SCTP is managed by sctp command. It allows to perform following:

- sctp server create
- sctp server destroy
- sctp server start
- sctp server stop
- sctp server show
- sctp association create
- sctp association destroy
- sctp association show

Create SCTP Server

SCTP Server can be created by issuing command with following structure:

```
sctp server create <server-name> <host-ip> <host-port> <socket-type>
```

Where:

server-name

Unique name assigned to the server.

host-ip

The host ip address where underlying SCTP server socket will bind. For SCTP multi-home support, you can pass comma separated ip addresses that this server socket will bind to. If the primary ip address becomes unavailable, it will automatically fall back to secondary address. For socket-type TCP, comma separated values will be ignored and only first value (primary address) will be used

host-port

The host port where underlying SCTP server socket will bind

socket-type

This is optional. If not passed default is SCTP else specify as TCP.

Example 1. SCTP Server creation

```
mobicents(127.0.0.1:3436)>sctp server create TestServer 127.0.0.1 2905 Successfully added Server=TestServer
```

mobicents(127.0.0.1:3436)>sctp server create TestServer 10.2.50.145,10.2.50.146 2905

Successfully added Server=TestServer

Example 3. TCP Server creation

mobicents(127.0.0.1:3436)>sctp server create TestServerTCP 10.2.50.145 2906 TCP Successfully added Server=TestServerTCP

Destroy SCTP Server

SCTP Server can be destroyed by issuing command with following structure:

sctp server destroy <server-name>

Where:

server-name

Unique name of the server to be destroyed. Make sure server is stopped before destroying.

Example 4. Destroy SCTP Server

mobicents(127.0.0.1:3436)>sctp server destroy TestServer
Successfully removed Server=TestServer

Start SCTP Server

SCTP Server can be started by issuing command with following structure:

sctp server start <server-name>

Where:

server-name

Unique name of the server to be started. The underlying SCTP server socket is bound to ip:port configured at creation time.

mobicents(127.0.0.1:3436)>sctp server start TestServer Successfully started Server=TestServer

Stop SCTP Server

SCTP Server can be stopped by issuing command with following structure:

sctp server stop <server-name>

Where:

server-name

Unique name of the server to be stopped. The underlying socket is closed at this point and all resource are released.

Example 6. Stop SCTP Server

mobicents(127.0.0.1:3436)>sctp server stop TestServer Successfully stopped Server=TestServer

Show SCTP Server

SCTP Server's configuration can be viewed by issuing command with following structure:

sctp server show

Example 7. Show SCTP Server

mobicents(local)>sctp server show

SERVER TCP name=TestServerTCP started=false hostIp=10.2.50.145 hostPort=2906 Associations:

SERVER SCTP name=TestServer started=false hostIp=10.2.50.145 hostPort=2905 secondaryHost=10.2.50.146 Associations:

Create SCTP Association

Association can be created by issuing command with following structure:

sctp association create <assoc-name> <CLIENT | SERVER> <server-name> <peer-ip> <peerport> <host-ip> <host-port> <socket-type>

Where:

assoc-name

Unique name of the association

CLIENT | SERVER

If this association is client side or server side. If its client side, it will initiate the connection to peer and bind's to host-ip:host-port trying to connect to peer-ip:peer-port. For SCTP multi-home support, you can pass comma separated ip addresses that this association will bind to. If the primary ip address becomes unavailable, it will automatically fall back to secondary address. For socket-type TCP, comma separated values will be ignored and only first value (primary address) will be used

server-name

If this association is server side, server-name must be passed to associate with server. Server with server-name should have already been created by using command Create SCTP Server

socket-type

This is optional. If not passed default is SCTP else specify as TCP. If association is of SERVER type, the socket-type should match with one specified while creating server.

Example 8. Create CLIENT SCTP Association

mobicents(local)>sctp association create Assoc1 CLIENT 192.168.56.101 2905 192.168.56.1,192.168.56.1 2905 Successfully added client Associtaion=Assoc1

Example 9. Create SERVER SCTP Association

mobicents(192.168.56.1:3436)>sctp association create Assoc2 SERVER TestServer 192.168.56.1 2905 Successfully added server Association=TestServer

Destroy SCTP Association

Association can be destroyed by issuing command with following structure:

sctp association destroy <assoc-name>

Where:

assoc-name

Unique name of the association to be destroyed

Example 10. Destroy SCTP Association

mobicents(192.168.56.1:3436)>sctp association destroy Assoc1 Successfully removed association=Assoc1

Show SCTP Association

Configuration of Association can be viewed by issuing command with following structure:

sctp association show

Example 11. Show SCTP Association

(local)>sctp association show

ASSOCIATION SCTP name=Assoc1 started=false peerIp=192.168.56.101 peerPort=2905 hostIp=192.168.56.1 hostPort2905 type=CLIENT secondaryHost=192.168.56.1

ASSOCIATION SCTP name=Assoc2 started=false peerIp=192.168.56.1 peerPort=2905 server=TestServer type=SERVER

M3UA Management

M3UA is managed by m3ua command. It allows to perform following:

- m3ua as create
- m3ua as destroy
- m3ua as show
- m3ua asp create
- m3ua asp destroy
- m3ua asp show
- m3ua asp start
- m3ua asp stop

- m3ua as add
- m3ua as remove
- m3ua route add
- m3ua route remove
- m3ua route show

Create AS

Application Server (AS) can be created by issuing command with following structure:

m3ua as create <as-name> <AS | SGW | IPSP> mode <SE | DE> ipspType <client | server> rc <routing-context> traffic-mode <traffic mode> min-asp <minimum asp active for TrafficModeType.Loadshare> network-appearance <network appearance>

Where:

as-name

simple string name, which identifies AS. Make sure this is unique. This is mandatory parameter

AS | SGW | IPSP

Specify if this is of type AS or SGW or IPSP. This is mandatory parameter

SE | DE

Specify if the single or double exchange of ASP State Maintenance (ASPSM) and ASP Traffic Maintenance (ASPTM) messages should be performed. This is mandatory parameter.

client | server

If As if of type IPSP, speicfy here if its client or server type.

routing-context

refers to Routing Context already configured on M3UA stack on SGW side. This is optional parameter. If no Routing Context is passed, Application Server Process (assigned to this AS) may not be configured to process signaling traffic related to more than one Application Server, over a single SCTP Association

traffic-mode

Traffic mode for ASP's. By default its loadshare. Mobicents M3UA only supports loadshare and override, broadcast is not supported.

min-asp

The minumum number of active ASPs needed (if the traffic mode is 'loadshare') before the payload starts flowing (AS goes into ACTIVE state). This is an optional parameter and if not specified the default value is 1. Also if the traffic-mode is not set as 'loadshare', this parameter has no effect.

network-appearance

The Network Appearance is a M3UA local reference shared by SG and AS (typically an integer)

that, together with an Signaling Point Code, uniquely identifies an SS7 node by indicating the specific SS7 network to which it belongs. It can be used to distinguish between signaling traffic associated with different networks being sent between the SG and the ASP over a common SCTP association. This is optional.

Example 12. AS (IPSP) creation

mobicents(127.0.0.1:3435)>m3ua as create AS1 IPSP mode DE ipspType server rc 1 traffic-mode loadshare
Successfully created AS name=AS1

Example 13. AS creation

mobicents(127.0.0.1:3435)>m3ua as create AS2 AS mode SE rc 100 traffic-mode loadshare network-appearance 12 Successfully created AS name=AS2

Destroy AS

Application Server (AS) can be destroyed by issuing command with following structure:

m3ua as destroy <as-name>

Where:

as-name

Simple string name, which identifies AS. Make sure AS is in state INACTIVE and all the ASP's are unassigned before destroying

Example 14. Destroy AS

mobicents(127.0.0.1:3435)>m3ua as destroy AS1 Successfully destroyed AS name=AS1

Show AS

Application Server configured can viewed by issuing command with following structure:

m3ua as show

```
mobicents(local)>m3ua as show
```

```
AS name=AS2 functionality=AS mode=SE rc=[100] trMode=2 defaultTrMode=2 na=12 peerFSMState=DOWN Assigned to :
```

AS name=AS1 functionality=IPSP mode=DE ipspType=SERVER rc=[1] trMode=2 defaultTrMode=2 localFSMState=DOWN peerFSMState=DOWN Assigned to :

Create ASP

Application Server Process (ASP) can be created by issuing command with following structure:

```
m3ua asp create <asp-name> <sctp-association> aspid <aspid>
```

Where:

asp-name

Name of this ASP. It should be unique

sctp-association

name of SCTP Association

aspid

Identifier for this newly created Application Server Process. If this is not passed, next available aspid will be used.

Example 16. ASP creation

```
mobicents(127.0.0.1:3435)>m3ua asp create ASP1 Assoc1 Successfully created AS name=ASP1
```

Destroy ASP

ASP can be destroyed by issuing command with following structure:

```
m3ua asp destroy <asp-name>
```

Where:

asp-name

Name of this ASP to be destroyed. Make sure ASP is stopped before destroying

Example 17. Destroy ASP

```
mobicents(127.0.0.1:3435)>m3ua asp destroy ASP1 Successfully destroyed ASP name=ASP1
```

Show ASP

ASP configured can be viewed by issuing command with following structure:

```
m3ua asp show
```

Example 18. Show ASP

```
mobicents(local)>m3ua asp show
```

```
ASP name=ASP1 sctpAssoc=Assoc1 started=false Assigned to :
```

Start ASP

Application Server Process (ASP) can be started with following structure

```
m3ua asp start <asp-name>
```

Where:

asp name

name of ASP created earlier. Make sure ASP you are trying to start is assigned to at least one AS

Example 19. Start ASP

```
mobicents(127.0.0.1:3435)>m3ua asp start ASP1 Successfully started ASP name=ASP1
```

Stop ASP

Application Server Process (ASP) can be stopped with following structure

m3ua asp stop <asp-name>

Where:

asp name

name of ASP started earlier.

Example 20. Stop ASP

mobicents(127.0.0.1:3435)>m3ua asp stop ASP1 Successfully stopped ASP name=ASP1

Add ASP to AS

Application Server Process (ASP) can be assigned to Application Server (AS) with following structure

m3ua as add <as-name> <asp-name>

Where:

as name

name of AS created earlier

asp name

name of ASP created earlier

Note



Mobicents M3UA supports configuring ASP to process signaling traffic related to more than one Application Server, over a single SCTP Association. However you need to make sure that all the AS's that ASP is shared with has Routing Context (unique) configured.

Example 21. Add ASP to AS

mobicents(127.0.0.1:3435)>m3ua as add AS1 ASP1 Successfully added ASP name=ASP1 to AS name=AS1

Remove ASP from AS

Application Server Process (ASP) can be unassigned from Application Server (AS) with following structure

m3ua as remove <as-name> <asp-name>

Where:

as name

name of AS

asp name

name of ASP

Example 22. Remove ASP from AS

mobicents(127.0.0.1:3435)>m3ua as remove AS1 ASP1
Successfully removed ASP name=ASP1 from AS name=AS1

Add Route

Configure the destination point code that message will be routed to

m3ua route add <as-name> <dpc> <opc> <si>

Where:

as name

name of AS created earlier

dpc

Destination point code

opc

Originating point code

si

Service Indicator

```
mobicents(127.0.0.1:3435)>m3ua route add AS1 2 -1 -1
```

Remove Route

Remove the As configured for the destination point code

```
m3ua route remove <as-name> <dpc> <opc> <si>
```

Where:

as name

name of AS assigned to route message for this dpc

dpc

Destination point code

opc

Originating point code

si

Service Indicator

Example 24. Remove Route

```
mobicents(127.0.0.1:3435)>m3ua route remove AS1 2 -1 -1
```

Show Route

Show all the routes configured

m3ua route show

Example 25. Show Route

```
mobicents(local)>m3ua route show
```

2:-1:-1 AS1,AS2,