

Design A - Live-tablen beregnes, når nogen spørger

Client

API

Liveboard

Commands (writes)

CancelTripCommand

CancelTripHandler

Queries (reads)

GetLiveboardQuery

GetLiveBoardHandler

Beregner live-tavlen ved forespørgsel ved at læse routes+trips (for givent tidsvindue)

Booking

Commands (writes)

MakeBookingCommand

MakeBookingHandler

Transaction (MakeBooking)

- Tjek request_id(idempotency)
- Lås tur (SELECT __ FOR UPDATE)
- Tjek trips.status = “Scheduled”
- Opret booking

PublishedPlan

Queries (reads)

GetPublishedPlanQuery

GetPublishedPlanHandler

Commands (writes)

PublishPlanCommand

PublishPlanHandler

Transaction (PublishPlan)

- Læs routes + trips (for vindue)
- Beregn værdier pr. rute
- Gem i published_plan_snapshot

Writer/Command

Reads/Query

Writes/Command

Writes/Command

Reads/Query

Reads/Query



Database

routes

id	text	PK
short_name	text	

trips

id	text	PK
route_id	text	FK
scheduled_departure_utc	timestampz	
status	text	

base

bookings

request_id	text	PK
trip_id	text	FK
booked_at_utc	timestampz	

published_plan_snapshot

id	text	
published_at_utc	timestampz	
route_id	text	
route_name	text	
scheduled_trip_count	integer	
next_departure_utc	timestampz	

Fordele
Altid korrekt og enkel.
Ingen ekstra tabeller at holde opdateret.
Understøtter alle tidsvinduer

Ulemper
En database-forespørgsel hver gang tavlen vises.
Kan være langsommere ved høj belastning.