

# CMOR

version 3.16.0

Charles Doutriaux

Karl E. Taylor

Chris Mauzey

Denis Nadeau

Paul J. Durack

*Last generated: September 16, 2026*





# Table of Contents

## Overview

|                            |    |
|----------------------------|----|
| Getting started .....      | 2  |
| CMOR API .....             | 10 |
| Acknowledgements .....     | 35 |
| PrePARE (deprecated) ..... | 36 |

## Installation

|                       |    |
|-----------------------|----|
| Miniforge/Mamba ..... | 39 |
| pip (Python) .....    | 43 |
| Source (GitHub) ..... | 45 |

## Examples

|                                     |     |
|-------------------------------------|-----|
| Python .....                        | 48  |
| Fortran .....                       | 119 |
| C .....                             | 190 |
| Controlled Vocabulary (CMIP6) ..... | 255 |

## Appendix

|                                        |     |
|----------------------------------------|-----|
| CMIP6 table Excerpt .....              | 265 |
| CMIP6 required Global Attributes ..... | 274 |
| User Input .....                       | 276 |
| Appendix A .....                       | 281 |
| Appendix B .....                       | 286 |

## Contact us!

|               |     |
|---------------|-----|
| Contact ..... | 287 |
|---------------|-----|

# Getting started overview

## Design Considerations and Overview

This document describes Version 3 of a software library called “Climate Model Output Rewriter” (CMOR3)[1] (page 8), written in C with access also provided via Fortran 90 and through Python[2] (page 8). CMOR is used to produce CF-compliant[3] (page 8) netCDF[4] (page 8) files. The structure of the files created by CMOR and the metadata they contain fulfill the requirements of many of the climate community’s standard model experiments (which are referred to here as “MIPs”[5] (page 8) and include, for example, AMIP, PMIP, APE, and IPCC [DN1] scenario runs).

CMOR was not designed to serve as an all-purpose writer of CF-compliant netCDF files, but simply to reduce the effort required to prepare and manage MIP model output. Although MIPs encourage systematic analysis of results across models, this is only easy to do if the model output is written in a common format with files structured similarly and with sufficient metadata uniformly stored according to a common standard. Individual modeling groups store their data in different ways, but if a group can read its own data, then it should easily be able to transform the data, using CMOR, into the common format required by the MIPs. The adoption of CMOR as a standard code for exchanging climate data will facilitate participation in MIPs because after learning how to satisfy the output requirements of one MIP, it will be easy to prepare output for other MIPs.

CMOR output has the following characteristics:

- Each file contains a single primary output variable (along with coordinate/grid variables, attributes and other metadata) from a single model and a single simulation (i.e., from a single ensemble member of a single climate experiment). This method of structuring model output best serves the needs of most researchers who are typically interested in only a few of the many variables in the MIP databases. Data requests can be satisfied by simply sending the appropriate file(s) without first extracting the individual field(s) of interest.
- There is flexibility in specifying how many time slices (samples) are stored in a single file. A single file can contain all the time-samples for a given variable and climate experiment, or the samples can be distributed in a sequence of files.
- Much of the metadata written to the output files is defined in MIP-specific tables of information, which in this document are referred to simply as “MIP tables”. These tables are JSON files that can be read by CMOR and are typically made available from MIP web sites. Because these tables contain much of the metadata that is useful in the MIP context, they are the key to reducing the programming burden imposed on the individual users contributing data to a MIP. Additional tables can be created as new MIPs are born.
- For metadata, different MIPs may have different requirements, but these are accommodated by CMOR, within the constraints of the CF convention and as specified in the MIP tables (e.g. [CMIP6 MIP tables \(https://github.com/PCMDI/cmip6-cmor-tables\)](https://github.com/PCMDI/cmip6-cmor-tables)).

- CMOR relies on NetCDF4 [See unidata web page \(http://www.unidata.ucar.edu/software/netcdf\)](http://www.unidata.ucar.edu/software/netcdf) to write the output files and can take advantage of its compression and chunking capabilities. CMOR3 outputs NetCDF4 files by default. For CMIP6, the NetCDF4/NC\_CLASSIC\_Model mode is used. As of CMOR 3.10, there is now support for zstandard compression and [lossy compression via quantization](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#lossy-compression-via-quantization) (<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#lossy-compression-via-quantization>)  
 . More on quantization in NetCDF4 [here](https://docs.unidata.ucar.edu/netcdf-c/4.9.2/md__media_psf_Home_Desktop_netcdf_releases_v4_9_2_release_netcdf_c_docs_quantize.html) ([https://docs.unidata.ucar.edu/netcdf-c/4.9.2/md\\_\\_media\\_psf\\_Home\\_Desktop\\_netcdf\\_releases\\_v4\\_9\\_2\\_release\\_netcdf\\_c\\_docs\\_quantize.html](https://docs.unidata.ucar.edu/netcdf-c/4.9.2/md__media_psf_Home_Desktop_netcdf_releases_v4_9_2_release_netcdf_c_docs_quantize.html))  
 .
- CMOR also must be linked against the udunits2 library [see http://www.unidata.ucar.edu/software/udunits/](http://www.unidata.ucar.edu/software/udunits/) (<http://www.unidata.ucar.edu/software/udunits/>), which enables CMOR to check that the units attribute is correct[6] (page 8). Finally CMOR3 must also be linked against the uuid library [see http://www.ossfp.org/pkg/lib/uuid](http://www.ossfp.org/pkg/lib/uuid) (<http://www.ossfp.org/pkg/lib/uuid>) in order to produce a unique tracking number for each file.

Although the CMOR output adheres to a fairly rigid structure, there is considerable flexibility allowed in the design of codes that write data through the CMOR functions. Depending on how the source data are stored, one might want to structure a code to read and rewrite the data through CMOR in several different ways. Consider, for example, a case where data are originally stored in “history” files that contain many different fields, but a single time sample. If one were to process several different fields through CMOR and one wanted to include many time samples per file, then it would usually be more efficient to read all the fields from the single input file at the same time, and then distribute them to the appropriate CMOR output files, rather than to process all the time-samples for a single field and then move on to the next field. If, however, the original data were stored already by field (i.e., one variable per file), then it would make more sense to simply loop through the fields, one at a time. The user is free to structure the conversion program in either of these ways (among others).

The following input files are typically needed by CMOR:

- The “User Input File” (e.g., CMIP6\_input\_example.json), which provides user-supplied metadata and configuration directives.
- A “controlled vocabulary file” (e.g., “CMIP6\_CV.json), which concatenates into a single file most of the CMIP6 controlled vocabularies archived at [https://github.com/WCRP-CMIP/CMIP6\\_CVs](https://github.com/WCRP-CMIP/CMIP6_CVs). This file is updated frequently as additional models and institutions register to participate in CMIP6.
- A “CMOR Table” (e.g., CMIP6\_Amon.json), which provides for each variable that might be written by CMOR much of the required metadata. It also provides additional information that CMOR uses to correctly write the data and to enable certain QC checks.
- A “Vertical Coordinate Formula Terms Table” (e.g., CMIP6\_formula\_terms.json)
- A “Coordinates Table” (e.g., CMIP6\_coordinate.json) CMIP6
- CMIP6\_grids.json supplements the Coordinates Table with axis information that is sometimes needed in the treatment of unstructured grids.

The files used by CMOR for CMIP6 are archived in <https://github.com/PCMDI/cmip6-cmor-tables/tree/master/Tables> (<https://github.com/PCMDI/cmip6-cmor-tables/tree/master/Tables>), and all but the CMIP6\_input\_example.json file must not be modified by the user. The CMIP6\_input\_example.json file must be edited to accurately reflect the output being written by the user (but do not modify the lines of text appearing after the comment line, “#note\_CV”: “ \*\* The following will be obtained from the CV and do not need to be defined here”). Note that the CMIP6\_CV.json file found in <https://github.com/PCMDI/cmip6-cmor-tables/tree/master/Tables> (<https://github.com/PCMDI/cmip6-cmor-tables/tree/master/Tables>) is updated whenever new models and institutions are registered to participate in CMIP6.

Converting data with CMOR typically involves the following steps (with the CMOR function names given in parentheses):

- Initialize CMOR and specify where output will be written and how error messages will be handled (cmor\_setup).
- Provide information directing where output should be placed and identifying the data source, project name, experiment, etc. (cmor\_dataset\_json). User need to provide a User Input CMOR file to define each attribute.
- Set any additional “dataset” (i.e. global) attributes (cmor\_set\_cur\_dataset function). Note that all CMIP6 attributes can also be defined in the CMOR input user JSON file (cmor\_dataset\_json).
- Define the axes (i.e., the coordinate values) associated with each of the dimensions of the data to be written and obtain “handles”, to be used in the next step, which uniquely identify the axes (cmor\_axis).
- In the case of non-Cartesian longitude-latitude grids or for “station data”, define the grid and its mapping parameters (cmor\_grid and cmor\_set\_grid\_mapping)
- Define the variables to be written by CMOR, indicate which axes are associated with each variable, and obtain “handles”, to be used in the next step, which uniquely identify each variable (cmor\_variable). For each variable defined, this function fills internal table entries containing file attributes passed by the user or obtained from a MIP table, along with coordinate variables and other related information. Thus, nearly all of the file’s metadata is collected during this step.
- Write an array of data that includes one or more time samples for a defined variable (cmor\_write). This step will typically be repeated to output additional variables or to append additional time samples of data.
- Close one or all files created by CMOR (cmor\_close)

There is an additional function (cmor\_zfactor), which enables one to define metadata associated with dimensionless vertical coordinates.

CMOR was designed to reduce the effort required of those contributing data to various MIPs. An important aim was to minimize any transformations that the user would have to perform on their original data structures to meet the MIP requirements. Toward this end, the code allows the following flexibility (with the MIP requirements obtained by CMOR from the appropriate MIP table and automatically applied):

- The input data can be structured with dimensions in any order and with coordinate values either increasing or decreasing monotonically; CMOR will rearrange them to meet the MIP's requirements before writing out the data.
- The input data and coordinate values can be provided in an array declared to be whatever "type" is convenient for the user (e.g., in the case of coordinate data, the user might pass type "real" values (32-bit floating-point numbers on most platforms) even though the output will be written type double (64-bit IEEE floating-point); CMOR will transform the data to the required type before writing.
- The input data can be provided in units different from what is required by a MIP. If those units can be transformed to the correct units using the udunits (version 2) software (see [udunits](http://www.unidata.ucar.edu/software/udunits/))[<http://www.unidata.ucar.edu/software/udunits/>], then CMOR performs the transformation before writing the data. Otherwise, CMOR will return an error. Time units are handled via the built-in cftime interface [7] (page 8).
- So-called "scalar dimensions" (sometimes referred to as "singleton dimensions") are automatically inserted by CMOR. Thus, for example, the user can provide surface air temperature (at 2 meters) as a function of longitude, latitude, and time, and CMOR adds as a "coordinate" attribute the "height" dimension, consistent with the metadata requirements of CF. If the model output does not conform to the MIP requirements (e.g., carries temperature at 1.5 m instead of 2 m), then the user can override the MIP table specifications.

The code does not, however, include a capability to interpolate data, either in the vertical or horizontally. If data originally stored on model levels, is supposed to be stored on standard pressure levels, according to MIP specifications, then the user must interpolate before passing the data to CMOR.

The output resulting from CMOR is "self-describing" and includes metadata summarized below, organized by attribute type (global, coordinate, or variable attributes) and by its source (specified by the user or in a MIP table, or generated by CMOR).

*Global attributes typically provided by the MIP table or generated by CMOR:*

- *title*, identification of the project, experiment, and table.
- *Conventions*, ('CF-1.4')
- *history*, any user-provided history along with a "timestamp" generated by CMOR and a statement that the data conform to both the CF standards and those of a particular MIP.
- *activity\_id*, scientific project that inspired this simulation (e.g., CMIP6)
- *table\_id*, MIP table used to define variable.
- *data\_specs\_version* Base on the latest CMIP6-Datarequest latest database version.
- *mip\_era*, define what cycle of CMIP dictates the experiment and data specification.
- *experiment*, a long name title for the experiment.
- *realm(s)* to which the variable belongs (e.g., ocean, land, atmosphere, etc.).
- *tracking\_id*, a unique identification string generated by uuid, which is useful at least within the ESG distributed data archive.
- *cmor\_version*, version of the library used to generate the files.

- *frequency*, the approximate time-sampling interval for a time-series of data.
- *creation\_date*, the date and time (UTZ) that the file was created.
- *product*, a descriptive string that distinguishes among various model data products.

*Global attributes typically provided by the user in a call to a CMOR function:*

- *institution*, identifying the modeling center contributing the output.
- *institute\_id*, a shorter identifying name of the modeling center (which would be appropriate for labeling plots in which results from many models might appear).
- *source*, identifying the model version that generated the output.
- *contact*, providing the name and email of someone responsible for the data
- *source\_id*, an acronym that identifies the model used to generate the output.
- *experiment\_id*, a short name for the experiment.
- *history*, providing an “audit trail” for the data, which will be supplemented with CMOR-generated information described above.
- *references*, typically containing documentation of the model and the model simulation.
- *comment*, typically including initialization and spin-up information for the simulation.
- *realization\_index*, an integer distinguishing among simulations that differ only from different equally reasonable initial conditions. This number should be greater than or equal to 1.
- *initialization\_index*, an integer distinguishing among simulations that differ only in the method of initialization. This number should be greater than or equal to 1.
- *physics\_index*, an integer indicating which of several closely related physics versions of a model produced the simulation.
- *parent\_experiment\_id*, a string indicating which experiment this branches from. For CMIP6 this should match the short name of the parent experiment id.
- *parent\_experiment\_rip*, a string indicating which member of an ensemble of parent experiment runs this simulation branched from.
- *branch\_time*, time in parent experiment when this simulation started (in the units of the parent experiment).

Note: additional global attributes can be added by the user via the `cmor_set_cur_dataset_attribute` function (see below).

*Coordinate attributes typically provided by a MIP table or generated by CMOR:*

- *standard\_name*, as defined in the CF standard name table.
- *units*, specifying the units for the coordinate variable.
- *axis*, indicating whether axis is of type x, y, z, t, or none of these.
- *bounds*, (when appropriate) indicating where the cell bounds are stored.
- *positive*, (when appropriate) indicating whether a vertical coordinate increases upward or

downward.

- *formula\_terms*, (when appropriate) providing information needed to transform from a dimensionless vertical coordinate to the actual location (e.g., from sigma-level to pressure).
- Coordinate or grid mapping attributes typically provided by the user in a call to a CMOR function:\*
- *calendar*, (when appropriate) indicating the calendar type assumed by the model.
- *grid\_mapping\_name* and the names of various mapping parameters, when necessary to describe grids other than lat-lon. See CF conventions at: <http://cfconventions.org/Data/cf-conventions/cf-conventions-1.7/cf-conventions.html#appendix-grid-mappings> (<http://cfconventions.org/Data/cf-conventions/cf-conventions-1.7/cf-conventions.html#appendix-grid-mappings>)
- Variable attributes typically provided by a MIP table or generated by CMOR:\*
- *standard\_name* as defined in the CF standard name table.
- *units*, specifying the units for the variable.
- *long\_name*, describing the variable and useful as a title on plots.
- *missing\_value* and *\_FillValue*, specifying how missing data will be identified.
- *cell\_methods*, (when appropriate) typically providing information concerning calculation of means or climatologies, which may be supplemented by information provided by the user.
- *cell\_measures*, when appropriate, indicates the names of the variables containing cell areas and volumes.
- *comment*, providing clarifying information concerning the variable (e.g., whether precipitation includes both liquid and solid forms of precipitation).
- *history*, indicating what CMOR has done to the user supplied data (e.g., transforming its units or rearranging its order to be consistent with the MIP requirements)
- *coordinates*, (when appropriate) supplying either scalar (singleton) dimension information or the name of the labels containing names of geographical regions.
- *flag\_values* and *flag\_meanings*
- *modeling\_realm*, providing the realm associated to the variable (ocean, land, aerosol, SeaIce, LandIce, ...)

*Variable attributes typically provided by the user in a call to a CMOR function:*

- *grid\_mapping*
- *original\_name*, containing the name of the variable as it is known at the user's home institution.i\*
- *original\_units*, the units of the data passed to CMOR.
- *history*, (when appropriate) information concerning processing of the variable prior to sending it to CMOR. (This information may be supplemented by further history information generated by CMOR.)

- *comment*, (when appropriate) providing miscellaneous information concerning the variable, which will supplement any comment contained in the MIP table.

As is evident from the above summary of metadata, a substantial fraction of the information is defined in the MIP tables, which explains why writing MIP output through CMOR is much easier than writing data without the help of the MIP tables. Besides the attribute information, the MIP tables also include information that controls the structure of the output and allows CMOR to apply some rudimentary quality assurance checks. Among this ancillary information in the MIP tables is the following:

- The direction each coordinate should be stored when it is output (i.e., either in order of increasing or decreasing values). The user need not be concerned with this since, if necessary, CMOR will reorder the coordinate values and the data.
- The acceptable values for coordinates (e.g., for a pressure coordinate axis, for example, perhaps the WCRP standard pressure levels).
- The acceptable values for various arguments passed to CMOR functions (e.g., acceptable calendars, experiment i.d.'s, etc.)
- The “type” of each output array (whether real, double precision, or integer). The user need not be concerned with this since, if necessary, CMOR will convert the data to the specified type.
- The order of the dimensions for output arrays. The user need not be concerned with this since, if necessary, CMOR will reorder the data consistent with the specified dimension order.
- The normally applied values for “scalar dimensions” (i.e., “singleton dimensions”).
- The range of acceptable values for output arrays.
- The acceptable range for the spatial mean of the absolute value of all elements in output arrays.
- The minimal global attributes required.

[1] CMOR is pronounced “C-more”, which suggests that CMOR should enable a wide community of scientists to “see more” climate data produced by modeling centers around the world. CMOR also reminds us of Ecinae Corianus, the revered ancient Greek scholar, known to his friends as “Seymour”. Seymour spent much of his life translating into Greek nearly all the existing climate data, which had originally been recorded on largely inscrutable hieroglyphic and cuneiform tablets. His resulting volumes, organized in a uniform fashion and in a language readable by the common scientists of the day, provided the basis for much subsequent scholarly research. Ecinae Corianus was later indirectly honored by early inhabitants of the British Isles who reversed the spelling of his name and used the resulting string of letters, grouped differently, to form new words referring to the major elements of climate.

[2] CMOR1 was written in Fortran 90 with access also provided through Python.

[3] See <http://www.cgd.ucar.edu/cms/eaton/cf-metadata>

[4] See <http://my.unidata.ucar.edu/content/software/netcdf/>

[5] “MIP” is an acronym for “model intercomparison project”.

[6] CMOR1 was linked to an earlier version of the netCDF library and udunits was optional.

[7] Cdtime is now built into CMOR. Therefore linking against cdms is no longer necessary.

## Preliminary notes

In the following, all arguments should be passed using keywords (to improve readability and flexibility in ordering the arguments). Those arguments appearing below that are followed by an equal sign may be optional and, if not passed by the user, are assigned the default value that follows the equal sign. The information in a MIP-specific input table determines whether or not an argument shown in brackets is optional or required, and the table provides MIP-specific default values for some parameters. All arguments not in brackets and not followed by an equal sign are always required.

Three versions of each function are shown below. The first one is for Fortran (green text) the second for C (blue text), and the third for Python (orange text). In the following, text that applies to only one of the coding languages appears in the appropriate color.

Some of the arguments passed to CMOR (e.g., names of variables and axes are only unambiguously defined in the context of a specific CMOR table, and in the Fortran version of the functions this is specified by one of the function arguments, whereas in the C and Python versions it is specified through a call to `cmor_load_table` and `cmor_set_table`.

All functions are type “integer”. If a function results in an error, an “exception” will be raised in the Python version (otherwise None will be returned), and in either the Fortran or C versions, the error will be indicated by the integer returned by the function itself. In C an integer other than 0 will be returned, and in Fortran errors will result in a negative integer (except in the case of `cmor_grid`, which will return a positive integer).

If no error is encountered, some functions will return information needed by the user in subsequent calls to CMOR. In almost all cases this information is indicated by the value of a single integer that in Fortran and Python is returned as the value of the function itself, whereas in C it is returned as an output argument). There are two cases in the Fortran version of CMOR, however, when a string argument may be set by CMOR (`cmor_close` and `cmor_create_output_path`). These are the only cases when the value of any of the Fortran function’s arguments might be modified by CMOR.

# CMOR Application program interface (API)

## cmor\_setup()

Fortran: `error_flag = cmor_setup(inpath='./', netcdf_file_action=CMOR_PRESERVE, set_verbosity=CMOR_NORMAL, exit_control=CMOR_NORMAL, logfile, create_subdirectories)`

C: `error_flag = cmor_setup(char *inpath, int *netcdf_file_action, int *set_verbosity, int *exit_control, char *logfile, int *create_subdirectories)`

Python: `setup(inpath='./', netcdf_file_action=CMOR_PRESERVE, set_verbosity=CMOR_NORMAL, exit_control=CMOR_NORMAL, logfile=None, create_subdirectories=1)`

*Description:* Initialize CMOR, specify path to MIP table(s) that will be read by CMOR, specify whether existing output files will be overwritten, and specify how error messages will be handled

### Arguments:

- **[inpath]** = a character string specifying the path to the directory where the needed MIP-specific tables reside.
- **[netcdf\_file\_action]** = controls handling of existing netCDF files. If the value passed is CMOR\_REPLACE, a new file will be created; any existing file with the same name as the one CMOR is trying to create will be overwritten. If the value is CMOR\_APPEND, an existing file will be appended; if the file does not exist, it will be created. If the value is CMOR\_PRESERVE, a new file will be created unless a file by the same name already exists, in which case the program will error exit.[8] To generate a NetCDF file in the "CLASSIC" NetCDF3 format, a "\_3" should be appended to the above parameters (e.g., CMOR\_APPEND would become CMOR\_APPEND\_3). To generate a NetCDF file in the "CLASSIC" NetCDF4 format, a "\_4" should be appended to the above parameters (e.g., CMOR\_APPEND would become CMOR\_APPEND\_4), this allows the user to take advantage of NetCDF4 compression and chunking capabilities. The default values (no underscore) are aliased to the \_4 values (satisfying the requirements of CMIP6).
- **[set\_verbosity]** controls how informational messages and error messages generated by CMOR are handled. If set\_verbosity=CMOR\_NORMAL, errors and warnings will be sent to the standard error device (typically the user's screen). If verbosity=CMOR\_QUIET, then only error messages will be sent (and warnings will be suppressed).
- **[exit\_control]** determines if errors will trigger program to exit:
  - CMOR\_EXIT\_ON\_MAJOR = stop only on critical error;
  - CMOR\_NORMAL = stop only if severe errors;
  - CMOR\_EXIT\_ON\_WARNING = stop even after minor errors detected.
- **[logfile]** where CMOR will write its messages – default is "standard error" (stderr).
- **[create\_subdirectories]** do we want to create the correct path subdirectory structure or simply

dump the files wherever cmor\_dataset will point to.

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: None
- 

**cmor\_dataset\_json()**

Fortran: `cmor_dataset_json(filename)`

C: `cmor_dataset_json(char *name)`

Python: `dataset_json(name)`

*Description:* This function provides information to CMOR that is common to all output files that will be written. The “dataset” defined by this function refers to some or all of the output from a single model simulation (i.e., output from a single realization of a single experiment from a single model). Only one dataset can be defined at any time, but the dataset can be closed (by calling `cmor_close()`), and then another dataset can be defined by calling `cmor_dataset`. Note that after a new dataset is defined, all axes and variables must be defined; axes and variables defined earlier are not associated with the new dataset.

*Arguments:*

- **name:** JSON file which contains all information needed by CMOR in the form of key:value. Here is an example: [CMIP6\\_input\\_example.json](https://github.com/PCMDI/cmip6-cmor-tables/blob/main/Tables/CMIP6_input_example.json) ([https://github.com/PCMDI/cmip6-cmor-tables/blob/main/Tables/CMIP6\\_input\\_example.json](https://github.com/PCMDI/cmip6-cmor-tables/blob/main/Tables/CMIP6_input_example.json))

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: 0
- 

**cmor\_set\_cur\_dataset\_attribute()**

Fortran: `error_flag = cmor_set_cur_dataset_attribute(name,value)`

C: `error_flag = cmor_set_cur_dataset_attribute(char *name, char *value, int optional)`

Python: `set_cur_dataset_attribute(name,value)`

*Description:* Associate a global attribute with the current dataset. In CMIP5, this function can be called to set, for example, “institute\_id”, “initialization” and “physics”.

*Arguments:*

- **name** = name of the global attribute to set.
- **value** = character string containing the value of this attribute.

- **optional** = an argument that is ignored. (Internally, CMOR calls this function and needs this argument.)

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: None
- 

`cmor_get_cur_dataset_attribute()`

Fortran: `error_flag = cmor_get_cur_dataset_attribute(name,result)`

C: `error_flag = cmor_get_cur_dataset_attribute(char *name, char *result)`

Python: `result = get_cur_dataset_attribute(name)`

*Description:* Retrieves a global attribute associated with the current dataset.

*Arguments:*

- **name** = name of the global attribute to retrieve.
- **result** = string (or pointer to a string), which is returned by the function and contains the retrieved global attribute (not for Python).

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: None
- 

`cmor_has_cur_dataset_attribute()`

Fortran: `error_flag = cmor_has_cur_dataset_attribute(name)`

C: `error_flag = cmor_has_cur_dataset_attribute(char *name)`

Python: `error_flag = has_cur_dataset_attribute(name)`

*Description:* Determines whether a global attribute is associated with the current dataset.

*Arguments:*

- **name** = name of the global attribute of interest.

Returns:

- a negative integer if an error is encountered; otherwise returns 0.
  - 0 upon success
  - True if the attribute exists, False otherwise.
-

**cmor\_load\_table()**Fortran: `table_id = cmor_load_table(table)`C: `error_flag = cmor_load_table(char *table, int *table_id)`Python: `table_id = load_table(table)`

*Description:* Loads a table and returns a “handle” (table\_id) to use later when defining CMOR components. CMOR will look for the table first following the path as specified by the “table” argument passed to this function. If it doesn’t find a file there it will prepend the outpath defined in calling cmor\_dataset. If it still doesn’t find it, it will use the “prefix” where the library CMOR is to be installed (from configure time) followed by share (e.g /usr/local/cmor/share). If it stills fails an error will be raised.

---

**cmor\_set\_table()**Fortran: `cmor_set_table(table_id)`C: `error_flag = cmor_set_table(int table_id)`Python: `table_id = set_table(table_id)`

*Description:* Sets the table referred to by table\_id as the table to obtain needed information when defining CMOR components (variables, axes, grids, etc...).

---

**cmor\_axis()**Fortran: `axis_id = cmor_axis([table], table_entry, units, [length], [coord_vals], [cell_bounds], [interval])`C: `error_flag = cmor_axis(int *axis_id, char *table_entry, char *units, int length, void *coord_vals, char type, void *cell_bounds, int cell_bounds_ndim, char *interval)`Python: `axis_id = axis(table_entry, length=??, coord_vals=None, units=None, cell_bounds=None, interval=None)`

*Description:* Define an axis and pass the coordinate values associated with one of the dimensions of the data to be written. This function returns a “handle” (axis\_id) that uniquely identifies the axis to be written. The axis\_id will subsequently be passed by the user to other CMOR functions. The cmor\_axis function will typically be repeatedly invoked to define all axes. The axis specified by the table\_entry argument must be found in the currently “set” CMOR table, as specified by the cmor\_load\_table and cmor\_set\_table functions, or as an option, it can be provided in the Fortran version (for backward compatibility) by the now deprecated “table” keyword argument. There normally is no need to call this function in the case of a singleton (scalar) dimension unless the MIP recommended (or required) coordinate value (or cell\_bounds) are inconsistent with what the user can supply, or unless the user wants to define the “interval” attribute. When defining a time axis in CMOR “Append mode” (in case the file already existed before a call to cmor\_setup), time values and bounds should be set to NULL and instead be passed via cmor\_write when writing data.

*Arguments:*

- **[table]** = character string containing the filename of the MIP-specific table where the axis defined here appears. (e.g., 'CMIP5\_table\_Amon', 'IPCC\_table\_A1', 'AMIP\_table\_1a', 'AMIP\_table\_2', 'CMIP\_table\_2', etc.). In CMOR2 this is an optional argument and is deprecated because the table can be specified through the `cmor_load_table` and `cmor_set_table` functions.
- **axis\_id** = the “handle”: a positive integer returned by CMOR, which uniquely identifies the axis stored in this call to `cmor_axis` and subsequently can be used in calls to `cmor_write`.
- **table\_entry** = name of the axis (as it appears in the MIP table) that will be defined by this function. **units** = units associated with the coordinates passed in `coord_vals` and `cell_bounds`. (These are the units of the user’s coordinate values, which, if CMOR is built with `udunits` (as is required in version 2), may differ from the units of the coordinates written to the netCDF file by CMOR.) These units must be recognized by `udunits` or must be identical to the units specified in the MIP table. In the case of a dimensionless vertical coordinate or in the case of a non-numerical axis (like geographical region), either set `units='none'`, or, optionally, set `units='1'`.
- **[length]** = integer specifying the number of elements that CMOR should extract from the `coord_vals` array (normally length will be the size of the array itself). For a simple “index axis” (i.e., an axis without coordinate values), this specifies the length of the dimension. In the Fortran and Python versions of the function, this argument is not always required (except in the case of a simple index axis); if omitted “length” will be the size of the `coord_vals` array,
- **[coord\_vals]** = 1-d array (single precision float, double precision float, or, for labels, character strings) containing coordinate values, ordered consistently with the data array that will be passed by the user to CMOR through function `cmor_write` (see documentation below). This argument is required except if: 1) the axis is a simple “index axis” (i.e., an axis without coordinate values), or 2) for a time coordinate, the user intends to pass the coordinate values when the `cmor_write` function is called. Note that the coordinate values must be ordered monotonically, so, for example, in the case of longitudes that might have the values, 0., 10., 20, ... 170., 180., 190., 200., ... 340., 350., passing the (equivalent) values, 0., 10., 20, ... 170., 180., -170., -160., ... -20., -10. is forbidden. In the case of time-coordinate values, if `cell_bounds` are also passed, then CMOR will first check that each coordinate value is not outside its associated cell bounds; subsequently, however, the user-defined coordinate value will be replaced by the mid-point of the interval defined by its bounds, and it is this value that will be written to the netCDF file. In the case of character string `coord_vals` there are no `cell_bounds`, but for the C version of the function, the argument `cell_bounds_ndim` is used to specify the length of the strings in the `coord_val` array (i.e., the array will be dimensioned `[length][cell_bounds_ndim]`).
- **type** = type of the `coord_vals/bnds` passed, which can be 'd' (double), 'f' (float), 'l' (long) or 'i' (int).
- **[cell\_bounds]** = 1-d or 2-d array (of the same type as `coord_vals`) containing cell bounds, which should be in the same units as `coord_vals` (specified in the “units” argument above) and should be ordered in the same way as `coord_vals`. In the case of a 1-d array, the size is one more than the size of `coord_vals` and the cells must be contiguous. In the case of a 2-d array, it is dimensioned (2, n) where n is the size of `coord_vals` (see CF standard document, <http://www.cgd.ucar.edu/cms/eaton/cf-metadata>, for further information). This argument may be omitted when cell bounds are not required. It must be omitted if `coord_vals` is omitted.

- **cell\_bounds\_ndim** = This argument only appears in the the C version of this function. Except in the case of a character string axis, it specifies the rank of the cell\_bounds array: if 1, the bounds array will contain n+1 elements, where n is length of coords and the cells must be contiguous, whereas if 2, the dimension will be (n,2) in C order. Pass 0 if no cell\_bounds values have been passed. In the special case of a character string axis, this argument is used to specify the length of the strings in the coord\_val array (i.e., the array will be dimensioned [length] [cell\_bounds\_ndim]).
- **[interval]** = Supplemental information that will be included in the cell\_methods attribute, which is typically defined for the time axis in order to describe the sampling interval. This string should be of the form: “value unit comment: anything” (where “comment:” and anything may always be omitted). For monthly mean data sampled every 15 minutes, for example, interval = “15 minutes”.

Returns:

- **Fortran:** a negative integer if an error is encountered; otherwise returns a positive integer (the “handle”) uniquely identifying the axis ..
  - **C:** 0 upon success.
  - **Python:** upon success, a positive integer (the “handle”) uniquely identifying the axis, or if an error is encountered an exception is raised.
- 

**cmor\_grid()**

**Fortran:** grid\_id = cmor\_grid(axis\_ids, latitude, longitude, [latitude\_vertices], [longitude\_vertices], [area])

**C:** error\_flag = cmor\_grid(int \*grid\_id, int ndims, int \*axis\_ids, char type, void \*latitude, void \*longitude, int nvertices, void \*latitude\_vertices, void \*longitude\_vertices, void \*area)

**Python:** grid\_id = grid( axis\_ids, latitude, longitude, latitude\_vertices=None, longitude\_vertices=None, area=None)

*Description:* Define a grid to be associated with data, including the latitude and longitude arrays. The grid can be structured with up to 6 dimensions. These dimensions, which may be simple “index” axes, must be defined via cmor\_axis prior to calling cmor\_grid. This function returns a “handle” (grid\_id) that uniquely identifies the grid (and its data/metadata) to be written. The grid\_id will subsequently be passed by the user to other CMOR functions. The cmor\_grid function will typically be invoked to define each grid necessary for the experiment (e.g ocean grid, vegetation grid, atmosphere grid, etc...). There is no need to call this function in the case of a Cartesian lat/lon grid. In this case, simply define the latitude and longitude axes and pass their id’s (“handles”) to cmor\_variable.

*Arguments:*

- **grid\_id** = the “handle”: a positive integer returned by CMOR, which uniquely identifies the grid defined in this call to CMOR and subsequently can be used in calls to CMOR.
- **ndims** = number of dimensions needed to define the grid. Namely the number of elements from axis\_ids that will be used.
- **axis\_ids** = array containing the axis\_s returned by cmor\_axis when defining the axes constituting the grid.

- **latitude** = array containing the grid's latitude information (ndim dimensions)
- **longitude** = array containing the grid's longitude information (ndim dimensions)
- **[latitude\_vertices]** = array containing the grid's latitude vertices information (ndim+1 dimensions). The vertices dimension must be the fastest varying dimension of the array (i.e first one in Fortran, last one in C, last one in Python)
- **[longitude\_vertices]** = array containing the grid's longitude vertices information (ndim+1 dimensions). The vertices dimension must be the fastest varying dimension of the array (i.e first one in Fortran, last one in C, last one in Python)
- **[area]** = array containing the grid's area information (ndim)

Returns:

- Fortran: a positive integer if an error is encountered; otherwise returns a negative integer (the "handle") uniquely identifying the grid.
  - C: 0 upon success.
  - Python: upon success, a positive integer (the "handle") uniquely identifying the axis, or if an error is encountered an exception is raised.
- 

**cmor\_set\_grid\_mapping()**

Fortran: `error_flag = cmor_set_grid_mapping(grid_id, mapping_name, parameter_names, parameter_values, parameter_units)`

C: `error_flag = cmor_set_grid_mapping(int grid_id, char *mapping_name, int nparameters, char **parameter_names, int lparameters, double parameter_values[], char **parameter_units, int lunits)`

Python: `set_grid_mapping(grid_id, mapping_name, parameter_names, parameter_values=None, parameter_units=None)`

*Description:* Define the grid mapping parameters associated with a grid (see CF conventions for more info on which parameters to set). Check validity of parameter names and units. Additional mapping names and parameter names can be defined via the MIP table.

*Arguments:*

- **grid\_id** = the "handle" returned by a previous call to `cmor_grid`, indicating which grid the mapping parameters should be associated with.
- **mapping\_name** = name of the mapping (see [CF conventions](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#appendix-grid-mappings) (<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#appendix-grid-mappings>) for a list of grid mapping names). This name dictates which parameters should be set and for some parameters restricts their possible values or range. New mapping names can be added via MIP tables. Below is the list of valid grid mapping names.
  - **albers\_conical\_equal\_area** ([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_albers\\_equal\\_area](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_albers_equal_area))

- **azimuthal\_equidistant**  
(<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#azimuthal-equidistant>)
- **geostationary**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_geostationary\\_projection](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_geostationary_projection))
- **lamert\_azimuthal\_equal\_area**  
(<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#lamert-azimuthal-equal-area>)
- **lamert\_conformal\_conic**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_lamert\\_conformal](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_lamert_conformal))
- **lamert\_cylindrical\_equal\_area**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_lamert\\_cylindrical\\_equal\\_area](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_lamert_cylindrical_equal_area))
- **latitude\_longitude**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_latitude\\_longitude](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_latitude_longitude))
- **mercator**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_mercator](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_mercator))
- **oblique\_mercator**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_oblique\\_mercator](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_oblique_mercator))
- **orthographic**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_orthographic](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_orthographic))
- **polar\_stereographic**  
(<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#polar-stereographic>)
- **rotated\_latitude\_longitude**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_rotated\\_pole](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_rotated_pole))
- **sinusoidal**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_sinusoidal](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_sinusoidal))
- **stereographic**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_stereographic](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_stereographic))
- **transverse\_mercator**

([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_transverse\\_mercator](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_transverse_mercator))

- **vertical\_perspective**  
(<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#vertical-perspective>)
- **nparameters** = number of parameters set.
- **parameter\_names** = array (list for Python) of strings containing the names of the parameters to set. In the case of “standard\_parallel”, CF allows either 1 or 2 parallels to be specified (i.e. the attribute standard\_parallel may be an array of length 2). In the case of 2 parallels, CMOR requires the user to specify these as separate parameters, named standard\_parallel\_1 and standard\_parallel\_2, but then the two parameters will be stored in an array, consistent with CF. In the case of a single parallel, the name standard\_parallel should be specified. In the C version of this function, parameter\_names is declared of length [nparameters][lparameters], where lparameters is the length of each string array element (see below). In Python parameter\_names can be defined as a dictionary containing the keys that represent the parameter\_names. The value associated with each key can be either a list [float, str] (or [str, float]) representing the value/units of each parameter, or another dictionary containing the keys “value” and “units”. If these conditions are fulfilled, then parameter\_units and parameter\_values are optional and would be ignored if passed.
- **lparameters** = length of each element of the string array. If, for example, parameter\_names includes 5 parameters, each 24 characters long (i.e., it is declared [5][24]), you would pass lparameters=24.
- **parameter\_values** = array containing the values associated with each parameter. In Python this is optional if parameter\_names is a dictionary containing the values and units.
- **parameter\_units** = array (list for Python) of string containing the units of the parameters to set. In C parameter\_units is declared of length [nparameters][lunits]. In Python it is optional if parameter\_names is a dictionary containing the value and units.
- **lunits** = length of each elements of the units string array (e.g., if parameters\_units is declared [5][24], you would pass 24 because each elements has 24 characters).

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: None
- 

**cmor\_set\_crs()**

Fortran: error\_flag = cmor\_set\_crs(grid\_id, mapping\_name, parameter\_names, parameter\_values, parameter\_units, text\_parameter\_names, text\_parameter\_values)

```
C: error_flag = cmor_set_crs(int grid_id, char *mapping_name, int nparameters, char
**parameter_names, int lparameters, double parameter_values[], char **parameter_units, int lunits, int
ntextparameters, char **text_parameter_names, int ltextparameters, char *text_parameter_values, int
text_parameter_length[])
```

```
Python: set_crs(grid_id, mapping_name, parameter_names, parameter_values=None,
parameter_units=None)
```

*Description:* Define the Coordinate Reference System (CRS) variable that contains grid mapping parameters associated with a grid (see CF conventions for more info on which parameters to set). Similar to [cmor\\_set\\_grid\\_mapping \(page 16\)](#), but allows for the setting of text-based parameters.

*Note on crs\_wkt :* This function allows for the setting of a `crs_wkt` (<https://cfconventions.org/cf-conventions/cf-conventions.html#use-of-the-crs-well-known-text-format>) text attribute, meant to hold a Well-known Text (WKT) formatted string. However, CMOR will not validate the contents of this string.

*Arguments:*

- **grid\_id** = the “handle” returned by a previous call to `cmor_grid`, indicating which grid the mapping parameters should be associated with.
- **mapping\_name** = name of the mapping (see [CF conventions](#) (<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#appendix-grid-mappings>) for a list of grid mapping names). This name dictates which parameters should be set and for some parameters restricts their possible values or range. New mapping names can be added via MIP tables. Below is the list of valid grid mapping names.
  - [albers\\_conical\\_equal\\_area](#)  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_albers\\_equal\\_area](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_albers_equal_area))
  - [azimuthal\\_equidistant](#)  
(<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#azimuthal-equidistant>)
  - [geostationary](#)  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_geostationary\\_projection](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_geostationary_projection))
  - [lambert\\_azimuthal\\_equal\\_area](#)  
(<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#lambert-azimuthal-equal-area>)
  - [lambert\\_conformal\\_conic](#)  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_lambert\\_conformal](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_lambert_conformal))
  - [lambert\\_cylindrical\\_equal\\_area](#)  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_lambert\\_cylindrical\\_equal\\_area](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_lambert_cylindrical_equal_area))
  - [latitude\\_longitude](#)

- [https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_latitude\\_longitude](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_latitude_longitude))
- **mercator**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_mercator](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_mercator))
- **oblique\_mercator**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_oblique\\_mercator](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_oblique_mercator))
- **orthographic**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_orthographic](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_orthographic))
- **polar\_stereographic**  
(<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#polar-stereographic>)
- **rotated\_latitude\_longitude**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_rotated\\_pole](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_rotated_pole))
- **sinusoidal**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_sinusoidal](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_sinusoidal))
- **stereographic**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_stereographic](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_stereographic))
- **transverse\_mercator**  
([https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#\\_transverse\\_mercator](https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#_transverse_mercator))
- **vertical\_perspective**  
(<https://cfconventions.org/Data/cf-conventions/cf-conventions-1.12/cf-conventions.html#vertical-perspective>)
- **nparameters** = number of parameters set.
- **parameter\_names** = array (list for Python) of strings containing the names of the parameters to set. In the case of “standard\_parallel”, CF allows either 1 or 2 parallels to be specified (i.e. the attribute standard\_parallel may be an array of length 2). In the case of 2 parallels, CMOR requires the user to specify these as separate parameters, named standard\_parallel\_1 and standard\_parallel\_2, but then the two parameters will be stored in an array, consistent with CF. In the case of a single parallel, the name standard\_parallel should be specified. In the C version of this function, parameter\_names is declared of length [nparameters][lparameters], where lparameters is the length of each string array element (see below). In Python, parameter\_names can be defined as a dictionary containing the keys that represent the parameter\_names. The value associated with each key can be either a list [float, str] (or [str, float]) representing the

value/units of each parameter, or another dictionary containing the keys “value” and “units”. If these conditions are fulfilled, then `parameter_units` and `parameter_values` are optional and would be ignored if passed.

- **lparameters** = length of each element of the `parameter_names` string array. If, for example, `parameter_names` includes 5 parameters, each 24 characters long (i.e., it is declared `[5][24]`), you would pass `lparameters=24`.
- **parameter\_values** = array containing the values associated with each parameter. In Python, `parameter_values` is ignored if `parameter_names` is a dictionary containing the values and units.
- **parameter\_units** = array (list for Python) of string containing the units of the parameters to set. In C `parameter_units` is declared of length `[nparameters][lunits]`. In Python, `parameter_units` is ignored if `parameter_names` is a dictionary containing the value and units.
- **lunits** = length of each elements of the units string array (e.g., if `parameters_units` is declared `[5][24]`, you would pass 24 because each elements has 24 characters).
- **ntextparameters** = number of text parameters set.
- **text\_parameter\_names** = array (list for Python) of strings containing the names of the text parameters to set. In the C version of this function, `text_parameter_names` is declared of length `[ntextparameters][ltextparameters]`, where `ltextparameters` is the length of each string array element (see below). In Python, `parameter_names` can be defined as a dictionary containing the keys that represent the text parameter names. The value associated with each key can be a string value of each text parameter.
- **ltextparameters** = length of each element of the `text_parameter_names` string array. If, for example, `text_parameter_names` includes 5 parameters, each 24 characters long (i.e., it is declared `[5][24]`), you would pass `ltextparameters=24`.
- **text\_parameter\_values** = array containing the string values associated with each text parameter. In the C version of this function, this array will contain null-terminated strings that are concatenated end-to-end in the same order as their names in `text_parameter_names` and their lengths in `text_parameter_length`. In Python, `parameter_values` is ignored if `parameter_names` is a dictionary containing the text values.
- **text\_parameter\_length** = array containing the length of each string value in `text_parameter_values`.

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: None
- 

`cmor_time_varying_grid_coordinate()`

**DEPRECATED:** `cmor_time_varying_grid_coordinate` is no longer supported as of CMOR 3.11 and has been removed as of CMOR 3.12.

Fortran: `coord_var_id = cmor_time_varying_grid_coordinate(grid_id, table_entry, units, missing_value)`

C: `error_flag = cmor_time_varying_grid_coordinate(int *coord_var_id, int grid_id, char *table_entry, char *units, char type, void *missing, [int *coordinate_type])`

Python: `coord_var_id = time_varying_grid_coordinate(grid_id, table_entry, units, [missing_value])`

*Description:* Define a grid to be associated with data, including the latitude and longitude arrays. Note that in CMIP5 this function must be called to store the variables called for in the cf3hr MIP table. The grid can be structured with up to 6 dimensions. These dimensions, which may be simple “index” axes, must be defined via `cmor_axis` prior to calling `cmor_grid`. This function returns a “handle” (`grid_id`) that uniquely identifies the grid (and its data/metadata) to be written. The `grid_id` will subsequently be passed by the user to other CMOR functions. The `cmor_grid` function will typically be invoked to define each grid necessary for the experiment (e.g., ocean grid, vegetation grid, atmosphere grid, etc.). There is no need to call this function in the case of a Cartesian lat/lon grid. In this case, simply define the latitude and longitude axes and pass their id’s (“handles”) to `cmor_variable`.

*Arguments:*

- **coord\_var\_id** = the “handle”: a positive integer returned by this function, which uniquely identifies the variable and can be used in subsequent calls to CMOR.
- **grid\_id** = the value returned by `cmor_grid` when the grid was created.
- **table\_entry** = name of the variable (as it appears in the MIP table) that this function defines.
- **units** = units of the data that will be passed to CMOR by function `cmor_write`. These units may differ from the units of the data output by CMOR. Whenever possible, this string should be interpretable by udunits (see <http://my.unitdata.ucar.edu/content/software/udunits/>). In the case of dimensionless quantities the units should be specified consistent with the CF conventions, so for example: percent, units='%'; for a fraction, units='1'; for parts per million, units='1e-6', etc.).
- **type** = type of the `missing_value`, which must be the same as the type of the array that will be passed to `cmor_write`. The options are: 'd' (double), 'f' (float), 'l' (long) or 'i' (int).
- **[missing\_value]** = scalar that is used to indicate missing data for this variable. It must be the same type as the data that will be passed to `cmor_write`. This `missing_value` will in general be replaced by a standard `missing_value` specified in the MIP table. If there are no missing data, and the user chooses not to declare the missing value, then this argument may be omitted.
- **[coordinate\_type]** = place holder for future implementation, unused, pass NULL

*Returns:*

- Fortran: a positive integer if an error is encountered; otherwise returns a negative integer (the “handle”) uniquely identifying the grid.
  - C: 0 upon success.
  - Python: upon success, a positive integer (the “handle”) uniquely identifying the axis, or if an error is encountered an exception is raised.
-

**cmor\_zfactor()**

Fortran: `zfactor_id = cmor_zfactor(zaxis_id, zfactor_name, [axis_ids], [units], zfactor_values, zfactor_bounds)`

C: `error_flag = cmor_zfactor (int *zfactor_id, int zaxis_id, char *zfactor_name, char *units, int ndims, int axis_ids[], char type, void *zfactor_values, void *zfactor_bounds)`

Python: `zfactor_id = zfactor(zaxis_id, zfactor_name, units, axis_ids, data_type, zfactor_values=None, zfactor_bounds=None)`

*Description:* Define a factor needed to convert a non-dimensional vertical coordinate (model level) to a physical location. For pressure, height, or depth, this function is unnecessary, but for dimensionless coordinates it is needed. In the case of atmospheric sigma coordinates, for example, a scalar parameter must be defined indicating the top of the model, and the variable containing the surface pressure must be identified. The parameters that must be defined for different vertical dimensionless coordinates are listed in Appendix D of the CF convention document (<http://www.cgd.ucar.edu/cms/eaton/cf-metadata>). Often bounds for the zfactors will be needed (e.g., for hybrid sigma coordinates, “A’s” and “B’s” must be defined both for the layers and, often more importantly, for the layer interfaces). This function must be invoked for each z-factor required.

*Arguments:*

- **zfactor\_id** = the “handle”: a positive integer returned by this function which uniquely identifies the grid defined in this call to CMOR and can subsequently be used in calls to CMOR.
- **zaxis\_id** = an integer (“handle”) returned by `cmor_axis` (which must have been previously called) indicating which axis requires this factor.
- **zfactor\_name** = name of the z-factor that will be defined by this function. This should correspond to an entry in the MIP table.
- **[axis\_ids]** = an integer array containing the list of `axis_id`’s (individually defined by calls to `cmor_axis`), which the z-factor defined here is a function of (e.g. for surface pressure, the array of i.d.’s would usually include the longitude, latitude, and time axes.) The order of the axes must be consistent with the array passed as `param_values`. If the z-factor parameter is a function of a single dimension (e.g., model level), the single `axis_id` should be passed as an array of rank one and length 1, not as a scalar. If the parameter is a scalar, then this parameter may be omitted. If this parameter is carried on a non-cartesian latitude-longitude grid, then the `grid_id` should be passed instead of `axis_ids`, for latitude/longitude. Again if `axis_ids` collapses to a scalar, it should be passed as an array of rank one and length 1, not as a scalar.
- **[units]** = units associated with the z-factor passed in `zfactor_values` and `zfactor_bounds`. (These are the units of the user’s z-factors, which may differ from the units of the z-factors written to the netCDF file by CMOR.) . These units must be recognized by `udunits` or must be identical to the units specified in the MIP table. In the case of a dimensionless z-factors, either omit this argument, or set `units=""`, or set `units='1'`.
- **type** = type of the `zfactor_values` and `zfactor_bounds` (if present) passed to this function. This can be ‘d’ (double), ‘f’ (float), ‘l’ (long), ‘i’ (int), or ‘c’ (char).

- **[zfactor\_values]** = z-factor values associated with dimensionless vertical coordinate identified by `zaxis_id`. If this z-factor is a function of time (e.g., surface pressure for sigma coordinates), the user can omit this argument and instead store the z-factor values by calling `cmor_write`. In that case the `cmor_write` argument, “`var_id`”, should be set to `zfactor_id` (returned by this function) and the argument, “`store_with`”, should be set to the variable id of the output field that requires zfactor as part of its metadata. When many fields are a function of the (dimensionless) model level, `cmor_write` will have to be called several times, with the same `zfactor_id`, but with different variable ids. If no values are passed, omit this argument.
- **[zfactor\_bounds]** = z-factor values associated with the cell bounds of the vertical dimensionless coordinate. These values should be of the same type as the `zfactor_values` (e.g., if `zfactor_values` is double precision, then `zfactor_bounds` must also be double precision). If no bounds values are passed, omit this argument or set `zfactor = 'none'`. This is a ONE dimensional array of length `nlevs+1`.

Returns:

- Fortran: a negative integer if an error is encountered; otherwise returns a positive integer (the “handle”) uniquely identifying the z-factor.
- C: 0 upon success.
- Python: upon success, a positive integer (the “handle”) uniquely identifying the z-factor, or if an error is encountered an exception is raised.

`cmor_variable()`

Fortran: `var_id = cmor_variable([table], table_entry, units, axis_ids, [missing_value], [tolerance], [positive], [original_name], [history], [comment])`

C: `error_flag = int cmor_variable(int var_id, char *table_entry, char *units, int ndims, int axis_ids[], char type, void *missing, double *tolerance, char *positive, char *original_name, char *history, char *comment)`

Python: `var_id = variable(table_entry, units, axis_ids, data_type='f', missing_value=None, tolerance = 1.e-4, positive=None, original_name=None, history=None, comment=None)`

*Description:* Define a variable to be written by CMOR and indicate which axes are associated with it. This function prepares CMOR to write the file that will contain the data for this variable. This function returns a “handle” (`var_id`), uniquely identifying the variable, which will subsequently be passed as an argument to the `cmor_write` function. The variable specified by the `table_entry` argument must be found in the currently “set” CMOR table, as specified by the `cmor_load_table` and `cmor_set_table` functions, or as an option, it can be provided in the Fortran version (for backward compatibility) by the now deprecated “`table`” keyword argument. The `cmor_variable` function will typically be repeatedly invoked to define other variables. Note that backward compatibility was kept with the Fortran-only optional “`table`” keyword. But it is now recommended to use `cmor_load_table` and `cmor_set_table` instead (and necessary for C/Python).

*Arguments:*

- **var\_id** = the “handle”: a positive integer returned by this function, which uniquely identifies the variable and can be used in subsequent calls to CMOR.

- **[table]** = character string containing the filename of the MIP-specific table where table\_entry (described next) can be found (e.g., “CMIP5\_table\_amon”, ‘IPCC\_table\_A1’, ‘AMIP\_table\_1a’, ‘AMIP\_table\_2’, ‘CMIP\_table\_2’, etc.) In CMOR2 this is an optional argument and is deprecated because the table can be specified through the cmor\_load\_table and cmor\_set\_table functions.
- **table\_entry** = name of the variable (as it appears in the MIP table) that this function defines.
- **units** = units of the data that will be passed to CMOR by function cmor\_write. These units may differ from the units of the data output by CMOR. Whenever possible, this string should be interpretable by udunits (see <http://my.unitdata.ucar.edu/content/software/udunits/>). In the case of dimensionless quantities the units should be specified consistent with the CF conventions, so for example: percent, units='%'; for a fraction, units='1'; for parts per million, units='1e-6', etc.).
- **ndims** = number of axes the variable contains (i.e., the rank of the array), which in fact is the number of elements in the axis\_ids array that will be processed by CMOR.
- **axis\_ids** = 1-d array containing integers returned by cmor\_axis, which specifies, via their “handles” (i.e., axis\_ids), the axes associated with the variable that this function defines. These handles should be ordered consistently with the data that will be passed to CMOR through function cmor\_write (see documentation below). If the size of the 1-d array is larger than the number of dimensions, the ‘unused’ dimension handles must be set to 0. Note that if the handle of a single axis is passed, it must not be passed as a scalar but as a rank 1 array of length 1. Scalar (“singleton”) dimensions defined in the MIP table may be omitted from axis\_ids unless they have been explicitly redefined by the user through calls to cmor\_axis. A “singleton” dimension that has been explicitly defined by the user should appear last in the list of axis\_ids if the array of data passed to cmor\_write for this variable actually omits this dimension; otherwise it should appear consistent with the position of the axis in the array of data passed to cmor\_write. In the case of a non-Cartesian grid, replace the values of the grid specific axes (representing the lat/lon axes) with the single grid\_id returned by cmor\_grid.
- **type** = type of the missing\_value, which must be the same as the type of the array that will be passed to cmor\_write. The options are: ‘d’ (double), ‘f’ (float), ‘l’ (long) or ‘i’ (int).
- **[missing\_value]** = scalar that is used to indicate missing data for this variable. It must be the same type as the data that will be passed to cmor\_write. This missing\_value will in general be replaced by a standard missing\_value specified in the MIP table. If there are no missing data, and the user chooses not to declare the missing value, then this argument may be omitted or assigned the value ‘none’ (i.e., missing\_value='none').
- **[tolerance]** = scalar (type real) indicating fractional tolerance allowed in missing values found in the data. A value will be considered missing if it lies within  $\pm \text{tolerance} * \text{missing\_value}$  of missing\_value. The default tolerance for real and double precision missing values is 1.0e-4 and for integers 0. This argument is ignored if the missing\_value argument is not present.
- **[positive]** = ‘up’ or ‘down’ depending on whether a user-passed vertical energy (heat) flux or surface momentum flux (stress) input to CMOR is positive when it is directed upward or downward, respectively. This information will be used by CMOR to determine whether a sign change is necessary to make the data consistent with the MIP requirements. This argument is required for vertical energy and salt fluxes, for “flux correction” fields, and for surface stress; it is ignored for all other variables.

- **[original\_name]** = the name of the variable as it is commonly known at the user's home institute. If the variable passed to CMOR was computed in some simple way from two or more original fields (e.g., subtracting the upwelling and downwelling fluxes to get a net flux), then it is recommended that this be indicated in the "original\_name" (e.g., "irup – irdown", where "irup" and "irdown" are the names of the original fields that were subtracted). If more complicated processing was required, this information would more naturally be included in a "history" attribute for this variable, described next.
- **[history]** = how the variable was processed before outputting through CMOR (e.g., give name(s) of the file(s) from which the data were read and indicate what calculations were performed, such as interpolating to standard pressure levels or adding 2 fluxes together). This information should allow someone at the user's institute to reproduce the procedure that created the CMOR output. Note that this history attribute is variable-specific, whereas the history attribute defined by `cmor_dataset` provides information concerning the model simulation itself or refers to processing procedures common to all variables (for example, mapping model output from an irregular grid to a Cartesian coordinate grid). Note that when appropriate, CMOR will also indicate in the "history" attribute any operations it performs on the data (e.g., scaling the data, changing the sign, changing its type, reordering the dimensions, reversing a coordinate's direction or offsetting longitude). Any user-defined history will precede the information generated by CMOR.
- **[comment]** = additional notes concerning this variable can be included here.

Returns:

- Fortran: a negative integer if an error is encountered; otherwise returns a positive integer (the "handle") uniquely identifying the variable.
  - C: 0 upon success.
  - Python: upon success, a positive integer (the "handle") uniquely identifying the variable, or if an error is encountered an exception is raised.
- 

`cmor_set_deflate()`

Fortran: `error_flag = cmor_set_deflate(var_id, shuffle, deflate, deflate_level)`

C: `error_flag = cmor_set_deflate(int var_id, int shuffle, int deflate, int deflate_level)`

Python: `set_deflate(var_id, shuffle, deflate, deflate_level)`

*Description:* Sets netCDF4 shuffle and compression on a CMOR variable.

*Arguments:*

- **var\_id** = the cmor variable id
- **shuffle** = if true, turn on netCDF the shuffle filter
- **deflate** = if true, turn on the deflate filter at the level specified by the `deflate_level` parameter
- **deflate\_level** = if the deflate parameter is non-zero, deflate variable using value. Must be between 0 and 9

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: 0
- 

**cmor\_set\_zstandard()**

Fortran: `error_flag = cmor_set_zstandard(var_id, zstandard_level)`

C: `error_flag = cmor_set_zstandard(int var_id, int zstandard_level)`

Python: `set_zstandard(var_id, zstandard_level)`

*Description:* Sets netCDF4 Zstandard compression level on a CMOR variable. CMOR's deflate compression must be disabled (use `cmor_set_deflate` to set to false) to enable the use of Zstandard compression on the netCDF file's data variable.

*Arguments:*

- **var\_id** = the cmor variable id
- **zstandard\_level** = Compression level. Must be between -131072 and 22

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: 0
- 

**cmor\_set\_quantize()**

Fortran: `error_flag = cmor_set_quantize(var_id, quantize_mode, quantize_nsd)`

C: `error_flag = cmor_set_quantize(int var_id, int quantize_mode, int quantize_nsd)`

Python: `set_quantize(var_id, quantize_mode, quantize_nsd)`

*Description:* Sets netCDF4 quantization mode and number of significant digits/bits preserved.

*Arguments:*

- **var\_id** = the cmor variable id
- **quantize\_mode** = Quantization mode. Can be set to the following values.
  - 0: No quantization mode
  - 1: BitGroom
    - Determines the number of bits to retain for the user-requested number of significant decimal digits, and then sets excess bits to zero or one for alternate array values. This method is not recommended since it has poorer

compression ratios and more sharply changing least significant bits than Granular BitRound.

- 2: Granular BitRound (**recommended**)
  - Determines the number to retain for the user-requested number of significant decimal digits for each value in the array, and applies IEEE rounding to the least significant bits. This mode is preferred to BitGroom for retaining the user-specified number of decimal significant digits as it produces a better overall compression ratio and smoother least significant bits than BitGroom.
- 3: BitRound
  - The user directly specifies the number of significant bits to retain, and applies IEEE rounding to the least significant bits. This method is recommended for preserving the user-specified number of significant bits.
- **quantize\_nsd** = Number of significant digits or bits. Its use is dependent on the quantization mode used.
  - 0 (No quantization mode): The value is ignored.
  - 1 (BitGroom) or 2 (Granular BitRound): The value can be set from 1 to 7 digits for floats or 1 to 23 digits for doubles.
  - 3 (BitRound): The value can be set from 1 to 15 bits for floats or 1 to 52 bits for doubles.

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: 0
- 

**cmor\_set\_chunking()**

Fortran: `error_flag = cmor_set_chunking(var_id, chunking_dims)`

C: `error_flag = cmor_set_chunking(int variable_id, int *chunking_dims)`

Python: `set_chunking(var_id, chunking_dims)`

*Description:* Define the NetCDF chunking dimensions of the variable specified by the `variable_id`. The `chunking_dims` parameter must be an array of positive integers that is the same length as the number of axes for the variable. The values in `chunking_dims` follow the order of the variable's list of axes.

Any negative values in `chunking_dims` will make CMOR warn that the value will be replaced with zero.

*Arguments:*

- **variable\_id** = the “handle” returned by `cmor_variable` (when the variable was defined), which will become better described by the attribute defined in this function.
- **chunking\_dims** = an array of chunking dimensions.

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: 0
- 

#### cmor\_set\_variable\_attribute()

Fortran: `error_flag = cmor_set_variable_attribute(integer var_id, character(*) name, character(*) type, character(*) value)`

C: `error_flag = cmor_set_variable_attribute(int variable_id, char *attribute_name, char type, void *value)`

Python: `set_variable_attribute(var_id,name,data_type,value)`

*Description:* Defines an attribute to be associated with the variable specified by the variable\_id. This function is unlikely to be called in preparing CMIP5 output, except to delete the “ext\_cell\_measures” attribute (setting it to a empty string). For this reason you can only set character type attributes at the moment via Python and Fortran.

*Arguments:*

- **variable\_id** = the “handle” returned by cmor\_variable (when the variable was defined), which will become better described by the attribute defined in this function.
- **attribute\_name** = name of the attribute
- **type** = type of the attribute value passed, which can be ‘d’ (double), ‘f’ (float), ‘l’ (long), ‘i’ (int), or ‘c’ (char).
- **value** = whatever value you wish to set the attribute to (type defined by type argument).

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: 0
- 

#### cmor\_get\_variable\_attribute()

Fortran: `error_flag = cmor_get_variable_attribute(integer var_id, character(*) name, character *value)`

C: `error_flag = cmor_get_variable_attribute(int variable_id, char *attribute_name, char type, void *value)`

Python: `get_variable_attribute(var_id,name)`

*Description:* retrieves an attribute value set for the variable specified by the variable\_id. This function is unlikely to be called in preparing CMIP5 output. The Python and Fortran version will only work on attribute of character (string) type, otherwise chaotic results should be expected

*Arguments:*

- **variable\_id** = the “handle” returned by `cmor_variable` (when the variable was defined) identifying which variable the attribute is associated with.
- **attribute\_name** = name of the attribute
- **type** = type of the attribute value to be retrieved. This can be ‘d’ (double), ‘f’ (float), ‘l’ (long), ‘i’ (int), or ‘c’ (char)
- **value** = the argument that will accept the retrieved attribute.

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: The attribute value
- 

### `cmor_has_variable_attribute()`

Fortran: `error_flag = cmor_has_variable_attribute(integer var_id, character(*) name)`

C: `error_flag = cmor_has_variable_attribute(int variable_id, char *attribute_name)`

Python: `has_variable_attribute(var_id,name)`

*Description:* Determines whether an attribute exists and is associated with the variable specified by `variable_id`, which is a handle returned to the user by a previous call to `cmor_variable`. This function is unlikely to be called in preparing CMIP5 output.

*Arguments:*

- **variable\_id** = the “handle” specifying which variable is of interest. A `variable_id` is returned by `cmor_variable` each time a variable is defined.
- **attribute\_name** = name of the attribute of interest.

Returns upon success (i.e., if the attribute is found):

- Fortran: 0
  - C: 0
  - Python: True
- 

### `cmor_create_output_path()`

Fortran: `call cmor_create_output_path(var_id, path)`

C : `isfixed = cmor_create_output_path(int var_id, char *path)`

Python: `path = create_output_path(var_id)`

*Description:* construct the output path, consistent with CMIP5 specifications, where the file will be stored.

*Arguments:*

- **var\_id** = variable identification (as returned from `cmor_variable`) you wish to get the output path for.
- **path** = string (or pointer to a string), which is returned by the function and contains the output path.

Returns:

- Fortran: nothing it is a subroutine
  - C: 0 upon success or 1 if the field is a fixed field
  - Python: the full path to the output file
- 

### `cmor_write()`

Fortran: `error_flag = cmor_write(var_id, data, [file_suffix], [ntimes_passed], [time_vals], [time_bnds], [store_with])`

C: `error_flag = cmor_write(int var_id, void *data, char type, char *file_suffix, int ntimes_passed, double *time_vals, double *time_bounds, int *store_with)`

Python: `write(var_id, data, ntimes_passed=None, file_suffix="", time_vals=None, time_bnds=None, store_with=None)`

*Description:* For the variable identified by `var_id`, write an array of data that includes one or more time samples. This function will typically be repeatedly invoked to write other variables or append additional time samples of data. Note that time-slices of data must be written chronologically.

*Arguments:*

- **var\_id** = integer returned by `cmor_variable` identifying the variable that will be written by this function.
- **data** = array of data written by this function (of rank<8). The rank of this array should either be: (a) consistent with the number of axes that were defined for it, or (b) it should be 1-dimensional, in which case the data must be stored contiguously in memory. In case (a), an exception is that for a variable that is a function of time and when only one “time-slice” is passed, then the array can optionally omit this dimension. Thus, for a variable that is a function of longitude, latitude, and time, for example, if only a single time-slice is passed to `cmor_write`, the rank of array “data” may be declared as either 2 or 3; when declared rank 3, the time-dimension will be size 1. It is recommended (but not required) that the shape of data (i.e., the size of each dimension) be consistent with those expected for this variable (based on the axis definitions), but they are allowed to be larger (the extra values beyond the defined dimension domain will be ignored). In any case the dimension sizes (lengths) must obviously not be smaller than those defined by the calls to `cmor_axis`.
- **type** = type of variable array (“data”), which can be ‘d’ (double), ‘f’ (float), ‘l’ (long) or ‘i’ (int).
- **[file\_suffix]** = string that will be concatenated with a string automatically generated by CMOR to form a unique filename where the output is written. This suffix is only required when a time-sequence of output fields will not all be written into a single file (i.e., two or more files will contain the output for the variable). The file prefix generated by CMOR is of the form

variable\_table, where variable is replaced by table\_entry (i.e., the name of the variable), and table is replaced by the table number (e.g., tas\_A1 refers to surface air temperature as specified in table A1). Permitted characters will be: a-z, A-Z, 0-9, and "-". There are no restrictions on the suffix except that it must yield unique filenames and that it cannot contain any ".". *If the user supplies a suffix, the leading "* should be omitted (e.g., pass '1979-1988', not '\_1979-1988'). Note that the suffix passed through cmor\_write remains in effect for the particular variable until (optionally) redefined by a subsequent call. In the case of CMOR "Append mode" (in case the file already existed before a call to cmor\_setup), then file\_suffix is to be used to point to the original file, this value should reflect the FULL path where the file can be found, not just the file name. CMOR2 will be smart enough to figure out if a suffix was used when creating that file. Note that this file will be first moved to a temporary file and eventually renamed to reflect the additional times written to it.

- **[ntimes\_passed]** = integer number of time slices passed on this call. If omitted, the number will be assumed to be the size of the time dimension of the data (if there is a time dimension).
- **[time\_vals]** = 1-d array (must be double precision) time coordinate values associated with the data array. This argument should appear only if the time coordinate values were not passed in defining the time axis (i.e., in calling cmor\_axis) such as when CMOR is set to "Append mode." The units should be consistent with those passed as an argument to cmor\_axis in defining the time axis. If cell bounds are also passed (see next argument, '[time\_bnds]'), then CMOR will first check that each coordinate value is not outside its associated cell bounds; subsequently, however, the user-defined coordinate value will be replaced by the mid-point of the interval defined by its bounds, and it is this value that will be written to the netCDF file.
- **[time\_bnds]** = 2-d array (must be double precision) containing time bounds, which should be in the same units as time\_vals. If the time\_vals argument is omitted, this argument should also be omitted. The array should be dimensioned (2, n) in Fortran, and (n,2) in C/Python, where n is the size of time\_vals (see CF standard document, <http://www.cgd.ucar.edu/cms/eaton/cf-metadata>, for further information).
- **[store\_with]** = integer returned by cmor\_variable identifying the variable that the zfactor should be stored with. This argument must be defined when and only when writing a z-factor. (See description of the zfactor function above.)

Returns upon success:

- Fortran: 0
  - C: 0
  - Python: None
- 

cmor\_close()

Fortran: error\_flag = cmor\_close(var\_id, file\_name, preserve)

C: error\_flag = cmor\_close(void) or

C: error\_flag = cmor\_close\_variable(int var\_id, char \*file\_name, int \*preserve)

Python: `error_flag` (or if `name=True`, returns the name of the file) = `close(var_id=None, file_name=False, preserve=False)`

*Description:* Close a single file specified by optional argument `var_id`, or if this argument is omitted, close all files created by CMOR (including log files). To be safe, before exiting any program that invokes CMOR, it is best to call this function with the argument omitted. In C to close a single variable, use: `cmor_close_variable(var_id)`. When using this function to close a single file, an additional optional argument (of type "string") can be included, into which will be returned the file name created by CMOR. [In python, the string is returned by the function.] Another additional optional argument can be passed specifying if the variable should be preserved for future use (e.g., if you want to write additional data but to a new file). Note that when `preserve` is true, the original `var_id` is preserved.

*Arguments:*

- **[var\_id]** = the "handle" identifying an individual variable and the associated output file that will be closed by this function.
- **[file\_name]** = a string where the output file name will be stored. The `file_name` is returned only if its `var_id` has been included in the `close_cmor` argument list. This option provides a convenient method for the user to record the filename, which might be needed on a subsequent call to CMOR, for example, in order to append additional time samples to the file.
- **[preserve]** = Do you want to preserve the var definition? (0/1) If true, the original `var_id` is preserved.

*Returns:*

- Fortran: 0 upon success
  - C: 0 upon success
  - Python: None if `file_name=False`, or the name of the file if `file_name=True` and a `var_id` is passed as an argument.
- 

`cmor_get_terminate_signal()`

Fortran: `signal_code = cmor_get_terminate_signal()`

C: `signal_code = cmor_get_terminate_signal()`

Python: `signal_code = get_terminate_signal()`

*Description:* Get the current value of the signal code issue by CMOR's C when encountering a termination error. Initially this is set to -999. If the user does not set it then the first call to `cmor_setup` will set the signal to SIGTERM for C and Python and to SIGINT for FORTRAN. FORTRAN does exit nicely with SIGTERM, hence the different default values

*Returns upon success:*

- Fortran: the current signal code
  - C: the current signal code
  - Python: the current signal code
-

`cmor_set_terminate_signal()`

Fortran: `cmor_set_terminate_signal(signal)`

C: `cmor_set_terminate_signal(int signal)`

Python: `set_terminate_signal(signal)`

*Description:* Set sthe signal code to send uppon termination from an error

*Arguments:*

- **[signal]** = an integer representing the signal code desired
-

# Acknowledgements

## Acknowledgements

Several individuals have supported the development of the CMOR1 software and provided encouragement, including Dean Williams, Dave Bader, and Peter Gleckler. Jonathan Gregory, Jim Boyle, and Bob Drach all provided valuable suggestions on how to simplify or in other ways improve the design of this software, and we particularly appreciate the time they spent reading and thinking about this problem. Jim Boyle additionally helped in a number of other ways, including porting CMOR to various platforms. Brian Eaton provided his usual careful and thoughtful responses to questions about CF compliance. Finally, we appreciate the encouragement expressed by the WGCM for developing CMOR.

The complete rewrite of CMOR, along with the new capabilities added to version 2, was implemented by Charles Doutriaux. We thank Dean Williams, Bob Drach, Renata McCoy, Jim Boyle, and the British Atmospheric Data Center (BADC). We also thank every one of the “early” adopters of CMOR2 who patiently helped us test and debug CMOR2. In particular we would like to thank Jamie Kettleborough from the UK Metoffice, Stephen Pascoe of the British Atmospheric Data Centre, Joerg Wegner of Zentrum für Marine und Atmosphärische Wissenschaften, Yana Malysheva of the Geophysical Fluid Dynamics Laboratory and Alejandro Bodas-Salcedo of UK Metoffice for the many lines of codes, bug fixes, and sample tests they sent our way

Enhancements to CMOR with capabilities added for version 3 were implemented by Denis Nadeau with help from Charles Doutriaux. We thanks Paul Durack and Martin Juckes who provided inputs, enhancement and solutions to improve flexibility. We also thank the “early” users of CMOR3 for their patience and for helping use improving CMOR3.

The code of CMOR is released under the BSD 3-Clause License. For more details, see the [LICENSE](https://github.com/PCMDI/cmor/blob/main/LICENSE) (<https://github.com/PCMDI/cmor/blob/main/LICENSE>) File.

LLNL-CODE-2005936

# PrePARE (deprecated)

## Note

**PrePARE is a legacy application that is no longer supported as of CMOR 3.12 and has been removed as of CMOR 3.13**

In order to use PrePARE please follow these instructions.

- [miniforge/mamba installation \(https://cmor.llnl.gov/mydoc\\_cmor3\\_conda/\)](https://cmor.llnl.gov/mydoc_cmor3_conda/)

PrePARE has been created to validate CMIP6 data before publishing files to ESGF. It may not work properly on CMIP5 files.

## Usage

```
PrePARE [-h] [-l [CWD]] [--variable VARIABLE] [-v] [--table-path TABLE_PATH]
        [--max-processes 4] [--all] [--hide-progress] [--no-text-color]
        [--ignore-dir PYTHON_REGEX] [--include-file PYTHON_REGEX]
        [--exclude-file PYTHON_REGEX]
        input [input ...]
```

where:

- **input** Input CMIP6 netCDF data to validate. If a directory is submitted all netCDF recursively found will be validated independently.
- **-h** Display synopsis of the program.
- **-l, -log** Logfile directory. Default is the working directory. If not, standard output is used. Only available in multiprocessing mode.
- **-variable** Specify geophysical variable name. If not variable is deduced from filename.
- **-v, -version** Version of software.
- **-table-path** Specify the CMIP6 CMOR tables path (JSON file). If not submitted read the CMIP6\_CMOR\_TABLES environment variable if it exists. If a directory is submitted table is deduced from filename (default is “./Tables”).
  - [CMIP6 tables \(https://github.com/PCMDI/cmip6-cmor-tables/\)](https://github.com/PCMDI/cmip6-cmor-tables/)
- **-max-processes** Maximum number of processes to simultaneously validate several files. Set to one seems sequential processing (default). Set to “-1” uses all available resources as returned by “multiprocessing.cpu\_count()”.
- **-all** Show all results. Default only shows error(s) (i.e., file(s) not compliant).

- **–hide-progress** Do not show the percentage of progress / number of files checked while running PrePARE.
- **–no-text-color** Remove text color from output.
- **–ignore-dir** Filter directories NON-matching the regular expression. Default ignores paths with folder name(s) starting with “.”.
- **–exclude-file** Filter files NON-matching the regular expression. Duplicate the flag to set several filters. Default only exclude hidden files (with names not starting with “.”).

## Validation

PrePARE will verify that all attributes in the input file are present and conform to CMIP6 for publication into ESGF. We also recommend running the python program [cfchecker](https://pypi.python.org/pypi/cfchecker) (<https://pypi.python.org/pypi/cfchecker>) created by the University of Reading in the UK to confirm that your file is CF-1 compliant.

- In order to validate all CMIP6 required attributes by PrePARE, a [Controlled Vocabulary file](https://github.com/PCMDI/cmip6-cmor-tables/blob/main/Tables/CMIP6_CV.json) ([https://github.com/PCMDI/cmip6-cmor-tables/blob/main/Tables/CMIP6\\_CV.json](https://github.com/PCMDI/cmip6-cmor-tables/blob/main/Tables/CMIP6_CV.json)) is read by the program where a JSON dictionary called “[required\\_global\\_attributes](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L3)” ([https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6\\_CV.json#L3](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L3)) points to a list of strings. Each element of that list corresponds to a global attribute.
- PrePARE can also use regular expressions to validate the value of the some global attributes. Here is an [example](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L11554-L11555) ([https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6\\_CV.json#L11554-L11555](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L11554-L11555)) used for `variant_label`.
- Institutions and `institution_ids` need to be registered into a list. PrePARE will only accept institutions which have been pre-registered for CMIP6 publication into ESGF. Click [here](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L74) ([https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6\\_CV.json#L74](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L74)) for the list of institutions. If you wish to register your institution write to the [cmor mailing list](#).
- Source and Source ID also need to be registered for CMIP6 publication. Here is the [list](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L125) ([https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6\\_CV.json#L125](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L125)) of registered sources.
- Only experiments found in the Controlled Vocabulary files are accepted for CMIP6 publication. A list of [experiment\\_ids](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L3708) ([https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6\\_CV.json#L3708](https://github.com/PCMDI/cmip6-cmor-tables/blob/a46dcbf17ec5e11af23dc2d55107f5e52afbcade/Tables/CMIP6_CV.json#L3708)) have been pre-defined including mandatory attributes. A warning will be displayed if one experiment attribute is missing or is not properly set by your program.
- `grid` and `nominal_resolution` are mandatory global attributes in CMIP6. PrePARE will make sure that these attributes are conformed to one of the following syntax:

| grid                | nominal_resolution                                                                                                               |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------|
| gs1x1               | 1x1 degree                                                                                                                       |
| gs1x1 or gn0 to gn9 | 1x1 degree                                                                                                                       |
| gs1x1 or gr0 to gr9 | 1x1 degree                                                                                                                       |
| gn0 to gn9          | “5 km” or “10 km” or “25 km” or “50 km” or “100 km” or “250 km” or “500 km” or “1000 km” or “2500 km” or “5000 km” or “10000 km” |
| gr0 to gr9          | “5 km” or “10 km” or “25 km” or “50 km” or “100 km” or “250 km” or “500 km” or “1000 km” or “2500 km” or “5000 km” or “10000 km” |

- PrePARE verifies that the creation date found in the netCDF file is conform to [ISO 8601 \(https://en.wikipedia.org/wiki/ISO\\_8601\)](https://en.wikipedia.org/wiki/ISO_8601) standard.
- The Further Info URL attribute has to be set according to a very specific template. The PrePARE will use global attribute names found in the netCDF input file and replace the corresponding tag found in a template to rebuild proper CMIP6 link. If the reconstructed URL does not correspond to the value found in the input file, PrePARE will display an critical error on the screen.
  - Below is the default template used for the **furtherinfoURL** attribute. Each string found between the “<>” characters correspond to a global attribute. The program will replace these strings with the corresponding global attribute values and add the “.” character between each tag.

```
http://furtherinfo.es-doc.org/<mip_era><institution_id><source_id><experiment_id><sub_experiment_id><variant_label>
```

becomes

```
http://furtherinfo.es-doc.org/CMIP6.CSIRO-BOM.NICAM.piControl.none.r1i1p1f1"
```

- PrePARE will also verify variable attributes necessary for CMIP6 publication. It validates: long\_name, standard\_name, units and missing\_value according the CMIP6 tables information.

# Mamba installation

## Installing Miniforge

- **CMOR 3.16.0 on conda-forge has support for Python 3.11, 3.12, 3.13, and 3.14.**
- Download the [Miniforge installer \(https://conda-forge.org/download/\)](https://conda-forge.org/download/) for your system.
  - CMOR is currently only supported for Linux and macOS x86\_64, and macOS arm64 (Apple Silicon)
- Start the install with the following command

```
bash Miniforge3-$(uname)-$(uname -m).sh
```

## Installing CMOR and PrePARE

- Run the following commands

```
# install cmor
# -----
mamba create -n CMOR -c conda-forge cmor
mamba activate CMOR

# Clone the CMIP6 table to your working directory.
# -----
mkdir CMIP6_work
cd CMIP6_work
git clone https://github.com/PCMDI/cmip6-cmor-tables.git

# Note:
# -----
# UDUNITS2_XML_PATH is set automatically by activating CMOR.
# export UDUNITS2_XML_PATH=${CONDA_PREFIX}/share/udunits/udunits2.xml
#
```

## Testing

- Run the full test suite for C, Fortran, and Python

Clone CMOR code and CMIP6 tables

```
# Clone the CMOR repository to your working directory.
# -----
git clone https://github.com/PCMDI/cmor.git
cd cmor

# Update the CMIP6 tables submodule.
# -----
git submodule init
git submodule update
```

Install gcc and gfortran compilers, HDF5 plugins, and packages for tests. Set up linking environment variable.

Linux:

```
mamba install -n CMOR -c conda-forge gcc_linux-64 gfortran_linux-64 pyfive
udunits2 hdf5plugin
export LD_SHARED_FLAGS="-shared -pthread"
```

For Intel Mac:

```
mamba install -n CMOR -c conda-forge clang_osx-64 gfortran_osx-64 pyfive u
dunits2 hdf5plugin
export LD_SHARED_FLAGS=" -bundle -undefined dynamic_lookup"
```

For Apple Silicon Mac:

```
mamba install -n CMOR -c conda-forge clang_osx-arm64 gfortran_osx-arm64 p
yfive udunits2 hdf5plugin
export LD_SHARED_FLAGS=" -bundle -undefined dynamic_lookup"
```

Build and run tests

```

# Set prefix for configure step.
# -----
export PREFIX=$(python -c "import sys; print(sys.prefix)")

# Configure the Makefile.
# -----
./configure --prefix=$PREFIX --with-python --with-uuid=$PREFIX --with-json-
c=$PREFIX --with-udunits2=$PREFIX --with-netcdf=$PREFIX --enable-verbos
e-test

# Set up HDF5_PLUGIN_PATH environment variable to point the NetCDF librar
y to the zstd filters
# for zstandard compression.
# -----
export HDF5_PLUGIN_PATH="$(python -c 'import hdf5plugin; print(hdf5plugi
n.PLUGINS_PATH)')"

# Run the tests with the Makefile (without rebuilding CMOR).
# -----
make test -o cmor -o python

```

### Mamba environment

- Create your different CMOR environment with mamba.

```

mamba create -n [YOUR_ENV_NAME_HERE] -c conda-forge cmor
mamba activate [YOUR_ENV_NAME_HERE]

```

- [To learn more about mamba environments](https://mamba.readthedocs.io/en/latest/user_guide/concepts.html)  
([https://mamba.readthedocs.io/en/latest/user\\_guide/concepts.html](https://mamba.readthedocs.io/en/latest/user_guide/concepts.html))

### Obtaining Nightly builds

- Create a dedicated environment for nightly (in between releases code):

```

mamba create -n [YOUR_ENV_NAME_HERE] -c pcmdi/label/nightly -c conda-forg
e cmor
mamba activate [YOUR_ENV_NAME_HERE]

```

- Create an environment with compilers for development/testing:

```
mamba create -n [YOUR_ENV_NAME_HERE] -c pcmdi/label/nightly -c conda-forg  
e cmor gcc_linux-64 gfortran_linux-64  
mamba activate [YOUR_ENV_NAME_HERE]
```

# pip installation

## Creating a Python environment

- Create and activate a virtual environment for CMOR.

```
python -m venv cmor_venv
source cmor_venv/bin/activate
python -m pip install --upgrade pip
```

## Installing CMOR with pip

- CMOR is not currently published on PyPI.
- To install a released CMOR wheel with `pip`, download the wheel for your platform and Python version from the [CMOR releases page \(https://github.com/PCMDI/cmor/releases\)](https://github.com/PCMDI/cmor/releases), then install it locally.

```
pip install /path/to/cmor-<version>-<python tag>-<abi tag>-<platform tag>.whl
```

- Install the nightly Python build of CMOR.

```
pip install cmor --extra-index-url https://pcmdi.github.io/cmor
```

## Running CMOR's Python tests

- If you want to run CMOR's Python tests from a source checkout, first install the extra Python packages used by the tests.

```
pip install netcdf4 pyfive hdf5plugin
```

- Point the NetCDF library to the bundled zstandard filter plugins.

```
export HDF5_PLUGIN_PATH="$(python -c 'import hdf5plugin; print(hdf5plugin.PLUGINS_PATH)')"
```

- Clone the CMOR repository with its table submodule.

```
git clone --recursive https://github.com/PCMDI/cmor.git
cd cmor
```

- If you already cloned the repository without submodules, run:

```
git submodule update --init
```

- Run the Python test scripts you want from the repository root. For example:

```
python Test/test_doc.py
python Test/test_cmor_CMIP7.py
```

## Notes

- These instructions install the Python package only. For installing the C and Fortran API, use the [Miniforge/Mamba \(page 0\)](#) or [Source \(GitHub\) \(page 0\)](#) installation instructions.

# Source installation

## Obtaining the CMOR and PrePARE source code and CMIP6 tables

- Clone the repo from gituhb

```
git clone git://github.com/pcmdi/cmor
cd cmor
git submodule init
git submodule update
```

## Installing Miniforge

- **CMOR 3.16.0 has support for Python 3.11, 3.12, 3.13, and 3.14.**
- Download the [Miniforge installer \(https://conda-forge.org/download/\)](https://conda-forge.org/download/) for your system.
  - CMOR is currently only supported for Linux and macOS x86\_64, and macOS arm64 (Apple Silicon)
- Start the install with the following command

```
bash Miniforge3-$(uname)-$(uname -m).sh
```

## Creating the mamba environment with compilers and needed libraries

- Depending on your os mamba brings different compilers

For Linux

```
export CONDA_COMPILERS="gcc_linux-64 gfortran_linux-64"
```

For Intel Mac

```
export CONDA_COMPILERS="clang_osx-64 gfortran_osx-64"
```

For Apple Silicon Mac

```
export CONDA_COMPILERS="clang_osx-arm64 gfortran_osx-arm64"
```

- Run the following command to create the mamba environment for building CMOR

```
mamba create -n cmor_dev -c conda-forge libuuid json-c udunits2 hdf5 libnetcdf openblas netcdf4 numpy openssl python pyfive hdf5plugin $CONDA_COMPILERS
```

- Activate the mamba environment

```
mamba activate cmor_dev
```

### Configuring cmor

- Depending on your OS linking environment variables are different

For Linux

```
export LD_SHARED_FLAGS="-shared -pthread"
```

For Mac

```
export LD_SHARED_FLAGS=" -bundle -undefined dynamic_lookup"
```

- Set the PREFIX

Since your environment can use a different name and its location is system dependent use:

```
export PREFIX=$(python -c "import sys; print(sys.prefix)")
```

- configure cmor:

```
./configure --prefix=$PREFIX --with-python --with-uuid=$PREFIX --with-json-c=$PREFIX --with-udunits2=$PREFIX --with-netcdf=$PREFIX --enable-verbose-test
```

## Building and installing CMOR and PrePARE

- Run

```
make install
```

## Testing the installation

- Set up HDF5\_PLUGIN\_PATH environment variable to point the NetCDF library to the zstd filters for zstandard compression.

```
export HDF5_PLUGIN_PATH="$(python -c 'import hdf5plugin; print(hdf5plugin.PLUGINS_PATH)')"
```

- Run C, Fortran, and Python tests

```
make test
```

# Python Examples

These examples are based on the CMOR repository's [examples/python](https://github.com/PCMDI/cmor/tree/main/examples/python) (<https://github.com/PCMDI/cmor/tree/main/examples/python>) directory. They use one shared CMIP7 user input file and load CMIP7 tables from a local clone of [WCRP-CMIP/cmip7-cmor-tables](https://github.com/WCRP-CMIP/cmip7-cmor-tables) (<https://github.com/WCRP-CMIP/cmip7-cmor-tables>).

Install CMOR with conda:

```
conda install -c conda-forge cmor
```

or with pip:

```
pip install cmor --extra-index-url https://pcmdi.github.io/cmor
```

Run the examples from a working directory that contains the `cmip7-cmor-tables` repository:

```
git clone https://github.com/WCRP-CMIP/cmip7-cmor-tables.git
python /path/to/example_01_usual_2d_field.py
```

The examples expect tables under `./cmip7-cmor-tables/tables`. To use a different location, set `CMOR_TABLES_PATH` to the directory containing the CMIP7 table JSON files. Each example also accepts `--output-dir` to choose where CMOR writes NetCDF output.

Each example builds the CMIP7 compound variable name and uses it to read `CMIP7_cell_measures.json` and `CMIP7_long_name_overrides.json` before writing data.

## CMOR Input Files

- [CMIP7\\_input\\_example.json](#) (page 0)
- [CMIP7\\_coordinate.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_coordinate.json)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_coordinate.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_coordinate.json))
- [CMIP7\\_formula\\_terms.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_formula_terms.json)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_formula\\_terms.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_formula_terms.json))
- [CMIP7\\_cell\\_measures.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_cell_measures.json)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_cell\\_measures.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_cell_measures.json))
- [CMIP7\\_long\\_name\\_overrides.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_long_name_overrides.json)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_long\\_name\\_overrides.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_long_name_overrides.json))

- [cmor-cvs.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables-cvs/cmor-cvs.json)  
(<https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables-cvs/cmor-cvs.json>)

**Click to expand shared JSON input**

```
{
  "_AXIS_ENTRY_FILE": "CMIP7_coordinate.json",
  "_FORMULA_VAR_FILE": "CMIP7_formula_terms.json",
  "_cmip7_option": 1,
  "_controlled_vocabulary_file": "../tables-cvs/cmor-cvs.json",
  "activity_id": "CMIP",
  "archive_id": "WCRP",
  "calendar": "360_day",
  "experiment_id": "amip",
  "forcing_index": "f1",
  "frequency": "mon",
  "grid_label": "g999",
  "host_collection": "CMIP7",
  "initialization_index": "i1",
  "institution_id": "MOHC",
  "license_id": "CC-BY-4.0",
  "nominal_resolution": "100 km",
  "outpath": "output",
  "physics_index": "p1",
  "realization_index": "r1",
  "region": "glb",
  "source_id": "ACCESS-ESM1-6"
}
```

#### Example 1: Usual Treatment of a 2-D Field

- [example\\_01\\_usual\\_2d\\_field.py](#) (page 0)

**Click to expand Python code**

```
#!/usr/bin/env python3

from __future__ import annotations

import argparse
import json
import os
from pathlib import Path

import cmor
import numpy as np

EXAMPLE_DIR = Path(__file__).resolve().parent
RUN_DIR = Path.cwd()
DEFAULT_TABLES_PATH = RUN_DIR / "cmip7-cmor-tables" / "tables"
TABLES_PATH = Path(os.environ.get("CMOR_TABLES_PATH", DEFAULT_TABLES_PATH))
INPUT_PATH = EXAMPLE_DIR.parent / "CMIP7_input_example.json"

def configure(
    output_dir: Path,
    frequency: str = "mon",
    realization_index: str = "r1",
    forcing_index: str = "f1",
) -> None:
    output_dir.mkdir(parents=True, exist_ok=True)
    user_input = json.loads(INPUT_PATH.read_text())
    user_input["outpath"] = str(output_dir)
    user_input["frequency"] = frequency
    user_input["realization_index"] = realization_index
    user_input["forcing_index"] = forcing_index
    input_path = output_dir / "CMIP7_input_example.json"
    input_path.write_text(json.dumps(user_input, indent=2, sort_keys=True))
    cmor.setup(inpath=str(TABLES_PATH), netcdf_file_action=cmor.CMOR_REPLACE)
    cmor.dataset_json(str(input_path))

def apply_cmip7_variable_metadata(
    var_id: int,
    realm: str,
    table_entry: str,
    frequency: str,
    region: str,
) -> str:
    compound_name = ".".join(
        [realm] + table_entry.split("_") + [frequency, region]
    )

    with (TABLES_PATH / "CMIP7_cell_measures.json").open() as handle:
        cell_measures = json.load(handle)["cell_measures"]
```

```

    cmor.set_variable_attribute(
        var_id,
        "cell_measures",
        "c",
        cell_measures.get(compound_name, ""),
    )

    with (TABLES_PATH / "CMIP7_long_name_overrides.json").open() as handle:
        long_name_overrides = json.load(handle)["long_name_overrides"]
    if compound_name in long_name_overrides:
        cmor.set_variable_attribute(
            var_id,
            "long_name",
            "c",
            long_name_overrides[compound_name],
        )

    return compound_name


def write_example(output_dir: Path) -> str:
    configure(output_dir)
    cmor.load_table("CMIP7_ocean.json")
    lat_id = cmor.axis(
        "latitude",
        "degrees_north",
        coord_vals=np.array([10.0, 20.0, 30.0], dtype="d"),
        cell_bounds=np.array([5.0, 15.0, 25.0, 35.0], dtype="d"),
    )
    lon_id = cmor.axis(
        "longitude",
        "degrees_east",
        coord_vals=np.array([0.0, 90.0, 180.0, 270.0], dtype="d"),
        cell_bounds=np.array([-45.0, 45.0, 135.0, 225.0, 315.0], dtype="d"),
    )
    time_id = cmor.axis(
        "time",
        "days since 1979-01-01",
        coord_vals=np.array([15.5, 45.5], dtype="d"),
        cell_bounds=np.array([0.0, 31.0, 60.0], dtype="d"),
    )
    data = np.array(
        [
            [254.0895, 258.4085, 1.0e20, 258.7101],
            [258.6680, 258.2990, 1.0e20, 255.0432],
            [253.7254, 251.2460, 1.0e20, 255.4808],
            [254.0995, 258.5085, 1.0e20, 258.8101],
            [258.8680, 258.4990, 1.0e20, 255.2432],
            [254.0254, 251.5460, 1.0e20, 255.7808],
        ],
    ),

```

```
        dtype="f4",
    ).reshape(2, 3, 4)
    var_id = cmor.variable(
        "tos_tavg-u-hxy-sea",
        "degC",
        [time_id, lat_id, lon_id],
        missing_value=1.0e20,
    )
    apply_cmip7_variable_metadata(
        var_id,
        "ocean",
        "tos_tavg-u-hxy-sea",
        "mon",
        "glb",
    )
    cmor.write(var_id, data)
    path = cmor.close(var_id, file_name=True)
    cmor.close()
    return path

def main() -> None:
    parser = argparse.ArgumentParser(
        description="Write CMIP7 example 1 with CMOR."
    )
    parser.add_argument(
        "--output-dir",
        type=Path,
        default=Path(__file__).resolve().parent / "output",
    )
    args = parser.parse_args()
    print(write_example(args.output_dir))

if __name__ == "__main__":
    main()
```

**Click to expand NetCDF dump**

```

netcdf tos_tavg-u-hxy-sea_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902
{
dimensions:
    time = UNLIMITED ; // (2 currently)
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float tos(time, lat, lon) ;
        tos:standard_name = "sea_surface_temperature" ;
        tos:long_name = "Sea Surface Temperature" ;
        tos:units = "degC" ;
        tos:cell_methods = "area: mean where sea time: mean" ;
        tos:missing_value = 1.e+20f ;
        tos:_FillValue = 1.e+20f ;
        tos:cell_measures = "area: areacello" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "sea" ;
    :branded_variable = "tos_tavg-u-hxy-sea" ;
    :branding_suffix = "tavg-u-hxy-sea" ;
    :creation_date = "2026-09-14T18:13:50Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;

```

```

:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacello" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:13:50Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "ocean" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_ocean.json; Creation Date:(2026-07-21
13:16:24) MD5:734c6f53560fa60b7c1c21b38e5b9a3f" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/aa165c13-7897-4667-abe7-814822d880a
9" ;
:variable_id = "tos" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:
    time = 15.5, 45.5 ;

```

```
time_bnds =  
    0, 31,  
    31, 60 ;  
  
lat = 10, 20, 30 ;  
  
lat_bnds =  
    5, 15,  
    15, 25,  
    25, 35 ;  
  
lon = 0, 90, 180, 270 ;  
  
lon_bnds =  
    -45, 45,  
    45, 135,  
    135, 225,  
    225, 315 ;  
  
tos =  
    254.0895, 258.4085, _, 258.7101,  
    258.668, 258.299, _, 255.0432,  
    253.7254, 251.246, _, 255.4808,  
    254.0995, 258.5085, _, 258.8101,  
    258.868, 258.499, _, 255.2432,  
    254.0254, 251.546, _, 255.7808 ;  
}
```

### Example 2: Usual Treatment of a 3-D Field on Pressure Levels

- [example\\_02\\_pressure\\_levels.py](#) (page 0)

**Click to expand Python code**

```
#!/usr/bin/env python3

from __future__ import annotations

import argparse
import json
import os
from pathlib import Path

import cmor
import numpy as np

EXAMPLE_DIR = Path(__file__).resolve().parent
RUN_DIR = Path.cwd()
DEFAULT_TABLES_PATH = RUN_DIR / "cmip7-cmor-tables" / "tables"
TABLES_PATH = Path(os.environ.get("CMOR_TABLES_PATH", DEFAULT_TABLES_PATH))
INPUT_PATH = EXAMPLE_DIR.parent / "CMIP7_input_example.json"

def configure(
    output_dir: Path,
    frequency: str = "mon",
    realization_index: str = "r1",
    forcing_index: str = "f1",
) -> None:
    output_dir.mkdir(parents=True, exist_ok=True)
    user_input = json.loads(INPUT_PATH.read_text())
    user_input["outpath"] = str(output_dir)
    user_input["frequency"] = frequency
    user_input["realization_index"] = realization_index
    user_input["forcing_index"] = forcing_index
    input_path = output_dir / "CMIP7_input_example.json"
    input_path.write_text(json.dumps(user_input, indent=2, sort_keys=True))
    cmor.setup(inpath=str(TABLES_PATH), netcdf_file_action=cmor.CMOR_REPLACE)
    cmor.dataset_json(str(input_path))

def apply_cmip7_variable_metadata(
    var_id: int,
    realm: str,
    table_entry: str,
    frequency: str,
    region: str,
) -> str:
    compound_name = ".".join(
        [realm] + table_entry.split("_") + [frequency, region]
    )

    with (TABLES_PATH / "CMIP7_cell_measures.json").open() as handle:
        cell_measures = json.load(handle)["cell_measures"]
```

```

    cmor.set_variable_attribute(
        var_id,
        "cell_measures",
        "c",
        cell_measures.get(compound_name, ""),
    )

    with (TABLES_PATH / "CMIP7_long_name_overrides.json").open() as handle:
        long_name_overrides = json.load(handle)["long_name_overrides"]
    if compound_name in long_name_overrides:
        cmor.set_variable_attribute(
            var_id,
            "long_name",
            "c",
            long_name_overrides[compound_name],
        )

    return compound_name


def write_example(output_dir: Path) -> str:
    configure(output_dir)
    cmor.load_table("CMIP7_atmos.json")
    lat_id = cmor.axis(
        "latitude",
        "degrees_north",
        coord_vals=np.array([10.0, 20.0, 30.0], dtype="d"),
        cell_bounds=np.array([5.0, 15.0, 25.0, 35.0], dtype="d"),
    )
    lon_id = cmor.axis(
        "longitude",
        "degrees_east",
        coord_vals=np.array([0.0, 90.0, 180.0, 270.0], dtype="d"),
        cell_bounds=np.array([-45.0, 45.0, 135.0, 225.0, 315.0], dtype="d"),
    )
    time_id = cmor.axis(
        "time",
        "days since 1979-01-01",
        coord_vals=np.array([15.5, 45.5], dtype="d"),
        cell_bounds=np.array([0.0, 31.0, 60.0], dtype="d"),
    )
    plev_id = cmor.axis(
        "plev19",
        "Pa",
        coord_vals=np.array(
            [
                100000.0,
                92500.0,
                85000.0,
                70000.0,
            ]
        )
    )

```

```

        60000.0,
        50000.0,
        40000.0,
        30000.0,
        25000.0,
        20000.0,
        15000.0,
        10000.0,
        7000.0,
        5000.0,
        3000.0,
        2000.0,
        1000.0,
        500.0,
        100.0,
    ],
    dtype="d",
),
)
var_id = cmor.variable(
    "ta_tavg-p19-hxy-air",
    "K",
    [time_id, plev_id, lat_id, lon_id],
    missing_value=1.0e20,
)
apply_cmip7_variable_metadata(
    var_id,
    "atmos",
    "ta_tavg-p19-hxy-air",
    "mon",
    "glb",
)
data = np.linspace(
    250.0,
    275.0,
    2 * 19 * 3 * 4,
    dtype="f4",
).reshape(2, 19, 3, 4)
data[0, 0, 0, 0] = np.float32(1.0e20)
cmor.write(var_id, data)
path = cmor.close(var_id, file_name=True)
cmor.close()
return path

def main() -> None:
    parser = argparse.ArgumentParser(
        description="Write CMIP7 example 2 with CMOR."
    )
    parser.add_argument(

```

```
        "--output-dir",
        type=Path,
        default=Path(__file__).resolve().parent / "output",
    )
    args = parser.parse_args()
    print(write_example(args.output_dir))

if __name__ == "__main__":
    main()
```

**Click to expand NetCDF dump**

```

netcdf ta_tavg-p19-hxy-air_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-19790
2 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    plev = 19 ;
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double plev(plev) ;
        plev:units = "Pa" ;
        plev:axis = "Z" ;
        plev:positive = "down" ;
        plev:long_name = "Pressure Levels (19)" ;
        plev:standard_name = "air_pressure" ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float ta(time, plev, lat, lon) ;
        ta:standard_name = "air_temperature" ;
        ta:long_name = "Air Temperature" ;
        ta:units = "K" ;
        ta:cell_methods = "area: time: mean where air" ;
        ta:missing_value = 1.e+20f ;
        ta:_FillValue = 1.e+20f ;
        ta:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;

```

```

:area_label = "air" ;
:branded_variable = "ta_tavg-p19-hxy-air" ;
:branding_suffix = "tavg-p19-hxy-air" ;
:creation_date = "2026-09-14T18:13:51Z" ;
:data_specs_version = "MIP-DS7.1.0.0" ;
:description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacella" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:13:51Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/f121f6a6-09d5-4504-8332-46f8a68d1f8
6" ;
:variable_id = "ta" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "p19" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and

```

```

fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
        :cmor_version = "3.15.3" ;
data:

time = 15.5, 45.5 ;

time_bnds =
    0, 31,
    31, 60 ;

plev = 100000, 92500, 85000, 70000, 60000, 50000, 40000, 30000, 25000,
    20000, 15000, 10000, 7000, 5000, 3000, 2000, 1000, 500, 100 ;

lat = 10, 20, 30 ;

lat_bnds =
    5, 15,
    15, 25,
    25, 35 ;

lon = 0, 90, 180, 270 ;

lon_bnds =
    -45, 45,
    45, 135,
    135, 225,
    225, 315 ;

ta =
    _, 250.0549, 250.1099, 250.1648,
    250.2198, 250.2747, 250.3297, 250.3846,
    250.4396, 250.4945, 250.5495, 250.6044,
    250.6593, 250.7143, 250.7692, 250.8242,
    250.8791, 250.9341, 250.989, 251.044,
    251.0989, 251.1538, 251.2088, 251.2637,
    251.3187, 251.3736, 251.4286, 251.4835,
    251.5385, 251.5934, 251.6483, 251.7033,
    251.7582, 251.8132, 251.8681, 251.9231,
    251.978, 252.033, 252.0879, 252.1429,
    252.1978, 252.2527, 252.3077, 252.3626,
    252.4176, 252.4725, 252.5275, 252.5824,
    252.6374, 252.6923, 252.7473, 252.8022,
    252.8571, 252.9121, 252.967, 253.022,
    253.0769, 253.1319, 253.1868, 253.2418,
    253.2967, 253.3517, 253.4066, 253.4615,
    253.5165, 253.5714, 253.6264, 253.6813,
    253.7363, 253.7912, 253.8462, 253.9011,
    253.956, 254.011, 254.0659, 254.1209,

```

254.1758, 254.2308, 254.2857, 254.3407,  
254.3956, 254.4505, 254.5055, 254.5604,  
254.6154, 254.6703, 254.7253, 254.7802,  
254.8352, 254.8901, 254.9451, 255,  
255.0549, 255.1099, 255.1648, 255.2198,  
255.2747, 255.3297, 255.3846, 255.4396,  
255.4945, 255.5495, 255.6044, 255.6593,  
255.7143, 255.7692, 255.8242, 255.8791,  
255.9341, 255.989, 256.0439, 256.0989,  
256.1538, 256.2088, 256.2637, 256.3187,  
256.3736, 256.4286, 256.4835, 256.5385,  
256.5934, 256.6483, 256.7033, 256.7582,  
256.8132, 256.8681, 256.9231, 256.978,  
257.033, 257.0879, 257.1429, 257.1978,  
257.2527, 257.3077, 257.3626, 257.4176,  
257.4725, 257.5275, 257.5824, 257.6374,  
257.6923, 257.7473, 257.8022, 257.8571,  
257.9121, 257.967, 258.022, 258.0769,  
258.1319, 258.1868, 258.2418, 258.2967,  
258.3517, 258.4066, 258.4615, 258.5165,  
258.5714, 258.6264, 258.6813, 258.7363,  
258.7912, 258.8462, 258.9011, 258.9561,  
259.011, 259.0659, 259.1209, 259.1758,  
259.2308, 259.2857, 259.3407, 259.3956,  
259.4506, 259.5055, 259.5604, 259.6154,  
259.6703, 259.7253, 259.7802, 259.8352,  
259.8901, 259.9451, 260, 260.0549,  
260.1099, 260.1648, 260.2198, 260.2747,  
260.3297, 260.3846, 260.4396, 260.4945,  
260.5494, 260.6044, 260.6593, 260.7143,  
260.7692, 260.8242, 260.8791, 260.9341,  
260.989, 261.0439, 261.0989, 261.1538,  
261.2088, 261.2637, 261.3187, 261.3736,  
261.4286, 261.4835, 261.5385, 261.5934,  
261.6483, 261.7033, 261.7582, 261.8132,  
261.8681, 261.9231, 261.978, 262.033,  
262.0879, 262.1429, 262.1978, 262.2527,  
262.3077, 262.3626, 262.4176, 262.4725,  
262.5275, 262.5824, 262.6374, 262.6923,  
262.7473, 262.8022, 262.8571, 262.9121,  
262.967, 263.022, 263.0769, 263.1319,  
263.1868, 263.2418, 263.2967, 263.3517,  
263.4066, 263.4615, 263.5165, 263.5714,  
263.6264, 263.6813, 263.7363, 263.7912,  
263.8462, 263.9011, 263.9561, 264.011,  
264.0659, 264.1209, 264.1758, 264.2308,  
264.2857, 264.3407, 264.3956, 264.4506,  
264.5055, 264.5604, 264.6154, 264.6703,  
264.7253, 264.7802, 264.8352, 264.8901,  
264.9451, 265, 265.0549, 265.1099,

```
265.1648, 265.2198, 265.2747, 265.3297,  
265.3846, 265.4396, 265.4945, 265.5494,  
265.6044, 265.6593, 265.7143, 265.7692,  
265.8242, 265.8791, 265.9341, 265.989,  
266.0439, 266.0989, 266.1538, 266.2088,  
266.2637, 266.3187, 266.3736, 266.4286,  
266.4835, 266.5385, 266.5934, 266.6483,  
266.7033, 266.7582, 266.8132, 266.8681,  
266.9231, 266.978, 267.033, 267.0879,  
267.1429, 267.1978, 267.2527, 267.3077,  
267.3626, 267.4176, 267.4725, 267.5275,  
267.5824, 267.6374, 267.6923, 267.7473,  
267.8022, 267.8571, 267.9121, 267.967,  
268.022, 268.0769, 268.1319, 268.1868,  
268.2418, 268.2967, 268.3517, 268.4066,  
268.4615, 268.5165, 268.5714, 268.6264,  
268.6813, 268.7363, 268.7912, 268.8462,  
268.9011, 268.9561, 269.011, 269.0659,  
269.1209, 269.1758, 269.2308, 269.2857,  
269.3407, 269.3956, 269.4506, 269.5055,  
269.5604, 269.6154, 269.6703, 269.7253,  
269.7802, 269.8352, 269.8901, 269.9451,  
270, 270.0549, 270.1099, 270.1648,  
270.2198, 270.2747, 270.3297, 270.3846,  
270.4396, 270.4945, 270.5494, 270.6044,  
270.6593, 270.7143, 270.7692, 270.8242,  
270.8791, 270.9341, 270.989, 271.0439,  
271.0989, 271.1538, 271.2088, 271.2637,  
271.3187, 271.3736, 271.4286, 271.4835,  
271.5385, 271.5934, 271.6483, 271.7033,  
271.7582, 271.8132, 271.8681, 271.9231,  
271.978, 272.033, 272.0879, 272.1429,  
272.1978, 272.2527, 272.3077, 272.3626,  
272.4176, 272.4725, 272.5275, 272.5824,  
272.6374, 272.6923, 272.7473, 272.8022,  
272.8571, 272.9121, 272.967, 273.022,  
273.0769, 273.1319, 273.1868, 273.2418,  
273.2967, 273.3517, 273.4066, 273.4615,  
273.5165, 273.5714, 273.6264, 273.6813,  
273.7363, 273.7912, 273.8462, 273.9011,  
273.9561, 274.011, 274.0659, 274.1209,  
274.1758, 274.2308, 274.2857, 274.3407,  
274.3956, 274.4506, 274.5055, 274.5604,  
274.6154, 274.6703, 274.7253, 274.7802,  
274.8352, 274.8901, 274.9451, 275 ;  
}
```

### Example 3: Treatment of a Scalar Dimension

- [example\\_03\\_scalar\\_dimension.py \(page 0\)](#)

**Click to expand Python code**

```
#!/usr/bin/env python3

from __future__ import annotations

import argparse
import json
import os
from pathlib import Path

import cmor
import numpy as np

EXAMPLE_DIR = Path(__file__).resolve().parent
RUN_DIR = Path.cwd()
DEFAULT_TABLES_PATH = RUN_DIR / "cmip7-cmor-tables" / "tables"
TABLES_PATH = Path(os.environ.get("CMOR_TABLES_PATH", DEFAULT_TABLES_PATH))
INPUT_PATH = EXAMPLE_DIR.parent / "CMIP7_input_example.json"

def configure(
    output_dir: Path,
    frequency: str = "mon",
    realization_index: str = "r1",
    forcing_index: str = "f1",
) -> None:
    output_dir.mkdir(parents=True, exist_ok=True)
    user_input = json.loads(INPUT_PATH.read_text())
    user_input["outpath"] = str(output_dir)
    user_input["frequency"] = frequency
    user_input["realization_index"] = realization_index
    user_input["forcing_index"] = forcing_index
    input_path = output_dir / "CMIP7_input_example.json"
    input_path.write_text(json.dumps(user_input, indent=2, sort_keys=True))
    cmor.setup(inpath=str(TABLES_PATH), netcdf_file_action=cmor.CMOR_REPLACE)
    cmor.dataset_json(str(input_path))

def apply_cmip7_variable_metadata(
    var_id: int,
    realm: str,
    table_entry: str,
    frequency: str,
    region: str,
) -> str:
    compound_name = ".".join(
        [realm] + table_entry.split("_") + [frequency, region]
    )

    with (TABLES_PATH / "CMIP7_cell_measures.json").open() as handle:
        cell_measures = json.load(handle)["cell_measures"]
```

```

    cmor.set_variable_attribute(
        var_id,
        "cell_measures",
        "c",
        cell_measures.get(compound_name, ""),
    )

    with (TABLES_PATH / "CMIP7_long_name_overrides.json").open() as handle:
        long_name_overrides = json.load(handle)["long_name_overrides"]
    if compound_name in long_name_overrides:
        cmor.set_variable_attribute(
            var_id,
            "long_name",
            "c",
            long_name_overrides[compound_name],
        )

    return compound_name


def write_example(output_dir: Path) -> str:
    configure(output_dir, realization_index="r9", forcing_index="f2")
    cmor.load_table("CMIP7_atmos.json")
    lat_id = cmor.axis(
        "latitude",
        "degrees_north",
        coord_vals=np.array([10.0, 20.0, 30.0], dtype="d"),
        cell_bounds=np.array([5.0, 15.0, 25.0, 35.0], dtype="d"),
    )
    lon_id = cmor.axis(
        "longitude",
        "degrees_east",
        coord_vals=np.array([0.0, 90.0, 180.0, 270.0], dtype="d"),
        cell_bounds=np.array([-45.0, 45.0, 135.0, 225.0, 315.0], dtype="d"),
    )
    time_id = cmor.axis(
        "time",
        "days since 1979-01-01",
        coord_vals=np.array([15.5, 45.5], dtype="d"),
        cell_bounds=np.array([0.0, 31.0, 60.0], dtype="d"),
    )
    height_id = cmor.axis(
        "height2m",
        "m",
        coord_vals=np.array([2.0], dtype="d"),
    )
    var_id = cmor.variable(
        "tas_tavg-h2m-hxy-u",
        "K",
        [time_id, lat_id, lon_id, height_id],
    )

```

```
        missing_value=1.0e20,
    )
    apply_cmip7_variable_metadata(
        var_id,
        "atmos",
        "tas_tavg-h2m-hxy-u",
        "mon",
        "glb",
    )
    data = np.array(
        [
            254.0895,
            258.4085,
            250.5549,
            258.7101,
            258.6680,
            258.2990,
            252.1237,
            255.0432,
            253.7254,
            251.2460,
            254.3168,
            255.4808,
            259.7908,
            252.2754,
            257.1892,
            253.3132,
            253.8823,
            253.4698,
            253.5381,
            254.9730,
            256.1002,
            251.8168,
            259.3698,
            250.2994,
        ],
        dtype="f4",
    ).reshape(2, 3, 4, 1)
    cmor.write(var_id, data)
    path = cmor.close(var_id, file_name=True)
    cmor.close()
    return path

def main() -> None:
    parser = argparse.ArgumentParser(
        description="Write CMIP7 example 3 with CMOR."
    )
    parser.add_argument(
        "--output-dir",
```

```
        type=Path,
        default=Path(__file__).resolve().parent / "output",
    )
    args = parser.parse_args()
    print(write_example(args.output_dir))

if __name__ == "__main__":
    main()
```

**Click to expand NetCDF dump**

```

netcdf tas_tavg-h2m-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r9i1p1f2_197901-197902
{
dimensions:
    time = UNLIMITED ; // (2 currently)
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    double height ;
        height:units = "m" ;
        height:axis = "Z" ;
        height:positive = "up" ;
        height:long_name = "height" ;
        height:standard_name = "height" ;
    float tas(time, lat, lon) ;
        tas:standard_name = "air_temperature" ;
        tas:long_name = "Near-Surface Air Temperature" ;
        tas:units = "K" ;
        tas:cell_methods = "area: time: mean" ;
        tas:history = "2026-09-14T18:13:51Z altered by CMOR: Treated scalar dimension: \'height\'. " ;
        tas:coordinates = "height" ;
        tas:missing_value = 1.e+20f ;
        tas:_FillValue = 1.e+20f ;
        tas:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;

```

```

:activity_id = "CMIP" ;
:archive_id = "WCRP" ;
:area_label = "u" ;
:branded_variable = "tas_tavg-h2m-hxy-u" ;
:branding_suffix = "tavg-h2m-hxy-u" ;
:creation_date = "2026-09-14T18:13:51Z" ;
:data_specs_version = "MIP-DS7.1.0.0" ;
:description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacella" ;
:forcing_index = "f2" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:13:51Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r9" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;

:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/23b0cb45-1c79-4a26-bf43-a60257cbef1
2" ;

:variable_id = "tas" ;
:variant_label = "r9i1p1f2" ;
:vertical_label = "h2m" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack

```

nowledgment. The data producers and data providers make no warranty, either express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose. All liabilities arising from the supply of the information (including any liability arising in negligence) are excluded to the fullest extent permitted by law." ;

```
        :cmor_version = "3.15.3" ;
```

```
data:
```

```
    time = 15.5, 45.5 ;
```

```
    time_bnds =
        0, 31,
        31, 60 ;
```

```
    lat = 10, 20, 30 ;
```

```
    lat_bnds =
        5, 15,
        15, 25,
        25, 35 ;
```

```
    lon = 0, 90, 180, 270 ;
```

```
    lon_bnds =
        -45, 45,
        45, 135,
        135, 225,
        225, 315 ;
```

```
    height = 2 ;
```

```
    tas =
        254.0895, 258.4085, 250.5549, 258.7101,
        258.668, 258.299, 252.1237, 255.0432,
        253.7254, 251.246, 254.3168, 255.4808,
        259.7908, 252.2754, 257.1892, 253.3132,
        253.8823, 253.4698, 253.5381, 254.973,
        256.1002, 251.8168, 259.3698, 250.2994 ;
```

```
}
```

#### Example 4: Treatment of Auxiliary Coordinates

- [example\\_04\\_auxiliary\\_coordinates.py \(page 0\)](#)

**Click to expand Python code**

```
#!/usr/bin/env python3

from __future__ import annotations

import argparse
import json
import os
from pathlib import Path

import cmor
import numpy as np

EXAMPLE_DIR = Path(__file__).resolve().parent
RUN_DIR = Path.cwd()
DEFAULT_TABLES_PATH = RUN_DIR / "cmip7-cmor-tables" / "tables"
TABLES_PATH = Path(os.environ.get("CMOR_TABLES_PATH", DEFAULT_TABLES_PATH))
INPUT_PATH = EXAMPLE_DIR.parent / "CMIP7_input_example.json"

def configure(
    output_dir: Path,
    frequency: str = "mon",
    realization_index: str = "r1",
    forcing_index: str = "f1",
) -> None:
    output_dir.mkdir(parents=True, exist_ok=True)
    user_input = json.loads(INPUT_PATH.read_text())
    user_input["outpath"] = str(output_dir)
    user_input["frequency"] = frequency
    user_input["realization_index"] = realization_index
    user_input["forcing_index"] = forcing_index
    input_path = output_dir / "CMIP7_input_example.json"
    input_path.write_text(json.dumps(user_input, indent=2, sort_keys=True))
    cmor.setup(inpath=str(TABLES_PATH), netcdf_file_action=cmor.CMOR_REPLACE)
    cmor.dataset_json(str(input_path))

def apply_cmip7_variable_metadata(
    var_id: int,
    realm: str,
    table_entry: str,
    frequency: str,
    region: str,
) -> str:
    compound_name = ".".join(
        [realm] + table_entry.split("-") + [frequency, region]
    )

    with (TABLES_PATH / "CMIP7_cell_measures.json").open() as handle:
        cell_measures = json.load(handle)["cell_measures"]
```

```

    cmor.set_variable_attribute(
        var_id,
        "cell_measures",
        "c",
        cell_measures.get(compound_name, ""),
    )

    with (TABLES_PATH / "CMIP7_long_name_overrides.json").open() as handle:
        long_name_overrides = json.load(handle)["long_name_overrides"]
    if compound_name in long_name_overrides:
        cmor.set_variable_attribute(
            var_id,
            "long_name",
            "c",
            long_name_overrides[compound_name],
        )

    return compound_name


def write_example(output_dir: Path) -> str:
    configure(output_dir)
    cmor.load_table("CMIP7_ocean.json")
    time_id = cmor.axis(
        "time",
        "days since 1979-01-01",
        coord_vals=np.array([15.5, 45.5], dtype="d"),
        cell_bounds=np.array([0.0, 31.0, 60.0], dtype="d"),
    )
    lat_id = cmor.axis(
        "latitude",
        "degrees_north",
        coord_vals=np.array([10.0, 20.0, 30.0], dtype="d"),
        cell_bounds=np.array([5.0, 15.0, 25.0, 35.0], dtype="d"),
    )
    basin_id = cmor.axis(
        "basin",
        "",
        coord_vals=np.array(
            [
                "atlantic_arctic_ocean",
                "indian_pacific_ocean",
                "global_ocean",
            ],
            dtype="U21",
        ),
    )
    var_id = cmor.variable(
        "htovgyre_tavg-u-hyb-sea",
        "W",

```

```

        [time_id, basin_id, lat_id],
        missing_value=1.0e20,
    )
    apply_cmip7_variable_metadata(
        var_id,
        "ocean",
        "htovgyre_tavg-u-hyb-sea",
        "mon",
        "glb",
    )
    data = np.array(
        [
            -80.0,
            -84.0,
            -88.0,
            -100.0,
            -104.0,
            -76.0,
            -120.0,
            -92.0,
            -96.0,
            -79.0,
            -83.0,
            -87.0,
            -99.0,
            -103.0,
            -75.0,
            -107.0,
            -111.0,
            -115.0,
        ],
        dtype="f4",
    ).reshape(2, 3, 3)
    cmor.write(var_id, data)
    path = cmor.close(var_id, file_name=True)
    cmor.close()
    return path

def main() -> None:
    parser = argparse.ArgumentParser(
        description="Write CMIP7 example 4 with CMOR."
    )
    parser.add_argument(
        "--output-dir",
        type=Path,
        default=Path(__file__).resolve().parent / "output",
    )
    args = parser.parse_args()
    print(write_example(args.output_dir))

```

```
if __name__ == "__main__":  
    main()
```

**Click to expand NetCDF dump**

```

netcdf htovgyre_tavg-u-hyb-sea_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-1
97902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    basin = 3 ;
    lat = 3 ;
    bnds = 2 ;
    strlen = 21 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    char sector(basin, strlen) ;
        sector:long_name = "Ocean Basin" ;
        sector:standard_name = "region" ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    float htovgyre(time, basin, lat) ;
        htovgyre:standard_name = "northward_ocean_heat_transport_due_t
o_gyre" ;
        htovgyre:long_name = "Northward Ocean Heat Transport Due to Gyr
e" ;
        htovgyre:units = "W" ;
        htovgyre:cell_methods = "depth: longitude: sum where sea (along
a zig-zag grid path spanning a basin) time: mean" ;
        htovgyre:missing_value = 1.e+20f ;
        htovgyre:_FillValue = 1.e+20f ;
        htovgyre:coordinates = "sector" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "sea" ;
    :branded_variable = "htovgyre_tavg-u-hyb-sea" ;
    :branding_suffix = "tavg-u-hyb-sea" ;
    :creation_date = "2026-09-14T18:13:51Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past wit
h prescribed sea surface temperatures and sea ice concentrations." ;

```

```

:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:13:51Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hyb" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "ocean" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;

:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_ocean.json; Creation Date:(2026-07-21
13:16:24) MD5:734c6f53560fa60b7c1c21b38e5b9a3f" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/87523728-c4ea-4f94-9caa-72f72dc0daa
7" ;

:variable_id = "htovgyre" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

time = 15.5, 45.5 ;

```

```
time_bnds =
    0, 31,
    31, 60 ;

sector =
    "atlantic_arctic_ocean",
    "indian_pacific_ocean",
    "global_ocean" ;

lat = 10, 20, 30 ;

lat_bnds =
    5, 15,
    15, 25,
    25, 35 ;

htovgyre =
    -80, -84, -88,
    -100, -104, -76,
    -120, -92, -96,
    -79, -83, -87,
    -99, -103, -75,
    -107, -111, -115 ;
}
```

### Example 5: Treatment of a 3-D Field on Model Levels

- [example\\_05\\_model\\_levels.py](#) (page 0)

**Click to expand Python code**

```
#!/usr/bin/env python3

from __future__ import annotations

import argparse
import json
import os
from pathlib import Path

import cmor
import numpy as np

EXAMPLE_DIR = Path(__file__).resolve().parent
RUN_DIR = Path.cwd()
DEFAULT_TABLES_PATH = RUN_DIR / "cmip7-cmor-tables" / "tables"
TABLES_PATH = Path(os.environ.get("CMOR_TABLES_PATH", DEFAULT_TABLES_PATH))
INPUT_PATH = EXAMPLE_DIR.parent / "CMIP7_input_example.json"

def configure(
    output_dir: Path,
    frequency: str = "mon",
    realization_index: str = "r1",
    forcing_index: str = "f1",
) -> None:
    output_dir.mkdir(parents=True, exist_ok=True)
    user_input = json.loads(INPUT_PATH.read_text())
    user_input["outpath"] = str(output_dir)
    user_input["frequency"] = frequency
    user_input["realization_index"] = realization_index
    user_input["forcing_index"] = forcing_index
    input_path = output_dir / "CMIP7_input_example.json"
    input_path.write_text(json.dumps(user_input, indent=2, sort_keys=True))
    cmor.setup(inpath=str(TABLES_PATH), netcdf_file_action=cmor.CMOR_REPLACE)
    cmor.dataset_json(str(input_path))

def apply_cmip7_variable_metadata(
    var_id: int,
    realm: str,
    table_entry: str,
    frequency: str,
    region: str,
) -> str:
    compound_name = ".".join(
        [realm] + table_entry.split("-") + [frequency, region]
    )

    with (TABLES_PATH / "CMIP7_cell_measures.json").open() as handle:
        cell_measures = json.load(handle)["cell_measures"]
```

```

    cmor.set_variable_attribute(
        var_id,
        "cell_measures",
        "c",
        cell_measures.get(compound_name, ""),
    )

    with (TABLES_PATH / "CMIP7_long_name_overrides.json").open() as handle:
        long_name_overrides = json.load(handle)["long_name_overrides"]
    if compound_name in long_name_overrides:
        cmor.set_variable_attribute(
            var_id,
            "long_name",
            "c",
            long_name_overrides[compound_name],
        )

    return compound_name


def write_example(output_dir: Path) -> str:
    configure(output_dir)
    cmor.load_table("CMIP7_atmos.json")
    lat_id = cmor.axis(
        "latitude",
        "degrees_north",
        coord_vals=np.array([10.0, 20.0, 30.0], dtype="d"),
        cell_bounds=np.array([5.0, 15.0, 25.0, 35.0], dtype="d"),
    )
    lon_id = cmor.axis(
        "longitude",
        "degrees_east",
        coord_vals=np.array([0.0, 90.0, 180.0, 270.0], dtype="d"),
        cell_bounds=np.array([-45.0, 45.0, 135.0, 225.0, 315.0], dtype="d"),
    )
    time_id = cmor.axis(
        "time",
        "days since 1979-01-01",
        coord_vals=np.array([15.0, 45.0], dtype="d"),
        cell_bounds=np.array([0.0, 30.0, 60.0], dtype="d"),
    )
    lev_id = cmor.axis(
        "standard_hybrid_sigma",
        "1",
        coord_vals=np.array([0.92, 0.72, 0.50, 0.30, 0.10], dtype="d"),
        cell_bounds=np.array([1.00, 0.83, 0.61, 0.40, 0.20, 0.00], dtype="d"),
    )
    cmor.zfactor(
        zaxis_id=lev_id,
        zfactor_name="a",
    )

```

```

        axis_ids=[lev_id],
        zfactor_values=np.array([0.12, 0.22, 0.30, 0.20, 0.10], dtype="d"),
        zfactor_bounds=np.array(
            [0.06, 0.18, 0.26, 0.25, 0.15, 0.00],
            dtype="d",
        ),
    )
)
cmor.zfactor(
    zaxis_id=lev_id,
    zfactor_name="b",
    axis_ids=[lev_id],
    zfactor_values=np.array([0.80, 0.50, 0.20, 0.10, 0.00], dtype="d"),
    zfactor_bounds=np.array(
        [0.94, 0.65, 0.35, 0.15, 0.05, 0.00],
        dtype="d",
    ),
)
)
cmor.zfactor(
    zaxis_id=lev_id,
    zfactor_name="p0",
    units="Pa",
    zfactor_values=100000.0,
)
)
ps = np.array(
    [
        97000.0,
        97400.0,
        97800.0,
        98200.0,
        98600.0,
        99000.0,
        99400.0,
        99800.0,
        100200.0,
        100600.0,
        101000.0,
        101400.0,
        97100.0,
        97500.0,
        97900.0,
        98300.0,
        98700.0,
        99100.0,
        99500.0,
        99900.0,
        100300.0,
        100700.0,
        101100.0,
        101500.0,
    ],
)

```

```

        dtype="f4",
    ).reshape(2, 3, 4)
    ps_id = cmor.zfactor(
        zaxis_id=lev_id,
        zfactor_name="ps",
        axis_ids=[time_id, lat_id, lon_id],
        units="Pa",
    )
    var_id = cmor.variable(
        "cl_tavg-al-hxy-u",
        "%",
        [time_id, lev_id, lat_id, lon_id],
        missing_value=1.0e20,
    )
    apply_cmip7_variable_metadata(
        var_id,
        "atmos",
        "cl_tavg-al-hxy-u",
        "mon",
        "glb",
    )
    data = np.array(
        [
            72.8, 73.2, 73.6, 74.0,
            71.6, 72.0, 72.4, 72.4,
            70.4, 70.8, 70.8, 71.2,
            67.6, 69.2, 69.6, 70.0,
            66.0, 66.4, 66.8, 67.2,
            64.8, 65.2, 65.6, 66.0,
            63.6, 64.0, 64.4, 64.4,
            60.8, 61.2, 62.8, 63.2,
            59.6, 59.6, 60.0, 60.4,
            58.0, 58.4, 58.8, 59.2,
            56.8, 57.2, 57.6, 58.0,
            54.0, 54.4, 54.8, 56.4,
            52.8, 53.2, 53.2, 53.6,
            51.6, 51.6, 52.0, 52.4,
            50.0, 50.4, 50.8, 51.2,
            72.9, 73.3, 73.7, 74.1,
            71.7, 72.1, 72.5, 72.5,
            70.5, 70.9, 70.9, 71.3,
            67.7, 69.3, 69.7, 70.1,
            66.1, 66.5, 66.9, 67.3,
            64.9, 65.3, 65.7, 66.1,
            63.7, 64.1, 64.5, 64.5,
            60.9, 61.3, 62.9, 63.3,
            59.7, 59.7, 60.1, 60.5,
            58.1, 58.5, 58.9, 59.3,
            56.9, 57.3, 57.7, 58.1,
            54.1, 54.5, 54.9, 56.5,

```

```
        52.9, 53.3, 53.3, 53.7,
        51.7, 51.7, 52.1, 52.5,
        50.1, 50.5, 50.9, 51.3,
    ],
    dtype="f4",
).reshape(2, 5, 3, 4)
cmor.write(var_id, data)
cmor.write(ps_id, ps, store_with=var_id)
path = cmor.close(var_id, file_name=True)
cmor.close()
return path

def main() -> None:
    parser = argparse.ArgumentParser(
        description="Write CMIP7 example 5 with CMOR."
    )
    parser.add_argument(
        "--output-dir",
        type=Path,
        default=Path(__file__).resolve().parent / "output",
    )
    args = parser.parse_args()
    print(write_example(args.output_dir))

if __name__ == "__main__":
    main()
```

**Click to expand NetCDF dump**

```

netcdf cl_tavg-al-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    lev = 5 ;
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lev(lev) ;
        lev:bounds = "lev_bnds" ;
        lev:units = "1" ;
        lev:axis = "Z" ;
        lev:positive = "down" ;
        lev:long_name = "hybrid sigma pressure coordinate" ;
        lev:standard_name = "atmosphere_hybrid_sigma_pressure_coordinate" ;
        lev:formula = "p = a*p0 + b*ps" ;
        lev:formula_terms = "p0: p0 a: a b: b ps: ps" ;
    double lev_bnds(lev, bnds) ;
        lev_bnds:formula = "p = a*p0 + b*ps" ;
        lev_bnds:standard_name = "atmosphere_hybrid_sigma_pressure_coordinate" ;
        lev_bnds:units = "1" ;
        lev_bnds:formula_terms = "p0: p0 a: a_bnds b: b_bnds ps: ps" ;
    double p0 ;
        p0:standard_name = "reference_air_pressure_for_atmosphere_vertical_coordinate" ;
        p0:long_name = "vertical coordinate formula term: reference pressure" ;
        p0:units = "Pa" ;
    double a(lev) ;
        a:long_name = "vertical coordinate formula term: a" ;
    double b(lev) ;
        b:long_name = "vertical coordinate formula term: b" ;
    float ps(time, lat, lon) ;
        ps:standard_name = "air_pressure" ;
        ps:long_name = "Surface Air Pressure" ;
        ps:units = "Pa" ;
    double a_bnds(lev, bnds) ;
        a_bnds:long_name = "vertical coordinate formula term: a(k+1/2)" ;
    double b_bnds(lev, bnds) ;

```

```

        b_bnds:long_name = "vertical coordinate formula term: b(k+1/2)"
;
double lat(lat) ;
    lat:bounds = "lat_bnds" ;
    lat:units = "degrees_north" ;
    lat:axis = "Y" ;
    lat:long_name = "Latitude" ;
    lat:standard_name = "latitude" ;
double lat_bnds(lat, bnds) ;
double lon(lon) ;
    lon:bounds = "lon_bnds" ;
    lon:units = "degrees_east" ;
    lon:axis = "X" ;
    lon:long_name = "Longitude" ;
    lon:standard_name = "longitude" ;
double lon_bnds(lon, bnds) ;
float cl(time, lev, lat, lon) ;
    cl:standard_name = "cloud_area_fraction_in_atmosphere_layer" ;
    cl:long_name = "Percentage Cloud Cover" ;
    cl:units = "%" ;
    cl:cell_methods = "area: time: mean" ;
    cl:missing_value = 1.e+20f ;
    cl:_FillValue = 1.e+20f ;
    cl:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "u" ;
    :branded_variable = "cl_tavg-al-hxy-u" ;
    :branding_suffix = "tavg-al-hxy-u" ;
    :creation_date = "2026-09-14T18:13:51Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
    :drs_specs = "MIP-DRS7" ;
    :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
    :experiment_id = "amip" ;
    :external_variables = "areacella" ;
    :forcing_index = "f1" ;
    :frequency = "mon" ;
    :grid_label = "g999" ;
    :history = "2026-09-14T18:13:51Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
    :horizontal_label = "hxy" ;
    :host_collection = "CMIP7" ;
    :initialization_index = "i1" ;
    :institution = "Met Office Hadley Centre" ;

```

```

:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;

:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:variable_id = "cl" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "al" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
:tracking_id = "hdl:21.14107/18c1a76e-61e6-45ee-b54b-9b48184fea9
0" ;
data:

time = 15, 45 ;

time_bnds =
    0, 30,
    30, 60 ;

lev = 0.92, 0.72, 0.5, 0.3, 0.1 ;

lev_bnds =
    1, 0.83,
    0.83, 0.61,
    0.61, 0.4,
    0.4, 0.2,
    0.2, 0 ;

```

```
p0 = 100000 ;

a = 0.12, 0.22, 0.3, 0.2, 0.1 ;

b = 0.8, 0.5, 0.2, 0.1, 0 ;

ps =
  97000, 97400, 97800, 98200,
  98600, 99000, 99400, 99800,
  100200, 100600, 101000, 101400,
  97100, 97500, 97900, 98300,
  98700, 99100, 99500, 99900,
  100300, 100700, 101100, 101500 ;

a_bnds =
  0.06, 0.18,
  0.18, 0.26,
  0.26, 0.25,
  0.25, 0.15,
  0.15, 0 ;

b_bnds =
  0.94, 0.65,
  0.65, 0.35,
  0.35, 0.15,
  0.15, 0.05,
  0.05, 0 ;

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

lon = 0, 90, 180, 270 ;

lon_bnds =
  -45, 45,
  45, 135,
  135, 225,
  225, 315 ;

cl =
  72.8, 73.2, 73.6, 74,
  71.6, 72, 72.4, 72.4,
  70.4, 70.8, 70.8, 71.2,
  67.6, 69.2, 69.6, 70,
  66, 66.4, 66.8, 67.2,
  64.8, 65.2, 65.6, 66,
```

```
63.6, 64, 64.4, 64.4,  
60.8, 61.2, 62.8, 63.2,  
59.6, 59.6, 60, 60.4,  
58, 58.4, 58.8, 59.2,  
56.8, 57.2, 57.6, 58,  
54, 54.4, 54.8, 56.4,  
52.8, 53.2, 53.2, 53.6,  
51.6, 51.6, 52, 52.4,  
50, 50.4, 50.8, 51.2,  
72.9, 73.3, 73.7, 74.1,  
71.7, 72.1, 72.5, 72.5,  
70.5, 70.9, 70.9, 71.3,  
67.7, 69.3, 69.7, 70.1,  
66.1, 66.5, 66.9, 67.3,  
64.9, 65.3, 65.7, 66.1,  
63.7, 64.1, 64.5, 64.5,  
60.9, 61.3, 62.9, 63.3,  
59.7, 59.7, 60.1, 60.5,  
58.1, 58.5, 58.9, 59.3,  
56.9, 57.3, 57.7, 58.1,  
54.1, 54.5, 54.9, 56.5,  
52.9, 53.3, 53.3, 53.7,  
51.7, 51.7, 52.1, 52.5,  
50.1, 50.5, 50.9, 51.3 ;  
}
```

### Example 6: Treatment of Grid Coordinates

- [example\\_06\\_complex\\_grid.py \(page 0\)](#)

**Click to expand Python code**

```
#!/usr/bin/env python3

from __future__ import annotations

import argparse
import json
import os
from pathlib import Path

import cmor
import numpy as np

EXAMPLE_DIR = Path(__file__).resolve().parent
RUN_DIR = Path.cwd()
DEFAULT_TABLES_PATH = RUN_DIR / "cmip7-cmor-tables" / "tables"
TABLES_PATH = Path(os.environ.get("CMOR_TABLES_PATH", DEFAULT_TABLES_PATH))
INPUT_PATH = EXAMPLE_DIR.parent / "CMIP7_input_example.json"

def configure(
    output_dir: Path,
    frequency: str = "mon",
    realization_index: str = "r1",
    forcing_index: str = "f1",
) -> None:
    output_dir.mkdir(parents=True, exist_ok=True)
    user_input = json.loads(INPUT_PATH.read_text())
    user_input["outpath"] = str(output_dir)
    user_input["frequency"] = frequency
    user_input["realization_index"] = realization_index
    user_input["forcing_index"] = forcing_index
    input_path = output_dir / "CMIP7_input_example.json"
    input_path.write_text(json.dumps(user_input, indent=2, sort_keys=True))
    cmor.setup(inpath=str(TABLES_PATH), netcdf_file_action=cmor.CMOR_REPLACE)
    cmor.dataset_json(str(input_path))

def apply_cmip7_variable_metadata(
    var_id: int,
    realm: str,
    table_entry: str,
    frequency: str,
    region: str,
) -> str:
    compound_name = ".".join(
        [realm] + table_entry.split("_") + [frequency, region]
    )

    with (TABLES_PATH / "CMIP7_cell_measures.json").open() as handle:
        cell_measures = json.load(handle)["cell_measures"]
```

```

    cmor.set_variable_attribute(
        var_id,
        "cell_measures",
        "c",
        cell_measures.get(compound_name, ""),
    )

    with (TABLES_PATH / "CMIP7_long_name_overrides.json").open() as handle:
        long_name_overrides = json.load(handle)["long_name_overrides"]
    if compound_name in long_name_overrides:
        cmor.set_variable_attribute(
            var_id,
            "long_name",
            "c",
            long_name_overrides[compound_name],
        )

    return compound_name


def write_example(output_dir: Path) -> str:
    configure(output_dir)
    grid_table = cmor.load_table("CMIP7_grids.json")
    cmor.set_table(grid_table)
    y_id = cmor.axis(
        "y",
        "m",
        coord_vals=np.array([0.0, 10000.0, 20000.0], dtype="d"),
        cell_bounds=np.array(
            [-5000.0, 5000.0, 15000.0, 25000.0],
            dtype="d",
        ),
    )
    x_id = cmor.axis(
        "x",
        "m",
        coord_vals=np.array([0.0, 10000.0, 20000.0, 30000.0], dtype="d"),
        cell_bounds=np.array(
            [-5000.0, 5000.0, 15000.0, 25000.0, 35000.0],
            dtype="d",
        ),
    )
    latitude = np.array(
        [
            [10.0, 8.0, 6.0, 4.0],
            [20.0, 18.0, 16.0, 14.0],
            [30.0, 28.0, 26.0, 24.0],
        ],
        dtype="d",
    )

```

```

longitude = np.array(
    [
        [280.0, 290.0, 300.0, 310.0],
        [282.0, 292.0, 302.0, 312.0],
        [284.0, 294.0, 304.0, 314.0],
    ],
    dtype="d",
)
latitude_vertices = np.empty((3, 4, 4), dtype="d")
longitude_vertices = np.empty((3, 4, 4), dtype="d")
for j in range(3):
    for i in range(4):
        latitude_vertices[j, i, :] = [
            latitude[j, i] - 5.0,
            latitude[j, i] - 4.0,
            latitude[j, i] + 5.0,
            latitude[j, i] + 4.0,
        ]
        longitude_vertices[j, i, :] = [
            longitude[j, i] - 5.0,
            longitude[j, i] + 5.0,
            longitude[j, i] + 5.0,
            longitude[j, i] - 5.0,
        ]
grid_id = cmor.grid(
    axis_ids=[y_id, x_id],
    latitude=latitude,
    longitude=longitude,
    latitude_vertices=latitude_vertices,
    longitude_vertices=longitude_vertices,
)
cmor.set_grid_mapping(
    grid_id=grid_id,
    mapping_name="lambert_conformal_conic",
    parameter_names=[
        "standard_parallel1",
        "longitude_of_central_meridian",
        "latitude_of_projection_origin",
        "false_easting",
        "false_northing",
        "standard_parallel2",
    ],
    parameter_values=[-20.0, 175.0, 13.0, 8.0, 0.0, 20.0],
    parameter_units=["", "", "", "", "", ""],
)
cmor.load_table("CMIP7_atmos.json")
time_id = cmor.axis(
    "time",
    "days since 1979-01-01",
    coord_vals=np.array([15.5, 45.5], dtype="d"),

```

```
        cell_bounds=np.array([0.0, 31.0, 60.0], dtype="d"),
    )
    var_id = cmor.variable(
        "hfls_tavg-u-hxy-u",
        "W m-2",
        [time_id, grid_id],
        positive="up",
        missing_value=1.0e20,
    )
    apply_cmip7_variable_metadata(
        var_id,
        "atmos",
        "hfls_tavg-u-hxy-u",
        "mon",
        "glb",
    )
    data = np.array(
        [
            80.0,
            82.0,
            84.0,
            86.0,
            88.0,
            90.0,
            92.0,
            94.0,
            96.0,
            98.0,
            100.0,
            102.0,
            81.0,
            83.0,
            85.0,
            87.0,
            89.0,
            91.0,
            93.0,
            95.0,
            97.0,
            99.0,
            101.0,
            103.0,
        ],
        dtype="f4",
    ).reshape(2, 3, 4)
    cmor.write(var_id, data)
    path = cmor.close(var_id, file_name=True)
    cmor.close()
    return path
```

```
def main() -> None:
    parser = argparse.ArgumentParser(
        description="Write CMIP7 example 6 with CMOR."
    )
    parser.add_argument(
        "--output-dir",
        type=Path,
        default=Path(__file__).resolve().parent / "output",
    )
    args = parser.parse_args()
    print(write_example(args.output_dir))

if __name__ == "__main__":
    main()
```

**Click to expand NetCDF dump**

```

netcdf hfls_tavg-u-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    y = 3 ;
    x = 4 ;
    bnds = 2 ;
    vertices = 4 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double y(y) ;
        y:bounds = "y_bnds" ;
        y:units = "m" ;
        y:axis = "Y" ;
        y:long_name = "y coordinate of projection" ;
        y:standard_name = "projection_y_coordinate" ;
    double y_bnds(y, bnds) ;
    double x(x) ;
        x:bounds = "x_bnds" ;
        x:units = "m" ;
        x:axis = "X" ;
        x:long_name = "x coordinate of projection" ;
        x:standard_name = "projection_x_coordinate" ;
    double x_bnds(x, bnds) ;
    int lambert_conformal_conic ;
        lambert_conformal_conic:grid_mapping_name = "lambert_conformal_c
onic" ;
        lambert_conformal_conic:standard_parallel = -20., 20. ;
        lambert_conformal_conic:longitude_of_central_meridian = 175. ;
        lambert_conformal_conic:latitude_of_projection_origin = 13. ;
        lambert_conformal_conic:false_easting = 8. ;
        lambert_conformal_conic:false_northing = 0. ;
    double latitude(y, x) ;
        latitude:standard_name = "latitude" ;
        latitude:long_name = "latitude" ;
        latitude:units = "degrees_north" ;
        latitude:missing_value = 1.e+20 ;
        latitude:_FillValue = 1.e+20 ;
        latitude:bounds = "vertices_latitude" ;
    double longitude(y, x) ;
        longitude:standard_name = "longitude" ;
        longitude:long_name = "longitude" ;
        longitude:units = "degrees_east" ;
        longitude:missing_value = 1.e+20 ;

```

```

        longitude:_FillValue = 1.e+20 ;
        longitude:bounds = "vertices_longitude" ;
double vertices_latitude(y, x, vertices) ;
        vertices_latitude:units = "degrees_north" ;
        vertices_latitude:missing_value = 1.e+20 ;
        vertices_latitude:_FillValue = 1.e+20 ;
double vertices_longitude(y, x, vertices) ;
        vertices_longitude:units = "degrees_east" ;
        vertices_longitude:missing_value = 1.e+20 ;
        vertices_longitude:_FillValue = 1.e+20 ;
float hfls(time, y, x) ;
        hfls:standard_name = "surface_upward_latent_heat_flux" ;
        hfls:long_name = "Surface Upward Latent Heat Flux" ;
        hfls:units = "W m-2" ;
        hfls:cell_methods = "area: time: mean" ;
        hfls:missing_value = 1.e+20f ;
        hfls:_FillValue = 1.e+20f ;
        hfls:cell_measures = "area: areacella" ;
        hfls:grid_mapping = "lambert_conformal_conic" ;
        hfls:coordinates = "latitude longitude" ;

// global attributes:
        :Conventions = "CF-1.12" ;
        :activity_id = "CMIP" ;
        :archive_id = "WCRP" ;
        :area_label = "u" ;
        :branded_variable = "hfls_tavg-u-hxy-u" ;
        :branding_suffix = "tavg-u-hxy-u" ;
        :creation_date = "2026-09-14T18:13:51Z" ;
        :data_specs_version = "MIP-DS7.1.0.0" ;
        :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
        :drs_specs = "MIP-DRS7" ;
        :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
        :experiment_id = "amip" ;
        :external_variables = "areacella" ;
        :forcing_index = "f1" ;
        :frequency = "mon" ;
        :grid_label = "g999" ;
        :history = "2026-09-14T18:13:51Z ; CMOR rewrote data to be consistent
with CF-1.12 and CMIP7 data requirements." ;
        :horizontal_label = "hxy" ;
        :host_collection = "CMIP7" ;
        :initialization_index = "i1" ;
        :institution = "Met Office Hadley Centre" ;
        :institution_id = "MOHC" ;
        :license_id = "CC-BY-4.0" ;
        :mip_era = "CMIP7" ;
        :nominal_resolution = "100 km" ;

```

```

:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;

:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/f25fb30c-c23b-45b6-8807-804c2298fff
0" ;

:variable_id = "hfls" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

time = 15.5, 45.5 ;

time_bnds =
  0, 31,
  31, 60 ;

y = 0, 10000, 20000 ;

y_bnds =
  -5000, 5000,
  5000, 15000,
  15000, 25000 ;

x = 0, 10000, 20000, 30000 ;

x_bnds =
  -5000, 5000,
  5000, 15000,
  15000, 25000,

```

```

    25000, 35000 ;

lambert_conformal_conic = _ ;

latitude =
    10, 8, 6, 4,
    20, 18, 16, 14,
    30, 28, 26, 24 ;

longitude =
    280, 290, 300, 310,
    282, 292, 302, 312,
    284, 294, 304, 314 ;

vertices_latitude =
    5, 6, 15, 14,
    3, 4, 13, 12,
    1, 2, 11, 10,
    -1, 0, 9, 8,
    15, 16, 25, 24,
    13, 14, 23, 22,
    11, 12, 21, 20,
    9, 10, 19, 18,
    25, 26, 35, 34,
    23, 24, 33, 32,
    21, 22, 31, 30,
    19, 20, 29, 28 ;

vertices_longitude =
    275, 285, 285, 275,
    285, 295, 295, 285,
    295, 305, 305, 295,
    305, 315, 315, 305,
    277, 287, 287, 277,
    287, 297, 297, 287,
    297, 307, 307, 297,
    307, 317, 317, 307,
    279, 289, 289, 279,
    289, 299, 299, 289,
    299, 309, 309, 299,
    309, 319, 319, 309 ;

hfls =
    80, 82, 84, 86,
    88, 90, 92, 94,
    96, 98, 100, 102,
    81, 83, 85, 87,
    89, 91, 93, 95,
    97, 99, 101, 103 ;
}

```

### Example 7: Fixed Field

- [example\\_07\\_fixed\\_field.py](#) (page 0)

**Click to expand Python code**

```
#!/usr/bin/env python3

from __future__ import annotations

import argparse
import json
import os
from pathlib import Path

import cmor
import numpy as np

EXAMPLE_DIR = Path(__file__).resolve().parent
RUN_DIR = Path.cwd()
DEFAULT_TABLES_PATH = RUN_DIR / "cmip7-cmor-tables" / "tables"
TABLES_PATH = Path(os.environ.get("CMOR_TABLES_PATH", DEFAULT_TABLES_PATH))
INPUT_PATH = EXAMPLE_DIR.parent / "CMIP7_input_example.json"

def configure(
    output_dir: Path,
    frequency: str = "mon",
    realization_index: str = "r1",
    forcing_index: str = "f1",
) -> None:
    output_dir.mkdir(parents=True, exist_ok=True)
    user_input = json.loads(INPUT_PATH.read_text())
    user_input["outpath"] = str(output_dir)
    user_input["frequency"] = frequency
    user_input["realization_index"] = realization_index
    user_input["forcing_index"] = forcing_index
    input_path = output_dir / "CMIP7_input_example.json"
    input_path.write_text(json.dumps(user_input, indent=2, sort_keys=True))
    cmor.setup(inpath=str(TABLES_PATH), netcdf_file_action=cmor.CMOR_REPLACE)
    cmor.dataset_json(str(input_path))

def apply_cmip7_variable_metadata(
    var_id: int,
    realm: str,
    table_entry: str,
    frequency: str,
    region: str,
) -> str:
    compound_name = ".".join(
        [realm] + table_entry.split("-") + [frequency, region]
    )

    with (TABLES_PATH / "CMIP7_cell_measures.json").open() as handle:
        cell_measures = json.load(handle)["cell_measures"]
```

```

    cmor.set_variable_attribute(
        var_id,
        "cell_measures",
        "c",
        cell_measures.get(compound_name, ""),
    )

    with (TABLES_PATH / "CMIP7_long_name_overrides.json").open() as handle:
        long_name_overrides = json.load(handle)["long_name_overrides"]
    if compound_name in long_name_overrides:
        cmor.set_variable_attribute(
            var_id,
            "long_name",
            "c",
            long_name_overrides[compound_name],
        )

    return compound_name


def write_example(output_dir: Path) -> str:
    configure(output_dir, frequency="fx")
    cmor.load_table("CMIP7_land.json")
    lat_id = cmor.axis(
        "latitude",
        "degrees_north",
        coord_vals=np.array([10.0, 20.0, 30.0], dtype="d"),
        cell_bounds=np.array([5.0, 15.0, 25.0, 35.0], dtype="d"),
    )
    lon_id = cmor.axis(
        "longitude",
        "degrees_east",
        coord_vals=np.array([0.0, 90.0, 180.0, 270.0], dtype="d"),
        cell_bounds=np.array(
            [-45.0, 45.0, 135.0, 225.0, 315.0],
            dtype="d",
        ),
    )
    var_id = cmor.variable(
        "rootd_ti-u-hxy-lnd",
        "m",
        [lat_id, lon_id],
        missing_value=1.0e20,
    )
    apply_cmip7_variable_metadata(
        var_id,
        "land",
        "rootd_ti-u-hxy-lnd",
        "fx",
        "glb",
    )

```

```
)
data = np.array(
    [
        [0.50, 0.45, 1.0e20, 0.55],
        [0.60, 0.60, 1.0e20, 0.55],
        [1.0e20, 0.45, 0.50, 0.50],
    ],
    dtype="f4",
)
cmor.write(var_id, data)
path = cmor.close(var_id, file_name=True)
cmor.close()
return path

def main() -> None:
    parser = argparse.ArgumentParser(
        description="Write CMIP7 example 7 with CMOR."
    )
    parser.add_argument(
        "--output-dir",
        type=Path,
        default=Path(__file__).resolve().parent / "output",
    )
    args = parser.parse_args()
    print(write_example(args.output_dir))

if __name__ == "__main__":
    main()
```

**Click to expand NetCDF dump**

```

netcdf rootd_ti-u-hxy-lnd_fx_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1 {
dimensions:
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float rootd(lat, lon) ;
        rootd:standard_name = "root_depth" ;
        rootd:long_name = "Maximum Root Depth" ;
        rootd:units = "m" ;
        rootd:cell_methods = "area: mean where land" ;
        rootd:missing_value = 1.e+20f ;
        rootd:_FillValue = 1.e+20f ;
        rootd:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "lnd" ;
    :branded_variable = "rootd_ti-u-hxy-lnd" ;
    :branding_suffix = "ti-u-hxy-lnd" ;
    :creation_date = "2026-09-14T18:13:52Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
    :drs_specs = "MIP-DRS7" ;
    :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
    :experiment_id = "amip" ;
    :external_variables = "areacella" ;
    :forcing_index = "f1" ;
    :frequency = "fx" ;
    :grid_label = "g999" ;
    :history = "2026-09-14T18:13:52Z ; CMOR rewrote data to be consistent
with CF-1.12 and CMIP7 data requirements." ;

```

```

:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "land" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;

:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_land.json; Creation Date:(2026-07-21
13:16:24) MD5:ea523449976b1c3cc3c14c1492f2fb74" ;
:temporal_label = "ti" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/5f15d485-c9c2-46fb-a674-dff7a00f0e5
0" ;

:variable_id = "rootd" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

lon = 0, 90, 180, 270 ;

lon_bnds =
  -45, 45,

```

```
45, 135,  
135, 225,  
225, 315 ;  
  
rootd =  
0.5, 0.45, _, 0.55,  
0.6, 0.6, _, 0.55,  
_, 0.45, 0.5, 0.5 ;  
}
```

### Example 8: Site Dimension

- [example\\_08\\_site\\_dimension.py \(page 0\)](#)

**Click to expand Python code**

```
#!/usr/bin/env python3

from __future__ import annotations

import argparse
import json
import os
from pathlib import Path

import cmor
import numpy as np

EXAMPLE_DIR = Path(__file__).resolve().parent
RUN_DIR = Path.cwd()
DEFAULT_TABLES_PATH = RUN_DIR / "cmip7-cmor-tables" / "tables"
TABLES_PATH = Path(os.environ.get("CMOR_TABLES_PATH", DEFAULT_TABLES_PATH))
INPUT_PATH = EXAMPLE_DIR.parent / "CMIP7_input_example.json"

def configure(
    output_dir: Path,
    frequency: str = "mon",
    realization_index: str = "r1",
    forcing_index: str = "f1",
) -> None:
    output_dir.mkdir(parents=True, exist_ok=True)
    user_input = json.loads(INPUT_PATH.read_text())
    user_input["outpath"] = str(output_dir)
    user_input["frequency"] = frequency
    user_input["realization_index"] = realization_index
    user_input["forcing_index"] = forcing_index
    input_path = output_dir / "CMIP7_input_example.json"
    input_path.write_text(json.dumps(user_input, indent=2, sort_keys=True))
    cmor.setup(inpath=str(TABLES_PATH), netcdf_file_action=cmor.CMOR_REPLACE)
    cmor.dataset_json(str(input_path))

def apply_cmip7_variable_metadata(
    var_id: int,
    realm: str,
    table_entry: str,
    frequency: str,
    region: str,
) -> str:
    compound_name = ".".join(
        [realm] + table_entry.split("_") + [frequency, region]
    )

    with (TABLES_PATH / "CMIP7_cell_measures.json").open() as handle:
        cell_measures = json.load(handle)["cell_measures"]
```

```

    cmor.set_variable_attribute(
        var_id,
        "cell_measures",
        "c",
        cell_measures.get(compound_name, ""),
    )

    with (TABLES_PATH / "CMIP7_long_name_overrides.json").open() as handle:
        long_name_overrides = json.load(handle)["long_name_overrides"]
    if compound_name in long_name_overrides:
        cmor.set_variable_attribute(
            var_id,
            "long_name",
            "c",
            long_name_overrides[compound_name],
        )

    return compound_name


def write_example(output_dir: Path) -> str:
    configure(output_dir)
    cmor.load_table("CMIP7_atmos.json")

    time_id = cmor.axis(
        "time1",
        "days since 1979-01-01",
        coord_vals=np.array([15.5, 45.5], dtype="d"),
        cell_bounds=np.array([0.0, 31.0, 60.0], dtype="d"),
    )
    site_values = np.arange(1, 127, dtype="i")
    site_id = cmor.axis("site", "1", coord_vals=site_values)
    height_id = cmor.axis(
        "height2m",
        "m",
        coord_vals=np.array([2.0], dtype="d"),
    )

    cmor.load_table("CMIP7_grids.json")
    site_latitudes = np.linspace(-60.0, 60.0, site_values.size, dtype="f")
    site_longitudes = np.linspace(0.5, 359.5, site_values.size, dtype="f")
    site_grid_id = cmor.grid(
        [site_id],
        latitude=site_latitudes,
        longitude=site_longitudes,
        latitude_vertices=np.column_stack(
            (site_latitudes - 0.25, site_latitudes + 0.25)
        ),
        longitude_vertices=np.column_stack(
            (site_longitudes - 0.25, site_longitudes + 0.25)
        )
    )

```

```

    ),
)

cmor.load_table("CMIP7_atmos.json")
var_id = cmor.variable(
    "tas_tpt-h2m-hs-u",
    "K",
    [height_id, time_id, site_grid_id],
    missing_value=1.0e20,
)
apply_cmip7_variable_metadata(
    var_id,
    "atmos",
    "tas_tpt-h2m-hs-u",
    "mon",
    "glb",
)

data = np.linspace(
    275.0,
    290.0,
    2 * site_values.size,
    dtype="f4",
).reshape(1, 2, site_values.size)
cmor.write(var_id, data)
path = cmor.close(var_id, file_name=True)
cmor.close()
return path

def main() -> None:
    parser = argparse.ArgumentParser(
        description="Write CMIP7 example 8 with CMOR."
    )
    parser.add_argument(
        "--output-dir",
        type=Path,
        default=Path(__file__).resolve().parent / "output",
    )
    args = parser.parse_args()
    print(write_example(args.output_dir))

if __name__ == "__main__":
    main()

```

**Click to expand NetCDF dump**

```

netcdf tas_tpt-h2m-hs-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    site = 126 ;
    bnds = 2 ;
    vertices = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Points" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    int site(site) ;
        site:long_name = "site index" ;
    double latitude(site) ;
        latitude:standard_name = "latitude" ;
        latitude:long_name = "latitude" ;
        latitude:units = "degrees_north" ;
        latitude:missing_value = 1.e+20 ;
        latitude:_FillValue = 1.e+20 ;
        latitude:bounds = "vertices_latitude" ;
    double longitude(site) ;
        longitude:standard_name = "longitude" ;
        longitude:long_name = "longitude" ;
        longitude:units = "degrees_east" ;
        longitude:missing_value = 1.e+20 ;
        longitude:_FillValue = 1.e+20 ;
        longitude:bounds = "vertices_longitude" ;
    double vertices_latitude(site, vertices) ;
        vertices_latitude:units = "degrees_north" ;
        vertices_latitude:missing_value = 1.e+20 ;
        vertices_latitude:_FillValue = 1.e+20 ;
    double vertices_longitude(site, vertices) ;
        vertices_longitude:units = "degrees_east" ;
        vertices_longitude:missing_value = 1.e+20 ;
        vertices_longitude:_FillValue = 1.e+20 ;
    double height ;
        height:units = "m" ;
        height:axis = "Z" ;
        height:positive = "up" ;
        height:long_name = "height" ;
        height:standard_name = "height" ;
    float tas(time, site) ;
        tas:standard_name = "air_temperature" ;
        tas:long_name = "Near-Surface Air Temperature" ;
        tas:units = "K" ;
        tas:cell_methods = "area: point time: point" ;

```

```

        tas:history = "2026-09-14T18:13:52Z altered by CMOR: Treated scalar dimension: \
height\" ;
        tas:coordinates = "height latitude longitude" ;
        tas:missing_value = 1.e+20f ;
        tas:_FillValue = 1.e+20f ;

// global attributes:
        :Conventions = "CF-1.12" ;
        :activity_id = "CMIP" ;
        :archive_id = "WCRP" ;
        :area_label = "u" ;
        :branded_variable = "tas_tpt-h2m-hs-u" ;
        :branding_suffix = "tpt-h2m-hs-u" ;
        :creation_date = "2026-09-14T18:13:52Z" ;
        :data_specs_version = "MIP-DS7.1.0.0" ;
        :description = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;
        :drs_specs = "MIP-DRS7" ;
        :experiment = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;
        :experiment_id = "amip" ;
        :forcing_index = "f1" ;
        :frequency = "mon" ;
        :grid_label = "g999" ;
        :history = "2026-09-14T18:13:52Z ; CMOR rewrote data to be consistent with CF-1.12 and CMIP7 data requirements." ;
        :horizontal_label = "hs" ;
        :host_collection = "CMIP7" ;
        :initialization_index = "i1" ;
        :institution = "Met Office Hadley Centre" ;
        :institution_id = "MOHC" ;
        :license_id = "CC-BY-4.0" ;
        :mip_era = "CMIP7" ;
        :nominal_resolution = "100 km" ;
        :physics_index = "p1" ;
        :product = "model-output" ;
        :realization_index = "r1" ;
        :realm = "atmos" ;
        :region = "glb" ;
        :source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; land-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: cice5" ;
        :source_id = "ACCESS-ESM1-6" ;
        :table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21 13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
        :temporal_label = "tpt" ;
        :title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
        :tracking_id = "hdl:21.14107/fbe58c1f-b32b-4110-8f26-4909a19c2b49" ;

        :variable_id = "tas" ;

```

```

        :variant_label = "r1i1p1f1" ;
        :vertical_label = "h2m" ;
        :license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
        :cmor_version = "3.15.3" ;
data:

time = 15.5, 45.5 ;

time_bnds =
    0, 31,
    31, 60 ;

site = 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19,
    20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37,
    38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55,
    56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73,
    74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,
    92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107,
    108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121,
    122, 123, 124, 125, 126 ;

latitude = -60, -59.0400009155273, -58.0800018310547, -57.1199989318848,
    -56.1599998474121, -55.2000007629395, -54.2400016784668,
    -53.2799987792969, -52.3199996948242, -51.3600006103516,
    -50.4000015258789, -49.439998626709, -48.4799995422363,
    -47.5200004577637, -46.560001373291, -45.5999984741211,
    -44.6399993896484, -43.6800003051758, -42.7200012207031,
    -41.7599983215332, -40.7999992370605, -39.8400001525879,
    -38.8800010681152, -37.9199981689453, -36.9599990844727, -36,
    -35.0400009155273, -34.0800018310547, -33.1199989318848,
    -32.1599998474121, -31.2000007629395, -30.2399997711182,
    -29.2800006866455, -28.3199996948242, -27.3600006103516,
    -26.3999996185303, -25.4400005340576, -24.4799995422363,
    -23.5200004577637, -22.5599994659424, -21.6000003814697,
    -20.6399993896484, -19.6800003051758, -18.7199993133545,
    -17.7600002288818, -16.7999992370605, -15.8400001525879,
    -14.8800001144409, -13.9200000762939, -12.960000038147, -12,
    -11.039999961853, -10.0799999237061, -9.11999988555908,
    -8.15999984741211, -7.19999980926514, -6.23999977111816,
    -5.28000020980835, -4.32000017166138, -3.35999989509583,
    -2.40000009536743, -1.44000005722046, -0.479999989271164,

```

0.479999989271164, 1.44000005722046, 2.40000009536743, 3.35999989509583,  
 4.32000017166138, 5.28000020980835, 6.23999977111816, 7.19999980926514,  
 8.15999984741211, 9.11999988555908, 10.0799999237061, 11.039999961853,  
 12, 12.960000038147, 13.9200000762939, 14.8800001144409,  
 15.8400001525879, 16.7999992370605, 17.7600002288818, 18.7199993133545,  
 19.6800003051758, 20.6399993896484, 21.6000003814697, 22.5599994659424,  
 23.5200004577637, 24.4799995422363, 25.4400005340576, 26.3999996185303,  
 27.3600006103516, 28.3199996948242, 29.2800006866455, 30.2399997711182,  
 31.2000007629395, 32.1599998474121, 33.1199989318848, 34.0800018310547,  
 35.0400009155273, 36, 36.9599990844727, 37.9199981689453,  
 38.8800010681152, 39.8400001525879, 40.7999992370605, 41.7599983215332,  
 42.7200012207031, 43.6800003051758, 44.6399993896484, 45.5999984741211,  
 46.560001373291, 47.5200004577637, 48.4799995422363, 49.439998626709,  
 50.4000015258789, 51.3600006103516, 52.3199996948242, 53.2799987792969,  
 54.2400016784668, 55.2000007629395, 56.1599998474121, 57.1199989318848,  
 58.0800018310547, 59.0400009155273, 60 ;

longitude = 0.5, 3.37199997901917, 6.24399995803833, 9.11600017547607,  
 11.9879999160767, 14.8599996566772, 17.7320003509521, 20.6040000915527,  
 23.4759998321533, 26.3479995727539, 29.2199993133545, 32.0919990539551,  
 34.9640007019043, 37.8359985351562, 40.7080001831055, 43.5800018310547,  
 46.4519996643066, 49.3240013122559, 52.1959991455078, 55.068000793457,  
 57.939998626709, 60.8120002746582, 63.6839981079102, 66.5559997558594,  
 69.4280014038086, 72.3000030517578, 75.1719970703125, 78.0439987182617,  
 80.9160003662109, 83.7880020141602, 86.6600036621094, 89.5319976806641,  
 92.4039993286133, 95.2760009765625, 98.1480026245117, 101.019996643066,  
 103.891998291016, 106.763999938965, 109.636001586914, 112.508003234863,  
 115.379997253418, 118.251998901367, 121.124000549316, 123.996002197266,  
 126.86799621582, 129.740005493164, 132.611999511719, 135.483993530273,  
 138.356002807617, 141.227996826172, 144.100006103516, 146.97200012207,  
 149.843994140625, 152.716003417969, 155.587997436523, 158.460006713867,  
 161.332000732422, 164.203994750977, 167.07600402832, 169.947998046875,  
 172.820007324219, 175.692001342773, 178.563995361328, 181.436004638672,  
 184.307998657227, 187.179992675781, 190.052001953125, 192.92399597168,  
 195.796005249023, 198.667999267578, 201.539993286133, 204.412002563477,  
 207.283996582031, 210.156005859375, 213.02799987793, 215.899993896484,  
 218.772003173828, 221.643997192383, 224.516006469727, 227.388000488281,  
 230.259994506836, 233.13200378418, 236.003997802734, 238.876007080078,  
 241.748001098633, 244.619995117188, 247.492004394531, 250.363998413086,  
 253.235992431641, 256.108001708984, 258.980010986328, 261.851989746094,  
 264.723999023438, 267.596008300781, 270.467987060547, 273.339996337891,  
 276.212005615234, 279.084014892578, 281.955993652344, 284.828002929688,  
 287.700012207031, 290.571990966797, 293.444000244141, 296.316009521484,  
 299.18798828125, 302.059997558594, 304.932006835938, 307.803985595703,  
 310.675994873047, 313.548004150391, 316.420013427734, 319.2919921875,  
 322.164001464844, 325.036010742188, 327.907989501953, 330.779998779297,  
 333.652008056641, 336.523986816406, 339.39599609375, 342.268005371094,  
 345.140014648438, 348.011993408203, 350.884002685547, 353.756011962891,  
 356.627990722656, 359.5 ;

```
vertices_latitude =  
-60.25, -59.75,  
-59.2900009155273, -58.7900009155273,  
-58.3300018310547, -57.8300018310547,  
-57.3699989318848, -56.8699989318848,  
-56.409998474121, -55.909998474121,  
-55.4500007629395, -54.9500007629395,  
-54.4900016784668, -53.9900016784668,  
-53.5299987792969, -53.0299987792969,  
-52.5699996948242, -52.0699996948242,  
-51.6100006103516, -51.1100006103516,  
-50.6500015258789, -50.1500015258789,  
-49.689998626709, -49.189998626709,  
-48.7299995422363, -48.2299995422363,  
-47.7700004577637, -47.2700004577637,  
-46.810001373291, -46.310001373291,  
-45.8499984741211, -45.3499984741211,  
-44.8899993896484, -44.3899993896484,  
-43.9300003051758, -43.4300003051758,  
-42.9700012207031, -42.4700012207031,  
-42.0099983215332, -41.5099983215332,  
-41.0499992370605, -40.5499992370605,  
-40.0900001525879, -39.5900001525879,  
-39.1300010681152, -38.6300010681152,  
-38.1699981689453, -37.6699981689453,  
-37.2099990844727, -36.7099990844727,  
-36.25, -35.75,  
-35.2900009155273, -34.7900009155273,  
-34.3300018310547, -33.8300018310547,  
-33.3699989318848, -32.8699989318848,  
-32.409998474121, -31.909998474121,  
-31.4500007629395, -30.9500007629395,  
-30.4899997711182, -29.9899997711182,  
-29.5300006866455, -29.0300006866455,  
-28.5699996948242, -28.0699996948242,  
-27.6100006103516, -27.1100006103516,  
-26.6499996185303, -26.1499996185303,  
-25.6900005340576, -25.1900005340576,  
-24.7299995422363, -24.2299995422363,  
-23.7700004577637, -23.2700004577637,  
-22.8099994659424, -22.3099994659424,  
-21.8500003814697, -21.3500003814697,  
-20.8899993896484, -20.3899993896484,  
-19.9300003051758, -19.4300003051758,  
-18.9699993133545, -18.4699993133545,  
-18.0100002288818, -17.5100002288818,  
-17.0499992370605, -16.5499992370605,  
-16.0900001525879, -15.5900001525879,  
-15.1300001144409, -14.6300001144409,  
-14.1700000762939, -13.6700000762939,
```

-13.210000038147, -12.710000038147,  
-12.25, -11.75,  
-11.289999961853, -10.789999961853,  
-10.3299999237061, -9.82999992370605,  
-9.36999988555908, -8.86999988555908,  
-8.40999984741211, -7.90999984741211,  
-7.44999980926514, -6.94999980926514,  
-6.48999977111816, -5.98999977111816,  
-5.53000020980835, -5.03000020980835,  
-4.57000017166138, -4.07000017166138,  
-3.60999989509583, -3.10999989509583,  
-2.65000009536743, -2.15000009536743,  
-1.69000005722046, -1.19000005722046,  
-0.730000019073486, -0.229999989271164,  
0.229999989271164, 0.730000019073486,  
1.19000005722046, 1.69000005722046,  
2.15000009536743, 2.65000009536743,  
3.10999989509583, 3.60999989509583,  
4.07000017166138, 4.57000017166138,  
5.03000020980835, 5.53000020980835,  
5.98999977111816, 6.48999977111816,  
6.94999980926514, 7.44999980926514,  
7.90999984741211, 8.40999984741211,  
8.86999988555908, 9.36999988555908,  
9.82999992370605, 10.3299999237061,  
10.789999961853, 11.289999961853,  
11.75, 12.25,  
12.710000038147, 13.210000038147,  
13.6700000762939, 14.1700000762939,  
14.6300001144409, 15.1300001144409,  
15.5900001525879, 16.0900001525879,  
16.5499992370605, 17.0499992370605,  
17.5100002288818, 18.0100002288818,  
18.4699993133545, 18.9699993133545,  
19.4300003051758, 19.9300003051758,  
20.3899993896484, 20.8899993896484,  
21.3500003814697, 21.8500003814697,  
22.3099994659424, 22.8099994659424,  
23.2700004577637, 23.7700004577637,  
24.2299995422363, 24.7299995422363,  
25.1900005340576, 25.6900005340576,  
26.1499996185303, 26.6499996185303,  
27.1100006103516, 27.6100006103516,  
28.0699996948242, 28.5699996948242,  
29.0300006866455, 29.5300006866455,  
29.9899997711182, 30.4899997711182,  
30.9500007629395, 31.4500007629395,  
31.9099998474121, 32.4099998474121,  
32.86999989318848, 33.36999989318848,  
33.8300018310547, 34.3300018310547,

```

34.79000009155273, 35.29000009155273,
35.75, 36.25,
36.7099990844727, 37.2099990844727,
37.6699981689453, 38.1699981689453,
38.6300010681152, 39.1300010681152,
39.59000001525879, 40.09000001525879,
40.5499992370605, 41.0499992370605,
41.5099983215332, 42.0099983215332,
42.4700012207031, 42.9700012207031,
43.4300003051758, 43.9300003051758,
44.3899993896484, 44.8899993896484,
45.3499984741211, 45.8499984741211,
46.310001373291, 46.810001373291,
47.2700004577637, 47.7700004577637,
48.2299995422363, 48.7299995422363,
49.189998626709, 49.689998626709,
50.1500015258789, 50.6500015258789,
51.1100006103516, 51.6100006103516,
52.0699996948242, 52.5699996948242,
53.0299987792969, 53.5299987792969,
53.9900016784668, 54.4900016784668,
54.9500007629395, 55.4500007629395,
55.9099998474121, 56.4099998474121,
56.8699989318848, 57.3699989318848,
57.8300018310547, 58.3300018310547,
58.79000009155273, 59.29000009155273,
59.75, 60.25 ;

```

```

vertices_longitude =
0.25, 0.75,
3.12199997901917, 3.62199997901917,
5.99399995803833, 6.49399995803833,
8.86600017547607, 9.36600017547607,
11.7379999160767, 12.2379999160767,
14.6099996566772, 15.1099996566772,
17.4820003509521, 17.9820003509521,
20.3540000915527, 20.8540000915527,
23.2259998321533, 23.7259998321533,
26.0979995727539, 26.5979995727539,
28.9699993133545, 29.4699993133545,
31.8419990539551, 32.3419990539551,
34.7140007019043, 35.2140007019043,
37.5859985351562, 38.0859985351562,
40.4580001831055, 40.9580001831055,
43.3300018310547, 43.8300018310547,
46.2019996643066, 46.7019996643066,
49.0740013122559, 49.5740013122559,
51.9459991455078, 52.4459991455078,
54.818000793457, 55.318000793457,
57.689998626709, 58.189998626709,

```

60.5620002746582, 61.0620002746582,  
63.4339981079102, 63.9339981079102,  
66.3059997558594, 66.8059997558594,  
69.1780014038086, 69.6780014038086,  
72.0500030517578, 72.5500030517578,  
74.9219970703125, 75.4219970703125,  
77.7939987182617, 78.2939987182617,  
80.6660003662109, 81.1660003662109,  
83.5380020141602, 84.0380020141602,  
86.4100036621094, 86.9100036621094,  
89.2819976806641, 89.7819976806641,  
92.1539993286133, 92.6539993286133,  
95.0260009765625, 95.5260009765625,  
97.8980026245117, 98.3980026245117,  
100.769996643066, 101.269996643066,  
103.641998291016, 104.141998291016,  
106.513999938965, 107.013999938965,  
109.386001586914, 109.886001586914,  
112.258003234863, 112.758003234863,  
115.129997253418, 115.629997253418,  
118.001998901367, 118.501998901367,  
120.874000549316, 121.374000549316,  
123.746002197266, 124.246002197266,  
126.61799621582, 127.11799621582,  
129.490005493164, 129.990005493164,  
132.361999511719, 132.861999511719,  
135.233993530273, 135.733993530273,  
138.106002807617, 138.606002807617,  
140.977996826172, 141.477996826172,  
143.850006103516, 144.350006103516,  
146.72200012207, 147.22200012207,  
149.593994140625, 150.093994140625,  
152.466003417969, 152.966003417969,  
155.337997436523, 155.837997436523,  
158.210006713867, 158.710006713867,  
161.082000732422, 161.582000732422,  
163.953994750977, 164.453994750977,  
166.82600402832, 167.32600402832,  
169.697998046875, 170.197998046875,  
172.570007324219, 173.070007324219,  
175.442001342773, 175.942001342773,  
178.313995361328, 178.813995361328,  
181.186004638672, 181.686004638672,  
184.057998657227, 184.557998657227,  
186.929992675781, 187.429992675781,  
189.802001953125, 190.302001953125,  
192.67399597168, 193.17399597168,  
195.546005249023, 196.046005249023,  
198.417999267578, 198.917999267578,  
201.289993286133, 201.789993286133,

204.162002563477, 204.662002563477,  
207.033996582031, 207.533996582031,  
209.906005859375, 210.406005859375,  
212.77799987793, 213.27799987793,  
215.649993896484, 216.149993896484,  
218.522003173828, 219.022003173828,  
221.393997192383, 221.893997192383,  
224.266006469727, 224.766006469727,  
227.138000488281, 227.638000488281,  
230.009994506836, 230.509994506836,  
232.88200378418, 233.38200378418,  
235.753997802734, 236.253997802734,  
238.626007080078, 239.126007080078,  
241.498001098633, 241.998001098633,  
244.369995117188, 244.869995117188,  
247.242004394531, 247.742004394531,  
250.113998413086, 250.613998413086,  
252.985992431641, 253.485992431641,  
255.858001708984, 256.358001708984,  
258.730010986328, 259.230010986328,  
261.601989746094, 262.101989746094,  
264.473999023438, 264.973999023438,  
267.346008300781, 267.846008300781,  
270.217987060547, 270.717987060547,  
273.089996337891, 273.589996337891,  
275.962005615234, 276.462005615234,  
278.834014892578, 279.334014892578,  
281.705993652344, 282.205993652344,  
284.578002929688, 285.078002929688,  
287.450012207031, 287.950012207031,  
290.321990966797, 290.821990966797,  
293.194000244141, 293.694000244141,  
296.066009521484, 296.566009521484,  
298.93798828125, 299.43798828125,  
301.809997558594, 302.309997558594,  
304.682006835938, 305.182006835938,  
307.553985595703, 308.053985595703,  
310.425994873047, 310.925994873047,  
313.298004150391, 313.798004150391,  
316.170013427734, 316.670013427734,  
319.0419921875, 319.5419921875,  
321.914001464844, 322.414001464844,  
324.786010742188, 325.286010742188,  
327.657989501953, 328.157989501953,  
330.529998779297, 331.029998779297,  
333.402008056641, 333.902008056641,  
336.273986816406, 336.773986816406,  
339.14599609375, 339.64599609375,  
342.018005371094, 342.518005371094,  
344.890014648438, 345.390014648438,

```

347.761993408203, 348.261993408203,
350.634002685547, 351.134002685547,
353.506011962891, 354.006011962891,
356.377990722656, 356.877990722656,
359.25, 359.75 ;

height = 2 ;

tas =
275, 275.0598, 275.1195, 275.1793, 275.239, 275.2988, 275.3586, 275.4183,
275.4781, 275.5378, 275.5976, 275.6574, 275.7171, 275.7769, 275.8366,
275.8964, 275.9562, 276.0159, 276.0757, 276.1355, 276.1952, 276.255,
276.3147, 276.3745, 276.4343, 276.494, 276.5538, 276.6136, 276.6733,
276.7331, 276.7928, 276.8526, 276.9124, 276.9721, 277.0319, 277.0916,
277.1514, 277.2112, 277.2709, 277.3307, 277.3904, 277.4502, 277.5099,
277.5697, 277.6295, 277.6892, 277.749, 277.8088, 277.8685, 277.9283,
277.988, 278.0478, 278.1076, 278.1673, 278.2271, 278.2869, 278.3466,
278.4064, 278.4661, 278.5259, 278.5857, 278.6454, 278.7052, 278.765,
278.8247, 278.8845, 278.9442, 279.004, 279.0638, 279.1235, 279.1833,
279.243, 279.3028, 279.3625, 279.4223, 279.4821, 279.5418, 279.6016,
279.6613, 279.7211, 279.7809, 279.8406, 279.9004, 279.9602, 280.0199,
280.0797, 280.1394, 280.1992, 280.259, 280.3187, 280.3785, 280.4382,
280.498, 280.5578, 280.6175, 280.6773, 280.7371, 280.7968, 280.8566,
280.9163, 280.9761, 281.0359, 281.0956, 281.1554, 281.2151, 281.2749,
281.3347, 281.3944, 281.4542, 281.5139, 281.5737, 281.6335, 281.6932,
281.753, 281.8127, 281.8725, 281.9323, 281.992, 282.0518, 282.1115,
282.1713, 282.2311, 282.2908, 282.3506, 282.4104, 282.4701,
282.5299, 282.5896, 282.6494, 282.7092, 282.7689, 282.8287, 282.8885,
282.9482, 283.008, 283.0677, 283.1275, 283.1873, 283.247, 283.3068,
283.3665, 283.4263, 283.4861, 283.5458, 283.6056, 283.6653, 283.7251,
283.7849, 283.8446, 283.9044, 283.9641, 284.0239, 284.0837, 284.1434,
284.2032, 284.2629, 284.3227, 284.3825, 284.4422, 284.502, 284.5618,
284.6215, 284.6813, 284.741, 284.8008, 284.8606, 284.9203, 284.9801,
285.0398, 285.0996, 285.1594, 285.2191, 285.2789, 285.3387, 285.3984,
285.4582, 285.5179, 285.5777, 285.6375, 285.6972, 285.757, 285.8167,
285.8765, 285.9362, 285.996, 286.0558, 286.1155, 286.1753, 286.235,
286.2948, 286.3546, 286.4143, 286.4741, 286.5339, 286.5936, 286.6534,
286.7131, 286.7729, 286.8327, 286.8924, 286.9522, 287.012, 287.0717,
287.1315, 287.1912, 287.251, 287.3108, 287.3705, 287.4303, 287.4901,
287.5498, 287.6096, 287.6693, 287.7291, 287.7888, 287.8486, 287.9084,
287.9681, 288.0279, 288.0876, 288.1474, 288.2072, 288.2669, 288.3267,
288.3864, 288.4462, 288.506, 288.5657, 288.6255, 288.6853, 288.745,
288.8048, 288.8645, 288.9243, 288.9841, 289.0438, 289.1036, 289.1634,
289.2231, 289.2829, 289.3426, 289.4024, 289.4622, 289.5219, 289.5817,
289.6414, 289.7012, 289.761, 289.8207, 289.8805, 289.9402, 290 ;
}

```

# Fortran Examples

These examples are based on the CMOR repository's [examples/fortran](https://github.com/PCMDI/cmor/tree/main/examples/fortran) (<https://github.com/PCMDI/cmor/tree/main/examples/fortran>) directory. They use the same shared CMIP7 user input file as the Python examples and load CMIP7 tables from a local clone of [WCRP-CMIP/cmip7-cmor-tables](https://github.com/WCRP-CMIP/cmip7-cmor-tables) (<https://github.com/WCRP-CMIP/cmip7-cmor-tables>).

Create and activate a Conda or Mamba environment with CMOR and a Fortran compiler:

```
mamba create -n cmor-fortran -c conda-forge cmor fortran-compiler udunits2
mamba activate cmor-fortran
```

If you use Conda instead of Mamba, use the same package list:

```
conda create -n cmor-fortran -c conda-forge cmor fortran-compiler udunits2
conda activate cmor-fortran
```

Install the CMIP7 tables in the working directory where you will run the examples:

```
git clone https://github.com/WCRP-CMIP/cmip7-cmor-tables.git
```

Run the examples from a working directory that contains the `cmip7-cmor-tables` repository using the [run\\_examples.sh](#) (page 0) script:

```
chmod a+x run_examples.sh
./run_examples.sh
```

The examples expect tables under `./cmip7-cmor-tables/tables` in the directory where you run the script. To use a different table location, set `CMOR_TABLES_PATH` to the directory containing the CMIP7 table JSON files. To use a different user input file, set `CMOR_INPUT_PATH`.

Each example builds the CMIP7 compound variable name and uses it to read `CMIP7_cell_measures.json` and `CMIP7_long_name_overrides.json` before writing data. The fixed-field example overrides `frequency` from the shared user input file to `fx`.

## CMOR Input Files

- [CMIP7\\_input\\_example.json](#) (page 0)
- [CMIP7\\_coordinate.json](#)

([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_coordinate.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_coordinate.json))

- [CMIP7\\_formula\\_terms.json](#)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_formula\\_terms.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_formula_terms.json))
- [CMIP7\\_cell\\_measures.json](#)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_cell\\_measures.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_cell_measures.json))
- [CMIP7\\_long\\_name\\_overrides.json](#)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_long\\_name\\_overrides.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_long_name_overrides.json))
- [cmor-cvs.json](#)  
(<https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables-cvs/cmor-cvs.json>)

**Click to expand shared JSON input**

```
{
  "_AXIS_ENTRY_FILE": "CMIP7_coordinate.json",
  "_FORMULA_VAR_FILE": "CMIP7_formula_terms.json",
  "_cmip7_option": 1,
  "_controlled_vocabulary_file": "../tables-cvs/cmor-cvs.json",
  "activity_id": "CMIP",
  "archive_id": "WCRP",
  "calendar": "360_day",
  "experiment_id": "amip",
  "forcing_index": "f1",
  "frequency": "mon",
  "grid_label": "g999",
  "host_collection": "CMIP7",
  "initialization_index": "i1",
  "institution_id": "MOHC",
  "license_id": "CC-BY-4.0",
  "nominal_resolution": "100 km",
  "output": "output",
  "physics_index": "p1",
  "realization_index": "r1",
  "region": "glb",
  "source_id": "ACCESS-ESM1-6"
}
```

### Common Fortran Utilities

- [cmip7\\_fortran\\_common.f90](#) (page 0)
- [run\\_examples.sh](#) (page 0)

**Click to expand common Fortran code**

```

module cmip7_fortran_common
  use cmor_users_functions
  implicit none

  integer, parameter :: nlon = 4
  integer, parameter :: nlat = 3
  integer, parameter :: ntimes = 2
  real, parameter :: missing_value = 1.0e20

contains

  subroutine get_example_args(tables_path, input_path, output_dir)
    character(len=*), intent(out) :: tables_path
    character(len=*), intent(out) :: input_path
    character(len=*), intent(out) :: output_dir

    call get_command_argument(1, tables_path)
    call get_command_argument(2, input_path)
    call get_command_argument(3, output_dir)

    if (len_trim(tables_path) == 0) tables_path = "./cmip7-cmor-tables/tables"
    if (len_trim(input_path) == 0) input_path = "./CMIP7_input_example.json"
    if (len_trim(output_dir) == 0) output_dir = "output"
  end subroutine get_example_args

  subroutine load_shared_user_input(input_path, output_dir, frequency, &
    realization_index, forcing_index)
    character(len=*), intent(in) :: input_path
    character(len=*), intent(in) :: output_dir
    character(len=*), intent(in), optional :: frequency
    character(len=*), intent(in), optional :: realization_index
    character(len=*), intent(in), optional :: forcing_index
    integer :: ierr

    ierr = cmor_dataset_json(trim(input_path))
    call check_status("cmor_dataset_json", ierr)

    ierr = cmor_set_cur_dataset_attribute("outpath", trim(output_dir), 1)
    call check_status("cmor_set_cur_dataset_attribute(outpath)", ierr)

    if (present(frequency)) then
      ierr = cmor_set_cur_dataset_attribute("frequency", trim(frequency), 1)
      call check_status("cmor_set_cur_dataset_attribute(frequency)", ierr)
    endif

    if (present(realization_index)) then
      ierr = cmor_set_cur_dataset_attribute("realization_index", &
        trim(realization_index), 1)
      call check_status("cmor_set_cur_dataset_attribute(realization_index)", ier
r)

```

```

endif

if (present(forcing_index)) then
  ierr = cmor_set_cur_dataset_attribute("forcing_index", &
    trim(forcing_index), 1)
  call check_status("cmor_set_cur_dataset_attribute(forcing_index)", ierr)
endif
end subroutine load_shared_user_input

subroutine check_status(call_name, ierr)
  character(len=*), intent(in) :: call_name
  integer, intent(in) :: ierr

  if (ierr /= 0) then
    write(*, '(a, i0)') trim(call_name)//" failed with status ", ierr
    stop 1
  endif
end subroutine check_status

subroutine check_id(call_name, cmor_id)
  character(len=*), intent(in) :: call_name
  integer, intent(in) :: cmor_id

  if (cmor_id < 0) then
    write(*, '(a, i0)') trim(call_name)//" failed with id ", cmor_id
    stop 1
  endif
end subroutine check_id

subroutine check_grid_id(call_name, cmor_id)
  character(len=*), intent(in) :: call_name
  integer, intent(in) :: cmor_id

  if (cmor_id > -CMOR_MAX_GRIDS) then
    write(*, '(a, i0)') trim(call_name)//" failed with grid id ", cmor_id
    stop 1
  endif
end subroutine check_grid_id

subroutine apply_cmip7_variable_metadata(var_id, tables_path, realm, &
  table_entry, frequency, region)
  integer, intent(in) :: var_id
  character(len=*), intent(in) :: tables_path
  character(len=*), intent(in) :: realm
  character(len=*), intent(in) :: table_entry
  character(len=*), intent(in) :: frequency
  character(len=*), intent(in) :: region
  character(len=2048) :: compound_name
  character(len=2048) :: cell_measures
  character(len=2048) :: long_name

```

```

integer :: ierr
logical :: found

call cmip7_compound_name(realm, table_entry, frequency, region, &
    compound_name)

cell_measures = ""
call lookup_json_string(trim(tables_path)//"/CMIP7_cell_measures.json", &
    trim(compound_name), cell_measures, found)
ierr = cmor_set_variable_attribute(var_id, "cell_measures", &
    trim(cell_measures))
call check_status("cmor_set_variable_attribute(cell_measures)", ierr)

long_name = ""
call lookup_json_string(trim(tables_path)//"/CMIP7_long_name_overrides.js
n", &
    trim(compound_name), long_name, found)
if (found) then
    ierr = cmor_set_variable_attribute(var_id, "long_name", trim(long_name))
    call check_status("cmor_set_variable_attribute(long_name)", ierr)
endif
end subroutine apply_cmip7_variable_metadata

subroutine cmip7_compound_name(realm, table_entry, frequency, region, &
    compound_name)
character(len=*), intent(in) :: realm
character(len=*), intent(in) :: table_entry
character(len=*), intent(in) :: frequency
character(len=*), intent(in) :: region
character(len=*), intent(out) :: compound_name
character(len=1024) :: normalized_entry
integer :: i

normalized_entry = table_entry
do i = 1, len_trim(normalized_entry)
    if (normalized_entry(i:i) == "_") normalized_entry(i:i) = "."
enddo

compound_name = trim(realm)//"."//trim(normalized_entry)//"."// &
    trim(frequency)//"."//trim(region)
end subroutine cmip7_compound_name

subroutine lookup_json_string(path, key, value, found)
character(len=*), intent(in) :: path
character(len=*), intent(in) :: key
character(len=*), intent(out) :: value
logical, intent(out) :: found
character(len=8192) :: line
character(len=2050) :: search_key
integer :: colon_pos

```

```
integer :: ierr
integer :: quote_1
integer :: quote_2
integer :: start_pos
integer :: unit

value = ""
found = .false.
search_key = ''//trim(key)//''

open(newunit=unit, file=trim(path), status="old", action="read", &
      iostat=ierr)
if (ierr /= 0) then
  write(*, '(a)') "Could not open CMIP7 metadata table: "//trim(path)
  stop 1
endif

do
  read(unit, '(a)', iostat=ierr) line
  if (ierr /= 0) exit
  if (index(line, trim(search_key)) == 0) cycle

  colon_pos = index(line, ":")
  if (colon_pos == 0) exit

  quote_1 = index(line(colon_pos + 1:), '')
  if (quote_1 == 0) exit

  start_pos = colon_pos + quote_1
  quote_2 = index(line(start_pos + 1:), '')
  if (quote_2 == 0) exit

  value = line(start_pos + 1:start_pos + quote_2 - 1)
  found = .true.
  exit
enddo

close(unit)
end subroutine lookup_json_string

end module cmip7_fortran_common
```

**Click to expand runner script**

```

#!/usr/bin/env bash
set -euo pipefail

SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
RUN_DIR="${RUN_DIR:-$PWD}"
TABLES_PATH="${CMOR_TABLES_PATH:-$RUN_DIR/cmip7-cmor-tables/tables}"
INPUT_PATH="${CMOR_INPUT_PATH:-$RUN_DIR/CMIP7_input_example.json}"
OUTPUT_ROOT="$SCRIPT_DIR/output"
BUILD_DIR="${BUILD_DIR:-$SCRIPT_DIR/build}"

cd "$SCRIPT_DIR"

if [[ -z "${CONDA_PREFIX:-}" ]]; then
    echo "Activate your conda environment or run: conda run -n <env-name> $0" >&2
    exit 2
fi

detect_fortran_compiler() {
    if [[ -n "${FC:-}" ]]; then
        command -v "$FC" >/dev/null 2>&1 || {
            echo "FC is set to '$FC', but that compiler was not found" >&2
            exit 2
        }
        echo "$FC"
        return
    fi

    local compiler
    for compiler in "$CONDA_PREFIX"/bin/*gfortran "$CONDA_PREFIX"/bin/gfortran; do
        if [[ -x "$compiler" ]]; then
            echo "$compiler"
            return
        fi
    done

    if command -v gfortran >/dev/null 2>&1; then
        command -v gfortran
        return
    fi

    echo "Could not find a Fortran compiler. Install gfortran in the active conda environment or set FC." >&2
    exit 2
}

mkdir -p "$BUILD_DIR" "$OUTPUT_ROOT"

if [[ ! -d "$TABLES_PATH" ]]; then
    echo "Could not find CMIP7 tables under $TABLES_PATH. Clone cmip7-cmor-tables or set CMOR_TABLES_PATH." >&2

```

```

    exit 2
fi

if [[ ! -f "$INPUT_PATH" ]]; then
    echo "Could not find CMIP7 user input JSON at $INPUT_PATH. Set CMOR_INPUT_PATH
to override it." >&2
    exit 2
fi

FC="$(detect_fortran_compiler)"
CMOR_PREFIX="${CMOR_PREFIX:-$CONDA_PREFIX}"
CMOR_MOD_DIR="${CMOR_MOD_DIR:-$CMOR_PREFIX/include}"

if [[ -n "${CMOR_LIB:-}" ]]; then
    CMOR_LINK_FLAGS=("${CMOR_LIB}")
elif [[ -f "$CMOR_PREFIX/lib/libcmor.a" ]]; then
    CMOR_LINK_FLAGS=("${CMOR_PREFIX/lib/libcmor.a}")
elif [[ -f "$CMOR_PREFIX/lib/libcmor.dylib" || -f "$CMOR_PREFIX/lib/libcmor.so"
]]; then
    CMOR_LINK_FLAGS=("-L$CMOR_PREFIX/lib" "-lcmor")
else
    echo "Could not find CMOR in $CMOR_PREFIX. Install cmor in the active conda env
ironment or set CMOR_PREFIX/CMOR_LIB." >&2
    exit 2
fi

if [[ ! -f "$CMOR_MOD_DIR/cmor_users_functions.mod" ]]; then
    echo "Could not find cmor_users_functions.mod in $CMOR_MOD_DIR. Install cmor in
the active conda environment or set CMOR_MOD_DIR." >&2
    exit 2
fi

FFLAGS_DEFAULT="-g -O2 -ffree-line-length-none"
FFLAGS="${FFLAGS:-$FFLAGS_DEFAULT}"
EXTRA_LDFLAGS="${EXTRA_LDFLAGS:-}"
LINK_DIRS=("${CMOR_PREFIX/lib}")
if [[ "$CONDA_PREFIX/lib" != "$CMOR_PREFIX/lib" ]]; then
    LINK_DIRS+=("$CONDA_PREFIX/lib")
fi

LINK_FLAGS=("${CMOR_LINK_FLAGS[@]}")
for link_dir in "${LINK_DIRS[@]"; do
    LINK_FLAGS+=("-L$link_dir")
done
LINK_FLAGS+=("-lnetcdf" "-ludunits2" "-ljson-c" "-luuid" "-lm")
for link_dir in "${LINK_DIRS[@]"; do
    if [[ "$(uname -s)" != "Darwin" || "$link_dir" != "$CONDA_PREFIX/lib" ]]; then
        LINK_FLAGS+=("-Wl,-rpath,$link_dir")
    fi
done

```

```

INCLUDES=("-I$CMOR_MOD_DIR" "-I$BUILD_DIR" "-I$CONDA_PREFIX/include")
COMMON_SRC="$SCRIPT_DIR/cmip7_fortran_common.f90"

examples=(
  example_01_regular_grid_tos
  example_02_pressure_levels
  example_03_scalar_height_tas
  example_04_basin_axis
  example_05_hybrid_sigma_levels
  example_06_curvilinear_grid
  example_07_fixed_field_rootd
  example_08_site_dimension
)

for example in "${examples[@]}; do
  src="$SCRIPT_DIR/$example.f90"
  exe="$BUILD_DIR/$example"
  run_output="$OUTPUT_ROOT/$example"
  mkdir -p "$run_output"

  echo "Compiling $example"
  "$FC" $FFLAGS -J "$BUILD_DIR" "${INCLUDES[@]}" "$COMMON_SRC" "$src" "${LINK_FLAGS[@]}" $EXTRA_LDFLAGS -o "$exe"

  echo "Running $example"
  "$exe" "$TABLES_PATH" "$INPUT_PATH" "$run_output"
done

echo "Wrote CMIP7 example output under $OUTPUT_ROOT"

```

### Example 1: Regular Grid Ocean Field

- [example\\_01\\_regular\\_grid\\_tos.f90 \(page 0\)](#)

**Click to expand Fortran code**

```
program example_01_regular_grid_tos
  use cmip7_fortran_common
  implicit none

  character(len=1024) :: output_dir
  character(len=2048) :: tables_path
  character(len=2048) :: input_path
  integer :: lat_id
  integer :: lon_id
  integer :: time_id
  integer :: var_id
  integer :: ierr
  integer :: nul_pos
  real :: tos(nlon, nlat, ntimes)
  character(len=2048) :: filename
  double precision :: lat(nlat)
  double precision :: lon(nlon)
  double precision :: time(ntimes)
  double precision :: lat_bnds(2, nlat)
  double precision :: lon_bnds(2, nlon)
  double precision :: time_bnds(2, ntimes)

  call get_example_args(tables_path, input_path, output_dir)

  ierr = cmor_setup(inpath=trim(tables_path), &
    netcdf_file_action=CMOR_REPLACE, &
    exit_control=CMOR_EXIT_ON_MAJOR)
  call check_status("cmor_setup", ierr)

  call load_shared_user_input(input_path, output_dir)

  ierr = cmor_load_table("CMIP7_ocean.json")
  call check_id("cmor_load_table(CMIP7_ocean)", ierr)

  lat = (/ 10.0d0, 20.0d0, 30.0d0 /)
  lat_bnds(:, 1) = (/ 5.0d0, 15.0d0 /)
  lat_bnds(:, 2) = (/ 15.0d0, 25.0d0 /)
  lat_bnds(:, 3) = (/ 25.0d0, 35.0d0 /)

  lon = (/ 0.0d0, 90.0d0, 180.0d0, 270.0d0 /)
  lon_bnds(:, 1) = (/ -45.0d0, 45.0d0 /)
  lon_bnds(:, 2) = (/ 45.0d0, 135.0d0 /)
  lon_bnds(:, 3) = (/ 135.0d0, 225.0d0 /)
  lon_bnds(:, 4) = (/ 225.0d0, 315.0d0 /)

  time = (/ 15.5d0, 45.5d0 /)
  time_bnds(:, 1) = (/ 0.0d0, 31.0d0 /)
  time_bnds(:, 2) = (/ 31.0d0, 60.0d0 /)

  lon_id = cmor_axis(table="CMIP7_ocean.json", &
```

```
        table_entry="longitude", &
        units="degrees_east", &
        length=nlon, &
        coord_vals=lon, &
        cell_bounds=lon_bnds)
call check_id("cmor_axis(longitude)", lon_id)

lat_id = cmor_axis(table="CMIP7_ocean.json", &
        table_entry="latitude", &
        units="degrees_north", &
        length=nlat, &
        coord_vals=lat, &
        cell_bounds=lat_bnds)
call check_id("cmor_axis(latitude)", lat_id)

time_id = cmor_axis(table="CMIP7_ocean.json", &
        table_entry="time", &
        units="days since 1979-01-01", &
        length=ntimes, &
        coord_vals=time, &
        cell_bounds=time_bnds)
call check_id("cmor_axis(time)", time_id)

tos(:, :, 1) = reshape((/ &
        254.0895, 258.4085, missing_value, 258.7101, &
        258.6680, 258.2990, missing_value, 255.0432, &
        253.7254, 251.2460, missing_value, 255.4808 /), &
        (/ nlon, nlat /))
tos(:, :, 2) = reshape((/ &
        254.0995, 258.5085, missing_value, 258.8101, &
        258.8680, 258.4990, missing_value, 255.2432, &
        254.0254, 251.5460, missing_value, 255.7808 /), &
        (/ nlon, nlat /))

var_id = cmor_variable(table="CMIP7_ocean.json", &
        table_entry="tos_tavg-u-hxy-sea", &
        units="degC", &
        axis_ids=(/ lon_id, lat_id, time_id /), &
        missing_value=missing_value)
call check_id("cmor_variable(tos)", var_id)
call apply_cmip7_variable_metadata(var_id, tables_path, "ocean", &
        "tos_tavg-u-hxy-sea", "mon", "glb")

ierr = cmor_write(var_id, tos)
call check_status("cmor_write", ierr)

filename = ""
ierr = cmor_close(var_id, file_name=filename)
call check_status("cmor_close(var)", ierr)
nul_pos = index(filename, char(0))
```

```
if (nul_pos > 0) filename(nul_pos:) = " "  
write(*, '(a)') trim(filename)  
  
ierr = cmor_close()  
call check_status("cmor_close", ierr)  
end program example_01_regular_grid_tos
```

**Click to expand NetCDF dump**

```

netcdf tos_tavg-u-hxy-sea_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902
{
dimensions:
    time = UNLIMITED ; // (2 currently)
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float tos(time, lat, lon) ;
        tos:standard_name = "sea_surface_temperature" ;
        tos:long_name = "Sea Surface Temperature" ;
        tos:units = "degC" ;
        tos:cell_methods = "area: mean where sea time: mean" ;
        tos:missing_value = 1.e+20f ;
        tos:_FillValue = 1.e+20f ;
        tos:cell_measures = "area: areacello" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "sea" ;
    :branded_variable = "tos_tavg-u-hxy-sea" ;
    :branding_suffix = "tavg-u-hxy-sea" ;
    :creation_date = "2026-09-14T18:14:20Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;

```

```

:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacello" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:14:20Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/fortran/output/example_01_regular_grid_tos" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "ocean" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_ocean.json; Creation Date:(2026-07-21
13:16:24) MD5:734c6f53560fa60b7c1c21b38e5b9a3f" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/6dc45977-d9c6-432a-8aaa-fb53d6a6e22
4" ;
:variable_id = "tos" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

```

```
time = 15.5, 45.5 ;

time_bnds =
  0, 31,
  31, 60 ;

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

lon = 0, 90, 180, 270 ;

lon_bnds =
  -45, 45,
  45, 135,
  135, 225,
  225, 315 ;

tos =
  254.0895, 258.4085, _, 258.7101,
  258.668, 258.299, _, 255.0432,
  253.7254, 251.246, _, 255.4808,
  254.0995, 258.5085, _, 258.8101,
  258.868, 258.499, _, 255.2432,
  254.0254, 251.546, _, 255.7808 ;
}
```

### Example 2: 3-D Field on Pressure Levels

- [example\\_02\\_pressure\\_levels.f90](#) (page 0)

**Click to expand Fortran code**

```
program example_02_pressure_levels
  use cmip7_fortran_common
  implicit none

  integer, parameter :: nplev = 19
  character(len=1024) :: output_dir
  character(len=2048) :: tables_path
  character(len=2048) :: input_path
  integer :: lat_id
  integer :: lon_id
  integer :: time_id
  integer :: plev_id
  integer :: var_id
  integer :: ierr
  integer :: nul_pos
  integer :: i
  integer :: j
  integer :: k
  integer :: t
  real :: ta(nlon, nlat, nplev, ntimes)
  character(len=2048) :: filename
  double precision :: lat(nlat)
  double precision :: lon(nlon)
  double precision :: time(ntimes)
  double precision :: lat_bnds(2, nlat)
  double precision :: lon_bnds(2, nlon)
  double precision :: time_bnds(2, ntimes)
  double precision :: plev(nplev)

  call get_example_args(tables_path, input_path, output_dir)

  ierr = cmor_setup(inpath=trim(tables_path), &
    netcdf_file_action=CMOR_REPLACE, &
    exit_control=CMOR_EXIT_ON_MAJOR)
  call check_status("cmor_setup", ierr)

  call load_shared_user_input(input_path, output_dir)

  ierr = cmor_load_table("CMIP7_atmos.json")
  call check_id("cmor_load_table(CMIP7_atmos)", ierr)

  lat = (/ 10.0d0, 20.0d0, 30.0d0 /)
  lat_bnds(:, 1) = (/ 5.0d0, 15.0d0 /)
  lat_bnds(:, 2) = (/ 15.0d0, 25.0d0 /)
  lat_bnds(:, 3) = (/ 25.0d0, 35.0d0 /)

  lon = (/ 0.0d0, 90.0d0, 180.0d0, 270.0d0 /)
  lon_bnds(:, 1) = (/ -45.0d0, 45.0d0 /)
  lon_bnds(:, 2) = (/ 45.0d0, 135.0d0 /)
  lon_bnds(:, 3) = (/ 135.0d0, 225.0d0 /)
```

```

lon_bnds(:, 4) = (/ 225.0d0, 315.0d0 /)

time = (/ 15.5d0, 45.5d0 /)
time_bnds(:, 1) = (/ 0.0d0, 31.0d0 /)
time_bnds(:, 2) = (/ 31.0d0, 60.0d0 /)

lon_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="longitude", &
    units="degrees_east", &
    length=nlon, &
    coord_vals=lon, &
    cell_bounds=lon_bnds)
call check_id("cmor_axis(longitude)", lon_id)

lat_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="latitude", &
    units="degrees_north", &
    length=nlat, &
    coord_vals=lat, &
    cell_bounds=lat_bnds)
call check_id("cmor_axis(latitude)", lat_id)

time_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="time", &
    units="days since 1979-01-01", &
    length=ntimes, &
    coord_vals=time, &
    cell_bounds=time_bnds)
call check_id("cmor_axis(time)", time_id)

plev = (/ 100000.0d0, 92500.0d0, 85000.0d0, 70000.0d0, 60000.0d0, &
    50000.0d0, 40000.0d0, 30000.0d0, 25000.0d0, 20000.0d0, &
    15000.0d0, 10000.0d0, 7000.0d0, 5000.0d0, 3000.0d0, &
    2000.0d0, 1000.0d0, 500.0d0, 100.0d0 /)

plev_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="plev19", &
    units="Pa", &
    length=nplev, &
    coord_vals=plev)
call check_id("cmor_axis(plev19)", plev_id)

do t = 1, ntimes
    do k = 1, nplev
        do j = 1, nlat
            do i = 1, nlon
                ta(i, j, k, t) = 250.0 + 25.0 * real(i + 4*j + 12*k + 228*(t-1)) &
                    / real(nlon*nlat*nplev*ntimes)
            enddo
        enddo
    enddo
enddo

```

```
        enddo
    enddo
    ta(1, 1, 1, 1) = missing_value

    var_id = cmor_variable(table="CMIP7_atmos.json", &
        table_entry="ta_tavg-p19-hxy-air", &
        units="K", &
        axis_ids=(/ lon_id, lat_id, plev_id, time_id /), &
        missing_value=missing_value)
    call check_id("cmor_variable(ta)", var_id)
    call apply_cmip7_variable_metadata(var_id, tables_path, "atmos", &
        "ta_tavg-p19-hxy-air", "mon", "glb")

    ierr = cmor_write(var_id, ta)
    call check_status("cmor_write", ierr)

    filename = ""
    ierr = cmor_close(var_id, file_name=filename)
    call check_status("cmor_close(var)", ierr)
    nul_pos = index(filename, char(0))
    if (nul_pos > 0) filename(nul_pos:) = " "
    write(*, '(a)') trim(filename)

    ierr = cmor_close()
    call check_status("cmor_close", ierr)
end program example_02_pressure_levels
```

**Click to expand NetCDF dump**

```

netcdf ta_tavg-p19-hxy-air_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-19790
2 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    plev = 19 ;
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double plev(plev) ;
        plev:units = "Pa" ;
        plev:axis = "Z" ;
        plev:positive = "down" ;
        plev:long_name = "Pressure Levels (19)" ;
        plev:standard_name = "air_pressure" ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float ta(time, plev, lat, lon) ;
        ta:standard_name = "air_temperature" ;
        ta:long_name = "Air Temperature" ;
        ta:units = "K" ;
        ta:cell_methods = "area: time: mean where air" ;
        ta:missing_value = 1.e+20f ;
        ta:_FillValue = 1.e+20f ;
        ta:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;

```

```

:area_label = "air" ;
:branded_variable = "ta_tavg-p19-hxy-air" ;
:branding_suffix = "tavg-p19-hxy-air" ;
:creation_date = "2026-09-14T18:14:20Z" ;
:data_specs_version = "MIP-DS7.1.0.0" ;
:description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacella" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:14:20Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/fortran/output/example_02_pressure_levels" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/837662a2-90d4-4111-80ec-3f1031b559f
7" ;
:variable_id = "ta" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "p19" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack

```

nowledgment. The data producers and data providers make no warranty, either express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose. All liabilities arising from the supply of the information (including any liability arising in negligence) are excluded to the fullest extent permitted by law." ;

cmor\_version = "3.15.3" ;

data:

time = 15.5, 45.5 ;

time\_bnds =  
0, 31,  
31, 60 ;

plev = 100000, 92500, 85000, 70000, 60000, 50000, 40000, 30000, 25000,  
20000, 15000, 10000, 7000, 5000, 3000, 2000, 1000, 500, 100 ;

lat = 10, 20, 30 ;

lat\_bnds =  
5, 15,  
15, 25,  
25, 35 ;

lon = 0, 90, 180, 270 ;

lon\_bnds =  
-45, 45,  
45, 135,  
135, 225,  
225, 315 ;

ta =  
\_, 250.9868, 251.0417, 251.0965,  
251.1513, 251.2061, 251.261, 251.3158,  
251.3706, 251.4254, 251.4803, 251.5351,  
251.5899, 251.6447, 251.6996, 251.7544,  
251.8092, 251.864, 251.9189, 251.9737,  
252.0285, 252.0833, 252.1382, 252.193,  
252.2478, 252.3026, 252.3575, 252.4123,  
252.4671, 252.5219, 252.5768, 252.6316,  
252.6864, 252.7412, 252.7961, 252.8509,  
252.9057, 252.9605, 253.0154, 253.0702,  
253.125, 253.1798, 253.2346, 253.2895,  
253.3443, 253.3991, 253.4539, 253.5088,  
253.5636, 253.6184, 253.6732, 253.7281,  
253.7829, 253.8377, 253.8925, 253.9474,  
254.0022, 254.057, 254.1118, 254.1667,  
254.2215, 254.2763, 254.3311, 254.386,  
254.4408, 254.4956, 254.5504, 254.6053,

254.6601, 254.7149, 254.7697, 254.8246,  
254.8794, 254.9342, 254.989, 255.0439,  
255.0987, 255.1535, 255.2083, 255.2632,  
255.318, 255.3728, 255.4276, 255.4825,  
255.5373, 255.5921, 255.6469, 255.7018,  
255.7566, 255.8114, 255.8662, 255.9211,  
255.9759, 256.0307, 256.0855, 256.1404,  
256.1952, 256.25, 256.3048, 256.3596,  
256.4145, 256.4693, 256.5241, 256.5789,  
256.6338, 256.6886, 256.7434, 256.7982,  
256.8531, 256.9079, 256.9627, 257.0175,  
257.0724, 257.1272, 257.182, 257.2368,  
257.2917, 257.3465, 257.4013, 257.4561,  
257.511, 257.5658, 257.6206, 257.6754,  
257.7303, 257.7851, 257.8399, 257.8947,  
257.9496, 258.0044, 258.0592, 258.114,  
258.1689, 258.2237, 258.2785, 258.3333,  
258.3882, 258.443, 258.4978, 258.5526,  
258.6075, 258.6623, 258.7171, 258.7719,  
258.8268, 258.8816, 258.9364, 258.9912,  
259.0461, 259.1009, 259.1557, 259.2105,  
259.2654, 259.3202, 259.375, 259.4298,  
259.4846, 259.5395, 259.5943, 259.6491,  
259.7039, 259.7588, 259.8136, 259.8684,  
259.9232, 259.9781, 260.0329, 260.0877,  
260.1425, 260.1974, 260.2522, 260.307,  
260.3618, 260.4167, 260.4715, 260.5263,  
260.5811, 260.636, 260.6908, 260.7456,  
260.8004, 260.8553, 260.9101, 260.9649,  
261.0197, 261.0746, 261.1294, 261.1842,  
261.239, 261.2939, 261.3487, 261.4035,  
261.4583, 261.5132, 261.568, 261.6228,  
261.6776, 261.7325, 261.7873, 261.8421,  
261.8969, 261.9518, 262.0066, 262.0614,  
262.1162, 262.1711, 262.2259, 262.2807,  
262.3355, 262.3904, 262.4452, 262.5,  
262.5548, 262.6096, 262.6645, 262.7193,  
262.7741, 262.8289, 262.8838, 262.9386,  
262.9934, 263.0482, 263.1031, 263.1579,  
263.2127, 263.2675, 263.3224, 263.3772,  
263.432, 263.4868, 263.5417, 263.5965,  
263.6513, 263.7061, 263.761, 263.8158,  
263.8706, 263.9254, 263.9803, 264.0351,  
264.0899, 264.1447, 264.1996, 264.2544,  
264.3092, 264.364, 264.4189, 264.4737,  
264.5285, 264.5833, 264.6382, 264.693,  
264.7478, 264.8026, 264.8575, 264.9123,  
264.9671, 265.0219, 265.0768, 265.1316,  
265.1864, 265.2412, 265.2961, 265.3509,  
265.4057, 265.4605, 265.5154, 265.5702,

```
265.625, 265.6798, 265.7346, 265.7895,  
265.8443, 265.8991, 265.9539, 266.0088,  
266.0636, 266.1184, 266.1732, 266.2281,  
266.2829, 266.3377, 266.3925, 266.4474,  
266.5022, 266.557, 266.6118, 266.6667,  
266.7215, 266.7763, 266.8311, 266.886,  
266.9408, 266.9956, 267.0504, 267.1053,  
267.1601, 267.2149, 267.2697, 267.3246,  
267.3794, 267.4342, 267.489, 267.5439,  
267.5987, 267.6535, 267.7083, 267.7632,  
267.818, 267.8728, 267.9276, 267.9825,  
268.0373, 268.0921, 268.1469, 268.2018,  
268.2566, 268.3114, 268.3662, 268.4211,  
268.4759, 268.5307, 268.5855, 268.6404,  
268.6952, 268.75, 268.8048, 268.8596,  
268.9145, 268.9693, 269.0241, 269.0789,  
269.1338, 269.1886, 269.2434, 269.2982,  
269.3531, 269.4079, 269.4627, 269.5175,  
269.5724, 269.6272, 269.682, 269.7368,  
269.7917, 269.8465, 269.9013, 269.9561,  
270.011, 270.0658, 270.1206, 270.1754,  
270.2303, 270.2851, 270.3399, 270.3947,  
270.4496, 270.5044, 270.5592, 270.614,  
270.6689, 270.7237, 270.7785, 270.8333,  
270.8882, 270.943, 270.9978, 271.0526,  
271.1075, 271.1623, 271.2171, 271.2719,  
271.3268, 271.3816, 271.4364, 271.4912,  
271.5461, 271.6009, 271.6557, 271.7105,  
271.7654, 271.8202, 271.875, 271.9298,  
271.9846, 272.0395, 272.0943, 272.1491,  
272.2039, 272.2588, 272.3136, 272.3684,  
272.4232, 272.4781, 272.5329, 272.5877,  
272.6425, 272.6974, 272.7522, 272.807,  
272.8618, 272.9167, 272.9715, 273.0263,  
273.0811, 273.136, 273.1908, 273.2456,  
273.3004, 273.3553, 273.4101, 273.4649,  
273.5197, 273.5746, 273.6294, 273.6842,  
273.739, 273.7939, 273.8487, 273.9035,  
273.9583, 274.0132, 274.068, 274.1228,  
274.1776, 274.2325, 274.2873, 274.3421,  
274.3969, 274.4518, 274.5066, 274.5614,  
274.6162, 274.6711, 274.7259, 274.7807,  
274.8355, 274.8904, 274.9452, 275,  
275.0548, 275.1096, 275.1645, 275.2193,  
275.2741, 275.3289, 275.3838, 275.4386,  
275.4934, 275.5482, 275.6031, 275.6579,  
275.7127, 275.7675, 275.8224, 275.8772 ;  
}
```

### Example 3: Scalar Height Coordinate

- [example\\_03\\_scalar\\_height\\_tas.f90](#) (page 0)

**Click to expand Fortran code**

```
program example_03_scalar_height_tas
  use cmip7_fortran_common
  implicit none

  character(len=1024) :: output_dir
  character(len=2048) :: tables_path
  character(len=2048) :: input_path
  integer :: lat_id
  integer :: lon_id
  integer :: time_id
  integer :: height_id
  integer :: var_id
  integer :: ierr
  integer :: nul_pos
  real :: tas(nlon, nlat, ntimes)
  character(len=2048) :: filename
  double precision :: lat(nlat)
  double precision :: lon(nlon)
  double precision :: time(ntimes)
  double precision :: lat_bnds(2, nlat)
  double precision :: lon_bnds(2, nlon)
  double precision :: time_bnds(2, ntimes)

  call get_example_args(tables_path, input_path, output_dir)

  ierr = cmor_setup(inpath=trim(tables_path), &
    netcdf_file_action=CMOR_REPLACE, &
    exit_control=CMOR_EXIT_ON_MAJOR)
  call check_status("cmor_setup", ierr)

  call load_shared_user_input(input_path, output_dir, &
    realization_index="r9", forcing_index="f2")

  ierr = cmor_load_table("CMIP7_atmos.json")
  call check_id("cmor_load_table(CMIP7_atmos)", ierr)

  lat = (/ 10.0d0, 20.0d0, 30.0d0 /)
  lat_bnds(:, 1) = (/ 5.0d0, 15.0d0 /)
  lat_bnds(:, 2) = (/ 15.0d0, 25.0d0 /)
  lat_bnds(:, 3) = (/ 25.0d0, 35.0d0 /)

  lon = (/ 0.0d0, 90.0d0, 180.0d0, 270.0d0 /)
  lon_bnds(:, 1) = (/ -45.0d0, 45.0d0 /)
  lon_bnds(:, 2) = (/ 45.0d0, 135.0d0 /)
  lon_bnds(:, 3) = (/ 135.0d0, 225.0d0 /)
  lon_bnds(:, 4) = (/ 225.0d0, 315.0d0 /)

  time = (/ 15.5d0, 45.5d0 /)
  time_bnds(:, 1) = (/ 0.0d0, 31.0d0 /)
  time_bnds(:, 2) = (/ 31.0d0, 60.0d0 /)
```

```
lon_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="longitude", &
    units="degrees_east", &
    length=nlon, &
    coord_vals=lon, &
    cell_bounds=lon_bnds)
call check_id("cmor_axis(longitude)", lon_id)

lat_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="latitude", &
    units="degrees_north", &
    length=nlat, &
    coord_vals=lat, &
    cell_bounds=lat_bnds)
call check_id("cmor_axis(latitude)", lat_id)

time_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="time", &
    units="days since 1979-01-01", &
    length=ntimes, &
    coord_vals=time, &
    cell_bounds=time_bnds)
call check_id("cmor_axis(time)", time_id)

height_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="height2m", &
    units="m", &
    length=1, &
    coord_vals=(/ 2.0d0 /))
call check_id("cmor_axis(height2m)", height_id)

tas(:, :, 1) = reshape((/ &
    254.0895, 258.4085, 250.5549, 258.7101, &
    258.6680, 258.2990, 252.1237, 255.0432, &
    253.7254, 251.2460, 254.3168, 255.4808 /), &
    (/ nlon, nlat /))
tas(:, :, 2) = reshape((/ &
    259.7908, 252.2754, 257.1892, 253.3132, &
    253.8823, 253.4698, 253.5381, 254.9730, &
    256.1002, 251.8168, 259.3698, 250.2994 /), &
    (/ nlon, nlat /))

var_id = cmor_variable(table="CMIP7_atmos.json", &
    table_entry="tas_tavg-h2m-hxy-u", &
    units="K", &
    axis_ids=(/ lon_id, lat_id, time_id /), &
    missing_value=missing_value)
call check_id("cmor_variable(tas)", var_id)
call apply_cmip7_variable_metadata(var_id, tables_path, "atmos", &
```

```
      "tas_tavg-h2m-hxy-u", "mon", "glb")

      ierr = cmor_write(var_id, tas)
      call check_status("cmor_write", ierr)

      filename = ""
      ierr = cmor_close(var_id, file_name=filename)
      call check_status("cmor_close(var)", ierr)
      nul_pos = index(filename, char(0))
      if (nul_pos > 0) filename(nul_pos:) = " "
      write(*, '(a)') trim(filename)

      ierr = cmor_close()
      call check_status("cmor_close", ierr)
end program example_03_scalar_height_tas
```

**Click to expand NetCDF dump**

```

netcdf tas_tavg-h2m-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r9i1p1f2_197901-197902
{
dimensions:
    time = UNLIMITED ; // (2 currently)
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    double height ;
        height:units = "m" ;
        height:axis = "Z" ;
        height:positive = "up" ;
        height:long_name = "height" ;
        height:standard_name = "height" ;
    float tas(time, lat, lon) ;
        tas:standard_name = "air_temperature" ;
        tas:long_name = "Near-Surface Air Temperature" ;
        tas:units = "K" ;
        tas:cell_methods = "area: time: mean" ;
        tas:history = "2026-09-14T18:14:21Z altered by CMOR: Treated scalar dimension: \'height\'. " ;
        tas:coordinates = "height" ;
        tas:missing_value = 1.e+20f ;
        tas:_FillValue = 1.e+20f ;
        tas:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;

```

```

:activity_id = "CMIP" ;
:archive_id = "WCRP" ;
:area_label = "u" ;
:branded_variable = "tas_tavg-h2m-hxy-u" ;
:branding_suffix = "tavg-h2m-hxy-u" ;
:creation_date = "2026-09-14T18:14:21Z" ;
:data_specs_version = "MIP-DS7.1.0.0" ;
:description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacella" ;
:forcing_index = "f2" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:14:21Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/fortran/output/example_03_scalar_height_tas" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r9" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/b9b49546-a487-46ef-ae81-a44201b52bd
8" ;

:variable_id = "tas" ;
:variant_label = "r9i1p1f2" ;
:vertical_label = "h2m" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativc
ommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/

```

```
docs/CMIP7/Guidance_for_users/#2-terms-of-use-and-citations-requirements for terms of use governing CMIP7 output, including citation requirements and proper acknowledgment. The data producers and data providers make no warranty, either express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose. All liabilities arising from the supply of the information (including any liability arising in negligence) are excluded to the fullest extent permitted by law." ;
```

```
      :cmor_version = "3.15.3" ;
```

```
data:
```

```
  time = 15.5, 45.5 ;
```

```
  time_bnds =
```

```
    0, 31,
```

```
    31, 60 ;
```

```
  lat = 10, 20, 30 ;
```

```
  lat_bnds =
```

```
    5, 15,
```

```
    15, 25,
```

```
    25, 35 ;
```

```
  lon = 0, 90, 180, 270 ;
```

```
  lon_bnds =
```

```
   -45, 45,
```

```
    45, 135,
```

```
    135, 225,
```

```
    225, 315 ;
```

```
  height = 2 ;
```

```
  tas =
```

```
    254.0895, 258.4085, 250.5549, 258.7101,
```

```
    258.668, 258.299, 252.1237, 255.0432,
```

```
    253.7254, 251.246, 254.3168, 255.4808,
```

```
    259.7908, 252.2754, 257.1892, 253.3132,
```

```
    253.8823, 253.4698, 253.5381, 254.973,
```

```
    256.1002, 251.8168, 259.3698, 250.2994 ;
```

```
}
```

#### Example 4: Basin Axis

- [example\\_04\\_basin\\_axis.f90](#) (page 0)

**Click to expand Fortran code**

```

program example_04_basin_axis
  use cmip7_fortran_common
  implicit none

  integer, parameter :: nbasin = 3
  character(len=1024) :: output_dir
  character(len=2048) :: tables_path
  character(len=2048) :: input_path
  character(len=21) :: basin_names(nbasin)
  integer :: lat_id
  integer :: time_id
  integer :: basin_id
  integer :: var_id
  integer :: ierr
  integer :: nul_pos
  real :: heat_transport(nlat, nbasin, ntimes)
  character(len=2048) :: filename
  double precision :: lat(nlat)
  double precision :: lat_bnds(2, nlat)
  double precision :: time(ntimes)
  double precision :: time_bnds(2, ntimes)

  call get_example_args(tables_path, input_path, output_dir)

  ierr = cmor_setup(inpath=trim(tables_path), &
    netcdf_file_action=CMOR_REPLACE, &
    exit_control=CMOR_EXIT_ON_MAJOR)
  call check_status("cmor_setup", ierr)

  call load_shared_user_input(input_path, output_dir)

  ierr = cmor_load_table("CMIP7_ocean.json")
  call check_id("cmor_load_table(CMIP7_ocean)", ierr)

  lat = (/ 10.0d0, 20.0d0, 30.0d0 /)
  lat_bnds(:, 1) = (/ 5.0d0, 15.0d0 /)
  lat_bnds(:, 2) = (/ 15.0d0, 25.0d0 /)
  lat_bnds(:, 3) = (/ 25.0d0, 35.0d0 /)

  lat_id = cmor_axis(table="CMIP7_ocean.json", &
    table_entry="latitude", &
    units="degrees_north", &
    length=nlat, &
    coord_vals=lat, &
    cell_bounds=lat_bnds)
  call check_id("cmor_axis(latitude)", lat_id)

  time = (/ 15.5d0, 45.5d0 /)
  time_bnds(:, 1) = (/ 0.0d0, 31.0d0 /)
  time_bnds(:, 2) = (/ 31.0d0, 60.0d0 /)

```

```

time_id = cmor_axis(table="CMIP7_ocean.json", &
    table_entry="time", &
    units="days since 1979-01-01", &
    length=ntimes, &
    coord_vals=time, &
    cell_bounds=time_bnds)
call check_id("cmor_axis(time)", time_id)

basin_names(1) = "atlantic_arctic_ocean"
basin_names(2) = "indian_pacific_ocean"
basin_names(3) = "global_ocean"
basin_id = cmor_axis(table="CMIP7_ocean.json", &
    table_entry="basin", &
    units="", &
    length=nbasin, &
    coord_vals=basin_names)
call check_id("cmor_axis(basin)", basin_id)

heat_transport(:, :, 1) = reshape((/ &
    -80.0, -84.0, -88.0, &
    -100.0, -104.0, -76.0, &
    -120.0, -92.0, -96.0 /), &
    (/ nlat, nbasin /))
heat_transport(:, :, 2) = reshape((/ &
    -79.0, -83.0, -87.0, &
    -99.0, -103.0, -75.0, &
    -107.0, -111.0, -115.0 /), &
    (/ nlat, nbasin /))

var_id = cmor_variable(table="CMIP7_ocean.json", &
    table_entry="htovgyre_tavg-u-hyb-sea", &
    units="W", &
    axis_ids=(/ lat_id, basin_id, time_id /), &
    missing_value=missing_value)
call check_id("cmor_variable(htovgyre)", var_id)
call apply_cmip7_variable_metadata(var_id, tables_path, "ocean", &
    "htovgyre_tavg-u-hyb-sea", "mon", "glb")

ierr = cmor_write(var_id, heat_transport)
call check_status("cmor_write", ierr)

filename = ""
ierr = cmor_close(var_id, file_name=filename)
call check_status("cmor_close(var)", ierr)
nul_pos = index(filename, char(0))
if (nul_pos > 0) filename(nul_pos:) = " "
write(*, '(a)') trim(filename)

ierr = cmor_close()
call check_status("cmor_close", ierr)

```

```
end program example_04_basin_axis
```

**Click to expand NetCDF dump**

```

netcdf htovgyre_tavg-u-hyb-sea_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-1
97902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    basin = 3 ;
    lat = 3 ;
    bnds = 2 ;
    strlen = 21 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    char sector(basin, strlen) ;
        sector:long_name = "Ocean Basin" ;
        sector:standard_name = "region" ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    float htovgyre(time, basin, lat) ;
        htovgyre:standard_name = "northward_ocean_heat_transport_due_t
o_gyre" ;
        htovgyre:long_name = "Northward Ocean Heat Transport Due to Gyr
e" ;
        htovgyre:units = "W" ;
        htovgyre:cell_methods = "depth: longitude: sum where sea (along
a zig-zag grid path spanning a basin) time: mean" ;
        htovgyre:missing_value = 1.e+20f ;
        htovgyre:_FillValue = 1.e+20f ;
        htovgyre:coordinates = "sector" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "sea" ;
    :branded_variable = "htovgyre_tavg-u-hyb-sea" ;
    :branding_suffix = "tavg-u-hyb-sea" ;
    :creation_date = "2026-09-14T18:14:22Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past wit
h prescribed sea surface temperatures and sea ice concentrations." ;

```

```

:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:14:22Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hyb" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/fortran/output/example_04_basin_axis" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "ocean" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_ocean.json; Creation Date:(2026-07-21
13:16:24) MD5:734c6f53560fa60b7c1c21b38e5b9a3f" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/55477a08-41ad-4bfd-9bfe-f3721a8e0b7
8" ;
:variable_id = "htovgyre" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

```

```
time = 15.5, 45.5 ;

time_bnds =
  0, 31,
  31, 60 ;

sector =
  "atlantic_arctic_ocean",
  "indian_pacific_ocean ",
  "global_ocean          " ;

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

htovgyre =
  -80, -84, -88,
  -100, -104, -76,
  -120, -92, -96,
  -79, -83, -87,
  -99, -103, -75,
  -107, -111, -115 ;
}
```

### Example 5: Hybrid Sigma Model Levels

- [example\\_05\\_hybrid\\_sigma\\_levels.f90 \(page 0\)](#)

**Click to expand Fortran code**

```
program example_05_hybrid_sigma_levels
  use cmip7_fortran_common
  implicit none

  integer, parameter :: nlev = 5
  character(len=1024) :: output_dir
  character(len=2048) :: tables_path
  character(len=2048) :: input_path
  integer :: lat_id
  integer :: lon_id
  integer :: time_id
  integer :: lev_id
  integer :: ps_id
  integer :: var_id
  integer :: ierr
  integer :: nul_pos
  integer :: i
  integer :: j
  integer :: k
  integer :: t
  real :: cl(nlon, nlat, nlev, ntimes)
  real :: ps(nlon, nlat, ntimes)
  character(len=2048) :: filename
  double precision :: lat(nlat)
  double precision :: lon(nlon)
  double precision :: time(ntimes)
  double precision :: lat_bnds(2, nlat)
  double precision :: lon_bnds(2, nlon)
  double precision :: time_bnds(2, ntimes)
  double precision :: lev(nlev)
  double precision :: lev_bnds(nlev + 1)
  double precision :: a_coeff(nlev)
  double precision :: b_coeff(nlev)
  double precision :: a_bnds(nlev + 1)
  double precision :: b_bnds(nlev + 1)
  double precision :: p0

  call get_example_args(tables_path, input_path, output_dir)

  ierr = cmor_setup(inpath=trim(tables_path), &
    netcdf_file_action=CMOR_REPLACE, &
    exit_control=CMOR_EXIT_ON_MAJOR)
  call check_status("cmor_setup", ierr)

  call load_shared_user_input(input_path, output_dir)

  ierr = cmor_load_table("CMIP7_atmos.json")
  call check_id("cmor_load_table(CMIP7_atmos)", ierr)

  lat = (/ 10.0d0, 20.0d0, 30.0d0 /)
```

```
lat_bnds(:, 1) = (/ 5.0d0, 15.0d0 /)
lat_bnds(:, 2) = (/ 15.0d0, 25.0d0 /)
lat_bnds(:, 3) = (/ 25.0d0, 35.0d0 /)

lon = (/ 0.0d0, 90.0d0, 180.0d0, 270.0d0 /)
lon_bnds(:, 1) = (/ -45.0d0, 45.0d0 /)
lon_bnds(:, 2) = (/ 45.0d0, 135.0d0 /)
lon_bnds(:, 3) = (/ 135.0d0, 225.0d0 /)
lon_bnds(:, 4) = (/ 225.0d0, 315.0d0 /)

time = (/ 15.5d0, 45.5d0 /)
time_bnds(:, 1) = (/ 0.0d0, 31.0d0 /)
time_bnds(:, 2) = (/ 31.0d0, 60.0d0 /)

lon_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="longitude", &
    units="degrees_east", &
    length=nlon, &
    coord_vals=lon, &
    cell_bounds=lon_bnds)
call check_id("cmor_axis(longitude)", lon_id)

lat_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="latitude", &
    units="degrees_north", &
    length=nlat, &
    coord_vals=lat, &
    cell_bounds=lat_bnds)
call check_id("cmor_axis(latitude)", lat_id)

time_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="time", &
    units="days since 1979-01-01", &
    length=ntimes, &
    coord_vals=time, &
    cell_bounds=time_bnds)
call check_id("cmor_axis(time)", time_id)

lev = (/ 0.92d0, 0.72d0, 0.50d0, 0.30d0, 0.10d0 /)
lev_bnds = (/ 1.00d0, 0.83d0, 0.61d0, 0.40d0, 0.20d0, 0.00d0 /)
lev_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="standard_hybrid_sigma", &
    units="1", &
    length=nlev, &
    coord_vals=lev, &
    cell_bounds=lev_bnds)
call check_id("cmor_axis(standard_hybrid_sigma)", lev_id)

a_coeff = (/ 0.12d0, 0.22d0, 0.30d0, 0.20d0, 0.10d0 /)
b_coeff = (/ 0.80d0, 0.50d0, 0.20d0, 0.10d0, 0.00d0 /)
```

```
a_bnds = (/ 0.06d0, 0.18d0, 0.26d0, 0.25d0, 0.15d0, 0.00d0 /)
b_bnds = (/ 0.94d0, 0.65d0, 0.35d0, 0.15d0, 0.05d0, 0.00d0 /)
p0 = 100000.0d0

ierr = cmor_zfactor(zaxis_id=lev_id, &
  zfactor_name="a", &
  axis_ids=(/ lev_id /), &
  zfactor_values=a_coeff, &
  zfactor_bounds=a_bnds)
call check_id("cmor_zfactor(a)", ierr)

ierr = cmor_zfactor(zaxis_id=lev_id, &
  zfactor_name="b", &
  axis_ids=(/ lev_id /), &
  zfactor_values=b_coeff, &
  zfactor_bounds=b_bnds)
call check_id("cmor_zfactor(b)", ierr)

ierr = cmor_zfactor(zaxis_id=lev_id, &
  zfactor_name="p0", &
  units="Pa", &
  zfactor_values=p0)
call check_id("cmor_zfactor(p0)", ierr)

ps_id = cmor_zfactor(zaxis_id=lev_id, &
  zfactor_name="ps", &
  axis_ids=(/ lon_id, lat_id, time_id /), &
  units="Pa")
call check_id("cmor_zfactor(ps)", ps_id)

do t = 1, ntimes
  do j = 1, nlat
    do i = 1, nlon
      ps(i, j, t) = 97000.0 + 400.0 * real(i - 1) &
        + 1600.0 * real(j - 1) + 100.0 * real(t - 1)
    enddo
  enddo
enddo

do t = 1, ntimes
  do k = 1, nlev
    do j = 1, nlat
      do i = 1, nlon
        cl(i, j, k, t) = 75.0 - 5.0 * real(k) - 1.2 * real(j - 1) &
          + 0.4 * real(i - 1) + 0.1 * real(t - 1)
      enddo
    enddo
  enddo
enddo
```

```
var_id = cmor_variable(table="CMIP7_atmos.json", &
    table_entry="cl_tavg-al-hxy-u", &
    units="%", &
    axis_ids=(/ lon_id, lat_id, lev_id, time_id /), &
    missing_value=missing_value)
call check_id("cmor_variable(cl)", var_id)
call apply_cmip7_variable_metadata(var_id, tables_path, "atmos", &
    "cl_tavg-al-hxy-u", "mon", "glb")

ierr = cmor_write(var_id, cl)
call check_status("cmor_write(cl)", ierr)
ierr = cmor_write(ps_id, ps, store_with=var_id)
call check_status("cmor_write(ps)", ierr)

filename = ""
ierr = cmor_close(var_id, file_name=filename)
call check_status("cmor_close(var)", ierr)
nul_pos = index(filename, char(0))
if (nul_pos > 0) filename(nul_pos:) = " "
write(*, '(a)') trim(filename)

ierr = cmor_close()
call check_status("cmor_close", ierr)
end program example_05_hybrid_sigma_levels
```

**Click to expand NetCDF dump**

```

netcdf cl_tavg-al-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    lev = 5 ;
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lev(lev) ;
        lev:bounds = "lev_bnds" ;
        lev:units = "1" ;
        lev:axis = "Z" ;
        lev:positive = "down" ;
        lev:long_name = "hybrid sigma pressure coordinate" ;
        lev:standard_name = "atmosphere_hybrid_sigma_pressure_coordinate" ;
        lev:formula = "p = a*p0 + b*ps" ;
        lev:formula_terms = "p0: p0 a: a b: b ps: ps" ;
    double lev_bnds(lev, bnds) ;
        lev_bnds:formula = "p = a*p0 + b*ps" ;
        lev_bnds:standard_name = "atmosphere_hybrid_sigma_pressure_coordinate" ;
        lev_bnds:units = "1" ;
        lev_bnds:formula_terms = "p0: p0 a: a_bnds b: b_bnds ps: ps" ;
    double p0 ;
        p0:standard_name = "reference_air_pressure_for_atmosphere_vertical_coordinate" ;
        p0:long_name = "vertical coordinate formula term: reference pressure" ;
        p0:units = "Pa" ;
    double a(lev) ;
        a:long_name = "vertical coordinate formula term: a" ;
    double b(lev) ;
        b:long_name = "vertical coordinate formula term: b" ;
    float ps(time, lat, lon) ;
        ps:standard_name = "air_pressure" ;
        ps:long_name = "Surface Air Pressure" ;
        ps:units = "Pa" ;
    double a_bnds(lev, bnds) ;
        a_bnds:long_name = "vertical coordinate formula term: a(k+1/2)" ;
    double b_bnds(lev, bnds) ;

```

```

        b_bnds:long_name = "vertical coordinate formula term: b(k+1/2)"
;
double lat(lat) ;
    lat:bounds = "lat_bnds" ;
    lat:units = "degrees_north" ;
    lat:axis = "Y" ;
    lat:long_name = "Latitude" ;
    lat:standard_name = "latitude" ;
double lat_bnds(lat, bnds) ;
double lon(lon) ;
    lon:bounds = "lon_bnds" ;
    lon:units = "degrees_east" ;
    lon:axis = "X" ;
    lon:long_name = "Longitude" ;
    lon:standard_name = "longitude" ;
double lon_bnds(lon, bnds) ;
float cl(time, lev, lat, lon) ;
    cl:standard_name = "cloud_area_fraction_in_atmosphere_layer" ;
    cl:long_name = "Percentage Cloud Cover" ;
    cl:units = "%" ;
    cl:cell_methods = "area: time: mean" ;
    cl:missing_value = 1.e+20f ;
    cl:_FillValue = 1.e+20f ;
    cl:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "u" ;
    :branded_variable = "cl_tavg-al-hxy-u" ;
    :branding_suffix = "tavg-al-hxy-u" ;
    :creation_date = "2026-09-14T18:14:23Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
    :drs_specs = "MIP-DRS7" ;
    :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
    :experiment_id = "amip" ;
    :external_variables = "areacella" ;
    :forcing_index = "f1" ;
    :frequency = "mon" ;
    :grid_label = "g999" ;
    :history = "2026-09-14T18:14:23Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
    :horizontal_label = "hxy" ;
    :host_collection = "CMIP7" ;
    :initialization_index = "i1" ;
    :institution = "Met Office Hadley Centre" ;

```

```

      :institution_id = "MOHC" ;
      :license_id = "CC-BY-4.0" ;
      :mip_era = "CMIP7" ;
      :nominal_resolution = "100 km" ;
      :outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/fortran/output/example_05_hybrid_sigma_levels" ;
      :physics_index = "p1" ;
      :product = "model-output" ;
      :realization_index = "r1" ;
      :realm = "atmos" ;
      :region = "glb" ;
      :source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;

      :source_id = "ACCESS-ESM1-6" ;
      :table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
      :temporal_label = "tavg" ;
      :title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
      :tracking_id = "hdl:21.14107/f01bee5f-af93-4266-8692-882d99a28d1
6" ;

      :variable_id = "cl" ;
      :variant_label = "r1i1p1f1" ;
      :vertical_label = "al" ;
      :license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
      :cmor_version = "3.15.3" ;
data:

  time = 15.5, 45.5 ;

  time_bnds =
    0, 31,
    31, 60 ;

  lev = 0.92, 0.72, 0.5, 0.3, 0.1 ;

  lev_bnds =
    1, 0.83,
    0.83, 0.61,
    0.61, 0.4,
    0.4, 0.2,

```

```
0.2, 0 ;

p0 = 100000 ;

a = 0.12, 0.22, 0.3, 0.2, 0.1 ;

b = 0.8, 0.5, 0.2, 0.1, 0 ;

ps =
  97000, 97400, 97800, 98200,
  98600, 99000, 99400, 99800,
  100200, 100600, 101000, 101400,
  97100, 97500, 97900, 98300,
  98700, 99100, 99500, 99900,
  100300, 100700, 101100, 101500 ;

a_bnds =
  0.06, 0.18,
  0.18, 0.26,
  0.26, 0.25,
  0.25, 0.15,
  0.15, 0 ;

b_bnds =
  0.94, 0.65,
  0.65, 0.35,
  0.35, 0.15,
  0.15, 0.05,
  0.05, 0 ;

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

lon = 0, 90, 180, 270 ;

lon_bnds =
  -45, 45,
  45, 135,
  135, 225,
  225, 315 ;

cl =
  70, 70.4, 70.8, 71.2,
  68.8, 69.2, 69.60001, 70,
  67.6, 68, 68.4, 68.8,
  65, 65.4, 65.8, 66.2,
```

```
63.8, 64.2, 64.6, 65,  
62.6, 63, 63.4, 63.8,  
60, 60.4, 60.8, 61.2,  
58.8, 59.2, 59.6, 60,  
57.6, 58, 58.4, 58.8,  
55, 55.4, 55.8, 56.2,  
53.8, 54.2, 54.6, 55,  
52.6, 53, 53.4, 53.8,  
50, 50.4, 50.8, 51.2,  
48.8, 49.2, 49.6, 50,  
47.6, 48, 48.4, 48.8,  
70.1, 70.5, 70.9, 71.3,  
68.9, 69.3, 69.7, 70.1,  
67.7, 68.1, 68.5, 68.89999,  
65.1, 65.5, 65.9, 66.3,  
63.9, 64.3, 64.7, 65.1,  
62.7, 63.1, 63.5, 63.9,  
60.1, 60.5, 60.9, 61.3,  
58.9, 59.3, 59.7, 60.1,  
57.7, 58.1, 58.5, 58.9,  
55.1, 55.5, 55.9, 56.3,  
53.9, 54.3, 54.7, 55.1,  
52.7, 53.1, 53.5, 53.9,  
50.1, 50.5, 50.9, 51.3,  
48.9, 49.3, 49.7, 50.1,  
47.7, 48.1, 48.5, 48.9 ;  
}
```

### Example 6: Curvilinear Grid

- [example\\_06\\_curvilinear\\_grid.f90 \(page 0\)](#)

**Click to expand Fortran code**

```
program example_06_curvilinear_grid
  use cmip7_fortran_common
  implicit none

  integer, parameter :: nx = 4
  integer, parameter :: ny = 3
  integer, parameter :: nvertices = 4
  character(len=1024) :: output_dir
  character(len=2048) :: tables_path
  character(len=2048) :: input_path
  integer :: x_id
  integer :: y_id
  integer :: time_id
  integer :: grid_id
  integer :: grid_table_id
  integer :: var_id
  integer :: ierr
  integer :: nul_pos
  integer :: i
  integer :: j
  integer :: t
  real :: hfls(nx, ny, ntimes)
  character(len=2048) :: filename
  double precision :: x(nx)
  double precision :: y(ny)
  double precision :: x_bnds(2, nx)
  double precision :: y_bnds(2, ny)
  double precision :: latitude(nx, ny)
  double precision :: longitude(nx, ny)
  double precision :: latitude_vertices(nvertices, nx, ny)
  double precision :: longitude_vertices(nvertices, nx, ny)
  double precision :: time(ntimes)
  double precision :: time_bnds(2, ntimes)
  character(len=30) :: parameter_names(6)
  character(len=1) :: parameter_units(6)
  double precision :: parameter_values(6)

  call get_example_args(tables_path, input_path, output_dir)

  ierr = cmor_setup(inpath=trim(tables_path), &
    netcdf_file_action=CMOR_REPLACE, &
    exit_control=CMOR_EXIT_ON_MAJOR)
  call check_status("cmor_setup", ierr)

  call load_shared_user_input(input_path, output_dir)

  grid_table_id = cmor_load_table("CMIP7_grids.json")
  call check_id("cmor_load_table(CMIP7_grids)", grid_table_id)
  call cmor_set_table(grid_table_id)
```

```

x = (/ 0.0d0, 10000.0d0, 20000.0d0, 30000.0d0 /)
x_bnds(:, 1) = (/ -5000.0d0, 5000.0d0 /)
x_bnds(:, 2) = (/ 5000.0d0, 15000.0d0 /)
x_bnds(:, 3) = (/ 15000.0d0, 25000.0d0 /)
x_bnds(:, 4) = (/ 25000.0d0, 35000.0d0 /)
y = (/ 0.0d0, 10000.0d0, 20000.0d0 /)
y_bnds(:, 1) = (/ -5000.0d0, 5000.0d0 /)
y_bnds(:, 2) = (/ 5000.0d0, 15000.0d0 /)
y_bnds(:, 3) = (/ 15000.0d0, 25000.0d0 /)

x_id = cmor_axis(table_entry="x", units="m", length=nx, &
    coord_vals=x, cell_bounds=x_bnds)
call check_id("cmor_axis(x)", x_id)
y_id = cmor_axis(table_entry="y", units="m", length=ny, &
    coord_vals=y, cell_bounds=y_bnds)
call check_id("cmor_axis(y)", y_id)

do j = 1, ny
    do i = 1, nx
        latitude(i, j) = 10.0d0 * dble(j) - 2.0d0 * dble(i - 1)
        longitude(i, j) = 280.0d0 + 10.0d0 * dble(i - 1) &
            + 2.0d0 * dble(j - 1)
        latitude_vertices(:, i, j) = (/ latitude(i, j) - 5.0d0, &
            latitude(i, j) - 4.0d0, latitude(i, j) + 5.0d0, &
            latitude(i, j) + 4.0d0 /)
        longitude_vertices(:, i, j) = (/ longitude(i, j) - 5.0d0, &
            longitude(i, j) + 5.0d0, longitude(i, j) + 5.0d0, &
            longitude(i, j) - 5.0d0 /)
    enddo
enddo

grid_id = cmor_grid(axis_ids=(/ x_id, y_id /), &
    latitude=latitude, &
    longitude=longitude, &
    latitude_vertices=latitude_vertices, &
    longitude_vertices=longitude_vertices)
call check_grid_id("cmor_grid", grid_id)

parameter_names = (/ "standard_parallel1", &
    "longitude_of_central_meridian", &
    "latitude_of_projection_origin", &
    "false_easting", &
    "false_northing", &
    "standard_parallel2" /)
parameter_units = (/ " ", " ", " ", " ", " ", " " /)
parameter_values = (/ -20.0d0, 175.0d0, 13.0d0, 8.0d0, 0.0d0, 20.0d0 /)
ierr = cmor_set_grid_mapping(grid_id, "lambert_conformal_conic", &
    parameter_names, parameter_values, parameter_units)
call check_status("cmor_set_grid_mapping", ierr)

```

```

ierr = cmor_load_table("CMIP7_atmos.json")
call check_id("cmor_load_table(CMIP7_atmos)", ierr)
time = (/ 15.5d0, 45.5d0 /)
time_bnds(:, 1) = (/ 0.0d0, 31.0d0 /)
time_bnds(:, 2) = (/ 31.0d0, 60.0d0 /)
time_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="time", &
    units="days since 1979-01-01", &
    length=ntimes, &
    coord_vals=time, &
    cell_bounds=time_bnds)
call check_id("cmor_axis(time)", time_id)

do t = 1, ntimes
  do j = 1, ny
    do i = 1, nx
      hfls(i, j, t) = 80.0 + 2.0 * real(i - 1) + 8.0 * real(j - 1) &
        + real(t - 1)
    enddo
  enddo
enddo

var_id = cmor_variable(table="CMIP7_atmos.json", &
    table_entry="hfls_tavg-u-hxy-u", &
    units="W m-2", &
    axis_ids=(/ grid_id, time_id /), &
    positive="up", &
    missing_value=missing_value)
call check_id("cmor_variable(hfls)", var_id)
call apply_cmip7_variable_metadata(var_id, tables_path, "atmos", &
    "hfls_tavg-u-hxy-u", "mon", "glb")

ierr = cmor_write(var_id, hfls)
call check_status("cmor_write", ierr)

filename = ""
ierr = cmor_close(var_id, file_name=filename)
call check_status("cmor_close(var)", ierr)
nul_pos = index(filename, char(0))
if (nul_pos > 0) filename(nul_pos:) = " "
write(*, '(a)') trim(filename)

ierr = cmor_close()
call check_status("cmor_close", ierr)
end program example_06_curvilinear_grid

```

**Click to expand NetCDF dump**

```

netcdf hfls_tavg-u-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    y = 3 ;
    x = 4 ;
    bnds = 2 ;
    vertices = 4 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double y(y) ;
        y:bounds = "y_bnds" ;
        y:units = "m" ;
        y:axis = "Y" ;
        y:long_name = "y coordinate of projection" ;
        y:standard_name = "projection_y_coordinate" ;
    double y_bnds(y, bnds) ;
    double x(x) ;
        x:bounds = "x_bnds" ;
        x:units = "m" ;
        x:axis = "X" ;
        x:long_name = "x coordinate of projection" ;
        x:standard_name = "projection_x_coordinate" ;
    double x_bnds(x, bnds) ;
    int lambert_conformal_conic ;
        lambert_conformal_conic:grid_mapping_name = "lambert_conformal_c
onic" ;
        lambert_conformal_conic:standard_parallel = -20., 20. ;
        lambert_conformal_conic:longitude_of_central_meridian = 175. ;
        lambert_conformal_conic:latitude_of_projection_origin = 13. ;
        lambert_conformal_conic:false_easting = 8. ;
        lambert_conformal_conic:false_northing = 0. ;
    double latitude(y, x) ;
        latitude:standard_name = "latitude" ;
        latitude:long_name = "latitude" ;
        latitude:units = "degrees_north" ;
        latitude:missing_value = 1.e+20 ;
        latitude:_FillValue = 1.e+20 ;
        latitude:bounds = "vertices_latitude" ;
    double longitude(y, x) ;
        longitude:standard_name = "longitude" ;
        longitude:long_name = "longitude" ;
        longitude:units = "degrees_east" ;
        longitude:missing_value = 1.e+20 ;

```

```

        longitude:_FillValue = 1.e+20 ;
        longitude:bounds = "vertices_longitude" ;
double vertices_latitude(y, x, vertices) ;
        vertices_latitude:units = "degrees_north" ;
        vertices_latitude:missing_value = 1.e+20 ;
        vertices_latitude:_FillValue = 1.e+20 ;
double vertices_longitude(y, x, vertices) ;
        vertices_longitude:units = "degrees_east" ;
        vertices_longitude:missing_value = 1.e+20 ;
        vertices_longitude:_FillValue = 1.e+20 ;
float hfls(time, y, x) ;
        hfls:standard_name = "surface_upward_latent_heat_flux" ;
        hfls:long_name = "Surface Upward Latent Heat Flux" ;
        hfls:units = "W m-2" ;
        hfls:cell_methods = "area: time: mean" ;
        hfls:missing_value = 1.e+20f ;
        hfls:_FillValue = 1.e+20f ;
        hfls:cell_measures = "area: areacella" ;
        hfls:grid_mapping = "lambert_conformal_conic" ;
        hfls:coordinates = "latitude longitude" ;

// global attributes:
        :Conventions = "CF-1.12" ;
        :activity_id = "CMIP" ;
        :archive_id = "WCRP" ;
        :area_label = "u" ;
        :branded_variable = "hfls_tavg-u-hxy-u" ;
        :branding_suffix = "tavg-u-hxy-u" ;
        :creation_date = "2026-09-14T18:14:24Z" ;
        :data_specs_version = "MIP-DS7.1.0.0" ;
        :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
        :drs_specs = "MIP-DRS7" ;
        :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
        :experiment_id = "amip" ;
        :external_variables = "areacella" ;
        :forcing_index = "f1" ;
        :frequency = "mon" ;
        :grid_label = "g999" ;
        :history = "2026-09-14T18:14:24Z ; CMOR rewrote data to be consistent
with CF-1.12 and CMIP7 data requirements." ;
        :horizontal_label = "hxy" ;
        :host_collection = "CMIP7" ;
        :initialization_index = "i1" ;
        :institution = "Met Office Hadley Centre" ;
        :institution_id = "MOHC" ;
        :license_id = "CC-BY-4.0" ;
        :mip_era = "CMIP7" ;
        :nominal_resolution = "100 km" ;

```

```

      :outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/fortran/output/example_06_curvilinear_grid" ;
      :physics_index = "p1" ;
      :product = "model-output" ;
      :realization_index = "r1" ;
      :realm = "atmos" ;
      :region = "glb" ;
      :source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
      :source_id = "ACCESS-ESM1-6" ;
      :table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
      :temporal_label = "tavg" ;
      :title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
      :tracking_id = "hdl:21.14107/4edaa789-35f4-4e3f-8f09-9a225a00194
e" ;
      :variable_id = "hfls" ;
      :variant_label = "r1i1p1f1" ;
      :vertical_label = "u" ;
      :license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
      :cmor_version = "3.15.3" ;
data:

  time = 15.5, 45.5 ;

  time_bnds =
    0, 31,
    31, 60 ;

  y = 0, 10000, 20000 ;

  y_bnds =
    -5000, 5000,
    5000, 15000,
    15000, 25000 ;

  x = 0, 10000, 20000, 30000 ;

  x_bnds =
    -5000, 5000,

```

```
5000, 15000,  
15000, 25000,  
25000, 35000 ;  
  
lambert_conformal_conic = _ ;  
  
latitude =  
10, 8, 6, 4,  
20, 18, 16, 14,  
30, 28, 26, 24 ;  
  
longitude =  
280, 290, 300, 310,  
282, 292, 302, 312,  
284, 294, 304, 314 ;  
  
vertices_latitude =  
5, 6, 15, 14,  
3, 4, 13, 12,  
1, 2, 11, 10,  
-1, 0, 9, 8,  
15, 16, 25, 24,  
13, 14, 23, 22,  
11, 12, 21, 20,  
9, 10, 19, 18,  
25, 26, 35, 34,  
23, 24, 33, 32,  
21, 22, 31, 30,  
19, 20, 29, 28 ;  
  
vertices_longitude =  
275, 285, 285, 275,  
285, 295, 295, 285,  
295, 305, 305, 295,  
305, 315, 315, 305,  
277, 287, 287, 277,  
287, 297, 297, 287,  
297, 307, 307, 297,  
307, 317, 317, 307,  
279, 289, 289, 279,  
289, 299, 299, 289,  
299, 309, 309, 299,  
309, 319, 319, 309 ;  
  
hfls =  
80, 82, 84, 86,  
88, 90, 92, 94,  
96, 98, 100, 102,  
81, 83, 85, 87,  
89, 91, 93, 95,
```

```
    97, 99, 101, 103 ;  
}
```

### Example 7: Fixed Field

- [example\\_07\\_fixed\\_field\\_rootd.f90 \(page 0\)](#)

**Click to expand Fortran code**

```
program example_07_fixed_field_rootd
  use cmip7_fortran_common
  implicit none

  character(len=1024) :: output_dir
  character(len=2048) :: tables_path
  character(len=2048) :: input_path
  integer :: lat_id
  integer :: lon_id
  integer :: var_id
  integer :: ierr
  integer :: nul_pos
  real :: rootd(nlon, nlat)
  character(len=2048) :: filename
  double precision :: lat(nlat)
  double precision :: lon(nlon)
  double precision :: lat_bnds(2, nlat)
  double precision :: lon_bnds(2, nlon)

  call get_example_args(tables_path, input_path, output_dir)

  ierr = cmor_setup(inpath=trim(tables_path), &
    netcdf_file_action=CMOR_REPLACE, &
    exit_control=CMOR_EXIT_ON_MAJOR)
  call check_status("cmor_setup", ierr)

  call load_shared_user_input(input_path, output_dir, "fx")

  ierr = cmor_load_table("CMIP7_land.json")
  call check_id("cmor_load_table(CMIP7_land)", ierr)

  lat = (/ 10.0d0, 20.0d0, 30.0d0 /)
  lat_bnds(:, 1) = (/ 5.0d0, 15.0d0 /)
  lat_bnds(:, 2) = (/ 15.0d0, 25.0d0 /)
  lat_bnds(:, 3) = (/ 25.0d0, 35.0d0 /)

  lon = (/ 0.0d0, 90.0d0, 180.0d0, 270.0d0 /)
  lon_bnds(:, 1) = (/ -45.0d0, 45.0d0 /)
  lon_bnds(:, 2) = (/ 45.0d0, 135.0d0 /)
  lon_bnds(:, 3) = (/ 135.0d0, 225.0d0 /)
  lon_bnds(:, 4) = (/ 225.0d0, 315.0d0 /)

  lon_id = cmor_axis(table="CMIP7_land.json", &
    table_entry="longitude", &
    units="degrees_east", &
    length=nlon, &
    coord_vals=lon, &
    cell_bounds=lon_bnds)
  call check_id("cmor_axis(longitude)", lon_id)
```

```

lat_id = cmor_axis(table="CMIP7_land.json", &
    table_entry="latitude", &
    units="degrees_north", &
    length=nlat, &
    coord_vals=lat, &
    cell_bounds=lat_bnds)
call check_id("cmor_axis(latitude)", lat_id)

rootd = reshape((/ &
    0.50, 0.45, missing_value, 0.55, &
    0.60, 0.60, missing_value, 0.55, &
    missing_value, 0.45, 0.50, 0.50 /), &
    (/ nlon, nlat /))

var_id = cmor_variable(table="CMIP7_land.json", &
    table_entry="rootd_ti-u-hxy-lnd", &
    units="m", &
    axis_ids=(/ lon_id, lat_id /), &
    missing_value=missing_value)
call check_id("cmor_variable(rootd)", var_id)
call apply_cmip7_variable_metadata(var_id, tables_path, "land", &
    "rootd_ti-u-hxy-lnd", "fx", "glb")

ierr = cmor_write(var_id, rootd)
call check_status("cmor_write", ierr)

filename = ""
ierr = cmor_close(var_id, file_name=filename)
call check_status("cmor_close(var)", ierr)
nul_pos = index(filename, char(0))
if (nul_pos > 0) filename(nul_pos:) = " "
write(*, '(a)') trim(filename)

ierr = cmor_close()
call check_status("cmor_close", ierr)
end program example_07_fixed_field_rootd

```

**Click to expand NetCDF dump**

```

netcdf rootd_ti-u-hxy-lnd_fx_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1 {
dimensions:
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float rootd(lat, lon) ;
        rootd:standard_name = "root_depth" ;
        rootd:long_name = "Maximum Root Depth" ;
        rootd:units = "m" ;
        rootd:cell_methods = "area: mean where land" ;
        rootd:missing_value = 1.e+20f ;
        rootd:_FillValue = 1.e+20f ;
        rootd:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "lnd" ;
    :branded_variable = "rootd_ti-u-hxy-lnd" ;
    :branding_suffix = "ti-u-hxy-lnd" ;
    :creation_date = "2026-09-14T18:14:24Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
    :drs_specs = "MIP-DRS7" ;
    :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
    :experiment_id = "amip" ;
    :external_variables = "areacella" ;
    :forcing_index = "f1" ;
    :frequency = "fx" ;
    :grid_label = "g999" ;
    :history = "2026-09-14T18:14:24Z ; CMOR rewrote data to be consistent
with CF-1.12 and CMIP7 data requirements." ;

```

```

:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/fortran/output/example_07_fixed_field_rootd" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "land" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_land.json; Creation Date:(2026-07-21
13:16:24) MD5:ea523449976b1c3cc3c14c1492f2fb74" ;
:temporal_label = "ti" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/8739c638-aed0-4767-a519-225cf8cb276
5" ;

:variable_id = "rootd" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

lon = 0, 90, 180, 270 ;

```

```
lon_bnds =  
  -45, 45,  
  45, 135,  
  135, 225,  
  225, 315 ;  
  
rootd =  
  0.5, 0.45, _, 0.55,  
  0.6, 0.6, _, 0.55,  
  _, 0.45, 0.5, 0.5 ;  
}
```

### Example 8: Site Dimension

- [example\\_08\\_site\\_dimension.f90 \(page 0\)](#)

**Click to expand Fortran code**

```
program example_08_site_dimension
  use cmip7_fortran_common
  implicit none

  integer, parameter :: nsites = 126
  integer, parameter :: nvertices = 2
  character(len=1024) :: output_dir
  character(len=2048) :: tables_path
  character(len=2048) :: input_path
  character(len=2048) :: filename
  integer :: time_id
  integer :: site_id
  integer :: height_id
  integer :: grid_id
  integer :: grid_table_id
  integer :: var_id
  integer :: ierr
  integer :: nul_pos
  integer :: site
  integer :: time_index
  real :: tas(nsites, ntimes)
  double precision :: time(ntimes)
  double precision :: time_bnds(2, ntimes)
  double precision :: site_values(nsites)
  double precision :: latitude(nsites)
  double precision :: longitude(nsites)
  double precision :: latitude_vertices(nvertices, nsites)
  double precision :: longitude_vertices(nvertices, nsites)

  call get_example_args(tables_path, input_path, output_dir)

  ierr = cmor_setup(inpath=trim(tables_path), &
    netcdf_file_action=CMOR_REPLACE, &
    exit_control=CMOR_EXIT_ON_MAJOR)
  call check_status("cmor_setup", ierr)

  call load_shared_user_input(input_path, output_dir)

  ierr = cmor_load_table("CMIP7_atmos.json")
  call check_id("cmor_load_table(CMIP7_atmos)", ierr)

  time = (/ 15.5d0, 45.5d0 /)
  time_bnds(:, 1) = (/ 0.0d0, 31.0d0 /)
  time_bnds(:, 2) = (/ 31.0d0, 60.0d0 /)
  time_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="time1", &
    units="days since 1979-01-01", &
    length=ntimes, &
    coord_vals=time, &
    cell_bounds=time_bnds)
```

```

call check_id("cmor_axis(time1)", time_id)

height_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="height2m", &
    units="m", &
    length=1, &
    coord_vals=(/ 2.0d0 /))
call check_id("cmor_axis(height2m)", height_id)

do site = 1, nsites
    site_values(site) = dble(site)
    latitude(site) = -60.0d0 + 120.0d0 * dble(site - 1) / dble(nsites - 1)
    longitude(site) = 0.5d0 + 359.0d0 * dble(site - 1) / dble(nsites - 1)
    latitude_vertices(:, site) = (/ latitude(site) - 0.25d0, &
        latitude(site) + 0.25d0 /)
    longitude_vertices(:, site) = (/ longitude(site) - 0.25d0, &
        longitude(site) + 0.25d0 /)
enddo
site_id = cmor_axis(table="CMIP7_atmos.json", &
    table_entry="site", &
    units="1", &
    length=nsites, &
    coord_vals=site_values)
call check_id("cmor_axis(site)", site_id)

grid_table_id = cmor_load_table("CMIP7_grids.json")
call check_id("cmor_load_table(CMIP7_grids)", grid_table_id)
call cmor_set_table(grid_table_id)
grid_id = cmor_grid(axis_ids=(/ site_id /), latitude=latitude, &
    longitude=longitude, latitude_vertices=latitude_vertices, &
    longitude_vertices=longitude_vertices)
call check_grid_id("cmor_grid", grid_id)

ierr = cmor_load_table("CMIP7_atmos.json")
call check_id("cmor_load_table(CMIP7_atmos)", ierr)
var_id = cmor_variable(table="CMIP7_atmos.json", &
    table_entry="tas_tpt-h2m-hs-u", &
    units="K", &
    axis_ids=(/ grid_id, time_id /), &
    missing_value=missing_value)
call check_id("cmor_variable(tas)", var_id)
call apply_cmip7_variable_metadata(var_id, tables_path, "atmos", &
    "tas_tpt-h2m-hs-u", "mon", "glb")

do time_index = 1, ntimes
    do site = 1, nsites
        tas(site, time_index) = 275.0 + 15.0 * &
            real((time_index - 1) * nsites + site - 1) / &
            real(ntimes * nsites - 1)
    enddo
enddo

```

```
enddo
ierr = cmor_write(var_id, tas)
call check_status("cmor_write", ierr)

filename = ""
ierr = cmor_close(var_id, file_name=filename)
call check_status("cmor_close(var)", ierr)
nul_pos = index(filename, char(0))
if (nul_pos > 0) filename(nul_pos:) = " "
write(*, '(a)') trim(filename)

ierr = cmor_close()
call check_status("cmor_close", ierr)
end program example_08_site_dimension
```

**Click to expand NetCDF dump**

```

netcdf tas_tpt-h2m-hs-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    site = 126 ;
    bnds = 2 ;
    vertices = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Points" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    int site(site) ;
        site:long_name = "site index" ;
    double latitude(site) ;
        latitude:standard_name = "latitude" ;
        latitude:long_name = "latitude" ;
        latitude:units = "degrees_north" ;
        latitude:missing_value = 1.e+20 ;
        latitude:_FillValue = 1.e+20 ;
        latitude:bounds = "vertices_latitude" ;
    double longitude(site) ;
        longitude:standard_name = "longitude" ;
        longitude:long_name = "longitude" ;
        longitude:units = "degrees_east" ;
        longitude:missing_value = 1.e+20 ;
        longitude:_FillValue = 1.e+20 ;
        longitude:bounds = "vertices_longitude" ;
    double vertices_latitude(site, vertices) ;
        vertices_latitude:units = "degrees_north" ;
        vertices_latitude:missing_value = 1.e+20 ;
        vertices_latitude:_FillValue = 1.e+20 ;
    double vertices_longitude(site, vertices) ;
        vertices_longitude:units = "degrees_east" ;
        vertices_longitude:missing_value = 1.e+20 ;
        vertices_longitude:_FillValue = 1.e+20 ;
    double height ;
        height:units = "m" ;
        height:axis = "Z" ;
        height:positive = "up" ;
        height:long_name = "height" ;
        height:standard_name = "height" ;
    float tas(time, site) ;
        tas:standard_name = "air_temperature" ;
        tas:long_name = "Near-Surface Air Temperature" ;
        tas:units = "K" ;
        tas:cell_methods = "area: point time: point" ;

```

```

        tas:history = "2026-09-14T18:14:25Z altered by CMOR: Treated scalar dimension: \height\" ;
        tas:coordinates = "height latitude longitude" ;
        tas:missing_value = 1.e+20f ;
        tas:_FillValue = 1.e+20f ;

// global attributes:
        :Conventions = "CF-1.12" ;
        :activity_id = "CMIP" ;
        :archive_id = "WCRP" ;
        :area_label = "u" ;
        :branded_variable = "tas_tpt-h2m-hs-u" ;
        :branding_suffix = "tpt-h2m-hs-u" ;
        :creation_date = "2026-09-14T18:14:25Z" ;
        :data_specs_version = "MIP-DS7.1.0.0" ;
        :description = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;
        :drs_specs = "MIP-DRS7" ;
        :experiment = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;
        :experiment_id = "amip" ;
        :forcing_index = "f1" ;
        :frequency = "mon" ;
        :grid_label = "g999" ;
        :history = "2026-09-14T18:14:25Z ; CMOR rewrote data to be consistent with CF-1.12 and CMIP7 data requirements." ;
        :horizontal_label = "hs" ;
        :host_collection = "CMIP7" ;
        :initialization_index = "i1" ;
        :institution = "Met Office Hadley Centre" ;
        :institution_id = "MOHC" ;
        :license_id = "CC-BY-4.0" ;
        :mip_era = "CMIP7" ;
        :nominal_resolution = "100 km" ;
        :outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/mydoc/examples/fortran/output/example_08_site_dimension" ;
        :physics_index = "p1" ;
        :product = "model-output" ;
        :realization_index = "r1" ;
        :realm = "atmos" ;
        :region = "glb" ;
        :source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; land-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: cice5" ;
        :source_id = "ACCESS-ESM1-6" ;
        :table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21 13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
        :temporal_label = "tpt" ;
        :title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
        :tracking_id = "hdl:21.14107/5208df6b-b34e-45cc-ad98-8a4d6dfe793

```

```

6" ;

      :variable_id = "tas" ;
      :variant_label = "r1i1p1f1" ;
      :vertical_label = "h2m" ;
      :license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
      :cmor_version = "3.15.3" ;
data:

time = 15.5, 45.5 ;

time_bnds =
  0, 31,
  31, 60 ;

site = 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19,
      20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37,
      38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55,
      56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73,
      74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,
      92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107,
      108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121,
      122, 123, 124, 125, 126 ;

latitude = -60, -59.04, -58.08, -57.12, -56.16, -55.2, -54.24, -53.28,
          -52.32, -51.36, -50.4, -49.44, -48.48, -47.52, -46.56, -45.6, -44.64,
          -43.68, -42.72, -41.76, -40.8, -39.84, -38.88, -37.92, -36.96, -36,
          -35.04, -34.08, -33.12, -32.16, -31.2, -30.24, -29.28, -28.32, -27.36,
          -26.4, -25.44, -24.48, -23.52, -22.56, -21.6, -20.64, -19.68, -18.72,
          -17.76, -16.8, -15.84, -14.88, -13.92, -12.96, -12, -11.04, -10.08,
          -9.12, -8.16, -7.2, -6.24, -5.28, -4.32, -3.36, -2.4, -1.44,
          -0.479999999999997, 0.479999999999997, 1.44, 2.4, 3.36, 4.31999999999999,
          5.28, 6.23999999999999, 7.2, 8.16, 9.12, 10.08, 11.04, 12, 12.96, 13.92,
          14.88, 15.84, 16.8, 17.76, 18.72, 19.68, 20.64, 21.6, 22.56, 23.52,
          24.48, 25.44, 26.4, 27.36, 28.32, 29.28, 30.24, 31.2, 32.16, 33.12,
          34.08, 35.04, 36, 36.96, 37.92, 38.88, 39.84, 40.8, 41.76, 42.72, 43.68,
          44.64, 45.6, 46.56, 47.52, 48.48, 49.44, 50.4, 51.36, 52.32, 53.28,
          54.24, 55.2, 56.16, 57.12, 58.08, 59.04, 60 ;

longitude = 0.5, 3.372, 6.244, 9.116, 11.988, 14.86, 17.732, 20.604, 23.476,
           26.348, 29.22, 32.092, 34.964, 37.836, 40.708, 43.58, 46.452, 49.324,
           52.196, 55.068, 57.94, 60.812, 63.684, 66.556, 69.428, 72.3, 75.172,

```

```
78.044, 80.916, 83.788, 86.66, 89.532, 92.404, 95.276, 98.148, 101.02,  
103.892, 106.764, 109.636, 112.508, 115.38, 118.252, 121.124, 123.996,  
126.868, 129.74, 132.612, 135.484, 138.356, 141.228, 144.1, 146.972,  
149.844, 152.716, 155.588, 158.46, 161.332, 164.204, 167.076, 169.948,  
172.82, 175.692, 178.564, 181.436, 184.308, 187.18, 190.052, 192.924,  
195.796, 198.668, 201.54, 204.412, 207.284, 210.156, 213.028, 215.9,  
218.772, 221.644, 224.516, 227.388, 230.26, 233.132, 236.004, 238.876,  
241.748, 244.62, 247.492, 250.364, 253.236, 256.108, 258.98, 261.852,  
264.724, 267.596, 270.468, 273.34, 276.212, 279.084, 281.956, 284.828,  
287.7, 290.572, 293.444, 296.316, 299.188, 302.06, 304.932, 307.804,  
310.676, 313.548, 316.42, 319.292, 322.164, 325.036, 327.908, 330.78,  
333.652, 336.524, 339.396, 342.268, 345.14, 348.012, 350.884, 353.756,  
356.628, 359.5 ;
```

```
vertices_latitude =
```

```
-60.25, -59.75,  
-59.29, -58.79,  
-58.33, -57.83,  
-57.37, -56.87,  
-56.41, -55.91,  
-55.45, -54.95,  
-54.49, -53.99,  
-53.53, -53.03,  
-52.57, -52.07,  
-51.61, -51.11,  
-50.65, -50.15,  
-49.69, -49.19,  
-48.73, -48.23,  
-47.77, -47.27,  
-46.81, -46.31,  
-45.85, -45.35,  
-44.89, -44.39,  
-43.93, -43.43,  
-42.97, -42.47,  
-42.01, -41.51,  
-41.05, -40.55,  
-40.09, -39.59,  
-39.13, -38.63,  
-38.17, -37.67,  
-37.21, -36.71,  
-36.25, -35.75,  
-35.29, -34.79,  
-34.33, -33.83,  
-33.37, -32.87,  
-32.41, -31.91,  
-31.45, -30.95,  
-30.49, -29.99,  
-29.53, -29.03,  
-28.57, -28.07,  
-27.61, -27.11,
```

-26.65, -26.15,  
-25.69, -25.19,  
-24.73, -24.23,  
-23.77, -23.27,  
-22.81, -22.31,  
-21.85, -21.35,  
-20.89, -20.39,  
-19.93, -19.43,  
-18.97, -18.47,  
-18.01, -17.51,  
-17.05, -16.55,  
-16.09, -15.59,  
-15.13, -14.63,  
-14.17, -13.67,  
-13.21, -12.71,  
-12.25, -11.75,  
-11.29, -10.79,  
-10.33, -9.83,  
-9.37, -8.87,  
-8.41, -7.91,  
-7.45, -6.95,  
-6.49, -5.99,  
-5.53, -5.03,  
-4.57, -4.07,  
-3.61, -3.11,  
-2.65, -2.15,  
-1.69, -1.19,  
-0.729999999999997, -0.229999999999997,  
0.229999999999997, 0.729999999999997,  
1.19, 1.69,  
2.15, 2.65,  
3.11, 3.61,  
4.069999999999999, 4.569999999999999,  
5.03, 5.53,  
5.989999999999999, 6.489999999999999,  
6.95, 7.45,  
7.91, 8.41,  
8.87, 9.37,  
9.83, 10.33,  
10.79, 11.29,  
11.75, 12.25,  
12.71, 13.21,  
13.67, 14.17,  
14.63, 15.13,  
15.59, 16.09,  
16.55, 17.05,  
17.51, 18.01,  
18.47, 18.97,  
19.43, 19.93,  
20.39, 20.89,

```
21.35, 21.85,  
22.31, 22.81,  
23.27, 23.77,  
24.23, 24.73,  
25.19, 25.69,  
26.15, 26.65,  
27.11, 27.61,  
28.07, 28.57,  
29.03, 29.53,  
29.99, 30.49,  
30.95, 31.45,  
31.91, 32.41,  
32.87, 33.37,  
33.83, 34.33,  
34.79, 35.29,  
35.75, 36.25,  
36.71, 37.21,  
37.67, 38.17,  
38.63, 39.13,  
39.59, 40.09,  
40.55, 41.05,  
41.51, 42.01,  
42.47, 42.97,  
43.43, 43.93,  
44.39, 44.89,  
45.35, 45.85,  
46.31, 46.81,  
47.27, 47.77,  
48.23, 48.73,  
49.19, 49.69,  
50.15, 50.65,  
51.11, 51.61,  
52.07, 52.57,  
53.03, 53.53,  
53.99, 54.49,  
54.95, 55.45,  
55.91, 56.41,  
56.87, 57.37,  
57.83, 58.33,  
58.79, 59.29,  
59.75, 60.25 ;
```

```
vertices_longitude =  
0.25, 0.75,  
3.122, 3.622,  
5.994, 6.494,  
8.866, 9.366,  
11.738, 12.238,  
14.61, 15.11,  
17.482, 17.982,
```

20.354, 20.854,  
23.226, 23.726,  
26.098, 26.598,  
28.97, 29.47,  
31.842, 32.342,  
34.714, 35.214,  
37.586, 38.086,  
40.458, 40.958,  
43.33, 43.83,  
46.202, 46.702,  
49.074, 49.574,  
51.946, 52.446,  
54.818, 55.318,  
57.69, 58.19,  
60.562, 61.062,  
63.434, 63.934,  
66.306, 66.806,  
69.178, 69.678,  
72.05, 72.55,  
74.922, 75.422,  
77.794, 78.294,  
80.666, 81.166,  
83.538, 84.038,  
86.41, 86.91,  
89.282, 89.782,  
92.154, 92.654,  
95.026, 95.526,  
97.898, 98.398,  
100.77, 101.27,  
103.642, 104.142,  
106.514, 107.014,  
109.386, 109.886,  
112.258, 112.758,  
115.13, 115.63,  
118.002, 118.502,  
120.874, 121.374,  
123.746, 124.246,  
126.618, 127.118,  
129.49, 129.99,  
132.362, 132.862,  
135.234, 135.734,  
138.106, 138.606,  
140.978, 141.478,  
143.85, 144.35,  
146.722, 147.222,  
149.594, 150.094,  
152.466, 152.966,  
155.338, 155.838,  
158.21, 158.71,  
161.082, 161.582,

163.954, 164.454,  
166.826, 167.326,  
169.698, 170.198,  
172.57, 173.07,  
175.442, 175.942,  
178.314, 178.814,  
181.186, 181.686,  
184.058, 184.558,  
186.93, 187.43,  
189.802, 190.302,  
192.674, 193.174,  
195.546, 196.046,  
198.418, 198.918,  
201.29, 201.79,  
204.162, 204.662,  
207.034, 207.534,  
209.906, 210.406,  
212.778, 213.278,  
215.65, 216.15,  
218.522, 219.022,  
221.394, 221.894,  
224.266, 224.766,  
227.138, 227.638,  
230.01, 230.51,  
232.882, 233.382,  
235.754, 236.254,  
238.626, 239.126,  
241.498, 241.998,  
244.37, 244.87,  
247.242, 247.742,  
250.114, 250.614,  
252.986, 253.486,  
255.858, 256.358,  
258.73, 259.23,  
261.602, 262.102,  
264.474, 264.974,  
267.346, 267.846,  
270.218, 270.718,  
273.09, 273.59,  
275.962, 276.462,  
278.834, 279.334,  
281.706, 282.206,  
284.578, 285.078,  
287.45, 287.95,  
290.322, 290.822,  
293.194, 293.694,  
296.066, 296.566,  
298.938, 299.438,  
301.81, 302.31,  
304.682, 305.182,

```
307.554, 308.054,  
310.426, 310.926,  
313.298, 313.798,  
316.17, 316.67,  
319.042, 319.542,  
321.914, 322.414,  
324.786, 325.286,  
327.658, 328.158,  
330.53, 331.03,  
333.402, 333.902,  
336.274, 336.774,  
339.146, 339.646,  
342.018, 342.518,  
344.89, 345.39,  
347.762, 348.262,  
350.634, 351.134,  
353.506, 354.006,  
356.378, 356.878,  
359.25, 359.75 ;
```

```
height = 2 ;
```

```
tas =
```

```
275, 275.0598, 275.1195, 275.1793, 275.239, 275.2988, 275.3586, 275.4183,  
275.4781, 275.5378, 275.5976, 275.6574, 275.7171, 275.7769, 275.8366,  
275.8964, 275.9562, 276.0159, 276.0757, 276.1355, 276.1952, 276.255,  
276.3147, 276.3745, 276.4343, 276.494, 276.5538, 276.6136, 276.6733,  
276.7331, 276.7928, 276.8526, 276.9124, 276.9721, 277.0319, 277.0916,  
277.1514, 277.2112, 277.2709, 277.3307, 277.3904, 277.4502, 277.5099,  
277.5697, 277.6295, 277.6892, 277.749, 277.8088, 277.8685, 277.9283,  
277.988, 278.0478, 278.1076, 278.1673, 278.2271, 278.2869, 278.3466,  
278.4064, 278.4661, 278.5259, 278.5857, 278.6454, 278.7052, 278.765,  
278.8247, 278.8845, 278.9442, 279.004, 279.0638, 279.1235, 279.1833,  
279.243, 279.3028, 279.3625, 279.4223, 279.4821, 279.5418, 279.6016,  
279.6613, 279.7211, 279.7809, 279.8406, 279.9004, 279.9601, 280.0199,  
280.0797, 280.1394, 280.1992, 280.259, 280.3187, 280.3785, 280.4382,  
280.498, 280.5578, 280.6175, 280.6773, 280.7371, 280.7968, 280.8566,  
280.9163, 280.9761, 281.0359, 281.0956, 281.1554, 281.2151, 281.2749,  
281.3347, 281.3944, 281.4542, 281.5139, 281.5737, 281.6335, 281.6932,  
281.753, 281.8127, 281.8725, 281.9323, 281.992, 282.0518, 282.1115,  
282.1713, 282.2311, 282.2908, 282.3506, 282.4104, 282.4701,  
282.5299, 282.5896, 282.6494, 282.7092, 282.7689, 282.8287, 282.8885,  
282.9482, 283.008, 283.0677, 283.1275, 283.1873, 283.247, 283.3068,  
283.3665, 283.4263, 283.4861, 283.5458, 283.6056, 283.6653, 283.7251,  
283.7849, 283.8446, 283.9044, 283.9641, 284.0239, 284.0837, 284.1434,  
284.2032, 284.2629, 284.3227, 284.3825, 284.4422, 284.502, 284.5618,  
284.6215, 284.6813, 284.741, 284.8008, 284.8606, 284.9203, 284.9801,  
285.0399, 285.0996, 285.1594, 285.2191, 285.2789, 285.3387, 285.3984,  
285.4582, 285.5179, 285.5777, 285.6375, 285.6972, 285.757, 285.8167,  
285.8765, 285.9362, 285.996, 286.0558, 286.1155, 286.1753, 286.235,
```

```
286.2948, 286.3546, 286.4143, 286.4741, 286.5339, 286.5936, 286.6534,  
286.7131, 286.7729, 286.8327, 286.8924, 286.9522, 287.012, 287.0717,  
287.1315, 287.1912, 287.251, 287.3108, 287.3705, 287.4303, 287.4901,  
287.5498, 287.6096, 287.6693, 287.7291, 287.7888, 287.8486, 287.9084,  
287.9681, 288.0279, 288.0876, 288.1474, 288.2072, 288.2669, 288.3267,  
288.3864, 288.4462, 288.506, 288.5657, 288.6255, 288.6853, 288.745,  
288.8048, 288.8645, 288.9243, 288.9841, 289.0438, 289.1036, 289.1634,  
289.2231, 289.2829, 289.3426, 289.4024, 289.4622, 289.5219, 289.5817,  
289.6414, 289.7012, 289.761, 289.8207, 289.8805, 289.9402, 290 ;  
}
```

## C Examples

These examples are based on the CMOR repository's [examples/c](https://github.com/PCMDI/cmor/tree/main/examples/c) (<https://github.com/PCMDI/cmor/tree/main/examples/c>) directory. They use the same shared CMIP7 user input file as the Python and Fortran examples and load CMIP7 tables from a local clone of [WCRP-CMIP/cmip7-cmor-tables](https://github.com/WCRP-CMIP/cmip7-cmor-tables) (<https://github.com/WCRP-CMIP/cmip7-cmor-tables>).

Create and activate a Conda or Mamba environment with CMOR and a C compiler:

```
mamba create -n cmor-c -c conda-forge cmor c-compiler libnetcdf udunits2 json-c libuuid  
mamba activate cmor-c
```

If you use Conda instead of Mamba, use the same package list:

```
conda create -n cmor-c -c conda-forge cmor c-compiler libnetcdf udunits2 json-c libuuid  
conda activate cmor-c
```

Install the CMIP7 tables in the working directory where you will run the examples:

```
git clone https://github.com/WCRP-CMIP/cmip7-cmor-tables.git
```

Run the examples from a working directory that contains the `cmip7-cmor-tables` repository using the [run\\_examples.sh](#) (page 0) script:

```
chmod a+x run_examples.sh  
./run_examples.sh
```

The examples expect tables under `./cmip7-cmor-tables/tables` in the directory where you run the script. To use a different table location, set `CMOR_TABLES_PATH` to the directory containing the CMIP7 table JSON files. To use a different user input file, set `CMOR_INPUT_PATH`.

Each example builds the CMIP7 compound variable name and uses it to read `CMIP7_cell_measures.json` and `CMIP7_long_name_overrides.json` before writing data. The fixed-field example overrides `frequency` from the shared user input file to `fx`.

### CMOR Input Files

- [CMIP7\\_input\\_example.json](#) (page 0)

- [CMIP7\\_coordinate.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_coordinate.json)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_coordinate.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_coordinate.json))
- [CMIP7\\_formula\\_terms.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_formula_terms.json)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_formula\\_terms.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_formula_terms.json))
- [CMIP7\\_cell\\_measures.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_cell_measures.json)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_cell\\_measures.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_cell_measures.json))
- [CMIP7\\_long\\_name\\_overrides.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_long_name_overrides.json)  
([https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7\\_long\\_name\\_overrides.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables/CMIP7_long_name_overrides.json))
- [cmor-cvs.json](https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables-cvs/cmor-cvs.json)  
(<https://github.com/WCRP-CMIP/cmip7-cmor-tables/blob/main/tables-cvs/cmor-cvs.json>)

**Click to expand shared JSON input**

```
{
  "_AXIS_ENTRY_FILE": "CMIP7_coordinate.json",
  "_FORMULA_VAR_FILE": "CMIP7_formula_terms.json",
  "_cmip7_option": 1,
  "_controlled_vocabulary_file": "../tables-cvs/cmor-cvs.json",
  "activity_id": "CMIP",
  "archive_id": "WCRP",
  "calendar": "360_day",
  "experiment_id": "amip",
  "forcing_index": "f1",
  "frequency": "mon",
  "grid_label": "g999",
  "host_collection": "CMIP7",
  "initialization_index": "i1",
  "institution_id": "MOHC",
  "license_id": "CC-BY-4.0",
  "nominal_resolution": "100 km",
  "outputpath": "output",
  "physics_index": "p1",
  "realization_index": "r1",
  "region": "glb",
  "source_id": "ACCESS-ESM1-6"
}
```

### Common C Utilities

- [cmip7\\_c\\_common.h \(page 0\)](#)
- [cmip7\\_c\\_common.c \(page 0\)](#)
- [run\\_examples.sh \(page 0\)](#)

**Click to expand common C header**

```
#ifndef CMIP7_C_COMMON_H
#define CMIP7_C_COMMON_H

#include "cmor.h"
#include <stddef.h>

#define CMIP7_NLON 4
#define CMIP7_NLAT 3
#define CMIP7_NTIMES 2
#define CMIP7_MISSING_VALUE 1.0e20f
#define CMIP7_PATH_MAX 4096

void cmip7_get_example_args(int argc, char **argv, const char **tables_path,
                           const char **input_path, const char **output_dir);
void cmip7_load_shared_user_input(const char *input_path,
                                  const char *output_dir,
                                  const char *frequency,
                                  const char *realization_index,
                                  const char *forcing_index);
void cmip7_get_cell_measures(const char *tables_path, const char *realm,
                             const char *table_entry, const char *frequency,
                             const char *region, char *value,
                             size_t value_size);
int cmip7_get_long_name_override(const char *tables_path, const char *realm,
                                 const char *table_entry, const char *frequency,
                                 const char *region, char *value,
                                 size_t value_size);

#endif
```

**Click to expand common C code**

```

#include "cmip7_c_common.h"

#include <json-c/json.h>
#include <string.h>

static void copy_string(char *out, size_t out_size, const char *value) {
    if (out_size > 0) {
        snprintf(out, out_size, "%s", value);
    }
}

static void join_path(char *out, size_t out_size, const char *left,
                    const char *right) {
    size_t left_len = strlen(left);

    if (left_len > 0 && left[left_len - 1] == '/') {
        snprintf(out, out_size, "%s%s", left, right);
    } else {
        snprintf(out, out_size, "%s/%s", left, right);
    }
}

static void compound_name(char *out, size_t out_size, const char *realm,
                        const char *table_entry, const char *frequency,
                        const char *region) {
    char normalized[CMOR_MAX_STRING];
    size_t i;

    copy_string(normalized, sizeof(normalized), table_entry);
    for (i = 0; normalized[i] != '\0'; ++i) {
        if (normalized[i] == '-') {
            normalized[i] = '.';
        }
    }
    snprintf(out, out_size, "%s.%s.%s.%s", realm, normalized, frequency, region);
}

static void check_status(const char *call_name, int status) {
    if (status != 0) {
        fprintf(stderr, "%s failed with status %d\n", call_name, status);
        exit(1);
    }
}

void cmip7_get_example_args(int argc, char **argv, const char **tables_path,
                          const char **input_path, const char **output_dir) {
    *tables_path = argc > 1 && argv[1][0] != '\0' ? argv[1]
                                                : "./cmip7-cmor-tables/tables";
    *input_path = argc > 2 && argv[2][0] != '\0' ? argv[2]
                                                : "./CMIP7_input_example.json";
}

```

```

    *output_dir = argc > 3 && argv[3][0] != '\0' ? argv[3] : "output";
}

void cmip7_load_shared_user_input(const char *input_path,
                                  const char *output_dir,
                                  const char *frequency,
                                  const char *realization_index,
                                  const char *forcing_index) {
    check_status("cmor_dataset_json", cmor_dataset_json((char *)input_path));
    check_status("cmor_set_cur_dataset_attribute(outpath)",
                 cmor_set_cur_dataset_attribute("outpath", (char *)output_dir,
                                                 1));
    if (frequency != NULL) {
        check_status("cmor_set_cur_dataset_attribute(frequency)",
                     cmor_set_cur_dataset_attribute("frequency", (char *)frequency,
                                                     1));
    }
    if (realization_index != NULL) {
        check_status("cmor_set_cur_dataset_attribute(realization_index)",
                     cmor_set_cur_dataset_attribute(
                         "realization_index", (char *)realization_index, 1));
    }
    if (forcing_index != NULL) {
        check_status("cmor_set_cur_dataset_attribute(forcing_index)",
                     cmor_set_cur_dataset_attribute(
                         "forcing_index", (char *)forcing_index, 1));
    }
}

static int lookup_json_string(const char *path, const char *root_name,
                              const char *key, char *value, size_t value_size) {
    json_object *document = json_object_from_file(path);
    json_object *root = NULL;
    json_object *entry = NULL;

    value[0] = '\0';
    if (document == NULL) {
        fprintf(stderr, "Could not open CMIP7 metadata table %s\n", path);
        exit(1);
    }

    if (json_object_object_get_ex(document, root_name, &root) &&
        json_object_object_get_ex(root, key, &entry)) {
        copy_string(value, value_size, json_object_get_string(entry));
        json_object_put(document);
        return 1;
    }

    json_object_put(document);
    return 0;
}

```

```
}

void cmip7_get_cell_measures(const char *tables_path, const char *realm,
                             const char *table_entry, const char *frequency,
                             const char *region, char *value,
                             size_t value_size) {
    char key[CMOR_MAX_STRING];
    char path[CMIP7_PATH_MAX];

    compound_name(key, sizeof(key), realm, table_entry, frequency, region);
    join_path(path, sizeof(path), tables_path, "CMIP7_cell_measures.json");
    lookup_json_string(path, "cell_measures", key, value, value_size);
}

int cmip7_get_long_name_override(const char *tables_path, const char *realm,
                                 const char *table_entry, const char *frequency,
                                 const char *region, char *value,
                                 size_t value_size) {
    char key[CMOR_MAX_STRING];
    char path[CMIP7_PATH_MAX];

    compound_name(key, sizeof(key), realm, table_entry, frequency, region);
    join_path(path, sizeof(path), tables_path, "CMIP7_long_name_overrides.json");
    return lookup_json_string(path, "long_name_overrides", key, value,
                              value_size);
}
```

**Click to expand runner script**

```

#!/usr/bin/env bash
set -euo pipefail

SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
RUN_DIR="${RUN_DIR:-$PWD}"
TABLES_PATH="${CMOR_TABLES_PATH:-$RUN_DIR/cmip7-cmor-tables/tables}"
INPUT_PATH="${CMOR_INPUT_PATH:-$RUN_DIR/CMIP7_input_example.json}"
OUTPUT_ROOT="$SCRIPT_DIR/output"
BUILD_DIR="${BUILD_DIR:-$SCRIPT_DIR/build}"

cd "$SCRIPT_DIR"

if [[ -z "${CONDA_PREFIX:-}" ]]; then
    echo "Activate your conda environment or run: conda run -n <env-name> $0" >&2
    exit 2
fi

detect_c_compiler() {
    if [[ -n "${CC:-}" ]]; then
        command -v "$CC" >/dev/null 2>&1 || {
            echo "CC is set to '$CC', but that compiler was not found" >&2
            exit 2
        }
        echo "$CC"
        return
    fi

    local compiler
    for compiler in "$CONDA_PREFIX"/bin/*-cc "$CONDA_PREFIX"/bin/*-gcc "$CONDA_PRE
FIX"/bin/clang "$CONDA_PREFIX"/bin/gcc "$CONDA_PREFIX"/bin/cc; do
        if [[ -x "$compiler" ]]; then
            echo "$compiler"
            return
        fi
    done

    if command -v cc >/dev/null 2>&1; then
        command -v cc
        return
    fi

    echo "Could not find a C compiler. Install c-compiler in the active conda envir
onment or set CC." >&2
    exit 2
}

mkdir -p "$BUILD_DIR" "$OUTPUT_ROOT"

if [[ ! -d "$TABLES_PATH" ]]; then
    echo "Could not find CMIP7 tables under $TABLES_PATH. Clone cmip7-cmor-tables o

```

```

r set CMOR_TABLES_PATH." >&2
  exit 2
fi

if [[ ! -f "$INPUT_PATH" ]]; then
  echo "Could not find CMIP7 user input JSON at $INPUT_PATH. Set CMOR_INPUT_PATH
to override it." >&2
  exit 2
fi

CC="$(detect_c_compiler)"
CMOR_PREFIX="${CMOR_PREFIX:-$CONDA_PREFIX}"
CMOR_INCLUDE_DIR="${CMOR_INCLUDE_DIR:-$CMOR_PREFIX/include}"
CMOR_CDTIME_INCLUDE_DIR="${CMOR_CDTIME_INCLUDE_DIR:-$CMOR_INCLUDE_DIR/cdTime}"

if [[ -n "${CMOR_LIB:-}" ]]; then
  CMOR_LINK_FLAGS=("$CMOR_LIB")
elif [[ -f "$CMOR_PREFIX/lib/libcmor.a" ]]; then
  CMOR_LINK_FLAGS=("$CMOR_PREFIX/lib/libcmor.a")
elif [[ -f "$CMOR_PREFIX/lib/libcmor.dylib" || -f "$CMOR_PREFIX/lib/libcmor.so"
]]; then
  CMOR_LINK_FLAGS=(-L$CMOR_PREFIX/lib "-lcmor")
else
  echo "Could not find CMOR in $CMOR_PREFIX. Install cmor in the active conda env
ironment or set CMOR_PREFIX/CMOR_LIB." >&2
  exit 2
fi

if [[ ! -f "$CMOR_INCLUDE_DIR/cmor.h" ]]; then
  echo "Could not find cmor.h in $CMOR_INCLUDE_DIR. Install cmor in the active co
nda environment or set CMOR_INCLUDE_DIR." >&2
  exit 2
fi
if [[ ! -f "$CMOR_INCLUDE_DIR/cdmsint.h" && ! -f "$CMOR_CDTIME_INCLUDE_DIR/cdmsi
nt.h" ]]; then
  echo "Could not find cdmsint.h in $CMOR_INCLUDE_DIR or $CMOR_CDTIME_INCLUDE_DI
R. Install cmor in the active conda environment or set CMOR_CDTIME_INCLUDE_DI
R." >&2
  exit 2
fi

CFLAGS_DEFAULT="-g -O2 -Wall -Wextra"
CFLAGS="${CFLAGS:-$CFLAGS_DEFAULT}"
EXTRA_LDFLAGS="${EXTRA_LDFLAGS:-}"
LINK_DIRS=("$CMOR_PREFIX/lib")
if [[ "$CONDA_PREFIX/lib" != "$CMOR_PREFIX/lib" ]]; then
  LINK_DIRS+=("$CONDA_PREFIX/lib")
fi

LINK_FLAGS=("${CMOR_LINK_FLAGS[@]}")

```

```

for link_dir in "${LINK_DIRS[@]}"; do
    LINK_FLAGS+=("-L$link_dir")
done
LINK_FLAGS+=("-lnetcdf" "-ludunits2" "-ljson-c" "-luuid" "-lm")
for link_dir in "${LINK_DIRS[@]}"; do
    LINK_FLAGS+=("-Wl,-rpath,$link_dir")
done

INCLUDES=(-I$SCRIPT_DIR "-I$CMOR_INCLUDE_DIR" "-I$CMOR_CDTIME_INCLUDE_DIR" "-I$CONDA_PREFIX/include")
COMMON_SRC="$SCRIPT_DIR/cmip7_c_common.c"

examples=(
    example_01_regular_grid_tos
    example_02_pressure_levels
    example_03_scalar_height_tas
    example_04_basin_axis
    example_05_hybrid_sigma_levels
    example_06_curvilinear_grid
    example_07_fixed_field_rootd
    example_08_site_dimension
)

for example in "${examples[@]}"; do
    src="$SCRIPT_DIR/$example.c"
    exe="$BUILD_DIR/$example"

    echo "Compiling $example"
    "$CC" $CFLAGS "${INCLUDES[@]}" "$COMMON_SRC" "$src" "${LINK_FLAGS[@]}" $EXTRA_LDFLAGS -o "$exe"

    echo "Running $example"
    "$exe" "$TABLES_PATH" "$INPUT_PATH" "$OUTPUT_ROOT"
done

echo "Wrote CMIP7 example output under $OUTPUT_ROOT"

```

### Example 1: Regular Grid Ocean Field

- [example\\_01\\_regular\\_grid\\_tos.c \(page 0\)](#)

**Click to expand C code**

```

#include "cmip7_c_common.h"

#include <stdio.h>

int main(int argc, char **argv) {
    const char *tables_path;
    const char *input_path;
    const char *output_dir;
    char cell_measures[CMOR_MAX_STRING];
    char long_name[CMOR_MAX_STRING];
    char filename[CMOR_MAX_STRING];
    int file_action = CMOR_REPLACE;
    int exit_control = CMOR_EXIT_ON_MAJOR;
    int table_id, lon_id, lat_id, time_id, var_id;
    int axes[3];
    double lat[CMIP7_NLAT] = {10.0, 20.0, 30.0};
    double lat_bnds[CMIP7_NLAT + 1] = {5.0, 15.0, 25.0, 35.0};
    double lon[CMIP7_NLON] = {0.0, 90.0, 180.0, 270.0};
    double lon_bnds[CMIP7_NLON + 1] = {-45.0, 45.0, 135.0, 225.0, 315.0};
    double time[CMIP7_NTIMES] = {15.5, 45.5};
    double time_bnds[CMIP7_NTIMES + 1] = {0.0, 31.0, 60.0};
    float tos[CMIP7_NTIMES * CMIP7_NLAT * CMIP7_NLON] = {
        254.0895f, 258.4085f, CMIP7_MISSING_VALUE, 258.7101f,
        258.6680f, 258.2990f, CMIP7_MISSING_VALUE, 255.0432f,
        253.7254f, 251.2460f, CMIP7_MISSING_VALUE, 255.4808f,
        254.0995f, 258.5085f, CMIP7_MISSING_VALUE, 258.8101f,
        258.8680f, 258.4990f, CMIP7_MISSING_VALUE, 255.2432f,
        254.0254f, 251.5460f, CMIP7_MISSING_VALUE, 255.7808f};
    float missing = CMIP7_MISSING_VALUE;

    cmip7_get_example_args(argc, argv, &tables_path, &input_path, &output_dir);

    cmor_setup((char *)tables_path, &file_action, NULL, &exit_control, NULL,
        NULL);
    cmip7_load_shared_user_input(input_path, output_dir, NULL, NULL, NULL);
    cmor_load_table("CMIP7_ocean.json", &table_id);

    cmor_axis(&lon_id, "longitude", "degrees_east", CMIP7_NLON, lon, 'd',
        lon_bnds, 1, NULL);
    cmor_axis(&lat_id, "latitude", "degrees_north", CMIP7_NLAT, lat, 'd',
        lat_bnds, 1, NULL);
    cmor_axis(&time_id, "time", "days since 1979-01-01", CMIP7_NTIMES, time, 'd',
        time_bnds, 1, NULL);

    axes[0] = time_id;
    axes[1] = lat_id;
    axes[2] = lon_id;
    cmor_variable(&var_id, "tos_tavg-u-hxy-sea", "degC", 3, axes, 'f', &missing,
        NULL, NULL, NULL, NULL, NULL);

```

```
cmip7_get_cell_measures(tables_path, "ocean", "tos_tavg-u-hxy-sea", "mon",
                        "glb", cell_measures, sizeof(cell_measures));
cmor_set_variable_attribute(var_id, "cell_measures", 'c', cell_measures);
if (cmip7_get_long_name_override(tables_path, "ocean", "tos_tavg-u-hxy-sea",
                                "mon", "glb", long_name,
                                sizeof(long_name))) {
    cmor_set_variable_attribute(var_id, "long_name", 'c', long_name);
}

cmor_write(var_id, tos, 'f', NULL, CMIP7_NTIMES, NULL, NULL, NULL);
filename[0] = '\0';
cmor_close_variable(var_id, filename, NULL);
printf("%s\n", filename);
cmor_close();
return 0;
}
```

**Click to expand NetCDF dump**

```

netcdf tos_tavg-u-hxy-sea_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902
{
dimensions:
    time = UNLIMITED ; // (2 currently)
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float tos(time, lat, lon) ;
        tos:standard_name = "sea_surface_temperature" ;
        tos:long_name = "Sea Surface Temperature" ;
        tos:units = "degC" ;
        tos:cell_methods = "area: mean where sea time: mean" ;
        tos:missing_value = 1.e+20f ;
        tos:_FillValue = 1.e+20f ;
        tos:cell_measures = "area: areacello" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "sea" ;
    :branded_variable = "tos_tavg-u-hxy-sea" ;
    :branding_suffix = "tavg-u-hxy-sea" ;
    :creation_date = "2026-09-14T18:14:07Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;

```

```

:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacello" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:14:07Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/c/output" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "ocean" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_ocean.json; Creation Date:(2026-07-21
13:16:24) MD5:734c6f53560fa60b7c1c21b38e5b9a3f" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/da9ae437-6aa0-4ae2-a4cc-9f753206845
1" ;
:variable_id = "tos" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

```

```
time = 15.5, 45.5 ;

time_bnds =
  0, 31,
  31, 60 ;

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

lon = 0, 90, 180, 270 ;

lon_bnds =
  -45, 45,
  45, 135,
  135, 225,
  225, 315 ;

tos =
  254.0895, 258.4085, _, 258.7101,
  258.668, 258.299, _, 255.0432,
  253.7254, 251.246, _, 255.4808,
  254.0995, 258.5085, _, 258.8101,
  258.868, 258.499, _, 255.2432,
  254.0254, 251.546, _, 255.7808 ;
}
```

### Example 2: 3-D Field on Pressure Levels

- [example\\_02\\_pressure\\_levels.c \(page 0\)](#)

**Click to expand C code**

```

#include "cmip7_c_common.h"

#include <stdio.h>

#define NPLEV 19

int main(int argc, char **argv) {
    const char *tables_path;
    const char *input_path;
    const char *output_dir;
    char cell_measures[CMOR_MAX_STRING];
    char long_name[CMOR_MAX_STRING];
    char filename[CMOR_MAX_STRING];
    int file_action = CMOR_REPLACE;
    int exit_control = CMOR_EXIT_ON_MAJOR;
    int table_id, lon_id, lat_id, time_id, plev_id, var_id;
    int axes[4];
    int i, j, k, t;
    double lat[CMIP7_NLAT] = {10.0, 20.0, 30.0};
    double lat_bnds[CMIP7_NLAT + 1] = {5.0, 15.0, 25.0, 35.0};
    double lon[CMIP7_NLON] = {0.0, 90.0, 180.0, 270.0};
    double lon_bnds[CMIP7_NLON + 1] = {-45.0, 45.0, 135.0, 225.0, 315.0};
    double time[CMIP7_NTIMES] = {15.5, 45.5};
    double time_bnds[CMIP7_NTIMES + 1] = {0.0, 31.0, 60.0};
    double plev[NPLEV] = {100000.0, 92500.0, 85000.0, 70000.0, 60000.0,
                          50000.0, 40000.0, 30000.0, 25000.0, 20000.0,
                          15000.0, 10000.0, 7000.0, 5000.0, 3000.0,
                          2000.0, 1000.0, 500.0, 100.0};
    float ta[CMIP7_NTIMES * NPLEV * CMIP7_NLAT * CMIP7_NLON];
    float missing = CMIP7_MISSING_VALUE;

    cmip7_get_example_args(argc, argv, &tables_path, &input_path, &output_dir);

    cmor_setup((char *)tables_path, &file_action, NULL, &exit_control, NULL,
              NULL);
    cmip7_load_shared_user_input(input_path, output_dir, NULL, NULL, NULL);
    cmor_load_table("CMIP7_atmos.json", &table_id);

    cmor_axis(&lon_id, "longitude", "degrees_east", CMIP7_NLON, lon, 'd',
              lon_bnds, 1, NULL);
    cmor_axis(&lat_id, "latitude", "degrees_north", CMIP7_NLAT, lat, 'd',
              lat_bnds, 1, NULL);
    cmor_axis(&time_id, "time", "days since 1979-01-01", CMIP7_NTIMES, time, 'd',
              time_bnds, 1, NULL);
    cmor_axis(&plev_id, "plev19", "Pa", NPLEV, plev, 'd', NULL, 0, NULL);

    for (t = 0; t < CMIP7_NTIMES; ++t) {
        for (k = 0; k < NPLEV; ++k) {
            for (j = 0; j < CMIP7_NLAT; ++j) {
                for (i = 0; i < CMIP7_NLON; ++i) {

```

```

        int idx = ((t * NPLEV + k) * CMIP7_NLAT + j) * CMIP7_NLON + i;
        ta[idx] = 250.0f +
                25.0f *
                (float)(i + 1 + 4 * (j + 1) + 12 * (k + 1) + 228 * t) /
                (float)(CMIP7_NLON * CMIP7_NLAT * NPLEV * CMIP7_NTICES);
    }
}
}
ta[0] = CMIP7_MISSING_VALUE;

axes[0] = time_id;
axes[1] = plev_id;
axes[2] = lat_id;
axes[3] = lon_id;
cmor_variable(&var_id, "ta_tavg-p19-hxy-air", "K", 4, axes, 'f', &missing,
              NULL, NULL, NULL, NULL, NULL);

cmip7_get_cell_measures(tables_path, "atmos", "ta_tavg-p19-hxy-air", "mon",
                        "glb", cell_measures, sizeof(cell_measures));
cmor_set_variable_attribute(var_id, "cell_measures", 'c', cell_measures);
if (cmip7_get_long_name_override(tables_path, "atmos", "ta_tavg-p19-hxy-air",
                                "mon", "glb", long_name,
                                sizeof(long_name))) {
    cmor_set_variable_attribute(var_id, "long_name", 'c', long_name);
}

cmor_write(var_id, ta, 'f', NULL, CMIP7_NTICES, NULL, NULL, NULL);
filename[0] = '\0';
cmor_close_variable(var_id, filename, NULL);
printf("%s\n", filename);
cmor_close();
return 0;
}

```

**Click to expand NetCDF dump**

```

netcdf ta_tavg-p19-hxy-air_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-19790
2 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    plev = 19 ;
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double plev(plev) ;
        plev:units = "Pa" ;
        plev:axis = "Z" ;
        plev:positive = "down" ;
        plev:long_name = "Pressure Levels (19)" ;
        plev:standard_name = "air_pressure" ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float ta(time, plev, lat, lon) ;
        ta:standard_name = "air_temperature" ;
        ta:long_name = "Air Temperature" ;
        ta:units = "K" ;
        ta:cell_methods = "area: time: mean where air" ;
        ta:missing_value = 1.e+20f ;
        ta:_FillValue = 1.e+20f ;
        ta:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;

```

```

:area_label = "air" ;
:branded_variable = "ta_tavg-p19-hxy-air" ;
:branding_suffix = "tavg-p19-hxy-air" ;
:creation_date = "2026-09-14T18:14:07Z" ;
:data_specs_version = "MIP-DS7.1.0.0" ;
:description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacella" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:14:07Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/c/output" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/6767a5b5-015b-41e8-896d-c627e21f245
1" ;
:variable_id = "ta" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "p19" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack

```

nowledgment. The data producers and data providers make no warranty, either express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose. All liabilities arising from the supply of the information (including any liability arising in negligence) are excluded to the fullest extent permitted by law." ;

```
:cmor_version = "3.15.3" ;
```

```
data:
```

```
time = 15.5, 45.5 ;
```

```
time_bnds =  
  0, 31,  
 31, 60 ;
```

```
plev = 100000, 92500, 85000, 70000, 60000, 50000, 40000, 30000, 25000,  
       20000, 15000, 10000, 7000, 5000, 3000, 2000, 1000, 500, 100 ;
```

```
lat = 10, 20, 30 ;
```

```
lat_bnds =  
  5, 15,  
 15, 25,  
 25, 35 ;
```

```
lon = 0, 90, 180, 270 ;
```

```
lon_bnds =  
 -45, 45,  
 45, 135,  
 135, 225,  
 225, 315 ;
```

```
ta =  
_, 250.9868, 251.0417, 251.0965,  
251.1513, 251.2061, 251.261, 251.3158,  
251.3706, 251.4254, 251.4803, 251.5351,  
251.5899, 251.6447, 251.6996, 251.7544,  
251.8092, 251.864, 251.9189, 251.9737,  
252.0285, 252.0833, 252.1382, 252.193,  
252.2478, 252.3026, 252.3575, 252.4123,  
252.4671, 252.5219, 252.5768, 252.6316,  
252.6864, 252.7412, 252.7961, 252.8509,  
252.9057, 252.9605, 253.0154, 253.0702,  
253.125, 253.1798, 253.2346, 253.2895,  
253.3443, 253.3991, 253.4539, 253.5088,  
253.5636, 253.6184, 253.6732, 253.7281,  
253.7829, 253.8377, 253.8925, 253.9474,  
254.0022, 254.057, 254.1118, 254.1667,  
254.2215, 254.2763, 254.3311, 254.386,  
254.4408, 254.4956, 254.5504, 254.6053,
```

254.6601, 254.7149, 254.7697, 254.8246,  
254.8794, 254.9342, 254.989, 255.0439,  
255.0987, 255.1535, 255.2083, 255.2632,  
255.318, 255.3728, 255.4276, 255.4825,  
255.5373, 255.5921, 255.6469, 255.7018,  
255.7566, 255.8114, 255.8662, 255.9211,  
255.9759, 256.0307, 256.0855, 256.1404,  
256.1952, 256.25, 256.3048, 256.3596,  
256.4145, 256.4693, 256.5241, 256.5789,  
256.6338, 256.6886, 256.7434, 256.7982,  
256.8531, 256.9079, 256.9627, 257.0175,  
257.0724, 257.1272, 257.182, 257.2368,  
257.2917, 257.3465, 257.4013, 257.4561,  
257.511, 257.5658, 257.6206, 257.6754,  
257.7303, 257.7851, 257.8399, 257.8947,  
257.9496, 258.0044, 258.0592, 258.114,  
258.1689, 258.2237, 258.2785, 258.3333,  
258.3882, 258.443, 258.4978, 258.5526,  
258.6075, 258.6623, 258.7171, 258.7719,  
258.8268, 258.8816, 258.9364, 258.9912,  
259.0461, 259.1009, 259.1557, 259.2105,  
259.2654, 259.3202, 259.375, 259.4298,  
259.4846, 259.5395, 259.5943, 259.6491,  
259.7039, 259.7588, 259.8136, 259.8684,  
259.9232, 259.9781, 260.0329, 260.0877,  
260.1425, 260.1974, 260.2522, 260.307,  
260.3618, 260.4167, 260.4715, 260.5263,  
260.5811, 260.636, 260.6908, 260.7456,  
260.8004, 260.8553, 260.9101, 260.9649,  
261.0197, 261.0746, 261.1294, 261.1842,  
261.239, 261.2939, 261.3487, 261.4035,  
261.4583, 261.5132, 261.568, 261.6228,  
261.6776, 261.7325, 261.7873, 261.8421,  
261.8969, 261.9518, 262.0066, 262.0614,  
262.1162, 262.1711, 262.2259, 262.2807,  
262.3355, 262.3904, 262.4452, 262.5,  
262.5548, 262.6096, 262.6645, 262.7193,  
262.7741, 262.8289, 262.8838, 262.9386,  
262.9934, 263.0482, 263.1031, 263.1579,  
263.2127, 263.2675, 263.3224, 263.3772,  
263.432, 263.4868, 263.5417, 263.5965,  
263.6513, 263.7061, 263.761, 263.8158,  
263.8706, 263.9254, 263.9803, 264.0351,  
264.0899, 264.1447, 264.1996, 264.2544,  
264.3092, 264.364, 264.4189, 264.4737,  
264.5285, 264.5833, 264.6382, 264.693,  
264.7478, 264.8026, 264.8575, 264.9123,  
264.9671, 265.0219, 265.0768, 265.1316,  
265.1864, 265.2412, 265.2961, 265.3509,  
265.4057, 265.4605, 265.5154, 265.5702,

```
265.625, 265.6798, 265.7346, 265.7895,  
265.8443, 265.8991, 265.9539, 266.0088,  
266.0636, 266.1184, 266.1732, 266.2281,  
266.2829, 266.3377, 266.3925, 266.4474,  
266.5022, 266.557, 266.6118, 266.6667,  
266.7215, 266.7763, 266.8311, 266.886,  
266.9408, 266.9956, 267.0504, 267.1053,  
267.1601, 267.2149, 267.2697, 267.3246,  
267.3794, 267.4342, 267.489, 267.5439,  
267.5987, 267.6535, 267.7083, 267.7632,  
267.818, 267.8728, 267.9276, 267.9825,  
268.0373, 268.0921, 268.1469, 268.2018,  
268.2566, 268.3114, 268.3662, 268.4211,  
268.4759, 268.5307, 268.5855, 268.6404,  
268.6952, 268.75, 268.8048, 268.8596,  
268.9145, 268.9693, 269.0241, 269.0789,  
269.1338, 269.1886, 269.2434, 269.2982,  
269.3531, 269.4079, 269.4627, 269.5175,  
269.5724, 269.6272, 269.682, 269.7368,  
269.7917, 269.8465, 269.9013, 269.9561,  
270.011, 270.0658, 270.1206, 270.1754,  
270.2303, 270.2851, 270.3399, 270.3947,  
270.4496, 270.5044, 270.5592, 270.614,  
270.6689, 270.7237, 270.7785, 270.8333,  
270.8882, 270.943, 270.9978, 271.0526,  
271.1075, 271.1623, 271.2171, 271.2719,  
271.3268, 271.3816, 271.4364, 271.4912,  
271.5461, 271.6009, 271.6557, 271.7105,  
271.7654, 271.8202, 271.875, 271.9298,  
271.9846, 272.0395, 272.0943, 272.1491,  
272.2039, 272.2588, 272.3136, 272.3684,  
272.4232, 272.4781, 272.5329, 272.5877,  
272.6425, 272.6974, 272.7522, 272.807,  
272.8618, 272.9167, 272.9715, 273.0263,  
273.0811, 273.136, 273.1908, 273.2456,  
273.3004, 273.3553, 273.4101, 273.4649,  
273.5197, 273.5746, 273.6294, 273.6842,  
273.739, 273.7939, 273.8487, 273.9035,  
273.9583, 274.0132, 274.068, 274.1228,  
274.1776, 274.2325, 274.2873, 274.3421,  
274.3969, 274.4518, 274.5066, 274.5614,  
274.6162, 274.6711, 274.7259, 274.7807,  
274.8355, 274.8904, 274.9452, 275,  
275.0548, 275.1096, 275.1645, 275.2193,  
275.2741, 275.3289, 275.3838, 275.4386,  
275.4934, 275.5482, 275.6031, 275.6579,  
275.7127, 275.7675, 275.8224, 275.8772 ;  
}
```

### Example 3: Scalar Height Coordinate

- [example\\_03\\_scalar\\_height\\_tas.c](#) (page 0)

**Click to expand C code**

```

#include "cmip7_c_common.h"

#include <stdio.h>

int main(int argc, char **argv) {
    const char *tables_path;
    const char *input_path;
    const char *output_dir;
    char cell_measures[CMOR_MAX_STRING];
    char long_name[CMOR_MAX_STRING];
    char filename[CMOR_MAX_STRING];
    int file_action = CMOR_REPLACE;
    int exit_control = CMOR_EXIT_ON_MAJOR;
    int table_id, lon_id, lat_id, time_id, height_id, var_id;
    int axes[3];
    double lat[CMIP7_NLAT] = {10.0, 20.0, 30.0};
    double lat_bnds[CMIP7_NLAT + 1] = {5.0, 15.0, 25.0, 35.0};
    double lon[CMIP7_NLON] = {0.0, 90.0, 180.0, 270.0};
    double lon_bnds[CMIP7_NLON + 1] = {-45.0, 45.0, 135.0, 225.0, 315.0};
    double time[CMIP7_NTIMES] = {15.5, 45.5};
    double time_bnds[CMIP7_NTIMES + 1] = {0.0, 31.0, 60.0};
    double height = 2.0;
    float tas[CMIP7_NTIMES * CMIP7_NLAT * CMIP7_NLON] = {
        254.0895f, 258.4085f, 250.5549f, 258.7101f, 258.6680f, 258.2990f,
        252.1237f, 255.0432f, 253.7254f, 251.2460f, 254.3168f, 255.4808f,
        259.7908f, 252.2754f, 257.1892f, 253.3132f, 253.8823f, 253.4698f,
        253.5381f, 254.9730f, 256.1002f, 251.8168f, 259.3698f, 250.2994f};
    float missing = CMIP7_MISSING_VALUE;

    cmip7_get_example_args(argc, argv, &tables_path, &input_path, &output_dir);

    cmor_setup((char *)tables_path, &file_action, NULL, &exit_control, NULL,
        NULL);
    cmip7_load_shared_user_input(input_path, output_dir, NULL, "r9", "f2");
    cmor_load_table("CMIP7_atmos.json", &table_id);

    cmor_axis(&lon_id, "longitude", "degrees_east", CMIP7_NLON, lon, 'd',
        lon_bnds, 1, NULL);
    cmor_axis(&lat_id, "latitude", "degrees_north", CMIP7_NLAT, lat, 'd',
        lat_bnds, 1, NULL);
    cmor_axis(&time_id, "time", "days since 1979-01-01", CMIP7_NTIMES, time, 'd',
        time_bnds, 1, NULL);
    cmor_axis(&height_id, "height2m", "m", 1, &height, 'd', NULL, 0, NULL);

    axes[0] = time_id;
    axes[1] = lat_id;
    axes[2] = lon_id;
    cmor_variable(&var_id, "tas_tavg-h2m-hxy-u", "K", 3, axes, 'f', &missing,
        NULL, NULL, NULL, NULL, NULL);

```

```
cmip7_get_cell_measures(tables_path, "atmos", "tas_tavg-h2m-hxy-u", "mon",
                        "glb", cell_measures, sizeof(cell_measures));
cmor_set_variable_attribute(var_id, "cell_measures", 'c', cell_measures);
if (cmip7_get_long_name_override(tables_path, "atmos", "tas_tavg-h2m-hxy-u",
                                "mon", "glb", long_name,
                                sizeof(long_name))) {
    cmor_set_variable_attribute(var_id, "long_name", 'c', long_name);
}

cmor_write(var_id, tas, 'f', NULL, CMIP7_NTICES, NULL, NULL, NULL);
filename[0] = '\0';
cmor_close_variable(var_id, filename, NULL);
printf("%s\n", filename);
cmor_close();
return 0;
}
```

**Click to expand NetCDF dump**

```

netcdf tas_tavg-h2m-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r9i1p1f2_197901-197902
{
dimensions:
    time = UNLIMITED ; // (2 currently)
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    double height ;
        height:units = "m" ;
        height:axis = "Z" ;
        height:positive = "up" ;
        height:long_name = "height" ;
        height:standard_name = "height" ;
    float tas(time, lat, lon) ;
        tas:standard_name = "air_temperature" ;
        tas:long_name = "Near-Surface Air Temperature" ;
        tas:units = "K" ;
        tas:cell_methods = "area: time: mean" ;
        tas:history = "2026-09-14T18:14:08Z altered by CMOR: Treated scalar dimension: \'height\'. " ;
        tas:coordinates = "height" ;
        tas:missing_value = 1.e+20f ;
        tas:_FillValue = 1.e+20f ;
        tas:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;

```

```

:activity_id = "CMIP" ;
:archive_id = "WCRP" ;
:area_label = "u" ;
:branded_variable = "tas_tavg-h2m-hxy-u" ;
:branding_suffix = "tavg-h2m-hxy-u" ;
:creation_date = "2026-09-14T18:14:08Z" ;
:data_specs_version = "MIP-DS7.1.0.0" ;
:description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:external_variables = "areacella" ;
:forcing_index = "f2" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:14:08Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/c/output" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r9" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/18f5b4a5-cc35-4f21-9eb2-206145694da
f" ;

:variable_id = "tas" ;
:variant_label = "r9i1p1f2" ;
:vertical_label = "h2m" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativec
ommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/

```

```
docs/CMIP7/Guidance_for_users/#2-terms-of-use-and-citations-requirements for terms of use governing CMIP7 output, including citation requirements and proper acknowledgment. The data producers and data providers make no warranty, either express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose. All liabilities arising from the supply of the information (including any liability arising in negligence) are excluded to the fullest extent permitted by law." ;
```

```
    :cmor_version = "3.15.3" ;
```

```
data:
```

```
    time = 15.5, 45.5 ;
```

```
    time_bnds =
```

```
        0, 31,
```

```
        31, 60 ;
```

```
    lat = 10, 20, 30 ;
```

```
    lat_bnds =
```

```
        5, 15,
```

```
        15, 25,
```

```
        25, 35 ;
```

```
    lon = 0, 90, 180, 270 ;
```

```
    lon_bnds =
```

```
        -45, 45,
```

```
        45, 135,
```

```
        135, 225,
```

```
        225, 315 ;
```

```
    height = 2 ;
```

```
    tas =
```

```
        254.0895, 258.4085, 250.5549, 258.7101,
```

```
        258.668, 258.299, 252.1237, 255.0432,
```

```
        253.7254, 251.246, 254.3168, 255.4808,
```

```
        259.7908, 252.2754, 257.1892, 253.3132,
```

```
        253.8823, 253.4698, 253.5381, 254.973,
```

```
        256.1002, 251.8168, 259.3698, 250.2994 ;
```

```
}
```

#### Example 4: Basin Axis

- [example\\_04\\_basin\\_axis.c \(page 0\)](#)

**Click to expand C code**

```

#include "cmip7_c_common.h"

#include <stdio.h>

#define NBASIN 3

int main(int argc, char **argv) {
    const char *tables_path;
    const char *input_path;
    const char *output_dir;
    char cell_measures[CMOR_MAX_STRING];
    char long_name[CMOR_MAX_STRING];
    char filename[CMOR_MAX_STRING];
    char basin_names[NBASIN][CMOR_MAX_STRING] = {
        "atlantic_arctic_ocean", "indian_pacific_ocean", "global_ocean"};
    int file_action = CMOR_REPLACE;
    int exit_control = CMOR_EXIT_ON_MAJOR;
    int table_id, lat_id, time_id, basin_id, var_id;
    int axes[3];
    double lat[CMIP7_NLAT] = {10.0, 20.0, 30.0};
    double lat_bnds[CMIP7_NLAT + 1] = {5.0, 15.0, 25.0, 35.0};
    double time[CMIP7_NTIMES] = {15.5, 45.5};
    double time_bnds[CMIP7_NTIMES + 1] = {0.0, 31.0, 60.0};
    float heat_transport[CMIP7_NTIMES * NBASIN * CMIP7_NLAT] = {
        -80.0f, -84.0f, -88.0f, -100.0f, -104.0f, -76.0f,
        -120.0f, -92.0f, -96.0f, -79.0f, -83.0f, -87.0f,
        -99.0f, -103.0f, -75.0f, -107.0f, -111.0f, -115.0f};
    float missing = CMIP7_MISSING_VALUE;

    cmip7_get_example_args(argc, argv, &tables_path, &input_path, &output_dir);

    cmor_setup((char *)tables_path, &file_action, NULL, &exit_control, NULL,
        NULL);
    cmip7_load_shared_user_input(input_path, output_dir, NULL, NULL, NULL);
    cmor_load_table("CMIP7_ocean.json", &table_id);

    cmor_axis(&lat_id, "latitude", "degrees_north", CMIP7_NLAT, lat, 'd',
        lat_bnds, 1, NULL);
    cmor_axis(&time_id, "time", "days since 1979-01-01", CMIP7_NTIMES, time, 'd',
        time_bnds, 1, NULL);
    cmor_axis(&basin_id, "basin", "", NBASIN, basin_names, 'c', NULL,
        CMOR_MAX_STRING, NULL);

    axes[0] = time_id;
    axes[1] = basin_id;
    axes[2] = lat_id;
    cmor_variable(&var_id, "htovgyre_tavg-u-hyb-sea", "W", 3, axes, 'f', &missing,
        NULL, NULL, NULL, NULL, NULL);

    cmip7_get_cell_measures(tables_path, "ocean", "htovgyre_tavg-u-hyb-sea",

```

```
        "mon", "glb", cell_measures, sizeof(cell_measures));
cmor_set_variable_attribute(var_id, "cell_measures", 'c', cell_measures);
if (cmip7_get_long_name_override(tables_path, "ocean",
                                "htovgyre_tavg-u-hyb-sea", "mon", "glb",
                                long_name, sizeof(long_name))) {
    cmor_set_variable_attribute(var_id, "long_name", 'c', long_name);
}

cmor_write(var_id, heat_transport, 'f', NULL, CMIP7_NTICES, NULL, NULL, NULL);
filename[0] = '\0';
cmor_close_variable(var_id, filename, NULL);
printf("%s\n", filename);
cmor_close();
return 0;
}
```

**Click to expand NetCDF dump**

```

netcdf htovgyre_tavg-u-hyb-sea_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-1
97902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    basin = 3 ;
    lat = 3 ;
    bnds = 2 ;
    strlen = 21 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    char sector(basin, strlen) ;
        sector:long_name = "Ocean Basin" ;
        sector:standard_name = "region" ;
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    float htovgyre(time, basin, lat) ;
        htovgyre:standard_name = "northward_ocean_heat_transport_due_t
o_gyre" ;
        htovgyre:long_name = "Northward Ocean Heat Transport Due to Gyr
e" ;
        htovgyre:units = "W" ;
        htovgyre:cell_methods = "depth: longitude: sum where sea (along
a zig-zag grid path spanning a basin) time: mean" ;
        htovgyre:missing_value = 1.e+20f ;
        htovgyre:_FillValue = 1.e+20f ;
        htovgyre:coordinates = "sector" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "sea" ;
    :branded_variable = "htovgyre_tavg-u-hyb-sea" ;
    :branding_suffix = "tavg-u-hyb-sea" ;
    :creation_date = "2026-09-14T18:14:09Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past wit
h prescribed sea surface temperatures and sea ice concentrations." ;

```

```

:drs_specs = "MIP-DRS7" ;
:experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
:experiment_id = "amip" ;
:forcing_index = "f1" ;
:frequency = "mon" ;
:grid_label = "g999" ;
:history = "2026-09-14T18:14:09Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
:horizontal_label = "hyb" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/c/output" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "ocean" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_ocean.json; Creation Date:(2026-07-21
13:16:24) MD5:734c6f53560fa60b7c1c21b38e5b9a3f" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/cc74e46c-1f38-4a05-983c-55962f3777b
6" ;

:variable_id = "htovgyre" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

```

```
time = 15.5, 45.5 ;

time_bnds =
  0, 31,
  31, 60 ;

sector =
  "atlantic_arctic_ocean",
  "indian_pacific_ocean",
  "global_ocean" ;

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

htovgyre =
  -80, -84, -88,
  -100, -104, -76,
  -120, -92, -96,
  -79, -83, -87,
  -99, -103, -75,
  -107, -111, -115 ;
}
```

### Example 5: Hybrid Sigma Model Levels

- [example\\_05\\_hybrid\\_sigma\\_levels.c](#) (page 0)

**Click to expand C code**

```

#include "cmip7_c_common.h"

#include <stdio.h>

#define NLEV 5

int main(int argc, char **argv) {
    const char *tables_path;
    const char *input_path;
    const char *output_dir;
    char cell_measures[CMOR_MAX_STRING];
    char long_name[CMOR_MAX_STRING];
    char filename[CMOR_MAX_STRING];
    int file_action = CMOR_REPLACE;
    int exit_control = CMOR_EXIT_ON_MAJOR;
    int table_id, lon_id, lat_id, time_id, lev_id, ps_id, zfactor_id, var_id;
    int axes[4];
    int lev_axis[1];
    int ps_axes[3];
    int i, j, k, t;
    double lat[CMIP7_NLAT] = {10.0, 20.0, 30.0};
    double lat_bnds[CMIP7_NLAT + 1] = {5.0, 15.0, 25.0, 35.0};
    double lon[CMIP7_NLON] = {0.0, 90.0, 180.0, 270.0};
    double lon_bnds[CMIP7_NLON + 1] = {-45.0, 45.0, 135.0, 225.0, 315.0};
    double time[CMIP7_NTIMES] = {15.5, 45.5};
    double time_bnds[CMIP7_NTIMES + 1] = {0.0, 31.0, 60.0};
    double lev[NLEV] = {0.92, 0.72, 0.50, 0.30, 0.10};
    double lev_bnds[NLEV + 1] = {1.00, 0.83, 0.61, 0.40, 0.20, 0.00};
    double a_coeff[NLEV] = {0.12, 0.22, 0.30, 0.20, 0.10};
    double b_coeff[NLEV] = {0.80, 0.50, 0.20, 0.10, 0.00};
    double a_bnds[NLEV + 1] = {0.06, 0.18, 0.26, 0.25, 0.15, 0.00};
    double b_bnds[NLEV + 1] = {0.94, 0.65, 0.35, 0.15, 0.05, 0.00};
    double p0[1] = {100000.0};
    float cl[CMIP7_NTIMES * NLEV * CMIP7_NLAT * CMIP7_NLON];
    float ps[CMIP7_NTIMES * CMIP7_NLAT * CMIP7_NLON];
    float missing = CMIP7_MISSING_VALUE;

    cmip7_get_example_args(argc, argv, &tables_path, &input_path, &output_dir);

    cmor_setup((char *)tables_path, &file_action, NULL, &exit_control, NULL,
               NULL);
    cmip7_load_shared_user_input(input_path, output_dir, NULL, NULL, NULL);
    cmor_load_table("CMIP7_atmos.json", &table_id);

    cmor_axis(&lon_id, "longitude", "degrees_east", CMIP7_NLON, lon, 'd',
              lon_bnds, 1, NULL);
    cmor_axis(&lat_id, "latitude", "degrees_north", CMIP7_NLAT, lat, 'd',
              lat_bnds, 1, NULL);
    cmor_axis(&time_id, "time", "days since 1979-01-01", CMIP7_NTIMES, time, 'd',
              time_bnds, 1, NULL);

```

```

cmor_axis(&lev_id, "standard_hybrid_sigma", "1", NLEV, lev, 'd', lev_bnds, 1,
        NULL);

lev_axis[0] = lev_id;
cmor_zfactor(&zfactor_id, lev_id, "a", "", 1, lev_axis, 'd', a_coeff, a_bnds);
cmor_zfactor(&zfactor_id, lev_id, "b", "", 1, lev_axis, 'd', b_coeff, b_bnds);
cmor_zfactor(&zfactor_id, lev_id, "p0", "Pa", 0, NULL, 'd', p0, NULL);

ps_axes[0] = time_id;
ps_axes[1] = lat_id;
ps_axes[2] = lon_id;
cmor_zfactor(&ps_id, lev_id, "ps", "Pa", 3, ps_axes, 'f', NULL, NULL);

for (t = 0; t < CMIP7_NTICES; ++t) {
    for (j = 0; j < CMIP7_NLAT; ++j) {
        for (i = 0; i < CMIP7_NLON; ++i) {
            int idx = (t * CMIP7_NLAT + j) * CMIP7_NLON + i;
            ps[idx] = 97000.0f + 400.0f * (float)i + 1600.0f * (float)j +
                    100.0f * (float)t;
        }
    }
}
for (t = 0; t < CMIP7_NTICES; ++t) {
    for (k = 0; k < NLEV; ++k) {
        for (j = 0; j < CMIP7_NLAT; ++j) {
            for (i = 0; i < CMIP7_NLON; ++i) {
                int idx = ((t * NLEV + k) * CMIP7_NLAT + j) * CMIP7_NLON + i;
                cl[idx] = 75.0f - 5.0f * (float)(k + 1) - 1.2f * (float)j +
                        0.4f * (float)i + 0.1f * (float)t;
            }
        }
    }
}

axes[0] = time_id;
axes[1] = lev_id;
axes[2] = lat_id;
axes[3] = lon_id;
cmor_variable(&var_id, "cl_tavg-al-hxy-u", "%", 4, axes, 'f', &missing, NULL,
        NULL, NULL, NULL, NULL);

cmip7_get_cell_measures(tables_path, "atmos", "cl_tavg-al-hxy-u", "mon",
        "glb", cell_measures, sizeof(cell_measures));
cmor_set_variable_attribute(var_id, "cell_measures", 'c', cell_measures);
if (cmip7_get_long_name_override(tables_path, "atmos", "cl_tavg-al-hxy-u",
        "mon", "glb", long_name,
        sizeof(long_name))) {
    cmor_set_variable_attribute(var_id, "long_name", 'c', long_name);
}

```

```
cmor_write(var_id, cl, 'f', NULL, CMIP7_NTICES, NULL, NULL, NULL);
cmor_write(ps_id, ps, 'f', NULL, CMIP7_NTICES, NULL, NULL, &var_id);
filename[0] = '\0';
cmor_close_variable(var_id, filename, NULL);
printf("%s\n", filename);
cmor_close();
return 0;
}
```

**Click to expand NetCDF dump**

```

netcdf cl_tavg-al-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    lev = 5 ;
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double lev(lev) ;
        lev:bounds = "lev_bnds" ;
        lev:units = "1" ;
        lev:axis = "Z" ;
        lev:positive = "down" ;
        lev:long_name = "hybrid sigma pressure coordinate" ;
        lev:standard_name = "atmosphere_hybrid_sigma_pressure_coordinate" ;
        lev:formula = "p = a*p0 + b*ps" ;
        lev:formula_terms = "p0: p0 a: a b: b ps: ps" ;
    double lev_bnds(lev, bnds) ;
        lev_bnds:formula = "p = a*p0 + b*ps" ;
        lev_bnds:standard_name = "atmosphere_hybrid_sigma_pressure_coordinate" ;
        lev_bnds:units = "1" ;
        lev_bnds:formula_terms = "p0: p0 a: a_bnds b: b_bnds ps: ps" ;
    double p0 ;
        p0:standard_name = "reference_air_pressure_for_atmosphere_vertical_coordinate" ;
        p0:long_name = "vertical coordinate formula term: reference pressure" ;
        p0:units = "Pa" ;
    double a(lev) ;
        a:long_name = "vertical coordinate formula term: a" ;
    double b(lev) ;
        b:long_name = "vertical coordinate formula term: b" ;
    float ps(time, lat, lon) ;
        ps:standard_name = "air_pressure" ;
        ps:long_name = "Surface Air Pressure" ;
        ps:units = "Pa" ;
    double a_bnds(lev, bnds) ;
        a_bnds:long_name = "vertical coordinate formula term: a(k+1/2)" ;
    double b_bnds(lev, bnds) ;

```

```

        b_bnds:long_name = "vertical coordinate formula term: b(k+1/2)"
;
double lat(lat) ;
    lat:bounds = "lat_bnds" ;
    lat:units = "degrees_north" ;
    lat:axis = "Y" ;
    lat:long_name = "Latitude" ;
    lat:standard_name = "latitude" ;
double lat_bnds(lat, bnds) ;
double lon(lon) ;
    lon:bounds = "lon_bnds" ;
    lon:units = "degrees_east" ;
    lon:axis = "X" ;
    lon:long_name = "Longitude" ;
    lon:standard_name = "longitude" ;
double lon_bnds(lon, bnds) ;
float cl(time, lev, lat, lon) ;
    cl:standard_name = "cloud_area_fraction_in_atmosphere_layer" ;
    cl:long_name = "Percentage Cloud Cover" ;
    cl:units = "%" ;
    cl:cell_methods = "area: time: mean" ;
    cl:missing_value = 1.e+20f ;
    cl:_FillValue = 1.e+20f ;
    cl:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "u" ;
    :branded_variable = "cl_tavg-al-hxy-u" ;
    :branding_suffix = "tavg-al-hxy-u" ;
    :creation_date = "2026-09-14T18:14:10Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
    :drs_specs = "MIP-DRS7" ;
    :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
    :experiment_id = "amip" ;
    :external_variables = "areacella" ;
    :forcing_index = "f1" ;
    :frequency = "mon" ;
    :grid_label = "g999" ;
    :history = "2026-09-14T18:14:10Z ; CMOR rewrote data to be consi
stent with CF-1.12 and CMIP7 data requirements." ;
    :horizontal_label = "hxy" ;
    :host_collection = "CMIP7" ;
    :initialization_index = "i1" ;
    :institution = "Met Office Hadley Centre" ;

```

```

:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/c/output" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;

:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:variable_id = "cl" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "al" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
:tracking_id = "hdl:21.14107/8e48ae6a-6f74-4cdc-9297-49b05b89b29
1" ;
data:

time = 15.5, 45.5 ;

time_bnds =
  0, 31,
  31, 60 ;

lev = 0.92, 0.72, 0.5, 0.3, 0.1 ;

lev_bnds =
  1, 0.83,
  0.83, 0.61,
  0.61, 0.4,
  0.4, 0.2,

```

```
0.2, 0 ;

p0 = 100000 ;

a = 0.12, 0.22, 0.3, 0.2, 0.1 ;

b = 0.8, 0.5, 0.2, 0.1, 0 ;

ps =
  97000, 97400, 97800, 98200,
  98600, 99000, 99400, 99800,
  100200, 100600, 101000, 101400,
  97100, 97500, 97900, 98300,
  98700, 99100, 99500, 99900,
  100300, 100700, 101100, 101500 ;

a_bnds =
  0.06, 0.18,
  0.18, 0.26,
  0.26, 0.25,
  0.25, 0.15,
  0.15, 0 ;

b_bnds =
  0.94, 0.65,
  0.65, 0.35,
  0.35, 0.15,
  0.15, 0.05,
  0.05, 0 ;

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

lon = 0, 90, 180, 270 ;

lon_bnds =
  -45, 45,
  45, 135,
  135, 225,
  225, 315 ;

cl =
  70, 70.4, 70.8, 71.2,
  68.8, 69.2, 69.60001, 70,
  67.6, 68, 68.4, 68.8,
  65, 65.4, 65.8, 66.2,
```

```
63.8, 64.2, 64.6, 65,  
62.6, 63, 63.4, 63.8,  
60, 60.4, 60.8, 61.2,  
58.8, 59.2, 59.6, 60,  
57.6, 58, 58.4, 58.8,  
55, 55.4, 55.8, 56.2,  
53.8, 54.2, 54.6, 55,  
52.6, 53, 53.4, 53.8,  
50, 50.4, 50.8, 51.2,  
48.8, 49.2, 49.6, 50,  
47.6, 48, 48.4, 48.8,  
70.1, 70.5, 70.9, 71.3,  
68.9, 69.3, 69.7, 70.1,  
67.7, 68.1, 68.5, 68.89999,  
65.1, 65.5, 65.9, 66.3,  
63.9, 64.3, 64.7, 65.1,  
62.7, 63.1, 63.5, 63.9,  
60.1, 60.5, 60.9, 61.3,  
58.9, 59.3, 59.7, 60.1,  
57.7, 58.1, 58.5, 58.9,  
55.1, 55.5, 55.9, 56.3,  
53.9, 54.3, 54.7, 55.1,  
52.7, 53.1, 53.5, 53.9,  
50.1, 50.5, 50.9, 51.3,  
48.9, 49.3, 49.7, 50.1,  
47.7, 48.1, 48.5, 48.9 ;  
}
```

#### Example 6: Curvilinear Grid

- [example\\_06\\_curvilinear\\_grid.c \(page 0\)](#)

**Click to expand C code**

```

#include "cmip7_c_common.h"

#include <stdio.h>

#define NX 4
#define NY 3
#define NVERTICES 4
#define NPARAMS 6
#define PARAM_LEN 32
#define UNIT_LEN 2

int main(int argc, char **argv) {
    const char *tables_path;
    const char *input_path;
    const char *output_dir;
    char cell_measures[CMOR_MAX_STRING];
    char long_name[CMOR_MAX_STRING];
    char filename[CMOR_MAX_STRING];
    int file_action = CMOR_REPLACE;
    int exit_control = CMOR_EXIT_ON_MAJOR;
    int table_id, grid_table_id, x_id, y_id, time_id, grid_id, var_id;
    int grid_axes[2];
    int axes[2];
    int i, j, t;
    double x[NX] = {0.0, 10000.0, 20000.0, 30000.0};
    double y[NY] = {0.0, 10000.0, 20000.0};
    double x_bnds[NX + 1] = {-5000.0, 5000.0, 15000.0, 25000.0, 35000.0};
    double y_bnds[NY + 1] = {-5000.0, 5000.0, 15000.0, 25000.0};
    double latitude[NY * NX];
    double longitude[NY * NX];
    double latitude_vertices[NY * NX * NVERTICES];
    double longitude_vertices[NY * NX * NVERTICES];
    double time[CMIP7_NTICES] = {15.5, 45.5};
    double time_bnds[CMIP7_NTICES + 1] = {0.0, 31.0, 60.0};
    char parameter_names[NPARAMS][PARAM_LEN] = {"standard_parallel1",
                                                  "longitude_of_central_meridian",
                                                  "latitude_of_projection_origin",
                                                  "false_easting",
                                                  "false_northing",
                                                  "standard_parallel2"};
    char parameter_units[NPARAMS][UNIT_LEN] = {"", "", "", "", "", ""};
    double parameter_values[CMOR_MAX_GRID_ATTRIBUTES] = {-20.0, 175.0, 13.0,
                                                         8.0, 0.0, 20.0};

    float hfls[CMIP7_NTICES * NY * NX];
    float missing = CMIP7_MISSING_VALUE;

    cmip7_get_example_args(argc, argv, &tables_path, &input_path, &output_dir);

    cmor_setup((char *)tables_path, &file_action, NULL, &exit_control, NULL,
              NULL);

```

```

cmip7_load_shared_user_input(input_path, output_dir, NULL, NULL, NULL);

cmor_load_table("CMIP7_grids.json", &grid_table_id);
cmor_set_table(grid_table_id);
cmor_axis(&y_id, "y", "m", NY, y, 'd', y_bnds, 1, NULL);
cmor_axis(&x_id, "x", "m", NX, x, 'd', x_bnds, 1, NULL);

for (j = 0; j < NY; ++j) {
    for (i = 0; i < NX; ++i) {
        int idx = j * NX + i;
        int vertex_idx = idx * NVERTICES;

        latitude[idx] = 10.0 * (double)(j + 1) - 2.0 * (double)i;
        longitude[idx] = 280.0 + 10.0 * (double)i + 2.0 * (double)j;
        latitude_vertices[vertex_idx + 0] = latitude[idx] - 5.0;
        latitude_vertices[vertex_idx + 1] = latitude[idx] - 4.0;
        latitude_vertices[vertex_idx + 2] = latitude[idx] + 5.0;
        latitude_vertices[vertex_idx + 3] = latitude[idx] + 4.0;
        longitude_vertices[vertex_idx + 0] = longitude[idx] - 5.0;
        longitude_vertices[vertex_idx + 1] = longitude[idx] + 5.0;
        longitude_vertices[vertex_idx + 2] = longitude[idx] + 5.0;
        longitude_vertices[vertex_idx + 3] = longitude[idx] - 5.0;
    }
}

grid_axes[0] = y_id;
grid_axes[1] = x_id;
cmor_grid(&grid_id, 2, grid_axes, 'd', latitude, longitude, NVERTICES,
         latitude_vertices, longitude_vertices);
cmor_set_grid_mapping(grid_id, "lambert_conformal_conic", NPARAMS,
                     &parameter_names[0][0], PARAM_LEN, parameter_values,
                     &parameter_units[0][0], UNIT_LEN);

cmor_load_table("CMIP7_atmos.json", &table_id);
cmor_axis(&time_id, "time", "days since 1979-01-01", CMIP7_NTICES, time, 'd',
         time_bnds, 1, NULL);

for (t = 0; t < CMIP7_NTICES; ++t) {
    for (j = 0; j < NY; ++j) {
        for (i = 0; i < NX; ++i) {
            int idx = (t * NY + j) * NX + i;
            hfls[idx] = 80.0f + 2.0f * (float)i + 8.0f * (float)j + (float)t;
        }
    }
}

axes[0] = time_id;
axes[1] = grid_id;
cmor_variable(&var_id, "hfls_tavg-u-hxy-u", "W m-2", 2, axes, 'f', &missing,
             NULL, "up", NULL, NULL, NULL);

```

```
cmip7_get_cell_measures(tables_path, "atmos", "hfls_tavg-u-hxy-u", "mon",
                        "glb", cell_measures, sizeof(cell_measures));
cmor_set_variable_attribute(var_id, "cell_measures", 'c', cell_measures);
if (cmip7_get_long_name_override(tables_path, "atmos", "hfls_tavg-u-hxy-u",
                                "mon", "glb", long_name,
                                sizeof(long_name))) {
    cmor_set_variable_attribute(var_id, "long_name", 'c', long_name);
}

cmor_write(var_id, hfls, 'f', NULL, CMIP7_NTICES, NULL, NULL, NULL);
filename[0] = '\0';
cmor_close_variable(var_id, filename, NULL);
printf("%s\n", filename);
cmor_close();
return 0;
}
```

**Click to expand NetCDF dump**

```

netcdf hfls_tavg-u-hxy-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    y = 3 ;
    x = 4 ;
    bnds = 2 ;
    vertices = 4 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Intervals" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    double y(y) ;
        y:bounds = "y_bnds" ;
        y:units = "m" ;
        y:axis = "Y" ;
        y:long_name = "y coordinate of projection" ;
        y:standard_name = "projection_y_coordinate" ;
    double y_bnds(y, bnds) ;
    double x(x) ;
        x:bounds = "x_bnds" ;
        x:units = "m" ;
        x:axis = "X" ;
        x:long_name = "x coordinate of projection" ;
        x:standard_name = "projection_x_coordinate" ;
    double x_bnds(x, bnds) ;
    int lambert_conformal_conic ;
        lambert_conformal_conic:grid_mapping_name = "lambert_conformal_c
onic" ;
        lambert_conformal_conic:standard_parallel = -20., 20. ;
        lambert_conformal_conic:longitude_of_central_meridian = 175. ;
        lambert_conformal_conic:latitude_of_projection_origin = 13. ;
        lambert_conformal_conic:false_easting = 8. ;
        lambert_conformal_conic:false_northing = 0. ;
    double latitude(y, x) ;
        latitude:standard_name = "latitude" ;
        latitude:long_name = "latitude" ;
        latitude:units = "degrees_north" ;
        latitude:missing_value = 1.e+20 ;
        latitude:_FillValue = 1.e+20 ;
        latitude:bounds = "vertices_latitude" ;
    double longitude(y, x) ;
        longitude:standard_name = "longitude" ;
        longitude:long_name = "longitude" ;
        longitude:units = "degrees_east" ;
        longitude:missing_value = 1.e+20 ;

```

```

        longitude:_FillValue = 1.e+20 ;
        longitude:bounds = "vertices_longitude" ;
double vertices_latitude(y, x, vertices) ;
        vertices_latitude:units = "degrees_north" ;
        vertices_latitude:missing_value = 1.e+20 ;
        vertices_latitude:_FillValue = 1.e+20 ;
double vertices_longitude(y, x, vertices) ;
        vertices_longitude:units = "degrees_east" ;
        vertices_longitude:missing_value = 1.e+20 ;
        vertices_longitude:_FillValue = 1.e+20 ;
float hfls(time, y, x) ;
        hfls:standard_name = "surface_upward_latent_heat_flux" ;
        hfls:long_name = "Surface Upward Latent Heat Flux" ;
        hfls:units = "W m-2" ;
        hfls:cell_methods = "area: time: mean" ;
        hfls:missing_value = 1.e+20f ;
        hfls:_FillValue = 1.e+20f ;
        hfls:cell_measures = "area: areacella" ;
        hfls:grid_mapping = "lambert_conformal_conic" ;
        hfls:coordinates = "latitude longitude" ;

// global attributes:
        :Conventions = "CF-1.12" ;
        :activity_id = "CMIP" ;
        :archive_id = "WCRP" ;
        :area_label = "u" ;
        :branded_variable = "hfls_tavg-u-hxy-u" ;
        :branding_suffix = "tavg-u-hxy-u" ;
        :creation_date = "2026-09-14T18:14:11Z" ;
        :data_specs_version = "MIP-DS7.1.0.0" ;
        :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
        :drs_specs = "MIP-DRS7" ;
        :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
        :experiment_id = "amip" ;
        :external_variables = "areacella" ;
        :forcing_index = "f1" ;
        :frequency = "mon" ;
        :grid_label = "g999" ;
        :history = "2026-09-14T18:14:11Z ; CMOR rewrote data to be consistent
with CF-1.12 and CMIP7 data requirements." ;
        :horizontal_label = "hxy" ;
        :host_collection = "CMIP7" ;
        :initialization_index = "i1" ;
        :institution = "Met Office Hadley Centre" ;
        :institution_id = "MOHC" ;
        :license_id = "CC-BY-4.0" ;
        :mip_era = "CMIP7" ;
        :nominal_resolution = "100 km" ;

```

```

:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/c/output" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "atmos" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;

:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21
13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
:temporal_label = "tavg" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/f0e6a84b-7776-4cdc-9f35-cc9462b0ebf
a" ;

:variable_id = "hfls" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

time = 15.5, 45.5 ;

time_bnds =
  0, 31,
  31, 60 ;

y = 0, 10000, 20000 ;

y_bnds =
  -5000, 5000,
  5000, 15000,
  15000, 25000 ;

x = 0, 10000, 20000, 30000 ;

x_bnds =
  -5000, 5000,

```

```
5000, 15000,  
15000, 25000,  
25000, 35000 ;  
  
lambert_conformal_conic = _ ;  
  
latitude =  
10, 8, 6, 4,  
20, 18, 16, 14,  
30, 28, 26, 24 ;  
  
longitude =  
280, 290, 300, 310,  
282, 292, 302, 312,  
284, 294, 304, 314 ;  
  
vertices_latitude =  
5, 6, 15, 14,  
3, 4, 13, 12,  
1, 2, 11, 10,  
-1, 0, 9, 8,  
15, 16, 25, 24,  
13, 14, 23, 22,  
11, 12, 21, 20,  
9, 10, 19, 18,  
25, 26, 35, 34,  
23, 24, 33, 32,  
21, 22, 31, 30,  
19, 20, 29, 28 ;  
  
vertices_longitude =  
275, 285, 285, 275,  
285, 295, 295, 285,  
295, 305, 305, 295,  
305, 315, 315, 305,  
277, 287, 287, 277,  
287, 297, 297, 287,  
297, 307, 307, 297,  
307, 317, 317, 307,  
279, 289, 289, 279,  
289, 299, 299, 289,  
299, 309, 309, 299,  
309, 319, 319, 309 ;  
  
hfls =  
80, 82, 84, 86,  
88, 90, 92, 94,  
96, 98, 100, 102,  
81, 83, 85, 87,  
89, 91, 93, 95,
```

```
    97, 99, 101, 103 ;  
}
```

### Example 7: Fixed Field

- [example\\_07\\_fixed\\_field\\_rootd.c \(page 0\)](#)

**Click to expand C code**

```

#include "cmip7_c_common.h"

#include <stdio.h>

int main(int argc, char **argv) {
    const char *tables_path;
    const char *input_path;
    const char *output_dir;
    char cell_measures[CMOR_MAX_STRING];
    char long_name[CMOR_MAX_STRING];
    char filename[CMOR_MAX_STRING];
    int file_action = CMOR_REPLACE;
    int exit_control = CMOR_EXIT_ON_MAJOR;
    int table_id, lon_id, lat_id, var_id;
    int axes[2];
    double lat[CMIP7_NLAT] = {10.0, 20.0, 30.0};
    double lat_bnds[CMIP7_NLAT + 1] = {5.0, 15.0, 25.0, 35.0};
    double lon[CMIP7_NLON] = {0.0, 90.0, 180.0, 270.0};
    double lon_bnds[CMIP7_NLON + 1] = {-45.0, 45.0, 135.0, 225.0, 315.0};
    float rootd[CMIP7_NLAT * CMIP7_NLON] = {0.50f,
                                              0.45f,
                                              CMIP7_MISSING_VALUE,
                                              0.55f,
                                              0.60f,
                                              0.60f,
                                              CMIP7_MISSING_VALUE,
                                              0.55f,
                                              CMIP7_MISSING_VALUE,
                                              0.45f,
                                              0.50f,
                                              0.50f};

    float missing = CMIP7_MISSING_VALUE;

    cmip7_get_example_args(argc, argv, &tables_path, &input_path, &output_dir);

    cmor_setup((char *)tables_path, &file_action, NULL, &exit_control, NULL,
               NULL);
    cmip7_load_shared_user_input(input_path, output_dir, "fx", NULL, NULL);
    cmor_load_table("CMIP7_land.json", &table_id);

    cmor_axis(&lon_id, "longitude", "degrees_east", CMIP7_NLON, lon, 'd',
              lon_bnds, 1, NULL);
    cmor_axis(&lat_id, "latitude", "degrees_north", CMIP7_NLAT, lat, 'd',
              lat_bnds, 1, NULL);

    axes[0] = lat_id;
    axes[1] = lon_id;
    cmor_variable(&var_id, "rootd_ti-u-hxy-lnd", "m", 2, axes, 'f', &missing,
                  NULL, NULL, NULL, NULL, NULL);

```

```
cmip7_get_cell_measures(tables_path, "land", "rootd_ti-u-hxy-lnd", "fx",
                        "glb", cell_measures, sizeof(cell_measures));
cmor_set_variable_attribute(var_id, "cell_measures", 'c', cell_measures);
if (cmip7_get_long_name_override(tables_path, "land", "rootd_ti-u-hxy-lnd",
                                "fx", "glb", long_name, sizeof(long_name))) {
    cmor_set_variable_attribute(var_id, "long_name", 'c', long_name);
}

cmor_write(var_id, rootd, 'f', NULL, 0, NULL, NULL, NULL);
filename[0] = '\0';
cmor_close_variable(var_id, filename, NULL);
printf("%s\n", filename);
cmor_close();
return 0;
}
```

**Click to expand NetCDF dump**

```

netcdf rootd_ti-u-hxy-lnd_fx_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1 {
dimensions:
    lat = 3 ;
    lon = 4 ;
    bnds = 2 ;
variables:
    double lat(lat) ;
        lat:bounds = "lat_bnds" ;
        lat:units = "degrees_north" ;
        lat:axis = "Y" ;
        lat:long_name = "Latitude" ;
        lat:standard_name = "latitude" ;
    double lat_bnds(lat, bnds) ;
    double lon(lon) ;
        lon:bounds = "lon_bnds" ;
        lon:units = "degrees_east" ;
        lon:axis = "X" ;
        lon:long_name = "Longitude" ;
        lon:standard_name = "longitude" ;
    double lon_bnds(lon, bnds) ;
    float rootd(lat, lon) ;
        rootd:standard_name = "root_depth" ;
        rootd:long_name = "Maximum Root Depth" ;
        rootd:units = "m" ;
        rootd:cell_methods = "area: mean where land" ;
        rootd:missing_value = 1.e+20f ;
        rootd:_FillValue = 1.e+20f ;
        rootd:cell_measures = "area: areacella" ;

// global attributes:
    :Conventions = "CF-1.12" ;
    :activity_id = "CMIP" ;
    :archive_id = "WCRP" ;
    :area_label = "lnd" ;
    :branded_variable = "rootd_ti-u-hxy-lnd" ;
    :branding_suffix = "ti-u-hxy-lnd" ;
    :creation_date = "2026-09-14T18:14:11Z" ;
    :data_specs_version = "MIP-DS7.1.0.0" ;
    :description = "Simulation of the climate of the recent past with
h prescribed sea surface temperatures and sea ice concentrations." ;
    :drs_specs = "MIP-DRS7" ;
    :experiment = "Simulation of the climate of the recent past with
prescribed sea surface temperatures and sea ice concentrations." ;
    :experiment_id = "amip" ;
    :external_variables = "areacella" ;
    :forcing_index = "f1" ;
    :frequency = "fx" ;
    :grid_label = "g999" ;
    :history = "2026-09-14T18:14:11Z ; CMOR rewrote data to be consistent
with CF-1.12 and CMIP7 data requirements." ;

```

```

:horizontal_label = "hxy" ;
:host_collection = "CMIP7" ;
:initialization_index = "i1" ;
:institution = "Met Office Hadley Centre" ;
:institution_id = "MOHC" ;
:license_id = "CC-BY-4.0" ;
:mip_era = "CMIP7" ;
:nominal_resolution = "100 km" ;
:outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/my
doc/examples/c/output" ;
:physics_index = "p1" ;
:product = "model-output" ;
:realization_index = "r1" ;
:realm = "land" ;
:region = "glb" ;
:source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; l
and-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: ci
ce5" ;
:source_id = "ACCESS-ESM1-6" ;
:table_info = "Name: CMIP7_land.json; Creation Date:(2026-07-21
13:16:24) MD5:ea523449976b1c3cc3c14c1492f2fb74" ;
:temporal_label = "ti" ;
:title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
:tracking_id = "hdl:21.14107/cca25136-3bcb-48a3-bfda-fa9f003e4a7
8" ;
:variable_id = "rootd" ;
:variant_label = "r1i1p1f1" ;
:vertical_label = "u" ;
:license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativecommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/docs/CMIP7/Guidance\_for\_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
:cmor_version = "3.15.3" ;
data:

lat = 10, 20, 30 ;

lat_bnds =
  5, 15,
  15, 25,
  25, 35 ;

lon = 0, 90, 180, 270 ;

```

```
lon_bnds =  
  -45, 45,  
  45, 135,  
  135, 225,  
  225, 315 ;  
  
rootd =  
  0.5, 0.45, _, 0.55,  
  0.6, 0.6, _, 0.55,  
  _, 0.45, 0.5, 0.5 ;  
}
```

### Example 8: Site Dimension

- [example\\_08\\_site\\_dimension.c \(page 0\)](#)

**Click to expand C code**

```

#include "cmip7_c_common.h"

#include <stdio.h>

#define NSITES 126
#define NVERTICES 2

int main(int argc, char **argv) {
    const char *tables_path;
    const char *input_path;
    const char *output_dir;
    char cell_measures[CMOR_MAX_STRING];
    char long_name[CMOR_MAX_STRING];
    char filename[CMOR_MAX_STRING];
    int file_action = CMOR_REPLACE;
    int exit_control = CMOR_EXIT_ON_MAJOR;
    int table_id, grid_table_id, time_id, site_id, height_id, grid_id, var_id;
    int grid_axes[1];
    int axes[3];
    int site, time_index;
    double time[CMIP7_NTIMES] = {15.5, 45.5};
    double time_bnds[CMIP7_NTIMES + 1] = {0.0, 31.0, 60.0};
    double site_values[NSITES];
    double latitude[NSITES];
    double longitude[NSITES];
    double latitude_vertices[NSITES * NVERTICES];
    double longitude_vertices[NSITES * NVERTICES];
    double height = 2.0;
    float tas[CMIP7_NTIMES * NSITES];
    float missing = CMIP7_MISSING_VALUE;

    cmip7_get_example_args(argc, argv, &tables_path, &input_path, &output_dir);

    cmor_setup((char *)tables_path, &file_action, NULL, &exit_control, NULL,
               NULL);
    cmip7_load_shared_user_input(input_path, output_dir, NULL, NULL, NULL);
    cmor_load_table("CMIP7_atmos.json", &table_id);

    cmor_axis(&time_id, "time1", "days since 1979-01-01", CMIP7_NTIMES, time,
              'd', time_bnds, 1, NULL);
    cmor_axis(&height_id, "height2m", "m", 1, &height, 'd', NULL, 0, NULL);

    for (site = 0; site < NSITES; ++site) {
        int vertex = site * NVERTICES;
        site_values[site] = (double)(site + 1);
        latitude[site] = -60.0 + 120.0 * (double)site / (double)(NSITES - 1);
        longitude[site] = 0.5 + 359.0 * (double)site / (double)(NSITES - 1);
        latitude_vertices[vertex] = latitude[site] - 0.25;
        latitude_vertices[vertex + 1] = latitude[site] + 0.25;
        longitude_vertices[vertex] = longitude[site] - 0.25;
    }
}

```

```

    longitude_vertices[vertex + 1] = longitude[site] + 0.25;
}
cmor_axis(&site_id, "site", "1", NSITES, site_values, 'd', NULL, 0, NULL);

cmor_load_table("CMIP7_grids.json", &grid_table_id);
cmor_set_table(grid_table_id);
grid_axes[0] = site_id;
cmor_grid(&grid_id, 1, grid_axes, 'd', latitude, longitude, NVERTICES,
          latitude_vertices, longitude_vertices);

cmor_load_table("CMIP7_atmos.json", &table_id);
axes[0] = height_id;
axes[1] = time_id;
axes[2] = grid_id;
cmor_variable(&var_id, "tas_tpt-h2m-hs-u", "K", 3, axes, 'f', &missing,
              NULL, NULL, NULL, NULL, NULL);

cmip7_get_cell_measures(tables_path, "atmos", "tas_tpt-h2m-hs-u", "mon",
                        "glb", cell_measures, sizeof(cell_measures));
cmor_set_variable_attribute(var_id, "cell_measures", 'c', cell_measures);
if (cmip7_get_long_name_override(tables_path, "atmos", "tas_tpt-h2m-hs-u",
                                "mon", "glb", long_name,
                                sizeof(long_name))) {
    cmor_set_variable_attribute(var_id, "long_name", 'c', long_name);
}

for (time_index = 0; time_index < CMIP7_NTIMES; ++time_index) {
    for (site = 0; site < NSITES; ++site) {
        tas[time_index * NSITES + site] =
            275.0f + 15.0f * (float)(time_index * NSITES + site) /
            (float)(CMIP7_NTIMES * NSITES - 1);
    }
}
cmor_write(var_id, tas, 'f', NULL, CMIP7_NTIMES, NULL, NULL, NULL);
filename[0] = '\0';
cmor_close_variable(var_id, filename, NULL);
printf("%s\n", filename);
cmor_close();
return 0;
}

```

**Click to expand NetCDF dump**

```

netcdf tas_tpt-h2m-hs-u_mon_glb_g999_ACCESS-ESM1-6_amip_r1i1p1f1_197901-197902 {
dimensions:
    time = UNLIMITED ; // (2 currently)
    site = 126 ;
    bnds = 2 ;
    vertices = 2 ;
variables:
    double time(time) ;
        time:bounds = "time_bnds" ;
        time:units = "days since 1979-01-01" ;
        time:calendar = "360_day" ;
        time:axis = "T" ;
        time:long_name = "Time Points" ;
        time:standard_name = "time" ;
    double time_bnds(time, bnds) ;
    int site(site) ;
        site:long_name = "site index" ;
    double latitude(site) ;
        latitude:standard_name = "latitude" ;
        latitude:long_name = "latitude" ;
        latitude:units = "degrees_north" ;
        latitude:missing_value = 1.e+20 ;
        latitude:_FillValue = 1.e+20 ;
        latitude:bounds = "vertices_latitude" ;
    double longitude(site) ;
        longitude:standard_name = "longitude" ;
        longitude:long_name = "longitude" ;
        longitude:units = "degrees_east" ;
        longitude:missing_value = 1.e+20 ;
        longitude:_FillValue = 1.e+20 ;
        longitude:bounds = "vertices_longitude" ;
    double vertices_latitude(site, vertices) ;
        vertices_latitude:units = "degrees_north" ;
        vertices_latitude:missing_value = 1.e+20 ;
        vertices_latitude:_FillValue = 1.e+20 ;
    double vertices_longitude(site, vertices) ;
        vertices_longitude:units = "degrees_east" ;
        vertices_longitude:missing_value = 1.e+20 ;
        vertices_longitude:_FillValue = 1.e+20 ;
    double height ;
        height:units = "m" ;
        height:axis = "Z" ;
        height:positive = "up" ;
        height:long_name = "height" ;
        height:standard_name = "height" ;
    float tas(time, site) ;
        tas:standard_name = "air_temperature" ;
        tas:long_name = "Near-Surface Air Temperature" ;
        tas:units = "K" ;
        tas:cell_methods = "area: point time: point" ;

```

```

        tas:history = "2026-09-14T18:14:12Z altered by CMOR: Treated scalar dimension: \height\" ;
        tas:coordinates = "height latitude longitude" ;
        tas:missing_value = 1.e+20f ;
        tas:_FillValue = 1.e+20f ;

// global attributes:
        :Conventions = "CF-1.12" ;
        :activity_id = "CMIP" ;
        :archive_id = "WCRP" ;
        :area_label = "u" ;
        :branded_variable = "tas_tpt-h2m-hs-u" ;
        :branding_suffix = "tpt-h2m-hs-u" ;
        :creation_date = "2026-09-14T18:14:12Z" ;
        :data_specs_version = "MIP-DS7.1.0.0" ;
        :description = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;
        :drs_specs = "MIP-DRS7" ;
        :experiment = "Simulation of the climate of the recent past with prescribed sea surface temperatures and sea ice concentrations." ;
        :experiment_id = "amip" ;
        :forcing_index = "f1" ;
        :frequency = "mon" ;
        :grid_label = "g999" ;
        :history = "2026-09-14T18:14:12Z ; CMOR rewrote data to be consistent with CF-1.12 and CMIP7 data requirements." ;
        :horizontal_label = "hs" ;
        :host_collection = "CMIP7" ;
        :initialization_index = "i1" ;
        :institution = "Met Office Hadley Centre" ;
        :institution_id = "MOHC" ;
        :license_id = "CC-BY-4.0" ;
        :mip_era = "CMIP7" ;
        :nominal_resolution = "100 km" ;
        :outpath = "/Users/mauzey1/Desktop/github/cmor3_documentation/mydoc/examples/c/output" ;
        :physics_index = "p1" ;
        :product = "model-output" ;
        :realization_index = "r1" ;
        :realm = "atmos" ;
        :region = "glb" ;
        :source = "ACCESS-ESM1-6: aerosol: classic; atmosphere: um7-3; land-surface: cable3; ocean-biogeochemistry: wombatlite; ocean: mom5; sea-ice: cice5" ;
        :source_id = "ACCESS-ESM1-6" ;
        :table_info = "Name: CMIP7_atmos.json; Creation Date:(2026-07-21 13:16:24) MD5:28339aa355908b9331150e1536f5e384" ;
        :temporal_label = "tpt" ;
        :title = "ACCESS-ESM1-6 output prepared for CMIP7" ;
        :tracking_id = "hdl:21.14107/a15beb4c-3e7a-4a11-abf9-c3364e73788

```

```
f" ;
    :variable_id = "tas" ;
    :variant_label = "r1i1p1f1" ;
    :vertical_label = "h2m" ;
    :license = "CC-BY-4.0; CMIP7 data produced by MOHC is licensed u
nder a Creative Commons Attribution 4.0 International License (https://creativec
ommons.org/licenses/by/4.0). Consult https://wcrp-cmip.github.io/cmip7-guidance/
docs/CMIP7/Guidance_for_users/#2-terms-of-use-and-citations-requirements for ter
ms of use governing CMIP7 output, including citation requirements and proper ack
nowledgment. The data producers and data providers make no warranty, either expr
ess or implied, including, but not limited to, warranties of merchantability and
fitness for a particular purpose. All liabilities arising from the supply of the
information (including any liability arising in negligence) are excluded to the
fullest extent permitted by law." ;
    :cmor_version = "3.15.3" ;
data:

time = 15.5, 45.5 ;

time_bnds =
    0, 31,
    31, 60 ;

site = 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19,
    20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37,
    38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55,
    56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73,
    74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,
    92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107,
    108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121,
    122, 123, 124, 125, 126 ;

latitude = -60, -59.04, -58.08, -57.12, -56.16, -55.2, -54.24, -53.28,
    -52.32, -51.36, -50.4, -49.44, -48.48, -47.52, -46.56, -45.6, -44.64,
    -43.68, -42.72, -41.76, -40.8, -39.84, -38.88, -37.92, -36.96, -36,
    -35.04, -34.08, -33.12, -32.16, -31.2, -30.24, -29.28, -28.32, -27.36,
    -26.4, -25.44, -24.48, -23.52, -22.56, -21.6, -20.64, -19.68, -18.72,
    -17.76, -16.8, -15.84, -14.88, -13.92, -12.96, -12, -11.04, -10.08,
    -9.12, -8.16, -7.2, -6.24, -5.28, -4.32, -3.36, -2.4, -1.44,
    -0.4799999999999997, 0.4799999999999997, 1.44, 2.4, 3.36, 4.319999999999999,
    5.28, 6.239999999999999, 7.2, 8.16, 9.12, 10.08, 11.04, 12, 12.96, 13.92,
    14.88, 15.84, 16.8, 17.76, 18.72, 19.68, 20.64, 21.6, 22.56, 23.52,
    24.48, 25.44, 26.4, 27.36, 28.32, 29.28, 30.24, 31.2, 32.16, 33.12,
    34.08, 35.04, 36, 36.96, 37.92, 38.88, 39.84, 40.8, 41.76, 42.72, 43.68,
    44.64, 45.6, 46.56, 47.52, 48.48, 49.44, 50.4, 51.36, 52.32, 53.28,
    54.24, 55.2, 56.16, 57.12, 58.08, 59.04, 60 ;

longitude = 0.5, 3.372, 6.244, 9.116, 11.988, 14.86, 17.732, 20.604, 23.476,
    26.348, 29.22, 32.092, 34.964, 37.836, 40.708, 43.58, 46.452, 49.324,
    52.196, 55.068, 57.94, 60.812, 63.684, 66.556, 69.428, 72.3, 75.172,
```

78.044, 80.916, 83.788, 86.66, 89.532, 92.404, 95.276, 98.148, 101.02,  
 103.892, 106.764, 109.636, 112.508, 115.38, 118.252, 121.124, 123.996,  
 126.868, 129.74, 132.612, 135.484, 138.356, 141.228, 144.1, 146.972,  
 149.844, 152.716, 155.588, 158.46, 161.332, 164.204, 167.076, 169.948,  
 172.82, 175.692, 178.564, 181.436, 184.308, 187.18, 190.052, 192.924,  
 195.796, 198.668, 201.54, 204.412, 207.284, 210.156, 213.028, 215.9,  
 218.772, 221.644, 224.516, 227.388, 230.26, 233.132, 236.004, 238.876,  
 241.748, 244.62, 247.492, 250.364, 253.236, 256.108, 258.98, 261.852,  
 264.724, 267.596, 270.468, 273.34, 276.212, 279.084, 281.956, 284.828,  
 287.7, 290.572, 293.444, 296.316, 299.188, 302.06, 304.932, 307.804,  
 310.676, 313.548, 316.42, 319.292, 322.164, 325.036, 327.908, 330.78,  
 333.652, 336.524, 339.396, 342.268, 345.14, 348.012, 350.884, 353.756,  
 356.628, 359.5 ;

vertices\_latitude =

-60.25, -59.75,  
 -59.29, -58.79,  
 -58.33, -57.83,  
 -57.37, -56.87,  
 -56.41, -55.91,  
 -55.45, -54.95,  
 -54.49, -53.99,  
 -53.53, -53.03,  
 -52.57, -52.07,  
 -51.61, -51.11,  
 -50.65, -50.15,  
 -49.69, -49.19,  
 -48.73, -48.23,  
 -47.77, -47.27,  
 -46.81, -46.31,  
 -45.85, -45.35,  
 -44.89, -44.39,  
 -43.93, -43.43,  
 -42.97, -42.47,  
 -42.01, -41.51,  
 -41.05, -40.55,  
 -40.09, -39.59,  
 -39.13, -38.63,  
 -38.17, -37.67,  
 -37.21, -36.71,  
 -36.25, -35.75,  
 -35.29, -34.79,  
 -34.33, -33.83,  
 -33.37, -32.87,  
 -32.41, -31.91,  
 -31.45, -30.95,  
 -30.49, -29.99,  
 -29.53, -29.03,  
 -28.57, -28.07,  
 -27.61, -27.11,

-26.65, -26.15,  
-25.69, -25.19,  
-24.73, -24.23,  
-23.77, -23.27,  
-22.81, -22.31,  
-21.85, -21.35,  
-20.89, -20.39,  
-19.93, -19.43,  
-18.97, -18.47,  
-18.01, -17.51,  
-17.05, -16.55,  
-16.09, -15.59,  
-15.13, -14.63,  
-14.17, -13.67,  
-13.21, -12.71,  
-12.25, -11.75,  
-11.29, -10.79,  
-10.33, -9.83,  
-9.37, -8.87,  
-8.41, -7.91,  
-7.45, -6.95,  
-6.49, -5.99,  
-5.53, -5.03,  
-4.57, -4.07,  
-3.61, -3.11,  
-2.65, -2.15,  
-1.69, -1.19,  
-0.729999999999997, -0.229999999999997,  
0.229999999999997, 0.729999999999997,  
1.19, 1.69,  
2.15, 2.65,  
3.11, 3.61,  
4.069999999999999, 4.569999999999999,  
5.03, 5.53,  
5.989999999999999, 6.489999999999999,  
6.95, 7.45,  
7.91, 8.41,  
8.87, 9.37,  
9.83, 10.33,  
10.79, 11.29,  
11.75, 12.25,  
12.71, 13.21,  
13.67, 14.17,  
14.63, 15.13,  
15.59, 16.09,  
16.55, 17.05,  
17.51, 18.01,  
18.47, 18.97,  
19.43, 19.93,  
20.39, 20.89,

```
21.35, 21.85,  
22.31, 22.81,  
23.27, 23.77,  
24.23, 24.73,  
25.19, 25.69,  
26.15, 26.65,  
27.11, 27.61,  
28.07, 28.57,  
29.03, 29.53,  
29.99, 30.49,  
30.95, 31.45,  
31.91, 32.41,  
32.87, 33.37,  
33.83, 34.33,  
34.79, 35.29,  
35.75, 36.25,  
36.71, 37.21,  
37.67, 38.17,  
38.63, 39.13,  
39.59, 40.09,  
40.55, 41.05,  
41.51, 42.01,  
42.47, 42.97,  
43.43, 43.93,  
44.39, 44.89,  
45.35, 45.85,  
46.31, 46.81,  
47.27, 47.77,  
48.23, 48.73,  
49.19, 49.69,  
50.15, 50.65,  
51.11, 51.61,  
52.07, 52.57,  
53.03, 53.53,  
53.99, 54.49,  
54.95, 55.45,  
55.91, 56.41,  
56.87, 57.37,  
57.83, 58.33,  
58.79, 59.29,  
59.75, 60.25 ;
```

```
vertices_longitude =  
0.25, 0.75,  
3.122, 3.622,  
5.994, 6.494,  
8.866, 9.366,  
11.738, 12.238,  
14.61, 15.11,  
17.482, 17.982,
```

20.354, 20.854,  
23.226, 23.726,  
26.098, 26.598,  
28.97, 29.47,  
31.842, 32.342,  
34.714, 35.214,  
37.586, 38.086,  
40.458, 40.958,  
43.33, 43.83,  
46.202, 46.702,  
49.074, 49.574,  
51.946, 52.446,  
54.818, 55.318,  
57.69, 58.19,  
60.562, 61.062,  
63.434, 63.934,  
66.306, 66.806,  
69.178, 69.678,  
72.05, 72.55,  
74.922, 75.422,  
77.794, 78.294,  
80.666, 81.166,  
83.538, 84.038,  
86.41, 86.91,  
89.282, 89.782,  
92.154, 92.654,  
95.026, 95.526,  
97.898, 98.398,  
100.77, 101.27,  
103.642, 104.142,  
106.514, 107.014,  
109.386, 109.886,  
112.258, 112.758,  
115.13, 115.63,  
118.002, 118.502,  
120.874, 121.374,  
123.746, 124.246,  
126.618, 127.118,  
129.49, 129.99,  
132.362, 132.862,  
135.234, 135.734,  
138.106, 138.606,  
140.978, 141.478,  
143.85, 144.35,  
146.722, 147.222,  
149.594, 150.094,  
152.466, 152.966,  
155.338, 155.838,  
158.21, 158.71,  
161.082, 161.582,

163.954, 164.454,  
166.826, 167.326,  
169.698, 170.198,  
172.57, 173.07,  
175.442, 175.942,  
178.314, 178.814,  
181.186, 181.686,  
184.058, 184.558,  
186.93, 187.43,  
189.802, 190.302,  
192.674, 193.174,  
195.546, 196.046,  
198.418, 198.918,  
201.29, 201.79,  
204.162, 204.662,  
207.034, 207.534,  
209.906, 210.406,  
212.778, 213.278,  
215.65, 216.15,  
218.522, 219.022,  
221.394, 221.894,  
224.266, 224.766,  
227.138, 227.638,  
230.01, 230.51,  
232.882, 233.382,  
235.754, 236.254,  
238.626, 239.126,  
241.498, 241.998,  
244.37, 244.87,  
247.242, 247.742,  
250.114, 250.614,  
252.986, 253.486,  
255.858, 256.358,  
258.73, 259.23,  
261.602, 262.102,  
264.474, 264.974,  
267.346, 267.846,  
270.218, 270.718,  
273.09, 273.59,  
275.962, 276.462,  
278.834, 279.334,  
281.706, 282.206,  
284.578, 285.078,  
287.45, 287.95,  
290.322, 290.822,  
293.194, 293.694,  
296.066, 296.566,  
298.938, 299.438,  
301.81, 302.31,  
304.682, 305.182,

307.554, 308.054,  
 310.426, 310.926,  
 313.298, 313.798,  
 316.17, 316.67,  
 319.042, 319.542,  
 321.914, 322.414,  
 324.786, 325.286,  
 327.658, 328.158,  
 330.53, 331.03,  
 333.402, 333.902,  
 336.274, 336.774,  
 339.146, 339.646,  
 342.018, 342.518,  
 344.89, 345.39,  
 347.762, 348.262,  
 350.634, 351.134,  
 353.506, 354.006,  
 356.378, 356.878,  
 359.25, 359.75 ;

height = 2 ;

tas =

275, 275.0598, 275.1195, 275.1793, 275.239, 275.2988, 275.3586, 275.4183,  
 275.4781, 275.5378, 275.5976, 275.6574, 275.7171, 275.7769, 275.8366,  
 275.8964, 275.9562, 276.0159, 276.0757, 276.1355, 276.1952, 276.255,  
 276.3147, 276.3745, 276.4343, 276.494, 276.5538, 276.6136, 276.6733,  
 276.7331, 276.7928, 276.8526, 276.9124, 276.9721, 277.0319, 277.0916,  
 277.1514, 277.2112, 277.2709, 277.3307, 277.3904, 277.4502, 277.5099,  
 277.5697, 277.6295, 277.6892, 277.749, 277.8088, 277.8685, 277.9283,  
 277.988, 278.0478, 278.1076, 278.1673, 278.2271, 278.2869, 278.3466,  
 278.4064, 278.4661, 278.5259, 278.5857, 278.6454, 278.7052, 278.765,  
 278.8247, 278.8845, 278.9442, 279.004, 279.0638, 279.1235, 279.1833,  
 279.243, 279.3028, 279.3625, 279.4223, 279.4821, 279.5418, 279.6016,  
 279.6613, 279.7211, 279.7809, 279.8406, 279.9004, 279.9601, 280.0199,  
 280.0797, 280.1394, 280.1992, 280.259, 280.3187, 280.3785, 280.4382,  
 280.498, 280.5578, 280.6175, 280.6773, 280.7371, 280.7968, 280.8566,  
 280.9163, 280.9761, 281.0359, 281.0956, 281.1554, 281.2151, 281.2749,  
 281.3347, 281.3944, 281.4542, 281.5139, 281.5737, 281.6335, 281.6932,  
 281.753, 281.8127, 281.8725, 281.9323, 281.992, 282.0518, 282.1115,  
 282.1713, 282.2311, 282.2908, 282.3506, 282.4104, 282.4701,  
 282.5299, 282.5896, 282.6494, 282.7092, 282.7689, 282.8287, 282.8885,  
 282.9482, 283.008, 283.0677, 283.1275, 283.1873, 283.247, 283.3068,  
 283.3665, 283.4263, 283.4861, 283.5458, 283.6056, 283.6653, 283.7251,  
 283.7849, 283.8446, 283.9044, 283.9641, 284.0239, 284.0837, 284.1434,  
 284.2032, 284.2629, 284.3227, 284.3825, 284.4422, 284.502, 284.5618,  
 284.6215, 284.6813, 284.741, 284.8008, 284.8606, 284.9203, 284.9801,  
 285.0399, 285.0996, 285.1594, 285.2191, 285.2789, 285.3387, 285.3984,  
 285.4582, 285.5179, 285.5777, 285.6375, 285.6972, 285.757, 285.8167,  
 285.8765, 285.9362, 285.996, 286.0558, 286.1155, 286.1753, 286.235,

```
286.2948, 286.3546, 286.4143, 286.4741, 286.5339, 286.5936, 286.6534,  
286.7131, 286.7729, 286.8327, 286.8924, 286.9522, 287.012, 287.0717,  
287.1315, 287.1912, 287.251, 287.3108, 287.3705, 287.4303, 287.4901,  
287.5498, 287.6096, 287.6693, 287.7291, 287.7888, 287.8486, 287.9084,  
287.9681, 288.0279, 288.0876, 288.1474, 288.2072, 288.2669, 288.3267,  
288.3864, 288.4462, 288.506, 288.5657, 288.6255, 288.6853, 288.745,  
288.8048, 288.8645, 288.9243, 288.9841, 289.0438, 289.1036, 289.1634,  
289.2231, 289.2829, 289.3426, 289.4024, 289.4622, 289.5219, 289.5817,  
289.6414, 289.7012, 289.761, 289.8207, 289.8805, 289.9402, 290 ;
```

```
}
```

# Controlled Vocabulary (CMIP6)

## CMIP7 Controlled Vocabulary (CV) in development.

Work is currently ongoing to develop and document CMIP7 CVs. To see progress, see the following links

- [CMIP7 Guidance Pages \(Overview guidance pages for the CMIP7 project\)](https://wcrp-cmip.github.io/cmip7-guidance/)  
(<https://wcrp-cmip.github.io/cmip7-guidance/>)
- [WCRP Universe \(master collection of cross-project MIP relevant content\)](https://github.com/WCRP-CMIP/WCRP-universe)  
(<https://github.com/WCRP-CMIP/WCRP-universe>)
- [CMIP7-CVs \(Controlled Vocabularies for CMIP7\)](https://github.com/WCRP-CMIP/CMIP7-CVs) (<https://github.com/WCRP-CMIP/CMIP7-CVs>)
- [Variable Registry \(Registry of all MIP-relevant variables, for use across MIP projects\)](https://github.com/WCRP-CMIP/Variable-Registry)  
(<https://github.com/WCRP-CMIP/Variable-Registry>)
- [CMIP7 Essential Model Documentation](https://github.com/WCRP-CMIP/Essential-Model-Documentation)  
(<https://github.com/WCRP-CMIP/Essential-Model-Documentation>)

## CMIP6 Controlled Vocabulary (CV) minimum requirements.

While the CMIP6 project is now complete, the templates below are preserved and provide guidance which will look very similar to the CMIP7 CVs once they are finalized.

- CMOR 3 requires a new Controlled Vocabulary file which must contain 5 mandatory keys for CMIP6.
  - institutions\_id: A dictionary of registered institution IDs with a description.
  - source\_id: A dictionary of registered source IDs (model) with a specific description.
  - experiment\_id: A dictionary of experiment IDs (CMIP6) pointing to a dictionary of specific metadata.
  - grid\_label: An array or dictionary of grid labels (gr, gn, ...).
  - nominal\_resolution: An array or dictionary of grid resolutions ("0.5 km", "1 km", "10 km", ...).

**Click to expand example JSON file**

```
{
  "CV": {
    "institution_id": { "BNU": "GCESS, BNU, Beijing, China" },
    "source_id": { "CESM1-CAM5": "CESM1 (CAM5): model version ca. 2009" },
    "experiment_id": { "piControl": { } },
    "grid_label": { "gn": "data reported on a model's native grid" },
    "nominal_resolution": [ "0.5 km" ]
  }
}
```

### To register, activities, sources or institutions

- See guidance pages above, both for CMIP7 and CMIP6

### CMIP6 Controlled Vocabularies

The [CMIP6 Controlled Vocabularies \(CVs\)](https://github.com/WCRP-CMIP/CMIP6_CVs) ([https://github.com/WCRP-CMIP/CMIP6\\_CVs](https://github.com/WCRP-CMIP/CMIP6_CVs)) are a collection of registered values, either defined by the project, or registered by contributors to define their data contributions.

Some examples of project defined content are CMIP6\_DRS (Data Reference Syntax) ([https://github.com/WCRP-CMIP/CMIP6\\_CVs/blob/main/CMIP6\\_DRS.json](https://github.com/WCRP-CMIP/CMIP6_CVs/blob/main/CMIP6_DRS.json)), CMIP6\_activity\_id (CMIP6 registered MIPs) ([https://github.com/WCRP-CMIP/CMIP6\\_CVs/blob/main/CMIP6\\_activity\\_id.json](https://github.com/WCRP-CMIP/CMIP6_CVs/blob/main/CMIP6_activity_id.json)), CMIP6\_experiment\_id (CMIP6 experiments sponsored by a MIP) ([https://github.com/WCRP-CMIP/CMIP6\\_CVs/blob/main/CMIP6\\_experiment\\_id.json](https://github.com/WCRP-CMIP/CMIP6_CVs/blob/main/CMIP6_experiment_id.json)), etc.

Examples of contributor defined content are CMIP6\_institution\_id ([https://github.com/WCRP-CMIP/CMIP6\\_CVs/blob/main/CMIP6\\_institution\\_id.json](https://github.com/WCRP-CMIP/CMIP6_CVs/blob/main/CMIP6_institution_id.json)), CMIP6\_source\_id ([https://github.com/WCRP-CMIP/CMIP6\\_CVs/blob/main/CMIP6\\_source\\_id.json](https://github.com/WCRP-CMIP/CMIP6_CVs/blob/main/CMIP6_source_id.json))

Below are some expanded examples of registered content.

### CMIP6 required global attributes

- [CMIP6\\_CV.json:required\\_global\\_attributes](#)  
([https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6\\_CV.json#L3-L34](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L3-L34))

**Click to expand example JSON section**

```
"required_global_attributes": [  
  "Conventions",  
  "activity_id",  
  "creation_date",  
  "data_specs_version",  
  "experiment",  
  "experiment_id",  
  "forcing_index",  
  "frequency",  
  "further_info_url",  
  "grid",  
  "grid_label",  
  "initialization_index",  
  "institution",  
  "institution_id",  
  "license",  
  "mip_era",  
  "nominal_resolution",  
  "physics_index",  
  "product",  
  "realization_index",  
  "realm",  
  "source",  
  "source_id",  
  "source_type",  
  "sub_experiment",  
  "sub_experiment_id",  
  "table_id",  
  "tracking_id",  
  "variable_id",  
  "variant_label"  
],
```

### CV attribute format

- CMOR validates required attributes using list of values or regular expression(REGEX)

**Click to expand example JSON section**

```
"required_parent_attributes": [
  "parent_experiment_id"
],

"variant_label": [ "r[[:digit:]]\\{1,\\}i[[:digit:]]\\{1,\\}p[[:digit:]]\\{1,\\}f[[:digit:]]\\{1,\\}$" ],

"product": [ "model-output" ] ,

"mip_era": [ "CMIP6" ],

"further_info_url": [ "https://furtherinfo.es-doc.org/.*" ],
```

- CMOR can also validate required attributes using JSON objects containing key-value pairs where the “key” is a value option for the attribute and the “value” is a description of the value

**Click to expand example JSON section**

```

"sub_experiment_id":{
  "none":"none",
  "s1910":"initialized near end of year 1910",
  "s1920":"initialized near end of year 1920",
  "s1950":"initialized near end of year 1950"
}
"realm":{
  "aerosol":"Aerosol",
  "atmos":"Atmosphere",
  "atmosChem":"Atmospheric Chemistry",
  "land":"Land Surface",
  "landIce":"Land Ice",
  "ocean":"Ocean",
  "ocnBgchem":"Ocean Biogeochemistry",
  "seaIce":"Sea Ice"
},
"frequency":{
  "1hr":"sampled hourly",
  "1hrCM":"monthly-mean diurnal cycle resolving each day into 1-hour means",
  "1hrPt":"sampled hourly, at specified time point within an hour",
  "3hr":"3 hourly mean samples",
  "3hrPt":"sampled 3 hourly, at specified time point within the time period",
  "6hr":"6 hourly mean samples",
  "6hrPt":"sampled 6 hourly, at specified time point within the time period",
  "day":"daily mean samples",
  "dec":"decadal mean samples",
  "fx":"fixed (time invariant) field",
  "mon":"monthly mean samples",
  "monC":"monthly climatology computed from monthly mean samples",
  "monPt":"sampled monthly, at specified time point within the time period",
  "subhrPt":"sampled sub-hourly, at specified time point within an hour",
  "yr":"annual mean samples",
  "yrPt":"sampled yearly, at specified time point within the time period"
},

```

### Registered activities

- [CMIP6\\_CV.json:activity\\_id](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L48-L73)  
([https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6\\_CV.json#L48-L73](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L48-L73))

**Click to expand example JSON section**

```
"activity_id":[
  "AerChemMIP",
  "C4MIP",
  "CFMIP",
  "CMIP",
  "CORDEX",
  "DAMIP",
  "DCPP",
  "DynVarMIP",
  "FAFMIP",
  "GMMIP",
  "GeoMIP",
  "HighResMIP",
  "ISMIP6",
  "LS3MIP",
  "LUMIP",
  "OMIP",
  "PMIP",
  "RFMIP",
  "SIMIP",
  "ScenarioMIP",
  "VIACSAB",
  "VolMIP"
],
```

### Registered sources

- [CMIP6\\_CV.json:source\\_id](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L125-L3465)  
([https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6\\_CV.json#L125-L3465](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L125-L3465))

**Click to expand example JSON section**

```

"source_id": {
  "ACCESS-CM2":{
    "activity_participation":[
      "CMIP",
      "DAMIP",
      "FAFMIP",
      "OMIP",
      "RFMIP",
      "SIMIP",
      "ScenarioMIP"
    ],
    "cohort":[
      "Published"
    ],
    "institution_id":[
      "CSIRO-ARCCSS"
    ],
    "license_info":{
      "exceptions_contact":"@csiro.au <- access_csiro",
      "history":"2019-11-08: initially published under CC BY-SA 4.0; 202
2-06-10: relaxed to CC BY 4.0",
      "id":"CC BY 4.0",
      "license":"Creative Commons Attribution 4.0 International (CC BY
4.0; https://creativecommons.org/licenses/by/4.0/)",
      "source_specific_info":"",
      "url":"https://creativecommons.org/licenses/by/4.0/"
    },
    "source_id":"ACCESS-CM2",
    "source":"ACCESS-CM2 (2019): \naerosol: UKCA-GLOMAP-mode\natmos: MetUM-H
adGEM3-GA7.1 (N96; 192 x 144 longitude/latitude; 85 levels; top level 85 km)\nat
mosChem: none\nland: CABLE2.5\nlandIce: none\nocean: ACCESS-OM2 (GFDL-MOM5, trip
olar primarily 1deg; 360 x 300 longitude/latitude; 50 levels; top grid cell 0-10
m)\nocnBgchem: none\nseaIce: CICE5.1.2 (same grid as ocean)"
  },
  ...
},

```

### Registered institutions

- [CMIP6\\_CV.json:institution\\_id](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L74-L124)  
([https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6\\_CV.json#L74-L124](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L74-L124))

**Click to expand example JSON section**

```
"institution_id": {
  "NSF-DOE-NCAR": "NSF/DOE NCAR (National Center for Atmospheric Research) Boul
der, CO, USA"
  ...
},
```

### Valid grids

- [CMIP6\\_CV.json:grid\\_label](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L3496-L3542)  
([https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6\\_CV.json#L3496-L3542](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L3496-L3542))

### Click to expand example JSON section

```
"grid_label": {
  "gm": "global mean data",
  "gn": "data reported on a model's native grid",
  "gna": "data reported on a native grid in the region of Antarctica",
  "gng": "data reported on a native grid in the region of Greenland",
  "gnz": "zonal mean data reported on a model's native latitude grid",
  "gr": "regridded data reported on the data provider's preferred target grid"
},
```

### Grid resolutions

- [CMIP6\\_CV.json:nominal\\_resolution](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L3543-L3559)  
([https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6\\_CV.json#L3543-L3559](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L3543-L3559))

### Click to expand example JSON section

```
"nominal_resolution":[
  "0.5 km",
  "1 km",
  "10 km",
  "100 km",
  "1000 km",
  "10000 km",
  "1x1 degree",
  "2.5 km",
  "25 km",
  "250 km",
  "2500 km",
  "5 km",
  "50 km",
  "500 km",
  "5000 km"
],
```

### Registered experiments

- [CMIP6\\_CV.json:experiment\\_id](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L3702-L11535)  
([https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6\\_CV.json#L3702-L11535](https://github.com/PCMDI/cmip6-cmor-tables/blob/087fe45d21c082e28723e0f930e4266abe91b853/Tables/CMIP6_CV.json#L3702-L11535))

**Click to expand example JSON section**

```
"experiment_id": {  
  "piControl": {  
    "activity_id": [  
      "CMIP"  
    ],  
    "additional_allowed_model_components": [  
      "AER",  
      "CHEM",  
      "BGC"  
    ],  
    "experiment": "pre-industrial control",  
    "experiment_id": "piControl",  
    "parent_activity_id": [  
      "CMIP"  
    ],  
    "parent_experiment_id": [  
      "piControl-spinup"  
    ],  
    "required_model_components": [  
      "AOGCM"  
    ],  
    "sub_experiment_id": [  
      "none"  
    ]  
  },  
}
```

# CMIP6 Table Excerpt

## WCRP Data Request links

The names of the MIP tables are constructed using the tokens described below, and a frequency token. The frequency is generally taken from the CIP6 frequency vocabulary, except for the “monClim” frequency, which is abbreviated to “clim”.

- MIP Tables in the CMIP6 Data Request

[about mip table \(https://earthsystemcog.org/projects/wip/mip\\_table\\_about\)](https://earthsystemcog.org/projects/wip/mip_table_about)

- **WCRP Table List**

Here is the WCRP [mip tables list \(http://clipc-services.ceda.ac.uk/dreq/index/miptable.html\)](http://clipc-services.ceda.ac.uk/dreq/index/miptable.html)

- **Cmor Tables**

Corresponding CMOR3 CMIP6 tables to link above can be found [here \(https://github.com/PCMDI/cmip6-cmor-tables/tree/master/Tables\)](https://github.com/PCMDI/cmip6-cmor-tables/tree/master/Tables).

## Header

```
"Header": {
  "mip_era": "CMIP6",
  "approx_interval": "30.00000",
  "realm": "atmos",
  "product": "output",
  "cmor_version": "3.3",
  "Conventions": "CF-1.6 CMIP-6.0",
  "table_id": "Table Amon",
  "data_specs_version": "3.0",
  "generic_levels": "alevel alevhalf",
  "missing_value": "1e20",
  "table_date": "01 April 2016"
},
```

axis\_entry

```

"axis_entry": {
  "forecast": {
    "stored_direction": "increasing",
    "must_have_bounds": "no",
    "long_name": "ensemble time axis",
    "standard_name": "time",
    "out_name": "forecast",
    "type": "double",
    "units": "days since 1900-01-01",
    "value": "0.0",
    "axis": "T"
  },
  "plev17": {
    "requested": [
      "100000.",
      "92500.",
      "85000.",
      "70000.",
      "60000.",
      "50000.",
      "40000.",
      "30000.",
      "25000.",
      "20000.",
      "15000.",
      "10000.",
      "7000.",
      "5000.",
      "3000.",
      "2000.",
      "1000."
    ],
    "stored_direction": "decreasing",
    "z_factors": "",
    "positive": "down",
    "must_have_bounds": "no",
    "valid_min": "",
    "requested_bounds": "",
    "z_bounds_factors": "",
    "bounds_values": "",
    "long_name": "pressure",
    "standard_name": "air_pressure",
    "value": "",
    "out_name": "plev",
    "type": "double",
    "units": "Pa",
    "formula": "",
    "climatology": "",
    "tolerance": "0.001",
    "valid_max": "",

```

```

    "axis": "Z"
  },
  "height2m": {
    "requested": "",
    "stored_direction": "increasing",
    "z_factors": "",
    "positive": "up",
    "must_have_bounds": "no",
    "valid_min": "1.0",
    "requested_bounds": "",
    "z_bounds_factors": "",
    "bounds_values": "",
    "long_name": "height",
    "standard_name": "height",
    "value": "2.0",
    "out_name": "height",
    "type": "double",
    "units": "m",
    "formula": "",
    "climatology": "",
    "tolerance": "",
    "valid_max": "10.0",
    "axis": "Z"
  },
  "latitude": {
    "requested": "",
    "stored_direction": "increasing",
    "z_factors": "",
    "positive": "",
    "must_have_bounds": "yes",
    "valid_min": "-90.0",
    "requested_bounds": "",
    "z_bounds_factors": "",
    "bounds_values": "",
    "long_name": "latitude",
    "standard_name": "latitude",
    "value": "",
    "out_name": "lat",
    "type": "double",
    "units": "degrees_north",
    "formula": "",
    "climatology": "",
    "tolerance": "",
    "valid_max": "90.0",
    "axis": "Y"
  },
  "longitude": {
    "requested": "",
    "stored_direction": "increasing",
    "z_factors": "",

```

```

    "positive": "",
    "must_have_bounds": "yes",
    "valid_min": "0.0",
    "requested_bounds": "",
    "z_bounds_factors": "",
    "bounds_values": "",
    "long_name": "longitude",
    "standard_name": "longitude",
    "value": "",
    "out_name": "lon",
    "type": "double",
    "units": "degrees_east",
    "formula": "",
    "climatology": "",
    "tolerance": "",
    "valid_max": "360.0",
    "axis": "X"
  },
  "time": {
    "requested": "",
    "stored_direction": "increasing",
    "z_factors": "",
    "positive": "",
    "must_have_bounds": "yes",
    "valid_min": "",
    "requested_bounds": "",
    "z_bounds_factors": "",
    "bounds_values": "",
    "long_name": "time",
    "standard_name": "time",
    "value": "",
    "out_name": "time",
    "type": "double",
    "units": "days since ?",
    "formula": "",
    "climatology": "",
    "tolerance": "",
    "valid_max": "",
    "axis": "T"
  }
},

```

variable\_entry

```

"variable_entry": {
  "rsutcs": {
    "comment": "",
    "dimensions": "longitude latitude time",
    "frequency": "mon",
    "positive": "up",
    "valid_min": "0",
    "long_name": "TOA Outgoing Clear-Sky Shortwave Radiation",
    "standard_name": "toa_outgoing_shortwave_flux_assuming_clear_sky",
    "modeling_realm": "atmos",
    "cell_measures": "time: mean",
    "cell_methods": "area: areacella",
    "ok_min_mean_abs": "54.7",
    "units": "W m-2",
    "out_name": "rsutcs",
    "type": "real",
    "valid_max": "444",
    "ok_max_mean_abs": "73.36"
  },
  "tas": {
    "comment": "near-surface (usually, 2 meter) air temperature",
    "dimensions": "longitude latitude time height2m",
    "frequency": "mon",
    "positive": "",
    "valid_min": "180.6",
    "long_name": "Near-Surface Air Temperature",
    "standard_name": "air_temperature",
    "modeling_realm": "atmos",
    "cell_measures": "time: mean",
    "cell_methods": "area: areacella",
    "ok_min_mean_abs": "262.4",
    "units": "K",
    "out_name": "tas",
    "type": "real",
    "valid_max": "335.1",
    "ok_max_mean_abs": "293"
  },
  "tasforecast": {
    "comment": "near-surface (usually, 2 meter) air temperature",
    "dimensions": "longitude latitude time height2m forecast",
    "frequency": "mon",
    "positive": "",
    "valid_min": "180.6",
    "long_name": "Near-Surface Air Temperature",
    "standard_name": "air_temperature",
    "modeling_realm": "atmos",
    "cell_measures": "time: mean",
    "cell_methods": "area: areacella",
    "ok_min_mean_abs": "262.4",
    "units": "K",

```

```

      "out_name": "tas",
      "type": "real",
      "valid_max": "335.1",
      "ok_max_mean_abs": "293"
    },
    "rldscs": {
      "comment": "",
      "dimensions": "longitude latitude time",
      "frequency": "mon",
      "positive": "down",
      "valid_min": "33.55",
      "long_name": "Surface Downwelling Clear-Sky Longwave Radiation",
      "standard_name": "surface_downwelling_longwave_flux_in_air_assuming_clea
r_sky",
      "modeling_realm": "atmos",
      "cell_measures": "time: mean",
      "cell_methods": "area: areacella",
      "ok_min_mean_abs": "238.6",
      "units": "W m-2",
      "out_name": "rldscs",
      "type": "real",
      "valid_max": "543.6",
      "ok_max_mean_abs": "293.8"
    },
    "n2oglobal": {
      "comment": "",
      "dimensions": "time",
      "frequency": "mon",
      "positive": "",
      "valid_min": "",
      "long_name": "Global Mean Mole Fraction of N2O",
      "standard_name": "mole_fraction_of_nitrous_oxide_in_air",
      "modeling_realm": "atmos atmosChem",
      "cell_measures": "time: mean",
      "cell_methods": "",
      "ok_min_mean_abs": "",
      "units": "1e-09",
      "out_name": "n2oglobal",
      "type": "real",
      "valid_max": "",
      "ok_max_mean_abs": ""
    },
    "ts": {
      "comment": "'skin' temperature (i.e., SST for open ocean)",
      "dimensions": "longitude latitude time",
      "frequency": "mon",
      "positive": "",
      "valid_min": "176.8",
      "long_name": "Surface Temperature",
      "standard_name": "surface_temperature",

```

```

    "modeling_realm": "atmos",
    "cell_measures": "time: mean",
    "cell_methods": "area: areacella",
    "ok_min_mean_abs": "262.8",
    "units": "K",
    "out_name": "ts",
    "type": "real",
    "valid_max": "339.6",
    "ok_max_mean_abs": "293.3"
  },
  "clt": {
    "comment": "cloud area fraction",
    "dimensions": "longitude latitude time",
    "frequency": "mon",
    "positive": "",
    "valid_min": "-0.0001822",
    "long_name": "Total Cloud Fraction",
    "standard_name": "cloud_area_fraction_in_atmosphere_layer",
    "modeling_realm": "atmos",
    "cell_measures": "time: mean",
    "cell_methods": "area: areacella",
    "ok_min_mean_abs": "39.37",
    "units": "1.0",
    "out_name": "clt",
    "type": "real",
    "valid_max": "105",
    "ok_max_mean_abs": "84.98"
  },
  "tasmax": {
    "comment": "maximum near-surface (usually, 2 meter) air temperature (add
cell_method attribute 'time: max')",
    "dimensions": "longitude latitude time height2m",
    "frequency": "mon",
    "positive": "",
    "valid_min": "181.9",
    "long_name": "Daily Maximum Near-Surface Air Temperature",
    "standard_name": "air_temperature",
    "modeling_realm": "atmos",
    "cell_measures": "time: maximum within days time: mean over days",
    "cell_methods": "area: areacella",
    "ok_min_mean_abs": "264.9",
    "units": "K",
    "out_name": "tasmax",
    "type": "real",
    "valid_max": "341.9",
    "ok_max_mean_abs": "294"
  }
}

```

# CMIP6 Global Attributes

## CMIP6 Global Attributes

- *variant\_label*
- *activity\_id*
- *branch\_method*
- *Conventions*
- *creation\_date*
- *mip\_era*
- *data\_specs\_version*
- *experiment\_id*
- *experiment*
- *forcing\_index*
- *further\_info\_url*
- *frequency*
- *grid*
- *grid\_label*
- *nominal\_resolution*
- *initialization\_index*
- *institution*
- *institution\_id*
- *license*
- *physics\_index*
- *product*
- *realization\_index*
- *realm*
- *variant\_label*
- *source*
- *source\_id*
- *source\_type*

- *sub\_experiment*
- *sub\_experiment\_id*
- *table\_id*
- *tracking\_id*
- *variable\_id*

# User Input

## Overview

User input is used by CMOR to set the global attributes in netCDF files, and to set other parameters that control CMOR's behavior. They are passed to CMOR in a JSON file using the `cmor_dataset_json` (page 0).

```
import cmor

cmor.setup(
    inpath='Tables',
    netcdf_file_action=cmor.CMOR_REPLACE_4
)

cmor.dataset_json("Test/CMOR_input_example.json")
```

## Controlled Vocabulary Attributes

Attributes are entries used by CMOR to set global attributes in netCDF files. The values of these attributes must be valid according to the controlled vocabulary.

```
"source_id":          "ACCESS-CM2",
"experiment_id":      "1pctCO2",
"activity_id":        "AerChemMIP",
```

## CMOR parameters

CMOR parameters are entries used by CMOR for setting paths to table files, directory and file templates, and other settings.

### Controlled Vocabulary and Variable Table Paths

- **\_controlled\_vocabulary\_file**: Specify Controlled Vocabulary file name – default: CMIP6\_CV.json
- **\_AXIS\_ENTRY\_FILE**: Specify Coordinate table file(axes) – default: CMIP6\_coordinate.json
- **\_FORMULA\_VAR\_FILE**: Specify Formula terms table file – default: CMIP6\_formula\_terms.json

### String-Valued Index Attributes

- **\_use\_strings\_for\_indexes**: Used to allow string values rather than integers for the attributes

realization\_index, initialization\_index, physics\_index, and forcing\_index.

### CMIP-Specific Checks

- **\_cmip6\_option:** Enables the validation of attributes for CMIP6, which includes checks related to source and experiment IDs, grid resolution, parent attributes, and subexperiments.
- **\_cmip7\_option:** Enables the validation of attributes for CMIP7, which are similar to the CMIP6 checks but without the subexperiments. This will also allow for the use of string for index attributes just like `_use_strings_for_indexes`.

### Output Directory and Filename Templates

Templates are strings composed of attribute names within `<>` that are filled out by their corresponding attribute values of the current dataset used by CMOR.

- **output\_path\_template:** Template of the output directory for netCDF files. – default:  
`<mip_era><activity_id><institution_id><source_id><experiment_id><member_id><table><variable_id>`
- **output\_file\_template:** Template of the names of netCDF files. – default `<variable_id><table><source_id><experiment_id><member_id><grid_label>`

### Dataset Version

- **version:** Set this to name the `<version>` part of the output path template. If not set, then CMOR will use the current date as the version in the format of “vYYYYMMDD” (ex. “v20220718”).
  - Setting the `version` attribute will cause it to be added to the global attributes of the netCDF file.
  - To avoid adding the attribute, set an [internal attribute \(page 277\)](#) that can be used as a template value while not being a global attribute. For example, set the attribute `_dir_version` and replace `<version>` with `<dir_version>` in the output path template.
    - Do not use `_version` as an internal attribute as it is used by CMOR to store the version value derived from the current date.

```
"_dir_version": "output_v4",
"output_path_template": "<drs_specs><mip_era><activity_id><institution_id><source_id><experiment_id><variant_label><region><frequency><variable_id><branding_suffix><grid_label><dir_version>",
```

### Internal Attributes

Internal attributes are entries with keys that begin with a `_` character that will be added to a CMOR variable’s attribute list but will not be written to the netCDF file as global attributes. These can be used for setting values in directory or filename templates.

```
"_dev_directory":          "debug",
```

### Comments

Comments are entries with keys that begin with a # character. These will be ignored by CMOR.

```
"#note":                  "CMIP6 valid experiment_ids are found in CMIP6_C  
V.json",
```

### CMIP6 User Input Example

Below is an example of a user input file used for CMIP6. More details on CMIP6 global attributes can be found in [CMIP6\\_global\\_attributes\\_filenames\\_CVs.doc](#)

([https://docs.google.com/document/d/1h0r8RZr\\_f3-8egBMMh7aqLwy3snpD6\\_MrDz1q8n5XUk](https://docs.google.com/document/d/1h0r8RZr_f3-8egBMMh7aqLwy3snpD6_MrDz1q8n5XUk))

```

{
  "#note":          "explanation of what source_type is goes here",
  "source_type":    "AOGCM ISM AER",

  "#note":          "CMIP6 valid experiment_ids are found in CMIP6_C
V.json",
  "experiment_id":   "piControl-withism",
  "activity_id":     "ISMIP6",
  "sub_experiment_id": "none",

  "realization_index": "3",
  "initialization_index": "1",
  "physics_index":     "1",
  "forcing_index":     "1",

  "#note":          "Text stored in attribute variant_info (recommende
d, not required description of run variant)",
  "run_variant":     "3rd realization",

  "parent_experiment_id": "no parent",
  "parent_activity_id":  "no parent",
  "parent_source_id":    "PCMDI-test-1-0",
  "parent_variant_label": "r3i1p1f1",

  "parent_time_units":  "days since 1850-01-01",
  "branch_method":      "standard",
  "branch_time_in_child": 59400.0,
  "branch_time_in_parent": 59400.0,

  "#note":          "institution_id must be registered at https://gith
ub.com/WCRP-CMIP/CMIP6_CVs/issues/new ",
  "institution_id":    "PCMDI",

  "#note":          "source_id (model name) must be registered at http
s://github.com/WCRP-CMIP/CMIP6_CVs/issues/new ",
  "source_id":         "PCMDI-test-1-0",

  "calendar":         "360_day",

  "grid":             "native atmosphere regular grid (3x4 latxlon)",
  "grid_label":        "gn",
  "nominal_resolution": "10000 km",

  "license":          "CMIP6 model data produced by Lawrence Livermore
PCMDI is licensed under a Creative Commons Attribution 4.0 International License
(https://creativecommons.org/licenses/by/4.0/). Consult https://pcmdi.llnl.gov/C
MIP6/TermsOfUse for terms of use governing CMIP6 output, including citation requ
irements and proper acknowledgment. Further information about this data, includi
ng some limitations, can be found via the further_info_url (recorded as a global
attribute in this file) and at https://pcmdi.llnl.gov/. The data producers and d

```

ata providers make no warranty, either express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose. All liabilities arising from the supply of the information (including any liability arising in negligence) are excluded to the fullest extent permitted by law.",

```
"#output":          "Root directory for output (can be either a relative or full path)",
  "outpath":         "CMIP6",
```

```
"#note":            " **** The following descriptors are optional and may be set to an empty string ",
```

```
"contact ":         "Python Coder (coder@a.b.c.com)",
"history":          "Output from archivcl_A1.nce/giccm_03_std_2xC02_2256.",
"comment":          "",
"references":       "Model described by Koder and Tolkien (J. Geophys. Res., 2001, 576-591). Also see http://www.GICC.su/giccm/doc/index.html. The ss p245 simulation is described in Dorkey et al. '(Clim. Dyn., 2003, 323-357.)'",
```

```
"#note":            " **** The following will be obtained from the CV and do not need to be defined here",
```

```
"sub_experiment":   "none",
"institution":      "",
"source":           "PCMDI-test 1.0 (1989)",
```

```
"#note":            " **** The following are set correctly for CMIP6 and should not normally need editing",
```

```
"_controlled_vocabulary_file": "CMIP6_CV.json",
"_AXIS_ENTRY_FILE":           "CMIP6_coordinate.json",
"_FORMULA_VAR_FILE":          "CMIP6_formula_terms.json",
"_cmip6_option":              "CMIP6",
```

```
"mip_era":           "CMIP6",
"parent_mip_era":    "CMIP6",
```

```
"tracking_prefix":    "hdl:21.14100",
"_history_template":  "%s ;rewrote data to be consistent with <activity_id> for variable <variable_id> found in table <table_id>.",
```

```
"#output_path_template": "Template for output path directory using tables keys or global attributes, these should follow the relevant data reference syntax",
```

```
"output_path_template": "<mip_era><activity_id><institution_id><source_id><experiment_id><member_id><table><variable_id><grid_label><version>",
"output_file_template": "<variable_id><table><source_id><experiment_id><member_id><grid_label>"
}
```

# Appendix A

## Critical Errors

The following errors are considered as CRITICAL and will cause a CMOR code to stop.

1. Calling a CMOR function before running cmor\_setup
2. NetCDF version is neither 3.6.3 or 4.1 or greater
3. Udunits could not parse units
4. Incompatible units
5. Udunits could not create a converter
6. Logfile could not be open for writing
7. Output directory does not exist
8. Output directory is not a directory
9. User does not have read/write privileges on the output directory
10. Wrong value for error\_mode
11. wrong value for netCDF mode
12. error reading udunits system
13. NetCDF could not set variable attribute
14. Dataset does not have one of the required attributes (required attributes can be defined in the MIP table)
15. Required global attribute is missing
16. If CMIP5 project: source attributes does not start with model\_id attribute.
17. Forcing dataset attribute is not valid
18. Leap\_year defined with invalid leap\_month
19. Invalid leap month (<1 or >12)
20. Leap month defined but no leap year
21. Negative realization number
22. Zfactor variable not defined when needed
23. Zfactor defined w/o values and NOT time dependent.
24. Variable has axis defined with formula terms depending on axis that are not part of the variable
25. NetCDF error when creating zfactor variable

26. NetCDF Error defining compression parameters
27. Calling `cmor_write` with an invalid variable id
28. Could not create path structure
29. “variable id” contains a “\_” or a “-” this means bad MIP table.
30. “file\_suffix” contains a “\_”
31. Could not rename the file you’re trying to append to.
32. Trying to write an “Associated variable” before the variable itself
33. Output file exists and you’re not in append/replace mode
34. NetCDF Error opening file for appending
35. NetCDF could not find time dimension in a file onto which you want to append
36. NetCDF could not figure out the length time dimension in a file onto which you want to append
37. NetCDF could not find your variable while appending to a file
38. NetCDF could not find time dimension in the variable onto which you’re trying to append
39. NetCDF could not find time bounds in the variable onto which you’re trying to append
40. NetCDF mode got corrupted.
41. NetCDF error creating file
42. NetCDF error putting file in definition mode
43. NetCDF error writing file global attribute
44. NetCDF error creating dimension in file
45. NetCDF error creating variable
46. NetCDF error writing variable attribute
47. NetCDF error setting chunking parameters
48. NetCDF error leaving definition mode
49. Hybrid coordinate, could not find “a” coefficient
50. Hybrid coordinate, could not find “b” coefficient
51. Hybrid coordinate, could not find “a\_bnds” coefficient
52. Hybrid coordinate, could not find “b\_bnds” coefficient
53. Hybrid coordinate, could not find “p0” coefficient
54. Hybrid coordinate, could not find “ap” coefficient
55. Hybrid coordinate, could not find “ap\_bnds” coefficient
56. Hybrid coordinate, could not find “sigma” coefficient
57. Hybrid coordinate, could not find “sigma\_bnds” coefficient

58. NetCDF writing error
59. NetCDF error closing file
60. Could not rename temporary file to its final name.
61. Cdms could not convert time values for calendar.
62. Variable does not have all required attributes (cmor\_variable)
63. Reference variable is defined with “positive”, user did not pass it to cmor\_variable
64. Could not allocate memory for zfactor elements
65. Udunits error freeing units
66. Udunits error freeing converter
67. Could not allocate memory for zfactor\_bounds
68. Calling cmor\_variable before reading in a MIP table
69. Too many variable defined (see appendix on CMOR limits)
70. Could not find variable in MIP table
71. Wrong parameter “positive” passed
72. No “positive” parameter passed to cmor\_variable and it is required for this variable
73. Variable defined with too many (not enough) dimensions
74. Variable defined with axis that should not be on this variable
75. Variable defined within existing axis (wrong axis\_id)
76. Defining variable with axes defined in a MIP table that is not the current one.
77. Defining a variable with too many axes (see annex on CMOR limits)
78. Defining variable with axes ids that are not valid.
79. Defining variable with grid id that is not valid.
80. Defining a variable with dimensions that are not part of the MIP table (except for var named “latitude” and “longitude”, since they could have grid axes defined in another MIP table)
81. Trying to retrieve length of time for a variable defined w/o time length
82. Trying to retrieve variable shape into an array of wrong rank (Fortran only really)
83. Calling cmor\_write with time values for a timeless variable
84. Cannot allocate memory for temporary array to write
85. Invalid absolute mean for data written (lower or greater by one order of magintudethan what the MIP table allows)
86. Calling cmor\_write with time values when they have already been defined with cmor\_axis when creating time axis
87. Cannot allocate memory to store time values

88. Cannot allocate memory to store time bounds values
89. Time values are not monotonic
90. Calling `cmor_write` w/o time values when no values were defined via `cmor_axis` when creating time axis
91. Time values already written in file
92. Time axis units do not contain “since” word (`cmor_axis`)
93. Invalid data type for time values (ok are ‘f’, ‘l’, ‘i’, ‘d’)
94. Time values are not within time bounds
95. Non monotonic time bounds
96. Longitude axis spread over 360 degrees.
97. Overlapping bound values (except for climatological data)
98. bounds and axis values are not stored in the same order
99. requested value for axis not present
100. approximate time axis interval much greater (>20%) than the one defined in your MIP table
101. calling `cmor_axis` before loading a MIP table
102. too many axes defined (see appendix on CMOR limits)
103. could not find reference axis name in current MIP table
104. output axis needs to be `standard_hybrid_sigma` and input axis is not one of :  
“standard\_hybrid\_sigma”, “alternate\_hybrid\_sigma”, “standard\_sigma”
105. MIP table requires to convert axis to unknown type
106. requested “region” not present on axis
107. axis (with bounds) values are in invalid type (valid are: ‘f’, ‘d’, ‘l’, ‘i’)
108. requested values already checked but stored internally, could be bad user cleanup
109. MIP table defined for version of CMOR greater than the library you’re using
110. too many experiments defined in MIP table (see appendix on CMOR limits)
111. `cmor_set_table` used with invalid `table_id`
112. MIP table has too many axes defined in it (see appendix on CMOR limits)
113. MIP table has too many variables defined in it (see appendix on CMOR limits)
114. MIP table has too many mappings defined in it (see appendix on CMOR limits)
115. MIP table defines the same mapping twice
116. grid mapping has too many parameters (see appendix on CMOR limits)
117. grid has different number of axes than what `grid_mapping` prescribes.
118. Could not find all the axes required by `grid_mapping`

- 119. Call to `cmor_grid` with axis that are not created yet via `cmor_axis`
- 120. Too many grids defined (see appendix on `cmor_limits`)
- 121. Call to `cmor_grid` w/o latitude array
- 122. Call to `cmor_grid` w/o longitude array

## Appendix B

### Limits in cmor

The following are defined in cmor.h

```
#define CMOR_MAX_STRING 1024
#define CMOR_DEF_ATT_STR_LEN 256
#define CMOR_MAX_ELEMENTS 500
#define CMOR_MAX_AXES CMOR_MAX_ELEMENTS*3
#define CMOR_MAX_VARIABLES CMOR_MAX_ELEMENTS
#define CMOR_MAX_GRIDS 100
#define CMOR_MAX_DIMENSIONS 7
#define CMOR_MAX_ATTRIBUTES 100
#define CMOR_MAX_ERRORS 10
#define CMOR_MAX_TABLES 10
#define CMOR_MAX_GRID_ATTRIBUTES 25
```

# Contact us

## CMOR3 issues

<https://github.com/PCMDI/cmor/issues> (<https://github.com/PCMDI/cmor/issues>)

## CMIP6 table issues

<https://github.com/PCMDI/cmip6-cmor-tables/issues> (<https://github.com/PCMDI/cmip6-cmor-tables/issues>)

<http://dreq01.vanillaforums.com/categories/cmip6-issues>  
(<http://dreq01.vanillaforums.com/categories/cmip6-issues>)

## CMOR3 documentations issues

[https://github.com/PCMDI/cmor3\\_documentation/issues](https://github.com/PCMDI/cmor3_documentation/issues)  
([https://github.com/PCMDI/cmor3\\_documentation/issues](https://github.com/PCMDI/cmor3_documentation/issues))

## Mailing list

[cmor@lists.llnl.gov](mailto:cmor@lists.llnl.gov)

1. To subscribe to the CMOR mailing list,
    - send an email writing `subscribe cmor` in the text of your message to [LISTSERV@listserv.llnl.gov](mailto:LISTSERV@listserv.llnl.gov)
  2. To learn how to use the LISTSERV email application, go to <https://www.lsoft.com/resources/manuals.asp> (<https://www.lsoft.com/resources/manuals.asp>)
  3. The following email addresses are used for the specified purposes:
    - To send an email to the list: [CMOR@LISTS.LLNL.GOV](mailto:CMOR@LISTS.LLNL.GOV) ([page 0](#))
    - To contact the list owner: [CMOR-request@LISTSERV.LLNL.GOV](mailto:CMOR-request@LISTSERV.LLNL.GOV)
    - To send commands to the LISTSERV server: [LISTSERV@LISTSERV.LLNL.GOV](mailto:LISTSERV@LISTSERV.LLNL.GOV)
    - To unsubscribe from the list: [CMOR-signoff-request@LISTSERV.LLNL.GOV](mailto:CMOR-signoff-request@LISTSERV.LLNL.GOV)
  4. INTERACTING WITH LISTSERV BY EMAIL \*
- You may leave the list at any time by sending a `SIGNOFF CMOR` command (include `SIGNOFF CMOR` in the email body to: [LISTSERV@LISTSERV.LLNL.GOV](mailto:LISTSERV@LISTSERV.LLNL.GOV))
  - Or by sending a blank email to: [CMOR-signoff-request@LISTSERV.LLNL.GOV](mailto:CMOR-signoff-request@LISTSERV.LLNL.GOV)
  - You can also tell LISTSERV how you want it to confirm the receipt of messages that you send to the list. To send yourself a copy of your own messages, send a `SET CMOR REPRO` command.

- Alternatively, to have `LISTSERV` send you a short acknowledgement instead of the entire message, send a `SET CMOR ACK NOREPRO` command. Finally, you can turn off acknowledgements completely with the `SET CMOR NOACK NOREPRO` command.
- This list is available in digest form. If you wish to receive the digested version of the postings, then issue a `SET CMOR DIGEST` command.
- Please note that it is presently possible for other people to determine that you are signed up to the list using the `REVIEW` command, which returns the email address and name of all the subscribers (include `Review CMOR` in the email body) to:  
[LISTSERV@LISTSERV.LLNL.GOV](mailto:LISTSERV@LISTSERV.LLNL.GOV)
- If you do not want your name to be visible, then just issue a `SET CMOR CONCEAL` command.
- Following instructions from the list owner, your subscription options have been set to `"REPRO IETFHDR "` rather than the usual `LISTSERV` defaults. For more information about subscription options, send a `QUERY CMOR` command to  
[LISTSERV@LISTSERV.LLNL.GOV](mailto:LISTSERV@LISTSERV.LLNL.GOV).