

| | | | | |
|--|---------------------------------------|-----------------|-------------------------------------|----------------------|
| | | | | |
| | Screws and nuts: | | | |
| | diameter , length | quantity | Description | Link |
| | M2.5 x 8mm | 4 | | |
| | M2 x 4mm | 8 | | |
| | M3 x 5mm cheese head | 5 | | |
| | M2 x 10 mm | 1 | | |
| | M3 x 8mm cheese head | 7 | | |
| | M4 x 10mm | 4 | | |
| | M3 x 12 mm | 4 | | |
| | M3 x 10 mm | 4 | | |
| | M2 x 10 mm | 3 | | |
| | Brass inserts: | | | |
| | Length 3mm, M3 (OD 4.5mm) | 1 | | Link |
| | Length 5mm, M3 (OD 4.5mm) | 15 | | Link |
| | Motors: | | | |
| | Type | quantity | Description | Link |
| | GBM5208-75 | 1 | Link | Link |
| | Mechanical: | | | |
| | Type | quantity | Description | Link |
| | Shaft coupler | 1 | 8 mm hole shaft, M4 screw holes | Link |
| | MGN7C slider | 2 | | Link |
| | Linear guide | 1 | 100mm | Link |
| | Magnet | 1 | 6 mm diameter, 2.5 mm tickness | |
| | Electronics: | | | |
| | Type | quantity | Description | Link |
| | Spectral micro BLDC driver | 1 | source-robotics.com | Link |
| | XH 2.54MM, 300MM, 2P, Double end same | 1 | Cable for 24V | Link |
| | ZH 1.5MM, 300MM, 2P, Double end same | 1 | Cable for CAN bus | Link |
| | Male 4pin connector | 1 | Looks like this | Link |
| | Cable: | | | |
| | 26AWG 0.15mm2 4wire twisted pair | 0.4 meter | Usually 35 cm cable is enough | Link |
| | 4 pin male wire connector | 1 | Looks like this | Link |
| | 4 pin female wire connector | 1 | Looks like this | Link |
| | | | | |