Screws and nuts:			
diameter , length	quantity	Description	Link
M2.5 x 8mm	4		
M2 x 4mm	8		
M3 x 5mm cheese head	5		
M2 x 10 mm	1		
M3 x 8mm cheese head	7		
M4 x 10mm	4		
M3 x 12 mm	4		
M3 x 10 mm	4		
M2 x 10 mm	3		
Brass inserts:			
Length 3mm, M3 (OD 4.5mm)	1		<u>Link</u>
Length 5mm, M3 (OD 4.5mm)	15		<u>Link</u>
Motors:			
Туре	quantity	Description	Link
GBM5208-75	1	<u>Link</u>	<u>Link</u>
Mechanical:			
Туре	quantity	Description	Link
Shaft coupler	1	8 mm hole shaft,	<u>Link</u>
MGN7C slider	2		<u>Link</u>
Linear guide	1	100mm	<u>Link</u>
Magnet	1	6 mm diameter, 2	2.5 mm tickne
Electronics:			
Туре	quantity	Description	Link
Spectral micro BLDC driver	1	source-robotics.c	<u>Link</u>
XH 2.54MM, 300MM, 2P, Double end same	1	Cable for 24V	<u>Link</u>
ZH 1.5MM, 300MM, 2P, Double end same	1	Cable for CAN b	<u>Link</u>
Male 4pin connector	1	Looks like this	<u>Link</u>
Cable:			
26AWG 0.15mm2 4wire twisted pair	0.4 meter	Usually 35 cm ca	<u>Link</u>
4 pin male wire connector	1	Looks like this	<u>Link</u>
4 pin female wire connector	1	Looks like this	<u>Link</u>