cardona-qft-methods — formula report

3760 inline formulas (section omitted; all rendered), 1012 display equations, 8 tables, 40 unrecovered image regions.

Unresolved (1)

Identifier	Page	Conf.	LaTeX source	Rendered	Scan image
cardona-qft-methods_ EQ0654	261	—	`\phi_{\theta}(x) \phi_{\theta}(y)=e^{-\frac{1}{2} \frac{ \partial}{\partial x^{\mu}} \theta^{\mu \nu} \frac{ \partial}{\partial y^{\nu}}} \phi_{0}(x) \phi_{0}(y) e^{ \frac{1}{2}\left(\frac{\overleftarrow{\delta}}{\partial x^{\mu}}+\frac{\overleftarrow{☐}}{\partial y^{\mu}} \right) \theta^{\mu \nu} P_{\nu}} \neq \phi_{0}(x) \phi_{0}(y) .`	*(not rendered)*	$\phi_\theta(x)\phi_\theta(y) = e^{-\frac{1}{2}\frac{\partial}{\partial x^\mu}\theta^{\mu\nu}\frac{\partial}{\partial y^\nu}}\phi_0(x)\phi_0(y)e^{\frac{1}{2}\left(\frac{\overleftarrow{\partial}}{\partial x^\mu}+\frac{\overleftarrow{\partial}}{\partial y^\mu}\right)\theta^{\mu\nu}P_\nu} \neq \phi_0(x)\phi_0(y).$

Conf. MathPix confidence: ■ ≥0.9 ■ 0.5–0.9 ■ <0.5 — no value

Residual render vs scan (inkdrill): • C component • W weak • S stable • N noise • K clean • not measured

Flagged, not acted on — 1 of 110 shown

Identifier	Page	Conf.	LaTeX source	Rendered	Scan image
cardona-qft-methods_EQ0748	284	■ 0.547	`\begin{aligned} A d S_{5} & : & -R^{2} & =-Z_{0}^{2}+Z_{1}^{2}+Z_{2}^{2}+Z_{3}^{2}+Z_{4}^{2}-Z_{5}^{2} \\ S^{5} & : & R^{2} & =Y_{1}^{2}+Y_{2}^{2}+Y_{3}^{2}+Y_{4}^{2}+Y_{5}^{2}+Y_{6}^{2} \end{aligned}`	$\begin{aligned} AdS_{5} : \quad -R^{2} &=-Z_{0}^{2}+Z_{1}^{2}+Z_{2}^{2}+Z_{3}^{2}+Z_{4}^{2}-Z_{5}^{2} \\ S^{5} : \quad R^{2} &=Y_{1}^{2}+Y_{2}^{2}+Y_{3}^{2}+Y_{4}^{2}+Y_{5}^{2}+Y_{6}^{2} \end{aligned}$	$\begin{aligned} AdS_{5} : \quad -R^{2} &=-Z_{0}^{2}+Z_{1}^{2}+Z_{2}^{2}+Z_{3}^{2}+Z_{4}^{2}-Z_{5}^{2}, \\ S^{5} : \quad R^{2} &=Y_{1}^{2}+Y_{2}^{2}+Y_{3}^{2}+Y_{4}^{2}+Y_{5}^{2}+Y_{6}^{2}. \end{aligned}$

Conf. MathPix confidence: ■ $\geq$0.9 ■ 0.5–0.9 ■ <0.5 — no value
Residual render vs scan (inkdrill): • C component • W weak • S stable • N noise • K clean • not measured

The remaining 109 flagged rows are stated as a count.

Each differs from its scan by fewer than 20 components, which is the tail of the distribution rather than its bulk: 23 are component (`C`), 86 weak (`W`). By MathPix confidence: 72 at $\geq$0.9, 18 in 0.6–0.9, 19 below 0.6, 0 with none. Out/465 sampled twenty rows drawn from the $\geq$0.9 band corpus-wide and found eighteen purely typographic differences, one typographic plus a crop overrun, one borderline and *no* unambiguous content errors — so a high-confidence flag here is evidence of a rendering difference, not of a defect. Every row is in `report.ink.json`.