

kohlhase-omdoc — formula report

459 inline formulas (section omitted; 3 did not render), 6 display equations, 103 tables, 271 unrecovered image regions.

Unresolved (4)

Identifier	Page	Conf.	LaTeX source	Rendered	Scan image
kohlhase-omdoc_ F00317	215	—	{\,p\mid\hbox{	(not rendered)	English description: for example consider '{p p and p+2 are pri hbox would do the job}'/n>
kohlhase-omdoc_ F00319	215	—	are prime}\,}	(not rendered)	English description: for example consider '{p p and p+2 are pri hbox would do the job}'/n>
kohlhase-omdoc_ F00323	215	—	\{\,p\mid p\\{\rm and}\,p+2\rm\ are\ prime\,}	(not rendered)	kin) within math formulas. Of course it may be best to display a formula like this instead of breaking it between lines
kohlhase-omdoc_ E00005	309	—	$\begin{array}{l} \begin{array}{l} \left. \frac{\mathbf{A}:\mathbb{B} \rightarrow \mathbb{C} \quad \mathbf{B}:\mathbb{B}}{\mathbf{A}\mathbf{B}:\mathbb{C}} \right) = \frac{\frac{\forall X.\mathbb{B}(X) \Rightarrow \mathbb{C}(\mathbf{A}X)}{\mathbb{B}(\mathbf{B}) \Rightarrow \mathbb{C}(\mathbf{A}\mathbf{B})} \quad \mathbb{B}(\mathbf{B})}{\mathbb{C}(\mathbf{A}\mathbf{B})} \\ \frac{\forall X.\mathbb{B}.\mathbf{A} \quad \mathbf{B}:\mathbb{B}}{[\mathbf{B}/X]\mathbf{A}} \right) = \frac{\frac{\forall X.\mathbb{B}(X) \Rightarrow \mathcal{R}(\mathbf{A})}{\mathbb{B}(\mathcal{R}(\mathbf{B})) \Rightarrow \mathcal{R}([\mathbf{B}/X]\mathbf{A})} \quad \mathbb{B}(\mathbf{B})}{\mathcal{R}([\mathbf{B}/X]\mathbf{A})} \end{array} \\ \begin{array}{l} \begin{array}{l} \left. \frac{\mathbf{A}:\mathbb{B} \rightarrow \mathbb{C} \quad \mathbf{B}:\mathbb{B}}{\mathbf{A}\mathbf{B}:\mathbb{C}} \right) = \frac{\frac{\forall X.\mathbb{B}(X) \Rightarrow \mathbb{C}(\mathbf{A}X)}{\mathbb{B}(\mathbf{B}) \Rightarrow \mathbb{C}(\mathbf{A}\mathbf{B})} \quad \mathbb{B}(\mathbf{B})}{\mathbb{C}(\mathbf{A}\mathbf{B})} \\ \frac{\forall X.\mathbb{B}.\mathbf{A} \quad \mathbf{B}:\mathbb{B}}{[\mathbf{B}/X]\mathbf{A}} \right) = \frac{\frac{\forall X.\mathbb{B}(X) \Rightarrow \mathcal{R}(\mathbf{A})}{\mathbb{B}(\mathcal{R}(\mathbf{B})) \Rightarrow \mathcal{R}([\mathbf{B}/X]\mathbf{A})} \quad \mathbb{B}(\mathbf{B})}{\mathcal{R}([\mathbf{B}/X]\mathbf{A})} \end{array} \end{array} \end{array}$	(not rendered)	
Conf. MathPix confidence: ■ ≥0.9 ■ 0.5-0.9 ■ <0.5 — no value Residual render vs scan (inkdrill): ● C component ● W weak ● S stable ● N noise ● K clean ● not measured					

Flagged, not acted on — 1 of 2 shown

Identifier	Page	Conf.	LaTeX source	Rendered	Scan image
kohlhase-omdoc_000001 • C +38	060	■ 0.863	\forall M . \operatorname{magma}(M) \Leftrightarrow \exists E, F . M=(E, F) \wedge \text { law_of_composition }(E, F)	(not rendered)	$\forall M.magma(M) \Leftrightarrow \exists E, F.M = (E, F) \wedge law_of_composition(E, F)$
Conf. MathPix confidence: ■ ≥0.9 ■ 0.5-0.9 ■ <0.5 — no value					
Residual render vs scan (inkdrill): • C component • W weak • S stable • N noise • K clean • not measured					

The remaining 1 flagged rows are stated as a count.

Each differs from its scan by fewer than 20 components, which is the tail of the distribution rather than its bulk: 1 are component (C), 0 weak (W). By MathPix confidence: 0 at ≥0.9, 0 in 0.6–0.9, 1 below 0.6, 0 with none. Out/465 sampled twenty rows drawn from the ≥0.9 band corpus-wide and found eighteen purely typographic differences, one typographic plus a crop overrun, one borderline and *no* unambiguous content errors — so a high-confidence flag here is evidence of a rendering difference, not of a defect. Every row is in report.ink.json.