


kohlhase-omdoc: table evidence

Tables

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																										
kohlhase-omdoc_TAB_001	28	■ 1.000	<pre>\begin{tabular}[t]{t l l l l}\hline language & MathML & & & OpenMath \\ \hline by & W3C Math WG & & & OpenMath society \\ \hline origin & math for HTML & & & integration of CAS \\ \hline coverage & content + presentation; K14 & & & content; extensible \\ \hline status & Version 2.2e (VI 2003) & & & Version 2 (VI 2004) \\ \hline activity & maintenance & & & maintenance \\ \hline Info & http://w3c.org/Math/ & & & http://www.openmath.org/ \\ \hline\end{tabular}</pre>	<table><tr><td>language</td><td>MathML</td><td>OpenMath</td></tr><tr><td>by</td><td>W3C Math WG</td><td>OpenMath society</td></tr><tr><td>origin</td><td>math for HTML</td><td>integration of CAS</td></tr><tr><td>coverage</td><td>content + presentation; K14</td><td>content; extensible</td></tr><tr><td>status</td><td>Version 2.2e (VI 2003)</td><td>Version 2 (VI 2004)</td></tr><tr><td>activity</td><td>maintenance</td><td>maintenance</td></tr><tr><td>Info</td><td>http://w3c.org/Math/</td><td>http://www.openmath.org/</td></tr></table>	language	MathML	OpenMath	by	W3C Math WG	OpenMath society	origin	math for HTML	integration of CAS	coverage	content + presentation; K14	content; extensible	status	Version 2.2e (VI 2003)	Version 2 (VI 2004)	activity	maintenance	maintenance	Info	http://w3c.org/Math/	http://www.openmath.org/	<table><tr><td>language</td><td>MATHML</td><td>OPENMATH</td></tr><tr><td>by</td><td>W3C Math WG</td><td>OPENMATH society</td></tr><tr><td>origin</td><td>math for HTML</td><td>integration of CAS</td></tr><tr><td>coverage</td><td>content + presentation; K-14</td><td>content; extensible</td></tr><tr><td>status</td><td>Version 2.2e (VI 2003)</td><td>Version 2 (VI 2004)</td></tr><tr><td>activity</td><td>maintenance</td><td>maintenance</td></tr><tr><td>Info</td><td>http://w3c.org/Math/</td><td>http://www.openmath.org/</td></tr></table>	language	MATHML	OPENMATH	by	W3C Math WG	OPENMATH society	origin	math for HTML	integration of CAS	coverage	content + presentation; K-14	content; extensible	status	Version 2.2e (VI 2003)	Version 2 (VI 2004)	activity	maintenance	maintenance	Info	http://w3c.org/Math/	http://www.openmath.org/
language	MathML	OpenMath																																													
by	W3C Math WG	OpenMath society																																													
origin	math for HTML	integration of CAS																																													
coverage	content + presentation; K14	content; extensible																																													
status	Version 2.2e (VI 2003)	Version 2 (VI 2004)																																													
activity	maintenance	maintenance																																													
Info	http://w3c.org/Math/	http://www.openmath.org/																																													
language	MATHML	OPENMATH																																													
by	W3C Math WG	OPENMATH society																																													
origin	math for HTML	integration of CAS																																													
coverage	content + presentation; K-14	content; extensible																																													
status	Version 2.2e (VI 2003)	Version 2 (VI 2004)																																													
activity	maintenance	maintenance																																													
Info	http://w3c.org/Math/	http://www.openmath.org/																																													

Identifier	Page	Conf.	LaTeX source	Rendered	Image												
kohlhase-omdoc_TAB_002 [conf 0.000]	41	0.000	<pre>\begin{tabular}[t]{l} \hline Level of Representation & OMDoc Example \\ \hline \begin{tabular}[t]{l} Theory Level: Development Graph \begin{itemize} \item[-] Inheritance via symbol-mapping \item[-] Theory inclusion via proofobligations \item[-] Local (one-step) vs. global links \end{itemize} \end{tabular} &  \end{tabular} & \begin{tabular}[t]{l} Statement Level: \begin{itemize} \item[-] Axiom, definition, theorem, proof, example,... \item[-] Structure explicit in statement forms and references \end{itemize} \end{tabular} & <pre><definition for="#plus" type="recursive"> <CMP>Addition is defined by recursion on the second argument </CMP> <FMP>X + 0 = 0</FMP> <FMP>X + s(Y) = s(X + Y)</FMP> </definition> </pre> \end{tabular} & \begin{tabular}[t]{l} Object Level: OPENMATH/MATHML \begin{itemize} \item[-] Objects as logical formulae \item[-] Semantics by pointing to theory level \end{itemize} \end{tabular} & <pre><OMA> <OMS cd="arith1" name="plus"/> <OMV name="X"/> <OMS cd="nat" name="zero"/> </OMA> </pre></pre>	(not rendered)													
kohlhase-omdoc_TAB_003	50	1.000	<pre>\begin{tabular}[t]{l} \hline line & Description & ref. \\ \hline 1 & This document is an XML 1.0 file that is encoded in the UTF-8 encoding. & \end{tabular}</pre>	<table><tr><th>line</th><th>Description</th><th>ref.</th></tr><tr><td>1</td><td>This document is an XML 1.0 file that is encoded in the UTF-8 encoding.</td><td></td></tr></table>	line	Description	ref.	1	This document is an XML 1.0 file that is encoded in the UTF-8 encoding.		<table><tr><th>line</th><th>Description</th><th>ref.</th></tr><tr><td>1</td><td>This document is an XML 1.0 file that is encoded in the UTF-8 encoding.</td><td></td></tr></table>	line	Description	ref.	1	This document is an XML 1.0 file that is encoded in the UTF-8 encoding.	
line	Description	ref.															
1	This document is an XML 1.0 file that is encoded in the UTF-8 encoding.																
line	Description	ref.															
1	This document is an XML 1.0 file that is encoded in the UTF-8 encoding.																

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																
kohlhase-omdoc_TAB_004	51	0.905	<pre>\begin{tabular}[t]{l l l l } \hline 2,3 & The parser is told to use a document type definition for validation. The string omdoc specifies the name of the root element, the identifier PUBLIC specifies that the DTD (we use the "OMDoc basic" DTD; see Subsection 22.3.1), which can be identified by the public identifier in the first string and looked up in an XML catalog or (if that fails) can be found at the URL specified in the second string. A DTD declaration is not strictly needed for an OMDoc document, but is recommended, since the DTD supplies default values for some attributes. & 24.1 p. 228 \\ \hline 4 & In general, XML files can contain as much whitespace as they want between elements, here we have used it for structuring the document. & \\ \hline 5 & Start tag of the root element of the document. It declares the version (OMDoc 1.2) via the version, and an identifier of the document using the xml:id attribute. The optional modules specifies the sub-language used in this document. This is used when no DTD is present (see Subsection 22.3.1). & 11.1 p. 90 \\ \hline 6,7 & the namespace prefix declarations for the Dublin Core, Creative Commons, and OpenMath namespaces. They declare the prefixes dc:, cc:, and om:, and bind them to the specified URIs. We will need the OpenMath namespace</pre>		<table><tr><td>2,3</td><td>The parser is told to use a document type definition for validation. The string <code>omdoc</code> specifies the name of the root element, the identifier <code>PUBLIC</code> specifies that the DTD (we use the “OMDoc basic” DTD; see Subsection 22.3.1), which can be identified by the public identifier in the first string and looked up in an XML catalog or (if that fails) can be found at the URL specified in the second string. A DTD declaration is not strictly needed for an OMDoc document, but is recommended, since the DTD supplies default values for some attributes.</td><td>24.1 p. 228</td></tr><tr><td>4</td><td>In general, XML files can contain as much whitespace as they want between elements, here we have used it for structuring the document.</td><td></td></tr><tr><td>5</td><td>Start tag of the root element of the document. It declares the version (OMDoc 1.2) via the <code>version</code>, and an identifier of the document using the <code>xml:id</code> attribute. The optional <code>modules</code> specifies the sub-language used in this document. This is used when no DTD is present (see Subsection 22.3.1).</td><td>11.1 p. 90</td></tr><tr><td>6,7</td><td>the namespace prefix declarations for the Dublin Core, Creative Commons, and OPENMATH namespaces. They declare the prefixes <code>dc:</code>, <code>cc:</code>, and <code>om:</code>, and bind them to the specified URIs. We will need the OPENMATH namespace only in the third markup step described in Section 4.3, but spurious namespace prefix declarations are not a problem in the XML world.</td><td>10 p. 83</td></tr><tr><td>8</td><td>the namespace declaration for the document; if not prefixed, all elements live in the OMDoc namespace.</td><td>10.1 p. 83</td></tr><tr><td>9–29</td><td>The metadata for the whole document in Dublin Core format</td><td>11.2 p. 92</td></tr><tr><td>10</td><td>The title of the document</td><td>12.1 p. 98</td></tr><tr><td>11</td><td>The document creator, here in the role of a translator</td><td>12.2 p. 101</td></tr><tr><td>12</td><td>The date and time of first creation of the document in ISO 8601 norm format.</td><td>12.1 p. 99</td></tr><tr><td>13</td><td>The date and time of the last update to the document in ISO 8601 norm format.</td><td>12.1 p. 99</td></tr><tr><td>14–16</td><td>A short description of the contents of the document</td><td>12.1 p. 99</td></tr><tr><td>17–19</td><td>Here we acknowledge that the OMDoc document is just a translation from an earlier work.</td><td>12.1 p. 100</td></tr><tr><td>20</td><td>The type of the document, this can be <code>Dataset</code> (un-ordered mathematical knowledge) or <code>Text</code> (arranged for human consumption).</td><td>12.1 p. 100</td></tr><tr><td>21</td><td>The format/MIME type [FB96] of the document, for OMDoc, this is <code>application/omdoc+xml</code>.</td><td>12.1 p. 100</td></tr><tr><td>22</td><td>The copyright resides with the creator of the OMDoc document</td><td>12.1 p. 100</td></tr><tr><td>23–28</td><td>The creator licenses the document to the world under certain conditions as specified in the Creative Commons license specified in this element.</td><td>12.3 p. 102</td></tr></table>	2,3	The parser is told to use a document type definition for validation. The string <code>omdoc</code> specifies the name of the root element, the identifier <code>PUBLIC</code> specifies that the DTD (we use the “OMDoc basic” DTD; see Subsection 22.3.1), which can be identified by the public identifier in the first string and looked up in an XML catalog or (if that fails) can be found at the URL specified in the second string. A DTD declaration is not strictly needed for an OMDoc document, but is recommended, since the DTD supplies default values for some attributes.	24.1 p. 228	4	In general, XML files can contain as much whitespace as they want between elements, here we have used it for structuring the document.		5	Start tag of the root element of the document. It declares the version (OMDoc 1.2) via the <code>version</code> , and an identifier of the document using the <code>xml:id</code> attribute. The optional <code>modules</code> specifies the sub-language used in this document. This is used when no DTD is present (see Subsection 22.3.1).	11.1 p. 90	6,7	the namespace prefix declarations for the Dublin Core, Creative Commons, and OPENMATH namespaces. They declare the prefixes <code>dc:</code> , <code>cc:</code> , and <code>om:</code> , and bind them to the specified URIs. We will need the OPENMATH namespace only in the third markup step described in Section 4.3, but spurious namespace prefix declarations are not a problem in the XML world.	10 p. 83	8	the namespace declaration for the document; if not prefixed, all elements live in the OMDoc namespace.	10.1 p. 83	9–29	The metadata for the whole document in Dublin Core format	11.2 p. 92	10	The title of the document	12.1 p. 98	11	The document creator, here in the role of a translator	12.2 p. 101	12	The date and time of first creation of the document in ISO 8601 norm format.	12.1 p. 99	13	The date and time of the last update to the document in ISO 8601 norm format.	12.1 p. 99	14–16	A short description of the contents of the document	12.1 p. 99	17–19	Here we acknowledge that the OMDoc document is just a translation from an earlier work.	12.1 p. 100	20	The type of the document, this can be <code>Dataset</code> (un-ordered mathematical knowledge) or <code>Text</code> (arranged for human consumption).	12.1 p. 100	21	The format/MIME type [FB96] of the document, for OMDoc, this is <code>application/omdoc+xml</code> .	12.1 p. 100	22	The copyright resides with the creator of the OMDoc document	12.1 p. 100	23–28	The creator licenses the document to the world under certain conditions as specified in the Creative Commons license specified in this element.	12.3 p. 102
2,3	The parser is told to use a document type definition for validation. The string <code>omdoc</code> specifies the name of the root element, the identifier <code>PUBLIC</code> specifies that the DTD (we use the “OMDoc basic” DTD; see Subsection 22.3.1), which can be identified by the public identifier in the first string and looked up in an XML catalog or (if that fails) can be found at the URL specified in the second string. A DTD declaration is not strictly needed for an OMDoc document, but is recommended, since the DTD supplies default values for some attributes.	24.1 p. 228																																																			
4	In general, XML files can contain as much whitespace as they want between elements, here we have used it for structuring the document.																																																				
5	Start tag of the root element of the document. It declares the version (OMDoc 1.2) via the <code>version</code> , and an identifier of the document using the <code>xml:id</code> attribute. The optional <code>modules</code> specifies the sub-language used in this document. This is used when no DTD is present (see Subsection 22.3.1).	11.1 p. 90																																																			
6,7	the namespace prefix declarations for the Dublin Core, Creative Commons, and OPENMATH namespaces. They declare the prefixes <code>dc:</code> , <code>cc:</code> , and <code>om:</code> , and bind them to the specified URIs. We will need the OPENMATH namespace only in the third markup step described in Section 4.3, but spurious namespace prefix declarations are not a problem in the XML world.	10 p. 83																																																			
8	the namespace declaration for the document; if not prefixed, all elements live in the OMDoc namespace.	10.1 p. 83																																																			
9–29	The metadata for the whole document in Dublin Core format	11.2 p. 92																																																			
10	The title of the document	12.1 p. 98																																																			
11	The document creator, here in the role of a translator	12.2 p. 101																																																			
12	The date and time of first creation of the document in ISO 8601 norm format.	12.1 p. 99																																																			
13	The date and time of the last update to the document in ISO 8601 norm format.	12.1 p. 99																																																			
14–16	A short description of the contents of the document	12.1 p. 99																																																			
17–19	Here we acknowledge that the OMDoc document is just a translation from an earlier work.	12.1 p. 100																																																			
20	The type of the document, this can be <code>Dataset</code> (un-ordered mathematical knowledge) or <code>Text</code> (arranged for human consumption).	12.1 p. 100																																																			
21	The format/MIME type [FB96] of the document, for OMDoc, this is <code>application/omdoc+xml</code> .	12.1 p. 100																																																			
22	The copyright resides with the creator of the OMDoc document	12.1 p. 100																																																			
23–28	The creator licenses the document to the world under certain conditions as specified in the Creative Commons license specified in this element.	12.3 p. 102																																																			

Identifier	Page	Conf.	LaTeX source	Rendered	Image																					
kohlhase-omdoc_TAB_005	52	■ 0.221	<pre>\begin{tabular}{t}{ l l l } \hline 24,25 & The cc:permissions element gives the world the permission to reproduce and distribute it freely. Furthermore the license grants the public the right to make derivative works under certain conditions. & 12.3 p. 103 \\ \hline 26 & The cc:prohibitions can be used to prohibit certain uses of the document, but this one is unencumbered. & 12.3 p. 103 \\ \hline 27 & The cc:requirements states conditions under which the license is granted. In our case the licensee is required to keep the copyright notice and license notices intact during distribution, to give credit to the copyright holder, and that any derivative works derived from this document must be licensed under the same terms as this document (the copyleft clause). & 12.3 p. 103 \\ \hline 31-37 & The omdoc element is used to mark up text fragments. Here, we have simply used a single omdoc to classify the whole text in the fragment as unspecific "text". & 14.3 p. 124 \\ \hline 32-36 & The CMP element holds the actual text in a multilingual group. Its xml:lang specifies the language. If the document is used with a DTD or an XML schema (as we are) this attribute is redundant, since the default value given by the DTD or schema is en. More keywords in other languages can be given by adding more CMP elements. & 14.1 p. 122 \\ \hline 33-35 & The text of the L^AT_EX fragment we are migrating. For simplicity we do not change the text, and leave that to later stages of the migration. & \\ \hline 38 & The closing tag of the root omdoc element. There may not be text after this in the file. & 11.1 p. 90 \\ \hline \end{tabular}</pre>		<table><tr><td>24,25</td><td>The cc:permissions element gives the world the permission to reproduce and distribute it freely. Furthermore the license grants the public the right to make derivative works under certain conditions.</td><td>12.3 p. 103</td></tr><tr><td>26</td><td>The cc:prohibitions can be used to prohibit certain uses of the document, but this one is unencumbered.</td><td>12.3 p. 103</td></tr><tr><td>27</td><td>The cc:requirements states conditions under which the license is granted. In our case the licensee is required to keep the copyright notice and license notices intact during distribution, to give credit to the copyright holder, and that any derivative works derived from this document must be licensed under the same terms as this document (the copyleft clause).</td><td>12.3 p. 103</td></tr><tr><td>31-37</td><td>The omdoc element is used to mark up text fragments. Here, we have simply used a single omdoc to classify the whole text in the fragment as unspecific “text”.</td><td>14.3 p. 124</td></tr><tr><td>32-36</td><td>The CMP element holds the actual text in a multilingual group. Its xml:lang specifies the language. If the document is used with a DTD or an XML schema (as we are) this attribute is redundant, since the default value given by the DTD or schema is en. More keywords in other languages can be given by adding more CMP elements.</td><td>14.1 p. 122</td></tr><tr><td>33-35</td><td>The text of the L^AT_EX fragment we are migrating. For simplicity we do not change the text, and leave that to later stages of the migration.</td><td></td></tr><tr><td>38</td><td>The closing tag of the root omdoc element. There may not be text after this in the file.</td><td>11.1 p. 90</td></tr></table>	24,25	The cc:permissions element gives the world the permission to reproduce and distribute it freely. Furthermore the license grants the public the right to make derivative works under certain conditions.	12.3 p. 103	26	The cc:prohibitions can be used to prohibit certain uses of the document, but this one is unencumbered.	12.3 p. 103	27	The cc:requirements states conditions under which the license is granted. In our case the licensee is required to keep the copyright notice and license notices intact during distribution, to give credit to the copyright holder, and that any derivative works derived from this document must be licensed under the same terms as this document (the copyleft clause).	12.3 p. 103	31-37	The omdoc element is used to mark up text fragments. Here, we have simply used a single omdoc to classify the whole text in the fragment as unspecific “text”.	14.3 p. 124	32-36	The CMP element holds the actual text in a multilingual group. Its xml:lang specifies the language. If the document is used with a DTD or an XML schema (as we are) this attribute is redundant, since the default value given by the DTD or schema is en. More keywords in other languages can be given by adding more CMP elements.	14.1 p. 122	33-35	The text of the L ^A T _E X fragment we are migrating. For simplicity we do not change the text, and leave that to later stages of the migration.		38	The closing tag of the root omdoc element. There may not be text after this in the file.	11.1 p. 90
24,25	The cc:permissions element gives the world the permission to reproduce and distribute it freely. Furthermore the license grants the public the right to make derivative works under certain conditions.	12.3 p. 103																								
26	The cc:prohibitions can be used to prohibit certain uses of the document, but this one is unencumbered.	12.3 p. 103																								
27	The cc:requirements states conditions under which the license is granted. In our case the licensee is required to keep the copyright notice and license notices intact during distribution, to give credit to the copyright holder, and that any derivative works derived from this document must be licensed under the same terms as this document (the copyleft clause).	12.3 p. 103																								
31-37	The omdoc element is used to mark up text fragments. Here, we have simply used a single omdoc to classify the whole text in the fragment as unspecific “text”.	14.3 p. 124																								
32-36	The CMP element holds the actual text in a multilingual group. Its xml:lang specifies the language. If the document is used with a DTD or an XML schema (as we are) this attribute is redundant, since the default value given by the DTD or schema is en. More keywords in other languages can be given by adding more CMP elements.	14.1 p. 122																								
33-35	The text of the L ^A T _E X fragment we are migrating. For simplicity we do not change the text, and leave that to later stages of the migration.																									
38	The closing tag of the root omdoc element. There may not be text after this in the file.	11.1 p. 90																								

Identifier	Page	Conf.	LaTeX source	Rendered	Image																					
kohlhase-omdoc_TAB_006	53	■ 1.000	\begin{tabular}[t]{l l l l} \hline line & Description & ref. \\ 1 & The <code>omtext</code> element classifies the text fragment as a <code>definition</code> , other types for mathematical statements include <code>axiom</code> , <code>example</code> , <code>theorem</code> , and <code>lemma</code> . Note that the numbering of the original text is lost, but can be re-created in the text presentation process. The optional <code>xml:id</code> attribute specifies a document-unique identifier that can be used for reference later. & 14.3 p. 124 \\ 2 & A multilingual group of <code>CMP</code> elements that hold the text (in our case, there is only the English default). Here the <code>T_EX</code> formulae have been marked up with <code>legacy</code> elements characterizing them as such. This might simplify a later automatic transformation to <code>OPENMATH</code> or <code>Content-MATHML</code> . & 13.5 p. 120 \\ 4-13 & We have classified every paragraph in the original as a separate <code>omtext</code> element, which does not carry a <code>type</code> since it does not fit any other mathematical category at the moment. & 14.3 p. 124 \\ 15 & The three examples in the original in Figure 4.1 are grouped into an enumeration. We use the <code>OMDOC omgroup</code> element for this. The optional attribute <code>xml:id</code> can be used for referencing later. We have chosen <code>enumeration</code> for the <code>type</code> attribute to specify the numbering of the examples in the original. & 11.4 p. 93 \\ 16 & We can use the <code>metadata</code> of the <code>omgroup</code> element to accommodate the title “Examples” in the original. We could enter more metadata at this level. & 14.1 p. 122 \\ 18 & The <code>type</code> attribute of this <code>omtext</code> element classifies this text fragment as an example. & 14.3 p. 124 \\ \end{tabular}		<table><tr><th>line</th><th>Description</th><th>ref.</th></tr><tr><td>1</td><td>The <code>omtext</code> element classifies the text fragment as a <code>definition</code>, other types for mathematical statements include <code>axiom</code>, <code>example</code>, <code>theorem</code>, and <code>lemma</code>. Note that the numbering of the original text is lost, but can be re-created in the text presentation process. The optional <code>xml:id</code> attribute specifies a document-unique identifier that can be used for reference later.</td><td>14.3 p. 124</td></tr><tr><td>2</td><td>A multilingual group of <code>CMP</code> elements that hold the text (in our case, there is only the English default). Here the <code>T_EX</code> formulae have been marked up with <code>legacy</code> elements characterizing them as such. This might simplify a later automatic transformation to <code>OPENMATH</code> or <code>Content-MATHML</code>.</td><td>13.5 p. 120</td></tr><tr><td>4-13</td><td>We have classified every paragraph in the original as a separate <code>omtext</code> element, which does not carry a <code>type</code> since it does not fit any other mathematical category at the moment.</td><td>14.3 p. 124</td></tr><tr><td>15</td><td>The three examples in the original in Figure 4.1 are grouped into an enumeration. We use the <code>OMDOC omgroup</code> element for this. The optional attribute <code>xml:id</code> can be used for referencing later. We have chosen <code>enumeration</code> for the <code>type</code> attribute to specify the numbering of the examples in the original.</td><td>11.4 p. 93</td></tr><tr><td>16</td><td>We can use the <code>metadata</code> of the <code>omgroup</code> element to accommodate the title “Examples” in the original. We could enter more metadata at this level.</td><td>14.1 p. 122</td></tr><tr><td>18</td><td>The <code>type</code> attribute of this <code>omtext</code> element classifies this text fragment as an example.</td><td>14.3 p. 124</td></tr></table>	line	Description	ref.	1	The <code>omtext</code> element classifies the text fragment as a <code>definition</code> , other types for mathematical statements include <code>axiom</code> , <code>example</code> , <code>theorem</code> , and <code>lemma</code> . Note that the numbering of the original text is lost, but can be re-created in the text presentation process. The optional <code>xml:id</code> attribute specifies a document-unique identifier that can be used for reference later.	14.3 p. 124	2	A multilingual group of <code>CMP</code> elements that hold the text (in our case, there is only the English default). Here the <code>T_EX</code> formulae have been marked up with <code>legacy</code> elements characterizing them as such. This might simplify a later automatic transformation to <code>OPENMATH</code> or <code>Content-MATHML</code> .	13.5 p. 120	4-13	We have classified every paragraph in the original as a separate <code>omtext</code> element, which does not carry a <code>type</code> since it does not fit any other mathematical category at the moment.	14.3 p. 124	15	The three examples in the original in Figure 4.1 are grouped into an enumeration. We use the <code>OMDOC omgroup</code> element for this. The optional attribute <code>xml:id</code> can be used for referencing later. We have chosen <code>enumeration</code> for the <code>type</code> attribute to specify the numbering of the examples in the original.	11.4 p. 93	16	We can use the <code>metadata</code> of the <code>omgroup</code> element to accommodate the title “Examples” in the original. We could enter more metadata at this level.	14.1 p. 122	18	The <code>type</code> attribute of this <code>omtext</code> element classifies this text fragment as an example.	14.3 p. 124
					line	Description	ref.																			
					1	The <code>omtext</code> element classifies the text fragment as a <code>definition</code> , other types for mathematical statements include <code>axiom</code> , <code>example</code> , <code>theorem</code> , and <code>lemma</code> . Note that the numbering of the original text is lost, but can be re-created in the text presentation process. The optional <code>xml:id</code> attribute specifies a document-unique identifier that can be used for reference later.	14.3 p. 124																			
					2	A multilingual group of <code>CMP</code> elements that hold the text (in our case, there is only the English default). Here the <code>T_EX</code> formulae have been marked up with <code>legacy</code> elements characterizing them as such. This might simplify a later automatic transformation to <code>OPENMATH</code> or <code>Content-MATHML</code> .	13.5 p. 120																			
					4-13	We have classified every paragraph in the original as a separate <code>omtext</code> element, which does not carry a <code>type</code> since it does not fit any other mathematical category at the moment.	14.3 p. 124																			
					15	The three examples in the original in Figure 4.1 are grouped into an enumeration. We use the <code>OMDOC omgroup</code> element for this. The optional attribute <code>xml:id</code> can be used for referencing later. We have chosen <code>enumeration</code> for the <code>type</code> attribute to specify the numbering of the examples in the original.	11.4 p. 93																			
					16	We can use the <code>metadata</code> of the <code>omgroup</code> element to accommodate the title “Examples” in the original. We could enter more metadata at this level.	14.1 p. 122																			
18	The <code>type</code> attribute of this <code>omtext</code> element classifies this text fragment as an example.	14.3 p. 124																								

Identifier	Page	Conf.	LaTeX source	Rendered	Image
kohlhase-omdoc_TAB_007	55	■ 0.487	\begin{tabular}[t]{l l l } \hline line & Description & ref. \\ 1-4 & The omdoc-basic document type definition is no longer sufficient for our purposes, since we introduce new symbols that can be used in other documents. The DTD for OMDoc content dictionaries (see Chapter 5), which allows this. Correspondingly, we would specify the value cd for the attribute module. \\ The part in line 4 is the internal subset of the DTD, which sets a parameter entity for the modularized DTD to instruct it to accept OpenMath elements in their namespace prefixed form. Of course a suitable namespace prefix declaration is needed as well. \\ \end{tabular} & 22.3.2 p. 218 \\ 5 & The start tag of a theory. We need this, since symbols and definitions can only appear inside theory elements. \\ 15.6 p. 149 \\ 6,7 & We need to import the theory products to be able to use symbols from it in the definition below. The value of the from is a relative URI reference to a theory element much like the one in line 5. The other imports element imports the theory relation1 from the OPENMATH standard content dictionaries ¹ . Note that we do not need to import the theory sets here, since this is already imported by the theory products. \\ 15.6.1 p. 150 \\ 9-11 & A symbol declaration: For every definition, OMDoc requires the declaration of one or more symbol elements for the concept that is to be defined. The name attribute is used to identify it. The dc:description element allows to supply a multilingual (via the xml:lang attribute) group of keywords for the declared symbol \\ 15.2.1 p. 136 \\ 12 & Upon closer inspection it turns out that the definition in Listing 4.4 actually defines three concepts: “law of composition”, “composition”, and “magma”. Note that “composition” is just another name for the value under the law of composition, therefore we do not need to declare a symbol for this. Thus we only declare one for “law of composition”. \\ 15.2.1 p. 136 \\ 14 & A definition: the definition element carries a name attribute for reference within the theory. We need to reference the two symbols defined here in the for attribute of the definition element; it takes a whitespace-separated list of name attributes of symbol elements in the same theory as values. \\ 15.2.4 p.139 \\ 16 & We use an OPENMATH object for the set E. It is an om:OMOBJ element with an om:OMV daughter, whose name attribute specifies the object to be a variable with name E. We have chosen to represent the set E as a variable instead of a constant (via an om:OMS element) in the theory, since it seems to be local to the definition. We will discuss this further in the next section, where we talk about formalization. \\ 13.1.1 p. 108		

Identifier	Page	Conf.	LaTeX source	Rendered	Image															
kohlhase-omdoc_TAB_008	56	■ 0.448	<pre>\begin{tabular}[t]{l l l l} \hline 17-21 & This om:OMOBJ represents the Cartesian product \(\E \times E\) of the set \(\E\) with itself. It is an application (via an om:OMA element) of the symbol for the binary Cartesian product relation to \(\E\). & 13.1.1 p. 108 \\ \hline 18 & The symbol for the Cartesian product constructor is represented as an om:OMS element. The cd attribute specifies the theory that defines the symbol, and the name points to the symbol element in it that declares this symbol. The value of the cd attribute is a theory identifier. Note that this theory has to be imported into the current theory, to be legally used. & 13.1.1 p. 108 \\ \hline 22 & We use the term element to characterize the defined terms in the text of the definition. Its role attribute can used to mark the text fragment as a definiens, i.e. a concept that is under definition. & 14.5 p. 128 \\ \hline 24-28 & This object stands for $f(x,y)$ & \\ \hline 30-39 & This object represents $(x,y) \in E \times E$. Note that we make use of the symbol for the elementhood relation from the OPEN-MATH core content dictionary set1 and of the pairconstructor from the theory of products from the Bourbaki collection there. & \\ \hline \end{tabular}</pre>		<table><tr><td>17–21</td><td>This om:OMOBJ represents the Cartesian product $E \times E$ of the set E with itself. It is an application (via an om:OMA element) of the symbol for the binary Cartesian product relation to E.</td><td>13.1.1 p. 108</td></tr><tr><td>18</td><td>The symbol for the Cartesian product constructor is represented as an om:OMS element. The cd attribute specifies the theory that defines the symbol, and the name points to the symbol element in it that declares this symbol. The value of the cd attribute is a theory identifier. Note that this theory has to be imported into the current theory, to be legally used.</td><td>13.1.1 p. 108</td></tr><tr><td>22</td><td>We use the term element to characterize the defined terms in the text of the definition. Its role attribute can used to mark the text fragment as a definiens, i.e. a concept that is under definition.</td><td>14.5 p. 128</td></tr><tr><td>24–28</td><td>This object stands for $f(x,y)$</td><td></td></tr><tr><td>30–39</td><td>This object represents $(x,y) \in E \times E$. Note that we make use of the symbol for the elementhood relation from the OPEN-MATH core content dictionary set1 and of the pairconstructor from the theory of products from the Bourbaki collection there.</td><td></td></tr></table>	17–21	This om:OMOBJ represents the Cartesian product $E \times E$ of the set E with itself. It is an application (via an om:OMA element) of the symbol for the binary Cartesian product relation to E .	13.1.1 p. 108	18	The symbol for the Cartesian product constructor is represented as an om:OMS element. The cd attribute specifies the theory that defines the symbol, and the name points to the symbol element in it that declares this symbol. The value of the cd attribute is a theory identifier. Note that this theory has to be imported into the current theory, to be legally used.	13.1.1 p. 108	22	We use the term element to characterize the defined terms in the text of the definition. Its role attribute can used to mark the text fragment as a definiens, i.e. a concept that is under definition.	14.5 p. 128	24–28	This object stands for $f(x,y)$		30–39	This object represents $(x,y) \in E \times E$. Note that we make use of the symbol for the elementhood relation from the OPEN-MATH core content dictionary set1 and of the pairconstructor from the theory of products from the Bourbaki collection there.	
17–21	This om:OMOBJ represents the Cartesian product $E \times E$ of the set E with itself. It is an application (via an om:OMA element) of the symbol for the binary Cartesian product relation to E .	13.1.1 p. 108																		
18	The symbol for the Cartesian product constructor is represented as an om:OMS element. The cd attribute specifies the theory that defines the symbol, and the name points to the symbol element in it that declares this symbol. The value of the cd attribute is a theory identifier. Note that this theory has to be imported into the current theory, to be legally used.	13.1.1 p. 108																		
22	We use the term element to characterize the defined terms in the text of the definition. Its role attribute can used to mark the text fragment as a definiens, i.e. a concept that is under definition.	14.5 p. 128																		
24–28	This object stands for $f(x,y)$																			
30–39	This object represents $(x,y) \in E \times E$. Note that we make use of the symbol for the elementhood relation from the OPEN-MATH core content dictionary set1 and of the pairconstructor from the theory of products from the Bourbaki collection there.																			

Identifier	Page	Conf.	LaTeX source	Rendered	Image
kohlhase-omdoc_TAB_009	93	■1.000	\begin{tabular}{t l l l l } \hline Module & Title & Required? & Chapter \\ \hline MOBJ & Mathematical Objects & yes & Chapter 13 \\ \hline \multicolumn{4}{Formulae are a central part of mathematical documents; this module integrates the content-oriented representation formats OpenMath and MathML into OMDoc} \\ \hline MTXT & Mathematical Text & yes & Chapter 14 \\ \hline \multicolumn{4}{Mathematical vernacular, i.e. natural language with embedded formulae} \\ \hline DOC & Document Infrastructure & yes & Chapter 11 \\ \hline \multicolumn{4}{A basic infrastructure for assembling pieces of mathematical knowledge into functional documents and referencing their parts} \\ \hline DC & Dublin Core Metadata & yes & Sections 12.1 and 12.2 \\ \hline \multicolumn{4}{Contains bibliographical “data about data”, which can be used to annotate many OMDoc elements by descriptive and administrative information that facilitates navigation and organization} \\ \hline CC & Creative Commons Metadata & yes & Section 12.3 \\ \hline \multicolumn{4}{Licenses for text use} \\ \hline RT & Rich Text Structure & no & Section 14.6 \\ \hline \multicolumn{4}{Rich text structure in mathematical vernacular (lists, paragraphs, tables, ...)} \\ \hline ST & Mathematical Statements & no & Chapter 15 \\ \hline \multicolumn{4}{Markup for mathematical forms like theorems, axioms, definitions, and examples that can be used to specify or define properties of given mathematical objects and theories to group mathematical statements and provide a notion of context.} \\ \hline PF & Proofs and proof objects & no & Chapter 17 \\ \hline \multicolumn{4}{Structure of proofs and argumentations at various levels of details and formality} \\ \hline ADT & Abstract Data Types & no & Chapter 16 \\ \hline \multicolumn{4}{Definition schemata for sets that are built up inductively from constructor symbols} \\ \hline CTH & Complex Theories & no & Chapter 18 \\ \hline \multicolumn{4}{Theory morphisms; they can be used to structure mathematical theories} \\ \hline DG & Development Graphs & no & Section 18.5 \\ \hline \multicolumn{4}{Infrastructure for managing theory inclusions, change management} \\ \hline EXT & Applets, Code, and Data & no & Chapter 20 \\ \hline \multicolumn{4}{Markup for applets, program code, and data (e.g. images, measurements, ...)} \\ \hline PRES & Presentation Information & no & Chapter 19 \\ \hline \multicolumn{4}{Limited functionality for specifying presentation and notation information for local typographic conventions that cannot be determined by general principles alone} \\ \hline QUIZ & Infrastructure for Assessments & no & Chapter 21 \\ \hline \multicolumn{4}{Markup for exercises integrated into the OMDoc document model} \\ \hline \end{tabular}		
8					

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																
kohlhase-omdoc_TAB_010	94	■0.999	<pre>\begin{tabular}[t]{l l l l} \hline Format & namespace URI & see \\ \hline Dublin Core & http://purl.org/dc/elements/1.1/ & Sections 12.1 and 12.2 \\ \hline Creative Commons & http://creativecommons.org/ns & Section 12.3 \\ \hline MATHML & http://www.w3.org/1998/Math/MathML & Section 13.2 \\ \hline OPENMATH & http://www.openmath.org/OpenMath & Section 13.1 \\ \hline XSLT & http://www.w3.org/1999/XSL/Transform & Chapter 19 \\ \end{tabular}</pre>	(not rendered)	<table><tr><th>Format</th><th>namespace URI</th><th>see</th></tr><tr><td>Dublin Core</td><td>http://purl.org/dc/elements/1.1/</td><td>Sections 12.1 and 12.2</td></tr><tr><td>Creative Commons</td><td>http://creativecommons.org/ns</td><td>Section 12.3</td></tr><tr><td>MATHML</td><td>http://www.w3.org/1998/Math/MathML</td><td>Section 13.2</td></tr><tr><td>OPENMATH</td><td>http://www.openmath.org/OpenMath</td><td>Section 13.1</td></tr><tr><td>XSLT</td><td>http://www.w3.org/1999/XSL/Transform</td><td>Chapter 19</td></tr></table>	Format	namespace URI	see	Dublin Core	http://purl.org/dc/elements/1.1/	Sections 12.1 and 12.2	Creative Commons	http://creativecommons.org/ns	Section 12.3	MATHML	http://www.w3.org/1998/Math/MathML	Section 13.2	OPENMATH	http://www.openmath.org/OpenMath	Section 13.1	XSLT	http://www.w3.org/1999/XSL/Transform	Chapter 19																																														
Format	namespace URI	see																																																																			
Dublin Core	http://purl.org/dc/elements/1.1/	Sections 12.1 and 12.2																																																																			
Creative Commons	http://creativecommons.org/ns	Section 12.3																																																																			
MATHML	http://www.w3.org/1998/Math/MathML	Section 13.2																																																																			
OPENMATH	http://www.openmath.org/OpenMath	Section 13.1																																																																			
XSLT	http://www.w3.org/1999/XSL/Transform	Chapter 19																																																																			
kohlhase-omdoc_TAB_011	99	■0.529	<pre>\begin{tabular}[t]{l l l l l} \hline Element & Attributes & D & Content \\ \hline omdoc & version, xmlns & C \\ \hline omgroup & & + & (\langle top-level \rangle)* \\ \hline metadata & & - & \langle MDelt \rangle* \\ \hline ref & xref & - & \\ \hline ignore & & - & ANY \\ \hline \end{tabular} where \langle top-level \rangle stands for top-level OMDoc elements, and \langle MDelt \rangle for those introduced in Chapter 12</pre>	<table><tr><th>Element</th><th>Attributes</th><th>D</th><th>Content</th></tr><tr><th></th><th>Required</th><th>Optional</th><th>C</th></tr><tr><td>omdoc</td><td>version, xmlns</td><td>xml:id, type, class, style, version, modules</td><td>+ ($\langle top-level \rangle$)*</td></tr><tr><td>omgroup</td><td></td><td>xml:id, modules, type, class, style</td><td>+ ($\langle top-level \rangle$)*</td></tr><tr><td>metadata</td><td></td><td>xml:id, inherits, class, style</td><td>- $\langle MDelt \rangle^*$</td></tr><tr><td>ref</td><td>xref</td><td>type, class, style</td><td>-</td></tr><tr><td>ignore</td><td></td><td>type, comment</td><td>- ANY</td></tr><tr><td colspan="4">where $\langle top-level \rangle$ stands for top-level OMDoc elements, and $\langle MDelt \rangle$ for those introduced in Chapter 12</td></tr></table>	Element	Attributes	D	Content		Required	Optional	C	omdoc	version, xmlns	xml:id, type, class, style, version, modules	+ ($\langle top-level \rangle$)*	omgroup		xml:id, modules, type, class, style	+ ($\langle top-level \rangle$)*	metadata		xml:id, inherits, class, style	- $\langle MDelt \rangle^*$	ref	xref	type, class, style	-	ignore		type, comment	- ANY	where $\langle top-level \rangle$ stands for top-level OMDoc elements, and $\langle MDelt \rangle$ for those introduced in Chapter 12				<table><tr><th>Element</th><th>Attributes</th><th>D</th><th>Content</th></tr><tr><th></th><th>Required</th><th>Optional</th><th>C</th></tr><tr><td>omdoc</td><td>version, xmlns</td><td>xml:id, type, class, style, version, modules</td><td>+ ($\langle top-level \rangle$)*</td></tr><tr><td>omgroup</td><td></td><td>xml:id, modules, type, class, style</td><td>+ ($\langle top-level \rangle$)*</td></tr><tr><td>metadata</td><td></td><td>xml:id, inherits, class, style</td><td>- $\langle MDelt \rangle^*$</td></tr><tr><td>ref</td><td>xref</td><td>type, class, style</td><td>-</td></tr><tr><td>ignore</td><td></td><td>type, comment</td><td>- ANY</td></tr><tr><td colspan="4">where $\langle top-level \rangle$ stands for top-level OMDoc elements, and $\langle MDelt \rangle$ for those introduced in Chapter 12</td></tr></table>	Element	Attributes	D	Content		Required	Optional	C	omdoc	version, xmlns	xml:id, type, class, style, version, modules	+ ($\langle top-level \rangle$)*	omgroup		xml:id, modules, type, class, style	+ ($\langle top-level \rangle$)*	metadata		xml:id, inherits, class, style	- $\langle MDelt \rangle^*$	ref	xref	type, class, style	-	ignore		type, comment	- ANY	where $\langle top-level \rangle$ stands for top-level OMDoc elements, and $\langle MDelt \rangle$ for those introduced in Chapter 12			
Element	Attributes	D	Content																																																																		
	Required	Optional	C																																																																		
omdoc	version, xmlns	xml:id, type, class, style, version, modules	+ ($\langle top-level \rangle$)*																																																																		
omgroup		xml:id, modules, type, class, style	+ ($\langle top-level \rangle$)*																																																																		
metadata		xml:id, inherits, class, style	- $\langle MDelt \rangle^*$																																																																		
ref	xref	type, class, style	-																																																																		
ignore		type, comment	- ANY																																																																		
where $\langle top-level \rangle$ stands for top-level OMDoc elements, and $\langle MDelt \rangle$ for those introduced in Chapter 12																																																																					
Element	Attributes	D	Content																																																																		
	Required	Optional	C																																																																		
omdoc	version, xmlns	xml:id, type, class, style, version, modules	+ ($\langle top-level \rangle$)*																																																																		
omgroup		xml:id, modules, type, class, style	+ ($\langle top-level \rangle$)*																																																																		
metadata		xml:id, inherits, class, style	- $\langle MDelt \rangle^*$																																																																		
ref	xref	type, class, style	-																																																																		
ignore		type, comment	- ANY																																																																		
where $\langle top-level \rangle$ stands for top-level OMDoc elements, and $\langle MDelt \rangle$ for those introduced in Chapter 12																																																																					

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																
kohlhase-omdoc_TAB_012	105	■0.922	<pre>\begin{tabular}[t]{ l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & Content \\ \hline & Req. & Optional & \\ \hline dc:creator & & xml:id, class, style, role & ANY \\ dc:contributor & & xml:id, class, style, role & ANY \\ dc:title & & xml:lang & ⟨math vernacular⟩ \\ dc:subject & & xml:lang & ⟨math vernacular⟩ \\ dc:description & & xml:lang & ⟨math vernacular⟩ \\ dc:publisher & & xml:id, class, style & ANY \\ dc:date & & action, who & ISO 8601 \\ dc:type & & & fixed: "Dataset" or "Text" \\ dc:format & & & fixed: "application/omdoc+xml" \\ dc:identifier & & scheme & ANY \\ dc:source & & & ANY \\ dc:language & & & ISO 639 \\ dc:relation & & & ANY \\ dc:rights & & & ANY \\ \hline \end{tabular}</pre> for ⟨math vernacular⟩ see Section 14.1	(not rendered)	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><td></td></tr><tr><td>dc:creator</td><td></td><td>xml:id, class, style, role</td><td>ANY</td></tr><tr><td>dc:contributor</td><td></td><td>xml:id, class, style, role</td><td>ANY</td></tr><tr><td>dc:title</td><td></td><td>xml:lang</td><td>⟨math vernacular⟩</td></tr><tr><td>dc:subject</td><td></td><td>xml:lang</td><td>⟨math vernacular⟩</td></tr><tr><td>dc:description</td><td></td><td>xml:lang</td><td>⟨math vernacular⟩</td></tr><tr><td>dc:publisher</td><td></td><td>xml:id, class, style</td><td>ANY</td></tr><tr><td>dc:date</td><td></td><td>action, who</td><td>ISO 8601</td></tr><tr><td>dc:type</td><td></td><td></td><td>fixed: "Dataset" or "Text"</td></tr><tr><td>dc:format</td><td></td><td></td><td>fixed: "application/omdoc+xml"</td></tr><tr><td>dc:identifier</td><td></td><td>scheme</td><td>ANY</td></tr><tr><td>dc:source</td><td></td><td></td><td>ANY</td></tr><tr><td>dc:language</td><td></td><td></td><td>ISO 639</td></tr><tr><td>dc:relation</td><td></td><td></td><td>ANY</td></tr><tr><td>dc:rights</td><td></td><td></td><td>ANY</td></tr></table>	Element	Attributes		Content		Req.	Optional		dc:creator		xml:id, class, style, role	ANY	dc:contributor		xml:id, class, style, role	ANY	dc:title		xml:lang	⟨math vernacular⟩	dc:subject		xml:lang	⟨math vernacular⟩	dc:description		xml:lang	⟨math vernacular⟩	dc:publisher		xml:id, class, style	ANY	dc:date		action, who	ISO 8601	dc:type			fixed: "Dataset" or "Text"	dc:format			fixed: "application/omdoc+xml"	dc:identifier		scheme	ANY	dc:source			ANY	dc:language			ISO 639	dc:relation			ANY	dc:rights			ANY
Element	Attributes		Content																																																																		
	Req.	Optional																																																																			
dc:creator		xml:id, class, style, role	ANY																																																																		
dc:contributor		xml:id, class, style, role	ANY																																																																		
dc:title		xml:lang	⟨math vernacular⟩																																																																		
dc:subject		xml:lang	⟨math vernacular⟩																																																																		
dc:description		xml:lang	⟨math vernacular⟩																																																																		
dc:publisher		xml:id, class, style	ANY																																																																		
dc:date		action, who	ISO 8601																																																																		
dc:type			fixed: "Dataset" or "Text"																																																																		
dc:format			fixed: "application/omdoc+xml"																																																																		
dc:identifier		scheme	ANY																																																																		
dc:source			ANY																																																																		
dc:language			ISO 639																																																																		
dc:relation			ANY																																																																		
dc:rights			ANY																																																																		
kohlhase-omdoc_TAB_013	111	■1.000	<pre>\begin{tabular}[t]{ l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & Content \\ \hline & Req. & Optional & \\ \hline cc:license & & jurisdiction & permissions, prohibitions, requirements \\ cc:permissions & & reproduction, distribution, derivative_works & EMPTY \\ cc:prohibitions & & commercial_use & EMPTY \\ cc:requirements & & notice, copyleft, attribution & EMPTY \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><td></td></tr><tr><td>cc:license</td><td></td><td>jurisdiction</td><td>permissions, prohibitions, requirements</td></tr><tr><td>cc:permissions</td><td></td><td>reproduction, distribution, derivative_works</td><td>EMPTY</td></tr><tr><td>cc:prohibitions</td><td></td><td>commercial_use</td><td>EMPTY</td></tr><tr><td>cc:requirements</td><td></td><td>notice, copyleft, attribution</td><td>EMPTY</td></tr></table>	Element	Attributes		Content		Req.	Optional		cc:license		jurisdiction	permissions, prohibitions, requirements	cc:permissions		reproduction, distribution, derivative_works	EMPTY	cc:prohibitions		commercial_use	EMPTY	cc:requirements		notice, copyleft, attribution	EMPTY																																								
Element	Attributes		Content																																																																		
	Req.	Optional																																																																			
cc:license		jurisdiction	permissions, prohibitions, requirements																																																																		
cc:permissions		reproduction, distribution, derivative_works	EMPTY																																																																		
cc:prohibitions		commercial_use	EMPTY																																																																		
cc:requirements		notice, copyleft, attribution	EMPTY																																																																		
kohlhase-omdoc_TAB_014	111	■1.000	<pre>\begin{tabular}[t]{ l l l } \hline Attribute & Permission & Default \\ \hline reproduction & the work may be reproduced & permitted \\ distribution & the work may be distributed, publicly displayed, and publicly performed & permitted \\ derivative_works & derivative works may be created and reproduced & permitted \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><th>Attribute</th><th>Permission</th><th>Default</th></tr><tr><td>reproduction</td><td>the work may be reproduced</td><td>permitted</td></tr><tr><td>distribution</td><td>the work may be distributed, publicly displayed, and publicly performed</td><td>permitted</td></tr><tr><td>derivative_works</td><td>derivative works may be created and reproduced</td><td>permitted</td></tr></table>	Attribute	Permission	Default	reproduction	the work may be reproduced	permitted	distribution	the work may be distributed, publicly displayed, and publicly performed	permitted	derivative_works	derivative works may be created and reproduced	permitted																																																				
Attribute	Permission	Default																																																																			
reproduction	the work may be reproduced	permitted																																																																			
distribution	the work may be distributed, publicly displayed, and publicly performed	permitted																																																																			
derivative_works	derivative works may be created and reproduced	permitted																																																																			
kohlhase-omdoc_TAB_015	111	■1.000	<pre>\begin{tabular}[t]{ l l l } \hline Attribute & Prohibition & Default \\ \hline commercial_use & stating that rights may be exercised for commercial purposes. & permitted \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><th>Attribute</th><th>Prohibition</th><th>Default</th></tr><tr><td>commercial_use</td><td>stating that rights may be exercised for commercial purposes.</td><td>permitted</td></tr></table>	Attribute	Prohibition	Default	commercial_use	stating that rights may be exercised for commercial purposes.	permitted																																																										
Attribute	Prohibition	Default																																																																			
commercial_use	stating that rights may be exercised for commercial purposes.	permitted																																																																			

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																																																								
kohlhase-omdoc_TAB_016	111	■ 1.000	<pre>\begin{tabular}[t]{l l l l } \hline Attribute & Requirement & Default \\ \hline notice & copyright and license notices must be kept intact & required \\ \hline attribution & credit must be given to copyright holder and/or author & required \\ \hline copyleft & derivative works, if authorized, must be licensed under the same terms as the work & required \\ \hline \end{tabular}</pre>	<table><tr><th>Attribute</th><th>Requirement</th><th>Default</th></tr><tr><td>notice</td><td>copyright and license notices must be kept intact</td><td>required</td></tr><tr><td>attribution</td><td>credit must be given to copyright holder and/or author</td><td>required</td></tr><tr><td>copyleft</td><td>derivative works, if authorized, must be licensed under the same terms as the work</td><td>required</td></tr></table>	Attribute	Requirement	Default	notice	copyright and license notices must be kept intact	required	attribution	credit must be given to copyright holder and/or author	required	copyleft	derivative works, if authorized, must be licensed under the same terms as the work	required	<table><tr><th>Attribute</th><th>Requirement</th><th>Default</th></tr><tr><td>notice</td><td>copyright and license notices must be kept intact</td><td>required</td></tr><tr><td>attribution</td><td>credit must be given to copyright holder and/or author</td><td>required</td></tr><tr><td>copyleft</td><td>derivative works, if authorized, must be licensed under the same terms as the work</td><td>required</td></tr></table>	Attribute	Requirement	Default	notice	copyright and license notices must be kept intact	required	attribution	credit must be given to copyright holder and/or author	required	copyleft	derivative works, if authorized, must be licensed under the same terms as the work	required																																																																																																																
Attribute	Requirement	Default																																																																																																																																											
notice	copyright and license notices must be kept intact	required																																																																																																																																											
attribution	credit must be given to copyright holder and/or author	required																																																																																																																																											
copyleft	derivative works, if authorized, must be licensed under the same terms as the work	required																																																																																																																																											
Attribute	Requirement	Default																																																																																																																																											
notice	copyright and license notices must be kept intact	required																																																																																																																																											
attribution	credit must be given to copyright holder and/or author	required																																																																																																																																											
copyleft	derivative works, if authorized, must be licensed under the same terms as the work	required																																																																																																																																											
kohlhase-omdoc_TAB_017	114	■ 0.986	<pre>\begin{tabular}[t]{l l l l l } \hline Element & \multicolumn{2}{l }{Attributes} & Content \\ \hline Required & Optional & \\ \hline OMOBJ & id & class, style & See Figure 13.2 \\ \hline m:math & & id, xlink:href & See Figure 13.8 \\ \hline legacy & format & xml:id, formalism & #PCDATA \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td></td></tr><tr><td>OMOBJ</td><td>id</td><td>class, style</td><td>See Figure 13.2</td></tr><tr><td>m:math</td><td></td><td>id, xlink:href</td><td>See Figure 13.8</td></tr><tr><td>legacy</td><td>format</td><td>xml:id, formalism</td><td>#PCDATA</td></tr></table>	Element	Attributes		Content		Required	Optional		OMOBJ	id	class, style	See Figure 13.2	m:math		id, xlink:href	See Figure 13.8	legacy	format	xml:id, formalism	#PCDATA	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td></td></tr><tr><td>OMOBJ</td><td>id</td><td>class, style</td><td>See Figure 13.2</td></tr><tr><td>m:math</td><td></td><td>id, xlink:href</td><td>See Figure 13.8</td></tr><tr><td>legacy</td><td>format</td><td>xml:id, formalism</td><td>#PCDATA</td></tr></table>	Element	Attributes		Content		Required	Optional		OMOBJ	id	class, style	See Figure 13.2	m:math		id, xlink:href	See Figure 13.8	legacy	format	xml:id, formalism	#PCDATA																																																																																																
Element	Attributes		Content																																																																																																																																										
	Required	Optional																																																																																																																																											
OMOBJ	id	class, style	See Figure 13.2																																																																																																																																										
m:math		id, xlink:href	See Figure 13.8																																																																																																																																										
legacy	format	xml:id, formalism	#PCDATA																																																																																																																																										
Element	Attributes		Content																																																																																																																																										
	Required	Optional																																																																																																																																											
OMOBJ	id	class, style	See Figure 13.2																																																																																																																																										
m:math		id, xlink:href	See Figure 13.8																																																																																																																																										
legacy	format	xml:id, formalism	#PCDATA																																																																																																																																										
kohlhase-omdoc_TAB_018	115	■ 0.448	<pre>\begin{tabular}[t]{l l l l l } \hline Element & \multicolumn{2}{l }{Attributes} & Content \\ \hline Required & Optional & \\ \hline OMOBJ & id & cdbase, class, style & 《OMel》? \\ \hline OMS & cd, name & id, cdbase, class, style & EMPTY \\ \hline OMV & name & id, class, style & EMPTY \\ \hline OMA & & id, cdbase, class, style & 《OMel》* \\ \hline OMBIND & & id, cdbase, class, style & 《OMel》,OMBVAR,《OMel》 \\ \hline OMBVAR & & id, class, style & (OMV OMATTR)+ \\ \hline OMFOREIGN & & id, cdbase, class, style & ANY \\ \hline OMATTR & & id, cdbase, class, style & 《OMel》 \\ \hline OMATP & & id, cdbase, class, style & (OMS,(《OMel》 OMFOREIGN))+ \\ \hline OMI & & id, class, style & [0-9]* \\ \hline OMB & & id, class, style & #PCDATA \\ \hline OMF & & id, class, style, dec, hex & #PCDATA \\ \hline OME & & id, class, style & 《OMel》? \\ \hline OMR & href & & 《OMel》? \\ \hline \end{tabular} where 《OMel》 is (OMS OMV OMI OMB OMSTR OMF OMA OMBIND OME OMATTR)</pre>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td></td></tr><tr><td>OMOBJ</td><td></td><td>id, cdbase, class, style</td><td>《OMel》?</td></tr><tr><td>OMS</td><td>cd, name</td><td>id, cdbase, class, style</td><td>EMPTY</td></tr><tr><td>OMV</td><td>name</td><td>id, class, style</td><td>EMPTY</td></tr><tr><td>OMA</td><td></td><td>id, cdbase, class, style</td><td>《OMel》*</td></tr><tr><td>OMBIND</td><td></td><td>id, cdbase, class, style</td><td>《OMel》,OMBVAR,《OMel》</td></tr><tr><td>OMBVAR</td><td></td><td>id, class, style</td><td>(OMV OMATTR)+</td></tr><tr><td>OMFOREIGN</td><td></td><td>id, cdbase, class, style</td><td>ANY</td></tr><tr><td>OMATTR</td><td></td><td>id, cdbase, class, style</td><td>《OMel》</td></tr><tr><td>OMATP</td><td></td><td>id, cdbase, class, style</td><td>(OMS,(《OMel》 OMFOREIGN))+</td></tr><tr><td>OMI</td><td></td><td>id, class, style</td><td>[0-9]*</td></tr><tr><td>OMB</td><td></td><td>id, class, style</td><td>#PCDATA</td></tr><tr><td>OMF</td><td></td><td>id, class, style, dec, hex</td><td>#PCDATA</td></tr><tr><td>OME</td><td></td><td>id, class, style</td><td>《OMel》?</td></tr><tr><td>OMR</td><td>href</td><td></td><td>《OMel》?</td></tr><tr><td colspan="4">where 《OMel》 is (OMS OMV OMI OMB OMSTR OMF OMA OMBIND OME OMATTR)</td></tr></table>	Element	Attributes		Content		Required	Optional		OMOBJ		id, cdbase, class, style	《OMel》?	OMS	cd, name	id, cdbase, class, style	EMPTY	OMV	name	id, class, style	EMPTY	OMA		id, cdbase, class, style	《OMel》*	OMBIND		id, cdbase, class, style	《OMel》,OMBVAR,《OMel》	OMBVAR		id, class, style	(OMV OMATTR)+	OMFOREIGN		id, cdbase, class, style	ANY	OMATTR		id, cdbase, class, style	《OMel》	OMATP		id, cdbase, class, style	(OMS,(《OMel》 OMFOREIGN))+	OMI		id, class, style	[0-9]*	OMB		id, class, style	#PCDATA	OMF		id, class, style, dec, hex	#PCDATA	OME		id, class, style	《OMel》?	OMR	href		《OMel》?	where 《OMel》 is (OMS OMV OMI OMB OMSTR OMF OMA OMBIND OME OMATTR)				<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td></td></tr><tr><td>OMOBJ</td><td></td><td>id, cdbase, class, style</td><td>《OMel》?</td></tr><tr><td>OMS</td><td>cd, name</td><td>id, cdbase, class, style</td><td>EMPTY</td></tr><tr><td>OMV</td><td>name</td><td>id, class, style</td><td>EMPTY</td></tr><tr><td>OMA</td><td></td><td>id, cdbase, class, style</td><td>《OMel》*</td></tr><tr><td>OMBIND</td><td></td><td>id, cdbase, class, style</td><td>《OMel》,OMBVAR,《OMel》</td></tr><tr><td>OMBVAR</td><td></td><td>id, class, style</td><td>(OMV OMATTR)+</td></tr><tr><td>OMFOREIGN</td><td></td><td>id, cdbase, class, style</td><td>ANY</td></tr><tr><td>OMATTR</td><td></td><td>id, cdbase, class, style</td><td>《OMel》</td></tr><tr><td>OMATP</td><td></td><td>id, cdbase, class, style</td><td>(OMS, (《OMel》 OMFOREIGN))+</td></tr><tr><td>OMI</td><td></td><td>id, class, style</td><td>[0-9]*</td></tr><tr><td>OMB</td><td></td><td>id, class, style</td><td>#PCDATA</td></tr><tr><td>OMF</td><td></td><td>id, class, style, dec, hex</td><td>#PCDATA</td></tr><tr><td>OME</td><td></td><td>id, class, style</td><td>《OMel》?</td></tr><tr><td>OMR</td><td>href</td><td></td><td>《OMel》?</td></tr><tr><td colspan="4">where 《OMel》 is (OMS OMV OMI OMB OMSTR OMF OMA OMBIND OME OMATTR)</td></tr></table>	Element	Attributes		Content		Required	Optional		OMOBJ		id, cdbase, class, style	《OMel》?	OMS	cd, name	id, cdbase, class, style	EMPTY	OMV	name	id, class, style	EMPTY	OMA		id, cdbase, class, style	《OMel》*	OMBIND		id, cdbase, class, style	《OMel》,OMBVAR,《OMel》	OMBVAR		id, class, style	(OMV OMATTR)+	OMFOREIGN		id, cdbase, class, style	ANY	OMATTR		id, cdbase, class, style	《OMel》	OMATP		id, cdbase, class, style	(OMS, (《OMel》 OMFOREIGN))+	OMI		id, class, style	[0-9]*	OMB		id, class, style	#PCDATA	OMF		id, class, style, dec, hex	#PCDATA	OME		id, class, style	《OMel》?	OMR	href		《OMel》?	where 《OMel》 is (OMS OMV OMI OMB OMSTR OMF OMA OMBIND OME OMATTR)			
Element	Attributes		Content																																																																																																																																										
	Required	Optional																																																																																																																																											
OMOBJ		id, cdbase, class, style	《OMel》?																																																																																																																																										
OMS	cd, name	id, cdbase, class, style	EMPTY																																																																																																																																										
OMV	name	id, class, style	EMPTY																																																																																																																																										
OMA		id, cdbase, class, style	《OMel》*																																																																																																																																										
OMBIND		id, cdbase, class, style	《OMel》,OMBVAR,《OMel》																																																																																																																																										
OMBVAR		id, class, style	(OMV OMATTR)+																																																																																																																																										
OMFOREIGN		id, cdbase, class, style	ANY																																																																																																																																										
OMATTR		id, cdbase, class, style	《OMel》																																																																																																																																										
OMATP		id, cdbase, class, style	(OMS,(《OMel》 OMFOREIGN))+																																																																																																																																										
OMI		id, class, style	[0-9]*																																																																																																																																										
OMB		id, class, style	#PCDATA																																																																																																																																										
OMF		id, class, style, dec, hex	#PCDATA																																																																																																																																										
OME		id, class, style	《OMel》?																																																																																																																																										
OMR	href		《OMel》?																																																																																																																																										
where 《OMel》 is (OMS OMV OMI OMB OMSTR OMF OMA OMBIND OME OMATTR)																																																																																																																																													
Element	Attributes		Content																																																																																																																																										
	Required	Optional																																																																																																																																											
OMOBJ		id, cdbase, class, style	《OMel》?																																																																																																																																										
OMS	cd, name	id, cdbase, class, style	EMPTY																																																																																																																																										
OMV	name	id, class, style	EMPTY																																																																																																																																										
OMA		id, cdbase, class, style	《OMel》*																																																																																																																																										
OMBIND		id, cdbase, class, style	《OMel》,OMBVAR,《OMel》																																																																																																																																										
OMBVAR		id, class, style	(OMV OMATTR)+																																																																																																																																										
OMFOREIGN		id, cdbase, class, style	ANY																																																																																																																																										
OMATTR		id, cdbase, class, style	《OMel》																																																																																																																																										
OMATP		id, cdbase, class, style	(OMS, (《OMel》 OMFOREIGN))+																																																																																																																																										
OMI		id, class, style	[0-9]*																																																																																																																																										
OMB		id, class, style	#PCDATA																																																																																																																																										
OMF		id, class, style, dec, hex	#PCDATA																																																																																																																																										
OME		id, class, style	《OMel》?																																																																																																																																										
OMR	href		《OMel》?																																																																																																																																										
where 《OMel》 is (OMS OMV OMI OMB OMSTR OMF OMA OMBIND OME OMATTR)																																																																																																																																													


Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																
kohlhase-omdoc_TAB_021	122	0.662	<pre>\begin{tabular}[t]{ l l l l } \hline Element & Attributes & & Content \\ \hline & Required & Optional & \\ \hline m:math & & id, xlink:href & ⟨CMe⟩ + \\ m:apply & & id, xlink:href & m:bvar?, ⟨CMe⟩ * \\ m:csymbol & definitionURL & id, xlink:href & m:EMPTY \\ m:ci & & id, xlink:href & #PCDATA \\ m:cn & & id, xlink:href & ([0-9] , .)(*[e([0-9] , .)*]? \\ m:bvar & & id, xlink:href & m:ci m:semantics \\ m:semantics & & id, xlink:href, definitionURL & ⟨CMe⟩,(m:annotation m:annotation-xml)* \\ m:annotation & & definitionURL, encoding & #PCDATA \\ m:annotation-xml & & definitionURL, encoding & ANY \\ \hline \multicolumn{4}{where ⟨CMe⟩ is m:apply m:csymbol m:ci m:cn m:semantics} \\ \end{tabular}</pre>	<table><tr><th>Element</th><th>Attributes</th><th></th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td></td></tr><tr><td>m:math</td><td></td><td>id,xlink:href</td><td>⟨CMe⟩ +</td></tr><tr><td>m:apply</td><td></td><td>id,xlink:href</td><td>m:bvar?, ⟨CMe⟩ *</td></tr><tr><td>m:csymbol</td><td>definitionURL</td><td>id, xlink:href</td><td>m:EMPTY</td></tr><tr><td>m:ci</td><td></td><td>id,xlink:href</td><td>#PCDATA</td></tr><tr><td>m:cn</td><td></td><td>id,xlink:href</td><td>([0-9] , .)(*[e([0-9] , .)*]?</td></tr><tr><td>m:bvar</td><td></td><td>id,xlink:href</td><td>m:ci m:semantics</td></tr><tr><td>m:semantics</td><td></td><td>id,xlink:href, definitionURL</td><td>⟨CMe⟩,(m:annotation m:annotation-xml)*</td></tr><tr><td>m:annotation</td><td></td><td>definitionURL, encoding</td><td>#PCDATA</td></tr><tr><td>m:annotation-xml</td><td></td><td>definitionURL, encoding</td><td>ANY</td></tr><tr><td colspan="4">where ⟨CMe⟩ is m:apply m:csymbol m:ci m:cn m:semantics</td></tr></table>	Element	Attributes		Content		Required	Optional		m:math		id,xlink:href	⟨CMe⟩ +	m:apply		id,xlink:href	m:bvar?, ⟨CMe⟩ *	m:csymbol	definitionURL	id, xlink:href	m:EMPTY	m:ci		id,xlink:href	#PCDATA	m:cn		id,xlink:href	([0-9] , .)(*[e([0-9] , .)*]?	m:bvar		id,xlink:href	m:ci m:semantics	m:semantics		id,xlink:href, definitionURL	⟨CMe⟩,(m:annotation m:annotation-xml)*	m:annotation		definitionURL, encoding	#PCDATA	m:annotation-xml		definitionURL, encoding	ANY	where ⟨CMe⟩ is m:apply m:csymbol m:ci m:cn m:semantics				<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td></td></tr><tr><td>m:math</td><td></td><td>id, xlink:href</td><td>⟨CMe⟩+</td></tr><tr><td>m:apply</td><td></td><td>id, xlink:href</td><td>m:bvar?,⟨CMe⟩*</td></tr><tr><td>m:csymbol</td><td>definitionURL</td><td>id, xlink:href</td><td>m:EMPTY</td></tr><tr><td>m:ci</td><td></td><td>id, xlink:href</td><td>#PCDATA</td></tr><tr><td>m:cn</td><td></td><td>id, xlink:href</td><td>([0-9] , .)(*[e([0-9] , .)*]?</td></tr><tr><td>m:bvar</td><td></td><td>id, xlink:href</td><td>m:ci m:semantics</td></tr><tr><td>m:semantics</td><td></td><td>id, xlink:href, definitionURL</td><td>⟨CMe⟩,(m:annotation m:annotation-xml)*</td></tr><tr><td>m:annotation</td><td></td><td>definitionURL, encoding</td><td>#PCDATA</td></tr><tr><td>m:annotation-xml</td><td></td><td>definitionURL, encoding</td><td>ANY</td></tr><tr><td colspan="4">where ⟨CMe⟩ is m:apply m:csymbol m:ci m:cn m:semantics</td></tr></table>	Element	Attributes		Content		Required	Optional		m:math		id, xlink:href	⟨CMe⟩+	m:apply		id, xlink:href	m:bvar?,⟨CMe⟩*	m:csymbol	definitionURL	id, xlink:href	m:EMPTY	m:ci		id, xlink:href	#PCDATA	m:cn		id, xlink:href	([0-9] , .)(*[e([0-9] , .)*]?	m:bvar		id, xlink:href	m:ci m:semantics	m:semantics		id, xlink:href, definitionURL	⟨CMe⟩,(m:annotation m:annotation-xml)*	m:annotation		definitionURL, encoding	#PCDATA	m:annotation-xml		definitionURL, encoding	ANY	where ⟨CMe⟩ is m:apply m:csymbol m:ci m:cn m:semantics			
Element	Attributes		Content																																																																																																		
	Required	Optional																																																																																																			
m:math		id,xlink:href	⟨CMe⟩ +																																																																																																		
m:apply		id,xlink:href	m:bvar?, ⟨CMe⟩ *																																																																																																		
m:csymbol	definitionURL	id, xlink:href	m:EMPTY																																																																																																		
m:ci		id,xlink:href	#PCDATA																																																																																																		
m:cn		id,xlink:href	([0-9] , .)(*[e([0-9] , .)*]?																																																																																																		
m:bvar		id,xlink:href	m:ci m:semantics																																																																																																		
m:semantics		id,xlink:href, definitionURL	⟨CMe⟩,(m:annotation m:annotation-xml)*																																																																																																		
m:annotation		definitionURL, encoding	#PCDATA																																																																																																		
m:annotation-xml		definitionURL, encoding	ANY																																																																																																		
where ⟨CMe⟩ is m:apply m:csymbol m:ci m:cn m:semantics																																																																																																					
Element	Attributes		Content																																																																																																		
	Required	Optional																																																																																																			
m:math		id, xlink:href	⟨CMe⟩+																																																																																																		
m:apply		id, xlink:href	m:bvar?,⟨CMe⟩*																																																																																																		
m:csymbol	definitionURL	id, xlink:href	m:EMPTY																																																																																																		
m:ci		id, xlink:href	#PCDATA																																																																																																		
m:cn		id, xlink:href	([0-9] , .)(*[e([0-9] , .)*]?																																																																																																		
m:bvar		id, xlink:href	m:ci m:semantics																																																																																																		
m:semantics		id, xlink:href, definitionURL	⟨CMe⟩,(m:annotation m:annotation-xml)*																																																																																																		
m:annotation		definitionURL, encoding	#PCDATA																																																																																																		
m:annotation-xml		definitionURL, encoding	ANY																																																																																																		
where ⟨CMe⟩ is m:apply m:csymbol m:ci m:cn m:semantics																																																																																																					
kohlhase-omdoc_TAB_022	128	0.889	<pre>\begin{tabular}[t]{ l l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Required & Optional & C & \\ \hline CMP & & xml:lang,id & - & ⟨math vernacular⟩ \\ FMP & & xml:id,logic & - & (assumption*, conclusion*) OMOBJ m:math legacy \\ assumption & & xml:id, inductive, class, style & + & (OMOBJ m:math legacy) \\ conclusion & & xml:id, class, style & + & (OMOBJ m:math legacy) \\ phrase & & xml:id, class, style, index, verbalizes, type & - & ⟨math vernacular⟩ \\ term & cd, name & role, xml:id, class, style & - & ⟨math vernacular⟩ \\ omtext & & xml:id, type, for, class, style, verbalizes & + & CMP+, FMP* \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th>Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td>C</td></tr><tr><td>CMP</td><td></td><td>xml:lang, id</td><td>−</td></tr><tr><td>FMP</td><td></td><td>xml:id, logic</td><td>−</td></tr><tr><td>assumption</td><td></td><td>xml:id, inductive, class, style</td><td>+</td></tr><tr><td>conclusion</td><td></td><td>xml:id, class, style</td><td>+</td></tr><tr><td>phrase</td><td></td><td>xml:id, class, style, index, verbalizes, type</td><td>−</td></tr><tr><td>term</td><td>cd, name</td><td>role, xml:id, class, style</td><td>−</td></tr><tr><td>omtext</td><td></td><td>xml:id, type, for, class, style, verbalizes</td><td>+</td></tr></table>	Element	Attributes	D	Content		Required	Optional	C	CMP		xml:lang, id	−	FMP		xml:id, logic	−	assumption		xml:id, inductive, class, style	+	conclusion		xml:id, class, style	+	phrase		xml:id, class, style, index, verbalizes, type	−	term	cd, name	role, xml:id, class, style	−	omtext		xml:id, type, for, class, style, verbalizes	+	<table><tr><th>Element</th><th>Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td>C</td></tr><tr><td>CMP</td><td></td><td>xml:lang, id</td><td>−</td></tr><tr><td>FMP</td><td></td><td>xml:id, logic</td><td>−</td></tr><tr><td>assumption</td><td></td><td>xml:id, inductive, class, style</td><td>+</td></tr><tr><td>conclusion</td><td></td><td>xml:id, class, style</td><td>+</td></tr><tr><td>phrase</td><td></td><td>xml:id, class, style, index, verbalizes, type</td><td>−</td></tr><tr><td>term</td><td>cd, name</td><td>role, xml:id, class, style</td><td>−</td></tr><tr><td>omtext</td><td></td><td>xml:id, type, for, class, style, verbalizes</td><td>+</td></tr></table>	Element	Attributes	D	Content		Required	Optional	C	CMP		xml:lang, id	−	FMP		xml:id, logic	−	assumption		xml:id, inductive, class, style	+	conclusion		xml:id, class, style	+	phrase		xml:id, class, style, index, verbalizes, type	−	term	cd, name	role, xml:id, class, style	−	omtext		xml:id, type, for, class, style, verbalizes	+																								
Element	Attributes	D	Content																																																																																																		
	Required	Optional	C																																																																																																		
CMP		xml:lang, id	−																																																																																																		
FMP		xml:id, logic	−																																																																																																		
assumption		xml:id, inductive, class, style	+																																																																																																		
conclusion		xml:id, class, style	+																																																																																																		
phrase		xml:id, class, style, index, verbalizes, type	−																																																																																																		
term	cd, name	role, xml:id, class, style	−																																																																																																		
omtext		xml:id, type, for, class, style, verbalizes	+																																																																																																		
Element	Attributes	D	Content																																																																																																		
	Required	Optional	C																																																																																																		
CMP		xml:lang, id	−																																																																																																		
FMP		xml:id, logic	−																																																																																																		
assumption		xml:id, inductive, class, style	+																																																																																																		
conclusion		xml:id, class, style	+																																																																																																		
phrase		xml:id, class, style, index, verbalizes, type	−																																																																																																		
term	cd, name	role, xml:id, class, style	−																																																																																																		
omtext		xml:id, type, for, class, style, verbalizes	+																																																																																																		

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																												
kohlhase-omdoc_TAB_023	129	0.829	<pre>\begin{tabular}[t]{ l l l l } \hline Module & Elements & Comment & see \\ MOBJ & om:OMOBJ, m:math, legacy & mathematical Objects & p. 107 \\ MTXT & phrase, term & phrase-level markup & below \\ DOC & ref, ignore & document structure & p. 89 \\ RT & p, ol, ul, dl, table, link, note, idx & rich text structure & p. 128 \\ EXT & omlet & for applets, images, ... & p. 205 \\ \hline \end{tabular}</pre>	<table><tr><th>Module</th><th>Elements</th><th>Comment</th><th>see</th></tr><tr><td>MOBJ</td><td>om:OMOBJ, m:math, legacy</td><td>mathematical Objects</td><td>p. 107</td></tr><tr><td>MTXT</td><td>phrase, term</td><td>phrase-level markup</td><td>below</td></tr><tr><td>DOC</td><td>ref, ignore</td><td>document structure</td><td>p. 89</td></tr><tr><td>RT</td><td>p, ol, ul, dl, table, link, note, idx</td><td>rich text structure</td><td>p. 128</td></tr><tr><td>EXT</td><td>omlet</td><td>for applets, images, ...</td><td>p. 205</td></tr></table>	Module	Elements	Comment	see	MOBJ	om:OMOBJ, m:math, legacy	mathematical Objects	p. 107	MTXT	phrase, term	phrase-level markup	below	DOC	ref, ignore	document structure	p. 89	RT	p, ol, ul, dl, table, link, note, idx	rich text structure	p. 128	EXT	omlet	for applets, images, ...	p. 205	<table><tr><th>Module</th><th>Elements</th><th>Comment</th><th>see</th></tr><tr><td>MOBJ</td><td>om:OMOBJ, m:math, legacy</td><td>mathematical Objects</td><td>p. 107</td></tr><tr><td>MTXT</td><td>phrase, term</td><td>phrase-level markup</td><td>below</td></tr><tr><td>DOC</td><td>ref, ignore</td><td>document structure</td><td>p. 89</td></tr><tr><td>RT</td><td>p, ol, ul, dl, table, link, note, idx</td><td>rich text structure</td><td>p. 128</td></tr><tr><td>EXT</td><td>omlet</td><td>for applets, images, ...</td><td>p. 205</td></tr></table>	Module	Elements	Comment	see	MOBJ	om:OMOBJ, m:math, legacy	mathematical Objects	p. 107	MTXT	phrase, term	phrase-level markup	below	DOC	ref, ignore	document structure	p. 89	RT	p, ol, ul, dl, table, link, note, idx	rich text structure	p. 128	EXT	omlet	for applets, images, ...	p. 205																												
Module	Elements	Comment	see																																																																														
MOBJ	om:OMOBJ, m:math, legacy	mathematical Objects	p. 107																																																																														
MTXT	phrase, term	phrase-level markup	below																																																																														
DOC	ref, ignore	document structure	p. 89																																																																														
RT	p, ol, ul, dl, table, link, note, idx	rich text structure	p. 128																																																																														
EXT	omlet	for applets, images, ...	p. 205																																																																														
Module	Elements	Comment	see																																																																														
MOBJ	om:OMOBJ, m:math, legacy	mathematical Objects	p. 107																																																																														
MTXT	phrase, term	phrase-level markup	below																																																																														
DOC	ref, ignore	document structure	p. 89																																																																														
RT	p, ol, ul, dl, table, link, note, idx	rich text structure	p. 128																																																																														
EXT	omlet	for applets, images, ...	p. 205																																																																														
kohlhase-omdoc_TAB_024	136	0.922	<pre>\begin{tabular}[t]{ l l l l } \hline Element & Optional Attributes & DC & Content \\ p & xml:id, style, class, index, verbalizes & + & «math vernacular» \\ ol & xml:id, style, class, index, verbalizes & + & li* \\ ul & xml:id, style, class, index, verbalizes & + & li* \\ li & xml:id, style, class, index, verbalizes & + & «math vernacular» \\ dl & xml:id, style, class, index, verbalizes & + & di* \\ di & xml:id, style, class, index, verbalizes & + & dt*,dd* \\ dt & xml:id, style, class, index, verbalizes & + & «math vernacular» \\ dd & xml:id, style, class, index, verbalizes & + & «math vernacular» \\ idx & (xml:id xref) & - & idt?, ide+ \\ ide & index, sort-by, see, seealso, links & - & idp* \\ idt & style, class & - & «math vernacular» \\ idp & sort-by, see, seealso, links & - & «math vernacular» \\ table & xml:id, style, class, index, verbalizes & + & tr* \\ tr & xml:id, style, class, index, verbalizes & + & td* \\ td & xml:id, style, class, index, verbalizes & + & «math vernacular» \\ th & xml:id, style, class, index, verbalizes & + & «math vernacular» \\ link & xml:id, style, class, index, verbalizes & - & «math vernacular» \\ note & type, xml:id, style, class, index, verbalizes & + & «math vernacular» \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><th>Element</th><th>Optional Attributes</th><th>DC</th><th>Content</th></tr><tr><td>p</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>«math vernacular»</td></tr><tr><td>ol</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>li*</td></tr><tr><td>ul</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>li*</td></tr><tr><td>li</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>«math vernacular»</td></tr><tr><td>dl</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>di*</td></tr><tr><td>di</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>dt*,dd*</td></tr><tr><td>dt</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>«math vernacular»</td></tr><tr><td>dd</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>«math vernacular»</td></tr><tr><td>idx</td><td>(xml:id xref)</td><td>–</td><td>idt?, ide+</td></tr><tr><td>ide</td><td>index, sort-by, see, seealso, links</td><td>–</td><td>idp*</td></tr><tr><td>idt</td><td>style, class</td><td>–</td><td>«math vernacular»</td></tr><tr><td>idp</td><td>sort-by, see, seealso, links</td><td>–</td><td>«math vernacular»</td></tr><tr><td>table</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>tr*</td></tr><tr><td>tr</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>td*</td></tr><tr><td>td</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>«math vernacular»</td></tr><tr><td>th</td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>«math vernacular»</td></tr><tr><td>link</td><td>xml:id, style, class, index, verbalizes</td><td>–</td><td>«math vernacular»</td></tr><tr><td>note</td><td>type, xml:id, style, class, index, verbalizes</td><td>+</td><td>«math vernacular»</td></tr></table>	Element	Optional Attributes	DC	Content	p	xml:id, style, class, index, verbalizes	+	«math vernacular»	ol	xml:id, style, class, index, verbalizes	+	li*	ul	xml:id, style, class, index, verbalizes	+	li*	li	xml:id, style, class, index, verbalizes	+	«math vernacular»	dl	xml:id, style, class, index, verbalizes	+	di*	di	xml:id, style, class, index, verbalizes	+	dt*,dd*	dt	xml:id, style, class, index, verbalizes	+	«math vernacular»	dd	xml:id, style, class, index, verbalizes	+	«math vernacular»	idx	(xml:id xref)	–	idt?, ide+	ide	index, sort-by, see, seealso, links	–	idp*	idt	style, class	–	«math vernacular»	idp	sort-by, see, seealso, links	–	«math vernacular»	table	xml:id, style, class, index, verbalizes	+	tr*	tr	xml:id, style, class, index, verbalizes	+	td*	td	xml:id, style, class, index, verbalizes	+	«math vernacular»	th	xml:id, style, class, index, verbalizes	+	«math vernacular»	link	xml:id, style, class, index, verbalizes	–	«math vernacular»	note	type, xml:id, style, class, index, verbalizes	+	«math vernacular»
Element	Optional Attributes	DC	Content																																																																														
p	xml:id, style, class, index, verbalizes	+	«math vernacular»																																																																														
ol	xml:id, style, class, index, verbalizes	+	li*																																																																														
ul	xml:id, style, class, index, verbalizes	+	li*																																																																														
li	xml:id, style, class, index, verbalizes	+	«math vernacular»																																																																														
dl	xml:id, style, class, index, verbalizes	+	di*																																																																														
di	xml:id, style, class, index, verbalizes	+	dt*,dd*																																																																														
dt	xml:id, style, class, index, verbalizes	+	«math vernacular»																																																																														
dd	xml:id, style, class, index, verbalizes	+	«math vernacular»																																																																														
idx	(xml:id xref)	–	idt?, ide+																																																																														
ide	index, sort-by, see, seealso, links	–	idp*																																																																														
idt	style, class	–	«math vernacular»																																																																														
idp	sort-by, see, seealso, links	–	«math vernacular»																																																																														
table	xml:id, style, class, index, verbalizes	+	tr*																																																																														
tr	xml:id, style, class, index, verbalizes	+	td*																																																																														
td	xml:id, style, class, index, verbalizes	+	«math vernacular»																																																																														
th	xml:id, style, class, index, verbalizes	+	«math vernacular»																																																																														
link	xml:id, style, class, index, verbalizes	–	«math vernacular»																																																																														
note	type, xml:id, style, class, index, verbalizes	+	«math vernacular»																																																																														

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																
kohlhase-omdoc_TAB_025	141	0.554	<pre>\begin{tabular}[t]{ l l l } \hline Definiendum & Definiens & Type \\ \hline The number 1 & \(\(1:=s(0)\)\) (1 is the successor of 0) & simple \\ \hline The exponential function \((e^{\cdot})\) & The exponential function \((e)\) is the solution to the differential equation \(\partial f=f\) where \((f(0)=1)\). & implicit \\ \hline The addition function + & Addition on the natural numbers is defined by the equations \((x+0=x)\) and \((x+s(y)=s(x+y))\). & recursive \\ \hline \end{tabular}</pre>	<table><tr><th>Definiendum</th><th>Definiens</th><th>Type</th></tr><tr><td>The number 1</td><td>$1 := s(0)$ (1 is the successor of 0)</td><td>simple</td></tr><tr><td>The exponential function $e^{\cdot}$</td><td>The exponential function e is the solution to the differential equation $\partial f = f$ [where $f(0) = 1$].</td><td>implicit</td></tr><tr><td>The addition function $+$</td><td>Addition on the natural numbers is defined by the equations $x + 0 = x$ and $x + s(y) = s(x + y)$.</td><td>recursive</td></tr></table>	Definiendum	Definiens	Type	The number 1	$1 := s(0)$ (1 is the successor of 0)	simple	The exponential function $e^{\cdot}$	The exponential function e is the solution to the differential equation $\partial f = f$ [where $f(0) = 1$].	implicit	The addition function $+$	Addition on the natural numbers is defined by the equations $x + 0 = x$ and $x + s(y) = s(x + y)$.	recursive	<table><tr><th>Definiendum</th><th>Definiens</th><th>Type</th></tr><tr><td>The number 1</td><td>$1 := s(0)$ (1 is the successor of 0)</td><td>simple</td></tr><tr><td>The exponential function $e^{\cdot}$</td><td>The exponential function $e^{\cdot}$ is the solution to the differential equation $\partial f = f$ [where $f(0) = 1$].</td><td>implicit</td></tr><tr><td>The addition function $+$</td><td>Addition on the natural numbers is defined by the equations $x + 0 = x$ and $x + s(y) = s(x + y)$.</td><td>recursive</td></tr></table>	Definiendum	Definiens	Type	The number 1	$1 := s(0)$ (1 is the successor of 0)	simple	The exponential function $e^{\cdot}$	The exponential function $e^{\cdot}$ is the solution to the differential equation $\partial f = f$ [where $f(0) = 1$].	implicit	The addition function $+$	Addition on the natural numbers is defined by the equations $x + 0 = x$ and $x + s(y) = s(x + y)$.	recursive																																																								
Definiendum	Definiens	Type																																																																																			
The number 1	$1 := s(0)$ (1 is the successor of 0)	simple																																																																																			
The exponential function $e^{\cdot}$	The exponential function e is the solution to the differential equation $\partial f = f$ [where $f(0) = 1$].	implicit																																																																																			
The addition function $+$	Addition on the natural numbers is defined by the equations $x + 0 = x$ and $x + s(y) = s(x + y)$.	recursive																																																																																			
Definiendum	Definiens	Type																																																																																			
The number 1	$1 := s(0)$ (1 is the successor of 0)	simple																																																																																			
The exponential function $e^{\cdot}$	The exponential function $e^{\cdot}$ is the solution to the differential equation $\partial f = f$ [where $f(0) = 1$].	implicit																																																																																			
The addition function $+$	Addition on the natural numbers is defined by the equations $x + 0 = x$ and $x + s(y) = s(x + y)$.	recursive																																																																																			
kohlhase-omdoc_TAB_026	142	0.286	<pre>\begin{tabular}[t]{ l l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Required & Optional & C & \\ \hline symbol & name & xml:id,role,scope,style, class & + & type* \\ \hline type & & xml:id,system,style, class & - & CMP*,\(\langle mobj \rangle\) \\ \hline axiom & & xml:id,for,type,style, class & + & CMP*,FMP* \\ \hline definition & for & xml:id,type,style, class, uniqueness, existence, consistency, exhaustivity & + & CMP*,(FMP*[requation+ \(\langle mobj \rangle\)]?,measure?, ordering?) \\ \hline requation & & xml:id,style, class & - & \(\langle mobj \rangle\),\(\langle mobj \rangle\) \\ \hline measure & & xml:id,style, class & - & \(\langle mobj \rangle\) \\ \hline ordering & & xml:id,style, class & - & \(\langle mobj \rangle\) \\ \hline where \(\langle mobj \rangle\) is(OMOBJ m:math legacy) \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th>Attributes</th><th>D</th><th>Content</th></tr><tr><th></th><th>Required</th><th>Optional</th><th>C</th></tr><tr><td>symbol</td><td>name</td><td>xml:id, role, scope, style, class</td><td>+</td></tr><tr><td>type</td><td></td><td>xml:id, system, style, class</td><td>-</td></tr><tr><td>axiom</td><td></td><td>xml:id, for, type, style, class</td><td>+</td></tr><tr><td>definition</td><td>for</td><td>xml:id, type, style, class, uniqueness, existence, consistency, exhaustivity</td><td>+</td></tr><tr><td>requation</td><td></td><td>xml:id, style, class</td><td>-</td></tr><tr><td>measure</td><td></td><td>xml:id, style, class</td><td>-</td></tr><tr><td>ordering</td><td></td><td>xml:id, style, class</td><td>-</td></tr><tr><td colspan="4">where $\langle mobj \rangle$ is (OMOBJ m:math legacy)</td></tr></table>	Element	Attributes	D	Content		Required	Optional	C	symbol	name	xml:id, role, scope, style, class	+	type		xml:id, system, style, class	-	axiom		xml:id, for, type, style, class	+	definition	for	xml:id, type, style, class, uniqueness, existence, consistency, exhaustivity	+	requation		xml:id, style, class	-	measure		xml:id, style, class	-	ordering		xml:id, style, class	-	where $\langle mobj \rangle$ is (OMOBJ m:math legacy)				<table><tr><th>Element</th><th>Attributes</th><th>D</th><th>Content</th></tr><tr><th></th><th>Required</th><th>Optional</th><th>C</th></tr><tr><td>symbol</td><td>name</td><td>xml:id, role, scope, style, class</td><td>+</td></tr><tr><td>type</td><td></td><td>xml:id, system, style, class</td><td>-</td></tr><tr><td>axiom</td><td></td><td>xml:id, for, type, style, class</td><td>+</td></tr><tr><td>definition</td><td>for</td><td>xml:id, type, style, class, uniqueness, existence, consistency, exhaustivity</td><td>+</td></tr><tr><td>requation</td><td></td><td>xml:id, style, class</td><td>-</td></tr><tr><td>measure</td><td></td><td>xml:id, style, class</td><td>-</td></tr><tr><td>ordering</td><td></td><td>xml:id, style, class</td><td>-</td></tr><tr><td colspan="4">where $\langle mobj \rangle$ is (OMOBJ m:math legacy)</td></tr></table>	Element	Attributes	D	Content		Required	Optional	C	symbol	name	xml:id, role, scope, style, class	+	type		xml:id, system, style, class	-	axiom		xml:id, for, type, style, class	+	definition	for	xml:id, type, style, class, uniqueness, existence, consistency, exhaustivity	+	requation		xml:id, style, class	-	measure		xml:id, style, class	-	ordering		xml:id, style, class	-	where $\langle mobj \rangle$ is (OMOBJ m:math legacy)			
Element	Attributes	D	Content																																																																																		
	Required	Optional	C																																																																																		
symbol	name	xml:id, role, scope, style, class	+																																																																																		
type		xml:id, system, style, class	-																																																																																		
axiom		xml:id, for, type, style, class	+																																																																																		
definition	for	xml:id, type, style, class, uniqueness, existence, consistency, exhaustivity	+																																																																																		
requation		xml:id, style, class	-																																																																																		
measure		xml:id, style, class	-																																																																																		
ordering		xml:id, style, class	-																																																																																		
where $\langle mobj \rangle$ is (OMOBJ m:math legacy)																																																																																					
Element	Attributes	D	Content																																																																																		
	Required	Optional	C																																																																																		
symbol	name	xml:id, role, scope, style, class	+																																																																																		
type		xml:id, system, style, class	-																																																																																		
axiom		xml:id, for, type, style, class	+																																																																																		
definition	for	xml:id, type, style, class, uniqueness, existence, consistency, exhaustivity	+																																																																																		
requation		xml:id, style, class	-																																																																																		
measure		xml:id, style, class	-																																																																																		
ordering		xml:id, style, class	-																																																																																		
where $\langle mobj \rangle$ is (OMOBJ m:math legacy)																																																																																					

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																
kohlhase-omdoc_TAB_027	148	0.397	<pre>\begin{tabular}[t]{l l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Required & Optional & C & \\ \hline assertion & & xml:id, for, type, theory, class, style, status, just-by & + & CMP*, FMP* \\ \hline type & system & xml:id, for, just-by, theory, class, style & - & CMP*, \langle\langle mobj \rangle\rangle, \langle\langle mobj \rangle\rangle \\ \hline example & for & xml:id, type, assertion, theory, class, style & + & CMP* \langle\langle mobj \rangle\rangle* \\ \hline alternative & for, theory, entailed-by, entails, entailed-by-thm, entails-thm & xml:id, type, theory, class, style & + & CMP*, (FMP* requation* \langle\langle mobj \rangle\rangle) \\ \hline \multicolumn{5}{ l }{where \langle\langle mobj \rangle\rangle is (OMOBJ m:math legacy)} \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th>Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td>C</td></tr><tr><td>assertion</td><td></td><td>xml:id, for, type, theory, class, style, status, just-by</td><td>+ CMP*, FMP*</td></tr><tr><td>type</td><td>system</td><td>xml:id, for, just-by, theory, class, style</td><td>- CMP*, ((mobj) , (mobj))</td></tr><tr><td>example</td><td>for</td><td>xml:id, type, assertion, theory, class, style</td><td>+ CMP* mobj *</td></tr><tr><td>alternative</td><td>for, theory, entailed-by, entails, entailed-by-thm, entails-thm</td><td>xml:id, type, theory, class, style</td><td>+ CMP*, (FMP* requation* (mobj))</td></tr></table> where $\langle\langle mobj \rangle\rangle$ is (OMOBJ m:math legacy)	Element	Attributes	D	Content		Required	Optional	C	assertion		xml:id, for, type, theory, class, style, status, just-by	+ CMP*, FMP*	type	system	xml:id, for, just-by, theory, class, style	- CMP*, ((mobj) , (mobj))	example	for	xml:id, type, assertion, theory, class, style	+ CMP* mobj *	alternative	for, theory, entailed-by, entails, entailed-by-thm, entails-thm	xml:id, type, theory, class, style	+ CMP*, (FMP* requation* (mobj))	<table><tr><th>Element</th><th>Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><td>Required</td><td>Optional</td><td>C</td></tr><tr><td>assertion</td><td></td><td>xml:id, for, type, theory, class, style, status, just-by</td><td>+ CMP*, FMP*</td></tr><tr><td>type</td><td>system</td><td>xml:id, for, just-by, theory, class, style</td><td>- CMP*, $\langle\langle mobj \rangle\rangle, \langle\langle mobj \rangle\rangle$</td></tr><tr><td>example</td><td>for</td><td>xml:id, type, assertion, theory, class, style</td><td>+ CMP* $\langle\langle mobj \rangle\rangle^*$</td></tr><tr><td>alternative</td><td>for, theory, entailed-by, entails, entailed-by-thm, entails-thm</td><td>xml:id, type, theory, class, style</td><td>+ CMP*, (FMP* requation* $\langle\langle mobj \rangle\rangle$)</td></tr></table> where $\langle\langle mobj \rangle\rangle$ is (OMOBJ m:math legacy)	Element	Attributes	D	Content		Required	Optional	C	assertion		xml:id, for, type, theory, class, style, status, just-by	+ CMP*, FMP*	type	system	xml:id, for, just-by, theory, class, style	- CMP*, $\langle\langle mobj \rangle\rangle, \langle\langle mobj \rangle\rangle$	example	for	xml:id, type, assertion, theory, class, style	+ CMP* $\langle\langle mobj \rangle\rangle^*$	alternative	for, theory, entailed-by, entails, entailed-by-thm, entails-thm	xml:id, type, theory, class, style	+ CMP*, (FMP* requation* $\langle\langle mobj \rangle\rangle$)
Element	Attributes	D	Content																																																		
	Required	Optional	C																																																		
assertion		xml:id, for, type, theory, class, style, status, just-by	+ CMP*, FMP*																																																		
type	system	xml:id, for, just-by, theory, class, style	- CMP*, ((mobj) , (mobj))																																																		
example	for	xml:id, type, assertion, theory, class, style	+ CMP* mobj *																																																		
alternative	for, theory, entailed-by, entails, entailed-by-thm, entails-thm	xml:id, type, theory, class, style	+ CMP*, (FMP* requation* (mobj))																																																		
Element	Attributes	D	Content																																																		
	Required	Optional	C																																																		
assertion		xml:id, for, type, theory, class, style, status, just-by	+ CMP*, FMP*																																																		
type	system	xml:id, for, just-by, theory, class, style	- CMP*, $\langle\langle mobj \rangle\rangle, \langle\langle mobj \rangle\rangle$																																																		
example	for	xml:id, type, assertion, theory, class, style	+ CMP* $\langle\langle mobj \rangle\rangle^*$																																																		
alternative	for, theory, entailed-by, entails, entailed-by-thm, entails-thm	xml:id, type, theory, class, style	+ CMP*, (FMP* requation* $\langle\langle mobj \rangle\rangle$)																																																		

Identifier	Page	Conf.	LaTeX source	Rendered	Image																														
kohlhase-omdoc_TAB_028	149	■ 1.000	\begin{tabular}[t]{l l} \hline Value & Explanation \\ \hline theorem, proposition & an important assertion with a proof \\ \hline \multicolumn{2}{ c }{Note that the meaning of the type (in this case the existence of a proof) is not enforced by OMDoc applications. It can be appropriate to give an assertion the type theorem, if the author knows of a proof (e.g. in the literature), but has not formalized it in OMDoc yet.} \\ \hline lemma & a less important assertion with a proof \\ \hline \multicolumn{2}{ c }{The difference of importance specified in this type is even softer than the other ones, since e.g. reusing a mathematical paper as a chapter in a larger monograph, may make it necessary to downgrade a theorem (e.g. the main theorem of the paper) and give it the status of a lemma in the overall work.} \\ \hline corollary & a simple consequence \\ \hline \multicolumn{2}{ c }{An assertion is sometimes marked as a corollary to some other statement, if the proof is considered simple. This is often the case for important theorems that are simple to get from technical lemmata.} \\ \hline postulate, conjecture & an assertion without proof or counter-example \\ \hline \multicolumn{2}{ c }{Conjectures are assertions, whose semantic value is not yet decided, but which the author considers likely to be true. In particular, there is no proof or counter-example (see Section 15.4).} \\ \hline false-conjecture & an assertion with a counter-example \\ \hline \multicolumn{2}{ c }{A conjecture that has proven to be false, i.e. it has a counter-example. Such assertions are often kept for illustration and historical purposes.} \\ \hline obligation, assumption & an assertion on which the proof of another depends \\ \hline \multicolumn{2}{ c }{These kinds of assertions are convenient during the exploration of a mathematical theory. They can be used and proven later (or assumed as an axiom).} \\ \hline formula & if everything else fails \\ \hline \multicolumn{2}{ c }{This type is the catch-all if none of the others applies.} \\ \hline \end{tabular}		<table><tr><th>Value</th><th>Explanation</th></tr><tr><td>theorem, proposition</td><td>an important assertion with a proof</td></tr><tr><td colspan="2">Note that the meaning of the type (in this case the existence of a proof) is not enforced by OMDoc applications. It can be appropriate to give an assertion the type theorem, if the author knows of a proof (e.g. in the literature), but has not formalized it in OMDoc yet.</td></tr><tr><td>lemma</td><td>a less important assertion with a proof</td></tr><tr><td colspan="2">The difference of importance specified in this type is even softer than the other ones, since e.g. reusing a mathematical paper as a chapter in a larger monograph, may make it necessary to downgrade a theorem (e.g. the main theorem of the paper) and give it the status of a lemma in the overall work.</td></tr><tr><td>corollary</td><td>a simple consequence</td></tr><tr><td colspan="2">An assertion is sometimes marked as a corollary to some other statement, if the proof is considered simple. This is often the case for important theorems that are simple to get from technical lemmata.</td></tr><tr><td>postulate, conjecture</td><td>an assertion without proof or counter-example</td></tr><tr><td colspan="2">Conjectures are assertions, whose semantic value is not yet decided, but which the author considers likely to be true. In particular, there is no proof or counter-example (see Section 15.4).</td></tr><tr><td>false-conjecture</td><td>an assertion with a counter-example</td></tr><tr><td colspan="2">A conjecture that has proven to be false, i.e. it has a counter-example. Such assertions are often kept for illustration and historical purposes.</td></tr><tr><td>obligation, assumption</td><td>an assertion on which the proof of another depends</td></tr><tr><td colspan="2">These kinds of assertions are convenient during the exploration of a mathematical theory. They can be used and proven later (or assumed as an axiom).</td></tr><tr><td>formula</td><td>if everything else fails</td></tr><tr><td colspan="2">This type is the catch-all if none of the others applies.</td></tr></table>	Value	Explanation	theorem, proposition	an important assertion with a proof	Note that the meaning of the type (in this case the existence of a proof) is not enforced by OMDoc applications. It can be appropriate to give an assertion the type theorem , if the author knows of a proof (e.g. in the literature), but has not formalized it in OMDoc yet.		lemma	a less important assertion with a proof	The difference of importance specified in this type is even softer than the other ones, since e.g. reusing a mathematical paper as a chapter in a larger monograph, may make it necessary to downgrade a theorem (e.g. the main theorem of the paper) and give it the status of a lemma in the overall work.		corollary	a simple consequence	An assertion is sometimes marked as a corollary to some other statement, if the proof is considered simple. This is often the case for important theorems that are simple to get from technical lemmata.		postulate, conjecture	an assertion without proof or counter-example	Conjectures are assertions, whose semantic value is not yet decided, but which the author considers likely to be true. In particular, there is no proof or counter-example (see Section 15.4).		false-conjecture	an assertion with a counter-example	A conjecture that has proven to be false, i.e. it has a counter-example. Such assertions are often kept for illustration and historical purposes.		obligation, assumption	an assertion on which the proof of another depends	These kinds of assertions are convenient during the exploration of a mathematical theory. They can be used and proven later (or assumed as an axiom).		formula	if everything else fails	This type is the catch-all if none of the others applies.	
				Value	Explanation																														
theorem, proposition	an important assertion with a proof																																		
Note that the meaning of the type (in this case the existence of a proof) is not enforced by OMDoc applications. It can be appropriate to give an assertion the type theorem , if the author knows of a proof (e.g. in the literature), but has not formalized it in OMDoc yet.																																			
lemma	a less important assertion with a proof																																		
The difference of importance specified in this type is even softer than the other ones, since e.g. reusing a mathematical paper as a chapter in a larger monograph, may make it necessary to downgrade a theorem (e.g. the main theorem of the paper) and give it the status of a lemma in the overall work.																																			
corollary	a simple consequence																																		
An assertion is sometimes marked as a corollary to some other statement, if the proof is considered simple. This is often the case for important theorems that are simple to get from technical lemmata.																																			
postulate, conjecture	an assertion without proof or counter-example																																		
Conjectures are assertions, whose semantic value is not yet decided, but which the author considers likely to be true. In particular, there is no proof or counter-example (see Section 15.4).																																			
false-conjecture	an assertion with a counter-example																																		
A conjecture that has proven to be false, i.e. it has a counter-example. Such assertions are often kept for illustration and historical purposes.																																			
obligation, assumption	an assertion on which the proof of another depends																																		
These kinds of assertions are convenient during the exploration of a mathematical theory. They can be used and proven later (or assumed as an axiom).																																			
formula	if everything else fails																																		
This type is the catch-all if none of the others applies.																																			


Identifier	Page	Conf.	LaTeX source	Rendered	Image																										
kohlhase-omdoc_TAB_029	150	1.000	<pre>\begin{tabular}[t]{ l l } \hline status & just-by points to \\ \hline tautology & Proof of $\mathcal{F}$ \\ & All T-interpretations satisfy $\mathcal{A}$ and some $\mathcal{C}_i$ \\ \hline tautologous-conclusion & Proof of $\mathcal{F}_c$. \\ & All T-interpretations satisfy some $\mathcal{C}_j$ \\ \hline equivalent & Proofs of $\mathcal{F}$ and $\mathcal{F}^{-1}$ \\ & $\mathcal{A}$ and $\mathcal{C}$ have the same T-models (and there are some) \\ \hline theorem & Proof of $\mathcal{F}$ \\ & All T-models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$ \\ \hline satisfiable & Model of $\mathcal{A}$ and some $\mathcal{C}_i$ \\ & Some T-models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$ \\ \hline contradictory-axioms & Refutation of $\mathcal{A}$ \\ & There are no T-models of $\mathcal{A}$ \\ \hline no-consequence & T-model of $\mathcal{A}$ and some $\mathcal{C}_i$, T-model of $\mathcal{A} \cup \overline{\mathcal{C}}$. \\ & Some T-models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$, some satisfy $\overline{\mathcal{C}}$ \\ \hline counter-satisfiable & Model of $\mathcal{A} \cup \overline{\mathcal{C}}$ \\ & Some T-models of $\mathcal{A}$ (and there are some) satisfy $\overline{\mathcal{C}}$ \\ \hline counter-theorem & Proof of $\overline{\mathcal{C}}$ from $\mathcal{A}$ \\ & All T-models of $\mathcal{A}$ (and there are some) satisfy $\overline{\mathcal{C}}$ \\ \hline counter-equivalent & Proof of $\overline{\mathcal{C}}$ from $\mathcal{A}$ and proof of $\mathcal{A}$ from $\overline{\mathcal{C}}$ \\ & $\mathcal{A}$ and $\overline{\mathcal{C}}$ have the same T-models (and there are some) \\ \hline unsatisfiable-conclusion & Proof of $\overline{\mathcal{C}}$ \\ & All T-interpretations satisfy $\overline{\mathcal{C}}$ \\ \hline unsatisfiable & Proof of $\neg \mathcal{F}$ \\ & All T-interpretations satisfy $\mathcal{A}$ and $\overline{\mathcal{C}}$ \\ \hline \end{tabular}</pre> Where $\mathcal{F}$ is an assertion whose FMP has assumption elements $\mathcal{A}_1, \dots, \mathcal{A}_n$ and conclusion elements $\mathcal{C}_1, \dots, \mathcal{C}_m$. Furthermore, let $\mathcal{A} = \{\mathcal{A}_1, \dots, \mathcal{A}_n\}$ and $\mathcal{C} = \{\mathcal{C}_1, \dots, \mathcal{C}_m\}$, and $\mathcal{F}^{-1}$ be the sequent that has the $\mathcal{C}_i$ as assumptions and the $\mathcal{A}_i$ as conclusions. Finally, let $\overline{\mathcal{C}} = \{\overline{\mathcal{C}}_1, \dots, \overline{\mathcal{C}}_m\}$, where $\overline{\mathcal{C}}_i$ is a negation of $\mathcal{C}_i$.		<table><tr><td>status</td><td>just-by points to</td></tr><tr><td>tautology</td><td>Proof of $\mathcal{F}$ All T-interpretations satisfy $\mathcal{A}$ and some $\mathcal{C}_i$</td></tr><tr><td>tautologous-conclusion</td><td>Proof of $\mathcal{F}_c$. All T-interpretations satisfy some $\mathcal{C}_j$</td></tr><tr><td>equivalent</td><td>Proofs of $\mathcal{F}$ and $\mathcal{F}^{-1}$ $\mathcal{A}$ and $\mathcal{C}$ have the same T-models (and there are some)</td></tr><tr><td>theorem</td><td>Proof of $\mathcal{F}$ All T-models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$</td></tr><tr><td>satisfiable</td><td>Model of $\mathcal{A}$ and some $\mathcal{C}_i$ Some T-models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$</td></tr><tr><td>contradictory-axioms</td><td>Refutation of $\mathcal{A}$ There are no T-models of $\mathcal{A}$</td></tr><tr><td>no-consequence</td><td>T-model of $\mathcal{A}$ and some $\mathcal{C}_i$, T-model of $\mathcal{A} \cup \overline{\mathcal{C}}$. Some T-models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$, some satisfy $\overline{\mathcal{C}}$</td></tr><tr><td>counter-satisfiable</td><td>Model of $\mathcal{A} \cup \overline{\mathcal{C}}$ Some T-models of $\mathcal{A}$ (and there are some) satisfy $\overline{\mathcal{C}}$</td></tr><tr><td>counter-theorem</td><td>Proof of $\overline{\mathcal{C}}$ from $\mathcal{A}$ All T-models of $\mathcal{A}$ (and there are some) satisfy $\overline{\mathcal{C}}$</td></tr><tr><td>counter-equivalent</td><td>Proof of $\overline{\mathcal{C}}$ from $\mathcal{A}$ and proof of $\mathcal{A}$ from $\overline{\mathcal{C}}$ $\mathcal{A}$ and $\overline{\mathcal{C}}$ have the same T-models (and there are some)</td></tr><tr><td>unsatisfiable-conclusion</td><td>Proof of $\overline{\mathcal{C}}$ All T-interpretations satisfy $\overline{\mathcal{C}}$</td></tr><tr><td>unsatisfiable</td><td>Proof of $\neg \mathcal{F}$ All T-interpretations satisfy $\mathcal{A}$ and $\overline{\mathcal{C}}$</td></tr></table> Where $\mathcal{F}$ is an assertion whose FMP has assumption elements $\mathcal{A}_1, \dots, \mathcal{A}_n$ and conclusion elements $\mathcal{C}_1, \dots, \mathcal{C}_m$. Furthermore, let $\mathcal{A} = \{\mathcal{A}_1, \dots, \mathcal{A}_n\}$ and $\mathcal{C} = \{\mathcal{C}_1, \dots, \mathcal{C}_m\}$, and $\mathcal{F}^{-1}$ be the sequent that has the $\mathcal{C}_i$ as assumptions and the $\mathcal{A}_i$ as conclusions. Finally, let $\overline{\mathcal{C}} = \{\overline{\mathcal{C}}_1, \dots, \overline{\mathcal{C}}_m\}$, where $\overline{\mathcal{C}}_i$ is a negation of $\mathcal{C}_i$.	status	just-by points to	tautology	Proof of $\mathcal{F}$ All T -interpretations satisfy $\mathcal{A}$ and some $\mathcal{C}_i$	tautologous-conclusion	Proof of $\mathcal{F}_c$. All T -interpretations satisfy some $\mathcal{C}_j$	equivalent	Proofs of $\mathcal{F}$ and $\mathcal{F}^{-1}$ $\mathcal{A}$ and $\mathcal{C}$ have the same T -models (and there are some)	theorem	Proof of $\mathcal{F}$ All T -models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$	satisfiable	Model of $\mathcal{A}$ and some $\mathcal{C}_i$ Some T -models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$	contradictory-axioms	Refutation of $\mathcal{A}$ There are no T -models of $\mathcal{A}$	no-consequence	T -model of $\mathcal{A}$ and some $\mathcal{C}_i$, T -model of $\mathcal{A} \cup \overline{\mathcal{C}}$. Some T -models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$, some satisfy $\overline{\mathcal{C}}$	counter-satisfiable	Model of $\mathcal{A} \cup \overline{\mathcal{C}}$ Some T -models of $\mathcal{A}$ (and there are some) satisfy $\overline{\mathcal{C}}$	counter-theorem	Proof of $\overline{\mathcal{C}}$ from $\mathcal{A}$ All T -models of $\mathcal{A}$ (and there are some) satisfy $\overline{\mathcal{C}}$	counter-equivalent	Proof of $\overline{\mathcal{C}}$ from $\mathcal{A}$ and proof of $\mathcal{A}$ from $\overline{\mathcal{C}}$ $\mathcal{A}$ and $\overline{\mathcal{C}}$ have the same T -models (and there are some)	unsatisfiable-conclusion	Proof of $\overline{\mathcal{C}}$ All T -interpretations satisfy $\overline{\mathcal{C}}$	unsatisfiable	Proof of $\neg \mathcal{F}$ All T -interpretations satisfy $\mathcal{A}$ and $\overline{\mathcal{C}}$
status	just-by points to																														
tautology	Proof of $\mathcal{F}$ All T -interpretations satisfy $\mathcal{A}$ and some $\mathcal{C}_i$																														
tautologous-conclusion	Proof of $\mathcal{F}_c$. All T -interpretations satisfy some $\mathcal{C}_j$																														
equivalent	Proofs of $\mathcal{F}$ and $\mathcal{F}^{-1}$ $\mathcal{A}$ and $\mathcal{C}$ have the same T -models (and there are some)																														
theorem	Proof of $\mathcal{F}$ All T -models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$																														
satisfiable	Model of $\mathcal{A}$ and some $\mathcal{C}_i$ Some T -models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$																														
contradictory-axioms	Refutation of $\mathcal{A}$ There are no T -models of $\mathcal{A}$																														
no-consequence	T -model of $\mathcal{A}$ and some $\mathcal{C}_i$, T -model of $\mathcal{A} \cup \overline{\mathcal{C}}$. Some T -models of $\mathcal{A}$ (and there are some) satisfy some $\mathcal{C}_i$, some satisfy $\overline{\mathcal{C}}$																														
counter-satisfiable	Model of $\mathcal{A} \cup \overline{\mathcal{C}}$ Some T -models of $\mathcal{A}$ (and there are some) satisfy $\overline{\mathcal{C}}$																														
counter-theorem	Proof of $\overline{\mathcal{C}}$ from $\mathcal{A}$ All T -models of $\mathcal{A}$ (and there are some) satisfy $\overline{\mathcal{C}}$																														
counter-equivalent	Proof of $\overline{\mathcal{C}}$ from $\mathcal{A}$ and proof of $\mathcal{A}$ from $\overline{\mathcal{C}}$ $\mathcal{A}$ and $\overline{\mathcal{C}}$ have the same T -models (and there are some)																														
unsatisfiable-conclusion	Proof of $\overline{\mathcal{C}}$ All T -interpretations satisfy $\overline{\mathcal{C}}$																														
unsatisfiable	Proof of $\neg \mathcal{F}$ All T -interpretations satisfy $\mathcal{A}$ and $\overline{\mathcal{C}}$																														
18																															

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																										
kohlhase-omdoc_TAB_030	156	0.939	<pre>\begin{tabular}[t]{ l l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Req. & Optional & C & \\ \hline theory & & xml:id, class, style, cdbase, cdversion, cdrevision, cdstatus, cdurl, cdreviewdate & + & (⟨⟨top+thc⟩ imports)* \\ \hline imports & from & id, type, class, style & + & \\ \hline tgroup & & xml:id, modules, type, class, style & + & (⟨⟨top+thc⟩⟩)* \\ \hline where ⟨⟨top+thc⟩⟩ stands for top-level and theory-constitutive elements \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><th>C</th><td></td></tr><tr><td>theory</td><td></td><td>xml:id, class, style, cdbase, cdversion, cdrevision, cdstatus, cdurl, cdreviewdate</td><td>+</td><td>(⟨⟨top+thc⟩ imports)*</td></tr><tr><td>imports</td><td>from</td><td>id, type, class, style</td><td>+</td><td></td></tr><tr><td>tgroup</td><td></td><td>xml:id, modules, type, class, style</td><td>+</td><td>(⟨⟨top+thc⟩⟩)*</td></tr><tr><td colspan="5">where ⟨⟨top+thc⟩⟩ stands for top-level and theory-constitutive elements</td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		theory		xml:id, class, style, cdbase, cdversion, cdrevision, cdstatus, cdurl, cdreviewdate	+	(⟨⟨top+thc⟩ imports)*	imports	from	id, type, class, style	+		tgroup		xml:id, modules, type, class, style	+	(⟨⟨top+thc⟩⟩)*	where ⟨⟨top+thc⟩⟩ stands for top-level and theory-constitutive elements																																																																
Element	Attributes		D	Content																																																																																											
	Req.	Optional	C																																																																																												
theory		xml:id, class, style, cdbase, cdversion, cdrevision, cdstatus, cdurl, cdreviewdate	+	(⟨⟨top+thc⟩ imports)*																																																																																											
imports	from	id, type, class, style	+																																																																																												
tgroup		xml:id, modules, type, class, style	+	(⟨⟨top+thc⟩⟩)*																																																																																											
where ⟨⟨top+thc⟩⟩ stands for top-level and theory-constitutive elements																																																																																															
kohlhase-omdoc_TAB_031	162	0.989	<pre>\begin{tabular}[t]{ l l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Req. & Optional & C & \\ \hline adt & & xml:id,class,style, parameters & + & sortdef+ \\ \hline sortdef & name & type,role,scope,class, style & + & (constructor insert)*,recognizer? \\ \hline constructor & name & type,scope,class,style & + & argument* \\ \hline argument & & & + & type,selector? \\ \hline insert & for & & - & \\ \hline selector & name & type,scope,role,total, class,style & + & EMPTY \\ \hline recognizer & name & type,scope,role,class, style & + & \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><th>C</th><td></td></tr><tr><td>adt</td><td></td><td>xml:id,class,style, parameters</td><td>+</td><td>sortdef+</td></tr><tr><td>sortdef</td><td>name</td><td>type,role,scope,class, style</td><td>+</td><td>(constructor insert)*,recognizer?</td></tr><tr><td>constructor</td><td>name</td><td>type,scope,class,style</td><td>+</td><td>argument*</td></tr><tr><td>argument</td><td></td><td></td><td>+</td><td>type,selector?</td></tr><tr><td>insert</td><td>for</td><td></td><td>-</td><td></td></tr><tr><td>selector</td><td>name</td><td>type,scope,role,total, class,style</td><td>+</td><td>EMPTY</td></tr><tr><td>recognizer</td><td>name</td><td>type,scope,role,class, style</td><td>+</td><td></td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		adt		xml:id,class,style, parameters	+	sortdef+	sortdef	name	type,role,scope,class, style	+	(constructor insert)*,recognizer?	constructor	name	type,scope,class,style	+	argument*	argument			+	type,selector?	insert	for		-		selector	name	type,scope,role,total, class,style	+	EMPTY	recognizer	name	type,scope,role,class, style	+		<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><th>C</th><td></td></tr><tr><td>adt</td><td></td><td>xml:id, class, style, parameters</td><td>+</td><td>sortdef+</td></tr><tr><td>sortdef</td><td>name</td><td>type, role, scope, class, style</td><td>+</td><td>(constructor insert)*, recognizer?</td></tr><tr><td>constructor</td><td>name</td><td>type, scope, class, style</td><td>+</td><td>argument*</td></tr><tr><td>argument</td><td></td><td></td><td>+</td><td>type, selector?</td></tr><tr><td>insert</td><td>for</td><td></td><td>−</td><td></td></tr><tr><td>selector</td><td>name</td><td>type, scope, role, total, class, style</td><td>+</td><td>EMPTY</td></tr><tr><td>recognizer</td><td>name</td><td>type, scope, role, class, style</td><td>+</td><td></td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		adt		xml:id, class, style, parameters	+	sortdef+	sortdef	name	type, role, scope, class, style	+	(constructor insert)*, recognizer?	constructor	name	type, scope, class, style	+	argument*	argument			+	type, selector?	insert	for		−		selector	name	type, scope, role, total, class, style	+	EMPTY	recognizer	name	type, scope, role, class, style	+	
Element	Attributes		D	Content																																																																																											
	Req.	Optional	C																																																																																												
adt		xml:id,class,style, parameters	+	sortdef+																																																																																											
sortdef	name	type,role,scope,class, style	+	(constructor insert)*,recognizer?																																																																																											
constructor	name	type,scope,class,style	+	argument*																																																																																											
argument			+	type,selector?																																																																																											
insert	for		-																																																																																												
selector	name	type,scope,role,total, class,style	+	EMPTY																																																																																											
recognizer	name	type,scope,role,class, style	+																																																																																												
Element	Attributes		D	Content																																																																																											
	Req.	Optional	C																																																																																												
adt		xml:id, class, style, parameters	+	sortdef+																																																																																											
sortdef	name	type, role, scope, class, style	+	(constructor insert)*, recognizer?																																																																																											
constructor	name	type, scope, class, style	+	argument*																																																																																											
argument			+	type, selector?																																																																																											
insert	for		−																																																																																												
selector	name	type, scope, role, total, class, style	+	EMPTY																																																																																											
recognizer	name	type, scope, role, class, style	+																																																																																												
kohlhase-omdoc_TAB_032	168	0.979	<pre>\begin{tabular}[t]{ l l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Req. & Optional & C & \\ \hline proof & for & theory, xml:id, class, style & + & (omtext derive hypothesis symbol definition)* \\ \hline proofobject & & xml:id, for, class, style, theory & + & CMP*, (OMOBJ m:math legacy) \\ \hline hypothesis & & xml:id, class, style, inductive & - & CMP*, FMP* \\ \hline derive & & xml:id, class, style, type & - & CMP*, FMP*, method? \\ \hline method & & xref & - & (OMOBJ m:math legacy premise proof proofobject)* \\ \hline premise & xref & & - & EMPTY \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><th>C</th><td></td></tr><tr><td>proof</td><td>for</td><td>theory, xml:id, class, style</td><td>+</td><td>(omtext derive hypothesis symbol definition)*</td></tr><tr><td>proofobject</td><td></td><td>xml:id, for, class, style, theory</td><td>+</td><td>CMP*, (OMOBJ m:math legacy)</td></tr><tr><td>hypothesis</td><td></td><td>xml:id, class, style, inductive</td><td>−</td><td>CMP*, FMP*</td></tr><tr><td>derive</td><td></td><td>xml:id, class, style, type</td><td>−</td><td>CMP*, FMP*, method?</td></tr><tr><td>method</td><td></td><td>xref</td><td>−</td><td>(OMOBJ m:math legacy premise proof proofobject)*</td></tr><tr><td>premise</td><td>xref</td><td></td><td>−</td><td>EMPTY</td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		proof	for	theory, xml:id, class, style	+	(omtext derive hypothesis symbol definition)*	proofobject		xml:id, for, class, style, theory	+	CMP*, (OMOBJ m:math legacy)	hypothesis		xml:id, class, style, inductive	−	CMP*, FMP*	derive		xml:id, class, style, type	−	CMP*, FMP*, method?	method		xref	−	(OMOBJ m:math legacy premise proof proofobject)*	premise	xref		−	EMPTY	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><th>C</th><td></td></tr><tr><td>proof</td><td>for</td><td>theory, xml:id, class, style</td><td>+</td><td>(omtext derive hypothesis symbol definition)*</td></tr><tr><td>proofobject</td><td></td><td>xml:id, for, class, style, theory</td><td>+</td><td>CMP*, (OMOBJ m:math legacy)</td></tr><tr><td>hypothesis</td><td></td><td>xml:id, class, style, inductive</td><td>−</td><td>CMP*, FMP*</td></tr><tr><td>derive</td><td></td><td>xml:id, class, style, type</td><td>−</td><td>CMP*, FMP*, method?</td></tr><tr><td>method</td><td></td><td>xref</td><td>−</td><td>(OMOBJ m:math legacy premise proof proofobject)*</td></tr><tr><td>premise</td><td>xref</td><td></td><td>−</td><td>EMPTY</td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		proof	for	theory, xml:id, class, style	+	(omtext derive hypothesis symbol definition)*	proofobject		xml:id, for, class, style, theory	+	CMP*, (OMOBJ m:math legacy)	hypothesis		xml:id, class, style, inductive	−	CMP*, FMP*	derive		xml:id, class, style, type	−	CMP*, FMP*, method?	method		xref	−	(OMOBJ m:math legacy premise proof proofobject)*	premise	xref		−	EMPTY										
Element	Attributes		D	Content																																																																																											
	Req.	Optional	C																																																																																												
proof	for	theory, xml:id, class, style	+	(omtext derive hypothesis symbol definition)*																																																																																											
proofobject		xml:id, for, class, style, theory	+	CMP*, (OMOBJ m:math legacy)																																																																																											
hypothesis		xml:id, class, style, inductive	−	CMP*, FMP*																																																																																											
derive		xml:id, class, style, type	−	CMP*, FMP*, method?																																																																																											
method		xref	−	(OMOBJ m:math legacy premise proof proofobject)*																																																																																											
premise	xref		−	EMPTY																																																																																											
Element	Attributes		D	Content																																																																																											
	Req.	Optional	C																																																																																												
proof	for	theory, xml:id, class, style	+	(omtext derive hypothesis symbol definition)*																																																																																											
proofobject		xml:id, for, class, style, theory	+	CMP*, (OMOBJ m:math legacy)																																																																																											
hypothesis		xml:id, class, style, inductive	−	CMP*, FMP*																																																																																											
derive		xml:id, class, style, type	−	CMP*, FMP*, method?																																																																																											
method		xref	−	(OMOBJ m:math legacy premise proof proofobject)*																																																																																											
premise	xref		−	EMPTY																																																																																											

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																												
kohlhase-omdoc_TAB_033	178	0.974	<pre>\begin{tabular}[t]{ l l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Required & Optional & C & \\ \hline theory & & xml:id, class, style & + & ((\langle\langle top-level \rangle\rangle) imports inclusion)* \\ \hline imports & from & xml:id, type, class, style, conservativity, conservativity-just & + & morphism? \\ \hline morphism & & xml:id, base, class, style, type, hiding, consistency, exhaustivity & - & reequation*, measure?, ordering? \\ \hline inclusion & via & xml:id, conservativity, conservativity-just & - & EMPTY \\ \hline theory-inclusion & from, to & xml:id, class, style, conservativity, conservativity-just & + & (CMP*,FMP*, morphism, obligation*) \\ \hline axiom-inclusion & from, to & xml:id, class, style, conservativity, conservativity-just & + & morphism?, obligation* \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Required</th><th>Optional</th><th>C</th><td></td></tr><tr><td>theory</td><td></td><td>xml:id, class, style</td><td>+</td><td>((\langle\langle top-level \rangle\rangle) imports inclusion)*</td></tr><tr><td>imports</td><td>from</td><td>xml:id, type, class, style, conservativity, conservativity-just</td><td>+</td><td>morphism?</td></tr><tr><td>morphism</td><td></td><td>xml:id, base, class, style, type, hiding, consistency, exhaustivity</td><td>−</td><td>requation*, measure?, ordering?</td></tr><tr><td>inclusion</td><td>via</td><td>xml:id, conservativity, conservativity-just</td><td>−</td><td>EMPTY</td></tr><tr><td>theory-inclusion</td><td>from, to</td><td>xml:id, class, style, conservativity, conservativity-just</td><td>+</td><td>(CMP*,FMP*, morphism, obligation*)</td></tr><tr><td>axiom-inclusion</td><td>from, to</td><td>xml:id, class, style, conservativity, conservativity-just</td><td>+</td><td>morphism?, obligation*</td></tr></table>	Element	Attributes		D	Content		Required	Optional	C		theory		xml:id, class, style	+	((\langle\langle top-level \rangle\rangle) imports inclusion)*	imports	from	xml:id, type, class, style, conservativity, conservativity-just	+	morphism?	morphism		xml:id, base, class, style, type, hiding, consistency, exhaustivity	−	requation*, measure?, ordering?	inclusion	via	xml:id, conservativity, conservativity-just	−	EMPTY	theory-inclusion	from, to	xml:id, class, style, conservativity, conservativity-just	+	(CMP*,FMP*, morphism, obligation*)	axiom-inclusion	from, to	xml:id, class, style, conservativity, conservativity-just	+	morphism?, obligation*																				
Element	Attributes		D	Content																																																													
	Required	Optional	C																																																														
theory		xml:id, class, style	+	((\langle\langle top-level \rangle\rangle) imports inclusion)*																																																													
imports	from	xml:id, type, class, style, conservativity, conservativity-just	+	morphism?																																																													
morphism		xml:id, base, class, style, type, hiding, consistency, exhaustivity	−	requation*, measure?, ordering?																																																													
inclusion	via	xml:id, conservativity, conservativity-just	−	EMPTY																																																													
theory-inclusion	from, to	xml:id, class, style, conservativity, conservativity-just	+	(CMP*,FMP*, morphism, obligation*)																																																													
axiom-inclusion	from, to	xml:id, class, style, conservativity, conservativity-just	+	morphism?, obligation*																																																													
kohlhase-omdoc_TAB_034	189	0.515	<pre>\begin{tabular}[t]{ l l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Required & Optional & C & \\ \hline decomposition & links & & - & EMPTY \\ \hline path-just & local, globals & for & - & EMPTY \\ \hline theory-inclusion & from, to, by & xml:id, class, style & + & (CMP*,FMP*, morphism, (decomposition* obligation*)) \\ \hline axiom-inclusion & from, to & xml:id, class, style & + & morphism?, (path-just* obligation*) \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Required</th><th>Optional</th><th>C</th><td></td></tr><tr><td>decomposition</td><td>links</td><td></td><td>-</td><td>EMPTY</td></tr><tr><td>path-just</td><td>local, globals</td><td>for</td><td>-</td><td>EMPTY</td></tr><tr><td>theory-inclusion</td><td>from, to, by</td><td>xml:id, class, style</td><td>+</td><td>(CMP*,FMP*, morphism, (decomposition* obligation*))</td></tr><tr><td>axiom-inclusion</td><td>from, to</td><td>xml:id, class, style</td><td>+</td><td>morphism?, (path-just* obligation*)</td></tr></table>	Element	Attributes		D	Content		Required	Optional	C		decomposition	links		-	EMPTY	path-just	local, globals	for	-	EMPTY	theory-inclusion	from, to, by	xml:id, class, style	+	(CMP*,FMP*, morphism, (decomposition* obligation*))	axiom-inclusion	from, to	xml:id, class, style	+	morphism?, (path-just* obligation*)	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Required</th><th>Optional</th><th>C</th><td></td></tr><tr><td>decomposition</td><td>links</td><td></td><td>−</td><td>EMPTY</td></tr><tr><td>path-just</td><td>local, globals</td><td>for</td><td>−</td><td>EMPTY</td></tr><tr><td>theory-inclusion</td><td>from, to, by</td><td>xml:id, class, style</td><td>+</td><td>(CMP*,FMP*, morphism, (decomposition* obligation*))</td></tr><tr><td>axiom-inclusion</td><td>from, to</td><td>xml:id, class, style</td><td>+</td><td>morphism?, (path-just* obligation*)</td></tr></table>	Element	Attributes		D	Content		Required	Optional	C		decomposition	links		−	EMPTY	path-just	local, globals	for	−	EMPTY	theory-inclusion	from, to, by	xml:id, class, style	+	(CMP*,FMP*, morphism, (decomposition* obligation*))	axiom-inclusion	from, to	xml:id, class, style	+	morphism?, (path-just* obligation*)
Element	Attributes		D	Content																																																													
	Required	Optional	C																																																														
decomposition	links		-	EMPTY																																																													
path-just	local, globals	for	-	EMPTY																																																													
theory-inclusion	from, to, by	xml:id, class, style	+	(CMP*,FMP*, morphism, (decomposition* obligation*))																																																													
axiom-inclusion	from, to	xml:id, class, style	+	morphism?, (path-just* obligation*)																																																													
Element	Attributes		D	Content																																																													
	Required	Optional	C																																																														
decomposition	links		−	EMPTY																																																													
path-just	local, globals	for	−	EMPTY																																																													
theory-inclusion	from, to, by	xml:id, class, style	+	(CMP*,FMP*, morphism, (decomposition* obligation*))																																																													
axiom-inclusion	from, to	xml:id, class, style	+	morphism?, (path-just* obligation*)																																																													

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																
kohlhase-omdoc_TAB_035	192	■ 1.000	<pre>\begin{tabular}[t]{ l l l l } \hline Element & \multicolumn{2}{ l }{Attributes} & Content \\ \hline & Required & Optional & \\ \hline omstyle & element & for, xml:id, xref, class, style & (style xslt)* \\ \hline presentation & for & xml:id, xref, fixity, role, lbrack, rbrack, separator, bracket-style, class, style, precedence, crossref-symbol & (use xslt style)* \\ \hline xslt & format & xml:lang, requires, xref & XSLT fragment \\ \hline use & format & xml:lang, requires, fixity, lbrack, rbrack, separator, element, attributes, crossref-symbol & (element text recurse map value-of)* \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><th>Required</th><th>Optional</th><td></td></tr><tr><td>omstyle</td><td>element</td><td>for, xml:id, xref, class, style</td><td>(style xslt)*</td></tr><tr><td>presentation</td><td>for</td><td>xml:id, xref, fixity, role, lbrack, rbrack, separator, bracket-style, class, style, precedence, crossref-symbol</td><td>(use xslt style)*</td></tr><tr><td>xslt</td><td>format</td><td>xml:lang, requires, xref</td><td>XSLT fragment</td></tr><tr><td>use</td><td>format</td><td>xml:lang, requires, fixity, lbrack, rbrack, separator, element, attributes, crossref-symbol</td><td>(element text recurse map value-of)*</td></tr></table>	Element	Attributes		Content		Required	Optional		omstyle	element	for, xml:id, xref, class, style	(style xslt)*	presentation	for	xml:id, xref, fixity, role, lbrack, rbrack, separator, bracket-style, class, style, precedence, crossref-symbol	(use xslt style)*	xslt	format	xml:lang, requires, xref	XSLT fragment	use	format	xml:lang, requires, fixity, lbrack, rbrack, separator, element, attributes, crossref-symbol	(element text recurse map value-of)*	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><th>Required</th><th>Optional</th><td></td></tr><tr><td>omstyle</td><td>element</td><td>for, xml:id, xref, class, style</td><td>(style xslt)*</td></tr><tr><td>presentation</td><td>for</td><td>xml:id, xref, fixity, role, lbrack, rbrack, separator, bracket-style, class, style, precedence, crossref-symbol</td><td>(use xslt style)*</td></tr><tr><td>xslt</td><td>format</td><td>xml:lang, requires, xref</td><td>XSLT fragment</td></tr><tr><td>use</td><td>format</td><td>xml:lang, requires, fixity, lbrack, rbrack, separator, element, attributes, crossref-symbol</td><td>(element text recurse map value-of)*</td></tr></table>	Element	Attributes		Content		Required	Optional		omstyle	element	for, xml:id, xref, class, style	(style xslt)*	presentation	for	xml:id, xref, fixity, role, lbrack, rbrack, separator, bracket-style, class, style, precedence, crossref-symbol	(use xslt style)*	xslt	format	xml:lang, requires, xref	XSLT fragment	use	format	xml:lang, requires, fixity, lbrack, rbrack, separator, element, attributes, crossref-symbol	(element text recurse map value-of)*																																
Element	Attributes		Content																																																																																		
	Required	Optional																																																																																			
omstyle	element	for, xml:id, xref, class, style	(style xslt)*																																																																																		
presentation	for	xml:id, xref, fixity, role, lbrack, rbrack, separator, bracket-style, class, style, precedence, crossref-symbol	(use xslt style)*																																																																																		
xslt	format	xml:lang, requires, xref	XSLT fragment																																																																																		
use	format	xml:lang, requires, fixity, lbrack, rbrack, separator, element, attributes, crossref-symbol	(element text recurse map value-of)*																																																																																		
Element	Attributes		Content																																																																																		
	Required	Optional																																																																																			
omstyle	element	for, xml:id, xref, class, style	(style xslt)*																																																																																		
presentation	for	xml:id, xref, fixity, role, lbrack, rbrack, separator, bracket-style, class, style, precedence, crossref-symbol	(use xslt style)*																																																																																		
xslt	format	xml:lang, requires, xref	XSLT fragment																																																																																		
use	format	xml:lang, requires, fixity, lbrack, rbrack, separator, element, attributes, crossref-symbol	(element text recurse map value-of)*																																																																																		
kohlhase-omdoc_TAB_036	195	■ 1.000	<pre>\begin{tabular}[t]{ l l l l } \hline Element & Attributes & & Content \\ \hline & Required & Optional & \\ \hline style & format & xml:lang, requires, xref & (element text recurse map value-of)* \\ \hline element & name & crid, cr, ns & (attribute element text value-of recurse map)* \\ \hline attribute & name & & (value-of text)* \\ \hline text & & & (#PCDATA) \\ \hline value-of & select & & EMPTY \\ \hline recurse & & select & EMPTY \\ \hline map & & select & separator?, (element text recurse map) \\ \hline separator & & & (element text recurse map) \\ \hline \end{tabular}</pre>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><th>Required</th><th>Optional</th><td></td></tr><tr><td>style</td><td>format</td><td>xml:lang, requires, xref</td><td>(element text recurse map value-of)*</td></tr><tr><td>element</td><td>name</td><td>crid, cr, ns</td><td>(attribute element text value-of recurse map)*</td></tr><tr><td>attribute</td><td>name</td><td></td><td>(value-of text)*</td></tr><tr><td>text</td><td></td><td></td><td>(#PCDATA)</td></tr><tr><td>value-of</td><td>select</td><td></td><td>EMPTY</td></tr><tr><td>recurse</td><td></td><td>select</td><td>EMPTY</td></tr><tr><td>map</td><td></td><td>select</td><td>separator?, (element text recurse map)</td></tr><tr><td>separator</td><td></td><td></td><td>(element text recurse map)</td></tr></table>	Element	Attributes		Content		Required	Optional		style	format	xml:lang, requires, xref	(element text recurse map value-of)*	element	name	crid, cr, ns	(attribute element text value-of recurse map)*	attribute	name		(value-of text)*	text			(#PCDATA)	value-of	select		EMPTY	recurse		select	EMPTY	map		select	separator?, (element text recurse map)	separator			(element text recurse map)	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>Content</th></tr><tr><td></td><th>Required</th><th>Optional</th><td></td></tr><tr><td>style</td><td>format</td><td>xml:lang, requires, xref</td><td>(element text recurse map value-of)*</td></tr><tr><td>element</td><td>name</td><td>crid, cr, ns</td><td>(attribute element text value-of recurse map)*</td></tr><tr><td>attribute</td><td>name</td><td></td><td>(value-of text)*</td></tr><tr><td>text</td><td></td><td></td><td>(#PCDATA)</td></tr><tr><td>value-of</td><td>select</td><td></td><td>EMPTY</td></tr><tr><td>recurse</td><td></td><td>select</td><td>EMPTY</td></tr><tr><td>map</td><td></td><td>select</td><td>separator?, (element text recurse map)</td></tr><tr><td>separator</td><td></td><td></td><td>(element text recurse map)</td></tr></table>	Element	Attributes		Content		Required	Optional		style	format	xml:lang, requires, xref	(element text recurse map value-of)*	element	name	crid, cr, ns	(attribute element text value-of recurse map)*	attribute	name		(value-of text)*	text			(#PCDATA)	value-of	select		EMPTY	recurse		select	EMPTY	map		select	separator?, (element text recurse map)	separator			(element text recurse map)
Element	Attributes		Content																																																																																		
	Required	Optional																																																																																			
style	format	xml:lang, requires, xref	(element text recurse map value-of)*																																																																																		
element	name	crid, cr, ns	(attribute element text value-of recurse map)*																																																																																		
attribute	name		(value-of text)*																																																																																		
text			(#PCDATA)																																																																																		
value-of	select		EMPTY																																																																																		
recurse		select	EMPTY																																																																																		
map		select	separator?, (element text recurse map)																																																																																		
separator			(element text recurse map)																																																																																		
Element	Attributes		Content																																																																																		
	Required	Optional																																																																																			
style	format	xml:lang, requires, xref	(element text recurse map value-of)*																																																																																		
element	name	crid, cr, ns	(attribute element text value-of recurse map)*																																																																																		
attribute	name		(value-of text)*																																																																																		
text			(#PCDATA)																																																																																		
value-of	select		EMPTY																																																																																		
recurse		select	EMPTY																																																																																		
map		select	separator?, (element text recurse map)																																																																																		
separator			(element text recurse map)																																																																																		
kohlhase-omdoc_TAB_037	201	■ 0.952	<pre>\begin{tabular}[t]{ l l l } \hline Precedence & Operators & Comment \\ \hline 200 & +, - & unary \\ \hline 200 & ^ & exponentiation \\ \hline 400 & *, \wedge, \cap & multiplicative \\ \hline 500 & +, -, \vee, \cup & additive \\ \hline 600 & / & fraction \\ \hline 700 & =, \neq, \leq, <, >, \geq & relation \\ \hline \end{tabular}</pre>	<table><tr><th>Precedence</th><th>Operators</th><th>Comment</th></tr><tr><td>200</td><td>+, -</td><td>unary</td></tr><tr><td>200</td><td>-</td><td>exponentiation</td></tr><tr><td>400</td><td>*, $\wedge$, $\cap$</td><td>multiplicative</td></tr><tr><td>500</td><td>+, -, $\vee$, $\cup$</td><td>additive</td></tr><tr><td>600</td><td>/</td><td>fraction</td></tr><tr><td>700</td><td>=, $\neq$, $\leq$, $<$, $>$, $\geq$</td><td>relation</td></tr></table>	Precedence	Operators	Comment	200	+, -	unary	200	-	exponentiation	400	*, $\wedge$, $\cap$	multiplicative	500	+, -, $\vee$, $\cup$	additive	600	/	fraction	700	=, $\neq$, $\leq$, $<$, $>$, $\geq$	relation	<table><tr><th>Precedence</th><th>Operators</th><th>Comment</th></tr><tr><td>200</td><td>+, -</td><td>unary</td></tr><tr><td>200</td><td>-</td><td>exponentiation</td></tr><tr><td>400</td><td>*, $\wedge$, $\cap$</td><td>multiplicative</td></tr><tr><td>500</td><td>+, -, $\vee$, $\cup$</td><td>additive</td></tr><tr><td>600</td><td>/</td><td>fraction</td></tr><tr><td>700</td><td>=, $\neq$, $\leq$, $<$, $>$, $\geq$</td><td>relation</td></tr></table>	Precedence	Operators	Comment	200	+, -	unary	200	-	exponentiation	400	*, $\wedge$, $\cap$	multiplicative	500	+, -, $\vee$, $\cup$	additive	600	/	fraction	700	=, $\neq$, $\leq$, $<$, $>$, $\geq$	relation																																						
Precedence	Operators	Comment																																																																																			
200	+, -	unary																																																																																			
200	-	exponentiation																																																																																			
400	*, $\wedge$, $\cap$	multiplicative																																																																																			
500	+, -, $\vee$, $\cup$	additive																																																																																			
600	/	fraction																																																																																			
700	=, $\neq$, $\leq$, $<$, $>$, $\geq$	relation																																																																																			
Precedence	Operators	Comment																																																																																			
200	+, -	unary																																																																																			
200	-	exponentiation																																																																																			
400	*, $\wedge$, $\cap$	multiplicative																																																																																			
500	+, -, $\vee$, $\cup$	additive																																																																																			
600	/	fraction																																																																																			
700	=, $\neq$, $\leq$, $<$, $>$, $\geq$	relation																																																																																			

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																
kohlhase-omdoc_TAB_040	206	0.997	<pre>\begin{tabular}[t]{ l l l l l }\hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Req. & Optional & C & \\ \hline private & & xml:id, for, theory, requires, type, reformulates, class, style & + & CMP*, data+ \\ \hline code & & xml:id, for, theory, requires, type, class, style & + & CMP*, input?, output?, effect?, data+ \\ \hline input & & xml:id, style, class & + & CMP*, FMP* \\ \hline output & & xml:id, style, class & + & CMP*, FMP* \\ \hline effect & & xml:id, style, class & + & CMP*, FMP* \\ \hline data & & format, href, size, original, pto, pto-version & - & <![CDATA[...]]> \\ \hline\end{tabular}</pre>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><td>C</td><td></td></tr><tr><td>private</td><td></td><td>xml:id, for, theory, requires, type, reformulates, class, style</td><td>+</td><td>CMP*, data+</td></tr><tr><td>code</td><td></td><td>xml:id, for, theory, requires, type, class, style</td><td>+</td><td>CMP*, input?, output?, effect?, data+</td></tr><tr><td>input</td><td></td><td>xml:id, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>output</td><td></td><td>xml:id, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>effect</td><td></td><td>xml:id, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>data</td><td></td><td>format, href, size, original, pto, pto-version</td><td>-</td><td><![CDATA[...]]></td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		private		xml:id, for, theory, requires, type, reformulates, class, style	+	CMP*, data+	code		xml:id, for, theory, requires, type, class, style	+	CMP*, input?, output?, effect?, data+	input		xml:id, style, class	+	CMP*, FMP*	output		xml:id, style, class	+	CMP*, FMP*	effect		xml:id, style, class	+	CMP*, FMP*	data		format, href, size, original, pto, pto-version	-	<![CDATA[...]]>	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><td>C</td><td></td></tr><tr><td>private</td><td></td><td>xml:id, for, theory, requires, type, reformulates, class, style</td><td>+</td><td>CMP*, data+</td></tr><tr><td>code</td><td></td><td>xml:id, for, theory, requires, type, class, style</td><td>+</td><td>CMP*, input?, output?, effect?, data+</td></tr><tr><td>input</td><td></td><td>xml:id, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>output</td><td></td><td>xml:id, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>effect</td><td></td><td>xml:id, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>data</td><td></td><td>format, href, size, original, pto, pto-version</td><td>-</td><td><![CDATA[...]]></td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		private		xml:id, for, theory, requires, type, reformulates, class, style	+	CMP*, data+	code		xml:id, for, theory, requires, type, class, style	+	CMP*, input?, output?, effect?, data+	input		xml:id, style, class	+	CMP*, FMP*	output		xml:id, style, class	+	CMP*, FMP*	effect		xml:id, style, class	+	CMP*, FMP*	data		format, href, size, original, pto, pto-version	-	<![CDATA[...]]>
Element	Attributes		D	Content																																																																																	
	Req.	Optional	C																																																																																		
private		xml:id, for, theory, requires, type, reformulates, class, style	+	CMP*, data+																																																																																	
code		xml:id, for, theory, requires, type, class, style	+	CMP*, input?, output?, effect?, data+																																																																																	
input		xml:id, style, class	+	CMP*, FMP*																																																																																	
output		xml:id, style, class	+	CMP*, FMP*																																																																																	
effect		xml:id, style, class	+	CMP*, FMP*																																																																																	
data		format, href, size, original, pto, pto-version	-	<![CDATA[...]]>																																																																																	
Element	Attributes		D	Content																																																																																	
	Req.	Optional	C																																																																																		
private		xml:id, for, theory, requires, type, reformulates, class, style	+	CMP*, data+																																																																																	
code		xml:id, for, theory, requires, type, class, style	+	CMP*, input?, output?, effect?, data+																																																																																	
input		xml:id, style, class	+	CMP*, FMP*																																																																																	
output		xml:id, style, class	+	CMP*, FMP*																																																																																	
effect		xml:id, style, class	+	CMP*, FMP*																																																																																	
data		format, href, size, original, pto, pto-version	-	<![CDATA[...]]>																																																																																	
kohlhase-omdoc_TAB_041	210	0.931	<pre>\begin{tabular}[t]{ l l l l l l }\hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Req. & Optional & C & \\ \hline omlet & data, & xml:id, action, show, actuate, class, style & + & (⟨⟨CMP content⟩⟩ param)*,data* \\ \hline param & name & value, valuetype & - & EMPTY \\ \hline\end{tabular}</pre>	(not rendered)	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><td>C</td><td></td></tr><tr><td>omlet</td><td>data,</td><td>xml:id, action, show, actuate, class, style</td><td>+</td><td>(⟨⟨CMP content⟩⟩ param)*,data*</td></tr><tr><td>param</td><td>name</td><td>value, valuetype</td><td>-</td><td>EMPTY</td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		omlet	data,	xml:id, action, show, actuate, class, style	+	(⟨⟨CMP content⟩⟩ param)*,data*	param	name	value, valuetype	-	EMPTY																																																												
Element	Attributes		D	Content																																																																																	
	Req.	Optional	C																																																																																		
omlet	data,	xml:id, action, show, actuate, class, style	+	(⟨⟨CMP content⟩⟩ param)*,data*																																																																																	
param	name	value, valuetype	-	EMPTY																																																																																	
kohlhase-omdoc_TAB_042	214	0.919	<pre>\begin{tabular}[t]{ l l l l l l }\hline Element & \multicolumn{2}{ l }{Attributes} & D & Content \\ \hline & Req. & Optional & C & \\ \hline exercise & & xml:id, class, style & + & CMP*,FMP*,hint?,(solution* mc*) \\ \hline hint & & xml:id, class, style & + & CMP*, FMP* \\ \hline solution & & xml:id, for, class, style & + & ⟨⟨top-level element⟩⟩ \\ \hline mc & & xml:id, for, class, style & - & choice, hint?, answer \\ \hline choice & & xml:id, class, style & + & CMP*, FMP* \\ \hline answer & verdict & xml:id, class, style & + & CMP*, FMP* \\ \hline\end{tabular}</pre>	(not rendered)	<table><tr><th>Element</th><th colspan="2">Attributes</th><th>D</th><th>Content</th></tr><tr><td></td><th>Req.</th><th>Optional</th><td>C</td><td></td></tr><tr><td>exercise</td><td></td><td>xml:id, class, style</td><td>+</td><td>CMP*,FMP*,hint?,(solution* mc*)</td></tr><tr><td>hint</td><td></td><td>xml:id, class, style</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>solution</td><td></td><td>xml:id, for, class, style</td><td>+</td><td>⟨⟨top-level element⟩⟩</td></tr><tr><td>mc</td><td></td><td>xml:id, for, class, style</td><td>-</td><td>choice, hint?, answer</td></tr><tr><td>choice</td><td></td><td>xml:id, class, style</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>answer</td><td>verdict</td><td>xml:id, class, style</td><td>+</td><td>CMP*, FMP*</td></tr></table>	Element	Attributes		D	Content		Req.	Optional	C		exercise		xml:id, class, style	+	CMP*,FMP*,hint?,(solution* mc*)	hint		xml:id, class, style	+	CMP*, FMP*	solution		xml:id, for, class, style	+	⟨⟨top-level element⟩⟩	mc		xml:id, for, class, style	-	choice, hint?, answer	choice		xml:id, class, style	+	CMP*, FMP*	answer	verdict	xml:id, class, style	+	CMP*, FMP*																																								
Element	Attributes		D	Content																																																																																	
	Req.	Optional	C																																																																																		
exercise		xml:id, class, style	+	CMP*,FMP*,hint?,(solution* mc*)																																																																																	
hint		xml:id, class, style	+	CMP*, FMP*																																																																																	
solution		xml:id, for, class, style	+	⟨⟨top-level element⟩⟩																																																																																	
mc		xml:id, for, class, style	-	choice, hint?, answer																																																																																	
choice		xml:id, class, style	+	CMP*, FMP*																																																																																	
answer	verdict	xml:id, class, style	+	CMP*, FMP*																																																																																	


Identifier	Page	Conf.	LaTeX source	Rendered	Image																				
kohlhase-omdoc_TAB_043	220	■ 0.940	<pre>\begin{tabular}[t]{ l l l l } \hline \# & Rule & comment & elements \\ \hline 1 & unordere d & The order of children of this element is irrelevant (as far as permitted by the content model). For instance only the order of obligation elements in the axiom-inclusion element is arbitrary, since the others must precede them in the content model. & adt axiom-inclusion metadata symbol code private presentation omstyle \\ \hline 2 & multi-group & The order between siblings elements does not matter, as long as the values of the key attributes differ. & CMP FMP requation dc:description sortdef data dc:title solution \\ \hline 3 & DAG encoding & Directed acyclic graphs built up using om:OMR elements are equal, iff their tree expansions are equal. & om:OMR ref \\ \hline 4 & Dataset & If the content of the dc:type element is Dataset, then the order of the siblings of the parent metadata element is irrelevant. & dc:type \\ \hline \end{tabular}</pre>		<table><tr><th>#</th><th>Rule</th><th>comment</th><th>elements</th></tr><tr><td>1</td><td>unordere d</td><td>The order of children of this element is irrelevant (as far as permitted by the content model). For instance only the order of obligation elements in the axiom-inclusion element is arbitrary, since the others must precede them in the content model.</td><td>adt axiom-inclusion metadata symbol code private presentation omstyle</td></tr><tr><td>2</td><td>multi-group</td><td>The order between siblings elements does not matter, as long as the values of the key attributes differ.</td><td>CMP FMP requation dc:description sortdef data dc:title solution</td></tr><tr><td>3</td><td>DAG encoding</td><td>Directed acyclic graphs built up using om:OMR elements are equal, iff their tree expansions are equal.</td><td>om:OMR ref</td></tr><tr><td>4</td><td>Dataset</td><td>If the content of the dc:type element is Dataset, then the order of the siblings of the parent metadata element is irrelevant.</td><td>dc:type</td></tr></table>	#	Rule	comment	elements	1	unordere d	The order of children of this element is irrelevant (as far as permitted by the content model). For instance only the order of obligation elements in the axiom-inclusion element is arbitrary, since the others must precede them in the content model.	adt axiom-inclusion metadata symbol code private presentation omstyle	2	multi-group	The order between siblings elements does not matter, as long as the values of the key attributes differ.	CMP FMP requation dc:description sortdef data dc:title solution	3	DAG encoding	Directed acyclic graphs built up using om:OMR elements are equal, iff their tree expansions are equal.	om:OMR ref	4	Dataset	If the content of the dc:type element is Dataset, then the order of the siblings of the parent metadata element is irrelevant.	dc:type
#	Rule	comment	elements																						
1	unordere d	The order of children of this element is irrelevant (as far as permitted by the content model). For instance only the order of obligation elements in the axiom-inclusion element is arbitrary, since the others must precede them in the content model.	adt axiom-inclusion metadata symbol code private presentation omstyle																						
2	multi-group	The order between siblings elements does not matter, as long as the values of the key attributes differ.	CMP FMP requation dc:description sortdef data dc:title solution																						
3	DAG encoding	Directed acyclic graphs built up using om:OMR elements are equal, iff their tree expansions are equal.	om:OMR ref																						
4	Dataset	If the content of the dc:type element is Dataset, then the order of the siblings of the parent metadata element is irrelevant.	dc:type																						
kohlhase-omdoc_TAB_044	227	■ 0.992	<pre>\begin{tabular}[t]{ l l } \hline directories & content \\ \hline bin, lib, oz, thirdParty & programs and third-party software used in the administration and examples \\ \hline css, xsl & style sheets for displaying OMDoc documents on the web, see Chapter 25 for a discussion. \\ \hline doc & The OMDoc documentation, including the specification, papers about a the OMDoc format and tools. \\ \hline dtd, rnc & The OMDoc document type definition and the RelaxNG schemata for OMDoc \\ \hline examples & Various example documents in OMDoc format. \\ \hline projects & various contributed developments for OMDoc. Documentation is usually in their doc sub-directory \\ \hline \end{tabular}</pre>		<table><tr><th>directories</th><th>content</th></tr><tr><td>bin, lib, oz, thirdParty</td><td>programs and third-party software used in the administration and examples</td></tr><tr><td>css, xsl</td><td>style sheets for displaying OMDoc documents on the web, see Chapter 25 for a discussion.</td></tr><tr><td>doc</td><td>The OMDoc documentation, including the specification, papers about a the OMDoc format and tools.</td></tr><tr><td>dtd, rnc</td><td>The OMDoc document type definition and the RELAXNG schemata for OMDoc</td></tr><tr><td>examples</td><td>Various example documents in OMDoc format.</td></tr><tr><td>projects</td><td>various contributed developments for OMDoc. Documentation is usually in their doc sub-directory</td></tr></table>	directories	content	bin, lib, oz, thirdParty	programs and third-party software used in the administration and examples	css, xsl	style sheets for displaying OMDoc documents on the web, see Chapter 25 for a discussion.	doc	The OMDoc documentation, including the specification, papers about a the OMDoc format and tools.	dtd, rnc	The OMDoc document type definition and the RELAXNG schemata for OMDoc	examples	Various example documents in OMDoc format.	projects	various contributed developments for OMDoc. Documentation is usually in their doc sub-directory						
directories	content																								
bin, lib, oz, thirdParty	programs and third-party software used in the administration and examples																								
css, xsl	style sheets for displaying OMDoc documents on the web, see Chapter 25 for a discussion.																								
doc	The OMDoc documentation, including the specification, papers about a the OMDoc format and tools.																								
dtd, rnc	The OMDoc document type definition and the RELAXNG schemata for OMDoc																								
examples	Various example documents in OMDoc format.																								
projects	various contributed developments for OMDoc. Documentation is usually in their doc sub-directory																								

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																										
kohlhase-omdoc_TAB_045	233	0.940	$\begin{tabular}{t}{ l l } \hline language & namespace & prefix \\ \hline MathML & http://www.w3.org/1998/Math/MathML & m: \\ \hline OpenMath & http://www.openmath.org/OpenMath & om: \\ \hline XSLT & http://www.w3.org/1999/XSL/Transform & xsl: \\ \hline Dublin Core & http://purl.org/dc/elements/1.1/ & dc: \\ \hline Creative Commons & http://creativecommons.org/ns & cc: \\ \hline OMDoc & http://www.mathweb.org/omdoc & omdoc: \\ \hline \end{tabular}$	<table><tr><td>language</td><td>namespace</td><td>prefix</td></tr><tr><td>MathML</td><td>http://www.w3.org/1998/Math/MathML</td><td>m:</td></tr><tr><td>OpenMath</td><td>http://www.openmath.org/OpenMath</td><td>om:</td></tr><tr><td>XSLT</td><td>http://www.w3.org/1999/XSL/Transform</td><td>xsl:</td></tr><tr><td>Dublin Core</td><td>http://purl.org/dc/elements/1.1/</td><td>dc:</td></tr><tr><td>Creative Commons</td><td>http://creativecommons.org/ns</td><td>cc:</td></tr><tr><td>OMDoc</td><td>http://www.mathweb.org/omdoc</td><td>omdoc:</td></tr></table>	language	namespace	prefix	MathML	http://www.w3.org/1998/Math/MathML	m:	OpenMath	http://www.openmath.org/OpenMath	om:	XSLT	http://www.w3.org/1999/XSL/Transform	xsl:	Dublin Core	http://purl.org/dc/elements/1.1/	dc:	Creative Commons	http://creativecommons.org/ns	cc:	OMDoc	http://www.mathweb.org/omdoc	omdoc:	<table><tr><td>language</td><td>namespace</td><td>prefix</td></tr><tr><td>MATHML</td><td>http://www.w3.org/1998/Math/MathML</td><td>m:</td></tr><tr><td>OPENMATH</td><td>http://www.openmath.org/OpenMath</td><td>om:</td></tr><tr><td>XSLT</td><td>http://www.w3.org/1999/XSL/Transform</td><td>xsl:</td></tr><tr><td>Dublin Core</td><td>http://purl.org/dc/elements/1.1/</td><td>dc:</td></tr><tr><td>Creative Commons</td><td>http://creativecommons.org/ns</td><td>cc:</td></tr><tr><td>OMDoc</td><td>http://www.mathweb.org/omdoc</td><td>omdoc:</td></tr></table>	language	namespace	prefix	MATHML	http://www.w3.org/1998/Math/MathML	m:	OPENMATH	http://www.openmath.org/OpenMath	om:	XSLT	http://www.w3.org/1999/XSL/Transform	xsl:	Dublin Core	http://purl.org/dc/elements/1.1/	dc:	Creative Commons	http://creativecommons.org/ns	cc:	OMDoc	http://www.mathweb.org/omdoc	omdoc:
language	namespace	prefix																																													
MathML	http://www.w3.org/1998/Math/MathML	m:																																													
OpenMath	http://www.openmath.org/OpenMath	om:																																													
XSLT	http://www.w3.org/1999/XSL/Transform	xsl:																																													
Dublin Core	http://purl.org/dc/elements/1.1/	dc:																																													
Creative Commons	http://creativecommons.org/ns	cc:																																													
OMDoc	http://www.mathweb.org/omdoc	omdoc:																																													
language	namespace	prefix																																													
MATHML	http://www.w3.org/1998/Math/MathML	m:																																													
OPENMATH	http://www.openmath.org/OpenMath	om:																																													
XSLT	http://www.w3.org/1999/XSL/Transform	xsl:																																													
Dublin Core	http://purl.org/dc/elements/1.1/	dc:																																													
Creative Commons	http://creativecommons.org/ns	cc:																																													
OMDoc	http://www.mathweb.org/omdoc	omdoc:																																													
kohlhase-omdoc_TAB_046	245	0.999	$\begin{tabular}{t}{ l l } \hline Project Home & http://www.matracas.org/qmath/index.en.html \\ \hline Authors & Alberto González Palomo Toledo, Spain \\ \hline \end{tabular}$	<table><tr><td>Project Home</td><td>http://www.matracas.org/qmath/index.en.html</td></tr><tr><td>Authors</td><td>Alberto González Palomo Toledo, Spain²</td></tr></table>	Project Home	http://www.matracas.org/qmath/index.en.html	Authors	Alberto González Palomo Toledo, Spain ²	<table><tr><td>Project Home</td><td>http://www.matracas.org/qmath/index.en.html</td></tr><tr><td>Authors</td><td>Alberto González Palomo Toledo, Spain²</td></tr></table>	Project Home	http://www.matracas.org/qmath/index.en.html	Authors	Alberto González Palomo Toledo, Spain ²																																		
Project Home	http://www.matracas.org/qmath/index.en.html																																														
Authors	Alberto González Palomo Toledo, Spain ²																																														
Project Home	http://www.matracas.org/qmath/index.en.html																																														
Authors	Alberto González Palomo Toledo, Spain ²																																														
kohlhase-omdoc_TAB_047	248	1.000	$\begin{tabular}{t}{ l l } \hline Project Home & http://www.matracas.org/sentido/index.en.html \\ \hline Authors & Alberto González Palomo Toledo, Spain \\ \hline \end{tabular}$	<table><tr><td>Project Home</td><td>http://www.matracas.org/sentido/index.en.html</td></tr><tr><td>Authors</td><td>Alberto González Palomo Toledo, Spain⁴</td></tr></table>	Project Home	http://www.matracas.org/sentido/index.en.html	Authors	Alberto González Palomo Toledo, Spain ⁴	<table><tr><td>Project Home</td><td>http://www.matracas.org/sentido/index.en.html</td></tr><tr><td>Authors</td><td>Alberto González Palomo Toledo, Spain⁴</td></tr></table>	Project Home	http://www.matracas.org/sentido/index.en.html	Authors	Alberto González Palomo Toledo, Spain ⁴																																		
Project Home	http://www.matracas.org/sentido/index.en.html																																														
Authors	Alberto González Palomo Toledo, Spain ⁴																																														
Project Home	http://www.matracas.org/sentido/index.en.html																																														
Authors	Alberto González Palomo Toledo, Spain ⁴																																														
kohlhase-omdoc_TAB_048	253	1.000	$\begin{tabular}{t}{ l l } \hline Project Home & http://www.mathweb.org/mbase \\ \hline Authors & Andreas Franke1, Michael Kohlhase2 \\ \hline \end{tabular}$	(not rendered)	<table><tr><td>Project Home</td><td>http://www.mathweb.org/mbase</td></tr><tr><td>Authors</td><td>Andreas Franke¹, Michael Kohlhase² ¹ Computer Science, Saarland University ² School of Engineering and Science, International University Bremen</td></tr></table>	Project Home	http://www.mathweb.org/mbase	Authors	Andreas Franke ¹ , Michael Kohlhase ² ¹ Computer Science, Saarland University ² School of Engineering and Science, International University Bremen																																						
Project Home	http://www.mathweb.org/mbase																																														
Authors	Andreas Franke ¹ , Michael Kohlhase ² ¹ Computer Science, Saarland University ² School of Engineering and Science, International University Bremen																																														
kohlhase-omdoc_TAB_049	255	1.000	$\begin{tabular}{t}{ l l } \hline Project Home & http://search.mathweb.org/ \\ \hline Authors & Ioan Sucan, Michael Kohlhase Computer Science, International University Bremen \\ \hline \end{tabular}$	<table><tr><td>Project Home</td><td>http://search.mathweb.org/</td></tr><tr><td>Authors</td><td>Ioan Sucan, Michael Kohlhase Computer Science, International University Bremen</td></tr></table>	Project Home	http://search.mathweb.org/	Authors	Ioan Sucan, Michael Kohlhase Computer Science, International University Bremen	<table><tr><td>Project Home</td><td>http://search.mathweb.org/</td></tr><tr><td>Authors</td><td>Ioan Sucan, Michael Kohlhase Computer Science, International University Bremen</td></tr></table>	Project Home	http://search.mathweb.org/	Authors	Ioan Sucan, Michael Kohlhase Computer Science, International University Bremen																																		
Project Home	http://search.mathweb.org/																																														
Authors	Ioan Sucan, Michael Kohlhase Computer Science, International University Bremen																																														
Project Home	http://search.mathweb.org/																																														
Authors	Ioan Sucan, Michael Kohlhase Computer Science, International University Bremen																																														
kohlhase-omdoc_TAB_050	259	1.000	$\begin{tabular}{t}{ l l } \hline Project Home & http://www.mmiss.de \\ \hline Authors & Bernd Krieg-Brückner, Achim Mahnke Computer Science, University of Bremen, Germany \\ \hline \end{tabular}$	<table><tr><td>Project Home</td><td>http://www.mmiss.de</td></tr><tr><td>Authors</td><td>Bernd Krieg-Brückner, Achim Mahnke Computer Science, University of Bremen, Germany</td></tr></table>	Project Home	http://www.mmiss.de	Authors	Bernd Krieg-Brückner, Achim Mahnke Computer Science, University of Bremen, Germany	<table><tr><td>Project Home</td><td>http://www.mmiss.de</td></tr><tr><td>Authors</td><td>Bernd Krieg-Brückner, Achim Mahnke Computer Science, University of Bremen, Germany</td></tr></table>	Project Home	http://www.mmiss.de	Authors	Bernd Krieg-Brückner, Achim Mahnke Computer Science, University of Bremen, Germany																																		
Project Home	http://www.mmiss.de																																														
Authors	Bernd Krieg-Brückner, Achim Mahnke Computer Science, University of Bremen, Germany																																														
Project Home	http://www.mmiss.de																																														
Authors	Bernd Krieg-Brückner, Achim Mahnke Computer Science, University of Bremen, Germany																																														

Identifier	Page	Conf.	LaTeX source	Rendered	Image								
kohlhase-omdoc_TAB_051	263	1.000	$\begin{tabular}{t}{ l l }\hline Project Home & \texttt{http://www.mathdox.org} \\ \hline Authors & \texttt{A.M. Cohen, H. Cuypers, E. Reinaldo Barreiro} \\ & \texttt{Department of Mathematics and Computer Science, Eindhoven University of Technology} \\ \hline\end{tabular}$	<table><tr><td>Project Home</td><td>http://www.mathdox.org</td></tr><tr><td>Authors</td><td>A.M. Cohen, H. Cuypers, E. Reinaldo Barreiro Department of Mathematics and Computer Science, Eindhoven University of Technology</td></tr></table>	Project Home	http://www.mathdox.org	Authors	A.M. Cohen, H. Cuypers, E. Reinaldo Barreiro Department of Mathematics and Computer Science, Eindhoven University of Technology	<table><tr><td>Project Home</td><td>http://www.mathdox.org</td></tr><tr><td>Authors</td><td>A.M. Cohen, H. Cuypers, E. Reinaldo Barreiro Department of Mathematics and Computer Science, Eindhoven University of Technology</td></tr></table>	Project Home	http://www.mathdox.org	Authors	A.M. Cohen, H. Cuypers, E. Reinaldo Barreiro Department of Mathematics and Computer Science, Eindhoven University of Technology
Project Home	http://www.mathdox.org												
Authors	A.M. Cohen, H. Cuypers, E. Reinaldo Barreiro Department of Mathematics and Computer Science, Eindhoven University of Technology												
Project Home	http://www.mathdox.org												
Authors	A.M. Cohen, H. Cuypers, E. Reinaldo Barreiro Department of Mathematics and Computer Science, Eindhoven University of Technology												
kohlhase-omdoc_TAB_052	267	1.000	$\begin{tabular}{t}{ l l }\hline Project Home & \texttt{http://www.activemath.org/} \\ \hline Authors & \texttt{The ACTIVEMATH group: Erica Melis, Giorgi Gogvadse, Alberto Gonzales-Palomo, Adrian Frischauf, Martin Homik, Paul Libbrecht, Carsten Ullrich} \\ & \texttt{DFKI GmbH and Universität des Saarlandes} \\ \hline\end{tabular}$	<table><tr><td>Project Home</td><td>http://www.activemath.org/</td></tr><tr><td>Authors</td><td>The ACTIVEMATH group: Erica Melis, Giorgi Gogvadse, Alberto Gonzales-Palomo, Adrian Frischauf, Martin Homik, Paul Libbrecht, Carsten Ullrich DFKI GmbH and Universität des Saarlandes</td></tr></table>	Project Home	http://www.activemath.org/	Authors	The ACTIVEMATH group: Erica Melis, Giorgi Gogvadse, Alberto Gonzales-Palomo, Adrian Frischauf, Martin Homik, Paul Libbrecht, Carsten Ullrich DFKI GmbH and Universität des Saarlandes	<table><tr><td>Project Home</td><td>http://www.activemath.org/</td></tr><tr><td>Authors</td><td>The ACTIVEMATH group: Erica Melis, Giorgi Gogvadse, Alberto Gonzales-Palomo, Adrian Frischauf, Martin Homik, Paul Libbrecht, Carsten Ullrich DFKI GmbH and Universität des Saarlandes</td></tr></table>	Project Home	http://www.activemath.org/	Authors	The ACTIVEMATH group: Erica Melis, Giorgi Gogvadse, Alberto Gonzales-Palomo, Adrian Frischauf, Martin Homik, Paul Libbrecht, Carsten Ullrich DFKI GmbH and Universität des Saarlandes
Project Home	http://www.activemath.org/												
Authors	The ACTIVEMATH group: Erica Melis, Giorgi Gogvadse, Alberto Gonzales-Palomo, Adrian Frischauf, Martin Homik, Paul Libbrecht, Carsten Ullrich DFKI GmbH and Universität des Saarlandes												
Project Home	http://www.activemath.org/												
Authors	The ACTIVEMATH group: Erica Melis, Giorgi Gogvadse, Alberto Gonzales-Palomo, Adrian Frischauf, Martin Homik, Paul Libbrecht, Carsten Ullrich DFKI GmbH and Universität des Saarlandes												
kohlhase-omdoc_TAB_053	273	0.999	$\begin{tabular}{t}{ l l }\hline Project Home & \texttt{http://www.activemath.org/projects/jEdit0QMath} \\ \hline Authors & \texttt{Paul Libbrecht DFKI GmbH and Universität des Saarlandes} \\ \hline\end{tabular}$	<table><tr><td>Project Home</td><td>http://www.activemath.org/projects/jEdit0QMath</td></tr><tr><td>Authors</td><td>Paul Libbrecht DFKI GmbH and Universität des Saarlandes</td></tr></table>	Project Home	http://www.activemath.org/projects/jEdit0QMath	Authors	Paul Libbrecht DFKI GmbH and Universität des Saarlandes	<table><tr><td>Project Home</td><td>http://www.activemath.org/projects/jEdit0QMath</td></tr><tr><td>Authors</td><td>Paul Libbrecht DFKI GmbH and Universität des Saarlandes</td></tr></table>	Project Home	http://www.activemath.org/projects/jEdit0QMath	Authors	Paul Libbrecht DFKI GmbH and Universität des Saarlandes
Project Home	http://www.activemath.org/projects/jEdit0QMath												
Authors	Paul Libbrecht DFKI GmbH and Universität des Saarlandes												
Project Home	http://www.activemath.org/projects/jEdit0QMath												
Authors	Paul Libbrecht DFKI GmbH and Universität des Saarlandes												
kohlhase-omdoc_TAB_054	275	1.000	$\begin{tabular}{t}{ l l }\hline Project Home & \texttt{http://kwarc.eecs.iu-bremen.de/projects/swim} \\ \hline Authors & \texttt{Christoph Lange, Michael Kohlhase} \\ & \texttt{Computer Science, International University Bremen} \\ \hline\end{tabular}$	<table><tr><td>Project Home</td><td>http://kwarc.eecs.iu-bremen.de/projects/swim</td></tr><tr><td>Authors</td><td>Christoph Lange, Michael Kohlhase Computer Science, International University Bremen</td></tr></table>	Project Home	http://kwarc.eecs.iu-bremen.de/projects/swim	Authors	Christoph Lange, Michael Kohlhase Computer Science, International University Bremen	<table><tr><td>Project Home</td><td>http://kwarc.eecs.iu-bremen.de/projects/swim</td></tr><tr><td>Authors</td><td>Christoph Lange, Michael Kohlhase Computer Science, International University Bremen</td></tr></table>	Project Home	http://kwarc.eecs.iu-bremen.de/projects/swim	Authors	Christoph Lange, Michael Kohlhase Computer Science, International University Bremen
Project Home	http://kwarc.eecs.iu-bremen.de/projects/swim												
Authors	Christoph Lange, Michael Kohlhase Computer Science, International University Bremen												
Project Home	http://kwarc.eecs.iu-bremen.de/projects/swim												
Authors	Christoph Lange, Michael Kohlhase Computer Science, International University Bremen												
kohlhase-omdoc_TAB_055	279	1.000	$\begin{tabular}{t}{ l l }\hline Project Home & \texttt{http://www.cs.nott.ac.uk/~lad/research/challenges/challenge_manager.html} \\ \hline Authors & \texttt{Thomas D. Attfield, Monica C. Duarte, Lin Li, HoYing Mak, Adam M. Neal, Lewis M. Toft, Zixuan Wang, Louise A. Dennis} \\ & \texttt{School of Computer Science and Information Technology, University of Nottingham} \\ \hline\end{tabular}$	(not rendered)	<table><tr><td>Project Home</td><td>http://www.cs.nott.ac.uk/~lad/research/challenges/challenge_manager.html</td></tr><tr><td>Authors</td><td>Thomas D. Attfield, Monica C. Duarte, Lin Li, HoYing Mak, Adam M. Neal, Lewis M. Toft, Zixuan Wang, Louise A. Dennis School of Computer Science and Information Technology, University of Nottingham</td></tr></table>	Project Home	http://www.cs.nott.ac.uk/~lad/research/challenges/challenge_manager.html	Authors	Thomas D. Attfield, Monica C. Duarte, Lin Li, HoYing Mak, Adam M. Neal, Lewis M. Toft, Zixuan Wang, Louise A. Dennis School of Computer Science and Information Technology, University of Nottingham				
Project Home	http://www.cs.nott.ac.uk/~lad/research/challenges/challenge_manager.html												
Authors	Thomas D. Attfield, Monica C. Duarte, Lin Li, HoYing Mak, Adam M. Neal, Lewis M. Toft, Zixuan Wang, Louise A. Dennis School of Computer Science and Information Technology, University of Nottingham												
kohlhase-omdoc_TAB_056	282	1.000	$\begin{tabular}{t}{ l l }\hline Project Home & \texttt{www.dfki.de/~inka/maya.html} \\ \hline Authors & \texttt{Serge Autexier, Dieter Hutter, Till Mossakowski, Axel Schairer} \\ & \texttt{DFKI GmbH, Stuhlsatzenhausweg 3, D 66123 Saarbrücken} \\ & \texttt{Computer Science, University of Bremen, Germany} \\ \hline\end{tabular}$	<table><tr><td>Project Home</td><td>www.dfki.de/~inka/maya.html</td></tr><tr><td>Authors</td><td>Serge Autexier¹, Dieter Hutter¹, Till Mossakowski², Axel Schairer¹ ¹ DFKI GmbH, Stuhlsatzenhausweg 3, D 66123 Saarbrücken ² Computer Science, University of Bremen, Germany</td></tr></table>	Project Home	www.dfki.de/~inka/maya.html	Authors	Serge Autexier ¹ , Dieter Hutter ¹ , Till Mossakowski ² , Axel Schairer ¹ ¹ DFKI GmbH, Stuhlsatzenhausweg 3, D 66123 Saarbrücken ² Computer Science, University of Bremen, Germany	<table><tr><td>Project Home</td><td>www.dfki.de/~inka/maya.html</td></tr><tr><td>Authors</td><td>Serge Autexier¹, Dieter Hutter¹, Till Mossakowski², Axel Schairer¹ ¹ DFKI GmbH, Stuhlsatzenhausweg 3, D 66123 Saarbrücken ² Computer Science, University of Bremen, Germany</td></tr></table>	Project Home	www.dfki.de/~inka/maya.html	Authors	Serge Autexier ¹ , Dieter Hutter ¹ , Till Mossakowski ² , Axel Schairer ¹ ¹ DFKI GmbH, Stuhlsatzenhausweg 3, D 66123 Saarbrücken ² Computer Science, University of Bremen, Germany
Project Home	www.dfki.de/~inka/maya.html												
Authors	Serge Autexier ¹ , Dieter Hutter ¹ , Till Mossakowski ² , Axel Schairer ¹ ¹ DFKI GmbH, Stuhlsatzenhausweg 3, D 66123 Saarbrücken ² Computer Science, University of Bremen, Germany												
Project Home	www.dfki.de/~inka/maya.html												
Authors	Serge Autexier ¹ , Dieter Hutter ¹ , Till Mossakowski ² , Axel Schairer ¹ ¹ DFKI GmbH, Stuhlsatzenhausweg 3, D 66123 Saarbrücken ² Computer Science, University of Bremen, Germany												


Identifier	Page	Conf.	LaTeX source	Rendered	Image								
kohlhase-omdoc_TAB_057	287	■ 1.000	<pre>\begin{tabular}[t]{l l l} \hline Project Home & www.tzi.de/cofi/hets \\ \hline Authors & Till Mossakowski, Christian Maeder, Klaus Lüttich Computer Science, University of Bremen, Germany \\ \hline \end{tabular}</pre>	<table><tr><td>Project Home</td><td>www.tzi.de/cofi/hets</td></tr><tr><td>Authors</td><td>Till Mossakowski, Christian Maeder, Klaus Lüttich Computer Science, University of Bremen, Germany</td></tr></table>	Project Home	www.tzi.de/cofi/hets	Authors	Till Mossakowski, Christian Maeder, Klaus Lüttich Computer Science, University of Bremen, Germany	<table><tr><td>Project Home</td><td>www.tzi.de/cofi/hets</td></tr><tr><td>Authors</td><td>Till Mossakowski, Christian Maeder, Klaus Lüttich Computer Science, University of Bremen, Germany</td></tr></table>	Project Home	www.tzi.de/cofi/hets	Authors	Till Mossakowski, Christian Maeder, Klaus Lüttich Computer Science, University of Bremen, Germany
Project Home	www.tzi.de/cofi/hets												
Authors	Till Mossakowski, Christian Maeder, Klaus Lüttich Computer Science, University of Bremen, Germany												
Project Home	www.tzi.de/cofi/hets												
Authors	Till Mossakowski, Christian Maeder, Klaus Lüttich Computer Science, University of Bremen, Germany												
kohlhase-omdoc_TAB_058	291	■ 1.000	<pre>\begin{tabular}[t]{l l l} \hline Project Home & http://kwarc.eecs.iu-bremen.de/software/CPoint/ \\ \hline Authors & \begin{tabular}[t]{l} Andrea Kohlhase \\ Digital Media in Education (DiMeB), Dept. of Mathematics and Computer Science, University Bremen \end{tabular} \\ \hline \end{tabular}</pre>	<table><tr><td>Project Home</td><td>http://kwarc.eecs.iu-bremen.de/software/CPoint/</td></tr><tr><td>Authors</td><td>Andrea Kohlhase Digital Media in Education (DiMeB), Dept. of Mathematics and Computer Science, University Bremen</td></tr></table>	Project Home	http://kwarc.eecs.iu-bremen.de/software/CPoint/	Authors	Andrea Kohlhase Digital Media in Education (DiMeB), Dept. of Mathematics and Computer Science, University Bremen	<table><tr><td>Project Home</td><td>http://kwarc.eecs.iu-bremen.de/software/CPoint/</td></tr><tr><td>Authors</td><td>Andrea Kohlhase Digital Media in Education (DiMeB), Dept. of Math-ematics and Computer Science, University Bremen</td></tr></table>	Project Home	http://kwarc.eecs.iu-bremen.de/software/CPoint/	Authors	Andrea Kohlhase Digital Media in Education (DiMeB), Dept. of Math-ematics and Computer Science, University Bremen
Project Home	http://kwarc.eecs.iu-bremen.de/software/CPoint/												
Authors	Andrea Kohlhase Digital Media in Education (DiMeB), Dept. of Mathematics and Computer Science, University Bremen												
Project Home	http://kwarc.eecs.iu-bremen.de/software/CPoint/												
Authors	Andrea Kohlhase Digital Media in Education (DiMeB), Dept. of Math-ematics and Computer Science, University Bremen												
kohlhase-omdoc_TAB_059	295	■ 1.000	<pre>\begin{tabular}[t]{l l l} \hline Project Home & http://kwarc.iu-bremen.de/projects/stex/ \\ \hline Authors & Michael Kohlhase Computer Science, International University Bremen \\ \hline \end{tabular}</pre>	<table><tr><td>Project Home</td><td>http://kwarc.iu-bremen.de/projects/stex/</td></tr><tr><td>Authors</td><td>Michael Kohlhase Computer Science, International University Bremen</td></tr></table>	Project Home	http://kwarc.iu-bremen.de/projects/stex/	Authors	Michael Kohlhase Computer Science, International University Bremen	<table><tr><td>Project Home</td><td>http://kwarc.iu-bremen.de/projects/stex/</td></tr><tr><td>Authors</td><td>Michael Kohlhase Computer Science, International University Bremen</td></tr></table>	Project Home	http://kwarc.iu-bremen.de/projects/stex/	Authors	Michael Kohlhase Computer Science, International University Bremen
Project Home	http://kwarc.iu-bremen.de/projects/stex/												
Authors	Michael Kohlhase Computer Science, International University Bremen												
Project Home	http://kwarc.iu-bremen.de/projects/stex/												
Authors	Michael Kohlhase Computer Science, International University Bremen												
kohlhase-omdoc_TAB_060	299	■ 0.997	<pre>\begin{tabular}[t]{l l l} \hline Project Home & http://www.cs.cmu.edu/~ccaps \\ \hline Authors & Peter Jansen School of Computer Science, Carnegie Mellon University \\ \hline \end{tabular}</pre>	<table><tr><td>Project Home</td><td>http://www.cs.cmu.edu/~ccaps</td></tr><tr><td>Authors</td><td>Peter Jansen School of Computer Science, Carnegie Mellon University</td></tr></table>	Project Home	http://www.cs.cmu.edu/~ccaps	Authors	Peter Jansen School of Computer Science, Carnegie Mellon University	<table><tr><td>Project Home</td><td>http://www.cs.cmu.edu/~ccaps</td></tr><tr><td>Authors</td><td>Peter Jansen School of Computer Science, Carnegie Mellon Uni-versity</td></tr></table>	Project Home	http://www.cs.cmu.edu/~ccaps	Authors	Peter Jansen School of Computer Science, Carnegie Mellon Uni-versity
Project Home	http://www.cs.cmu.edu/~ccaps												
Authors	Peter Jansen School of Computer Science, Carnegie Mellon University												
Project Home	http://www.cs.cmu.edu/~ccaps												
Authors	Peter Jansen School of Computer Science, Carnegie Mellon Uni-versity												
kohlhase-omdoc_TAB_061	302	■ 0.999	<pre>\begin{tabular}[t]{l l l} \hline Project Home & http://www.cs.cmu.edu/~ccaps \\ \hline Authors & Klaus Sutner School of Computer Science, Carnegie Mellon University \\ \hline \end{tabular}</pre>	<table><tr><td>Project Home</td><td>http://www.cs.cmu.edu/~ccaps</td></tr><tr><td>Authors</td><td>Klaus Sutner School of Computer Science, Carnegie Mellon University</td></tr></table>	Project Home	http://www.cs.cmu.edu/~ccaps	Authors	Klaus Sutner School of Computer Science, Carnegie Mellon University	<table><tr><td>Project Home</td><td>http://www.cs.cmu.edu/~ccaps</td></tr><tr><td>Authors</td><td>Klaus Sutner School of Computer Science, Carnegie Mellon Uni-versity</td></tr></table>	Project Home	http://www.cs.cmu.edu/~ccaps	Authors	Klaus Sutner School of Computer Science, Carnegie Mellon Uni-versity
Project Home	http://www.cs.cmu.edu/~ccaps												
Authors	Klaus Sutner School of Computer Science, Carnegie Mellon University												
Project Home	http://www.cs.cmu.edu/~ccaps												
Authors	Klaus Sutner School of Computer Science, Carnegie Mellon Uni-versity												
kohlhase-omdoc_TAB_062	305	■ 1.000	<pre>\begin{tabular}[t]{l l l} \hline Project Home & http://www.mathweb.org/omdoc/examples/logics \\ \hline Authors & Michael Kohlhase Computer Science, International University Bremen \\ \hline \end{tabular}</pre>	<table><tr><td>Project Home</td><td>http://www.mathweb.org/omdoc/examples/logics</td></tr><tr><td>Authors</td><td>Michael Kohlhase Computer Science, International University Bremen</td></tr></table>	Project Home	http://www.mathweb.org/omdoc/examples/logics	Authors	Michael Kohlhase Computer Science, International University Bremen	<table><tr><td>Project Home</td><td>http://www.mathweb.org/omdoc/examples/logics</td></tr><tr><td>Authors</td><td>Michael Kohlhase Computer Science, International University Bremen</td></tr></table>	Project Home	http://www.mathweb.org/omdoc/examples/logics	Authors	Michael Kohlhase Computer Science, International University Bremen
Project Home	http://www.mathweb.org/omdoc/examples/logics												
Authors	Michael Kohlhase Computer Science, International University Bremen												
Project Home	http://www.mathweb.org/omdoc/examples/logics												
Authors	Michael Kohlhase Computer Science, International University Bremen												

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																								
kohlhase-omdoc_TAB_063	306	0.994	<pre>\begin{tabular}[t]{ l l l l } \hline PVS & \(\Omega</pre> <pre>\) MEGA & PVS & \(\Omega_{\text{MEGA}}\)\) \\ \hline</pre> <pre>set & subset? & subset \\ \hline</pre> <pre>member & in & & \\ \hline</pre> <pre>empty? & empty & strict_subset? & \\ \hline</pre> <pre>emptyset & emptyset & & superset \\ \hline</pre> <pre>nonempty? & not-empty & union & union \\ \hline</pre> <pre>full? & & & union2 \\ \hline</pre> <pre>fullset & & & \\ \hline</pre> <pre>singleton? & singleton & intersection & intersection \\ \hline</pre> <pre>singleton & & intersection-over-coll. & \\ \hline</pre> <pre>complement & set-complement & disjoint? & misses \\ \hline</pre> <pre>difference & setminus & meets & \\ \hline</pre> <pre>symmetric_difference & & add & add-one \\ \hline</pre> <pre>& exclunion & remove & \\ \hline</pre> <pre>\end{tabular}</pre>	(not rendered)	<table><tr><td>PVS</td><td>ΩMEGA</td><td>PVS</td><td>ΩMEGA</td></tr><tr><td>set</td><td></td><td>subset?</td><td>subset</td></tr><tr><td>member</td><td>in</td><td></td><td>subset2</td></tr><tr><td>empty?</td><td>empty</td><td>strict_subset?</td><td>proper-subset</td></tr><tr><td>emptyset</td><td>emptyset</td><td></td><td>superset</td></tr><tr><td>nonempty?</td><td>not-empty</td><td>union</td><td>union</td></tr><tr><td>full?</td><td></td><td></td><td>union2</td></tr><tr><td>fullset</td><td></td><td></td><td>union-over-collection</td></tr><tr><td>singleton?</td><td>singleton</td><td>intersection</td><td>intersection</td></tr><tr><td>singleton</td><td></td><td></td><td>intersection-over-coll.</td></tr><tr><td>complement</td><td>set-complement</td><td>disjoint?</td><td>misses</td></tr><tr><td>difference</td><td>setminus</td><td>meets</td><td></td></tr><tr><td>symmetric_difference</td><td></td><td>add</td><td>add-one</td></tr><tr><td></td><td>exclunion</td><td>remove</td><td></td></tr></table>	PVS	Ω MEGA	PVS	Ω MEGA	set		subset?	subset	member	in		subset2	empty?	empty	strict_subset?	proper-subset	emptyset	emptyset		superset	nonempty?	not-empty	union	union	full?			union2	fullset			union-over-collection	singleton?	singleton	intersection	intersection	singleton			intersection-over-coll.	complement	set-complement	disjoint?	misses	difference	setminus	meets		symmetric_difference		add	add-one		exclunion	remove	
PVS	Ω MEGA	PVS	Ω MEGA																																																										
set		subset?	subset																																																										
member	in		subset2																																																										
empty?	empty	strict_subset?	proper-subset																																																										
emptyset	emptyset		superset																																																										
nonempty?	not-empty	union	union																																																										
full?			union2																																																										
fullset			union-over-collection																																																										
singleton?	singleton	intersection	intersection																																																										
singleton			intersection-over-coll.																																																										
complement	set-complement	disjoint?	misses																																																										
difference	setminus	meets																																																											
symmetric_difference		add	add-one																																																										
	exclunion	remove																																																											
kohlhase-omdoc_TAB_064	310	0.990	<pre>\begin{tabular}[t]{ l l } \hline Project Home &</pre> <pre>http://www.ags.uni-sb.de/~omega/projects/ verimathdoc</pre> <pre>\\ \hline</pre> <pre>Authors & Serge Autexier, Christoph Benzmüller,</pre> <pre>Armin Fiedler, and Henri Lesourd Computer Science,</pre> <pre>Saarland University, Saarbrücken, Germany \\ \hline</pre> <pre>\end{tabular}</pre>	<table><tr><td>Project Home</td><td>http://www.ags.uni-sb.de/ omega/projects/ verimathdoc</td></tr><tr><td>Authors</td><td>Serge Autexier, Christoph Benzmüller, Armin Fiedler, and Henri Lesourd Computer Science, Saarland University, Saarbrücken, Germany</td></tr></table>	Project Home	http://www.ags.uni-sb.de/ omega/projects/ verimathdoc	Authors	Serge Autexier, Christoph Benzmüller, Armin Fiedler, and Henri Lesourd Computer Science, Saarland University, Saarbrücken, Germany	<table><tr><td>Project Home</td><td>http://www.ags.uni-sb.de/~omega/projects/ verimathdoc</td></tr><tr><td>Authors</td><td>Serge Autexier, Christoph Benzmüller, Armin Fiedler, and Henri Lesourd Computer Science, Saarland University, Saarbrücken, Germany</td></tr></table>	Project Home	http://www.ags.uni-sb.de/~omega/projects/ verimathdoc	Authors	Serge Autexier, Christoph Benzmüller, Armin Fiedler, and Henri Lesourd Computer Science, Saarland University, Saarbrücken, Germany																																																
Project Home	http://www.ags.uni-sb.de/ omega/projects/ verimathdoc																																																												
Authors	Serge Autexier, Christoph Benzmüller, Armin Fiedler, and Henri Lesourd Computer Science, Saarland University, Saarbrücken, Germany																																																												
Project Home	http://www.ags.uni-sb.de/~omega/projects/ verimathdoc																																																												
Authors	Serge Autexier, Christoph Benzmüller, Armin Fiedler, and Henri Lesourd Computer Science, Saarland University, Saarbrücken, Germany																																																												
kohlhase-omdoc_TAB_065	314	1.000	<pre>\begin{tabular}[t]{ l l } \hline Project Home &</pre> <pre>http://www.verifun.de/ \\ \hline</pre> <pre>Authors & Normen</pre> <pre>Müller School of Engineering and Science, International</pre> <pre>University Bremen \\ \hline</pre> <pre>\end{tabular}</pre>	<table><tr><td>Project Home</td><td>http://www.verifun.de/</td></tr><tr><td>Authors</td><td>Normen Müller School of Engineering and Science, International University Bremen</td></tr></table>	Project Home	http://www.verifun.de/	Authors	Normen Müller School of Engineering and Science, International University Bremen	<table><tr><td>Project Home</td><td>http://www.verifun.de/</td></tr><tr><td>Authors</td><td>Normen Müller School of Engineering and Science, International University Bremen</td></tr></table>	Project Home	http://www.verifun.de/	Authors	Normen Müller School of Engineering and Science, International University Bremen																																																
Project Home	http://www.verifun.de/																																																												
Authors	Normen Müller School of Engineering and Science, International University Bremen																																																												
Project Home	http://www.verifun.de/																																																												
Authors	Normen Müller School of Engineering and Science, International University Bremen																																																												

Identifier	Page	Conf.	LaTeX source	Rendered	Image																
kohlhase-omdoc_TAB_066	320	■ 1.000	<pre>\begin{tabular}[t]{t}{ l l l l l } \hline element & state & comments & cf. \\ alternative & aug & This element can now have theory, generated-from, and generated-via attributes. & 145 \\ argument & cha & The sort has been replaced by a type child, so that higher-order sorts can be specified. & 156 \\ assertion & aug & the assertion element now has an optional for attribute. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism. Finally, two new attributes status and just-by have been added to mark up the deductive status of the assertion. & 142 \\ \hline \end{tabular}</pre>		<table><tr><th>element</th><th>state</th><th>comments</th><th>cf.</th></tr><tr><td>alternative</td><td>aug</td><td>This element can now have theory, generated-from, and generated-via attributes.</td><td>145</td></tr><tr><td>argument</td><td>cha</td><td>The sort has been replaced by a type child, so that higher-order sorts can be specified.</td><td>156</td></tr><tr><td>assertion</td><td>aug</td><td>the assertion element now has an optional for attribute. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism. Finally, two new attributes status and just-by have been added to mark up the deductive status of the assertion.</td><td>142</td></tr></table>	element	state	comments	cf.	alternative	aug	This element can now have theory, generated-from, and generated-via attributes.	145	argument	cha	The sort has been replaced by a type child, so that higher-order sorts can be specified.	156	assertion	aug	the assertion element now has an optional for attribute. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism. Finally, two new attributes status and just-by have been added to mark up the deductive status of the assertion.	142
element	state	comments	cf.																		
alternative	aug	This element can now have theory, generated-from, and generated-via attributes.	145																		
argument	cha	The sort has been replaced by a type child, so that higher-order sorts can be specified.	156																		
assertion	aug	the assertion element now has an optional for attribute. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism. Finally, two new attributes status and just-by have been added to mark up the deductive status of the assertion.	142																		

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																								
kohlhase-omdoc_TAB_067	321	0.977	<pre>\begin{tabular}[t]{t}{ l l l l l } \hline assumption & cha & This element can now have an attribute inductive for inductive assumptions. The natural language description in the optional CMP element is no longer allowed, use a phrase element in a CMP that is a sibling to the FMP instead. & 145 \\ \hline adt & aug & the adt loses the CMP and commonname children, use the Dublin Core metadata elements dc:description and dc:subject instead. The type attribute is now on the sortdef element. Furthermore, an optionalala attribute generated-via has been added to allow generation via a theory morphism. Finally, an attribute parameters has been added to allow for parametric ADTs. & 156 \\ \hline answer & cha & the answer element does not allow symbol children any more, if these are needed, the exercise should have its own theory. & 210 \\ \hline attribute & aug & the attribute element now has a optional ns attribute for the namespace URI of the generated attribute node and an attribute select for an XPath expression that specifies the value of the generated attribute. & 191 \\ \hline axiom & aug & the axiom element now has an optional for attribute which can point to a list of symbols. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism and an attribute type is now also allowed. & 138 \\ \hline axiom-inclusion & lib & the axiom-inclusion element can now contain multiple path-just children to record multiple justifications. Furthermore, it can now have theory, generated-from, and generated-via attributes. New optional attributes conservativity and conservativity-just for stating and justifying conservativity. & 180 \\ \hline catalogue & dep & the catalogue mechanism has been eliminated. & \\ \hline choice & cha & the choice element does not allow symbol children any more, if these are needed, the exercise should have its own theory & 210 \\ \hline code & cha & Attributes classid and codebase are deprecated. The attributes pto and pto-version have moved to the data element. The attribute type has been removed and optional attributes theory, generated-from, and generated-via have been added. & 202 \\ \hline commonname & dep & This element is deprecated in favor of a metadata/dc:subject element. & \end{tabular}</pre>		<table><tr><td>assumption</td><td>cha</td><td>This element can now have an attribute inductive for inductive assumptions. The natural language description in the optional CMP element is no longer allowed, use a phrase element in a CMP that is a sibling to the FMP instead.</td><td>145</td></tr><tr><td>adt</td><td>aug</td><td>the adt loses the CMP and commonname children, use the Dublin Core metadata elements dc:description and dc:subject instead. The type attribute is now on the sortdef element. Furthermore, an optionalala attribute generated-via has been added to allow generation via a theory morphism. Finally, an attribute parameters has been added to allow for parametric ADTs.</td><td>156</td></tr><tr><td>answer</td><td>cha</td><td>the answer element does not allow symbol children any more, if these are needed, the exercise should have its own theory.</td><td>210</td></tr><tr><td>attribute</td><td>aug</td><td>the attribute element now has a optional ns attribute for the namespace URI of the generated attribute node and an attribute select for an XPATH expression that specifies the value of the generated attribute.</td><td>191</td></tr><tr><td>axiom</td><td>aug</td><td>the axiom element now has an optional for attribute which can point to a list of symbols. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism and an attribute type is now also allowed.</td><td>138</td></tr><tr><td>axiom-inclusion</td><td>lib</td><td>the axiom-inclusion element can now contain multiple path-just children to record multiple justifications. Furthermore, it can now have theory, generated-from, and generated-via attributes. New optional attributes conservativity and conservativity-just for stating and justifying conservativity.</td><td>180</td></tr><tr><td>catalogue</td><td>dep</td><td>the catalogue mechanism has been eliminated.</td><td></td></tr><tr><td>choice</td><td>cha</td><td>the choice element does not allow symbol children any more, if these are needed, the exercise should have its own theory</td><td>210</td></tr><tr><td>code</td><td>cha</td><td>Attributes classid and codebase are deprecated. The attributes pto and pto-version have moved to the data element. The attribute type has been removed and optional attributes theory, generated-from, and generated-via have been added.</td><td>202</td></tr><tr><td>commonname</td><td>dep</td><td>This element is deprecated in favor of a metadata/dc:subject element.</td><td></td></tr></table>	assumption	cha	This element can now have an attribute inductive for inductive assumptions. The natural language description in the optional CMP element is no longer allowed, use a phrase element in a CMP that is a sibling to the FMP instead.	145	adt	aug	the adt loses the CMP and commonname children, use the Dublin Core metadata elements dc:description and dc:subject instead. The type attribute is now on the sortdef element. Furthermore, an optionalala attribute generated-via has been added to allow generation via a theory morphism. Finally, an attribute parameters has been added to allow for parametric ADTs.	156	answer	cha	the answer element does not allow symbol children any more, if these are needed, the exercise should have its own theory.	210	attribute	aug	the attribute element now has a optional ns attribute for the namespace URI of the generated attribute node and an attribute select for an XPATH expression that specifies the value of the generated attribute.	191	axiom	aug	the axiom element now has an optional for attribute which can point to a list of symbols. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism and an attribute type is now also allowed.	138	axiom-inclusion	lib	the axiom-inclusion element can now contain multiple path-just children to record multiple justifications. Furthermore, it can now have theory , generated-from , and generated-via attributes. New optional attributes conservativity and conservativity-just for stating and justifying conservativity.	180	catalogue	dep	the catalogue mechanism has been eliminated.		choice	cha	the choice element does not allow symbol children any more, if these are needed, the exercise should have its own theory	210	code	cha	Attributes classid and codebase are deprecated. The attributes pto and pto-version have moved to the data element. The attribute type has been removed and optional attributes theory , generated-from , and generated-via have been added.	202	commonname	dep	This element is deprecated in favor of a metadata/dc:subject element.	
assumption	cha	This element can now have an attribute inductive for inductive assumptions. The natural language description in the optional CMP element is no longer allowed, use a phrase element in a CMP that is a sibling to the FMP instead.	145																																										
adt	aug	the adt loses the CMP and commonname children, use the Dublin Core metadata elements dc:description and dc:subject instead. The type attribute is now on the sortdef element. Furthermore, an optionalala attribute generated-via has been added to allow generation via a theory morphism. Finally, an attribute parameters has been added to allow for parametric ADTs.	156																																										
answer	cha	the answer element does not allow symbol children any more, if these are needed, the exercise should have its own theory.	210																																										
attribute	aug	the attribute element now has a optional ns attribute for the namespace URI of the generated attribute node and an attribute select for an XPATH expression that specifies the value of the generated attribute.	191																																										
axiom	aug	the axiom element now has an optional for attribute which can point to a list of symbols. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism and an attribute type is now also allowed.	138																																										
axiom-inclusion	lib	the axiom-inclusion element can now contain multiple path-just children to record multiple justifications. Furthermore, it can now have theory , generated-from , and generated-via attributes. New optional attributes conservativity and conservativity-just for stating and justifying conservativity.	180																																										
catalogue	dep	the catalogue mechanism has been eliminated.																																											
choice	cha	the choice element does not allow symbol children any more, if these are needed, the exercise should have its own theory	210																																										
code	cha	Attributes classid and codebase are deprecated. The attributes pto and pto-version have moved to the data element. The attribute type has been removed and optional attributes theory , generated-from , and generated-via have been added.	202																																										
commonname	dep	This element is deprecated in favor of a metadata/dc:subject element.																																											


Identifier	Page	Conf.	LaTeX source	Rendered	Image																																												
kohlhase-omdoc_TAB_068	322	0.792	<pre>\begin{tabular}[t]{ l l l l } \hline conclusion & cha & The natural language description in the optional CMP element is no longer allowed, use a phrase element in a CMP that is a sibling to the FMP instead. & 124 \\ \hline constructor & cha & The role attribute is now fixed to object. The commonname child has been replaced by an initial metadata element. & 156 \\ \hline data & aug & new optional attributes original to specify whether the external resource referenced by the href attribute (value external) or the data content is the original (value local). The data element has acquired attributes pto and pto-version from the code and private elements. & 203 \\ \hline dc:* & aug & All Dublin Core tags have been lowercased to synchronize with the tag syntax recommended by the Dublin Core Initiative. The tags were capitalized in OMDoc1.1. Furthermore, dc:contributor, dc:creator, dc:publisher have received an optional xml:id attribute, so that they can be crossreferenced by the new who of the dc : date element. & 98 \\ \hline decomposition & aug & The for attribute is now optional, it need not be given, if the element is a child of a theory-inclusion element. Furthermore, it</pre>		<table><tr><td>conclusion</td><td>cha</td><td>The natural language description in the optional CMP element is no longer allowed, use a phrase element in a CMP that is a sibling to the FMP instead.</td><td>124</td></tr><tr><td>constructor</td><td>cha</td><td>The role attribute is now fixed to object. The commonname child has been replaced by an initial metadata element.</td><td>156</td></tr><tr><td>data</td><td>aug</td><td>new optional attributes original to specify whether the external resource referenced by the href attribute (value external) or the data content is the original (value local). The data element has acquired attributes pto and pto-version from the code and private elements.</td><td>203</td></tr><tr><td>dc:*</td><td>aug</td><td>All Dublin Core tags have been lowercased to synchronize with the tag syntax recommended by the Dublin Core Initiative. The tags were capitalized in OMDoc1.1. Furthermore, dc:contributor, dc:creator, dc:publisher have received an optional xml:id attribute, so that they can be cross-referenced by the new who of the dc:date element.</td><td>98</td></tr><tr><td>decomposition</td><td>aug</td><td>The for attribute is now optional, it need not be given, if the element is a child of a theory-inclusion element. Furthermore, it can now have a theory, generated-from, and generated-via attributes.</td><td>184</td></tr><tr><td>dc:description</td><td>aug</td><td>The dc:description can now have the optional xml:id, and CSS attributes</td><td>99</td></tr><tr><td>definition</td><td>aug</td><td>The definition element can now have the type pattern for pattern-defined functions. This is a degenerate case of the type inductive. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism.</td><td>139</td></tr><tr><td>effect</td><td>aug</td><td>allows an optional xml:id attribute</td><td>204</td></tr><tr><td>example</td><td>aug</td><td>The example element now has the optional theory attribute that specifies the home theory. Furthermore, it can now have attributes theory, generated-from, and generated-via.</td><td>146</td></tr><tr><td>exercise</td><td>cha</td><td>the exercise element does not allow symbol children any more, if these are needed, the exercise should have its own theory. Furthermore, it can now have a theory, generated-from, and generated-via attributes.</td><td>209</td></tr><tr><td>extradata</td><td>cha</td><td>The content of the old extradata element can now be directly in the metadata/dc:subject element.</td><td></td></tr></table>	conclusion	cha	The natural language description in the optional CMP element is no longer allowed, use a phrase element in a CMP that is a sibling to the FMP instead.	124	constructor	cha	The role attribute is now fixed to object. The commonname child has been replaced by an initial metadata element.	156	data	aug	new optional attributes original to specify whether the external resource referenced by the href attribute (value external) or the data content is the original (value local). The data element has acquired attributes pto and pto-version from the code and private elements.	203	dc:*	aug	All Dublin Core tags have been lowercased to synchronize with the tag syntax recommended by the Dublin Core Initiative. The tags were capitalized in OMDoc1.1. Furthermore, dc:contributor, dc:creator, dc:publisher have received an optional xml:id attribute, so that they can be cross-referenced by the new who of the dc:date element.	98	decomposition	aug	The for attribute is now optional, it need not be given, if the element is a child of a theory-inclusion element. Furthermore, it can now have a theory, generated-from, and generated-via attributes.	184	dc:description	aug	The dc:description can now have the optional xml:id, and CSS attributes	99	definition	aug	The definition element can now have the type pattern for pattern-defined functions. This is a degenerate case of the type inductive. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism.	139	effect	aug	allows an optional xml:id attribute	204	example	aug	The example element now has the optional theory attribute that specifies the home theory. Furthermore, it can now have attributes theory, generated-from, and generated-via.	146	exercise	cha	the exercise element does not allow symbol children any more, if these are needed, the exercise should have its own theory. Furthermore, it can now have a theory, generated-from, and generated-via attributes.	209	extradata	cha	The content of the old extradata element can now be directly in the metadata/dc:subject element.	
conclusion	cha	The natural language description in the optional CMP element is no longer allowed, use a phrase element in a CMP that is a sibling to the FMP instead.	124																																														
constructor	cha	The role attribute is now fixed to object. The commonname child has been replaced by an initial metadata element.	156																																														
data	aug	new optional attributes original to specify whether the external resource referenced by the href attribute (value external) or the data content is the original (value local). The data element has acquired attributes pto and pto-version from the code and private elements.	203																																														
dc:*	aug	All Dublin Core tags have been lowercased to synchronize with the tag syntax recommended by the Dublin Core Initiative. The tags were capitalized in OMDoc1.1. Furthermore, dc:contributor, dc:creator, dc:publisher have received an optional xml:id attribute, so that they can be cross-referenced by the new who of the dc:date element.	98																																														
decomposition	aug	The for attribute is now optional, it need not be given, if the element is a child of a theory-inclusion element. Furthermore, it can now have a theory, generated-from, and generated-via attributes.	184																																														
dc:description	aug	The dc:description can now have the optional xml:id, and CSS attributes	99																																														
definition	aug	The definition element can now have the type pattern for pattern-defined functions. This is a degenerate case of the type inductive. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism.	139																																														
effect	aug	allows an optional xml:id attribute	204																																														
example	aug	The example element now has the optional theory attribute that specifies the home theory. Furthermore, it can now have attributes theory, generated-from, and generated-via.	146																																														
exercise	cha	the exercise element does not allow symbol children any more, if these are needed, the exercise should have its own theory. Furthermore, it can now have a theory, generated-from, and generated-via attributes.	209																																														
extradata	cha	The content of the old extradata element can now be directly in the metadata/dc:subject element.																																															


Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																				
kohlhase-omdoc_TAB_069	323	0.990	<pre>\begin{tabular}[t]{ l l l l } \hline element & aug & The element element now allows the map and separator elements in the body. Furthermore, it carries the optional attributes crid for parallel markup, cr for cross-references, and ns for specifying the namespace. & 190 \\ \hline hint & aug & the hint element can now appear on toplevel and has a for attribute. It does not allow symbol children any more, if these are needed, the exercise should have its own theory. Furthermore, the exercise can now have a theory, generated-from, and generated-via attributes. & 209 \\ \hline hypothesis & cha & the discharged-in attribute has been eliminated. Scoping is now specified in terms of the enclosing proof element. Furthermore, the symbol child is no longer allowed inside the element. A sibling symbol should be used. & 162 \\ \hline inclusion & aug & allows optional attributes xml:id, conservativity, and conservativity-just for stating and justifying conservativity. & 179 \\ \hline imports & lib & the xml:id is now optional. New optional attributes conservativity and conservativity-just for stating and justifying conservativity. & 150 \\ \hline input & aug & allows an optional xml:id attribute & 204 \\ \hline legacy & new & An element for encapsulating legacy mathematics, can be used wherever m:math and om:OMOBJ are allowed. & 120 \\ \hline loc & dep & The catalogue mechanism has been eliminated. & \\ \hline m:math & new & Content-MATHML is now allowed wherever OPENMATH objects were allowed before. & 114 \\ \hline map & new & this element allows to map its style directives over a list of e.g. arguments & 191 \\ \hline mc & aug & the mc element can now have a for attribute. It does not allow symbol children any more, if these are needed, the dominating exercise element should have its own theory. Furthermore, the mc element can now have a theory, generated-from, and generated-via attributes. & 210 \\ \hline measure & aug & allows an optional xml:id attribute & 141 \\ \hline metacomment & dep & This element is superseded by the omtext element. & 124 \\ \hline \end{tabular}</pre>		<table><tr><td>element</td><td>aug</td><td>The element element now allows the map and separator elements in the body. Furthermore, it carries the optional attributes crid for parallel markup, cr for cross-references, and ns for specifying the namespace.</td><td>190</td></tr><tr><td>hint</td><td>aug</td><td>the hint element can now appear on toplevel and has a for attribute. It does not allow symbol children any more, if these are needed, the exercise should have its own theory. Furthermore, the exercise can now have a theory, generated-from, and generated-via attributes.</td><td>209</td></tr><tr><td>hypothesis</td><td>cha</td><td>the discharged-in attribute has been eliminated. Scoping is now specified in terms of the enclosing proof element. Furthermore, the symbol child is no longer allowed inside the element. A sibling symbol should be used.</td><td>162</td></tr><tr><td>inclusion</td><td>aug</td><td>allows optional attributes xml:id, conservativity, and conservativity-just for stating and justifying conservativity.</td><td>179</td></tr><tr><td>imports</td><td>lib</td><td>the xml:id is now optional. New optional attributes conservativity and conservativity-just for stating and justifying conservativity.</td><td>150</td></tr><tr><td>input</td><td>aug</td><td>allows an optional xml:id attribute</td><td>204</td></tr><tr><td>legacy</td><td>new</td><td>An element for encapsulating legacy mathematics, can be used wherever m:math and om:OMOBJ are allowed.</td><td>120</td></tr><tr><td>loc</td><td>dep</td><td>The catalogue mechanism has been eliminated.</td><td></td></tr><tr><td>m:math</td><td>new</td><td>Content-MATHML is now allowed wherever OPENMATH objects were allowed before.</td><td>114</td></tr><tr><td>map</td><td>new</td><td>this element allows to map its style directives over a list of e.g. arguments</td><td>191</td></tr><tr><td>mc</td><td>aug</td><td>the mc element can now have a for attribute. It does not allow symbol children any more, if these are needed, the dominating exercise element should have its own theory. Furthermore, the mc element can now have a theory, generated-from, and generated-via attributes.</td><td>210</td></tr><tr><td>measure</td><td>aug</td><td>allows an optional xml:id attribute</td><td>141</td></tr><tr><td>metacomment</td><td>dep</td><td>This element is superseded by the omtext element.</td><td>124</td></tr></table>	element	aug	The element element now allows the map and separator elements in the body. Furthermore, it carries the optional attributes crid for parallel markup, cr for cross-references, and ns for specifying the namespace.	190	hint	aug	the hint element can now appear on toplevel and has a for attribute. It does not allow symbol children any more, if these are needed, the exercise should have its own theory. Furthermore, the exercise can now have a theory, generated-from, and generated-via attributes.	209	hypothesis	cha	the discharged-in attribute has been eliminated. Scoping is now specified in terms of the enclosing proof element. Furthermore, the symbol child is no longer allowed inside the element. A sibling symbol should be used.	162	inclusion	aug	allows optional attributes xml:id, conservativity, and conservativity-just for stating and justifying conservativity.	179	imports	lib	the xml:id is now optional. New optional attributes conservativity and conservativity-just for stating and justifying conservativity.	150	input	aug	allows an optional xml:id attribute	204	legacy	new	An element for encapsulating legacy mathematics, can be used wherever m:math and om:OMOBJ are allowed.	120	loc	dep	The catalogue mechanism has been eliminated.		m:math	new	Content-MATHML is now allowed wherever OPENMATH objects were allowed before.	114	map	new	this element allows to map its style directives over a list of e.g. arguments	191	mc	aug	the mc element can now have a for attribute. It does not allow symbol children any more, if these are needed, the dominating exercise element should have its own theory. Furthermore, the mc element can now have a theory, generated-from, and generated-via attributes.	210	measure	aug	allows an optional xml:id attribute	141	metacomment	dep	This element is superseded by the omtext element.	124
element	aug	The element element now allows the map and separator elements in the body. Furthermore, it carries the optional attributes crid for parallel markup, cr for cross-references, and ns for specifying the namespace.	190																																																						
hint	aug	the hint element can now appear on toplevel and has a for attribute. It does not allow symbol children any more, if these are needed, the exercise should have its own theory. Furthermore, the exercise can now have a theory, generated-from, and generated-via attributes.	209																																																						
hypothesis	cha	the discharged-in attribute has been eliminated. Scoping is now specified in terms of the enclosing proof element. Furthermore, the symbol child is no longer allowed inside the element. A sibling symbol should be used.	162																																																						
inclusion	aug	allows optional attributes xml:id, conservativity, and conservativity-just for stating and justifying conservativity.	179																																																						
imports	lib	the xml:id is now optional. New optional attributes conservativity and conservativity-just for stating and justifying conservativity.	150																																																						
input	aug	allows an optional xml:id attribute	204																																																						
legacy	new	An element for encapsulating legacy mathematics, can be used wherever m:math and om:OMOBJ are allowed.	120																																																						
loc	dep	The catalogue mechanism has been eliminated.																																																							
m:math	new	Content-MATHML is now allowed wherever OPENMATH objects were allowed before.	114																																																						
map	new	this element allows to map its style directives over a list of e.g. arguments	191																																																						
mc	aug	the mc element can now have a for attribute. It does not allow symbol children any more, if these are needed, the dominating exercise element should have its own theory. Furthermore, the mc element can now have a theory, generated-from, and generated-via attributes.	210																																																						
measure	aug	allows an optional xml:id attribute	141																																																						
metacomment	dep	This element is superseded by the omtext element.	124																																																						


Identifier	Page	Conf.	LaTeX source	Rendered	Image																																												
kohlhase-omdoc_TAB_070	324	0.658	<pre>\begin{tabular}[t]{t}{ l l l l l } \hline morphism & aug & The morphism element now carries the optional attributes consistency, exhaustivity, hiding, and type. Furthermore the content model allows optional elements measure and ordering after the reequation children to specify termination information like in definition. & 92 \\ \hline obligation & aug & allows an optional xml:id attribute & 178 \\ \hline omdoc & aug & This element can now have a theory, generated-from, and generated-via attributes. & 90 \\ \hline omgroup & cha & The values dataset and labeled-dataset are deprecated in Version 1.2 of OMDoc, since we provide tables in module RT; see Section 14.6 for details. Furthermore, the element can now have the attributes, modules, theory, generated-from, and generated-via. & 93 \\ \hline omlet & cha & omlet can no longer occur at top-level (it just does not make sense). The data model for this element has been totally reworked, inspired by the xhtml:object element. & 205 \\ \hline omstyle & aug & This element can now have generated-from, and generated-via attributes. New attribute xref that allows to inherit the information from another omstyle element. & 188 \\ \hline om:* & aug & with OPENMATH2, the OPENMATH elements carry an optional id attribute for structure sharing via the om:OMR element. Furthermore, in OMDoc, they carry cref attributes for parallel markup with cross-references. & 108 \\ \hline om:OMFOREIGN & new & The om:OMFOREIGN element can be used to encapsulate arbitrary XML data in OPENMATH attributions. & 110 \\ \hline om:OMR & new & In the OPENMATH2 standard, this element is the main vehicle of the structure sharing representation. & 112 \\ \hline omtext & aug & the type attribute can now also have the values axiom, definition, theorem, proposition, lemma, corollary, postulate, conjecture, false-conjecture, obligation, assumption, and formula. Furthermore, omtext can now have theory, generated-from, and generated-via and verbalizes attributes. & 124 \\ \hline ordering & aug & Now allows the optional xml:id and terminating attributes. The latter points to a termination assertion. & 141 \\ \hline \end{tabular}</pre>		<table><tr><td>morphism</td><td>aug</td><td>The morphism element now carries the optional attributes consistency, exhaustivity, hiding, and type. Furthermore the content model allows optional elements measure and ordering after the reequation children to specify termination information like in definition.</td><td>92</td></tr><tr><td>obligation</td><td>aug</td><td>allows an optional xml:id attribute</td><td>178</td></tr><tr><td>omdoc</td><td>aug</td><td>This element can now have a theory, generated-from, and generated-via attributes.</td><td>90</td></tr><tr><td>omgroup</td><td>cha</td><td>The values dataset and labeled-dataset are deprecated in Version 1.2 of OMDoc, since we provide tables in module RT; see Section 14.6 for details. Furthermore, the element can now have the attributes, modules, theory, generated-from, and generated-via.</td><td>93</td></tr><tr><td>omlet</td><td>cha</td><td>omlet can no longer occur at top-level (it just does not make sense). The data model for this element has been totally reworked, inspired by the xhtml:object element.</td><td>205</td></tr><tr><td>omstyle</td><td>aug</td><td>This element can now have generated-from, and generated-via attributes. New attribute xref that allows to inherit the information from another omstyle element.</td><td>188</td></tr><tr><td>om:*</td><td>aug</td><td>with OPENMATH2, the OPENMATH elements carry an optional id attribute for structure sharing via the om:OMR element. Furthermore, in OMDoc, they carry cref attributes for parallel markup with cross-references.</td><td>108</td></tr><tr><td>om:OMFOREIGN</td><td>new</td><td>The om:OMFOREIGN element can be used to encapsulate arbitrary XML data in OPENMATH attributions.</td><td>110</td></tr><tr><td>om:OMR</td><td>new</td><td>In the OPENMATH2 standard, this element is the main vehicle of the structure sharing representation.</td><td>112</td></tr><tr><td>omtext</td><td>aug</td><td>the type attribute can now also have the values axiom, definition, theorem, proposition, lemma, corollary, postulate, conjecture, false-conjecture, obligation, assumption, and formula. Furthermore, omtext can now have theory, generated-from, and generated-via and verbalizes attributes.</td><td>124</td></tr><tr><td>ordering</td><td>aug</td><td>Now allows the optional xml:id and terminating attributes. The latter points to a termination assertion.</td><td>141</td></tr></table>	morphism	aug	The morphism element now carries the optional attributes consistency, exhaustivity, hiding, and type. Furthermore the content model allows optional elements measure and ordering after the reequation children to specify termination information like in definition.	92	obligation	aug	allows an optional xml:id attribute	178	omdoc	aug	This element can now have a theory, generated-from, and generated-via attributes.	90	omgroup	cha	The values dataset and labeled-dataset are deprecated in Version 1.2 of OMDoc, since we provide tables in module RT; see Section 14.6 for details. Furthermore, the element can now have the attributes, modules, theory, generated-from, and generated-via.	93	omlet	cha	omlet can no longer occur at top-level (it just does not make sense). The data model for this element has been totally reworked, inspired by the xhtml:object element.	205	omstyle	aug	This element can now have generated-from, and generated-via attributes. New attribute xref that allows to inherit the information from another omstyle element.	188	om:*	aug	with OPENMATH2, the OPENMATH elements carry an optional id attribute for structure sharing via the om:OMR element. Furthermore, in OMDoc, they carry cref attributes for parallel markup with cross-references.	108	om:OMFOREIGN	new	The om:OMFOREIGN element can be used to encapsulate arbitrary XML data in OPENMATH attributions.	110	om:OMR	new	In the OPENMATH2 standard, this element is the main vehicle of the structure sharing representation.	112	omtext	aug	the type attribute can now also have the values axiom, definition, theorem, proposition, lemma, corollary, postulate, conjecture, false-conjecture, obligation, assumption, and formula. Furthermore, omtext can now have theory, generated-from, and generated-via and verbalizes attributes.	124	ordering	aug	Now allows the optional xml:id and terminating attributes. The latter points to a termination assertion.	141
morphism	aug	The morphism element now carries the optional attributes consistency, exhaustivity, hiding, and type. Furthermore the content model allows optional elements measure and ordering after the reequation children to specify termination information like in definition.	92																																														
obligation	aug	allows an optional xml:id attribute	178																																														
omdoc	aug	This element can now have a theory, generated-from, and generated-via attributes.	90																																														
omgroup	cha	The values dataset and labeled-dataset are deprecated in Version 1.2 of OMDoc, since we provide tables in module RT; see Section 14.6 for details. Furthermore, the element can now have the attributes, modules, theory, generated-from, and generated-via.	93																																														
omlet	cha	omlet can no longer occur at top-level (it just does not make sense). The data model for this element has been totally reworked, inspired by the xhtml:object element.	205																																														
omstyle	aug	This element can now have generated-from, and generated-via attributes. New attribute xref that allows to inherit the information from another omstyle element.	188																																														
om:*	aug	with OPENMATH2, the OPENMATH elements carry an optional id attribute for structure sharing via the om:OMR element. Furthermore, in OMDoc, they carry cref attributes for parallel markup with cross-references.	108																																														
om:OMFOREIGN	new	The om:OMFOREIGN element can be used to encapsulate arbitrary XML data in OPENMATH attributions.	110																																														
om:OMR	new	In the OPENMATH2 standard, this element is the main vehicle of the structure sharing representation.	112																																														
omtext	aug	the type attribute can now also have the values axiom, definition, theorem, proposition, lemma, corollary, postulate, conjecture, false-conjecture, obligation, assumption, and formula. Furthermore, omtext can now have theory, generated-from, and generated-via and verbalizes attributes.	124																																														
ordering	aug	Now allows the optional xml:id and terminating attributes. The latter points to a termination assertion.	141																																														

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																															
kohlhase-omdoc_TAB_071	325	1.000	<pre>\begin{tabular}{t}{ l l l l } \hline output & aug & allows an optional xml:id attribute & 204 \\ \hline pattern & aug & this element is no longer used, the pattern of a recursive equation is determined by the position as the first child. & \\ \hline path-just & aug & The element can now appear as a toplevel element, if it does, the attribute for must point to the axiom-inclusion element it justifies. It also now allows an optional xml:id attribute & 184 \\ \hline phrase & new & used to mark up phrases in CMPs and supply them with identifiers and links to context that can be used for presentation and referencing. & 126 \\ \hline presentation & cha & The theory is not allowed any more, to refer to a symbol outside its theory use its xml:id attribute. The element now also allows a multilingual CMP group, so that it can be used as a notation definition element in mathematical vernacular. & 192 \\ \hline private & cha & The replaces attribute is now called reformulates. The attributes pto and pto-version have moved to the data element. The attribute type has been removed and optional attributes theory, generated-from, and generated-via have been added. & 202 \\ \hline proof & lib & The for attribute is now optional to allow for proofs as objects of mathematical discourse. Furthermore, it can now have generated-from and generated-via attributes. & 161 \\ \hline proofobject & lib & The for attribute is now optional to allow for proofs as objects of mathematical discourse. Furthermore, it can now have generated-from and generated-via attributes. & 169 \\ \hline recognizer & cha & The role attribute was fixed to object. The commonname child has been replaced by an initial metadata element. & 157 \\ \hline ref & aug & ref now has an optional xml:id attribute that identifies it. & 94 \\ \hline selector & cha & The role attribute was fixed to object. The commonname child has been replaced by an initial metadata element. & 157 \\ \hline solution & cha & the solution element now allows arbitrary OMDoc top-level elements as children. Furthermore, it can now have a theory, generated-from, and generated-via attributes. & 209 \\ \hline\end{tabular}</pre>	<table><tr><td>output</td><td>aug</td><td>allows an optional <code>xml:id</code> attribute</td><td>204</td></tr><tr><td>pattern</td><td>aug</td><td>this element is no longer used, the pattern of a recursive equation is determined by the position as the first child.</td><td></td></tr><tr><td>path-just</td><td>aug</td><td>The element can now appear as a toplevel element, if it does, the attribute <code>for</code> must point to the <code>axiom-inclusion</code> element it justifies. It also now allows an optional <code>xml:id</code> attribute</td><td>184</td></tr><tr><td>phrase</td><td>new</td><td>used to mark up phrases in CMPs and supply them with identifiers and links to context that can be used for presentation and referencing.</td><td>126</td></tr><tr><td>presentation</td><td>cha</td><td>The <code>theory</code> is not allowed any more, to refer to a symbol outside its theory use its <code>xml:id</code> attribute. The element now also allows a multilingual CMP group, so that it can be used as a notation definition element in mathematical vernacular.</td><td>192</td></tr><tr><td>private</td><td>cha</td><td>The <code>replaces</code> attribute is now called <code>reformulates</code>. The attributes <code>pto</code> and <code>pto-version</code> have moved to the <code>data</code> element. The attribute <code>type</code> has been removed and optional attributes <code>theory</code>, <code>generated-from</code>, and <code>generated-via</code> have been added.</td><td>202</td></tr><tr><td>proof</td><td>lib</td><td>The <code>for</code> attribute is now optional to allow for proofs as objects of mathematical discourse. Furthermore, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.</td><td>161</td></tr><tr><td>proofobject</td><td>lib</td><td>The <code>for</code> attribute is now optional to allow for proofs as objects of mathematical discourse. Furthermore, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.</td><td>169</td></tr><tr><td>recognizer</td><td>cha</td><td>The <code>role</code> attribute was fixed to <code>object</code>. The <code>commonname</code> child has been replaced by an initial <code>metadata</code> element.</td><td>157</td></tr><tr><td>ref</td><td>aug</td><td><code>ref</code> now has an optional <code>xml:id</code> attribute that identifies it.</td><td>94</td></tr><tr><td>selector</td><td>cha</td><td>The <code>role</code> attribute was fixed to <code>object</code>. The <code>commonname</code> child has been replaced by an initial <code>metadata</code> element.</td><td>157</td></tr><tr><td>solution</td><td>cha</td><td>the <code>solution</code> element now allows arbitrary OMDoc top-level elements as children. Furthermore, it can now have a <code>theory</code>, <code>generated-from</code>, and <code>generated-via</code> attributes.</td><td>209</td></tr></table>	output	aug	allows an optional <code>xml:id</code> attribute	204	pattern	aug	this element is no longer used, the pattern of a recursive equation is determined by the position as the first child.		path-just	aug	The element can now appear as a toplevel element, if it does, the attribute <code>for</code> must point to the <code>axiom-inclusion</code> element it justifies. It also now allows an optional <code>xml:id</code> attribute	184	phrase	new	used to mark up phrases in CMPs and supply them with identifiers and links to context that can be used for presentation and referencing.	126	presentation	cha	The <code>theory</code> is not allowed any more, to refer to a symbol outside its theory use its <code>xml:id</code> attribute. The element now also allows a multilingual CMP group, so that it can be used as a notation definition element in mathematical vernacular.	192	private	cha	The <code>replaces</code> attribute is now called <code>reformulates</code> . The attributes <code>pto</code> and <code>pto-version</code> have moved to the <code>data</code> element. The attribute <code>type</code> has been removed and optional attributes <code>theory</code> , <code>generated-from</code> , and <code>generated-via</code> have been added.	202	proof	lib	The <code>for</code> attribute is now optional to allow for proofs as objects of mathematical discourse. Furthermore, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.	161	proofobject	lib	The <code>for</code> attribute is now optional to allow for proofs as objects of mathematical discourse. Furthermore, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.	169	recognizer	cha	The <code>role</code> attribute was fixed to <code>object</code> . The <code>commonname</code> child has been replaced by an initial <code>metadata</code> element.	157	ref	aug	<code>ref</code> now has an optional <code>xml:id</code> attribute that identifies it.	94	selector	cha	The <code>role</code> attribute was fixed to <code>object</code> . The <code>commonname</code> child has been replaced by an initial <code>metadata</code> element.	157	solution	cha	the <code>solution</code> element now allows arbitrary OMDoc top-level elements as children. Furthermore, it can now have a <code>theory</code> , <code>generated-from</code> , and <code>generated-via</code> attributes.	209
output	aug	allows an optional <code>xml:id</code> attribute	204																																																	
pattern	aug	this element is no longer used, the pattern of a recursive equation is determined by the position as the first child.																																																		
path-just	aug	The element can now appear as a toplevel element, if it does, the attribute <code>for</code> must point to the <code>axiom-inclusion</code> element it justifies. It also now allows an optional <code>xml:id</code> attribute	184																																																	
phrase	new	used to mark up phrases in CMPs and supply them with identifiers and links to context that can be used for presentation and referencing.	126																																																	
presentation	cha	The <code>theory</code> is not allowed any more, to refer to a symbol outside its theory use its <code>xml:id</code> attribute. The element now also allows a multilingual CMP group, so that it can be used as a notation definition element in mathematical vernacular.	192																																																	
private	cha	The <code>replaces</code> attribute is now called <code>reformulates</code> . The attributes <code>pto</code> and <code>pto-version</code> have moved to the <code>data</code> element. The attribute <code>type</code> has been removed and optional attributes <code>theory</code> , <code>generated-from</code> , and <code>generated-via</code> have been added.	202																																																	
proof	lib	The <code>for</code> attribute is now optional to allow for proofs as objects of mathematical discourse. Furthermore, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.	161																																																	
proofobject	lib	The <code>for</code> attribute is now optional to allow for proofs as objects of mathematical discourse. Furthermore, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.	169																																																	
recognizer	cha	The <code>role</code> attribute was fixed to <code>object</code> . The <code>commonname</code> child has been replaced by an initial <code>metadata</code> element.	157																																																	
ref	aug	<code>ref</code> now has an optional <code>xml:id</code> attribute that identifies it.	94																																																	
selector	cha	The <code>role</code> attribute was fixed to <code>object</code> . The <code>commonname</code> child has been replaced by an initial <code>metadata</code> element.	157																																																	
solution	cha	the <code>solution</code> element now allows arbitrary OMDoc top-level elements as children. Furthermore, it can now have a <code>theory</code> , <code>generated-from</code> , and <code>generated-via</code> attributes.	209																																																	

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																
kohlhase-omdoc_TAB_072	326	1.000	<pre>\begin{tabular}[t]{t}{ l l l l l } \hline sortdef & cha & The role attribute was fixed to sort. The type from the adt element is now on the sortdef element. The commonname child has been replaced by an initial metadata element. & 156 \\ \hline dc:subject & aug & The dc:subject can now have the optional dc:id, and CSS attributes & 99 \\ \hline style & aug & The style element now allows a map element in the body & 189 \\ \hline symbol & cha & may no longer contain selector, since it only makes sense for constructors in data types. The kind attribute has been renamed to role for compatibility with OpenMath2 and can have the additional values binder, attribution, semantic-attribution, and error corresponding to the OpenMath 2 roles. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism. & 136 \\ \hline term & new & the term element can appear in mathematical text and contain it. It is used to link technical terms to symbols defined in content dictionaries via its cd and name attributes. & 128 \\ \hline theory & cha & the theory element loses the CMP and commonname children, use the Dublin Core metadata elements dc:description and dc:subject instead. The theory element also gains the optional cdbase attribute to specify the disambiguating string prescribed for content dictionaries by the OpenMath2 standard. The xml:id is now optional, it only needs to be specified, if the theory has constitutive elements. Finally, the element has gained the optional attributes cdurl, cdbase, cdreviewdate, cdversion, cdrevision, and cdstatus attributes for encoding the management metadata of OPENMATH content dictionaries. & 149 \\ \hline dc:title & aug & The dc:title can now have the optional dc:id, and CSS attributes. & 98 \\ \hline tgroup & new & The tgroup can be used to structure theories like documents. & 149 \end{tabular}</pre>		<table><tr><td>sortdef</td><td>cha</td><td>The role attribute was fixed to sort. The type from the adt element is now on the sortdef element. The commonname child has been replaced by an initial metadata element.</td><td>156</td></tr><tr><td>dc:subject</td><td>aug</td><td>The dc:subject can now have the optional dc:id, and CSS attributes</td><td>99</td></tr><tr><td>style</td><td>aug</td><td>The style element now allows a map element in the body</td><td>189</td></tr><tr><td>symbol</td><td>cha</td><td>may no longer contain selector, since it only makes sense for constructors in data types. The kind attribute has been renamed to role for compatibility with OPENMATH2 and can have the additional values binder, attribution, semantic-attribution, and error corresponding to the OPENMATH 2 roles. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism.</td><td>136</td></tr><tr><td>term</td><td>new</td><td>the term element can appear in mathematical text and contain it. It is used to link technical terms to symbols defined in content dictionaries via its cd and name attributes.</td><td>128</td></tr><tr><td>theory</td><td>cha</td><td>the theory element loses the CMP and commonname children, use the Dublin Core metadata elements dc:description and dc:subject instead. The theory element also gains the optional cdbase attribute to specify the disambiguating string prescribed for content dictionaries by the OPENMATH2 standard. The xml:id is now optional, it only needs to be specified, if the theory has constitutive elements. Finally, the element has gained the optional attributes cdurl, cdbase, cdreviewdate, cdversion, cdrevision, and cdstatus attributes for encoding the management metadata of OPENMATH content dictionaries.</td><td>149</td></tr><tr><td>dc:title</td><td>aug</td><td>The dc:title can now have the optional dc:id, and CSS attributes.</td><td>98</td></tr><tr><td>tgroup</td><td>new</td><td>The tgroup can be used to structure theories like documents.</td><td>149</td></tr></table>	sortdef	cha	The role attribute was fixed to sort. The type from the adt element is now on the sortdef element. The commonname child has been replaced by an initial metadata element.	156	dc:subject	aug	The dc:subject can now have the optional dc:id, and CSS attributes	99	style	aug	The style element now allows a map element in the body	189	symbol	cha	may no longer contain selector, since it only makes sense for constructors in data types. The kind attribute has been renamed to role for compatibility with OPENMATH2 and can have the additional values binder, attribution, semantic-attribution, and error corresponding to the OPENMATH 2 roles. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism.	136	term	new	the term element can appear in mathematical text and contain it. It is used to link technical terms to symbols defined in content dictionaries via its cd and name attributes.	128	theory	cha	the theory element loses the CMP and commonname children, use the Dublin Core metadata elements dc:description and dc:subject instead. The theory element also gains the optional cdbase attribute to specify the disambiguating string prescribed for content dictionaries by the OPENMATH2 standard. The xml:id is now optional, it only needs to be specified, if the theory has constitutive elements. Finally, the element has gained the optional attributes cdurl, cdbase, cdreviewdate, cdversion, cdrevision, and cdstatus attributes for encoding the management metadata of OPENMATH content dictionaries.	149	dc:title	aug	The dc:title can now have the optional dc:id, and CSS attributes.	98	tgroup	new	The tgroup can be used to structure theories like documents.	149
sortdef	cha	The role attribute was fixed to sort. The type from the adt element is now on the sortdef element. The commonname child has been replaced by an initial metadata element.	156																																		
dc:subject	aug	The dc:subject can now have the optional dc:id, and CSS attributes	99																																		
style	aug	The style element now allows a map element in the body	189																																		
symbol	cha	may no longer contain selector, since it only makes sense for constructors in data types. The kind attribute has been renamed to role for compatibility with OPENMATH2 and can have the additional values binder, attribution, semantic-attribution, and error corresponding to the OPENMATH 2 roles. Furthermore, an optional attribute generated-via has been added to allow generation via a theory morphism.	136																																		
term	new	the term element can appear in mathematical text and contain it. It is used to link technical terms to symbols defined in content dictionaries via its cd and name attributes.	128																																		
theory	cha	the theory element loses the CMP and commonname children, use the Dublin Core metadata elements dc:description and dc:subject instead. The theory element also gains the optional cdbase attribute to specify the disambiguating string prescribed for content dictionaries by the OPENMATH2 standard. The xml:id is now optional, it only needs to be specified, if the theory has constitutive elements. Finally, the element has gained the optional attributes cdurl, cdbase, cdreviewdate, cdversion, cdrevision, and cdstatus attributes for encoding the management metadata of OPENMATH content dictionaries.	149																																		
dc:title	aug	The dc:title can now have the optional dc:id, and CSS attributes.	98																																		
tgroup	new	The tgroup can be used to structure theories like documents.	149																																		

Identifier	Page	Conf.	LaTeX source	Rendered	Image																												
kohlhase-omdoc_TAB_073	327	1.000	<pre>\begin{tabular}[t]{l l l l l} \hline type & aug & the type element now has the optional just-by and theory attribute. The first one points to an assertion or axiom that justifies the type judgment, the second specifies the home theory. The system attribute is now optional. \\ Furthermore, the type element can have two math objects as children. If it does, then it is a term declaration, i.e. the first element is interpreted as a mathematical object and the second one is interpreted as its type. \\ Finally, it can now have generated-from and generated-via attributes. \\ \end{tabular} & 139 \\ \hline theory-inclusion & aug & the theory-inclusion element can now have obligation and decomposition children that justify it. Furthermore, it can now have a theory, generated-from, and generated-via attributes. New optional attributes conservativity and conservativity-just for stating and justifying conservativity. \\ \hline theory & aug & the theory element can now be nested. \\ \hline use & cha & can now contain element, text, recurse, map, and value-of to specify XML content. We have deprecated the larg-group and rarg-group attributes, since they were never used. \\ \hline value & aug & this element is no longer used, the value of a recursive equation is determined by the position as the second child. \\ \hline with & ren & the role of this element is now taken by the phrase element. \\ \hline xslt & cha & the content of this element need not be escaped any more, it is now a valid XSLT fragment. \\ \hline \end{tabular}</pre>		<table><tr><td>type</td><td>aug</td><td>the <code>type</code> element now has the optional <code>just-by</code> and <code>theory</code> attribute. The first one points to an assertion or axiom that justifies the type judgment, the second specifies the home theory. The <code>system</code> attribute is now optional. Furthermore, the <code>type</code> element can have two math objects as children. If it does, then it is a term declaration, i.e. the first element is interpreted as a mathematical object and the second one is interpreted as its type. Finally, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.</td><td>139</td></tr><tr><td>theory-inclusion</td><td>aug</td><td>the <code>theory-inclusion</code> element can now have <code>obligation</code> and <code>decomposition</code> children that justify it. Furthermore, it can now have a <code>theory</code>, <code>generated-from</code>, and <code>generated-via</code> attributes. New optional attributes <code>conservativity</code> and <code>conservativity-just</code> for stating and justifying conservativity.</td><td>178</td></tr><tr><td>theory</td><td>aug</td><td>the <code>theory</code> element can now be nested.</td><td>149</td></tr><tr><td>use</td><td>cha</td><td>can now contain <code>element</code>, <code>text</code>, <code>recurse</code>, <code>map</code>, and <code>value-of</code> to specify XML content. We have deprecated the <code>larg-group</code> and <code>rarg-group</code> attributes, since they were never used.</td><td>194</td></tr><tr><td>value</td><td>aug</td><td>this element is no longer used, the value of a recursive equation is determined by the position as the second child.</td><td></td></tr><tr><td>with</td><td>ren</td><td>the role of this element is now taken by the <code>phrase</code> element.</td><td>126</td></tr><tr><td>xslt</td><td>cha</td><td>the content of this element need not be escaped any more, it is now a valid XSLT fragment.</td><td>189</td></tr></table>	type	aug	the <code>type</code> element now has the optional <code>just-by</code> and <code>theory</code> attribute. The first one points to an assertion or axiom that justifies the type judgment, the second specifies the home theory. The <code>system</code> attribute is now optional. Furthermore, the <code>type</code> element can have two math objects as children. If it does, then it is a term declaration, i.e. the first element is interpreted as a mathematical object and the second one is interpreted as its type. Finally, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.	139	theory-inclusion	aug	the <code>theory-inclusion</code> element can now have <code>obligation</code> and <code>decomposition</code> children that justify it. Furthermore, it can now have a <code>theory</code> , <code>generated-from</code> , and <code>generated-via</code> attributes. New optional attributes <code>conservativity</code> and <code>conservativity-just</code> for stating and justifying conservativity.	178	theory	aug	the <code>theory</code> element can now be nested.	149	use	cha	can now contain <code>element</code> , <code>text</code> , <code>recurse</code> , <code>map</code> , and <code>value-of</code> to specify XML content. We have deprecated the <code>larg-group</code> and <code>rarg-group</code> attributes, since they were never used.	194	value	aug	this element is no longer used, the value of a recursive equation is determined by the position as the second child.		with	ren	the role of this element is now taken by the <code>phrase</code> element.	126	xslt	cha	the content of this element need not be escaped any more, it is now a valid XSLT fragment.	189
type	aug	the <code>type</code> element now has the optional <code>just-by</code> and <code>theory</code> attribute. The first one points to an assertion or axiom that justifies the type judgment, the second specifies the home theory. The <code>system</code> attribute is now optional. Furthermore, the <code>type</code> element can have two math objects as children. If it does, then it is a term declaration, i.e. the first element is interpreted as a mathematical object and the second one is interpreted as its type. Finally, it can now have <code>generated-from</code> and <code>generated-via</code> attributes.	139																														
theory-inclusion	aug	the <code>theory-inclusion</code> element can now have <code>obligation</code> and <code>decomposition</code> children that justify it. Furthermore, it can now have a <code>theory</code> , <code>generated-from</code> , and <code>generated-via</code> attributes. New optional attributes <code>conservativity</code> and <code>conservativity-just</code> for stating and justifying conservativity.	178																														
theory	aug	the <code>theory</code> element can now be nested.	149																														
use	cha	can now contain <code>element</code> , <code>text</code> , <code>recurse</code> , <code>map</code> , and <code>value-of</code> to specify XML content. We have deprecated the <code>larg-group</code> and <code>rarg-group</code> attributes, since they were never used.	194																														
value	aug	this element is no longer used, the value of a recursive equation is determined by the position as the second child.																															
with	ren	the role of this element is now taken by the <code>phrase</code> element.	126																														
xslt	cha	the content of this element need not be escaped any more, it is now a valid XSLT fragment.	189																														

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																								
kohlhase-omdoc_TAB_074	328	1.000	<pre>\begin{tabular}[t]{t}{ l l l l l } \hline element & state & comments & cf. \\ \hline attribute & new & presentation of attributes for XML elements & 191 \\ \hline alternative & cha & new form of the alternative-def element, it can now also used as an alternative to axiom. Compared to alternative-def it has a new optional attribute generated-by to show that an assertion is generated by expanding a some other element like adt. & 145 \\ \hline alternative-def & dep & new form is alternative, since there can be alternative axioms too. & \\ \hline argument & cha & attribute sort is now of type IDREF, since it must be local in the definition. & 156 \\ \hline assertion & aug & more values for the type attribute, new optional attribute generated-by to show that an assertion is generated by expanding a definition or an adt. New optional attribute proofs. & 142 \\ \hline assertion-just & dep & this is now obligation & \\ \hline axiom & aug & new optional attribute generated-by to show that an axiom is generated by expanding a definition. & 138 \\ \hline axiom-inclusion & cha & now allows a CMP group for descriptive text, includes a set of obligation elements instead of an assertion-just. The timestamp attribute is deprecated, use dc:date with appropriate action instead & 180 \\ \hline CMP & cha & the attribute format is now deprecated, it makes no sense, since we are more strict and consistent about CMP content. CMP now allows an optional id attribute. & 122 \\ \hline code & cha & Attributes width and height now in omlet, got attributes classid and codebase from private. Attribute format moved to data children. The multilingual group of CMP elements for description is deprecated, use metadata/dc:description instead. Child element data may appear multiple times (with different values of the format). & 202 \\ \hline constructor & aug & new optional child recognizer for a recognizer predicate & 156 \\ \hline Coverage & dep & this Dublin Core element specifies the place or time which the publication's contents addresses. This does not seem appropriate for the mathematical content of OMDoc. & \\ \hline data & aug & new optional attributes size to specify the size of the data file that is referenced by the href attribute and format for the format the data is in. & 203 \\ \hline \end{tabular}</pre>		<table><tr><th>element</th><th>state</th><th>comments</th><th>cf.</th></tr><tr><td>attribute</td><td>new</td><td>presentation of attributes for XML elements</td><td>191</td></tr><tr><td>alternative</td><td>cha</td><td>new form of the <code>alternative-def</code> element, it can now also used as an alternative to <code>axiom</code>. Compared to <code>alternative-def</code> it has a new optional attribute <code>generated-by</code> to show that an assertion is generated by expanding a some other element like <code>adt</code>.</td><td>145</td></tr><tr><td>alternative-def</td><td>dep</td><td>new form is <code>alternative</code>, since there can be alternative <code>axioms</code> too.</td><td></td></tr><tr><td>argument</td><td>cha</td><td>attribute <code>sort</code> is now of type IDREF, since it must be local in the definition.</td><td>156</td></tr><tr><td>assertion</td><td>aug</td><td>more values for the <code>type</code> attribute, new optional attribute <code>generated-by</code> to show that an assertion is generated by expanding a <code>definition</code> or an <code>adt</code>. New optional attribute <code>proofs</code>.</td><td>142</td></tr><tr><td>assertion-just</td><td>dep</td><td>this is now obligation</td><td></td></tr><tr><td>axiom</td><td>aug</td><td>new optional attribute <code>generated-by</code> to show that an axiom is generated by expanding a <code>definition</code>.</td><td>138</td></tr><tr><td>axiom-inclusion</td><td>cha</td><td>now allows a <code>CMP</code> group for descriptive text, includes a set of <code>obligation</code> elements instead of an <code>assertion-just</code>. The <code>timestamp</code> attribute is deprecated, use <code>dc:date</code> with appropriate <code>action</code> instead</td><td>180</td></tr><tr><td>CMP</td><td>cha</td><td>the attribute <code>format</code> is now deprecated, it makes no sense, since we are more strict and consistent about <code>CMP</code> content. <code>CMP</code> now allows an optional <code>id</code> attribute.</td><td>122</td></tr><tr><td>code</td><td>cha</td><td>Attributes <code>width</code> and <code>height</code> now in <code>omlet</code>, got attributes <code>classid</code> and <code>codebase</code> from <code>private</code>. Attribute <code>format</code> moved to <code>data</code> children. The multilingual group of <code>CMP</code> elements for description is deprecated, use <code>metadata/dc:description</code> instead. Child element <code>data</code> may appear multiple times (with different values of the <code>format</code>).</td><td>202</td></tr><tr><td>constructor</td><td>aug</td><td>new optional child <code>recognizer</code> for a recognizer predicate</td><td>156</td></tr><tr><td>Coverage</td><td>dep</td><td>this Dublin Core element specifies the place or time which the publication's contents addresses. This does not seem appropriate for the mathematical content of OMDoc.</td><td></td></tr><tr><td>data</td><td>aug</td><td>new optional attributes <code>size</code> to specify the size of the data file that is referenced by the <code>href</code> attribute and <code>format</code> for the format the data is in.</td><td>203</td></tr></table>	element	state	comments	cf.	attribute	new	presentation of attributes for XML elements	191	alternative	cha	new form of the <code>alternative-def</code> element, it can now also used as an alternative to <code>axiom</code> . Compared to <code>alternative-def</code> it has a new optional attribute <code>generated-by</code> to show that an assertion is generated by expanding a some other element like <code>adt</code> .	145	alternative-def	dep	new form is <code>alternative</code> , since there can be alternative <code>axioms</code> too.		argument	cha	attribute <code>sort</code> is now of type IDREF, since it must be local in the definition.	156	assertion	aug	more values for the <code>type</code> attribute, new optional attribute <code>generated-by</code> to show that an assertion is generated by expanding a <code>definition</code> or an <code>adt</code> . New optional attribute <code>proofs</code> .	142	assertion-just	dep	this is now obligation		axiom	aug	new optional attribute <code>generated-by</code> to show that an axiom is generated by expanding a <code>definition</code> .	138	axiom-inclusion	cha	now allows a <code>CMP</code> group for descriptive text, includes a set of <code>obligation</code> elements instead of an <code>assertion-just</code> . The <code>timestamp</code> attribute is deprecated, use <code>dc:date</code> with appropriate <code>action</code> instead	180	CMP	cha	the attribute <code>format</code> is now deprecated, it makes no sense, since we are more strict and consistent about <code>CMP</code> content. <code>CMP</code> now allows an optional <code>id</code> attribute.	122	code	cha	Attributes <code>width</code> and <code>height</code> now in <code>omlet</code> , got attributes <code>classid</code> and <code>codebase</code> from <code>private</code> . Attribute <code>format</code> moved to <code>data</code> children. The multilingual group of <code>CMP</code> elements for description is deprecated, use <code>metadata/dc:description</code> instead. Child element <code>data</code> may appear multiple times (with different values of the <code>format</code>).	202	constructor	aug	new optional child <code>recognizer</code> for a recognizer predicate	156	Coverage	dep	this Dublin Core element specifies the place or time which the publication's contents addresses. This does not seem appropriate for the mathematical content of OMDoc.		data	aug	new optional attributes <code>size</code> to specify the size of the data file that is referenced by the <code>href</code> attribute and <code>format</code> for the format the data is in.	203
element	state	comments	cf.																																																										
attribute	new	presentation of attributes for XML elements	191																																																										
alternative	cha	new form of the <code>alternative-def</code> element, it can now also used as an alternative to <code>axiom</code> . Compared to <code>alternative-def</code> it has a new optional attribute <code>generated-by</code> to show that an assertion is generated by expanding a some other element like <code>adt</code> .	145																																																										
alternative-def	dep	new form is <code>alternative</code> , since there can be alternative <code>axioms</code> too.																																																											
argument	cha	attribute <code>sort</code> is now of type IDREF, since it must be local in the definition.	156																																																										
assertion	aug	more values for the <code>type</code> attribute, new optional attribute <code>generated-by</code> to show that an assertion is generated by expanding a <code>definition</code> or an <code>adt</code> . New optional attribute <code>proofs</code> .	142																																																										
assertion-just	dep	this is now obligation																																																											
axiom	aug	new optional attribute <code>generated-by</code> to show that an axiom is generated by expanding a <code>definition</code> .	138																																																										
axiom-inclusion	cha	now allows a <code>CMP</code> group for descriptive text, includes a set of <code>obligation</code> elements instead of an <code>assertion-just</code> . The <code>timestamp</code> attribute is deprecated, use <code>dc:date</code> with appropriate <code>action</code> instead	180																																																										
CMP	cha	the attribute <code>format</code> is now deprecated, it makes no sense, since we are more strict and consistent about <code>CMP</code> content. <code>CMP</code> now allows an optional <code>id</code> attribute.	122																																																										
code	cha	Attributes <code>width</code> and <code>height</code> now in <code>omlet</code> , got attributes <code>classid</code> and <code>codebase</code> from <code>private</code> . Attribute <code>format</code> moved to <code>data</code> children. The multilingual group of <code>CMP</code> elements for description is deprecated, use <code>metadata/dc:description</code> instead. Child element <code>data</code> may appear multiple times (with different values of the <code>format</code>).	202																																																										
constructor	aug	new optional child <code>recognizer</code> for a recognizer predicate	156																																																										
Coverage	dep	this Dublin Core element specifies the place or time which the publication's contents addresses. This does not seem appropriate for the mathematical content of OMDoc.																																																											
data	aug	new optional attributes <code>size</code> to specify the size of the data file that is referenced by the <code>href</code> attribute and <code>format</code> for the format the data is in.	203																																																										

Identifier	Page	Conf.	LaTeX source	Rendered	Image			
kohlhase-omdoc_TAB_075	329	0.498	\begin{tabular}[t]{l l l l l}\hline dc:date & aug & new optional who attribute that can be used to specify who did the action on this date. & 99 \\ \hline Translator & dep & this element is not part of Dublin Core, it got into OMDoc by mistake, we use dc:contributor with role=trl for this. & 98 \\ \hline decomposition & aug & has a new required id attribute. It is no longer a child of theory-inclusion, but specifies which theory-inclusion it justifies by the new required attribute for. & 184 \\ \hline definition & aug & new optional children measure and ordering to specify termination of recursive definitions. New optional attribute generated-by to show that it is generated by expanding a definition. & 139 \\ \hline element & new & presentation of XML elements & 190 \\ \hline FMP & aug & now allows multiple conclusion elements, to represent general Gentzen-type sequents (not only natural deduction.) FMP now allows an optional id attribute. & 123 \\ \hline hypothesis & cha & new required attribute discharged-in to specify the derive element that discharges this hypothesis. & 162 \\ \hline measure & new & specifies a measure function (as an OMOBJ) & 141 \\ \hline metadata & aug & new optional attribute inherits that allows to inherit metadata from other declarations & 92 \\ \hline method & cha & first child that used to be an om:OMSTR or ref element is now moved into a required xref attribute that holds an URI that points to the element that defines the method. The om:OMOBJ content of the other children (they were parameter elements) is now directly included in the method element. & 164 \\ \hline obligation & new & takes over the role of assertion-just. & \\ \hline omgroup & aug & also allows the elements that can only appear in theory elements, so that omgroups can also be used for grouping inside theory elements. The type attribute is now restrained to one of narrative, sequence, alternative, contrast. & 93 \\ \hline omlet & aug & obtained attributes width and height from private. New optional attributes action for the action to be taken when activated, and data a URIfref to data in a private element. New optional attribute type for the type of the applet. & 205 \\ \hline omstyle & new & for specifying the style of OMDoc elements & 188 \\ \hline omtext & cha & the from is deprecated, we only leave the for attribute, to specify the referential character of the type. & 124 \\ \hline ordering & new & specifies a well-founded ordering (as an OMOBJ) & 141 \\ \hline \end{tabular}		dc:date	aug	new optional who attribute that can be used to specify who did the action on this date.	99
					Translator	dep	this element is not part of Dublin Core, it got into OMDoc by mistake, we use dc:contributor with role=trl for this.	98
					decomposition	aug	has a new required id attribute. It is no longer a child of theory-inclusion, but specifies which theory-inclusion it justifies by the new required attribute for.	184
					definition	aug	new optional children measure and ordering to specify termination of recursive definitions. New optional attribute generated-by to show that it is generated by expanding a definition.	139
					element	new	presentation of XML elements	190
					FMP	aug	now allows multiple conclusion elements, to represent general Gentzen-type sequents (not only natural deduction.) FMP now allows an optional id attribute.	123
					hypothesis	cha	new required attribute discharged-in to specify the derive element that discharges this hypothesis.	162
					measure	new	specifies a measure function (as an OMOBJ)	141
					metadata	aug	new optional attribute inherits that allows to inherit metadata from other declarations	92
					method	cha	first child that used to be an om:OMSTR or ref element is now moved into a required xref attribute that holds an URI that points to the element that defines the method. The om:OMOBJ content of the other children (they were parameter elements) is now directly included in the method element.	164
					obligation	new	takes over the role of assertion-just.	
					omgroup	aug	also allows the elements that can only appear in theory elements, so that omgroups can also be used for grouping inside theory elements. The type attribute is now restrained to one of narrative, sequence, alternative, contrast.	93
					omlet	aug	obtained attributes width and height from private. New optional attributes action for the action to be taken when activated, and data a URIfref to data in a private element. New optional attribute type for the type of the applet.	205
					omstyle	new	for specifying the style of OMDoc elements	188
					omtext	cha	the from is deprecated, we only leave the for attribute, to specify the referential character of the type.	124
					ordering	new	specifies a well-founded ordering (as an OMOBJ)	141

Identifier	Page	Conf.	LaTeX source	Rendered	Image
kohlhase-omdoc_TAB_076	330	0.999	\begin{tabular}{t}{ l l l l } \hline parameter & dep & the om:OMOBJ element child is now directly a child of method & \\ \hline pattern & cha & the child can be an arbitraryOpenMath element. & \\ \hline premise & cha & new optional attribute rank for the importance in the inference rule. The old href attribute is renamed to xref to be consistent with other cross-referencing. & \ \ \hline presentation & aug & \begin{tabular}{t}{l} New attribute xref that allows to inherit the information from another presentation element. New attribute theory to specify the theory the symbol is from; without this, referencing in OMDoc is not unique. \ \ The parent attribute has been renamed to role and now takes the values applied, binding, and key, since we want to be less OpenMath-centric \end{tabular} & 192 \\ \hline private & cha & \begin{tabular}{t}{l} new optional attribute for to point to an OMDoc element it provides data for. As a consequence, private elements are no longer allowed in other OMDoc elements, only on top-level. New attribute replaces as a pointer to the OMDoc elements that are replaced by the system-specific information in this element. Old attributes width and height now in omlet. Attribute format moved to data children. \ \ The descriptive CMP elements are deprecated. \end{tabular} & q 202 \\ \hline proof & cha & attribute theory is now optional, since the element can appear inside a theory element. & 161 \\ \hline proofobject & cha & attribute theory is now optional, since the element can appear inside a theory element. & 161 \\ \hline recognizer & new & specifies the recognizer predicate of a sort. & 157 \\ \hline recurse & new & recursive calls to presentation in style. & 191 \\ \hline ref & cha & attribute kind renamed to type. & 94 \\ \hline selector & cha & the old type attribute (had values total and partial) is deprecated, its duty is now carried by an attribute total (values yes and no). & 157 \\ \hline signature & dep & for the moment & \\ \hline sortdef & cha & has a mandatory name attribute, otherwise the defined symbol has no name. & 156 \\ \hline \end{tabular}		

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																								
kohlhase-omdoc_TAB_077	331	■ 0.999	<pre>\begin{tabular}[t]{l l l l l } \hline style & new & allows to specify style information in presentation and omstyle elements using a simplified OMDoc-internalized version of XSLT. & 189 \\ \hline symbol & aug & new optional attribute generated-by to show that it is generated by expanding a definition. & 136 \\ \hline text & new & presentation of text in omstyle. & 190 \\ \hline theory-inclusion & cha & now allows CMP group for descriptive text, no longer has a decomposition child, this is now attached by its for attribute. The timestamp attribute is deprecated, use dc:date with appropriate action instead. & 178 \\ \hline type & aug & can now also appear on top-level. Has an optional id attribute for identification, and an optional for attribute to point to a symbol element it declares type information for. & 139 \\ \hline use & aug & New attribute element allows to specify that the content should be encased in an XML element with the attribute-value pairs specified in the string specified in the attribute attributes. & 194 \\ \hline value-of & new & presentation of values in style. & 190 \\ \hline with & new & used to supply fragments of text in CMPs with style and id attributes that can be used for presentation and referencing. & 126 \\ \hline xslt & new & allows to embed XSLT into presentation and omstyle elements. & 189 \\ \hline \end{tabular}</pre>	<table><tr><td>style</td><td>new</td><td>allows to specify style information in presentation and omstyle elements using a simplified OMDoc-internalized version of XSLT.</td><td>189</td></tr><tr><td>symbol</td><td>aug</td><td>new optional attribute generated-by to show that it is generated by expanding a definition.</td><td>136</td></tr><tr><td>text</td><td>new</td><td>presentation of text in omstyle.</td><td>190</td></tr><tr><td>theory-inclusion</td><td>cha</td><td>now allows CMP group for descriptive text, no longer has a decomposition child, this is now attached by its for attribute. The timestamp attribute is deprecated, use dc:date with appropriate action instead.</td><td>178</td></tr><tr><td>type</td><td>aug</td><td>can now also appear on top-level. Has an optional id attribute for identification, and an optional for attribute to point to a symbol element it declares type information for.</td><td>139</td></tr><tr><td>use</td><td>aug</td><td>New attribute element allows to specify that the content should be encased in an XML element with the attribute-value pairs specified in the string specified in the attribute attributes.</td><td>194</td></tr><tr><td>value-of</td><td>new</td><td>presentation of values in style.</td><td>190</td></tr><tr><td>with</td><td>new</td><td>used to supply fragments of text in CMPs with style and id attributes that can be used for presentation and referencing.</td><td>126</td></tr><tr><td>xslt</td><td>new</td><td>allows to embed XSLT into presentation and omstyle elements.</td><td>189</td></tr></table>	style	new	allows to specify style information in presentation and omstyle elements using a simplified OMDoc-internalized version of XSLT.	189	symbol	aug	new optional attribute generated-by to show that it is generated by expanding a definition.	136	text	new	presentation of text in omstyle.	190	theory-inclusion	cha	now allows CMP group for descriptive text, no longer has a decomposition child, this is now attached by its for attribute. The timestamp attribute is deprecated, use dc:date with appropriate action instead.	178	type	aug	can now also appear on top-level. Has an optional id attribute for identification, and an optional for attribute to point to a symbol element it declares type information for.	139	use	aug	New attribute element allows to specify that the content should be encased in an XML element with the attribute-value pairs specified in the string specified in the attribute attributes .	194	value-of	new	presentation of values in style.	190	with	new	used to supply fragments of text in CMPs with style and id attributes that can be used for presentation and referencing.	126	xslt	new	allows to embed XSLT into presentation and omstyle elements.	189	<table><tr><td>style</td><td>new</td><td>allows to specify style information in presentation and omstyle elements using a simplified OMDoc-internalized version of XSLT.</td><td>189</td></tr><tr><td>symbol</td><td>aug</td><td>new optional attribute generated-by to show that it is generated by expanding a definition.</td><td>136</td></tr><tr><td>text</td><td>new</td><td>presentation of text in omstyle.</td><td>190</td></tr><tr><td>theory-inclusion</td><td>cha</td><td>now allows CMP group for descriptive text, no longer has a decomposition child, this is now attached by its for attribute. The timestamp attribute is deprecated, use dc:date with appropriate action instead.</td><td>178</td></tr><tr><td>type</td><td>aug</td><td>can now also appear on top-level. Has an optional id attribute for identification, and an optional for attribute to point to a symbol element it declares type information for.</td><td>139</td></tr><tr><td>use</td><td>aug</td><td>New attribute element allows to specify that the content should be encased in an XML element with the attribute-value pairs specified in the string specified in the attribute attributes.</td><td>194</td></tr><tr><td>value-of</td><td>new</td><td>presentation of values in style.</td><td>190</td></tr><tr><td>with</td><td>new</td><td>used to supply fragments of text in CMPs with style and id attributes that can be used for presentation and referencing.</td><td>126</td></tr><tr><td>xslt</td><td>new</td><td>allows to embed XSLT into presentation and omstyle elements.</td><td>189</td></tr></table>	style	new	allows to specify style information in presentation and omstyle elements using a simplified OMDoc-internalized version of XSLT.	189	symbol	aug	new optional attribute generated-by to show that it is generated by expanding a definition.	136	text	new	presentation of text in omstyle.	190	theory-inclusion	cha	now allows CMP group for descriptive text, no longer has a decomposition child, this is now attached by its for attribute. The timestamp attribute is deprecated, use dc:date with appropriate action instead.	178	type	aug	can now also appear on top-level. Has an optional id attribute for identification, and an optional for attribute to point to a symbol element it declares type information for.	139	use	aug	New attribute element allows to specify that the content should be encased in an XML element with the attribute-value pairs specified in the string specified in the attribute attributes .	194	value-of	new	presentation of values in style.	190	with	new	used to supply fragments of text in CMPs with style and id attributes that can be used for presentation and referencing.	126	xslt	new	allows to embed XSLT into presentation and omstyle elements.	189
style	new	allows to specify style information in presentation and omstyle elements using a simplified OMDoc-internalized version of XSLT.	189																																																																										
symbol	aug	new optional attribute generated-by to show that it is generated by expanding a definition.	136																																																																										
text	new	presentation of text in omstyle.	190																																																																										
theory-inclusion	cha	now allows CMP group for descriptive text, no longer has a decomposition child, this is now attached by its for attribute. The timestamp attribute is deprecated, use dc:date with appropriate action instead.	178																																																																										
type	aug	can now also appear on top-level. Has an optional id attribute for identification, and an optional for attribute to point to a symbol element it declares type information for.	139																																																																										
use	aug	New attribute element allows to specify that the content should be encased in an XML element with the attribute-value pairs specified in the string specified in the attribute attributes .	194																																																																										
value-of	new	presentation of values in style.	190																																																																										
with	new	used to supply fragments of text in CMPs with style and id attributes that can be used for presentation and referencing.	126																																																																										
xslt	new	allows to embed XSLT into presentation and omstyle elements.	189																																																																										
style	new	allows to specify style information in presentation and omstyle elements using a simplified OMDoc-internalized version of XSLT.	189																																																																										
symbol	aug	new optional attribute generated-by to show that it is generated by expanding a definition.	136																																																																										
text	new	presentation of text in omstyle.	190																																																																										
theory-inclusion	cha	now allows CMP group for descriptive text, no longer has a decomposition child, this is now attached by its for attribute. The timestamp attribute is deprecated, use dc:date with appropriate action instead.	178																																																																										
type	aug	can now also appear on top-level. Has an optional id attribute for identification, and an optional for attribute to point to a symbol element it declares type information for.	139																																																																										
use	aug	New attribute element allows to specify that the content should be encased in an XML element with the attribute-value pairs specified in the string specified in the attribute attributes .	194																																																																										
value-of	new	presentation of values in style.	190																																																																										
with	new	used to supply fragments of text in CMPs with style and id attributes that can be used for presentation and referencing.	126																																																																										
xslt	new	allows to embed XSLT into presentation and omstyle elements.	189																																																																										
kohlhase-omdoc_TAB_078	332	■ 1.000	<pre>\begin{tabular}[t]{l l l l l l l } \hline Element & p. & Mod. & Required & Optional & D & Content \\ \hline & & & Attribs & Attribs & C & \\ \hline \end{tabular}</pre>	<table><tr><td>Element</td><td>p.</td><td>Mod.</td><td>Required</td><td>Optional</td><td>D</td><td>Content</td></tr><tr><td></td><td></td><td></td><td>Attribs</td><td>Attribs</td><td>C</td><td></td></tr></table>	Element	p.	Mod.	Required	Optional	D	Content				Attribs	Attribs	C		<table><tr><td>Element</td><td>p.</td><td>Mod.</td><td>Required</td><td>Optional</td><td>D</td><td>Content</td></tr><tr><td></td><td></td><td></td><td>Attribs</td><td>Attribs</td><td>C</td><td></td></tr></table>	Element	p.	Mod.	Required	Optional	D	Content				Attribs	Attribs	C																																													
Element	p.	Mod.	Required	Optional	D	Content																																																																							
			Attribs	Attribs	C																																																																								
Element	p.	Mod.	Required	Optional	D	Content																																																																							
			Attribs	Attribs	C																																																																								

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																						
kohlhase-omdoc_TAB_079	332	0.619	<pre>\begin{tabular}[t]{ l l l l l l l } \hline adt & 156 & ADT & & xml:id, type, style, class, theory, generated-from, generated-via & + & sortdef+ \\ \hline alternative & 145 & ST & for, entailed-by, entails, entailed-by-thm, entails-thm & xml:id, type, theory, generated-from, generated-via, uniqueness, exhaustivity, consistency, existence, style, class & + & CMP*, (FMP requation* (OMOBJ m:math legacy)*) \\ \hline answer & 210 & QUIZ & verdict & xml:id, style, class & + & CMP*, FMP* \\ \hline m:apply & 115 & MML & & id, xlink:href & - & bvar?,⟨CMe⟩* \\ \hline argument & 156 & ADT & sort & & + & selector? \\ \hline assertion & 142 & ST & & xml:id, type, theory, generated-from, generated-via, style, class & + & CMP*, FMP* \\ \hline assumption & 124 & MTXT & & xml:id, inductive, style, class & + & CMP*, (OMOBJ m:math legacy)? \\ \hline attribute & 191 & PRES & name & & - & (value-of text)* \\ \hline axiom & 138 & ST & name & xml:id, type, generated-from, generated-via, style, class & + & CMP*, FMP* \\ \hline axiom-inclusion & 180 & CTH & from, to & xml:id, style, class, theory, generated-from, generated-via & + & morphism?, (path-just obligation*) \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><td>adt</td><td>156</td><td>ADT</td><td></td><td>xml:id, type, style, class, theory, generated-from, generated-via</td><td>+</td><td>sortdef+</td></tr><tr><td>alternative</td><td>145</td><td>ST</td><td>for, entailed-by, entails, entailed-by-thm, entails-thm</td><td>xml:id, type, theory, generated-from, generated-via, uniqueness, exhaustivity, consistency, existence, style, class</td><td>+</td><td>CMP*, (FMP requation* (OMOBJ m:math legacy)*)</td></tr><tr><td>answer</td><td>210</td><td>QUIZ</td><td>verdict</td><td>xml:id, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>m:apply</td><td>115</td><td>MML</td><td></td><td>id, xlink:href</td><td>−</td><td>bvar?,⟨CMe⟩*</td></tr><tr><td>argument</td><td>156</td><td>ADT</td><td>sort</td><td></td><td>+</td><td>selector?</td></tr><tr><td>assertion</td><td>142</td><td>ST</td><td></td><td>xml:id, type, theory, generated-from, generated-via, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>assumption</td><td>124</td><td>MTXT</td><td></td><td>xml:id, inductive, style, class</td><td>+</td><td>CMP*, (OMOBJ m:math legacy)?</td></tr><tr><td>attribute</td><td>191</td><td>PRES</td><td>name</td><td></td><td>−</td><td>(value-of text)*</td></tr><tr><td>axiom</td><td>138</td><td>ST</td><td>name</td><td>xml:id, type, generated-from, generated-via, style, class</td><td>+</td><td>CMP*, FMP*</td></tr><tr><td>axiom-inclusion</td><td>180</td><td>CTH</td><td>from, to</td><td>xml:id, style, class, theory, generated-from, generated-via</td><td>+</td><td>morphism?, (path-just obligation*)</td></tr></table>	adt	156	ADT		xml:id, type, style, class, theory, generated-from, generated-via	+	sortdef+	alternative	145	ST	for, entailed-by, entails, entailed-by-thm, entails-thm	xml:id, type, theory, generated-from, generated-via, uniqueness, exhaustivity, consistency, existence, style, class	+	CMP*, (FMP requation* (OMOBJ m:math legacy)*)	answer	210	QUIZ	verdict	xml:id, style, class	+	CMP*, FMP*	m:apply	115	MML		id, xlink:href	−	bvar?,⟨CMe⟩*	argument	156	ADT	sort		+	selector?	assertion	142	ST		xml:id, type, theory, generated-from, generated-via, style, class	+	CMP*, FMP*	assumption	124	MTXT		xml:id, inductive, style, class	+	CMP*, (OMOBJ m:math legacy)?	attribute	191	PRES	name		−	(value-of text)*	axiom	138	ST	name	xml:id, type, generated-from, generated-via, style, class	+	CMP*, FMP*	axiom-inclusion	180	CTH	from, to	xml:id, style, class, theory, generated-from, generated-via	+	morphism?, (path-just obligation*)
adt	156	ADT		xml:id, type, style, class, theory, generated-from, generated-via	+	sortdef+																																																																					
alternative	145	ST	for, entailed-by, entails, entailed-by-thm, entails-thm	xml:id, type, theory, generated-from, generated-via, uniqueness, exhaustivity, consistency, existence, style, class	+	CMP*, (FMP requation* (OMOBJ m:math legacy)*)																																																																					
answer	210	QUIZ	verdict	xml:id, style, class	+	CMP*, FMP*																																																																					
m:apply	115	MML		id, xlink:href	−	bvar?,⟨CMe⟩*																																																																					
argument	156	ADT	sort		+	selector?																																																																					
assertion	142	ST		xml:id, type, theory, generated-from, generated-via, style, class	+	CMP*, FMP*																																																																					
assumption	124	MTXT		xml:id, inductive, style, class	+	CMP*, (OMOBJ m:math legacy)?																																																																					
attribute	191	PRES	name		−	(value-of text)*																																																																					
axiom	138	ST	name	xml:id, type, generated-from, generated-via, style, class	+	CMP*, FMP*																																																																					
axiom-inclusion	180	CTH	from, to	xml:id, style, class, theory, generated-from, generated-via	+	morphism?, (path-just obligation*)																																																																					
kohlhase-omdoc_TAB_080	332	0.672	<pre>\begin{tabular}[t]{ l l l l l l } \hline m:bvar & 115 & MML & id, xlink:href & - & ci* \\ \hline m:ci & 115 & MML & id, xlink:href & - & PCDATA \\ \hline m:cn & 115 & MML & id, xlink:href & - & ([0-9] , .)([* e([0-9] , .)*])? \\ \hline choice & 210 & QUIZ & xml:id, style, class & + & CMP*, FMP* \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><td>m:bvar</td><td>115</td><td>MML</td><td></td><td>id, xlink:href</td><td>−</td><td>ci*</td></tr><tr><td>m:ci</td><td>115</td><td>MML</td><td></td><td>id, xlink:href</td><td>−</td><td>PCDATA</td></tr><tr><td>m:cn</td><td>115</td><td>MML</td><td></td><td>id, xlink:href</td><td>−</td><td>([0-9] , .)([* e([0-9] , .)*])?</td></tr><tr><td>choice</td><td>210</td><td>QUIZ</td><td></td><td>xml:id, style, class</td><td>+</td><td>CMP*, FMP*</td></tr></table>	m:bvar	115	MML		id, xlink:href	−	ci*	m:ci	115	MML		id, xlink:href	−	PCDATA	m:cn	115	MML		id, xlink:href	−	([0-9] , .)([* e([0-9] , .)*])?	choice	210	QUIZ		xml:id, style, class	+	CMP*, FMP*																																										
m:bvar	115	MML		id, xlink:href	−	ci*																																																																					
m:ci	115	MML		id, xlink:href	−	PCDATA																																																																					
m:cn	115	MML		id, xlink:href	−	([0-9] , .)([* e([0-9] , .)*])?																																																																					
choice	210	QUIZ		xml:id, style, class	+	CMP*, FMP*																																																																					

Identifier	Page	Conf.	LaTeX source	Rendered	Image
kohlhase-omdoc_TAB_081	333	0.981	<pre>\begin{tabular}[t]{l l</pre>		

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																												
kohlhase-omdoc_TAB_082	333	0.793	<pre>\begin{tabular}[t]{ l l l l l l l }\hline m:csymbol & 115 & MML & definitionURL & id,xlink:href & - & EMPTY \\ data & 203 & EXT & & format,href, size,original & - & <![CDATA[...]]> \\ dc:date & 99 & DC & & action,who & - & ISO 8601 norm \\ dd & 130 & RT & & xml:id,style, class,index, verbalizes & + & CMPcontent \\ di & 130 & RT & & xml:id,style, class,index, verbalizes & + & dt+,dd* \\ dl & 130 & RT & & xml:id,style, class,index, verbalizes & + & li* \\ dt & 130 & RT & & xml:id,style, class,index, verbalizes & + & CMPcontent \\ decomposition & 184 & DG & links & theory, generated-from, generated-via & - & EMPTY \\ definition & 139 & ST & xml:id, for & uniqueness, existence, consistency, exhaustivity, type, generated-from, generated-via, style, class & + & CMP*, (FMP reequation+ OMOBJ m:math legacy)?, measure?, ordering? \\ dc:description & 99 & DC & & xml:lang & - & CMPcontent \\ derive & 162 & PF & & xml:id, style, class & - & CMP*, FMP?, method? \end{tabular}</pre>	<table><tr><td>m:csymbol</td><td>115</td><td>MML</td><td>definitionURL</td><td>id, xlink:href</td><td>-</td><td>EMPTY</td></tr><tr><td>data</td><td>203</td><td>EXT</td><td></td><td>format, href, size, original</td><td>-</td><td><![CDATA[...]]></td></tr><tr><td>dc:date</td><td>99</td><td>DC</td><td></td><td>action, who</td><td>-</td><td>ISO 8601 norm</td></tr><tr><td>dd</td><td>130</td><td>RT</td><td></td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>CMPcontent</td></tr><tr><td>di</td><td>130</td><td>RT</td><td></td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>dt+,dd*</td></tr><tr><td>dl</td><td>130</td><td>RT</td><td></td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>li*</td></tr><tr><td>dt</td><td>130</td><td>RT</td><td></td><td>xml:id, style, class, index, verbalizes</td><td>+</td><td>CMPcontent</td></tr><tr><td>decomposition</td><td>184</td><td>DG</td><td>links</td><td>theory, generated-from, generated-via</td><td>-</td><td>EMPTY</td></tr><tr><td>definition</td><td>139</td><td>ST</td><td>xml:id, for</td><td>uniqueness, existence, consistency, exhaustivity, type, generated-from, generated-via, style, class</td><td>+</td><td>CMP*, (FMP reequation+ OMOBJ m:math legacy)?, measure?, ordering?</td></tr><tr><td>dc:description</td><td>99</td><td>DC</td><td></td><td>xml:lang</td><td>-</td><td>CMPcontent</td></tr><tr><td>derive</td><td>162</td><td>PF</td><td></td><td>xml:id, style, class</td><td>-</td><td>CMP*, FMP?, method?</td></tr></table>	m:csymbol	115	MML	definitionURL	id, xlink:href	-	EMPTY	data	203	EXT		format, href, size, original	-	<![CDATA[...]]>	dc:date	99	DC		action, who	-	ISO 8601 norm	dd	130	RT		xml:id, style, class, index, verbalizes	+	CMPcontent	di	130	RT		xml:id, style, class, index, verbalizes	+	dt+,dd*	dl	130	RT		xml:id, style, class, index, verbalizes	+	li*	dt	130	RT		xml:id, style, class, index, verbalizes	+	CMPcontent	decomposition	184	DG	links	theory, generated-from, generated-via	-	EMPTY	definition	139	ST	xml:id, for	uniqueness, existence, consistency, exhaustivity, type, generated-from, generated-via, style, class	+	CMP*, (FMP reequation+ OMOBJ m:math legacy)?, measure?, ordering?	dc:description	99	DC		xml:lang	-	CMPcontent	derive	162	PF		xml:id, style, class	-	CMP*, FMP?, method?
m:csymbol	115	MML	definitionURL	id, xlink:href	-	EMPTY																																																																											
data	203	EXT		format, href, size, original	-	<![CDATA[...]]>																																																																											
dc:date	99	DC		action, who	-	ISO 8601 norm																																																																											
dd	130	RT		xml:id, style, class, index, verbalizes	+	CMPcontent																																																																											
di	130	RT		xml:id, style, class, index, verbalizes	+	dt+,dd*																																																																											
dl	130	RT		xml:id, style, class, index, verbalizes	+	li*																																																																											
dt	130	RT		xml:id, style, class, index, verbalizes	+	CMPcontent																																																																											
decomposition	184	DG	links	theory, generated-from, generated-via	-	EMPTY																																																																											
definition	139	ST	xml:id, for	uniqueness, existence, consistency, exhaustivity, type, generated-from, generated-via, style, class	+	CMP*, (FMP reequation+ OMOBJ m:math legacy)?, measure?, ordering?																																																																											
dc:description	99	DC		xml:lang	-	CMPcontent																																																																											
derive	162	PF		xml:id, style, class	-	CMP*, FMP?, method?																																																																											
kohlhase-omdoc_TAB_083	333	0.597	<pre>\begin{tabular}[t]{ l l l l l l l }\hline effect & 204 & EXT & & xml:id,style, class & - & CMP*,FMP* \\ element & 190 & PRES & name & xml:id,cr,ns & - & (attribute element text recurse)* \\ example & 146 & ST & for & xml:id,type, assertion, proof,style, class,theory, generated-from, generated-via & + & CMP* (OMOBJ m:math legacy)? \end{tabular}</pre>	<table><tr><td>effect</td><td>204</td><td>EXT</td><td></td><td>xml:id,style, class</td><td>-</td><td>CMP*,FMP*</td></tr><tr><td>element</td><td>190</td><td>PRES</td><td>name</td><td>xml:id,cr,ns</td><td>-</td><td>(attribute element text recurse)*</td></tr><tr><td>example</td><td>146</td><td>ST</td><td>for</td><td>xml:id,type, assertion, proof,style, class,theory, generated-from, generated-via</td><td>+</td><td>CMP* (OMOBJ m:math legacy)?</td></tr></table>	effect	204	EXT		xml:id,style, class	-	CMP*,FMP*	element	190	PRES	name	xml:id,cr,ns	-	(attribute element text recurse)*	example	146	ST	for	xml:id,type, assertion, proof,style, class,theory, generated-from, generated-via	+	CMP* (OMOBJ m:math legacy)?	<table><tr><td>effect</td><td>204</td><td>EXT</td><td></td><td>xml:id, style, class</td><td>-</td><td>CMP*,FMP*</td></tr><tr><td>element</td><td>190</td><td>PRES</td><td>name</td><td>xml:id, cr, ns</td><td>-</td><td>(attribute element text recurse)*</td></tr><tr><td>example</td><td>146</td><td>ST</td><td>for</td><td>xml:id, type, assertion, proof, style, class, theory, generated-from, generated-via</td><td>+</td><td>CMP* (OMOBJ m:math legacy)?</td></tr></table>	effect	204	EXT		xml:id, style, class	-	CMP*,FMP*	element	190	PRES	name	xml:id, cr, ns	-	(attribute element text recurse)*	example	146	ST	for	xml:id, type, assertion, proof, style, class, theory, generated-from, generated-via	+	CMP* (OMOBJ m:math legacy)?																																		
effect	204	EXT		xml:id,style, class	-	CMP*,FMP*																																																																											
element	190	PRES	name	xml:id,cr,ns	-	(attribute element text recurse)*																																																																											
example	146	ST	for	xml:id,type, assertion, proof,style, class,theory, generated-from, generated-via	+	CMP* (OMOBJ m:math legacy)?																																																																											
effect	204	EXT		xml:id, style, class	-	CMP*,FMP*																																																																											
element	190	PRES	name	xml:id, cr, ns	-	(attribute element text recurse)*																																																																											
example	146	ST	for	xml:id, type, assertion, proof, style, class, theory, generated-from, generated-via	+	CMP* (OMOBJ m:math legacy)?																																																																											

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																								
kohlhase-omdoc_TAB_088	334	0.980	<pre>\begin{tabular}[t]{ l l l l l l l }\hline cc:license & 102 & CC & & jurisdiction & - & permissions, prohibitions, requirements \\ \hline link & 130 & RT & & xml:id, style, class, index, verbalizes & - & Math Vernacular \\ \hline m:math & 114 & MML & & id, xlink:href & - & 《CMeI》+ \\ \hline mc & 210 & QUIZ & & xml:id, style, class, theory, generated-from, generated-via & - & choice, hint?, answer \\ \hline measure & 141 & ST & & xml:id & - & OMOBJ m:math legacy \\ \hline metadata & 92 & DC & & inherits & - & (dc-element)* \\ \hline method & 164 & PF & xref & & - & (OMOBJ m:math legacy premise proof proofobject)* \\ \hline morphism & 175 & CTH & & xml:id, base, consistency, exhaustivity, type, hiding, style, class & - & requation*, measure?, ordering? \\ \hline\end{tabular}</pre>	(not rendered)	<table><tr><td>cc:license</td><td>102</td><td>CC</td><td></td><td>jurisdiction</td><td>–</td><td>permissions, prohibitions, requirements</td></tr><tr><td>link</td><td>130</td><td>RT</td><td></td><td>xml:id, style, class, index, verbalizes</td><td>–</td><td>Math Vernacular</td></tr><tr><td>m:math</td><td>114</td><td>MML</td><td></td><td>id, xlink:href</td><td>–</td><td>《CMeI》+</td></tr><tr><td>mc</td><td>210</td><td>QUIZ</td><td></td><td>xml:id, style, class, theory, generated-from, generated-via</td><td>–</td><td>choice, hint?, answer</td></tr><tr><td>measure</td><td>141</td><td>ST</td><td></td><td>xml:id</td><td>–</td><td>OMOBJ m:math legacy</td></tr><tr><td>metadata</td><td>92</td><td>DC</td><td></td><td>inherits</td><td>–</td><td>(dc-element)*</td></tr><tr><td>method</td><td>164</td><td>PF</td><td>xref</td><td></td><td>–</td><td>(OMOBJ m:math legacy premise proof proofobject)*</td></tr><tr><td>morphism</td><td>175</td><td>CTH</td><td></td><td>xml:id, base, consistency, exhaustivity, type, hiding, style, class</td><td>–</td><td>requation*, measure?, ordering?</td></tr></table>	cc:license	102	CC		jurisdiction	–	permissions, prohibitions, requirements	link	130	RT		xml:id, style, class, index, verbalizes	–	Math Vernacular	m:math	114	MML		id, xlink:href	–	《CMeI》+	mc	210	QUIZ		xml:id, style, class, theory, generated-from, generated-via	–	choice, hint?, answer	measure	141	ST		xml:id	–	OMOBJ m:math legacy	metadata	92	DC		inherits	–	(dc-element)*	method	164	PF	xref		–	(OMOBJ m:math legacy premise proof proofobject)*	morphism	175	CTH		xml:id, base, consistency, exhaustivity, type, hiding, style, class	–	requation*, measure?, ordering?
cc:license	102	CC		jurisdiction	–	permissions, prohibitions, requirements																																																							
link	130	RT		xml:id, style, class, index, verbalizes	–	Math Vernacular																																																							
m:math	114	MML		id, xlink:href	–	《CMeI》+																																																							
mc	210	QUIZ		xml:id, style, class, theory, generated-from, generated-via	–	choice, hint?, answer																																																							
measure	141	ST		xml:id	–	OMOBJ m:math legacy																																																							
metadata	92	DC		inherits	–	(dc-element)*																																																							
method	164	PF	xref		–	(OMOBJ m:math legacy premise proof proofobject)*																																																							
morphism	175	CTH		xml:id, base, consistency, exhaustivity, type, hiding, style, class	–	requation*, measure?, ordering?																																																							
kohlhase-omdoc_TAB_089	334	0.963	<pre>\begin{tabular}[t]{ l l l l l l l }\hline note & 131 & RT & & type,xml:id, style, class, index, verbalizes & - & Math Vernacular \\ \hline\end{tabular}</pre>	<table><tr><td>note</td><td>131</td><td>RT</td><td></td><td>type,xml:id, style, class, index, verbalizes</td><td>-</td><td>Math Vernacular</td></tr></table>	note	131	RT		type,xml:id, style, class, index, verbalizes	-	Math Vernacular	<table><tr><td>note</td><td>131</td><td>RT</td><td></td><td>type,xml:id, style, class, index, verbalizes</td><td>–</td><td>Math Vernacular</td></tr></table>	note	131	RT		type,xml:id, style, class, index, verbalizes	–	Math Vernacular																																										
note	131	RT		type,xml:id, style, class, index, verbalizes	-	Math Vernacular																																																							
note	131	RT		type,xml:id, style, class, index, verbalizes	–	Math Vernacular																																																							

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																		
kohlhase-omdoc_TAB_093	336	0.651	<pre>\begin{tabular}[t]{ l l l l l l l }\hline ref & 94 & DOC & & xref, type & - & ANY \\recognizer & 157 & ADT & name & type, scope, role, style, class & + & \\recurse & 191 & PRES & & select & - & EMPTY \\dc:relation & 100 & DC & & & - & ANY \\requation & 140 & ST & & xml:id, style, class & - & (OMOBJ m:math legacy),(OMOBJ m:math legacy) \\cc:requirements & 103 & CC & & notice, copyleft, attribution & - & EMPTY \\dc:rights & 100 & DC & & & - & ANY \\ \hline\end{tabular}</pre>	<table><tr><td>ref</td><td>94</td><td>DOC</td><td></td><td>xref, type</td><td>-</td><td>ANY</td></tr><tr><td>recognizer</td><td>157</td><td>ADT</td><td>name</td><td>type, scope, role, style, class</td><td>+</td><td></td></tr><tr><td>recurse</td><td>191</td><td>PRES</td><td></td><td>select</td><td>-</td><td>EMPTY</td></tr><tr><td>dc:relation</td><td>100</td><td>DC</td><td></td><td></td><td>-</td><td>ANY</td></tr><tr><td>requation</td><td>140</td><td>ST</td><td></td><td>xml:id, style, class</td><td>-</td><td>(OMOBJ m:math legacy),(OMOBJ m:math legacy)</td></tr><tr><td>cc:requirements</td><td>103</td><td>CC</td><td></td><td>notice, copyleft, attribution</td><td>-</td><td>EMPTY</td></tr><tr><td>dc:rights</td><td>100</td><td>DC</td><td></td><td></td><td>-</td><td>ANY</td></tr></table>	ref	94	DOC		xref, type	-	ANY	recognizer	157	ADT	name	type, scope, role, style, class	+		recurse	191	PRES		select	-	EMPTY	dc:relation	100	DC			-	ANY	requation	140	ST		xml:id, style, class	-	(OMOBJ m:math legacy),(OMOBJ m:math legacy)	cc:requirements	103	CC		notice, copyleft, attribution	-	EMPTY	dc:rights	100	DC			-	ANY	<table><tr><td>ref</td><td>94</td><td>DOC</td><td></td><td>xref, type</td><td>-</td><td>ANY</td></tr><tr><td>recognizer</td><td>157</td><td>ADT</td><td>name</td><td>type, scope, role, style, class</td><td>+</td><td></td></tr><tr><td>recurse</td><td>191</td><td>PRES</td><td></td><td>select</td><td>-</td><td>EMPTY</td></tr><tr><td>dc:relation</td><td>100</td><td>DC</td><td></td><td></td><td>-</td><td>ANY</td></tr><tr><td>requation</td><td>140</td><td>ST</td><td></td><td>xml:id, style, class</td><td>-</td><td>(OMOBJ m:math legacy),(OMOBJ m:math legacy)</td></tr><tr><td>cc:requirements</td><td>103</td><td>CC</td><td></td><td>notice, copyleft, attribution</td><td>-</td><td>EMPTY</td></tr><tr><td>dc:rights</td><td>100</td><td>DC</td><td></td><td></td><td>-</td><td>ANY</td></tr></table>	ref	94	DOC		xref, type	-	ANY	recognizer	157	ADT	name	type, scope, role, style, class	+		recurse	191	PRES		select	-	EMPTY	dc:relation	100	DC			-	ANY	requation	140	ST		xml:id, style, class	-	(OMOBJ m:math legacy),(OMOBJ m:math legacy)	cc:requirements	103	CC		notice, copyleft, attribution	-	EMPTY	dc:rights	100	DC			-	ANY
ref	94	DOC		xref, type	-	ANY																																																																																																	
recognizer	157	ADT	name	type, scope, role, style, class	+																																																																																																		
recurse	191	PRES		select	-	EMPTY																																																																																																	
dc:relation	100	DC			-	ANY																																																																																																	
requation	140	ST		xml:id, style, class	-	(OMOBJ m:math legacy),(OMOBJ m:math legacy)																																																																																																	
cc:requirements	103	CC		notice, copyleft, attribution	-	EMPTY																																																																																																	
dc:rights	100	DC			-	ANY																																																																																																	
ref	94	DOC		xref, type	-	ANY																																																																																																	
recognizer	157	ADT	name	type, scope, role, style, class	+																																																																																																		
recurse	191	PRES		select	-	EMPTY																																																																																																	
dc:relation	100	DC			-	ANY																																																																																																	
requation	140	ST		xml:id, style, class	-	(OMOBJ m:math legacy),(OMOBJ m:math legacy)																																																																																																	
cc:requirements	103	CC		notice, copyleft, attribution	-	EMPTY																																																																																																	
dc:rights	100	DC			-	ANY																																																																																																	
kohlhase-omdoc_TAB_094	336	0.926	<pre>\begin{tabular}[t]{ l l l l l l l }\hline selector & 157 & ADT & name & type, scope, role, total, style, class & + & \\solution & 209 & QUIZ & & xml:id, for, style, class, theory, generated-from, generated-via & + & (CMP*, FMP*) proof \\sortdef & 156 & ADT & name & role, scope, style, class & + & (constructor insort)* \\dc:source & 100 & DC & & & - & ANY \\style & 189 & PRES & format & xml:lang, requires & - & (element text recurse value-of)* \\dc:subject & 99 & DC & & xml:lang & - & CMPcontent \\symbol & 136 & ST & name & role, scope, style, class, generated-from, generated-via & + & type* \\ \hline\end{tabular}</pre>	<table><tr><td>selector</td><td>157</td><td>ADT</td><td>name</td><td>type, scope, role, total, style, class</td><td>+</td><td></td></tr><tr><td>solution</td><td>209</td><td>QUIZ</td><td></td><td>xml:id, for, style, class, theory, generated-from, generated-via</td><td>+</td><td>(CMP*, FMP*) proof</td></tr><tr><td>sortdef</td><td>156</td><td>ADT</td><td>name</td><td>role, scope, style, class</td><td>+</td><td>(constructor insort)*</td></tr><tr><td>dc:source</td><td>100</td><td>DC</td><td></td><td></td><td>-</td><td>ANY</td></tr><tr><td>style</td><td>189</td><td>PRES</td><td>format</td><td>xml:lang, requires</td><td>-</td><td>(element text recurse value-of)*</td></tr><tr><td>dc:subject</td><td>99</td><td>DC</td><td></td><td>xml:lang</td><td>-</td><td>CMPcontent</td></tr><tr><td>symbol</td><td>136</td><td>ST</td><td>name</td><td>role, scope, style, class, generated-from, generated-via</td><td>+</td><td>type*</td></tr></table>	selector	157	ADT	name	type, scope, role, total, style, class	+		solution	209	QUIZ		xml:id, for, style, class, theory, generated-from, generated-via	+	(CMP*, FMP*) proof	sortdef	156	ADT	name	role, scope, style, class	+	(constructor insort)*	dc:source	100	DC			-	ANY	style	189	PRES	format	xml:lang, requires	-	(element text recurse value-of)*	dc:subject	99	DC		xml:lang	-	CMPcontent	symbol	136	ST	name	role, scope, style, class, generated-from, generated-via	+	type*	<table><tr><td>selector</td><td>157</td><td>ADT</td><td>name</td><td>type, scope, role, total, style, class</td><td>+</td><td></td></tr><tr><td>solution</td><td>209</td><td>QUIZ</td><td></td><td>xml:id, for, style, class, theory, generated-from, generated-via</td><td>+</td><td>(CMP*, FMP*) proof</td></tr><tr><td>sortdef</td><td>156</td><td>ADT</td><td>name</td><td>role, scope, style, class</td><td>+</td><td>(constructor insort)*</td></tr><tr><td>dc:source</td><td>100</td><td>DC</td><td></td><td></td><td>-</td><td>ANY</td></tr><tr><td>style</td><td>189</td><td>PRES</td><td>format</td><td>xml:lang, requires</td><td>-</td><td>(element text recurse value-of)*</td></tr><tr><td>dc:subject</td><td>99</td><td>DC</td><td></td><td>xml:lang</td><td>-</td><td>CMPcontent</td></tr><tr><td>symbol</td><td>136</td><td>ST</td><td>name</td><td>role, scope, style, class, generated-from, generated-via</td><td>+</td><td>type*</td></tr></table>	selector	157	ADT	name	type, scope, role, total, style, class	+		solution	209	QUIZ		xml:id, for, style, class, theory, generated-from, generated-via	+	(CMP*, FMP*) proof	sortdef	156	ADT	name	role, scope, style, class	+	(constructor insort)*	dc:source	100	DC			-	ANY	style	189	PRES	format	xml:lang, requires	-	(element text recurse value-of)*	dc:subject	99	DC		xml:lang	-	CMPcontent	symbol	136	ST	name	role, scope, style, class, generated-from, generated-via	+	type*
selector	157	ADT	name	type, scope, role, total, style, class	+																																																																																																		
solution	209	QUIZ		xml:id, for, style, class, theory, generated-from, generated-via	+	(CMP*, FMP*) proof																																																																																																	
sortdef	156	ADT	name	role, scope, style, class	+	(constructor insort)*																																																																																																	
dc:source	100	DC			-	ANY																																																																																																	
style	189	PRES	format	xml:lang, requires	-	(element text recurse value-of)*																																																																																																	
dc:subject	99	DC		xml:lang	-	CMPcontent																																																																																																	
symbol	136	ST	name	role, scope, style, class, generated-from, generated-via	+	type*																																																																																																	
selector	157	ADT	name	type, scope, role, total, style, class	+																																																																																																		
solution	209	QUIZ		xml:id, for, style, class, theory, generated-from, generated-via	+	(CMP*, FMP*) proof																																																																																																	
sortdef	156	ADT	name	role, scope, style, class	+	(constructor insort)*																																																																																																	
dc:source	100	DC			-	ANY																																																																																																	
style	189	PRES	format	xml:lang, requires	-	(element text recurse value-of)*																																																																																																	
dc:subject	99	DC		xml:lang	-	CMPcontent																																																																																																	
symbol	136	ST	name	role, scope, style, class, generated-from, generated-via	+	type*																																																																																																	
kohlhase-omdoc_TAB_095	336	0.958	<pre>\begin{tabular}[t]{ l l l l l l l }\hline table & 130 & RT & & xml:id, style, class, index, verbalizes & - & tr* \\term & 128 & MTXT & cd, name & xml:id, role, style, class & - & CMP content \\ \hline\end{tabular}</pre>	<table><tr><td>table</td><td>130</td><td>RT</td><td></td><td>xml:id, style, class, index, verbalizes</td><td>-</td><td>tr*</td></tr><tr><td>term</td><td>128</td><td>MTXT</td><td>cd, name</td><td>xml:id, role, style, class</td><td>-</td><td>CMP content</td></tr></table>	table	130	RT		xml:id, style, class, index, verbalizes	-	tr*	term	128	MTXT	cd, name	xml:id, role, style, class	-	CMP content	<table><tr><td>table</td><td>130</td><td>RT</td><td></td><td>xml:id, style, class, index, verbalizes</td><td>-</td><td>tr*</td></tr><tr><td>term</td><td>128</td><td>MTXT</td><td>cd, name</td><td>xml:id, role, style, class</td><td>-</td><td>CMP content</td></tr></table>	table	130	RT		xml:id, style, class, index, verbalizes	-	tr*	term	128	MTXT	cd, name	xml:id, role, style, class	-	CMP content																																																																						
table	130	RT		xml:id, style, class, index, verbalizes	-	tr*																																																																																																	
term	128	MTXT	cd, name	xml:id, role, style, class	-	CMP content																																																																																																	
table	130	RT		xml:id, style, class, index, verbalizes	-	tr*																																																																																																	
term	128	MTXT	cd, name	xml:id, role, style, class	-	CMP content																																																																																																	

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																																																												
kohlhase-omdoc_TAB_096	337	0.863	<pre>\begin{tabular}[t]{ l l l l l l l } \hline text & 190 & PRES & & & & \\ \hline td & 130 & RT & & & & \\ \hline th & 130 & RT & & & & \\ \hline theory & 149 & ST & xml:id & & & \\ \hline theory-inclusion & 178 & CTH & from, to & & & \\ \hline tr & 130 & RT & & & & \\ \hline dc:title & 98 & DC & & & & \\ \hline tgroup & 149 & DOC & & & & \\ \hline type & 139 & ST & system & & & \\ \hline dc:type & 100 & DC & & & & \\ \hline \end{tabular}</pre>	<table><tr><td>text</td><td>190</td><td>PRES</td><td></td><td></td><td>-</td><td>#PCDATA</td></tr><tr><td>td</td><td>130</td><td>RT</td><td></td><td></td><td>-</td><td>Math Vernacular</td></tr><tr><td>th</td><td>130</td><td>RT</td><td></td><td></td><td>-</td><td>Math Vernacular</td></tr><tr><td>theory</td><td>149</td><td>ST</td><td>xml:id</td><td></td><td>+</td><td>(statement theory)*</td></tr><tr><td>theory-inclusion</td><td>178</td><td>CTH</td><td>from, to</td><td></td><td>+</td><td>(morphism, decomposition?)</td></tr><tr><td>tr</td><td>130</td><td>RT</td><td></td><td></td><td>-</td><td>(td th)*</td></tr><tr><td>dc:title</td><td>98</td><td>DC</td><td></td><td></td><td>-</td><td>CMPcontent</td></tr><tr><td>tgroup</td><td>149</td><td>DOC</td><td></td><td></td><td>+</td><td>top-level or theory-constitutive element*</td></tr><tr><td>type</td><td>139</td><td>ST</td><td>system</td><td></td><td>-</td><td>CMP*, (OMOBJ m:math legacy)</td></tr><tr><td>dc:type</td><td>100</td><td>DC</td><td></td><td></td><td>-</td><td>fixed: "Dataset" or "Text" or "Collection"</td></tr></table>	text	190	PRES			-	#PCDATA	td	130	RT			-	Math Vernacular	th	130	RT			-	Math Vernacular	theory	149	ST	xml:id		+	(statement theory)*	theory-inclusion	178	CTH	from, to		+	(morphism, decomposition?)	tr	130	RT			-	(td th)*	dc:title	98	DC			-	CMPcontent	tgroup	149	DOC			+	top-level or theory-constitutive element*	type	139	ST	system		-	CMP*, (OMOBJ m:math legacy)	dc:type	100	DC			-	fixed: "Dataset" or "Text" or "Collection"	<table><tr><td>text</td><td>190</td><td>PRES</td><td></td><td></td><td>-</td><td>#PCDATA</td></tr><tr><td>td</td><td>130</td><td>RT</td><td></td><td></td><td>-</td><td>Math Vernacular</td></tr><tr><td>th</td><td>130</td><td>RT</td><td></td><td></td><td>-</td><td>Math Vernacular</td></tr><tr><td>theory</td><td>149</td><td>ST</td><td>xml:id</td><td></td><td>+</td><td>(statement theory)*</td></tr><tr><td>theory-inclusion</td><td>178</td><td>CTH</td><td>from, to</td><td></td><td>+</td><td>(morphism, decomposition?)</td></tr><tr><td>tr</td><td>130</td><td>RT</td><td></td><td></td><td>-</td><td>(td th)*</td></tr><tr><td>dc:title</td><td>98</td><td>DC</td><td></td><td></td><td>-</td><td>CMPcontent</td></tr><tr><td>tgroup</td><td>149</td><td>DOC</td><td></td><td></td><td>+</td><td>top-level or theoryconstitutive element*</td></tr><tr><td>type</td><td>139</td><td>ST</td><td>system</td><td></td><td>-</td><td>CMP*, (OMOBJ m:math legacy)</td></tr><tr><td>dc:type</td><td>100</td><td>DC</td><td></td><td></td><td>-</td><td>fixed: "Dataset" or "Text" or "Collection"</td></tr></table>	text	190	PRES			-	#PCDATA	td	130	RT			-	Math Vernacular	th	130	RT			-	Math Vernacular	theory	149	ST	xml:id		+	(statement theory)*	theory-inclusion	178	CTH	from, to		+	(morphism, decomposition?)	tr	130	RT			-	(td th)*	dc:title	98	DC			-	CMPcontent	tgroup	149	DOC			+	top-level or theoryconstitutive element*	type	139	ST	system		-	CMP*, (OMOBJ m:math legacy)	dc:type	100	DC			-	fixed: "Dataset" or "Text" or "Collection"
text	190	PRES			-	#PCDATA																																																																																																																																											
td	130	RT			-	Math Vernacular																																																																																																																																											
th	130	RT			-	Math Vernacular																																																																																																																																											
theory	149	ST	xml:id		+	(statement theory)*																																																																																																																																											
theory-inclusion	178	CTH	from, to		+	(morphism, decomposition?)																																																																																																																																											
tr	130	RT			-	(td th)*																																																																																																																																											
dc:title	98	DC			-	CMPcontent																																																																																																																																											
tgroup	149	DOC			+	top-level or theory-constitutive element*																																																																																																																																											
type	139	ST	system		-	CMP*, (OMOBJ m:math legacy)																																																																																																																																											
dc:type	100	DC			-	fixed: "Dataset" or "Text" or "Collection"																																																																																																																																											
text	190	PRES			-	#PCDATA																																																																																																																																											
td	130	RT			-	Math Vernacular																																																																																																																																											
th	130	RT			-	Math Vernacular																																																																																																																																											
theory	149	ST	xml:id		+	(statement theory)*																																																																																																																																											
theory-inclusion	178	CTH	from, to		+	(morphism, decomposition?)																																																																																																																																											
tr	130	RT			-	(td th)*																																																																																																																																											
dc:title	98	DC			-	CMPcontent																																																																																																																																											
tgroup	149	DOC			+	top-level or theoryconstitutive element*																																																																																																																																											
type	139	ST	system		-	CMP*, (OMOBJ m:math legacy)																																																																																																																																											
dc:type	100	DC			-	fixed: "Dataset" or "Text" or "Collection"																																																																																																																																											
kohlhase-omdoc_TAB_097	337	0.546	<pre>\begin{tabular}[t]{ l l l l l l l } \hline ul & 130 & RT & & & & \\ \hline use & 194 & PRES & format & & & \\ \hline value-of & 190 & PRES & select & & & \\ \hline phrase & 126 & MTXT & & & & \\ \hline xslt & 189 & PRES & format & & & \\ \hline \end{tabular}</pre>	<table><tr><td>ul</td><td>130</td><td>RT</td><td></td><td></td><td>-</td><td>li*</td></tr><tr><td>use</td><td>194</td><td>PRES</td><td>format</td><td></td><td>-</td><td>(use xslt style)*</td></tr><tr><td>value-of</td><td>190</td><td>PRES</td><td>select</td><td></td><td>-</td><td>EMPTY</td></tr><tr><td>phrase</td><td>126</td><td>MTXT</td><td></td><td></td><td>-</td><td>CMP content</td></tr><tr><td>xslt</td><td>189</td><td>PRES</td><td>format</td><td></td><td>-</td><td>XSLT fragment</td></tr></table>	ul	130	RT			-	li*	use	194	PRES	format		-	(use xslt style)*	value-of	190	PRES	select		-	EMPTY	phrase	126	MTXT			-	CMP content	xslt	189	PRES	format		-	XSLT fragment	<table><tr><td>ul</td><td>130</td><td>RT</td><td></td><td></td><td>-</td><td>li*</td></tr><tr><td>use</td><td>194</td><td>PRES</td><td>format</td><td></td><td>-</td><td>(use xslt style)*</td></tr><tr><td>value-of</td><td>190</td><td>PRES</td><td>select</td><td></td><td>-</td><td>EMPTY</td></tr><tr><td>phrase</td><td>126</td><td>MTXT</td><td></td><td></td><td>-</td><td>CMP content</td></tr><tr><td>xslt</td><td>189</td><td>PRES</td><td>format</td><td></td><td>-</td><td>XSLT fragment</td></tr></table>	ul	130	RT			-	li*	use	194	PRES	format		-	(use xslt style)*	value-of	190	PRES	select		-	EMPTY	phrase	126	MTXT			-	CMP content	xslt	189	PRES	format		-	XSLT fragment																																																																						
ul	130	RT			-	li*																																																																																																																																											
use	194	PRES	format		-	(use xslt style)*																																																																																																																																											
value-of	190	PRES	select		-	EMPTY																																																																																																																																											
phrase	126	MTXT			-	CMP content																																																																																																																																											
xslt	189	PRES	format		-	XSLT fragment																																																																																																																																											
ul	130	RT			-	li*																																																																																																																																											
use	194	PRES	format		-	(use xslt style)*																																																																																																																																											
value-of	190	PRES	select		-	EMPTY																																																																																																																																											
phrase	126	MTXT			-	CMP content																																																																																																																																											
xslt	189	PRES	format		-	XSLT fragment																																																																																																																																											

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																			
kohlhase-omdoc_TAB_098	338	0.805	<pre>\begin{tabular}[t]{ l l l } \hline Attribute & element & Values \\ \hline action & dc:date & unspecified \\ \hline & & specifies the action taken on the document on this date. \\ \hline action & omlet & execute, display, other \\ \hline & & specifies the action to be taken when executing the omlet, the value is application-defined. \\ \hline actuate & omlet & onPresent, onLoad, onRequest, other \\ \hline & & specifies the timing of the action specified in the action attribute \\ \hline assertion & example & \\ \hline & & specifies the assertion that states that the objects given in the example really have the expected properties. \\ \hline assertion & obligation & \\ \hline & & specifies the assertion that states that the translation of the statement in the source theory specified by the induced-by attribute is valid in the target theory. \\ \hline attributes & use & \\ \hline & & the attribute string for the start tag of the XML element substituted for the brackets (this is specified in the element attribute). \\ \hline attribution & cc:requirements & required, not_required \\ \hline & & Specifies whether the copyright holder/author must be given credit in derivative works \\ \hline base & morphism & \\ \hline & & specifies another morphism that should be used as a base for expansion in the definition of this morphism \\ \hline bracket-style & presentation, use & lisp, math \\ \hline & & specifies whether a function application is of the form $f(a,b)$ or (fab) \\ \hline cd & om:OMS & \\ \hline & & specifies the content dictionary of an OPENMATH symbol \\ \hline cd & term & \\ \hline & & specifies the content dictionary of a technical term \\ \hline cdbase & om:* & \\ \hline & & specifies the base URI of the content dictionaries used in an OPENMATH object \\ \hline cdreviewdate & theory & \\ \hline & & specifies the date until which the content dictionary will remain unchanged \\ \hline cdrevision & theory & \\ \hline & & specifies the minor version number of the content dictionary \\ \hline cdstatus & theory & official, experimental, private, obsolete \\ \hline & & specifies the content dictionary status \\ \hline cdurl & theory & \\ \hline & & the main URL, where the newest version of the content dictionary can be found \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><td>Attribute</td><td><i>element</i></td><td>Values</td></tr><tr><td>action</td><td>dc:date</td><td>unspecified</td></tr><tr><td></td><td></td><td>specifies the action taken on the document on this date.</td></tr><tr><td>action</td><td>omlet</td><td>execute, display, other</td></tr><tr><td></td><td></td><td>specifies the action to be taken when executing the omlet, the value is application-defined.</td></tr><tr><td>actuate</td><td>omlet</td><td>onPresent, onLoad, onRequest, other</td></tr><tr><td></td><td></td><td>specifies the timing of the action specified in the action attribute</td></tr><tr><td>assertion</td><td>example</td><td></td></tr><tr><td></td><td></td><td>specifies the assertion that states that the objects given in the example really have the expected properties.</td></tr><tr><td>assertion</td><td>obligation</td><td></td></tr><tr><td></td><td></td><td>specifies the assertion that states that the translation of the statement in the source theory specified by the induced-by attribute is valid in the target theory.</td></tr><tr><td>attributes</td><td>use</td><td></td></tr><tr><td></td><td></td><td>the attribute string for the start tag of the XML element substituted for the brackets (this is specified in the element attribute).</td></tr><tr><td>attribution</td><td>cc:requirements</td><td>required, not_required</td></tr><tr><td></td><td></td><td>Specifies whether the copyright holder/author must be given credit in derivative works</td></tr><tr><td>base</td><td>morphism</td><td></td></tr><tr><td></td><td></td><td>specifies another morphism that should be used as a base for expansion in the definition of this morphism</td></tr><tr><td>bracket-style</td><td>presentation, use</td><td>lisp, math</td></tr><tr><td></td><td></td><td>specifies whether a function application is of the form $f(a,b)$ or (fab)</td></tr><tr><td>cd</td><td>om:OMS</td><td></td></tr><tr><td></td><td></td><td>specifies the content dictionary of an OPENMATH symbol</td></tr><tr><td>cd</td><td>term</td><td></td></tr><tr><td></td><td></td><td>specifies the content dictionary of a technical term</td></tr><tr><td>cdbase</td><td>om:*</td><td></td></tr><tr><td></td><td></td><td>specifies the base URI of the content dictionaries used in an OPENMATH object</td></tr><tr><td>cdreviewdate</td><td>theory</td><td></td></tr><tr><td></td><td></td><td>specifies the date until which the content dictionary will remain unchanged</td></tr><tr><td>cdrevision</td><td>theory</td><td></td></tr><tr><td></td><td></td><td>specifies the minor version number of the content dictionary</td></tr><tr><td>cdstatus</td><td>theory</td><td>official, experimental, private, obsolete</td></tr><tr><td></td><td></td><td>specifies the content dictionary status</td></tr><tr><td>cdurl</td><td>theory</td><td></td></tr><tr><td></td><td></td><td>the main URL, where the newest version of the content dictionary can be found</td></tr></table>	Attribute	<i>element</i>	Values	action	dc:date	unspecified			specifies the action taken on the document on this date.	action	omlet	execute, display, other			specifies the action to be taken when executing the omlet, the value is application-defined.	actuate	omlet	onPresent, onLoad, onRequest, other			specifies the timing of the action specified in the action attribute	assertion	example				specifies the assertion that states that the objects given in the example really have the expected properties.	assertion	obligation				specifies the assertion that states that the translation of the statement in the source theory specified by the induced-by attribute is valid in the target theory.	attributes	use				the attribute string for the start tag of the XML element substituted for the brackets (this is specified in the element attribute).	attribution	cc:requirements	required, not_required			Specifies whether the copyright holder/author must be given credit in derivative works	base	morphism				specifies another morphism that should be used as a base for expansion in the definition of this morphism	bracket-style	presentation, use	lisp, math			specifies whether a function application is of the form $f(a,b)$ or (fab)	cd	om:OMS				specifies the content dictionary of an OPENMATH symbol	cd	term				specifies the content dictionary of a technical term	cdbase	om:*				specifies the base URI of the content dictionaries used in an OPENMATH object	cdreviewdate	theory				specifies the date until which the content dictionary will remain unchanged	cdrevision	theory				specifies the minor version number of the content dictionary	cdstatus	theory	official, experimental, private, obsolete			specifies the content dictionary status	cdurl	theory				the main URL, where the newest version of the content dictionary can be found
Attribute	<i>element</i>	Values																																																																																																						
action	dc:date	unspecified																																																																																																						
		specifies the action taken on the document on this date.																																																																																																						
action	omlet	execute, display, other																																																																																																						
		specifies the action to be taken when executing the omlet, the value is application-defined.																																																																																																						
actuate	omlet	onPresent, onLoad, onRequest, other																																																																																																						
		specifies the timing of the action specified in the action attribute																																																																																																						
assertion	example																																																																																																							
		specifies the assertion that states that the objects given in the example really have the expected properties.																																																																																																						
assertion	obligation																																																																																																							
		specifies the assertion that states that the translation of the statement in the source theory specified by the induced-by attribute is valid in the target theory.																																																																																																						
attributes	use																																																																																																							
		the attribute string for the start tag of the XML element substituted for the brackets (this is specified in the element attribute).																																																																																																						
attribution	cc:requirements	required, not_required																																																																																																						
		Specifies whether the copyright holder/author must be given credit in derivative works																																																																																																						
base	morphism																																																																																																							
		specifies another morphism that should be used as a base for expansion in the definition of this morphism																																																																																																						
bracket-style	presentation, use	lisp, math																																																																																																						
		specifies whether a function application is of the form $f(a,b)$ or (fab)																																																																																																						
cd	om:OMS																																																																																																							
		specifies the content dictionary of an OPENMATH symbol																																																																																																						
cd	term																																																																																																							
		specifies the content dictionary of a technical term																																																																																																						
cdbase	om:*																																																																																																							
		specifies the base URI of the content dictionaries used in an OPENMATH object																																																																																																						
cdreviewdate	theory																																																																																																							
		specifies the date until which the content dictionary will remain unchanged																																																																																																						
cdrevision	theory																																																																																																							
		specifies the minor version number of the content dictionary																																																																																																						
cdstatus	theory	official, experimental, private, obsolete																																																																																																						
		specifies the content dictionary status																																																																																																						
cdurl	theory																																																																																																							
		the main URL, where the newest version of the content dictionary can be found																																																																																																						

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																																																													
kohlhase-omdoc_TAB_099	339	■ 0.420	<pre>\begin{tabular}[t]{ l l l } \hline cdversion & theory & \\ \hline & specifies the major version number of the content dictionary & \\ \hline comment & ignore & \\ \hline & specifies a reason why we want to ignore the contents & \\ \hline crossref-symbol & presentation, use & all, brackets, lbrack, no, rbrack, separator, yes \\ \hline & specifies whether cross-references to the symbol definition should be generated in the output format. & \\ \hline class & * & \\ \hline & specifies the CSS class & \\ \hline commercial_use & cc:permissions & permitted, prohibited \\ \hline & specifies, whether commercial use of the document with this license is permitted & \\ \hline consistency & morphism, definition & OMDoc reference \\ \hline & points to an assertion stating that the cases are consistent, i.e. that they give the same values, where they overlap & \\ \hline copleft & cc:restrictions & required, not_required \\ \hline & specifies whether derived works must be licensed with the same license as the current document. & \\ \hline cr & element & yes/no \\ \hline & specifies whether an xlink:href cross-reference should be set on the result element. & \\ \hline cref & om:* & URI reference \\ \hline & extra attribute for cross-references in parallel markup & \\ \hline crid & element & XPATH expression \\ \hline & the path to the sub-element that corresponds to the result element. & \\ \hline crossref-symbol & presentation, use & no, yes, brackets, separator, lbrack, rbrack, all \\ \hline & specifies which generated presentation elements should carry cross-references to the definition. & \\ \hline data & omlet & \\ \hline & points to a private element that contains the data for this omlet & \\ \hline definitionURL & m:* & URI \\ \hline & points to the definition of a mathematical concept & \\ \hline derivative_works & cc:permissions & permitted, not_permitted \\ \hline & specifies whether the document may be used for making derivative works. & \\ \hline distribution & cc:permissions & permitted,not_permitted \\ \hline & specifies whether distribution of the current document fragment is permitted. & \\ \hline element & use & \\ \hline & the XML element tags to be substituted for the brackets. & \\ \hline element & omstyle & \\ \hline & the XML element, the presentation information contained in the omstyle element should be applied to. & \\ \hline encoding & m:annotation,om:OMFOREIGN & MIME type of the content \\ \hline & specifies the format of the content & \\ \hline entails, entailed-by & alternative & \\ \hline & specifies the equivalent formulations of a definition or axiom & \\ \hline entails-thm, entailed-by-thm & alternative & \\ \hline & specifies the entailment statements for equivalent formulations of a definition or axiom & \\ \hline exhaustivity & morphism, definition & OMDoc reference \\ \hline & points to an assertion that states that the cases are exhaustive. & \\ \hline existence & definition & OMDoc reference \\ \hline & points to an assertion that states that the symbol described in an implicit definition exists & \\ \hline fixity & presentation & assoc, infix, postfix, prefix \\ \hline & specifies where the function symbol-of a function application should be displayed in the output format & \\ \hline function & omlet & \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><td>cdversion</td><td>theory</td><td></td></tr><tr><td></td><td>specifies the major version number of the content dictionary</td><td></td></tr><tr><td>comment</td><td>ignore</td><td></td></tr><tr><td></td><td>specifies a reason why we want to ignore the contents</td><td></td></tr><tr><td>crossref-symbol</td><td>presentation, use</td><td>all, brackets, lbrack, no, rbrack, separator, yes</td></tr><tr><td></td><td>specifies whether cross-references to the symbol definition should be generated in the output format.</td><td></td></tr><tr><td>class</td><td>*</td><td></td></tr><tr><td></td><td>specifies the CSS class</td><td></td></tr><tr><td>commercial_use</td><td>cc:permissions</td><td>permitted, prohibited</td></tr><tr><td></td><td>specifies, whether commercial use of the document with this license is permitted</td><td></td></tr><tr><td>consistency</td><td>morphism, definition</td><td>OMDoc reference</td></tr><tr><td></td><td>points to an assertion stating that the cases are consistent, i.e. that they give the same values, where they overlap</td><td></td></tr><tr><td>copleft</td><td>cc:restrictions</td><td>required, not_required</td></tr><tr><td></td><td>specifies whether derived works must be licensed with the same license as the current document.</td><td></td></tr><tr><td>cr</td><td>element</td><td>yes/no</td></tr><tr><td></td><td>specifies whether an xlink:href cross-reference should be set on the result element.</td><td></td></tr><tr><td>cref</td><td>om:*</td><td>URI reference</td></tr><tr><td></td><td>extra attribute for cross-references in parallel markup</td><td></td></tr><tr><td>crid</td><td>element</td><td>XPATH expression</td></tr><tr><td></td><td>the path to the sub-element that corresponds to the result element.</td><td></td></tr><tr><td>crossref-symbol</td><td>presentation, use</td><td>no, yes, brackets, separator, lbrack, rbrack, all</td></tr><tr><td></td><td>specifies which generated presentation elements should carry cross-references to the definition.</td><td></td></tr><tr><td>data</td><td>omlet</td><td></td></tr><tr><td></td><td>points to a private element that contains the data for this omlet</td><td></td></tr><tr><td>definitionURL</td><td>m:*</td><td>URI</td></tr><tr><td></td><td>points to the definition of a mathematical concept</td><td></td></tr><tr><td>derivative_works</td><td>cc:permissions</td><td>permitted, not_permitted</td></tr><tr><td></td><td>specifies whether the document may be used for making derivative works.</td><td></td></tr><tr><td>distribution</td><td>cc:permissions</td><td>permitted,not_permitted</td></tr><tr><td></td><td>specifies whether distribution of the current document fragment is permitted.</td><td></td></tr><tr><td>element</td><td>use</td><td></td></tr><tr><td></td><td>the XML element tags to be substituted for the brackets.</td><td></td></tr><tr><td>element</td><td>omstyle</td><td></td></tr><tr><td></td><td>the XML element, the presentation information contained in the omstyle element should be applied to.</td><td></td></tr><tr><td>encoding</td><td>m:annotation,om:OMFOREIGN</td><td>MIME type of the content</td></tr><tr><td></td><td>specifies the format of the content</td><td></td></tr><tr><td>entails, entailed-by</td><td>alternative</td><td></td></tr><tr><td></td><td>specifies the equivalent formulations of a definition or axiom</td><td></td></tr><tr><td>entails-thm, entailed-by-thm</td><td>alternative</td><td></td></tr><tr><td></td><td>specifies the entailment statements for equivalent formulations of a definition or axiom</td><td></td></tr><tr><td>exhaustivity</td><td>morphism, definition</td><td>OMDoc reference</td></tr><tr><td></td><td>points to an assertion that states that the cases are exhaustive.</td><td></td></tr><tr><td>existence</td><td>definition</td><td>OMDoc reference</td></tr><tr><td></td><td>points to an assertion that states that the symbol described in an implicit definition exists</td><td></td></tr><tr><td>fixity</td><td>presentation</td><td>assoc, infix, postfix, prefix</td></tr><tr><td></td><td>specifies where the function symbol-of a function application should be displayed in the output format</td><td></td></tr><tr><td>function</td><td>omlet</td><td></td></tr></table>	cdversion	theory			specifies the major version number of the content dictionary		comment	ignore			specifies a reason why we want to ignore the contents		crossref-symbol	presentation, use	all, brackets, lbrack, no, rbrack, separator, yes		specifies whether cross-references to the symbol definition should be generated in the output format.		class	*			specifies the CSS class		commercial_use	cc:permissions	permitted, prohibited		specifies, whether commercial use of the document with this license is permitted		consistency	morphism, definition	OMDoc reference		points to an assertion stating that the cases are consistent, i.e. that they give the same values, where they overlap		copleft	cc:restrictions	required, not_required		specifies whether derived works must be licensed with the same license as the current document.		cr	element	yes/no		specifies whether an xlink:href cross-reference should be set on the result element.		cref	om:*	URI reference		extra attribute for cross-references in parallel markup		crid	element	XPATH expression		the path to the sub-element that corresponds to the result element.		crossref-symbol	presentation, use	no, yes, brackets, separator, lbrack, rbrack, all		specifies which generated presentation elements should carry cross-references to the definition.		data	omlet			points to a private element that contains the data for this omlet		definitionURL	m:*	URI		points to the definition of a mathematical concept		derivative_works	cc:permissions	permitted, not_permitted		specifies whether the document may be used for making derivative works.		distribution	cc:permissions	permitted,not_permitted		specifies whether distribution of the current document fragment is permitted.		element	use			the XML element tags to be substituted for the brackets.		element	omstyle			the XML element, the presentation information contained in the omstyle element should be applied to.		encoding	m:annotation,om:OMFOREIGN	MIME type of the content		specifies the format of the content		entails, entailed-by	alternative			specifies the equivalent formulations of a definition or axiom		entails-thm, entailed-by-thm	alternative			specifies the entailment statements for equivalent formulations of a definition or axiom		exhaustivity	morphism, definition	OMDoc reference		points to an assertion that states that the cases are exhaustive.		existence	definition	OMDoc reference		points to an assertion that states that the symbol described in an implicit definition exists		fixity	presentation	assoc, infix, postfix, prefix		specifies where the function symbol-of a function application should be displayed in the output format		function	omlet	
cdversion	theory																																																																																																																																																	
	specifies the major version number of the content dictionary																																																																																																																																																	
comment	ignore																																																																																																																																																	
	specifies a reason why we want to ignore the contents																																																																																																																																																	
crossref-symbol	presentation, use	all, brackets, lbrack, no, rbrack, separator, yes																																																																																																																																																
	specifies whether cross-references to the symbol definition should be generated in the output format.																																																																																																																																																	
class	*																																																																																																																																																	
	specifies the CSS class																																																																																																																																																	
commercial_use	cc:permissions	permitted, prohibited																																																																																																																																																
	specifies, whether commercial use of the document with this license is permitted																																																																																																																																																	
consistency	morphism, definition	OMDoc reference																																																																																																																																																
	points to an assertion stating that the cases are consistent, i.e. that they give the same values, where they overlap																																																																																																																																																	
copleft	cc:restrictions	required, not_required																																																																																																																																																
	specifies whether derived works must be licensed with the same license as the current document.																																																																																																																																																	
cr	element	yes/no																																																																																																																																																
	specifies whether an xlink:href cross-reference should be set on the result element.																																																																																																																																																	
cref	om:*	URI reference																																																																																																																																																
	extra attribute for cross-references in parallel markup																																																																																																																																																	
crid	element	XPATH expression																																																																																																																																																
	the path to the sub-element that corresponds to the result element.																																																																																																																																																	
crossref-symbol	presentation, use	no, yes, brackets, separator, lbrack, rbrack, all																																																																																																																																																
	specifies which generated presentation elements should carry cross-references to the definition.																																																																																																																																																	
data	omlet																																																																																																																																																	
	points to a private element that contains the data for this omlet																																																																																																																																																	
definitionURL	m:*	URI																																																																																																																																																
	points to the definition of a mathematical concept																																																																																																																																																	
derivative_works	cc:permissions	permitted, not_permitted																																																																																																																																																
	specifies whether the document may be used for making derivative works.																																																																																																																																																	
distribution	cc:permissions	permitted,not_permitted																																																																																																																																																
	specifies whether distribution of the current document fragment is permitted.																																																																																																																																																	
element	use																																																																																																																																																	
	the XML element tags to be substituted for the brackets.																																																																																																																																																	
element	omstyle																																																																																																																																																	
	the XML element, the presentation information contained in the omstyle element should be applied to.																																																																																																																																																	
encoding	m:annotation,om:OMFOREIGN	MIME type of the content																																																																																																																																																
	specifies the format of the content																																																																																																																																																	
entails, entailed-by	alternative																																																																																																																																																	
	specifies the equivalent formulations of a definition or axiom																																																																																																																																																	
entails-thm, entailed-by-thm	alternative																																																																																																																																																	
	specifies the entailment statements for equivalent formulations of a definition or axiom																																																																																																																																																	
exhaustivity	morphism, definition	OMDoc reference																																																																																																																																																
	points to an assertion that states that the cases are exhaustive.																																																																																																																																																	
existence	definition	OMDoc reference																																																																																																																																																
	points to an assertion that states that the symbol described in an implicit definition exists																																																																																																																																																	
fixity	presentation	assoc, infix, postfix, prefix																																																																																																																																																
	specifies where the function symbol-of a function application should be displayed in the output format																																																																																																																																																	
function	omlet																																																																																																																																																	

51

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																																																																					
kohlhase-omdoc_TAB_100	340	0.938	<pre>\begin{tabular}[t]{ l l }\hline & \multicolumn{2}{ l }{specifies the function to be called when this omlet is activated.} \\ \hline format & data & \\ \hline & * & specifies the format of the data specified by a data element. The value should e.g. be a MIME type [FB96].} \\ \hline for & * & can be used to reference an element by its unique identifier given in its xml:id attribute. \\ \hline formalism & legacy & URI reference \\ \hline & & specifies the formalism in which the content is expressed \\ \hline format & legacy & URI reference \\ \hline & & specifies the encoding format of the content \\ \hline format & use & cmml, default, html, mathematica, pmml, TeX,... \\ \hline & & specifies the output format for which the notation is specified \\ \hline from & imports, theory-inclusion, axiom-inclusion & URI reference \\ \hline & & pointer to source theory of a theory morphism \\ \hline from & omtex & URI reference \\ \hline & & points to the source of a relation given by a text type \\ \hline generated-from & top-level elements & URI reference \\ \hline & & points to a higher-level syntax element, that generates this statement. \\ \hline generated-via & top-level elements,... & URI reference \\ \hline & & points to a theory-morphism, via which it is translated from the element pointed to by the generated-from attribute. \\ \hline globals & path-just & \\ \hline & & points to the axiom-inclusions or theory-inclusions that is the rest of the inclusion path. \\ \hline hiding & morphism & \\ \hline & & specifies the names of symbols that are in the domain of the morphism \\ \hline href & data, link, om:OMR & URI reference \\ \hline & & a URI to an external file containing the data. \\ \hline xml:id & & \\ \hline & & associates a unique identifier to an element, which can thus be referenced by an for or xref attribute. \\ \hline xml:base & & \\ \hline & & specifies a base URL for a resource fragment \\ \hline index & on RT elements & \\ \hline & & A path identifier to establish multilingual correspondence \\ \hline induced-by & obligation & \\ \hline & & points to the statement in the source theory that induces this proof obligation \\ \hline inductive & assumption, hypothesis & yes, no \\ \hline & & Marks an assumption or hypothesis inductive. \\ \hline inherits & metadata & URI reference \\ \hline & & points to a metadata element from which this one inherits. \\ \hline jurisdiction & cc:license & IANA Top level Domain designator \\ \hline & & specifies the country of jurisdiction for a Creative Commons license \\ \hline just-by & type & \\ \hline & & points to an assertion that states the type property in question. \\ \hline role & symbol, constructor, recognizer, selector, sortdef & object, type, sort, binder, attribution, semantic-attribution, error \\ \hline & & specifies the role (possible syntactic roles) of the symbol in this declaration. \\ \hline role & dc:creator,dc:contributor & MARC relators \\ \hline & & specifies the role of a person who has contributed to the document \\ \hline role & presentation & applied, binding, key \\ \hline & & specifies which role of the symbol is annotated with notation information \\ \hline lbrack & presentation, use & \\ \hline & & the left bracket to use in the notation of a function symbol \\ \hline links & decomposition & \end{tabular}</pre>	<table><tr><td></td><td>specifies the function to be called when this omlet is activated.</td><td></td></tr><tr><td>format</td><td>data</td><td></td></tr><tr><td></td><td>specifies the format of the data specified by a data element. The value should e.g. be a MIME type [FB96].</td><td></td></tr><tr><td>for</td><td>*</td><td></td></tr><tr><td></td><td>can be used to reference an element by its unique identifier given in its xml:id attribute.</td><td></td></tr><tr><td>formalism</td><td>legacy</td><td>URI reference</td></tr><tr><td></td><td>specifies the formalism in which the content is expressed</td><td></td></tr><tr><td>format</td><td>legacy</td><td>URI reference</td></tr><tr><td></td><td>specifies the encoding format of the content</td><td></td></tr><tr><td>format</td><td>use</td><td>cmml, default, html, mathematica, pmml, TeX,...</td></tr><tr><td></td><td>specifies the output format for which the notation is specified</td><td></td></tr><tr><td>from</td><td>imports, theory-inclusion, axiom-inclusion</td><td>URI reference</td></tr><tr><td></td><td>pointer to source theory of a theory morphism</td><td></td></tr><tr><td>from</td><td>omtext</td><td>URI reference</td></tr><tr><td></td><td>points to the source of a relation given by a text type</td><td></td></tr><tr><td>generated-from</td><td>top-level elements</td><td>URI reference</td></tr><tr><td></td><td>points to a higher-level syntax element, that generates this statement.</td><td></td></tr><tr><td>generated-via</td><td>top-level elements,...</td><td>URI reference</td></tr><tr><td></td><td>points to a theory-morphism, via which it is translated from the element pointed to by the generated-from attribute.</td><td></td></tr><tr><td>globals</td><td>path-just</td><td></td></tr><tr><td></td><td>points to the axiom-inclusions or theory-inclusions that is the rest of the inclusion path.</td><td></td></tr><tr><td>hiding</td><td>morphism</td><td></td></tr><tr><td></td><td>specifies the names of symbols that are in the domain of the morphism</td><td></td></tr><tr><td>href</td><td>data, link, om:OMR</td><td>URI reference</td></tr><tr><td></td><td>a URI to an external file containing the data.</td><td></td></tr><tr><td>xml:id</td><td></td><td></td></tr><tr><td></td><td>associates a unique identifier to an element, which can thus be referenced by an for or xref attribute.</td><td></td></tr><tr><td>xml:base</td><td></td><td></td></tr><tr><td></td><td>specifies a base URL for a resource fragment</td><td></td></tr><tr><td>index</td><td>on RT elements</td><td></td></tr><tr><td></td><td>A path identifier to establish multilingual correspondence</td><td></td></tr><tr><td>induced-by</td><td>obligation</td><td></td></tr><tr><td></td><td>points to the statement in the source theory that induces this proof obligation</td><td></td></tr><tr><td>inductive</td><td>assumption, hypothesis</td><td>yes, no</td></tr><tr><td></td><td>Marks an assumption or hypothesis inductive.</td><td></td></tr><tr><td>inherits</td><td>metadata</td><td>URI reference</td></tr><tr><td></td><td>points to a metadata element from which this one inherits.</td><td></td></tr><tr><td>jurisdiction</td><td>cc:license</td><td>IANA Top level Domain designator</td></tr><tr><td></td><td>specifies the country of jurisdiction for a Creative Commons license</td><td></td></tr><tr><td>just-by</td><td>type</td><td></td></tr><tr><td></td><td>points to an assertion that states the type property in question.</td><td></td></tr><tr><td>role</td><td>symbol, constructor, recognizer, selector, sortdef</td><td>object, type, sort, binder, attribution, semantic-attribution, error</td></tr><tr><td></td><td>specifies the role (possible syntactic roles) of the symbol in this declaration.</td><td></td></tr><tr><td>role</td><td>dc:creator,dc:contributor</td><td>MARC relators</td></tr><tr><td></td><td>specifies the role of a person who has contributed to the document</td><td></td></tr><tr><td>role</td><td>presentation</td><td>applied, binding, key</td></tr><tr><td></td><td>specifies which role of the symbol is annotated with notation information</td><td></td></tr><tr><td>lbrack</td><td>presentation, use</td><td></td></tr><tr><td></td><td>the left bracket to use in the notation of a function symbol</td><td></td></tr><tr><td>links</td><td>decomposition</td><td></td></tr></table>		specifies the function to be called when this omlet is activated.		format	data			specifies the format of the data specified by a data element. The value should e.g. be a MIME type [FB96].		for	*			can be used to reference an element by its unique identifier given in its xml:id attribute.		formalism	legacy	URI reference		specifies the formalism in which the content is expressed		format	legacy	URI reference		specifies the encoding format of the content		format	use	cmml, default, html, mathematica, pmml, TeX,...		specifies the output format for which the notation is specified		from	imports, theory-inclusion, axiom-inclusion	URI reference		pointer to source theory of a theory morphism		from	omtext	URI reference		points to the source of a relation given by a text type		generated-from	top-level elements	URI reference		points to a higher-level syntax element, that generates this statement.		generated-via	top-level elements,...	URI reference		points to a theory-morphism, via which it is translated from the element pointed to by the generated-from attribute.		globals	path-just			points to the axiom-inclusions or theory-inclusions that is the rest of the inclusion path.		hiding	morphism			specifies the names of symbols that are in the domain of the morphism		href	data, link, om:OMR	URI reference		a URI to an external file containing the data.		xml:id				associates a unique identifier to an element, which can thus be referenced by an for or xref attribute.		xml:base				specifies a base URL for a resource fragment		index	on RT elements			A path identifier to establish multilingual correspondence		induced-by	obligation			points to the statement in the source theory that induces this proof obligation		inductive	assumption, hypothesis	yes, no		Marks an assumption or hypothesis inductive.		inherits	metadata	URI reference		points to a metadata element from which this one inherits.		jurisdiction	cc:license	IANA Top level Domain designator		specifies the country of jurisdiction for a Creative Commons license		just-by	type			points to an assertion that states the type property in question.		role	symbol, constructor, recognizer, selector, sortdef	object, type, sort, binder, attribution, semantic-attribution, error		specifies the role (possible syntactic roles) of the symbol in this declaration.		role	dc:creator,dc:contributor	MARC relators		specifies the role of a person who has contributed to the document		role	presentation	applied, binding, key		specifies which role of the symbol is annotated with notation information		lbrack	presentation, use			the left bracket to use in the notation of a function symbol		links	decomposition	
	specifies the function to be called when this omlet is activated.																																																																																																																																																									
format	data																																																																																																																																																									
	specifies the format of the data specified by a data element. The value should e.g. be a MIME type [FB96].																																																																																																																																																									
for	*																																																																																																																																																									
	can be used to reference an element by its unique identifier given in its xml:id attribute.																																																																																																																																																									
formalism	legacy	URI reference																																																																																																																																																								
	specifies the formalism in which the content is expressed																																																																																																																																																									
format	legacy	URI reference																																																																																																																																																								
	specifies the encoding format of the content																																																																																																																																																									
format	use	cmml, default, html, mathematica, pmml, TeX,...																																																																																																																																																								
	specifies the output format for which the notation is specified																																																																																																																																																									
from	imports, theory-inclusion, axiom-inclusion	URI reference																																																																																																																																																								
	pointer to source theory of a theory morphism																																																																																																																																																									
from	omtext	URI reference																																																																																																																																																								
	points to the source of a relation given by a text type																																																																																																																																																									
generated-from	top-level elements	URI reference																																																																																																																																																								
	points to a higher-level syntax element, that generates this statement.																																																																																																																																																									
generated-via	top-level elements,...	URI reference																																																																																																																																																								
	points to a theory-morphism, via which it is translated from the element pointed to by the generated-from attribute.																																																																																																																																																									
globals	path-just																																																																																																																																																									
	points to the axiom-inclusions or theory-inclusions that is the rest of the inclusion path.																																																																																																																																																									
hiding	morphism																																																																																																																																																									
	specifies the names of symbols that are in the domain of the morphism																																																																																																																																																									
href	data, link, om:OMR	URI reference																																																																																																																																																								
	a URI to an external file containing the data.																																																																																																																																																									
xml:id																																																																																																																																																										
	associates a unique identifier to an element, which can thus be referenced by an for or xref attribute.																																																																																																																																																									
xml:base																																																																																																																																																										
	specifies a base URL for a resource fragment																																																																																																																																																									
index	on RT elements																																																																																																																																																									
	A path identifier to establish multilingual correspondence																																																																																																																																																									
induced-by	obligation																																																																																																																																																									
	points to the statement in the source theory that induces this proof obligation																																																																																																																																																									
inductive	assumption, hypothesis	yes, no																																																																																																																																																								
	Marks an assumption or hypothesis inductive.																																																																																																																																																									
inherits	metadata	URI reference																																																																																																																																																								
	points to a metadata element from which this one inherits.																																																																																																																																																									
jurisdiction	cc:license	IANA Top level Domain designator																																																																																																																																																								
	specifies the country of jurisdiction for a Creative Commons license																																																																																																																																																									
just-by	type																																																																																																																																																									
	points to an assertion that states the type property in question.																																																																																																																																																									
role	symbol, constructor, recognizer, selector, sortdef	object, type, sort, binder, attribution, semantic-attribution, error																																																																																																																																																								
	specifies the role (possible syntactic roles) of the symbol in this declaration.																																																																																																																																																									
role	dc:creator,dc:contributor	MARC relators																																																																																																																																																								
	specifies the role of a person who has contributed to the document																																																																																																																																																									
role	presentation	applied, binding, key																																																																																																																																																								
	specifies which role of the symbol is annotated with notation information																																																																																																																																																									
lbrack	presentation, use																																																																																																																																																									
	the left bracket to use in the notation of a function symbol																																																																																																																																																									
links	decomposition																																																																																																																																																									

52

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																		
kohlhase-omdoc_TAB_101	341	0.692	<pre>\begin{tabular}[t]{l l l } \hline & \multicolumn{2}{ c }{specifies a list of theory- or axiom-inclusions that justify (by decomposition) the theory-inclusion specified in the for attribute.} \\ \hline local & path-just & \hline & points to the axiom-inclusion that is the first element in the path. & \hline logic & FMP & token \\ \hline & & specifies the logical system used to encode the property. & \hline modules & omdoc, omgroup & module and sub-language shorthands, URI reference \\ \hline & & specifies the modules or OMDoc sub-language used in this document fragment} \\ \hline name & om:OMS, om:OMV, symbol, term & \hline & the name of a concept referenced by a symbol, variable, or technical term. \\ \hline name & attribute, element & \hline & the local name of generated element. \\ \hline name & param & \hline & the name of a parameter for an external object. \\ \hline notice & cc:requirements & required, not_required \\ \hline & & specifies whether copyright and license notices must be kept intact in distributed copies of this document} \\ \hline ns & element, attribute & URI \\ \hline & & specifies the namespace URI of the generated element or attribute node \\ \hline original & data & local, external \\ \hline & & specifies whether the local copy in the data element is the original or the external resource pointed to by the href attribute. \\ \hline parameters & adt & \hline & The list of formal parameters of a higher-order abstract data type \\ \hline precedence & presentation & \hline & the precedence of a function symbol (for elision of brackets) \\ \hline proofs & assertion & \hline & specifies a list of URIs to proofs of this assertion. \\ \hline pto, pto-version & private, code & \hline & specifies the system and its version this data or code is private to \\ \hline rank & premise & \hline & specifies the rank (importance) of a premise \\ \hline rbrack & presentation, use & \hline & the right bracket to use in the notation of a function symbol \\ \hline reformulates & private & \hline & points to a set of elements whose content is reformulated by the content of the private element for the system. \\ \hline reproduction & cc:permissions & permitted,not_permitted \\ \hline & & specifies whether reproduction of the current document fragment is permitted by the licensor \\ \hline requires & private, code, use, xslt, style & URI reference \\ \hline & & points to a code element that is needed for the execution of this data by the system. \\ \hline role & dc:creator, dc:collaborator & aft, ant, aqt, aui, aut, clb, edt, ths, trc, trl \\ \hline & & the MARC relator code for the contribution of the individual. \\ \hline role & phrase, term & \hline & the role of the phrase annotation \\ \hline role & presentation & applied, binding, key \\ \hline & & specifies for which role (as the head of a function application, as a binding symbol, or as a key in a attribution, or as a stand-alone symbol (the default)) of the symbol presentation is intended \\ \hline scheme & dc:identifier & scheme name \\ \hline & & specifies the identification scheme (e.g. ISBN) of a resource \\ \hline scope & symbol & global, local \\ \hline & & specifies the visibility of the symbol declared. This is a very crude specification, it is better to use theories and importing to specify symbol accessibility. \\ \hline select & map, recurse, value-of & XPATH expression \\ \hline & & specifies the path to the sub-expression to act on \\ \hline \end{tabular}</pre>	(not rendered)	<table><tr><td></td><td>specifies a list of theory- or axiom-inclusions that justify (by decomposition) the theory-inclusion specified in the for attribute.</td></tr><tr><td>local</td><td>path-just</td></tr><tr><td></td><td>points to the axiom-inclusion that is the first element in the path.</td></tr><tr><td>logic</td><td>FMPtoken</td></tr><tr><td></td><td>specifies the logical system used to encode the property.</td></tr><tr><td>modules</td><td>omdoc, omgroupmodule and sub-language shorthands, URI reference</td></tr><tr><td></td><td>specifies the modules or OMDoc sub-language used in this document fragment</td></tr><tr><td>name</td><td>om:OMS, om:OMV, symbol, term</td></tr><tr><td></td><td>the name of a concept referenced by a symbol, variable, or technical term.</td></tr><tr><td>name</td><td>attribute, element</td></tr><tr><td></td><td>the local name of generated element.</td></tr><tr><td>name</td><td>param</td></tr><tr><td></td><td>the name of a parameter for an external object.</td></tr><tr><td>notice</td><td>cc:requirementsrequired, not_required</td></tr><tr><td></td><td>specifies whether copyright and license notices must be kept intact in distributed copies of this document</td></tr><tr><td>ns</td><td>element, attributeURI</td></tr><tr><td></td><td>specifies the namespace URI of the generated element or attribute node</td></tr><tr><td>original</td><td>datalocal, external</td></tr><tr><td></td><td>specifies whether the local copy in the data element is the original or the external resource pointed to by the href attribute.</td></tr><tr><td>parameters</td><td>adt</td></tr><tr><td></td><td>The list of formal parameters of a higher-order abstract data type</td></tr><tr><td>precedence</td><td>presentation</td></tr><tr><td></td><td>the precedence of a function symbol (for elision of brackets)</td></tr><tr><td>proofs</td><td>assertion</td></tr><tr><td></td><td>specifies a list of URIs to proofs of this assertion.</td></tr><tr><td>pto, pto-version</td><td>private, code</td></tr><tr><td></td><td>specifies the system and its version this data or code is private to</td></tr><tr><td>rank</td><td>premise</td></tr><tr><td></td><td>specifies the rank (importance) of a premise</td></tr><tr><td>rbrack</td><td>presentation, use</td></tr><tr><td></td><td>the right bracket to use in the notation of a function symbol</td></tr><tr><td>reformulates</td><td>private</td></tr><tr><td></td><td>points to a set of elements whose content is reformulated by the content of the private element for the system.</td></tr><tr><td>reproduction</td><td>cc:permissionspermitted,not_permitted</td></tr><tr><td></td><td>specifies whether reproduction of the current document fragment is permitted by the licensor</td></tr><tr><td>requires</td><td>private, code, use, xslt, styleURI reference</td></tr><tr><td></td><td>points to a code element that is needed for the execution of this data by the system.</td></tr><tr><td>role</td><td>dc:creator, dc:collaboratoraft, ant, aqt, aui, aut, clb, edt, ths, trc, trl</td></tr><tr><td></td><td>the MARC relator code for the contribution of the individual.</td></tr><tr><td>role</td><td>phrase, term</td></tr><tr><td></td><td>the role of the phrase annotation</td></tr><tr><td>role</td><td>presentationapplied, binding, key</td></tr><tr><td></td><td>specifies for which role (as the head of a function application, as a binding symbol, or as a key in a attribution, or as a stand-alone symbol (the default)) of the symbol presentation is intended</td></tr><tr><td>scheme</td><td>dc:identifiervscheme name</td></tr><tr><td></td><td>specifies the identification scheme (e.g. ISBN) of a resource</td></tr><tr><td>scope</td><td>symbolglobal, local</td></tr><tr><td></td><td>specifies the visibility of the symbol declared. This is a very crude specification, it is better to use theories and importing to specify symbol accessibility.</td></tr><tr><td>select</td><td>map, recurse, value-ofXPath expression</td></tr><tr><td></td><td>specifies the path to the sub-expression to act on</td></tr></table>		specifies a list of theory- or axiom-inclusions that justify (by decomposition) the theory-inclusion specified in the for attribute.	local	path-just		points to the axiom-inclusion that is the first element in the path.	logic	FMPtoken		specifies the logical system used to encode the property.	modules	omdoc, omgroupmodule and sub-language shorthands, URI reference		specifies the modules or OMDoc sub-language used in this document fragment	name	om:OMS, om:OMV, symbol, term		the name of a concept referenced by a symbol, variable, or technical term.	name	attribute, element		the local name of generated element.	name	param		the name of a parameter for an external object.	notice	cc:requirementsrequired, not_required		specifies whether copyright and license notices must be kept intact in distributed copies of this document	ns	element, attributeURI		specifies the namespace URI of the generated element or attribute node	original	datalocal, external		specifies whether the local copy in the data element is the original or the external resource pointed to by the href attribute.	parameters	adt		The list of formal parameters of a higher-order abstract data type	precedence	presentation		the precedence of a function symbol (for elision of brackets)	proofs	assertion		specifies a list of URIs to proofs of this assertion.	pto, pto-version	private, code		specifies the system and its version this data or code is private to	rank	premise		specifies the rank (importance) of a premise	rbrack	presentation, use		the right bracket to use in the notation of a function symbol	reformulates	private		points to a set of elements whose content is reformulated by the content of the private element for the system.	reproduction	cc:permissionspermitted,not_permitted		specifies whether reproduction of the current document fragment is permitted by the licensor	requires	private, code, use, xslt, styleURI reference		points to a code element that is needed for the execution of this data by the system.	role	dc:creator, dc:collaboratoraft, ant, aqt, aui, aut, clb, edt, ths, trc, trl		the MARC relator code for the contribution of the individual.	role	phrase, term		the role of the phrase annotation	role	presentationapplied, binding, key		specifies for which role (as the head of a function application, as a binding symbol, or as a key in a attribution, or as a stand-alone symbol (the default)) of the symbol presentation is intended	scheme	dc:identifiervscheme name		specifies the identification scheme (e.g. ISBN) of a resource	scope	symbolglobal, local		specifies the visibility of the symbol declared. This is a very crude specification, it is better to use theories and importing to specify symbol accessibility.	select	map, recurse, value-ofXPath expression		specifies the path to the sub-expression to act on
	specifies a list of theory- or axiom-inclusions that justify (by decomposition) the theory-inclusion specified in the for attribute.																																																																																																						
local	path-just																																																																																																						
	points to the axiom-inclusion that is the first element in the path.																																																																																																						
logic	FMPtoken																																																																																																						
	specifies the logical system used to encode the property.																																																																																																						
modules	omdoc, omgroupmodule and sub-language shorthands, URI reference																																																																																																						
	specifies the modules or OMDoc sub-language used in this document fragment																																																																																																						
name	om:OMS, om:OMV, symbol, term																																																																																																						
	the name of a concept referenced by a symbol, variable, or technical term.																																																																																																						
name	attribute, element																																																																																																						
	the local name of generated element.																																																																																																						
name	param																																																																																																						
	the name of a parameter for an external object.																																																																																																						
notice	cc:requirementsrequired, not_required																																																																																																						
	specifies whether copyright and license notices must be kept intact in distributed copies of this document																																																																																																						
ns	element, attributeURI																																																																																																						
	specifies the namespace URI of the generated element or attribute node																																																																																																						
original	datalocal, external																																																																																																						
	specifies whether the local copy in the data element is the original or the external resource pointed to by the href attribute.																																																																																																						
parameters	adt																																																																																																						
	The list of formal parameters of a higher-order abstract data type																																																																																																						
precedence	presentation																																																																																																						
	the precedence of a function symbol (for elision of brackets)																																																																																																						
proofs	assertion																																																																																																						
	specifies a list of URIs to proofs of this assertion.																																																																																																						
pto, pto-version	private, code																																																																																																						
	specifies the system and its version this data or code is private to																																																																																																						
rank	premise																																																																																																						
	specifies the rank (importance) of a premise																																																																																																						
rbrack	presentation, use																																																																																																						
	the right bracket to use in the notation of a function symbol																																																																																																						
reformulates	private																																																																																																						
	points to a set of elements whose content is reformulated by the content of the private element for the system.																																																																																																						
reproduction	cc:permissionspermitted,not_permitted																																																																																																						
	specifies whether reproduction of the current document fragment is permitted by the licensor																																																																																																						
requires	private, code, use, xslt, styleURI reference																																																																																																						
	points to a code element that is needed for the execution of this data by the system.																																																																																																						
role	dc:creator, dc:collaboratoraft, ant, aqt, aui, aut, clb, edt, ths, trc, trl																																																																																																						
	the MARC relator code for the contribution of the individual.																																																																																																						
role	phrase, term																																																																																																						
	the role of the phrase annotation																																																																																																						
role	presentationapplied, binding, key																																																																																																						
	specifies for which role (as the head of a function application, as a binding symbol, or as a key in a attribution, or as a stand-alone symbol (the default)) of the symbol presentation is intended																																																																																																						
scheme	dc:identifiervscheme name																																																																																																						
	specifies the identification scheme (e.g. ISBN) of a resource																																																																																																						
scope	symbolglobal, local																																																																																																						
	specifies the visibility of the symbol declared. This is a very crude specification, it is better to use theories and importing to specify symbol accessibility.																																																																																																						
select	map, recurse, value-ofXPath expression																																																																																																						
	specifies the path to the sub-expression to act on																																																																																																						

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																																																										
kohlhase-omdoc_TAB_102	342	0.999	<pre>\begin{tabular}[t]{ l l l } \hline separator & presentation, use & \\ \hline show & omlet & new, replace, embed, other \\ \hline size & data & \\ \hline sort & argument & \\ \hline style & * & \\ \hline system & type & \\ \hline theory & + & \\ \hline to & theory-inclusion, axiom-inclusion & \\ \hline total & selector & no, yes \\ \hline type & adt & free, generated, loose \\ \hline type & assertion & theorem, lemma, corollary, conjecture, false-conjecture, obligation, postulate, formula, assumption, proposition \\ \hline type & definition & implicit, inductive, obj, recursive, simple \\ \hline type & derive & conclusion, gap \\ \hline type & example & against, for \\ \hline type & ignore & \\ \hline type & imports & global, local \\ \hline type & morphism & \\ \hline type & omgroup, omdoc & enumeration, sequence, itemize \\ \hline type & omtext & abstract, antithesis, comment, conclusion, elaboration, evidence, introduction, motivation, thesis \\ \hline type & phrase & \\ \hline type & ref & include, cite \\ \hline uniqueness & definition & URI reference \\ \hline value & param & \end{tabular}</pre>	<table><tr><td>separator</td><td>presentation, use</td><td></td></tr><tr><td>show</td><td>omlet</td><td>new, replace, embed, other</td></tr><tr><td>size</td><td>data</td><td></td></tr><tr><td>sort</td><td>argument</td><td></td></tr><tr><td>style</td><td>*</td><td></td></tr><tr><td>system</td><td>type</td><td></td></tr><tr><td>theory</td><td>+</td><td></td></tr><tr><td>to</td><td>theory-inclusion, axiom-inclusion</td><td></td></tr><tr><td>total</td><td>selector</td><td>no, yes</td></tr><tr><td>type</td><td>adt</td><td>free, generated, loose</td></tr><tr><td>type</td><td>assertion</td><td>theorem, lemma, corollary, conjecture, false-conjecture, obligation, postulate, formula, assumption, proposition</td></tr><tr><td>type</td><td>definition</td><td>implicit, inductive, obj, recursive, simple</td></tr><tr><td>type</td><td>derive</td><td>conclusion, gap</td></tr><tr><td>type</td><td>example</td><td>against, for</td></tr><tr><td>type</td><td>ignore</td><td></td></tr><tr><td>type</td><td>imports</td><td>global, local</td></tr><tr><td>type</td><td>morphism</td><td></td></tr><tr><td>type</td><td>omgroup, omdoc</td><td>enumeration, sequence, itemize</td></tr><tr><td>type</td><td>omtext</td><td>abstract, antithesis, comment, conclusion, elaboration, evidence, introduction, motivation, thesis</td></tr><tr><td>type</td><td>phrase</td><td></td></tr><tr><td>type</td><td>ref</td><td>include, cite</td></tr><tr><td>uniqueness</td><td>definition</td><td>URI reference</td></tr><tr><td>value</td><td>param</td><td></td></tr></table>	separator	presentation, use		show	omlet	new, replace, embed, other	size	data		sort	argument		style	*		system	type		theory	+		to	theory-inclusion, axiom-inclusion		total	selector	no, yes	type	adt	free, generated, loose	type	assertion	theorem, lemma, corollary, conjecture, false-conjecture, obligation, postulate, formula, assumption, proposition	type	definition	implicit, inductive, obj, recursive, simple	type	derive	conclusion, gap	type	example	against, for	type	ignore		type	imports	global, local	type	morphism		type	omgroup, omdoc	enumeration, sequence, itemize	type	omtext	abstract, antithesis, comment, conclusion, elaboration, evidence, introduction, motivation, thesis	type	phrase		type	ref	include, cite	uniqueness	definition	URI reference	value	param		<table><tr><td>separator</td><td>presentation, use</td><td></td></tr><tr><td>show</td><td>omlet</td><td>new, replace, embed, other</td></tr><tr><td>size</td><td>data</td><td></td></tr><tr><td>sort</td><td>argument</td><td></td></tr><tr><td>style</td><td>*</td><td></td></tr><tr><td>system</td><td>type</td><td></td></tr><tr><td>theory</td><td>+</td><td></td></tr><tr><td>to</td><td>theory-inclusion, axiom-inclusion</td><td></td></tr><tr><td>total</td><td>selector</td><td>no, yes</td></tr><tr><td>type</td><td>adt</td><td>free, generated, loose</td></tr><tr><td>type</td><td>assertion</td><td>theorem, lemma, corollary, conjecture, false-conjecture, obligation, postulate, formula, assumption, proposition</td></tr><tr><td>type</td><td>definition</td><td>implicit, inductive, obj, recursive, simple</td></tr><tr><td>type</td><td>derive</td><td>conclusion, gap</td></tr><tr><td>type</td><td>example</td><td>against, for</td></tr><tr><td>type</td><td>ignore</td><td></td></tr><tr><td>type</td><td>imports</td><td>global, local</td></tr><tr><td>type</td><td>morphism</td><td></td></tr><tr><td>type</td><td>omgroup, omdoc</td><td>enumeration, sequence, itemize</td></tr><tr><td>type</td><td>omtext</td><td>abstract, antithesis, comment, conclusion, elaboration, evidence, introduction, motivation, thesis</td></tr><tr><td>type</td><td>phrase</td><td></td></tr><tr><td>type</td><td>ref</td><td>include, cite</td></tr><tr><td>uniqueness</td><td>definition</td><td>URI reference</td></tr><tr><td>value</td><td>param</td><td></td></tr></table>	separator	presentation, use		show	omlet	new, replace, embed, other	size	data		sort	argument		style	*		system	type		theory	+		to	theory-inclusion, axiom-inclusion		total	selector	no, yes	type	adt	free, generated, loose	type	assertion	theorem, lemma, corollary, conjecture, false-conjecture, obligation, postulate, formula, assumption, proposition	type	definition	implicit, inductive, obj, recursive, simple	type	derive	conclusion, gap	type	example	against, for	type	ignore		type	imports	global, local	type	morphism		type	omgroup, omdoc	enumeration, sequence, itemize	type	omtext	abstract, antithesis, comment, conclusion, elaboration, evidence, introduction, motivation, thesis	type	phrase		type	ref	include, cite	uniqueness	definition	URI reference	value	param	
separator	presentation, use																																																																																																																																														
show	omlet	new, replace, embed, other																																																																																																																																													
size	data																																																																																																																																														
sort	argument																																																																																																																																														
style	*																																																																																																																																														
system	type																																																																																																																																														
theory	+																																																																																																																																														
to	theory-inclusion, axiom-inclusion																																																																																																																																														
total	selector	no, yes																																																																																																																																													
type	adt	free, generated, loose																																																																																																																																													
type	assertion	theorem, lemma, corollary, conjecture, false-conjecture, obligation, postulate, formula, assumption, proposition																																																																																																																																													
type	definition	implicit, inductive, obj, recursive, simple																																																																																																																																													
type	derive	conclusion, gap																																																																																																																																													
type	example	against, for																																																																																																																																													
type	ignore																																																																																																																																														
type	imports	global, local																																																																																																																																													
type	morphism																																																																																																																																														
type	omgroup, omdoc	enumeration, sequence, itemize																																																																																																																																													
type	omtext	abstract, antithesis, comment, conclusion, elaboration, evidence, introduction, motivation, thesis																																																																																																																																													
type	phrase																																																																																																																																														
type	ref	include, cite																																																																																																																																													
uniqueness	definition	URI reference																																																																																																																																													
value	param																																																																																																																																														
separator	presentation, use																																																																																																																																														
show	omlet	new, replace, embed, other																																																																																																																																													
size	data																																																																																																																																														
sort	argument																																																																																																																																														
style	*																																																																																																																																														
system	type																																																																																																																																														
theory	+																																																																																																																																														
to	theory-inclusion, axiom-inclusion																																																																																																																																														
total	selector	no, yes																																																																																																																																													
type	adt	free, generated, loose																																																																																																																																													
type	assertion	theorem, lemma, corollary, conjecture, false-conjecture, obligation, postulate, formula, assumption, proposition																																																																																																																																													
type	definition	implicit, inductive, obj, recursive, simple																																																																																																																																													
type	derive	conclusion, gap																																																																																																																																													
type	example	against, for																																																																																																																																													
type	ignore																																																																																																																																														
type	imports	global, local																																																																																																																																													
type	morphism																																																																																																																																														
type	omgroup, omdoc	enumeration, sequence, itemize																																																																																																																																													
type	omtext	abstract, antithesis, comment, conclusion, elaboration, evidence, introduction, motivation, thesis																																																																																																																																													
type	phrase																																																																																																																																														
type	ref	include, cite																																																																																																																																													
uniqueness	definition	URI reference																																																																																																																																													
value	param																																																																																																																																														

54

Identifier	Page	Conf.	LaTeX source	Rendered	Image																																																																																																																																																						
kohlhase-omdoc_TAB_103	343	0.993	<pre>\begin{tabular}[t]{ l l } \hline & \\ \multicolumn{2}{ l }{specifies the value of the parameter} \\ \hline \valuetype & param \\ \hline & specifies the type of the value of the parameter \\ \hline & & specifies the type of the value of the parameter \\ \hline & & verbalizes & on RT elements & URI references \\ \hline & & contains a whitespace-separated list of pointers to OMDoc elements that are verbalized \\ \hline verdict & answer \\ \hline & specifies the truth or falsity of the answer. This can be used e.g. by a grading application. \\ \hline version & omdoc & 1.2 \\ \hline & specifies the version of the document, so that the right DTD is used \\ \hline version & cc:license \\ \hline & specifies the version of the Creative Commons license that applies, if not present, the newest one is assumed \\ \hline via & inclusion \\ \hline & points to a theory-inclusion that is required for an actualization \\ \hline who & dc:date \\ \hline & specifies who acted on the document fragment \\ \hline xml:lang & CMP, dc:* & ISO 639 code \\ \hline & the language the text in the element is expressed in. \\ \hline xml:lang & use, xslt, style & whitespace-separated list of ISO 639 codes \\ \hline & specifies for which language the notation is meant \\ \hline xlink:* & om:OMR, m:* & URI reference \\ \hline & specify the link behavior on the elements \\ \hline xref & ref, method, premise & URI reference \\ \hline & Identifies the resource in question \\ \hline xref & presentation, omstyle & URI reference \\ \hline & The element, this URI points to should be in the place of the object containing this attribute. \\ \hline \end{tabular}</pre>	<table><tr><td></td><td>specifies the value of the parameter</td><td></td></tr><tr><td>valuetype</td><td>param</td><td></td></tr><tr><td></td><td>specifies the type of the value of the parameter</td><td></td></tr><tr><td>verbalizes</td><td>on RT elements</td><td>URI references</td></tr><tr><td></td><td>contains a whitespace-separated list of pointers to OMDoc elements that are verbalized</td><td></td></tr><tr><td>verdict</td><td>answer</td><td></td></tr><tr><td></td><td>specifies the truth or falsity of the answer. This can be used e.g. by a grading application.</td><td></td></tr><tr><td>version</td><td>omdoc</td><td>1.2</td></tr><tr><td></td><td>specifies the version of the document, so that the right DTD is used</td><td></td></tr><tr><td>version</td><td>cc:license</td><td></td></tr><tr><td></td><td>specifies the version of the Creative Commons license that applies, if not present, the newest one is assumed</td><td></td></tr><tr><td>via</td><td>inclusion</td><td></td></tr><tr><td></td><td>points to a theory-inclusion that is required for an actualization</td><td></td></tr><tr><td>who</td><td>dc:date</td><td></td></tr><tr><td></td><td>specifies who acted on the document fragment</td><td></td></tr><tr><td>xml:lang</td><td>CMP, dc:*</td><td>ISO 639 code</td></tr><tr><td></td><td>the language the text in the element is expressed in.</td><td></td></tr><tr><td>xml:lang</td><td>use, xslt, style</td><td>whitespace-separated list of ISO 639 codes</td></tr><tr><td></td><td>specifies for which language the notation is meant</td><td></td></tr><tr><td>xlink:*</td><td>om:OMR, m:*</td><td>URI reference</td></tr><tr><td></td><td>specify the link behavior on the elements</td><td></td></tr><tr><td>xref</td><td>ref, method, premise</td><td>URI reference</td></tr><tr><td></td><td>Identifies the resource in question</td><td></td></tr><tr><td>xref</td><td>presentation, omstyle</td><td>URI reference</td></tr><tr><td></td><td>The element, this URI points to should be in the place of the object containing this attribute.</td><td></td></tr></table>		specifies the value of the parameter		valuetype	param			specifies the type of the value of the parameter		verbalizes	on RT elements	URI references		contains a whitespace-separated list of pointers to OMDoc elements that are verbalized		verdict	answer			specifies the truth or falsity of the answer. This can be used e.g. by a grading application.		version	omdoc	1.2		specifies the version of the document, so that the right DTD is used		version	cc:license			specifies the version of the Creative Commons license that applies, if not present, the newest one is assumed		via	inclusion			points to a theory-inclusion that is required for an actualization		who	dc:date			specifies who acted on the document fragment		xml:lang	CMP, dc:*	ISO 639 code		the language the text in the element is expressed in.		xml:lang	use, xslt, style	whitespace-separated list of ISO 639 codes		specifies for which language the notation is meant		xlink:*	om:OMR, m:*	URI reference		specify the link behavior on the elements		xref	ref, method, premise	URI reference		Identifies the resource in question		xref	presentation, omstyle	URI reference		The element, this URI points to should be in the place of the object containing this attribute.		<table><tr><td></td><td>specifies the value of the parameter</td><td></td></tr><tr><td>valuetype</td><td>param</td><td></td></tr><tr><td></td><td>specifies the type of the value of the parameter</td><td></td></tr><tr><td>verbalizes</td><td>on RT elements</td><td>URI references</td></tr><tr><td></td><td>contains a whitespace-separated list of pointers to OMDoc elements that are verbalized</td><td></td></tr><tr><td>verdict</td><td>answer</td><td></td></tr><tr><td></td><td>specifies the truth or falsity of the answer. This can be used e.g. by a grading application.</td><td></td></tr><tr><td>version</td><td>omdoc</td><td>1.2</td></tr><tr><td></td><td>specifies the version of the document, so that the right DTD is used</td><td></td></tr><tr><td>version</td><td>cc:license</td><td></td></tr><tr><td></td><td>specifies the version of the Creative Commons license that applies, if not present, the newest one is assumed</td><td></td></tr><tr><td>via</td><td>inclusion</td><td></td></tr><tr><td></td><td>points to a theory-inclusion that is required for an actualization</td><td></td></tr><tr><td>who</td><td>dc:date</td><td></td></tr><tr><td></td><td>specifies who acted on the document fragment</td><td></td></tr><tr><td>xml:lang</td><td>CMP, dc:*</td><td>ISO 639 code</td></tr><tr><td></td><td>the language the text in the element is expressed in.</td><td></td></tr><tr><td>xml:lang</td><td>use, xslt, style</td><td>whitespace-separated list of ISO 639 codes</td></tr><tr><td></td><td>specifies for which language the notation is meant</td><td></td></tr><tr><td>xlink:*</td><td>om:OMR, m:*</td><td>URI reference</td></tr><tr><td></td><td>specify the link behavior on the elements</td><td></td></tr><tr><td>xref</td><td>ref, method, premise</td><td>URI reference</td></tr><tr><td></td><td>Identifies the resource in question</td><td></td></tr><tr><td>xref</td><td>presentation, omstyle</td><td>URI reference</td></tr><tr><td></td><td>The element, this URI points to should be in the place of the object containing this attribute.</td><td></td></tr></table>		specifies the value of the parameter		valuetype	param			specifies the type of the value of the parameter		verbalizes	on RT elements	URI references		contains a whitespace-separated list of pointers to OMDoc elements that are verbalized		verdict	answer			specifies the truth or falsity of the answer. This can be used e.g. by a grading application.		version	omdoc	1.2		specifies the version of the document, so that the right DTD is used		version	cc:license			specifies the version of the Creative Commons license that applies, if not present, the newest one is assumed		via	inclusion			points to a theory-inclusion that is required for an actualization		who	dc:date			specifies who acted on the document fragment		xml:lang	CMP, dc:*	ISO 639 code		the language the text in the element is expressed in.		xml:lang	use, xslt, style	whitespace-separated list of ISO 639 codes		specifies for which language the notation is meant		xlink:*	om:OMR, m:*	URI reference		specify the link behavior on the elements		xref	ref, method, premise	URI reference		Identifies the resource in question		xref	presentation, omstyle	URI reference		The element, this URI points to should be in the place of the object containing this attribute.	
	specifies the value of the parameter																																																																																																																																																										
valuetype	param																																																																																																																																																										
	specifies the type of the value of the parameter																																																																																																																																																										
verbalizes	on RT elements	URI references																																																																																																																																																									
	contains a whitespace-separated list of pointers to OMDoc elements that are verbalized																																																																																																																																																										
verdict	answer																																																																																																																																																										
	specifies the truth or falsity of the answer. This can be used e.g. by a grading application.																																																																																																																																																										
version	omdoc	1.2																																																																																																																																																									
	specifies the version of the document, so that the right DTD is used																																																																																																																																																										
version	cc:license																																																																																																																																																										
	specifies the version of the Creative Commons license that applies, if not present, the newest one is assumed																																																																																																																																																										
via	inclusion																																																																																																																																																										
	points to a theory-inclusion that is required for an actualization																																																																																																																																																										
who	dc:date																																																																																																																																																										
	specifies who acted on the document fragment																																																																																																																																																										
xml:lang	CMP, dc:*	ISO 639 code																																																																																																																																																									
	the language the text in the element is expressed in.																																																																																																																																																										
xml:lang	use, xslt, style	whitespace-separated list of ISO 639 codes																																																																																																																																																									
	specifies for which language the notation is meant																																																																																																																																																										
xlink:*	om:OMR, m:*	URI reference																																																																																																																																																									
	specify the link behavior on the elements																																																																																																																																																										
xref	ref, method, premise	URI reference																																																																																																																																																									
	Identifies the resource in question																																																																																																																																																										
xref	presentation, omstyle	URI reference																																																																																																																																																									
	The element, this URI points to should be in the place of the object containing this attribute.																																																																																																																																																										
	specifies the value of the parameter																																																																																																																																																										
valuetype	param																																																																																																																																																										
	specifies the type of the value of the parameter																																																																																																																																																										
verbalizes	on RT elements	URI references																																																																																																																																																									
	contains a whitespace-separated list of pointers to OMDoc elements that are verbalized																																																																																																																																																										
verdict	answer																																																																																																																																																										
	specifies the truth or falsity of the answer. This can be used e.g. by a grading application.																																																																																																																																																										
version	omdoc	1.2																																																																																																																																																									
	specifies the version of the document, so that the right DTD is used																																																																																																																																																										
version	cc:license																																																																																																																																																										
	specifies the version of the Creative Commons license that applies, if not present, the newest one is assumed																																																																																																																																																										
via	inclusion																																																																																																																																																										
	points to a theory-inclusion that is required for an actualization																																																																																																																																																										
who	dc:date																																																																																																																																																										
	specifies who acted on the document fragment																																																																																																																																																										
xml:lang	CMP, dc:*	ISO 639 code																																																																																																																																																									
	the language the text in the element is expressed in.																																																																																																																																																										
xml:lang	use, xslt, style	whitespace-separated list of ISO 639 codes																																																																																																																																																									
	specifies for which language the notation is meant																																																																																																																																																										
xlink:*	om:OMR, m:*	URI reference																																																																																																																																																									
	specify the link behavior on the elements																																																																																																																																																										
xref	ref, method, premise	URI reference																																																																																																																																																									
	Identifies the resource in question																																																																																																																																																										
xref	presentation, omstyle	URI reference																																																																																																																																																									
	The element, this URI points to should be in the place of the object containing this attribute.																																																																																																																																																										