

ETL Conventions for use with PEDSnet CDM v3.0 OMOP V5.2

The PEDSnet Common Data Model is an evolving specification, based in structure on the OMOP Common Data Model, but expanded to accommodate requirements of both the PCORnet Common Data Model and the primary research cohorts established in PEDSnet.

Version 3.0 of the PEDSnet CDM reflects the ETL processes developed after several iterations of network development. As such, it proposes to align with version 4.1 of the PCORnet CDM.

This document provides the ETL processing assumptions and conventions developed by the PEDSnet data partners that should be used by a data partner for ensuring common ETL business rules. This document will be modified as new situations are identified, incorrect business rules are identified and replaced, as new analytic use cases impose new/different ETL rules, and as the PEDSnet CDM continues to evolve.

Comments on this specification and ETL rules are welcome. Please send email to pedsnetdcc@email.chop.edu, or contact the PEDSnet project management office (details available via <http://www.pedsnet.info>).

PEDSnet Data Standards and Interoperability Policies:

1. The PEDSnet data network will store data using structures compatible with the PEDSnet Common Data Model (PCDM).
2. The PEDSnet CDM v3.0 is based on the Observational Medical Outcomes Partnership (OMOP) data model, version 5.2.
3. A subset of data elements in the PCDM will be identified as principal data elements (PDEs). The PDEs will be used for population-level queries. Data elements which are NOT PDEs will be marked as Optional (ETL at site discretion) or Non-PDE (ETL required, but data need not be transmitted to DCC), and will not be used in queries without prior approval of site.
4. It is anticipated that PEDSnet institutions will make a good faith attempt to obtain as many of the data elements not marked as Optional as possible.
5. The data elements classified as PDEs and those included in the PCDM will be approved by the PEDSnet Executive Committee (comprised of each PEDSnet institution's site principal investigator).
6. Concept IDs are taken from OMOP 5 vocabularies for PEDSnet CDM v3.0, using the complete (restricted) version that includes licensed terminologies such as CPT and others.
7. PCORnet CDM v4.1 requires data elements that are not currently considered "standard concepts". Vocabulary version 5 has a new vocabulary (*vocabularyid=PCORNet*) that was added by OMOP to capture all of the PCORnet concepts that are not in the standard terminologies. We use *conceptids* from *vocabularyid=PCORNet* where there are no existing standard concepts. We highlight where we are pulling *conceptids* from *vocabularyid=PCORNet* in the tables. While terms from *vocabularyid=PCORNet* violates the OMOP rule to use only *conceptids* from standard vocabularies (*vocabularyid=PCORNet* is a non-standard vocabulary), this convention enables a clean extraction from PEDSnet CDM to PCORnet CDM.
8. Some source fields may be considered sensitive by data sites. Potential examples include *patientsourcevalue*, *providersourcevalue*, *caresitesourcevalue*. Many of these fields are used to generate an ID field, such as *PERSON.patientsourcevalue* *PERSON.personid*, that is used as a primary key in *PERSON* and a foreign key in many other tables. Sites are free to obfuscate or not provide source values that are used to create ID variables. Sites must maintain a mapping from the ID variable back to the original site-specific value for local re-identification tasks.
 1. Source fields that contain clinical data, such as source condition occurrence, should be included
 2. The PEDSnet DCC will never release source values to external data partners.
 3. Source value obfuscation techniques may include replacing the real source value with a random number, an encrypted derivative value/string, or some other site-specific algorithm.
9. The PCORnet CDM has specific definitions for null values (as seen below). For the PEDSnet CDM, please use the following logic on which concept value to use for `source_concept_id` fields where there are null values in the source `*_source_value`.

Null Name	Definition of each field
NULL	A data field is not present in the source system. Note. This is not a 'NULL' string but the NULL value.
'NI' = No Information	A data field is present in the source system, but the source value is null or blank
'UN' = Unknown	A data field is present in the source system, but the source value explicitly denotes an unknown value
'OT' = Other	A data field is present in the source system, but the source value cannot be mapped to the CDM

Guidelines for populating `'*_concept_id'`, `'*_source_concept_id'` and `'*_source_value'` for flavors of null:

Data Extraction Guide

Please use the table headings as a guide in extracting and submitting data. These specifications are indicative of DCC and Network Requirements. All fields must be submitted to the DCC even if you are not submitting data in a field. Here are examples of how the specification should be interpreted:

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
Field Name	<ul style="list-style-type: none"> Yes 	<ul style="list-style-type: none"> Yes 	Data Type	Description	PEDSnet Conventions

- The above example indicates the data in this field is required by both the DCC and Network. It absolutely must be provided in the data submission.

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
Field Name	<ul style="list-style-type: none"> No 	<ul style="list-style-type: none"> Provide When Available 	Data Type	Description	PEDSnet Conventions

- The above example indicates the data in this field is required by Network if it is populated or available at your site. If it is available it must be provided in the data submission.

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
Field Name	<ul style="list-style-type: none"> No 	<ul style="list-style-type: none"> Site Preference 	Data Type	Description	PEDSnet Conventions

- The above example indicates the data in this field is not required by the DCC or Network. A site may choose to send this information if they desire to do so.

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
Field Name	<ul style="list-style-type: none"> No 	<ul style="list-style-type: none"> Optional 	Data Type	Description	PEDSnet Conventions

- The above example indicates the data in this field is truly optional for submission. A site may choose to send this information if they desire to do so.

1.1 PERSON

The person domain contains records that uniquely identify each patient in the source data who is time at-risk to have clinical observations recorded within the source systems. Each person record has associated demographic attributes, which are assumed to be constant for the patient throughout the course of their periods of observation. All other patient-related data domains have a foreign-key reference to the person domain.

PEDSnet uses a specific definition of an active PEDSnet patient. Only patients who meet the PEDSnet definition of an active patient should be included in this table. The criteria for identifying an active patient are:

- Has a unique identifier AND
- At least 1 "in person" clinical encounter on or after January 1, 2009 AND
- At least 1 coded diagnoses recorded on or after January 1, 2009 AND
- Is not a test patient or a research-only patient

The definition of an "in person" clinical encounter remains heuristic -any encounter type that involves a meaningful ****physical**** interaction with a clinician that involved clinical content. An encounter for a telephone encounter or a lab blood draw does not meet this definition.

For reference `Visit concept ids` that correspond to an "in person" clinical encounter are:

Visit Type	Visit concept id
Inpatient Hospital Stay	9201
Ambulatory Visit	9202
Emergency Department	9203
Long Term Care Visit	42898160
Non-Acute Institutional Stay	44814710
Emergency Department Admit to Inpatient Hospital Stay (If sites are unable to split the encounter)	2000000048
Observation Stay	2000000088

NOTE: While the 1/1/2009 date and "in person" clinical encounter restrictions apply to defining an active PEDSnet patient, once a patient has met this criteria, PEDSnet will extract *ALL* available clinical encounters/clinical data of any type across all available dates. That is, 1/1/2009 and 1 'in person' clinical encounter applies only to defining the active patient cohort. It does NOT apply to data extraction on active patients.

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
person_id	Yes	Yes	Integer	A unique identifier for each person; this is created by each contributing site.	<p>This is not a value found in the EHR.</p> <p><i>PERSONID must be unique for all patients within a single data set.</i></p> <p><i>SITE RESPONSIBILITY: This field must remain a stable identifier across submissions to the DCC.</i></p> <p><i>A mapping from the personid to a real patient ID or MRN from the source EHR must be kept at the local site. This mapping is not shared with the data coordinating center. It is used only by the site for re-identification for study recruitment or for data quality review.</i></p>
genderconceptid	Yes	Yes	Integer	A foreign key that refers to a standard concept identifier in the Vocabulary for the gender of the person.	<p>Please include valid concept ids (consistent with OMOP CDMv5.1). Predefined value set (valid <i>conceptids</i> found in <i>CONCEPT</i> table <i>select * from concept where ((domainid='Gender' and conceptclassid='Gender')or (domainid='Observation' and vocabularyid='PCORNet' and conceptclassid in ('Gender','Undefined')))) and conceptcode not in ('Sex-F','Sex-M') and invalidreason is null:</i></p> <ul style="list-style-type: none"> • Ambiguous: <i>conceptid = 44814664</i> • Female: <i>conceptid = 8532</i> • Male: <i>conceptid = 8507</i> • No Information: <i>conceptid = 44814650</i> (Vocabularyid='PCORNet') • Unknown: <i>conceptid = 44814653</i> • Other: <i>concept_id = 44814649</i>
gendersourceconcept_id	Yes	Yes	Integer	A foreign key to the gender concept that refers to the code used in the source.	If there is not a mapping for the source code in the standard vocabulary, use concept_id = 0
yearofbirth	Yes	Yes	Integer	The year of birth of the person.	For data sources with date of birth, the year is extracted. For data sources where the year of birth is not available, the approximate year of birth is derived based on any age group categorization available. Please keep all accurate/real dates (No date shifting)
monthofbirth	No	Provide When Available	Integer	The month of birth of the person.	For data sources that provide the precise date of birth, the month is extracted and stored in this field. Please keep all accurate/real dates (No date shifting)
dayofbirth	No	Provide When Available	Integer	The day of the month of birth of the person.	For data sources that provide the precise date of birth, the day is extracted and stored in this field. Please keep all accurate/real dates (No date shifting)
birth_datetime	No	Provide When Available	Datetime	The birth date and time	Do not include timezone. Please keep all accurate/real dates (No date shifting). If there is no time associated with the date assert midnight.
					<p>Details of categorical definitions:</p> <ul style="list-style-type: none"> • -American Indian or Alaska Native: A person having origins in any of the original peoples of North and South America (including Central America), and who maintains tribal affiliation or community attachment. • -Asian: A person having origins in any of the original peoples of the Far East, Southeast Asia, or the Indian subcontinent including, for example, Cambodia, China, India, Japan, Korea, Malaysia, Pakistan, the Philippine Islands, Thailand, and Vietnam. • -Black or African American: A person having origins in any of the black racial groups of Africa. • -Native Hawaiian or Other Pacific Islander: A person having origins in any of the original peoples of Hawaii, Guam, Samoa, or other Pacific Islands.

raceconceptid	Yes	Yes	Integer	A foreign key that refers to a standard concept identifier in the Vocabulary for the race of the person.	<p>islands.</p> <ul style="list-style-type: none"> • -White: A person having origins in any of the original peoples of Europe, the Middle East, or North Africa. <p>For patients with multiple races (i.e. biracial), race is considered a single concept, meaning there is only one race slot. If there are multiple races in the source system, concatenate all races into one racesourcevalue (see below) and use conceptid code as 'Multiple Race.'</p> <p><i>Predefined values (valid conceptids found in CONCEPT table where ((domainid='Race' and vocabularyid = 'Race') or (vocabularyid='PCORNet' and conceptclassid='Undefined') or conceptid in (44814659,44814660)) and invalidreason is null:</i></p> <ul style="list-style-type: none"> • <i>American Indian/Alaska Native: conceptid = 8657</i> • <i>Asian: conceptid = 8515</i> • <i>Black or African American: conceptid = 8516</i> • <i>Native Hawaiian or Other Pacific Islander: conceptid = 8557</i> • <i>White: conceptid = 8527</i> • <i>Multiple Race: conceptid = 44814659 (vocabularyid='PCORNet')</i> • <i>Refuse to answer: conceptid = 44814660 (vocabularyid='PCORNet')</i> • <i>No Information: conceptid = 44814650 vocabularyid='PCORNet')</i> • <i>Unknown: conceptid = 44814653</i> • <i>Other: conceptid = 44814649</i>
racesourceconcept_id	Yes	Yes	Integer	A foreign key to the race concept that refers to the code used in the source.	If there is not a mapping for the source code in the standard vocabulary, use concept_id = 0
ethnicityconceptid	Yes	Yes	Integer	A foreign key that refers to the standard concept identifier in the Vocabulary for the ethnicity of the person.	<p>For PEDSnet, a person with Hispanic ethnicity is defined as "A person of Cuban, Mexican, Puerto Rican, South or Central American, or other Spanish culture or origin, regardless of race."</p> <p>Please include valid concept ids (consistent with OMOP CDMv5). Predefined value set (valid conceptids found in CONCEPT table where vocabularyid ='Ethnicity' or (vocabularyid=PCORNet and conceptclassid='Undefined') where noted):</p> <ul style="list-style-type: none"> • <i>Hispanic: conceptid = 38003563</i> • <i>Not Hispanic: conceptid = 38003564</i> • <i>No Information: conceptid = 44814650 (vocabularyid='PCORNet')</i> • <i>Unknown: conceptid = 44814653 (vocabularyid='PCORNet')</i> • <i>Other: conceptid = 44814649 (vocabulary_id='PCORNet')</i>
ethnicitysourceconcept_id	Yes	Yes	Integer	A foreign key to the ethnicity concept that refers to the code used in the source.	If there is not a mapping for the source code in the standard vocabulary, use concept_id = 0
location_id	No	Provide When Available	Integer	A foreign key to the place of residency (ZIP code) for the person in the location table, where the detailed address information is stored.	
provider_id	No	Provide When Available	Integer	Foreign key to the primary care provider the person is seeing in the provider table.	For PEDSnet CDM v3.0.0: Sites will use site-specific logic to determine the best primary care provider and document how that decision was made (e.g., billing provider).

caresiteid	Yes	Yes	Integer	A foreign key to the site of primary care in the care_site table, where the details of the care site are stored	For patients who receive care at multiple care sites, use site-specific logic to select a care site that best represents where the patient obtains the majority of their recent care. If a specific site within the institution cannot be identified, use a caresiteid representing the institution as a whole.
pngestationalage	No	Provide When Available	Integer	The post-menstrual age in weeks of the person at birth, if known	Use granularity of age in weeks as is recorded in local EHR.
personsourcevalue	No	Provide When Available	Varchar	An encrypted key derived from the person identifier in the source data.	Insert a unique pseudo-identifier (random number, encrypted identifier) into the field. Do not insert the actual MRN or PATID from your site. A mapping from the pseudo-identifier for personsource_value in this field to a real patient ID or MRN from the source EHR must be kept at the local site. This mapping is not shared with the data coordinating center. It is used only by the site for re-identification for study recruitment or for data quality review.
gendersourcevalue	Yes	Yes	Varchar	The source code for the gender of the person as it appears in the source data.	The person's gender is mapped to a standard gender concept in the Vocabulary; the original value is stored here for reference. See genderconceptid
racessourcevalue	Yes	Yes	Varchar	The source code for the race of the person as it appears in the source data.	The person race is mapped to a standard race concept in the Vocabulary and the original value is stored here for reference. For patients with multiple races (i.e. biracial), race is considered a single concept, meaning there is only one race slot. If there are multiple races in the source system, concatenate all races into one source value, and use the concept_id for Multiple Race.
ethnicitysourcevalue	Yes	Yes	Varchar	The source code for the ethnicity of the person as it appears in the source data.	The person ethnicity is mapped to a standard ethnicity concept in the Vocabulary and the original code is, stored here for reference.
languageconceptid	Yes	Yes	Integer	A foreign key that refers to the standard concept identifier in the Vocabulary for the language of the person.	For PEDSNet, please map your source codes to acceptable language values in appendix 2 If there is not a mapping for the source code in the network language mapping, use concept_id = 44814649 (Other PCORNet Vocabulary)
languagesourceconcept_id	Yes	Yes	Integer	A foreign key to the language concept that refers to the code used in the source.	If there is not a mapping for the source code in the standard vocabulary, use concept_id = 0
languagesourcevalue	Yes	Yes	Varchar	The source code for the language of the person as it appears in the source data	The person language is mapped to a standard language concept in the Vocabulary and the original code is stored here for reference.

If a field marked as "Provide when available" for the network requirement is not available at your site, please relay this information to the DCC

1.2 DEATH

The death domain contains the clinical event for how and when a person dies. Living patients should not contain any information in the death table.

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
deathcauseid	Yes	Yes	Integer	A unique identifier for each death cause occurrence	This is not a value found in the EHR. Sites may choose to use a sequential value for this field

person_id	Yes	Yes	Integer	A foreign key identifier to the deceased person. The demographic details of that person are stored in the person table.	See PERSON.person_id (primary key)
death_date	Yes	Yes	Date	The date the person was deceased.	If the precise date including day or month is not known or not allowed, December is used as the default month, and the last day of the month the default day. If no date available, use date recorded as deceased. When the date of death is not present in the source data, use the date the source record was created.
death_datetime	Yes	Yes	Datetime	The date the person was deceased.	This field is custom to PEDSnet If the precise date including day or month is not known or not allowed, December is used as the default month, and the last day of the month the default day. If no date available, use date recorded as deceased. When the date of death is not present in the source data, use the date the source record was created. If there is no time associated with the date assert '23:59:59'.
deathtypeconcept_id	Yes	Yes	Integer	A foreign key referring to the predefined concept identifier in the Vocabulary reflecting how the death was represented in the source data.	Please include valid concept ids (consistent with OMOP CDMv5). Predefined value set (valid conceptids found in <i>CONCEPT</i> table where domainid ='Death Type') select * from concept where conceptclassid ='Death Type' yields 9 valid conceptids. If none are correct, use conceptid = 0 Note: Most current ETLs are extracting data from EHR. The common conceptid to insert here is <ul style="list-style-type: none"> 38003569 ("EHR record patient status "Deceased") . Please assert <ul style="list-style-type: none"> No information: conceptid = 44814650 where there is no information in the source Note: These terms only describe the source from which the death was reported. It does not describe our certainty/source of the date of death, which may have been created by one of the heuristics described in death_date.
causeconceptid	No	Provide When Available	Integer	A foreign referring to a standard concept identifier in the Vocabulary for conditions.	
causesourcevalue	No	Provide When Available	Varchar	The source code for the cause of death as it appears in the source. This code is mapped to a standard concept in the Vocabulary and the original code is stored here for reference.	
causesourceconcept_id	No	Provide When Available	Integer	A foreign key to the vocabulary concept that refers to the code used in the source.	This links to the concept id of the vocabulary of the cause of death concept id as stored in the source. For example, if the cause of death is "Acute myeloid leukemia, without mention of having achieved remission" which has an icd9 code of 205.00 the cause source concept id is 44826430 which is the icd9 code concept that corresponds to the diagnosis 205.00. If there is not a mapping for the source code in the standard vocabulary, use concept_id = 0

deathimputeconcept_id	Yes	Yes	Varchar	<p>A foreign key referring to a standard concept identifier in the vocabulary for death imputation.</p>	<p>p>Please include valid concept ids (consistent with OMOP CDMv5). Predefined value set (valid conceptids found in <i>CONCEPT</i> table where conceptclassid='Death Imput Type')</p> <p><i>select * from concept where (conceptclassid='Death Imput Type' or (vocabularyid='PCORNet' and conceptclassid='Undefined')) and invalidreason is null yields 8 valid conceptids.</i> If none are correct, use conceptid = 0</p> <ul style="list-style-type: none"> • Both month and day imputed: 2000000034 • Day imputed: 2000000035 • Month imputed: 2000000036 • Full Date imputed: 2000000038 • Not imputed:2000000037 • No Information: conceptid = 44814650 (Vocabularyid='PCORNet') • Unknown: conceptid = 44814653 • Other: concept_id = 44814649
-----------------------	-----	-----	---------	---	---

If a field marked as "Provide when available" for the network requirement is not available at your site, please relay this information to the DCC

1.2.1 Additional Notes

- Each Person may have more than one record of death in the source data. It is OK to insert multiple death records for an individual.
- If the Death Date cannot be precisely determined from the data, the best approximation should be used.

1.3 LOCATION

The Location domain represents a generic way to capture physical location or address information. Locations are used to define the addresses for Persons and Care Sites. The most important field is ZIP for location-based queries.

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
location_id	Yes	Yes	Integer	A unique identifier for each geographic location.	This is not a value found in the EHR. Sites may choose to use a sequential value for this field
state	No	Provide When Available	Varchar	The state field as it appears in the source data.	
zip	No	Provide When Available	Varchar	The zip code. For US addresses, valid zip codes can be 3, 5 or 9 digits long, depending on the source data.	While optional, this is the most important field in this table to support location-based queries.
locationsourcevalue	No	Provide When Available	Varchar	The verbatim information that is used to uniquely identify the location as it appears in the source data.	<p>If location source values are deemed sensitive by your organization, insert a pseudo-identifier (random number, encrypted identifier) into the field. Sites electing to obfuscate locationsourcevalues will keep the mapping between the value in this field and the original clear text location source value. This value is only used for site-level re-identification for study recruitment and for data quality review.</p> <p>Sites may consider using the locationid field value in this table as the pseudo-identifier as long as a local mapping from locationid to the real site identifier is maintained.</p>
address_1	No	NO	Varchar		Do not transmit to DCC
address_2	No	NO	Varchar		Do not transmit to DCC
city	No	NO	Varchar		Do not transmit to DCC
county	No	NO	Varchar		Do not transmit to DCC

If a field marked as "Provide when available" for the network requirement is not available at your site, please relay this information to the DCC

1.3.1 Additional Notes

- Each address or Location is unique and is present only once in the table
- Locations in this table are restricted to locations that are applicable to persons and care_sites in the Pedsnet cohort at each site. When external data is implemented, valid(data containing) locations may be expanded beyond locations of those only present in clinical tables.

1.4 CARE_SITE

The Care Site domain contains a list of uniquely identified physical or organizational units where healthcare delivery is practiced (offices, wards, hospitals, clinics, etc.).

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
caresiteid	Yes	Yes	Integer	A unique identifier for each defined location of care within an organization. Here, an organization is defined as a collection of one or more care sites that share a single EHR database.	This is not a value found in the EHR. Sites may choose to use a sequential value for this field
caresitename	No	Provide When Available	Varchar	The description of the care site	
					Please include valid concept ids (consistent with OMOP CDMv5.1). Predefined value set (valid conceptids found in <i>CONCEPT</i> table where conceptclassid = 'Place of Service' and invalidreason is null)

placeofserviceconceptid	No	Provide When Available	Integer	A foreign key that refers to a place of service concept identifier in the Vocabulary	<p>select * from concept where conceptclassid = 'Place of Service' and invalidreason is null yields 49 valid conceptids.</p> <p>Please use the following value set for PEDSnet v3.0:</p> <ul style="list-style-type: none"> • Urgent Care Facility = 8782 • Rural Health Clinic = 8761 • Outpatient (Examples: Hospital Dialysis, HOD, Day Hospital, Day Medicine) = 8756 • Office =8940 • Inpatient Psychiatric Facility =8971 • Inpatient Hospital =8717 • Independent Clinic =8716 • Emergency Room - Hospital = 8870 • Other Place of Service =8844 • Other Inpatient Care =8892 • Unknown: conceptid = 44814653 • Other: conceptid = 44814649 • No information: concept_id = 44814650
location_id	No	Provide When Available	Integer	A foreign key to the geographic location of the administrative offices of the organization in the location table, where the detailed address information is stored.	
caresitesource_value	Yes	Yes	Varchar	The identifier for the organization in the source data, stored here for reference.	<p>If care site source values are deemed sensitive by your organization, insert a pseudo-identifier (random number, encrypted identifier) into the field. Sites electing to obfuscate care sitesourcevalues will keep the mapping between the value in this field and the original clear text location source value. This value is only used for site-level re-identification for study recruitment and for data quality review.</p> <p>For EPIC EHRs, map caresiteid to Clarity Department.</p> <p>Sites may consider using the caresiteid field value in this table as the pseudo-identifier as long as a local mapping from caresiteid to the real site identifier is maintained.</p>
placeofservicesourcevalue	No	Provide When Available	Varchar	The source code for the place of service as it appears in the source data, stored here for reference.	
specialtyconceptid	No	Provide When Available	Integer	The specialty of the department linked to a standard specialty concept as it appears in the Vocabulary	<p>Care sites could have one or more specialties or a Care site could have no specialty information.</p> <p>Valid specialty concept ids for PEDSnet are found in the appendix</p> <p>Please use the following rules:</p> <ul style="list-style-type: none"> • If care site specialty information is unavailable, please follow the convention on reporting values that are unknown,null or unavailable. • If a care site has a single specialty associated with it, sites should link the specialty to the valid specialty concepts as assigned in the appendix. If the specialty does not correspond to a value in this listing, please use the NUCC Listing (vocabularyid='NUCC') <i>provided in the vocabulary as a reference</i>. • If there are multiple specialties associated with a particular care site and sites are not able to assign a specialty value on the visit occurrence level, sites should use the specialty concept id=38004477 "Pediatric Medicine".

					<ul style="list-style-type: none"> If there are multiple specialties associated with a particular care site and this information is attainable, sites should document the strategy used to obtain this information and the strategy used to link the correct care site/specialty pair for each visit occurrence. Sites should also link the specialty to the valid specialty concepts as assigned in the appendix If the specialty does not correspond to a value in this listing, please use the NUCC Listing (vocabularyid='NUCC') provided in the vocabulary as a reference. If the specialty does not correspond to a value in the NUCC Listing and no value in the ABMS Listing, please use the Specialty listing (vocabulary_id='Specialty') as a reference
specialtysourcevalue	No	Provide When Available	Varchar	The source code for the specialty as it appears in the source data, stored here for reference.	

If a field marked as "Provide when available" for the network requirement is not available at your site, please relay this information to the DCC

1.4.1 Additional Notes

- Care sites are primarily identified based on the specialty or type of care provided, and secondarily on physical location, if available (e.g. North Satellite Endocrinology Clinic)
- The Place of Service Concepts are based on a catalog maintained by the CMS (see vocabulary for values)

1.5 PROVIDER

The Provider domain contains a list of uniquely identified health care providers. These are typically physicians, nurses, etc.

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
provider_id	Yes	Yes	Integer	A unique identifier for each provider. Each site must maintain a map from this value to the identifier used for the provider in the source data.	<p>This is not a value found in the EHR.</p> <p>SITE RESPONSIBILITY: This field must remain a stable identifier across submissions to the DCC.</p> <p>A mapping from the provider_id to a real provider from the source EHR must be kept at the local site. This mapping is not shared with the data coordinating center. It is used only by the site for re-identification for study recruitment or for data quality review.</p> <p>Sites should document who they have included as a provider.</p>
provider_name	No	NO	Varchar	A description of the provider	DO NOT TRANSMIT TO DCC
genderconceptid	No	Provide When Available	Integer	The gender of the provider	A foreign key to the concept that refers to the code used in the source.
specialtyconceptid	No	Provide When Available	Integer	A foreign key to a standard provider's specialty concept identifier in the Vocabulary.	<p>Please map the source data to the mapped provider specialty concept associated with the American Medical Board of Specialties as seen in Appendix A1. Predefined value set (valid conceptids found in <i>CONCEPT</i> table where domainid='Provider Specialty' and vocabularyid in ('Specialty', 'ABMS', 'NUCC', 'PEDsnet'))</p> <p><i>select * from concept where domainid ='Provider Specialty' and vocabularyid in ('Specialty', 'ABMS', 'NUCC', 'PEDsnet') and invalidreason is null yields 1025 valid conceptids.</i></p> <p><i>If none are correct, use conceptid = 0</i></p> <p>For providers with more than one specialty, use site-specific logic to select one specialty and document the logic used. For example, sites may decide to always assert the **first** specialty listed in their data source. As a first guide please use</p>

					<p>Insert the NUCC specialty listed in their data source. For a NUCC gender please use the ABMS and PEDSnet vocabulary specialty listing listing to map your specialty values. If the specialty does not correspond to a value in these listings, please use the NUCC Listing (vocabularyid='NUCC') provided in the vocabulary as a reference and the Specialty (vocabularyid='Specialty') if no correspond value exists in the NUCC Listing.</p>
caresiteid	Yes	Yes	Integer	A foreign key to the main care site where the provider is practicing.	See CARESITE.caresite_id (primary key)
yearofbirth	No	Provide When Available	Integer	The year of birth of the provider	
NPI	No	Site Preference	Varchar	The National Provider Identifier (NPI) of the provider.	
DEA	No	Site Preference	Varchar	The Drug Enforcement Administration (DEA) number of the provider.	
providersourcevalue	Yes	Yes	Varchar	The identifier used for the provider in the source data, stored here for reference.	<p>Insert a pseudo-identifier (random number, encrypted identifier) into the field. Do not insert the actual PROVIDERID from your site. A mapping from the pseudo-identifier for providersourcevalue in this field to a real provider ID from the source EHR must be kept at the local site. This mapping is not shared with the data coordinating center. It is used only by the site for re-identification for study recruitment or for data quality review.</p> <p>Sites may consider using the providerid field value in this table as the pseudo-identifier as long as a local mapping from provider_id to the real site identifier is maintained.</p>
specialtysourcevalue	No	Provide When Available	Varchar	The source code for the provider specialty as it appears in the source data, stored here for reference.	Optional. May be obfuscated if deemed sensitive by local site.
specialtysourceconcept_id	No	Provide When Available	Integer	A foreign key to a concept that refers to the code used in the source.	<p>If providing this information, sites should document how they determine the specialty associated with the provider. Valid specialty concept ids for PEDSnet are found in the appendix If the specialty does not correspond to a value in this listing, please use the NUCC Listing (vocabularyid='NUCC') provided in the vocabulary as a reference.</p> <p>**If there is not a mapping for the source code in the standard vocabulary, use conceptid = 0**</p>
gendersourcevalue	No	Provide When Available	Varchar	The source value for the provider gender.	
gendersourceconcept_id	No	Provide When Available	Integer	The gender of the provider as represented in the source that maps to a concept in the	If there is not a mapping for the source code in the standard vocabulary, use concept_id = 0

				concept in the vocabulary	
--	--	--	--	---------------------------	--

If a field marked as "Provide when available" for the network requirement is not available at your site, please relay this information to the DCC

1.5.1 Additional Notes

- For PEDSnet, a provider is any individual (MD, DO, NP, PA, RN, etc) who is authorized to document care.
- Providers are not duplicated in the table.

1.6 VISIT_OCCURRENCE

The visit occurrence domain contains the spans of time a person continuously receives medical services from one or more providers at a care site in a given setting within the health care system.

Exclusions:

- Future Vists
- Cancelled Visits (where the patient was not seen)

Note 1: Please use the following logic to assign visit concept ids:

Visit Concept Id	Concept Name	Visit Type Inclusion	In Person	Examples/Logic (includes but is not limited to)
9201	Inpatient Visit (IP)	Visits that resulted in a patient admission	Yes	Hospital Admissions
9202	Ambulatory Visit (AV)	Outpatient Visits	Yes	Office Visits or Appointments
9203	Emergency Department Visit (ED)	Emergency Department visits	Yes	Emergency Room Visits
44814711	Other ambulatory Visit (OA)	Other outpatient visits that do not meet the 9202 criteria.	No	Telemedicine, Refills and Orders Only Encounters
42898160	Long Term Care Visit	Formal or Informal long term care for chronic illness management	Yes	Site discretion
44814710	Non-Acute Institutional	Non-Acute long term management of care	Yes	Site discretion
2000000048	Emergency Department Admit to Inpatient Hospital Stay	Combination of 9203 and 9201 visits	Yes	Use only if unable to split the ED and inpatient visit.
2000000088	Observation Visit	Please discern what defines an observation visit at your site	Yes	Only map to the observation visit type if the patient leaves the hospital or is discharged from what has been determined to be an observation visit. For sites splitting visits, ED->Observation visits are only to be mapped as Observation Stay Visits. The split in this case is not required.
2000000104	Administrative Visit	Other visits that are in the source system for administrative purposes.	No	Professional Billing or Hospital Abstractions

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
					<p>This is not a value found in the EHR.</p> <p>VISIT_OCCURRENCEID must be unique for all patients within a single data set.</p>

visitoccurrenceid	Yes	Yes	Integer	A unique identifier for each person's visits or encounter at a healthcare provider.	<p>SITE RESPONSIBILITY: This field must remain a stable identifier across submissions to the DCC.</p> <p>A mapping from the visit occurrence id to a real patient encounter from the source EHR must be kept at the local site. This mapping is not shared with the data coordinating center. It is used only by the site for re-identification for study recruitment or for data quality review. Do not use institutional encounter ID.</p>
person_id	Yes	Yes	Integer	A foreign key identifier to the person for whom the visit is recorded. The demographic details of that person are stored in the person table.	
visitstartdate	Yes	Yes	Date	The start date of the visit.	No date shifting. Full date.
visitenddate	No	Provide When Available	Date	The end date of the visit.	<p>No date shifting. Full date.</p> <p>If this is a one-day visit the end date should match the start date.</p> <p>If the encounter is on-going at the time of ETL, this should be null.</p>
visitstartdatetime	Yes	Yes	Datetime	The start date of the visit.	No date shifting. Full date and time. If there is no time associated with the date assert midnight for the start time
visitenddatetime	No	Provide When Available	Datetime	The end date of the visit.	<p>No date shifting.</p> <p>If this is a one-day visit the end date should match the start date.</p> <p>If the encounter is on-going at the time of ETL, this should be null. Full date and time. If there is no time associated with the date assert 11:59:59 pm for the end time</p>
provider_id	No	Provide When Available	Integer	A foreign key to the provider in the provider table who was associated with the visit.	<p>Use attending or billing provider for this field if available, even if multiple providers were involved in the visit. Otherwise, make site-specific decision on which provider to associate with visits and document.</p> <p>NOTE: this is NOT required in OMOP CDM v4, but appears in OMOP CDMv5.</p>
caresiteid	No	Provide When Available	Integer	A foreign key to the care site in the care site table that was visited.	See CARESITE.caresite_id (primary key)
visitconceptid	Yes	Yes	Integer	A foreign key that refers to a place of service concept identifier in the vocabulary.	<p>In PEDSnet CDM v1, this field was previously called placeofserviceconceptid</p> <p>Please include valid concept ids (consistent with OMOP CDMv5). Predefined value set (valid conceptids found in CONCEPT table where domainid='Visit' or (vocabularyid='PCORNet' and conceptclassid='Encounter Type' and not conceptcode ~ '-EDI-IPI-AV') or (vocabularyid='PCORNet' and conceptclassid='Undefined' and not conceptcode ~ '-EDI-IPI-AV') and invalidreason is null.</p> <p><i>select * from concept where domainid='Visit' or (vocabularyid='PCORNet' and conceptclassid='Encounter Type' and not conceptcode ~ '-EDI-IPI-AV') or (vocabularyid='PCORNet' and conceptclassid='Undefined' and not conceptcode ~ '-EDI-IPI-AV') and invalidreason is null yields 11 valid conceptids.</i></p> <p>If none are correct, use conceptid = 0</p>

					<ul style="list-style-type: none"> • <i>Inpatient Hospital Stay: conceptid = 9201</i> • <i>Ambulatory Visit: conceptid = 9202</i> • <i>Emergency Department: conceptid = 9203</i> • <i>Long Term Care Visit = 42898160</i> • <i>Other ambulatory Visit = 44814711</i> • <i>Non-Acute Institutional Stay: conceptid = 44814710)</i> • <i>Emergency Department Admit to Inpatient Hospital Stay (If sites are unable to split the encounter) = 2000000048</i> • <i>Observation Stay= 2000000088</i> • <i>Administrative Visit= 2000000104</i> • <i>Unknown: conceptid = 44814653</i> • <i>Other: conceptid = 44814649</i> • <i>No information: conceptid = 44814650</i> <p>See Note 1 Visit Definitions.</p>
visitsourceconcept_id	Yes	Yes	Integer	A foreign key to the predefined concept identifier in the standard vocabulary reflecting the type of source data from which the visit record is derived.	<p>select * from concept where conceptclassid='Visit Type' yields 3 valid conceptids.</p> <p><i>If none are correct, user conceptid=0. The majority of visits should be type 'Visit derived from EHR record' which is concept_id=44818518</i></p>
visitsourcevalue	No	Provide When Available	Varchar	The source code used to reflect the type or source of the visit in the source data. Valid entries include office visits, hospital admissions, etc. These source codes can also be type-of service codes and activity type codes.	
visitsourceconcept_id	No	Provide When Available	Integer	A foreign key to a concept that refers to the code used in the source.	<p>If a site is using HCPS or CPT for their visit source value, the standard concept id that maps to the particular vocabulary can be used here.</p> <p>If there is not a mapping for the source code in the standard vocabulary, use concept_id = 0</p>
precedingvisitoccurrence_id	No	NO	Integer	A foreign key to the VISIT_OCCURRENCE table record of the visit immediately preceding this visit.	Do not transmit to DCC
admittingsourceconcept_id	No	Provide When Available	Integer	A foreign key to the predefined concept in the Place of Service Vocabulary reflecting the admitting source for a visit.	<p>Please use the following valid concept id set for Admitting source:</p> <ul style="list-style-type: none"> • Adult Foster Home=44814670 • Assisted Living Facility=44814671 • Ambulatory Visit=44814672 • Emergency Department=8870= • Home Health=44814674 • Home / Self Care=44814675 • Hospice=8546 • Other Acute Inpatient Hospital=38004279 • Nursing Home (Includes ICF)=44814678 • Rehabilitation Facility=44814679 • Residential Facility=44814680 • Skilled Nursing Facility=8863 • No information=44814650 • Unknown=44814653 • Other=44814649 <p>This should be populated for inpatient encounters in the source but may vary for emergency department (ED) visits and outpatient encounters (AV,OA).</p>
					Please use the following valid concept id set for Discharge

discharge _{to} concept_id	No	Provide When Available	Integer	A foreign key to the predefined concept in the Place of Service Vocabulary reflecting the discharge disposition (destination) for a visit.	Destination: <ul style="list-style-type: none"> • Adult Foster Home=38004205 • Assisted Living Facility=38004301 • Against Medical Advice=4021968 • Absent without leave=44814693 • Expired=4216643 • Home Health=38004195 • Home / Self Care=8536 • Hospice=8546 • Other Acute Inpatient Hospital=38004279 • Nursing Home (Includes ICF)=8676 • Rehabilitation Facility=8920 • Residential Facility=44814701 • Still In Hospital=8717 • Skilled Nursing Facility=8863 • No information=44814650 • Unknown=44814653 • Other=44814649 This should be populated for inpatient encounters in the source but may vary for emergency department (ED) visits and outpatient encounters (AV,OA).
admitting _{source} value	No	Provide When Available	Varchar	The source code for the admitting source as it appears in the source data.	This should be populated for inpatient encounters in the source but may vary for emergency department (ED) visits and outpatient encounters (AV,OA).
discharge _{to} source_value	No	Provide When Available	Varchar	The source code for the discharge disposition as it appears in the source data.	This should be populated for inpatient encounters in the source but may vary for emergency department (ED) visits and outpatient encounters (AV,OA).

**If a field marked as "Provide when available" for the network requirement is not available at your site, please relay this information to the DCC

1.6.1 Additional Notes

- The 1/1/2009 date limitation that is used to define a PEDSnet active patient is **NOT** applied to visit_occurrence. All visits, of all types (physical and virtual) are included for an active patient.
- A Visit Occurrence is recorded for each visit to a healthcare facility.
- If a visit includes moving between different visit_{concepts} (ED -> inpatient) sites may opt to split the record into separate visit_{occurrence} records.

To show the relationship of the split (ED -> inpatient) encounter, use the FACT_RELATIONSHIP table.

An example of this is below:

VISIT_OCCURRENCE

visit _{occurrence} id	person_id	visit _{startdate}	visit _{enddate}	provider_id	care _{site} id	place _{of} service _{concept} id	place _{of} service _{source} value
35022489	209846	2011-11-14 17:36:00-05	2011-11-14 22:25:00-05	2238	322	9203	Emergency
35022490	209846	2011-11-14 22:25:00-05	2011-11-15 16:33:00-05	2238	43	9201	Emergency

FACT_RELATIONSHIP

Domain _{concept} id_1	fact _{id} 1	Domain _{concept} id_2	fact _{id} 2	relationship _{concept} id
Visit	35022489	Visit	35022490	Occurs before
Visit	35022490	Visit	35022489	Occurs after

Because the domain_{concept}id and relationship_{concept}id are actually numeric values the following is an example of how the table is stored:

Domainconceptid_1	factid1	Domainconceptid_2	factid2	relationshipconceptid
8	35022489	8	35022490	44818881
8	35022490	8	35022489	44818783

- Operating and Anesthesia encounters that occur as apart of the Inpatient stay should be rolled up into one Inpatient encounter.
- Each Visit is standardized by assigning a corresponding Concept Identifier based on the type of facility visited and the type of services rendered.
- At any one day, there could be more than one visit.
- One visit may involve multiple attending or billing providers (e.g. billing, attending, etc), in which case the ETL must specify how a single provider id is selected or leave the provider_id field null.
- One visit may involve multiple care sites, in which case the ETL must specify how a single caresite id is selected or leave the caresite_id field null.

1.7 CONDITION_OCCURRENCE

The condition occurrence domain captures records of a disease or a medical condition based on diagnoses, signs and/or symptoms observed by a provider or reported by a patient.

Conditions are recorded in different sources and levels of standardization. For example:

- Medical claims data include ICD-9-CM diagnosis codes that are submitted as part of a claim for health services and procedures.
- EHRs may capture a person's conditions in the form of diagnosis codes and symptoms as ICD-9-CM or ICD-10-CM codes, but may not have a way to capture out-of-system conditions.
- EHRs may also capture External Injury codes in different place in the source system. These types of codes are also to be included.

For the PEDSNet network, please provide **clinical physician based diagnosis** as opposed to billing or claim based diangosis data.

Note 1: For the PEDSNet network, we are coding all diagnosis codes to the SNOMED-CT Vocabulary. Research has showed that the IMO to SNOMED native mapping and IMO to ICD to SNOMED OMOP mapping produces highly variable results. For a particular IMO Code, when comparing the two mapping options, the same SNOMED concept id is only produced 25% of the time. See below examples of the mapping differences (IMO-SNOMED, ICD10 and ICD9):

IMO Description	Direct SNOMED	Via ICD
Numbness of Toes	Numbness of toe	Altered Sensation of Skin
Cerebellar ataxia/dyskinesia	Cerebellar Disorder	Cerebellar Ataxia
Choking episode	Choking sensation	Finding of head and neck region
Intestinal malrotation	Congenital malrotation of intestine	Congenital anomaly of fixation of intestine
Genetic disease carrier status testing	Genetic finding	Genetic disorder carrier
Duchenne muscular dystrophy	Duchenne muscular dystrophy	Hereditary progressive muscular dystrophy

For diagnosis codes, please provide the IMO to SNOMED mapping where it exists in the source system.

If the IMO to SNOMED mapping is not available in the system, utilize the IMO to ICD to SNOMED OMOP mapping in the vocabulary.

Please use the following logic to populate the `condition_concept_id` , `condition_source_concept_id` and `condition_source_value` based on what is available in your source system:

You have in your source system	conditionconceptid	conditionsourceconcept_id	conditionsourcevalue
Any diagnosis that was captured as a term or name (e.g. IMO to SNOMED)	Corresponding SNOMED concept id	Corresponding concept for site diagnosis captured (must correspond to ICD9/ICD10 concept mapping)	Diagnosis Name "I" IMO Code "I" Diagnosis Code
Any diagnosis that was captured directly as a code (e.g. ICD9/10) by a coder	Corresponding SNOMED concept id	Corresponding concept for site diagnosis code (must correspond to ICD9/ICD10 concept mapping)	Diagnosis Name "I" IMO Code "I" Diagnosis Code

Note 2: For the PEDSNet network, please provide clinical physician based diagnosis as opposed to billing or claim based diangosis data. The clinical physician based diagnosis corresponds to the "Order origin" concept ids for `condition_type_concept_id` . If you are providing billing or claim diagnosis data, please use the "Billing" or "Claim" concept_ids for `condition_type_concept_id` .

Note 3:* We have been made aware that there are a significant amount of conditions that route to a domain of Procedure, Measurement etc. Please **DO NOT** route these conditions to those domains or tables (i.e. *ProcedureOccurrence*, *Measurement*). *Instead, include all records coming out of our source tables for diagnosis data in the ConditionCccurrence table.*

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
-------	---------------------	---------------------	-----------	-------------	---------------------

conditionoccurrenceid	Yes	Yes	Integer	A unique identifier for each condition occurrence event.	This is not a value found in the EHR. Sites may choose to use a sequential value for this field
person_id	Yes	Yes	Integer	A foreign key identifier to the person who is experiencing the condition. The demographic details of that person are stored in the person table.	
conditionconceptid	Yes	Yes	Integer	A foreign key that refers to a standard condition concept identifier in the Vocabulary.	Please include valid concept ids (consistent with OMOP CDMv5). Predefined value set (valid conceptids found in <i>CONCEPT</i> table where vocabularyid = 'SNOMED') select * from concept where vocabularyid = 'SNOMED' yields ~440,000 valid conceptids. If none are correct, use concept_id = 0
conditionstartdate	Yes	Yes	Date	The date when the instance of the condition is recorded.	No date shifting.
conditionenddate	No	Provide When Available	Date	The date when the instance of the condition is considered to have ended	No date shifting. If this information is not available, set to NULL.
conditionstartdatetime	Yes	Yes	Datetime	The date and time when the instance of the condition is recorded.	No date shifting. Full date and time. If there is no time associated with the date assert midnight for the start time
conditionenddatetime	No	Provide When Available	Datetime	The date and time when the instance of the condition is considered to have ended	No date shifting. If this information is not available, set to NULL. Full date and time. If there is no time associated with the date assert 11:59:59 pm for the end time
conditiontypeconcept_id	Yes	Yes	Integer	A foreign key to the predefined concept identifier in the Vocabulary reflecting the source data from which the condition was recorded, the level of standardization, and the type of occurrence. For example, conditions may be defined as primary or secondary diagnoses, problem lists and person statuses.	Please include valid concept ids (consistent with OMOP CDMv5). Predefined value set (valid conceptids found in <i>CONCEPT</i> table where conceptclassid = 'Condition Type' and vocabularyid = 'PDSnet') select * from concept where conceptclassid = 'Condition Type' and vocabularyid = 'PDSnet' yields 15 valid conceptids. If none are correct, use concept_id = 0 For the primary diagnosis for the inpatient or outpatient setting (may be identified as Dx#1 in a source system), Please use concepts the following concepts: <ul style="list-style-type: none"> • Outpatient header - 1st position - Order Origin=2000000095 • Outpatient header - 1st position - Billing Origin=2000000096 • Outpatient header - 1st position - Claim Origin=2000000097 • Inpatient header - primary - Order Origin=2000000092 • Inpatient header - primary - Billing Origin=2000000093 • Inpatient header - primary - Claim Origin=2000000094 All other diagnosis that is not the primary (or Dx#1) in the inpatient or outpatient setting should correspond to the following concept ids: <ul style="list-style-type: none"> • Inpatient header - 2nd position - Order Origin=2000000098

					<ul style="list-style-type: none"> Inpatient header - 2nd position - Billing Origin = 2000000099 Inpatient header - 2nd position - Claim Origin = 2000000100 Outpatient header - 2nd position - Order Origin=2000000101 Outpatient header - 2nd position - Billing Origin =2000000102 Outpatient header - 2nd position - Claim Origin =2000000103 <p>For diagnosis from the problem list, please use the following concept ids:</p> <ul style="list-style-type: none"> EHR problem list entry - Order Origin = 2000000089 EHR problem list entry - Billing Origin =2000000090 EHR problem list entry - Claim Origin =2000000091 <p>SEE NOTE 2 for further guidance on determining the origin</p>
stop_reason	No	Provide When Available	Varchar	The reason, if available, that the condition was no longer recorded, as indicated in the source data.	Valid values include discharged, resolved, etc. Note that a stop_reason does not necessarily imply that the condition is no longer occurring, and therefore does not mandate that the end date be assigned.
provider_id	No	Provide When Available	Integer	A foreign key to the provider in the provider table who was responsible for determining (diagnosing) the condition.	<p>In PEDSnet CDM v1, this field was previously called associatedproviderid</p> <p>Any valid provider_id allowed (see definition of providers in PROVIDER table)</p> <p>Make a best-guess and document method used. Or leave blank</p>
visitoccurrenceid	No	Provide When Available	Integer	A foreign key to the visit in the visit table during which the condition was determined (diagnosed).	
conditionsourcevalue	Yes	Yes	Varchar	The source code for the condition as it appears in the source data. This code is mapped to a standard condition concept in the Vocabulary and the original code is, stored here for reference.	Condition source codes are typically ICD-9-CM or ICD-10-CM diagnosis codes from medical claims or discharge status/visit diagnosis codes from EHRs. Use source \rightarrow concept maps to translation from source codes to OMOP concept_ids. Please include the diagnosis name and source code when populating this field, by using the pipe delimiter " " when concatenating values. Example: Diagnosis Name "I" IMO Code "I" Diagnosis Code
conditionsourceconcept_id	No	Provide When Available	Integer	A foreign key to a condition concept that refers to the code used in the source	As a standard convention this code must correspond to the ICD9/ICD10 concept mapping of the source value only. For example, if the condition is "Acute myeloid leukemia, without mention of having achieved remission" which has an icd9 code of 205.00 the condition source concept id is 44826430 which is the icd9 code concept that corresponds to the diagnosis 205.00. If there is not a mapping for the source code in the standard vocabulary, use concept_id = 0
conditionstatusconcept_id	No	Optional	Integer	A foreign key to the predefined concept in the standard vocabulary reflecting the condition status.	For PEDSnet v3.0 we are only reporting final diagnosis, please use the following concept id: <ul style="list-style-type: none"> Final Diagnosis=4230359
conditionstatussource_value	No	Optional	Varchar	The source code for the condition status as it appears in the source data.	

poaconceptid	No	Optional	Integer	A foreign key to value in the source for that determines if the diagnosis is present on admission	<p>For Pedsnet CDM v3.0, please use the following:</p> <ul style="list-style-type: none"> • Yes=4188539 • No=4188540 • No Information: conceptid = 44814650 • Unknown: conceptid = 44814653 • Other: conceptid = 44814649 <p>If none are correct, use conceptid = 0.</p>
--------------	----	----------	---------	---	---

If a field marked as "Provide when available" for the network requirement is not available at your site, please relay this information to the DCC

1.7.1 Additional Notes

- The 1/1/2009 date limitation that is used to define a PEDSnet active patient is ****NOT**** applied to conditionoccurrence. All conditions are included for an active patient. For PEDSnet CDM v3.0, we limit conditionoccurrences to final diagnoses only (not reason-for-visit and provisional surgical diagnoses such as those recored in EPIC OPTIME). In EPIC, final diagnoses includes both encounter diagnoses and billing diagnoses, problem lists (all problems, not filtered on "chronic" versus "provisional" unless local practices use this flag as intended). Medical History diagnosis are optional.
- Condition records are inferred from diagnostic codes recorded in the source data by a clinician or abstractionist for a specific visit. In the current version of the CDM, diagnoses extracted from unstructured data (such as notes) are not included.
- Source code systems, like ICD-9-CM, ICD-10-CM, etc., provide coverage of conditions. However, if the code does not define a condition, but rather is an observation or a procedure, then such information is not stored in the CONDITIONOCCURRENCE table, but in the respective tables instead. An example are ICD-9-CM procedure codes. For example, OMOP source-to-concept table uses the MAPPINGTYPE column to distinguish ICD9 codes that represent procedures rather than conditions.
- Condition source values are mapped to standard concepts for conditions in the Vocabulary. For mapping ICD9 Codes to SNOMED, use the conceptrelationship table where the icd9code = conceptid1 and relationshipid='Maps to'. Conceptid2 will be the SNOMED conceptid mapping you need to populate the conditionconceptid.
- When the source code cannot be translated into a Standard Concept, a CONDITIONOCCURRENCE entry is stored with only the corresponding sourcevalue and a conditionconceptid of 0.
- Codes written in the process of establishing the diagnosis, such as "question of" of and "rule out", are not represented here.

1.8 PROCEDURE_OCCURRENCE

The procedure occurrence domain contains records of significant activities or processes ordered by and/or carried out by a healthcare provider on the patient to have a diagnostic and/or therapeutic purpose that are not fully captured in another table (e.g. drug_exposure).

Procedures records are extracted from structured data in Electronic Health Records that capture source procedure codes using CPT-4, ICD-9-CM (Procedures), ICD-10 (Procedures), HCPCS or OPCS-4 procedures as orders.

More specifically the procedure occurrence domain is intended to stores information about activity or processes involving a patient that has a billable code. This includes but is not limited to the following: - LOS Codes ((Eg. 99123) This code may not Not necessarily be a CPT and could require local mapping) - Lab Procedures (including a Lab Panel Order and Culture Orders) - Surgery Procedures - Imaging Procedures

Notes: **Only instantiated procedures are included in this table. Please exclude cancelled procedures For CPT Codes, only include codes that are included in the standard CPT4 vocabulary from the distributed vocabulary**

Note 1: Please use the following logic to populate the procedure_concept_id , procedure_source_concept_id and procedure_source_value based on what is available in your source system:

Site Information	procedureconceptid	proceduresourceconcept_id	proceduresourcevalue
Procedure codes using CPT-4, ICD-9-CM (Procedures), ICD-10 (Procedures), HCPCS or OPCS-4 procedures as orders	Corresponding CPT-4, ICD-9-CM (Procedures), ICD-10 (Procedures), HCPCS or OPCS-4 concept id	Corresponding CPT-4, ICD-9-CM (Procedures), ICD-10 (Procedures), HCPCS or OPCS-4 concept id	Procedure Name I Procedure Source Code
Custom Procedure Coding (That a site has knowledge of corresponding to a standard code but requires manual mapping)	Corresponding CPT-4, ICD-9-CM (Procedures), ICD-10 (Procedures), HCPCS or OPCS-4 concept id	0	Procedure Name I Custom Procedure Code

Field	NOT Null Constraint	Network Requirement	Data Type	Description	PEDSnet Conventions
procedureoccurrenceid	Yes	Yes	Integer	A system-generated unique identifier for each procedure occurrence	This is not a value found in the EHR. Sites may choose to use a sequential value for this field