

# R Programming Basics and Data management in R


Pablo E. Gutierrez-Fonseca

Fall 2024



# What is R Programming?

- R is a free and open source software environment and programming language for statistics.
- R was created by Ross Ihaka and Robert Gentleman at the University of Auckland (in New Zealand), and is based on the S language that was created by John Chambers at Bell Laboratories.



**Robert Gentleman**

**Ross Ihaka**

# What is R Programming?

- When you download and install R, you get a collection of basic packages (and libraries) that can be used to implement several common data manipulations, graphical displays, and statistical models.



# Strengths and Weaknesses

- **Strengths:**

- Free and Open Source.
- Strong User Community.
- Highly extensible, flexible.
- Implementation of high-end statistical methods.
- Flexible graphics and intelligent defaults.

- **Weakness:**

- Steep learning curve.
- Slow for large datasets.

# Why R?

- **Computing power:** R can handle much larger datasets than traditional programs, which is especially important for long-term ecological data, community science data, and public health data.
- **Flexibility & convenience:** Traditionally, scientists would need separate programs for data cleaning, statistical procedures, and data visualization.  
Learning R means you can do everything in a single program, and customize to fit the goals of your project.
- **Reproducibility:** Saving your code as an R script makes it easy for other scientists to see what you did, and repeat your methods.

# R Overview

# How to download?

- Google it using R or CRAN (Comprehensive R Archive Network)
  - <http://www.r-project.org>


# How to download?

- Having installed R, the next thing we will want to do is install **RStudio**, a popular and useful interface for writing scripts and using R.
- If you google **RStudio** you will get to this window:  
<https://www.rstudio.com/products/rstudio/download/>
- Rstudio is an ***integrated development environment (IDE)*** for R that allows users to interact more easily with R by integrating different aspects of scripting, from code completion to debugging.




# Typical Rstudio session

- **Code Editor:** Contains code to tell R what to do. Save scripts for future use




# Typical Rstudio session

- **Console:** output & temporary input - usually unsaved




# Typical Rstudio session

- **Workspace:** Stores objects created during the session. Save with `save.image()`.
- **History:** Records commands used. Save with `savehistory()`.



# Typical Rstudio session

- **Plots:** Displays graphs. Save plots with ggsave().
- **Files:** Shows files in the working directory.



# Data structures

# Data structures

- R is an object oriented programming language where an **object** is a generic term to describe something in R.
- There are many types of R-objects.

Vectors

Factors

Lists

Matrices

Data Frames

# Vectors in R

- Vector is a sequence of elements of the same type (numeric, character, logical).

```
a <- c(1,2,3,4,5)
b <- c(6,7,8,9,10)
```

- Command `c` creates a vector that is assigned to object `a` and `b`

# Vectors in R

- Two vectors of the same length can be added ( $a+b$ ), multiply ( $a*b$ )

```
c <- (a+b)  
c
```

```
## [1]  7  9 11 13 15
```

```
d <- (a*b)  
d
```

```
## [1]  6 14 24 36 50
```



# Vectors in R

- Element in a vector can be sorted (*sort()*)

```
e <- c(3,2,20,25,5)  
sort(e)
```

```
## [1]  2  3  5 20 25
```

# Factors in R

- Categorical data structure with predefined levels.

```
f <- factor(c("low", 'medium', "high", 'very high'))
```

# Data

- R has three general classes for data:
  - ① **list**: collection of objects of different lengths or classes
  - ② **matrix**: vectors of the same length and same class
  - ③ **data.frame**: vectors of the same length and different classes

# Lists

- A list is an R-object which can contain many different types of elements inside it like vectors, functions and even another list inside it.

```
# Creating a list in R with various types of elements  
my_list <- list(  
  # A numeric vector  
  Numbers = c(1, 2, 3, 4, 5),  
  # A character vector  
  Words = c("apple", "banana", "cherry"))
```

# Lists

- A list is an R-object which can contain many different types of elements inside it like vectors, functions and even another list inside it.

```
NestedList = list(  
  Logical = c(TRUE, FALSE, TRUE),  
  Mixed = c(3.14, "pi", FALSE))  
NestedList
```

```
## $Logical  
## [1] TRUE FALSE TRUE  
##  
## $Mixed  
## [1] "3.14" "pi" "FALSE"
```

# Matrices

- A matrix is a two-dimensional rectangular data set.
- It can be created using a vector input to the matrix function.

```
# Create a 3x3 matrix in R
my_matrix <- matrix(
  data = 1:9,           # Data to fill the matrix
  nrow = 3,             # Number of rows
  ncol = 3,             # Number of columns
  byrow = TRUE)         # Fill the matrix by rows
my_matrix
```

```
##      [,1] [,2] [,3]
## [1,]    1    2    3
## [2,]    4    5    6
## [3,]    7    8    9
```

# Data Frames

- Data frames are tabular data objects.
- **Unlike a matrix in data frame each column can contain different modes of data.**
- The first column can be numeric while the second column can be character and third column - Can be logical.
- It is a list of vectors of equal length.
- Data Frames are created using the ***data.frame()*** function.
- When we execute the above code, it produces the following result:

# Table

- Summary

	<b>Linear</b>	<b>Rectangular</b>
<b>All Same Types</b>	Vectors	Matrix
<b>Mixed</b>	List	Data Frame



# Reading data

# Reading data

- Command for reading in text files is:

```
read.table("suomi.txt", header=T, sep="\t")
```

- This examples has one command with three arguments:
  - ▶ file name (in quotes)
  - ▶ header that tells whether columns have titles
  - ▶ sep that tells that the file is tab-delimited.

# Reading data

- **CSV File**

- Usage: Reads comma-separated values, often used for structured data.

```
data <- read.csv("file.csv")
```

- **Text File**

- Usage: Reads tabular data from a text file; sep can be adjusted for different delimiters.

```
data <- read.table("file.txt", header = TRUE, sep = "\t")
```

- **Excel File**

- Usage: Reads data from Excel files; you can specify the sheet number or name.

```
library(readxl)  
data <- read_excel("file.xlsx", sheet = 1)
```

# Reading data

- Print the current working directory

```
getwd()
```

- Change to my directory

```
setwd(mydirectory)  
setwd("c:/docs/mydir")
```

# Reading data

- Subscripts are given inside square brackets after the object's name:
- `df[,1]`
  - ▶ Gets the **first column** from the object dat
- `df[1,]`
  - ▶ Gets the **first row** from the object dat
- `df[1,1]`
  - ▶ Gets the **first row** and it's **first column** from the object dat

# Reading data

- Subscripts can be used for, e.g., extracting a subset of the data:
  - ▶ `df[which(df$year>1900),]`
    - ★ Now, this takes a bit of pondering to work out.
    - ★ First we have the object `df`, and we are accessing a part of it, because it's name is followed by the square brackets
    - ★ Then we have one command (`which`) that makes an evaluation whether the column `year` in the object `df` has a value higher than 1900.
    - ★ Last the subscript ends with a comma, that tells us that we are accessing rows.
    - ★ So this command takes all the rows that have a year higher 1900 from the object `dat` that is a data frame.

# Assigning Values in R

- In R, you can assign values to objects using the syntax `object <- value`
- An arrow (`<-`) formed by a smaller than character and a hyphen without a space!
- The equal character (`=`).

# R Warning!

- Naming objects:
  - ▶ R is a case sensitive language.
  - ▶ FOO, Foo, and foo are three different objects
  - ▶ Object names can't start with a number
  - ▶ Never use special characters, such as å, ä, or ö in object names.



# Using Functions in R

- R is a function based language where a ***function*** takes in some input and produces some output.
  - ▶ Vegas rules: what happens in a function, stays in a function.

# Data Visualization in R

- Most powerful approach to statistical graphs, based on the **Grammar of Graphics**.
- A graphics language, composed of layers, **geoms** (points, lines, regions), each with graphical **aesthetics** (color, size, shape)

```
library(ggplot2)
```

```
## Warning: package 'ggplot2' was built under R version 4.3.3
```


```
library(palmerpenguins)
```

```
## Warning: package 'palmerpenguins' was built under R version
```

# An Introduction to ggplot2

```
ggplot(data = penguins, aes(x = flipper_length_mm,  
                             y = body_mass_g)) +  
  geom_point(aes(color = species, shape = species))
```

```
## Warning: Removed 2 rows containing missing values or values  
## ('geom_point()').
```



# An Introduction to ggplot2

```
ggplot(data = <your data set>, aes(x = <x axis variable>,
                                     y = <y axis variable>)) +
  geom_point(aes(size = <size variable>,
                 color = <color variable>,
                 shape = <shape variable>))
```