

Cisco Packet Tracer PC Command Line 1.0

C:\>ping 50.0.0.1

Pinging 50.0.0.1 with 32 bytes of data:

Reply from 50.0.0.1: bytes=32 time<1ms TTL=255

Reply from 50.0.0.1: bytes=32 time<1ms TTL=255

Reply from 50.0.0.1: bytes=32 time<1ms TTL=255

Reply from 50.0.0.1: bytes=32 time<1ms TTL=255

Ping statistics for 50.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>

Cisco Packet Tracer PC Command Line 1.0

C:\>ping 60.0.0.1

Pinging 60.0.0.1 with 32 bytes of data:

Reply from 60.0.0.1: bytes=32 time<1ms TTL=255

Reply from 60.0.0.1: bytes=32 time<1ms TTL=255

Reply from 60.0.0.1: bytes=32 time<1ms TTL=255

Reply from 60.0.0.1: bytes=32 time<1ms TTL=255

Ping statistics for 60.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>

Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#exit

Router#sho

*Aug 24 09:01:35.573: %SYS-5-CONFIG_I: Configured from console by console
Router#show ip interface brief

Interface	IP-Address	OK?	Method	Status	Protocol
Ethernet0/0	unassigned	YES	TFTP	up	up
Ethernet0/1	unassigned	YES	TFTP	up	up
Ethernet0/2	unassigned	YES	TFTP	down	down
Ethernet0/3	unassigned	YES	TFTP	down	down

Router#configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

Router(config)#interface ethernet0/0

Router(config-if)#ip add 50.0.0.1

% Incomplete command.

Router(config-if)#ip add 50.0.0.1 255.0.0.0

Router(config-if)#no shutdown

Router(config-if)#exit

Router(config)#exit

Router#

*Aug 24 09:03:42.100: %SYS-5-CONFIG_I: Configured from console by console

Router#

```
Router(config)#  
Router(config)#interface e0/1  
Router(config-if)#ip add 60.0.0.1 255.0.0.0  
Router(config-if)#no sh  
*Aug 24 09:05:16.742: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)  
Router(config-if)#no shutdown  
Router(config-if)#exit  
Router(config)#exit  
Router#  
*Aug 24 09:05:26.045: %SYS-5-CONFIG_I: Configured from console by console  
Router#
```

Router#

Router#show ip interface brief

Interface	IP-Address	OK?	Method	Status	Protocol
Ethernet0/0	50.0.0.1	YES	manual	up	up
Ethernet0/1	60.0.0.1	YES	manual	up	up
Ethernet0/2	unassigned	YES	TFTP	down	down
Ethernet0/3	unassigned	YES	TFTP	down	down

Router#

Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ping 50.0.0.1

Pinging 50.0.0.1 with 32 bytes of data:

Reply from 50.0.0.1: bytes=32 time=1ms TTL=255
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255

Ping statistics for 50.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\Documents and Settings\user>

Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ping 60.0.0.1

Pinging 60.0.0.1 with 32 bytes of data:

Reply from 60.0.0.1: bytes=32 time=1ms TTL=255
Reply from 60.0.0.1: bytes=32 time=1ms TTL=255
Reply from 60.0.0.1: bytes=32 time=1ms TTL=255
Reply from 60.0.0.1: bytes=32 time=1ms TTL=255

Ping statistics for 60.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\Documents and Settings\user>_

```
C:\Documents and Settings\user>route add 60.0.0.0 mask 255.0.0.0 50.0.0.1
```

```
C:\Documents and Settings\user>route print
```

```
=====
```

Interface List

0x1 MS TCP Loopback interface

0x2 ...50 fe 9c 09 4f 00 Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

```
=====
```

```
=====
```

Active Routes:

Network Destination	Netmask	Gateway	Interface	Metric
50.0.0.0	255.0.0.0	50.0.0.10	50.0.0.10	10
50.0.0.10	255.255.255.255	127.0.0.1	127.0.0.1	10
50.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	10
60.0.0.0	255.0.0.0	50.0.0.1	50.0.0.10	1
127.0.0.0	255.0.0.0	127.0.0.1	127.0.0.1	1
224.0.0.0	240.0.0.0	50.0.0.10	50.0.0.10	10
255.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	1

```
=====
```

Persistent Routes:

None

```
C:\Documents and Settings\user>
```

		Gateway	Interface	Metric
50.0.0.0	255.0.0.0	50.0.0.10	50.0.0.10	10
50.0.0.10	255.255.255.255	127.0.0.1	127.0.0.1	10
50.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	10
60.0.0.0	255.0.0.0	50.0.0.1	50.0.0.10	1
127.0.0.0	255.0.0.0	127.0.0.1	127.0.0.1	1
224.0.0.0	240.0.0.0	50.0.0.10	50.0.0.10	10
255.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	1

=====
 Persistent Routes:
 None

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:

Request timed out.
 Request timed out.
 Request timed out.
 Request timed out.

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss).

C:\Documents and Settings\user>

```
C:\Documents and Settings\user>
C:\Documents and Settings\user>route add 50.0.0.0 mask 255.0.0.0 60.0.0.1

C:\Documents and Settings\user>route print
=====
Interface List
0x1 ..... MS TCP Loopback interface
0x2 ...50 86 5f 09 50 00 ..... Intel(R) PRO/1000 MT Network Connection - Packet
Scheduler Miniport
=====
=====
Active Routes:
Network Destination        Netmask          Gateway           Interface        Metric
    50.0.0.0                255.0.0.0         60.0.0.1          60.0.0.10         1
    60.0.0.0                255.0.0.0         60.0.0.10         60.0.0.10        10
    60.0.0.10              255.255.255.255   127.0.0.1         127.0.0.1        10
  60.255.255.255            255.255.255.255   60.0.0.10         60.0.0.10        10
    127.0.0.0                255.0.0.0        127.0.0.1         127.0.0.1         1
    224.0.0.0                240.0.0.0         60.0.0.10         60.0.0.10        10
  255.255.255.255          255.255.255.255   60.0.0.10         60.0.0.10         1
=====
Persistent Routes:
None

C:\Documents and Settings\user>
```

None

C:\Documents and Settings\user>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:

Reply from 50.0.0.10: bytes=32 time=4ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time<1ms TTL=127

Ping statistics for 50.0.0.10:

Packets: Sent = 4, Received 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 4ms, Average = 1ms

Pinging 60.0.0.10 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:

Reply from 60.0.0.10: bytes=32 time=3ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 3ms, Average = 1ms

C:\Documents and Settings\user>

```
Reply from 60.0.0.10: bytes=32 time=3ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
```

```
Ping statistics for 60.0.0.10:
```

```
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 3ms, Average = 1ms
```

```
C:\Documents and Settings\user>route delete 60.0.0.0
```

```
C:\Documents and Settings\user>ping 60.0.0.10
```

```
Pinging 60.0.0.10 with 32 bytes of data:
```

```
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
```

```
Ping statistics for 60.0.0.10:
```

```
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss).
```

```
C:\Documents and Settings\user>
```

Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time<1ms TTL=127

Ping statistics for 50.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 4ms, Average = 1ms

C:\Documents and Settings\user>

C:\Documents and Settings\user>route delete 50.0.0.0

C:\Documents and Settings\user>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:

Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.

Ping statistics for 50.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss).

C:\Documents and Settings\user>

```
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time<1ms TTL=127
```

```
Ping statistics for 50.0.0.10:
```

```
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 4ms, Average = 1ms
```

```
C:\Documents and Settings\user>
```

```
C:\Documents and Settings\user>route delete 50.0.0.0
```

```
C:\Documents and Settings\user>ping 50.0.0.10
```

```
Pinging 50.0.0.10 with 32 bytes of data:
```

```
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
```

```
Ping statistics for 50.0.0.10:
```

```
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss).
```

```
C:\Documents and Settings\user>
```

Internet Protocol (TCP/IP) Properties

General

You can get IP settings assigned automatically if your network supports this capability. Otherwise, you need to ask your network administrator for the appropriate IP settings.

☐ Obtain an IP address automatically

☒ Use the following IP address:

IP address:

50 . 0 . 0 . 10

Subnet mask:

255 . 0 . 0 . 0

Default gateway:

50 . 0 . 0 . 1

☐ Obtain DNS server address automatically

☒ Use the following DNS server addresses:

Preferred DNS server:

Alternate DNS server:

Advanced...

OK

Cancel

Internet Protocol (TCP/IP) Properties



General

You can get IP settings assigned automatically if your network supports this capability. Otherwise, you need to ask your network administrator for the appropriate IP settings.

☐ Obtain an IP address automatically

☒ Use the following IP address:

IP address:

60 . 0 . 0 . 10

Subnet mask:

255 . 0 . 0 . 0

Default gateway:

60 . 0 . 0 . 1

☐ Obtain DNS server address automatically

☒ Use the following DNS server addresses:

Preferred DNS server:

Alternate DNS server:

Advanced...

OK

Cancel

Destination host unreachable.

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:

Reply from 60.0.0.10: bytes=32 time=3ms TTL=127

Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 3ms, Average = 1ms

C:\Documents and Settings\user>

Minimum = 0ms, Maximum = 4ms, Average = 1ms

C:\Documents and Settings\user>

C:\Documents and Settings\user>route delete 50.0.0.0

C:\Documents and Settings\user>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:

Destination host unreachable.

Destination host unreachable.

Destination host unreachable.

Destination host unreachable.

Ping statistics for 50.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:

Reply from 50.0.0.10: bytes=32 time=1ms TTL=127

Reply from 50.0.0.10: bytes=32 time<1ms TTL=127

Reply from 50.0.0.10: bytes=32 time<1ms TTL=127