

```
SW1#config t
```

```
Enter configuration commands, one per line. End with CNTL/Z.
```

```
SW1(config)#vlan 10
```

```
SW1(config-vlan)#name HR
```

```
SW1(config-vlan)#exit
```

```
SW1(config)#vlan 20
```

```
SW1(config-vlan)#name SALES
```

```
SW1(config-vlan)#exit
```

```
SW1(config)#int e0/0
```

```
SW1(config-if)#switchport access vlan 10
```

```
SW1(config-if)#exit
```

```
SW1(config)#int e0/1
```

```
SW1(config-if)#switchport access vlan 20
```

```
% Invalid input detected at '^' marker.
```

```
SW1(config-if)#switchport access vlan 20
```

```
% Invalid input detected at '^' marker.
```

```
SW1(config-if)#switc
```

```
*Sep 16 02:10:19.585: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Con
```

```
SW1(config-if)#switchport access vlan 20
```

```
SW1(config-if)#exit
```

```
SW1(config)#int e0/2
```

```
SW1(config-if)#switchport trunk encapsulation dot1q
```

```
SW1(config-if)#switchport mode trunk
```

```
SW1(config-if)#exit
```

```
SW1(config)#
```

Enter configuration commands, one per line. End with CNTL/Z.

SW2(config)#vlan 10

SW2(config-vlan)#name HR

SW2(config-vlan)#exit

SW2(config)#vlan 20

SW2(config-vlan)#name SALES

SW2(config-vlan)#exit

SW2(config)#int e0/0

SW2(config-if)#switchport access vlan 10

SW2(config-if)#exit

SW2(config)#int e0/1

SW2(config-if)#switchport access vlan 20

SW2(config-if)#exit

SW2(config)#int e0/2

SW2(config-if)#switchport trunk encapsulation dot1q

SW2(config-if)#switchport mode trunk

SW2(config-if)#exit

SW2(config)#show vlan brief

^
% Invalid input detected at '^' marker.

SW2(config)#exit

SW2#sho

*Sep 16 02:16:11.092: %SYS-5-CONFIG_I: Configured from console by console

SW2#show vlan brief

VLAN	Name	Status	Ports
1	default	active	Et0/3
10	HR	active	Et0/0
20	SALES	active	Et0/1
1002	fddi-default	act/unsup	
1003	token-ring-default	act/unsup	
1004	fddinet-default	act/unsup	
1005	trnet-default	act/unsup	

SW2#

File Edit C:\WINDOWS\system32\cmd.exe

Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

Address C:\Documents and Settings\user>ping 10.0.0.20

Pinging 10.0.0.20 with 32 bytes of data:

Reply from 10.0.0.20: bytes=32 time=1ms TTL=128
Reply from 10.0.0.20: bytes=32 time=1ms TTL=128
Reply from 10.0.0.20: bytes=32 time=1ms TTL=128
Reply from 10.0.0.20: bytes=32 time=1ms TTL=128

Ping statistics for 10.0.0.20:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\Documents and Settings\user>

connection

Other Places ^

- Control Panel
- My Network Places
- My Documents
- My Computer

Network Connections

File Edit View Favorites Tools Advanced Help

Address bar: C:\WINDOWS\system32\cmd.exe

```
Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ping 20.0.0.20

Pinging 20.0.0.20 with 32 bytes of data:

Reply from 20.0.0.20: bytes=32 time=2ms TTL=128
Reply from 20.0.0.20: bytes=32 time=2ms TTL=128
Reply from 20.0.0.20: bytes=32 time=1ms TTL=128
Reply from 20.0.0.20: bytes=32 time=1ms TTL=128

Ping statistics for 20.0.0.20:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>
```

Other Places

- Control Panel
- My Network Places
- My Documents
- My Computer

Details

Local Area Connection

LAN or High-Speed Internet