

Sqlp - Simple terminal query and .sql file processing for Sqlite3

Pablo Edronkin, 2019

<https://orcid.org/0000-0001-8690-7030>

Abstract.

Sqlp is a very small program written in C++ that allows the user to send SQL queries to a Sqlite3 database from a common terminal without the use of any application or library other than itself and Sqlite3.

Keywords.

Sqlite, sqlp, sqlite3, data, database, sql

Acknowledgements.

This project could not have taken place without the work done by:

- The developers of Sqlite3^[6.1.].

License and info for contributors.

Please read the following files included with this project:

- README.md: contains info on setting up your system and installing the files related to this module.

- `CONTRIBUTING.md`: if you want to contribute to this project.
- `COPYING`: for license information.

Table of Contents

| | |
|--|----|
| Abstract..... | 1 |
| Keywords..... | 1 |
| Acknowledgements..... | 1 |
| License and info for contributors..... | 1 |
| 1. Introduction..... | 4 |
| 2. Conventions, caveats and base conditions for development..... | 5 |
| 2.1. Terms and abbreviations used..... | 5 |
| 2.2. Caveats..... | 5 |
| 2.3.1. SQL dialect..... | 5 |
| 2.3.2. Retrieval of query results..... | 5 |
| 2.3.3. Sql file and composite query syntax..... | 6 |
| 2.3.4. System calls..... | 7 |
| 3. Development..... | 8 |
| 3.1. Possible developments in the future..... | 8 |
| 3.1.1. Embed sqlp in a multi threaded environment..... | 8 |
| 3.1.2. Call sqlp from within an uncommon language..... | 8 |
| 3.1.3. Provide multi threading capability from within sqlp..... | 9 |
| 3.2. Operating system..... | 9 |
| 4. Structure..... | 10 |
| 4.1. /doc..... | 10 |
| 4.2. /examples..... | 10 |
| 5. Use..... | 11 |
| 5.1. Installation..... | 11 |
| 5.1.1. Compilation..... | 11 |
| 5.2. Deinstallation..... | 11 |
| 5.3. Usage..... | 12 |
| 6. Sources..... | 13 |
| Alphabetical Index..... | 14 |

1. Introduction.

Sqlite3 is one of the most widely used relational database systems; it is very simple, lightweight and fast, and while it cannot be compared with great server - based relational database systems in terms of versatility or capabilities, it does fill a niche for many users, probably most of those that need a relational database system without the complications involved in maintaining a server – based alternative such as PostgreSQL, Mysql or MariaDB.

Recently I have been developing a dataset based on a Sqlite3 database. Being a relational system, datasets constructed using Sqlite3 are far better to handle and to safely keep data than common flat file formats used for dataset creation, not to mention the fact that data scientists usually spend more time preparing the data from a conventional dataset than actually using the data to do the actual research.

In this regard, SQL offers several advantages over tools used for flat files, plus, data integrity is better on relational databases. However, Sqlite3 has some limitations, and one of those is that it is not easy to execute a significant number of queries or SQL sentences at once using scripts or programs, like it is generally possible with products like those I mentioned before.

The development of this particular dataset requires constant updates and a processing protocol for the data entered that soon became repetitive, so I decided to write myself a program to help me automate the whole work, and thus I wrote sqlc.

This is not an ambitious project but a home – grown solution, so to speak. It does not pretend to be a super tool of any kind but it does the work of executing independent SQL queries or series of several queries grouped into a single file.

2. Conventions, caveats and base conditions for development.

Take into consideration these factors.

2.1. Terms and abbreviations used.

DB: Data base.

RDB: Relational data base.

RDBMS: Relational data base management system.

2.2. Caveats.

While using sqlc you should be aware of:

2.3.1. SQL dialect.

Sqlite3 uses its own SQL dialect. This program does not do anything with the code passed to Sqlite3; however you still need to pass adequate code. Sqlc does not prevent on it

2.3.2. Retrieval of query results.

Some queries return results, while others do not. A SELECT produces essentially a selection or listing, while an INSERT does not.

In the case of those SQL queries that do return results in the form of listings, sqlp stores them into a file called *sqlp_results.txt*, in which the values for every field and record are separated with the character “|”.

Note from example [2.3.3.2] below that in the case of a composite query, results for the second one will be appended to the results of the first query in *sqlp_results.txt*. It is up to the user in such a case to parse those results adequately, or to perform separate calls to sqlp doing a results – producing query on each case, and extracting the data from *sqlp_results.txt* on each occasion.

Keep in mind that each time that sqlc is called, it overwrites *sqlp_results.txt*, but on each call, if results are retrieved more than once, listings are appended at the end of *sqlp_results.txt*, thus:

2.3.2.1. sqlp_results.txt with one listing

```
./sqlc your_database "SELECT * FROM your_table_1;"
```

will overwrite any existing instance of *sqlp_results.txt* in the working folder and fill it with the contents of the SELECT operation described above.

2.3.2.2. sqlp_results.txt with two or more listings

```
./sqlc your_database "SELECT * FROM your_table_1; SELECT * FROM your_table_2;"
```

Will also overwrite any existing instance of *sqlp_results.txt* and will fill it with the results of the first SELECT, and then with the results of the second query appended to the first.

2.3.3. Sql file and composite query syntax.

Sqlc accepts single and composite queries, as well as sql files as input. In all cases you should end each query with a “;” to tell Sqlite3 that each is a separate query.

Examples:

2.3.3.1. Single query

*“SELECT * FROM your_table_1;”*

2.3.3.2. Composite query

*“SELECT * FROM your_table_1; SELECT * FROM your_table_2;”*

2.3.4. System calls.

In theory, Sqlp can be called via a system call from any program written in any language without the need of having language – specific libraries installed. It can also be called directly from the terminal prompt.

3. Development.

This is a very simple, short program written in C++. I wrote it as a time – saving tool to use during the development of a dataset that required some degree of data preparation using a somewhat lengthy and repetitive process.

It is not meant to do miracles, but to pass SQL queries to Sqlite3 using just two arguments, which are the database name and the string representing the query or file that contains the queries.

In the second case, when sqlp is called with an .sql file as second argument, sqlp opens the file and converts all its contents into a single string, that then is passed to Sqlite3. Once data is retrieved from the .sql file and converted into a rather long string, sqlp treats that data exactly as in the case of a short string query.

3.1. Possible developments in the future.

Some ideas that might work in the future, but I have not tested yet are:

3.1.1. Embed sqlp in a multi threaded environment.

Sqlp could work in a multi threaded environment provided by OpenMP or some MPI library integrated into a program that calls sqlp. The only thing to consider is how table locking will be managed by Sqlite3 in practice.

3.1.2. Call sqlp from within an uncommon language.

It would be possible to use sqlp with a language like Scheme or Fortran using a system call and thus eliminating the need for Sqlite3 libraries for those languages that are hard to come by and not updated often.

3.1.3. Provide multi threading capability from within sqlp.

MPI would probably be overkill, but OpenMP could feasibly work. The issue with table locking remains and SQL scripts for a multi threaded environment would require some extra care, but it is still possible.

3.2. Operating system.

I developed sqlp on a Linux machine to use within a Linux environment with gcc. I see no problems for any reasonably seasoned user to compile it for a Windows system.

4. Structure

In the main folder of the project you will find a couple of .cpp and .hpp files, as well as text files containing license and contribution information.

The main project folder also contains two sub folders:

4.1. /doc

This folder contains the manual for sqlp.

4.2. /examples

This folder contains a few example files, including databases and .sql files.

5. Use

5.1. Installation

Uncompress and copy the contents of this file wherever you want in your system.

Copy *sqlite3.cpp* and *sqlite3.h* to the same folder or open *sqlp1.hpp* and modify the *#include "sqlite3.h"* line in *sqlp1.hpp* accordingly, with the path to *sqlite3.h* on your system.

5.1.1. Compilation

In a Linux system using gcc:

```
g++ -std=c++17 -Wall -O3 -c sqlp0.cpp sqlp1.cpp
```

Link as:

```
g++ -std=c++17 -Wall -O3 sqlp0.o sqlp1.o -o sqlp -lsqlite3
```

Users with other operating systems or compilers will find little or no trouble adapting the compile and link snippets above. Please let me know your results in this regard.

5.2. Deinstallation

Delete the folder containing the contents of this file from your system.

5.3. Usage

Assuming that you have `sqlp` on the same folder that holds your database and you are using a Linux system, briefly, in a terminal write:

```
./sqlp [db] [query]
```

where

[db] is the database that you want to query.

[query] is a SQLite3 - compatible SQL query or the name of a `.sql` file.

For example:

*./sqlp your_database "SELECT * FROM your_table_1;"* will send this SELECT query to *your_database* and return the data of all records contained in *your_table_1*. The results will be saved to *sql_results.txt*.

*./sqlp your_database "SELECT * FROM your_table_1;SELECT * FROM your_table_2;"* will send both SELECT queries (composite query) to *your_database*, and *sql_results.txt* will store the results of both queries.

./sqlp your_database your_file.sql will send the queries contained in *your_file.sql* to *your_database* as a composite query. See the */examples* folder for more.

Query results are written as a continuous string to *sqlp_results.txt*. Data fields are separated with a "|" character.

Pay attention to the path to *[db]* and *[query]* if it is a `.sql` file. If they are not in the same folder as `sqlc`, then you will need to provide full paths or add those files or folders to your `$PATH`.

6. Sources

6.1. Sqlite.org. (2000). SQLite Home Page. [online] Available at: <https://www.sqlite.org/index.html> [Accessed 26 Aug. 2019].

Alphabetical Index

A

| | |
|------------------|---|
| advantage..... | 5 |
| append..... | 7 |
| application..... | 1 |

C

| | |
|-------------------|------------|
| call..... | 3, 7pp. |
| Call..... | 3, 9 |
| character..... | 7, 13 |
| code..... | 6 |
| common..... | 1, 3, 5, 9 |
| composite..... | 3, 7, 13 |
| Composite..... | 8 |
| contribute..... | 2 |
| CONTRIBUTING..... | 2 |
| COPYING..... | 2 |

D

| | |
|----------------|--------------------|
| database..... | 1, 5, 7, 9, 11, 13 |
| dataset..... | 5, 9 |
| DBMS..... | 6 |
| develop..... | 1 |
| developer..... | 1 |
| dialect..... | 3, 6 |

E

| | |
|------------------|--------|
| Edronkin..... | 1 |
| environment..... | 3, 9p. |
| es..... | 1, 14 |
| execute..... | 5 |

F

| | |
|--------------|----------------------|
| factor..... | 6 |
| file..... | 1, 3, 5, 7, 9, 11pp. |
| folder..... | 7, 11pp. |
| format..... | 2, 5, 11 |
| Fortran..... | 9 |

G

| | |
|----------|--------|
| g++..... | 12 |
| gcc..... | 10, 12 |

H

| | |
|-------------|---|
| handle..... | 5 |
|-------------|---|

I

| | |
|------------------|-------------|
| independent..... | 5 |
| information..... | 2 |
| INSERT..... | 6 |
| install..... | 1, 3, 8, 12 |
| Install..... | 3, 12 |
| instance..... | 7 |

L

| | |
|----------------|----------|
| libraries..... | 8p. |
| library..... | 1, 9 |
| license..... | 2, 11 |
| License..... | 1, 3 |
| link..... | 12 |
| Link..... | 12 |
| Linux..... | 10, 12p. |
| listing..... | 6p. |
| lock..... | 9p. |
| locking..... | 9p. |
| sqlite..... | 12 |

M

| | |
|--------------|-----------|
| manage..... | 6, 9 |
| MariaDB..... | 5 |
| module..... | 1 |
| mpi..... | 3, 10, 12 |
| MPI..... | 9p. |
| Mysql..... | 5 |

O

| | |
|----------------|-------|
| OpenMP..... | 9p. |
| operating..... | 12 |
| Operating..... | 3, 10 |
| operation..... | 7 |
| orcid..... | 1 |
| overwrite..... | 7 |

P

| | |
|------------------|-------------|
| parse..... | 7 |
| path..... | 12p. |
| PATH..... | 13 |
| PostgreSQL..... | 5 |
| preparation..... | 9 |
| program..... | 1, 5p., 8p. |
| project..... | 1p. |

Q

| | |
|--------------|----------------|
| queries..... | 1, 5pp., 9, 13 |
| query..... | 1, 3, 6pp., 13 |
| Query..... | 13 |

R

| | |
|-----------------|--------------|
| RDBMS..... | 6 |
| README..... | 1 |
| relational..... | 5 |
| Relational..... | 6 |
| repetitive..... | 5, 9 |
| result..... | 3, 6p., 12p. |
| results..... | 3, 6p., 12p. |
| retrieve..... | 7, 9 |
| return..... | 6p., 13 |

S

| | |
|-------------|---|
| Scheme..... | 9 |
|-------------|---|

| | |
|---------------|-----------------------|
| select..... | 6 |
| SELECT..... | 6pp., 13 |
| sentence..... | 5 |
| server..... | 5 |
| setting..... | 1 |
| single..... | 5, 7, 9 |
| Single..... | 8 |
| snippet..... | 12 |
| sql..... | 1, 3, 5pp., 9pp. |
| Sql..... | 1, 3, 5pp., 13p. |
| SQL..... | 1, 3, 5pp., 9p., 13p. |
| sqlite..... | 1, 12, 14 |
| Sqlite..... | 1, 5pp., 9, 13p. |
| SQLite..... | 14 |
| Sqlite3..... | 1 |
| string..... | 9, 13 |
| syntax..... | 3, 7 |
| system..... | 1, 3, 5p., 8pp., 12p. |
| System..... | 3, 8 |

T

| | |
|---------------|----------|
| table..... | 7pp., 13 |
| Table..... | 3 |
| terminal..... | 1, 8, 13 |
| thread..... | 3, 9p. |
| tool..... | 5, 9 |
| trouble..... | 12 |

W

Windows.....10

Y

your_database.....7, 13

your_table.....7p., 13

.

.cpp.....11p.

.hpp.....11p.

.sql.....1, 9, 11, 13p.

.txt.....7, 13

/

/doc.....3, 11

/examples.....3, 11, 13