

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Digital Signal and Image Processing (01CT1513)	AIM : Simulate smoothing and sharpening operation on images using spatial filters.	
Experiment No: 9	Date:	Enrollment No: 92400133030

Code:


```
import cv2
import numpy as np
from google.colab.patches import cv2_imshow
# Load the image
image = cv2.imread('/content/imgae fro exp 9.jpg')
# Define the Gaussian kernel for smoothing
kernel_size = (5, 5)
sigma = 1.5
gaussian_kernel = cv2.getGaussianKernel(kernel_size[0], sigma)
gaussian_kernel = np.outer(gaussian_kernel, gaussian_kernel)
# Apply Gaussian smoothing
smoothed_image = cv2.filter2D(image, -1, gaussian_kernel)
# Define a sharpening kernel
sharpening_kernel = np.array([[ -1, -1, -1],
                               [ -1,  9, -1],
                               [ -1, -1, -1]])
# Apply sharpening
sharpened_image = cv2.filter2D(image, -1, sharpening_kernel)
# Display the original image, smoothed, and sharpened images
cv2_imshow(image)
cv2_imshow(smoothed_image)
cv2_imshow(sharpened_image)
cv2.waitKey(0)
cv2.destroyAllWindows()
```

Output:



Noise image:

```
import cv2
import numpy as np
from google.colab.patches import cv2_imshow
# Load the image
image = cv2.imread('/content/imgae fro exp 9.1.jpg')
# Define the Gaussian kernel for smoothing
kernel_size = (5, 5)
sigma = 1.5
gaussian_kernel = cv2.getGaussianKernel(kernel_size[0], sigma)
gaussian_kernel = np.outer(gaussian_kernel, gaussian_kernel)
# Apply Gaussian smoothing
smoothed_image = cv2.filter2D(image, -1, gaussian_kernel)
# Define a sharpening kernel
sharpening_kernel = np.array([[ -1, -1, -1],
                               [-1, 9, -1],
                               [-1, -1, -1]])
# Apply sharpening
sharpened_image = cv2.filter2D(image, -1, sharpening_kernel)
# Display the original image, smoothed, and sharpened images
cv2_imshow(image)
cv2_imshow(smoothed_image)
cv2_imshow(sharpened_image)
cv2.waitKey(0)
cv2.destroyAllWindows()
```



Aim: write a python program to simulate smoothening using Averaging linear filters

Code: import cv2

```
import numpy as np
from google.colab.patches import cv2_imshow
# Load the image
image = cv2.imread('/content/imgae fro exp 9.jpg')
# Define the size of the Averaging filter kernel
kernel_size = (5, 5) # You can adjust the size based on the desired
#smoothing level
```

```

# Create the Averaging filter kernel
kernel = np.ones(kernel_size, dtype=np.float32) / (kernel_size[0] *
kernel_size[1])
# Apply the Averaging filter for smoothing
smoothed_image = cv2.filter2D(image, -1, kernel)
# Display the original and smoothed images
cv2.imshow(image)
cv2.imshow(smoothed_image)
cv2.waitKey(0)
cv2.destroyAllWindows()

```



Noise image:

```

import cv2
import numpy as np
from google.colab.patches import cv2_imshow
# Load the image
image = cv2.imread('/content/imgae fro exp 9.1.jpg')
# Define the size of the Averaging filter kernel
kernel_size = (5, 5) # You can adjust the size based on the desired
#smoothing level
# Create the Averaging filter kernel
kernel = np.ones(kernel_size, dtype=np.float32) / (kernel_size[0] *
kernel_size[1])
# Apply the Averaging filter for smoothing
smoothed_image = cv2.filter2D(image, -1, kernel)
# Display the original and smoothed images
cv2_imshow(image)
cv2_imshow(smoothed_image)
cv2.waitKey(0)
cv2.destroyAllWindows()

```



Aim: write a python program to simulate smoothening using median filters


Code:

```
import cv2
import numpy as np
from google.colab.patches import cv2_imshow
# Load the image
image = cv2.imread('/content/imgae fro exp 9.jpg')
# Define the size of the median filter kernel (should be an odd number)
kernel_size = 5 # You can adjust the size based on the desired
#smoothing level
# Apply the Median filter for smoothing
smoothed_image = cv2.medianBlur(image, kernel_size)
# Display the original and smoothed images
cv2_imshow(image)
cv2_imshow(smoothed_image)
cv2.waitKey(0)
cv2.destroyAllWindows()
```



Noise image:

```
import cv2
import numpy as np
from google.colab.patches import cv2_imshow
# Load the image
image = cv2.imread('/content/imgae fro exp 9.1.jpg')
# Define the size of the median filter kernel (should be an odd number)
kernel_size = 5 # You can adjust the size based on the desired
#smoothing level
# Apply the Median filter for smoothing
smoothed_image = cv2.medianBlur(image, kernel_size)
# Display the original and smoothed images
cv2_imshow(image)
cv2_imshow(smoothed_image)
cv2.waitKey(0)
cv2.destroyAllWindows()
```



Aim: write a python program to simulate sharpening using spatial high pass filters

Code:

```
import cv2
import numpy as np
from google.colab.patches import cv2_imshow
# Load the image
image = cv2.imread('/content/imgae fro exp 9.jpg')
# Apply Gaussian smoothing to reduce noise (optional but recommended)
blurred_image = cv2.GaussianBlur(image, (5, 5), 0)
# Create a Laplacian kernel for sharpening
laplacian_kernel = np.array([[0, -1, 0],
                             [-1, 5, -1],
                             [0, -1, 0]], dtype=np.float32)
# Apply the Laplacian filter for sharpening
sharpened_image = cv2.filter2D(blurred_image, -1, laplacian_kernel)
# Display the original image, blurred image, and sharpened image
cv2_imshow(image)
cv2_imshow(blurred_image)
cv2_imshow(sharpened_image)
cv2.waitKey(0)
cv2.destroyAllWindows()
```



Noise image:

```
import cv2
import numpy as np
from google.colab.patches import cv2_imshow
# Load the image
image = cv2.imread('/content/imgae fro exp 9.1.jpg')
# Apply Gaussian smoothing to reduce noise (optional but recommended)
blurred_image = cv2.GaussianBlur(image, (5, 5), 0)
# Create a Laplacian kernel for sharpening
laplacian_kernel = np.array([[0, -1, 0],
                             [-1, 5, -1],
                             [0, -1, 0]], dtype=np.float32)
# Apply the Laplacian filter for sharpening
sharpened_image = cv2.filter2D(blurred_image, -1, laplacian_kernel)
```

Display the original image, blurred image, and sharpened image

```
cv2_imshow(image)
```

```
cv2_imshow(blurred_image)
```

```
cv2_imshow(sharpened_image)
```

```
cv2.waitKey(0)
```

```
cv2.destroyAllWindows()
```



Github Link: <https://github.com/PG178/DSIP>