

Обзор некоторых исторических уязвимостей в Postgres

Андрей Бородин, руководитель
подразделения разработки РСУБД с
открытым кодом

 https://github.com/x4m/pg_cve_demo



Обо мне



Развиваю PostgreSQL в интересах Яндекса, Облака и 4 fun

- › Участвовал в разработке ~70 патчей
- › Иногда разрабатываю другие БД




ЗДРАВСТВУЙТЕ.
ЭТО ИЗ ШКОЛЫ, ГДЕ
УЧИТСЯ ВАШ СЫН.
У НАС ТУТ
НЕПРИЯТНОСТИ
С КОМПЬЮТЕРОМ.



О, БОЖЕ. ОН ЧТО-ТО
СЛОМАЛ?
МОЖНО
СКАЗАТЬ...




ВЫ ДЕЙСТВИТЕЛЬНО
НАЗВАЛИ СВОЕГО СЫНА
РОБЕРТ'); DROP
TABLE Students;-- ?



А, ДА. ДОМА МЫ
ЕГО ЗОВЕМ
РОБИН-БРОСЬ-
ТАБЛИЦУ.

ТЕПЕРЬ У НАС СТЕРЛАСЬ
БАЗА УЧЕНИКОВ ЗА
ЭТОТ ГОД.
НАДЕЮСЬ, ВЫ РАДЫ.



А Я НАДЕЮСЬ, ЧТО
ЭТО НАУЧИТ ВАС
ЭКРАНИРОВАТЬ
СИМВОЛЫ
ВО ВХОДНЫХ
ДАННЫХ.

<https://owasp.org/www-project-top-ten/>

OWASP top10

Common Vulnerability Scoring System

←

→

↺

https://nvd.nist.gov/vuln-metrics/cvss/v3-calculator

📄

☆

🔒

⬇

👤

🔴²

📄

☰

CVSS v3.1 Vector

NA

Base Score Metrics

Exploitability Metrics

Attack Vector (AV)*

Network (AV:N)Adjacent Network (AV:A)Local (AV:L)Physical (AV:P)

Attack Complexity (AC)*

Low (AC:L)High (AC:H)

Privileges Required (PR)*

None (PR:N)Low (PR:L)High (PR:H)

User Interaction (UI)*

None (UI:N)Required (UI:R)

Scope (S)*

Unchanged (S:U)Changed (S:C)

Impact Metrics

Confidentiality Impact (C)*

None (C:N)Low (C:L)High (C:H)

Integrity Impact (I)*

None (I:N)Low (I:L)High (I:H)

Availability Impact (A)*

None (A:N)Low (A:L)High (A:H)

* - All base metrics are required to generate a base score.

Temporal Score Metrics

Exploit Code Maturity (E)

Not Defined (E:X)Unproven that exploit exists (E:U)Proof of concept code (E:P)Functional exploit exists (E:F)High (E:H)

Remediation Level (RL)

Not Defined (RL:X)Official fix (RL:O)Temporary fix (RL:T)Workaround (RL:W)Unavailable (RL:U)

Report Confidence (RC)

Not Defined (RC:X)Unknown (RC:U)Reasonable (RC:R)Confirmed (RC:C)

https://nvd.nist.gov/vuln-metrics/cvss/v3-calculator

6

Common Vulnerability Scoring System

Rating	CVSS Score
Low	0.1 - 3.9
Medium	4.0 - 6.9
High	7.0 - 8.9
Critical	9.0 - 10.0


Known PostgreSQL Security Vulnerabilities in Supported Versions

You can filter the view of patches to show just patches for version:
15 - 14 - 13 - 12 - 11 - all


Reference	Affected	Fixed	Component & CVSS v3 Base Score	Description
CVE-2022-41862 Announcement	15, 14, 13, 12	15.2, 14.7, 13.10, 12.14	client 3.7 AV:N/AC:H/PR:N/UI:N /S:U/C:L/I:N/A:N	Client memory disclosure when connecting, with Kerberos, to modified server more details
CVE-2022-2625 Announcement	14, 13, 12, 11	14.5, 13.8, 12.12, 11.17	core server 7.1 AV:N/AC:H/PR:L/UI:R /S:U/C:H/I:H/A:H	Extension scripts replace objects not belonging to the extension more details
CVE-2022-1552 Announcement	14, 13, 12, 11	14.3, 13.7, 12.11, 11.16	core server 8.8 AV:N/AC:L/PR:L/UI:N /S:U/C:H/I:H/A:H	Autovacuum, REINDEX, and others omit "security restricted operation" sandbox more details


CVE-2018-10915: хитрые строки подключения **8.5**

Fixed in 10.5, 9.6.9, и др (9 августа 2018)



CVE-2007-6601





```
postgres=# SELECT dblink_exec(  
'host=my.standby.xyz,localhost dbname=postgres password=imahacker',  
'ALTER USER x4m WITH SUPERUSER;'  
);  
dblink_exec  
-----  
ALTER ROLE  
(1 row)
```

CVE-2022-1552: небезопасное обслуживание 8.8

Fixed in 14.3, 13.7, 12.11, 11.16, 10.21 (12 мая 2022)

```


180 + --
181 + -- Check that index expressions and predicates are run as the table's owner
182 + --
183 + TRUNCATE bttest_a;
184 + INSERT INTO bttest_a SELECT * FROM generate_series(1, 1000);
185 + ALTER TABLE bttest_a OWNER TO regress_bttest_role;
186 + -- A dummy index function checking current_user
187 + CREATE FUNCTION ifun(int8) RETURNS int8 AS $$
188 + BEGIN
189 +     ASSERT current_user = 'regress_bttest_role',
190 +         format('ifun(%s) called by %s', $1, current_user);
191 +     RETURN $1;
192 + END;
193 + $$ LANGUAGE plpgsql IMMUTABLE;
194 + CREATE INDEX bttest_a_expr_idx ON bttest_a ((ifun(id) + ifun(0)))
195 +     WHERE ifun(id + 10) > ifun(10);
196 + SELECT bt_index_check('bttest_a_expr_idx', true);
197 + bt_index_check
198 + -----
199 +
200 + (1 row)
201 +


```

Time to hack!


CVE-2021-23214: TLS аутентификация 8.1

Fixed in 14.1, 13.5, 12.9, 11.14, 10.19, 9.6.24 (11 ноября 2021)





Моя находка в Cancel Request



The screenshot shows a GitHub commit page for the postgres/postgres repository. The commit hash is e52daaak. The commit message is "✓ Reject CancelRequestPacket having unexpected length." The description explains that when the length was too short, the server read outside the allocation, which yielded the same log noise as sending the correct length with (backendPID, cancelAuthCode) matching nothing. The fix changes the message to be about the unexpected length. The commit is attributed to Andrey Borodin, reviewed by Tom Lane, and reported by Andrey Borodin. The commit is on the master branch and was committed on Jan 21 by nmisch.

← → ↻ https://github.com/postgres/postgres/commit/e52daaak

Search or jump to... / Pull requests Issues Codespaces Market

postgres / postgres Public

<> Code Pull requests 1 Actions Security Insights

✓ **Reject CancelRequestPacket having unexpected length.**

When the length was too short, the server read outside the allocation. That yielded the same log noise as sending the correct length with (backendPID,cancelAuthCode) matching nothing. Change to a message about the unexpected length. Given the attacker's lack of control over the memory layout and the general lack of diversity in memory layouts at the code in question, we doubt a would-be attacker could cause a segfault. Hence, while the report arrived via security@postgresql.org, this is not a vulnerability. Back-patch to v11 (all supported versions).

Andrey Borodin, reviewed by Tom Lane. Reported by Andrey Borodin.

master

nmisch committed on Jan 21

```
139  #define CANCEL_REQUEST_CODE PG_PROTOCOL(1234,5678)
140
141  typedef struct CancelRequestPacket
142  {
143      /* Note that each field is stored in network byte order! */
144      MsgType      cancelRequestCode; /* code to identify a cancel request */
145      uint32       backendPID;        /* PID of client's backend */
146      uint32       cancelAuthCode; /* secret key to authorize cancel */
147  } CancelRequestPacket;
```

7 src/backend/postmaster/postmaster.c

@@ -2016,6 +2016,13 @@ ProcessStartupPacket(Port *port, bool ssl_done, bool gss_done)

2016 2016

2017 2017 if (proto == CANCEL_REQUEST_CODE)

2018 2018 {

2019 + if (len != sizeof(CancelRequestPacket))

2020 + {

2021 + ereport(COMMERROR,

2022 + (errcode(ERRCODE_PROTOCOL_VIOLATION),

2023 + errmsg("invalid length of startup packet"));


2024 + return STATUS_ERROR;

2025 + }

2019 2026 processCancelRequest(port, buf);

2020 2027 /* Not really an error, but we don't want to proceed further */

2021 2028 return STATUS_ERROR;




CVE-2020-21469 is
not a security
vulnerability

The [PostgreSQL Security Team](#)
was made aware of [CVE-2020-21469](#), which was filed without the
prior knowledge of the
PostgreSQL Security Team.

**THIS IS NOT A SECURITY
VULNERABILITY.**

The CVE claims that it's possible
to create a denial-of-service in a
PostgreSQL 12.2 by sending
repeated SIGHUP (or reload)
signals to the primary PostgreSQL
process. However, to do this, you
need to have an account that is
explicitly granted elevated
privileges, including:

- A PostgreSQL superuser (postgres).
- A user that was granted permission to execute `pg_reload_conf` by a PostgreSQL superuser.
- Access to a privileged operating system user



security@postgresql.org



**IF YOU SEE
SOMETHING,
SAY
SOMETHING.**


Жду вопросы :)

Андрей Бородин

PostgreSQL contributor



x4mmm @yandex-team.ru



x4mmm