

| DIVIJA SPECIALTY POLYMERS-KHUDUS (AKLUJ).                      |                              |              |                     |          |                                           |                              |                      |                                                                                                                                                                                                 |              |              |                     |                                                                                                                                                                                       |
|----------------------------------------------------------------|------------------------------|--------------|---------------------|----------|-------------------------------------------|------------------------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SHORT OIL AIR DRYING / CHAIN STOPPED ALKYDS                    |                              |              |                     |          |                                           |                              |                      |                                                                                                                                                                                                 |              |              |                     |                                                                                                                                                                                       |
| PRODUCT CODE                                                   | Oil/Fatty Acid Type          | Oil Length % | Non Volatile % ± 2% | Volatile | Viscosity                                 | Acid value (Max) (Mg koh/gm) | Color (Gardner) Max. | Main Application Fields - Architectural / General industrials wood & metal                                                                                                                      |              |              |                     | Application / Features                                                                                                                                                                |
|                                                                |                              |              |                     |          | Seconds @ 30° c FCB4                      |                              |                      | Primer/Undercoat                                                                                                                                                                                | Gloss Enamel | wood varnish | Protective & Marine |                                                                                                                                                                                       |
| DSP FDA 5027                                                   | SOFA                         | 27           | 70                  | Xylene   | 120 -140 sec (100 gm Resin +50 gm Xylene) | 15                           | 6                    |                                                                                                                                                                                                 | OEM/ VR      |              | GI                  | High quality, Non-yellowing, quick drying primers and top coats.                                                                                                                      |
| DSP FDA 5028                                                   | SOFA                         | 28           | 70                  | Xylene   | 130 ± 20 sec (45% XL)                     | 15                           | 6                    |                                                                                                                                                                                                 | OEM/ VR      | 2K PU        | GI                  | Air drying refinishes, low bake industrial stoving enamels, two pack polyurethane based coating                                                                                       |
| DSP FDA 5030                                                   | COFA                         | 30           | 70                  | Xylene   | 40 - 60 (40% Xylene)                      | 15                           | 1                    | •                                                                                                                                                                                               | •            | •            |                     | white baking enamels for refrigerators, washing machinces, water filter and hospitall appliances and as plasticizer for NC Lacquers wood coating. bukkle clear, NC , Sanding sealers, |
| DSP FDA 5038                                                   | SOFA                         | 38           | 70                  | Xylene   | 110 - 150 (50% XL)                        | 12                           | 5                    |                                                                                                                                                                                                 | OEM/ VR      | 2K PU        | GI                  | Air drying refinishes, low bake industrial stoving enamels, two pack polyurethane based coating                                                                                       |
| ACRYLATED ALKYD RESIN - QUICK DRYING RESIN / SPECIALITY RESINS |                              |              |                     |          |                                           |                              |                      |                                                                                                                                                                                                 |              |              |                     |                                                                                                                                                                                       |
| DSP ACRYKYD 5035                                               | SOFA                         | 45           | 60                  | Xylene   | 80 - 100 (50% XL)                         | 10                           | 4                    | Quick drying & good through Hardness without using any driers, Excellent water & chemical resistance, excellent gloss and gloss retention, good adhesion on metal surface and good fkexibility. |              |              |                     |                                                                                                                                                                                       |
| DSP APM 5036                                                   | Epoxy Silicon Modified Resin | NA           | 36 - 38             | Xylene   | 60 - 70 (As such)                         | 1                            | 4                    | Ready to use alluminium paint medium, which is used for making High temperature silver paint upto 300°c                                                                                         |              |              |                     |                                                                                                                                                                                       |