

**DIVIJA SPECIALTY POLYMERS - KHUDUS (AKLUJ)****WAX DISPERSION**

PRODUCT CODE	POLYMER TYPE	Mixed Material Colour (G)	SOLVENT	% Non-volatile @ 150° c	Viscosity @25° (Poise)	Recommended Usages
DSP 5081 - WAXSOL	WAX DISPERSION	MILKY WHITE	XYLENE/ BUTYL ACETATE	10%	1 to 2 Poise	WAXSOL is Wax dispersion on the basis of an EVA copolymer wax for solvent-borne effect coating systems. Improves the orientation of effect pigments and reduces settling in the container. is recommended for solvent-borne base coats and one-coat metallic top coats in industrial coatings. The additive improves the orientation of effect pigments (e.g. aluminium, mica) and enhances the flip-flop effect. Short wave defects are minimized and levelling of the subsequent clear coat layer is improved. Settling in the container is also reduced.

ALLUMINIUM PAINT MEDIUM

PRODUCT CODE	Oil/Fatty Acid Type	Oil Length %	Non Volatile % ± 2%	Volatile	Viscosity @30° (FCB4)	Acid value (Max) (Mg koh/gm)	Color (Gardner) Max.	Recommended Usages
DSP APM 5036	Epoxy Silicon Modified Resin	NA	36 - 38	Xylene	60 - 70 (As such)	1	4	Ready to use alluminium paint medium, which is used for making High temperature silver paint upto 300°c