

		DIVIJA SPECIALTY POLYMERS-KHUDUS (AKLUJ)												
		NEW PRODUCT LIST												
		2K HYDROXYL FUNCTIONAL ACRYLICS												
PRODUCT CODE	% OH on solids	Non Volatile % ± 2	volatile	viscosity in poise @ 25° c	Acid value Max (mg/koh/gm)	Main Application Fields					Application/ Features	Equivalent to /		
						Vehicle Refinishes	Heavy Equipment (A.C.E)	Protective & Marine	General Industrial	Industrial wood finishes				
DSP 05	1.55	55	Xylene	25 to 50	10	•	•	•	•	•	Rapid drying good adhesion to galvanised steel	Synocure 862x - 55		
DSP 06	2.8	60	Xylene /Cellosolve Acetate	60 to 70	10	•	•	•	•	•	High Performance PU Coatings with excellent durability and all round performance	ARKEMA Syn 867 s	RPL Replakryl 929	
DSP 07	2.1	60	Xylene /Cellosolve Acetate	35 to 50	10		•	•	•		High Performance PU Coatings with excellent durability and all round performance	Synocure 870 s - 60	RPL Replakryl 939	
DSP 09	2.1	60	Xylene /Cellosolve Acetate	280 to 320	10			•	•		PU Coatings with excellent flexibility and weathering property compatible with CAB	Synocure 868 s - 60		
DSP 10	2.1	60	Xylene	40 to 50	5	•	•		•	•	Auto-Refinishing, wood coating, ind-coating, chemical resistant & High performance PU coatings.	Synocure 870 s - 60	DRC - Drokryl 7864	
DSP 12	4.5	60	Xylene/Butyl acetate	80 TO 120	10	•	•		•	•	Premium clear coat for vehicle refinish and wood coating application.	MacrynI sm 510 , syn 851 s -60		
HIGH SOLIDS - 2K HYDROXYL FUNCTIONAL ACRYLICS														
DSP 08	2.3	70	Xylene	40% xylene 30 to 60 sec (FCB4 30°C)	8	•	•	•	•		High solids and economical for base/ top coat automotive finishes	MacrynI 8649-70		
DSP 11	2.8	70	Xylene /Cellosolve Acetate	80 - 100	10	•	•	•	•		HIGH PERFORMANCE PU COATING WITH EXLENT DURABLITY & ALL ROUND PERFORMANCE.	macro 8064 , idecryl 8064		
DSP 13	4.5	70	Butyl acetate	40 to 60	10	•	•	•	•		Recommended for high performance industrial, vehicle refinishing & OEM Applications	macrynI sm 515 70BAC , syn 9299BA-70		
DSP 14	2.1	70	Xylene /Cellosolve Acetate	35 to 60	5	•	•	•	•		Air drying and force drying compatible with all types of acrylic resins , interior on metal furniture, agriculture machinery, Domestic appliances. Auto-refinishing,wood coatings, ind-coating, chemical resistant & high performance PU coating.	Replacryl 940		
THERMOSETTING ACRYLIC RESIN / TSA RESIN														
DSP 15	1.55	60	Xylene /Cellosolve Acetate	25 to 35	15 -20	Main Application - OEM & GI CLEAR COAT & MONOCOAT					Low temperature curing paints & lacquers for auto body enamels & domestic appliance finishing.	Synocryl 826s & 829 s -60%		
DSP 16	2.8	60	Xylene /Cellosolve Acetate	10 to 20	15	Main Application - OEM & GI CLEAR COAT & MONOCOAT					Low temperature curing paints & lacquers for auto body enamels & domestic appliance finishing.	macro TSA 1003 - 60%		
THERMOPLASTIC ACRYLIC RESIN														
		Non			Acid value	Main Application Fields								

Ideal 1069

UNICRYL 5007

Ideal 1069

UNICRYL 5007

PRODUCT CODE	Polymer	Volatile % ± 2	volatile	viscosity in poise @ 25° c	Max (mg/koh/gm)	Architectural	Vehicle Refinishes	Home Appliance	Protective & Marine	General Industrial	Application/ Features	Equivalent to /	
DSP 01	copolymer	40	Aromatic solvent 100	10 to 18	10	•	•		•	•	Versatile acrylic resin for decorative & industrial coatings, good durability, glass & color retention. Can also be used as modifier for chlorinated rubber paint. Very high quality flexible air drying finishes with excellent colour, gloss & durability	Synocryl 874 N - 40%	
DSP 02	copolymer	55	Xylene	80 to 100	10		V / R			•	It has very good CAB Compatibility gloss and exterior durability characteristics.	Synocryl 874 x - 45%	
DSP 03	copolymer	50	Xylene	40 - 60	10	•	•	•		Aerosol	Main application is for general purpose masonry,decorative coatings, aerosol paints.TPA exhibit good gloss, color retention,setting properties, good outdoor durability, excellent soap and detergent resistant.	Hitech A4010 x - 50%	
DSP 04	copolymer	60	Xylene	200 TO 230	10	•	•	•	•	•	Excellent flexibility, pigment dispersion and plasticizer. High gloss and gloss retention. Good around weathering properties. Good for exterior concrete applications.		