

**DSP TPA 03- 50%****DIVIJA SPECIALTY POLYMERS**

Product Description: DSP TPA 03-50% is a thermoplastic acrylic resin. Suitable for one component (1K) coatings and top coats. It contains xylene as the volatile component. Provides colour retention and durability. Applications include lacquers and general metal, can and protective marine coatings.

Applications:

- Architectural
- Vehicle refinishes
- Protective & Marine
- General industrial
- Decorative & industrial coatings
- For general purpose masonry.
- Aerosol paints.
- Road marking paints
- Can also be used as modifier for chlorinated rubber paint.

Advantage:

- Good Gloss & color retention
- Excellent soap & detergent Resistance.
- Excellent adhesion on bare metal
- Better durability
- Setting property

Technical Specification:

Property	Unit	Value
Appearance	---	Clear Water White Viscous Liquid
Color	CGS	1 Max
Solid	%	50 ± 2%
Volatile	---	Mix- Xylene
Viscosity @ 25°C	Poise	10 to 15
Acid value	Mg KOH/gm	10.0 Max.

Solubility: DSP TPA 03-50% is supplied in solvent Xylene, which is soluble in all aromatic hydrocarbons, esters and ketones. The resin has limited solubility in aliphatic hydrocarbons & alcohols.

Shelf Life: Under the above mentioned storage conditions the shelf life of the resin will be 12 months.

Packing: 200 Liter MS Drums.

Storage: DSP TPA 03-50% should be stored indoors in the original containers in a dry place at temperature between 5°C and 30°C. Avoid exposure to direct sunlight or frost.

DISCLAIMER: The information contained in this sheet is accurate to the best of our knowledge .In View of conditions of use being totally beyond our control, customers should evaluate the data and make their own tests to determine the suitability of our product for their special use All our products are sold without warranty express or implied, and no liability can be accepted in respect of information and products.