

| <div><div></div><div>DIVIJA SPECIALTY POLYMERS-KHUDUS (AKLUJ)</div></div> |                |                    |                            |                                     |                            |                                                   |                         |                     |                     |                          |                                                                                                                                                                                                                                                             |                                      |                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|--------------------|----------------------------|-------------------------------------|----------------------------|---------------------------------------------------|-------------------------|---------------------|---------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--------------------|
| NEW PRODUCT LIST                                                                                                                                           |                |                    |                            |                                     |                            |                                                   |                         |                     |                     |                          |                                                                                                                                                                                                                                                             |                                      |                    |
| 2K HYDROXYL FUNCTIONAL ACRYLICS                                                                                                                            |                |                    |                            |                                     |                            |                                                   |                         |                     |                     |                          |                                                                                                                                                                                                                                                             |                                      |                    |
| PRODUCT CODE                                                                                                                                               | % OH on solids | Non Volatile % ± 2 | volatile                   | viscosity in poise @ 25° c          | Acid value Max (mg/koh/gm) | Main Application Fields                           |                         |                     |                     |                          | Application/ Features                                                                                                                                                                                                                                       | Equivalent to /                      |                    |
|                                                                                                                                                            |                |                    |                            |                                     |                            | Vehicle Refinishes                                | Heavy Equipment (A.C.E) | Protective & Marine | General Industrial  | Industrial wood finishes |                                                                                                                                                                                                                                                             |                                      |                    |
| DSP 05                                                                                                                                                     | 1.55           | 55                 | Xylene                     | 25 to 50                            | 10                         | •                                                 | •                       | •                   | •                   | •                        | Rapid drying good adhesion to galvanised steel                                                                                                                                                                                                              | Synocure 862x - 55                   |                    |
| DSP 06                                                                                                                                                     | 2.8            | 60                 | Xylene /Cellosolve Acetate | 60 to 70                            | 10                         | •                                                 | •                       | •                   | •                   | •                        | High Performance PU Coatings with excellent durability and all round performance                                                                                                                                                                            | ARKEMA Syn 867 s                     | RPL Replakryl 929  |
| DSP 07                                                                                                                                                     | 2.1            | 60                 | Xylene /Cellosolve Acetate | 35 to 50                            | 10                         |                                                   | •                       | •                   | •                   |                          | High Performance PU Coatings with excellent durability and all round performance                                                                                                                                                                            | Synocure 870 s - 60                  | RPL Replakryl 939  |
| DSP 09                                                                                                                                                     | 2.1            | 60                 | Xylene /Cellosolve Acetate | 280 to 320                          | 10                         |                                                   |                         | •                   | •                   |                          | PU Coatings with excellent flexibility and weathering property compatible with CAB                                                                                                                                                                          | Synocure 868 s - 60                  |                    |
| DSP 10                                                                                                                                                     | 2.1            | 60                 | Xylene                     | 40 to 50                            | 5                          | •                                                 | •                       |                     | •                   | •                        | Auto-Refinishing, wood coating, ind-coating, chemical resistant & High performance PU coatings.                                                                                                                                                             | Synocure 870 s - 60                  | DRC - Drokryl 7864 |
| DSP 12                                                                                                                                                     | 4.5            | 60                 | Xylene/Butyl acetate       | 80 TO 120                           | 10                         | •                                                 | •                       |                     | •                   | •                        | Premium clear coat for vehicle refinsh and wood coating application.                                                                                                                                                                                        | Macrynl sm 510 , syn 851 s -60       |                    |
| HIGH SOLIDS - 2K HYDROXYL FUNCTIONAL ACRYLICS                                                                                                              |                |                    |                            |                                     |                            |                                                   |                         |                     |                     |                          |                                                                                                                                                                                                                                                             |                                      |                    |
| DSP 08                                                                                                                                                     | 2.3            | 70                 | Xylene                     | 40% xylene 30 to 60 sec (FCB4 30°C) | 8                          | •                                                 | •                       | •                   | •                   |                          | High solids and economical for base/ top coat automotive finishes                                                                                                                                                                                           | Macrynl 8649-70                      |                    |
| DSP 11                                                                                                                                                     | 2.8            | 70                 | Xylene /Cellosolve Acetate | 80 - 100                            | 10                         | •                                                 | •                       | •                   | •                   |                          | HIGH PERFORMANCE PU COATING WITH EXLENT DURABILITY & ALL ROUND PERFORMANCE.                                                                                                                                                                                 | macro 8064 , idecryl 8064            |                    |
| DSP 13                                                                                                                                                     | 4.5            | 70                 | Butyl acetate              | 40 to 60                            | 10                         | •                                                 | •                       | •                   | •                   |                          | Recommended for high performance industrial, vehicle refinishing & OEM Applications                                                                                                                                                                         | macrynl sm 515 70BAC , syn 9299BA-70 |                    |
| DSP 14                                                                                                                                                     | 2.1            | 70                 | Xylene /Cellosolve Acetate | 35 to 60                            | 5                          | •                                                 | •                       | •                   | •                   |                          | Air drying and force drying compatible with all types of acrylic resins , interior on metal furniture, agriculture machinery, Domestic appliances. Auto-refinishing,wood coatings, ind coating, chemical resistant & high performance PU coating.           | Replacryl 940                        |                    |
| THERMOSETTING ACRYLIC RESIN / TSA RESIN                                                                                                                    |                |                    |                            |                                     |                            |                                                   |                         |                     |                     |                          |                                                                                                                                                                                                                                                             |                                      |                    |
| DSP 15                                                                                                                                                     | 1.55           | 60                 | Xylene /Cellosolve Acetate | 25 to 35                            | 15 - 20                    | Main Application - OEM & GI CLEAR COAT & MONOCOAT |                         |                     |                     |                          | Low temperature curing paints & lacquers for auto body enamels & domestic appliance finishing.                                                                                                                                                              | Synocryl 826s & 829 s -60%           |                    |
| DSP 16                                                                                                                                                     | 2.8            | 60                 | Xylene /Cellosolve Acetate | 10 to 20                            | 15                         | Main Application - OEM & GI CLEAR COAT & MONOCOAT |                         |                     |                     |                          | Low temperature curing paints & lacquers for auto body enamels & domestic appliance finishing.                                                                                                                                                              | macro TSA 1003 - 60%                 |                    |
| THERMOPLASTIC ACRYLIC RESIN                                                                                                                                |                |                    |                            |                                     |                            |                                                   |                         |                     |                     |                          |                                                                                                                                                                                                                                                             |                                      |                    |
| PRODUCT CODE                                                                                                                                               | Polymer        | Non Volatile % ± 2 | volatile                   | viscosity in poise @ 25° c          | Acid value Max (mg/koh/gm) | Main Application Fields                           |                         |                     |                     |                          | Application/ Features                                                                                                                                                                                                                                       | Equivalent to /                      |                    |
|                                                                                                                                                            |                |                    |                            |                                     |                            | Architectural                                     | Vehicle Refinishes      | Home Appliance      | Protective & Marine | General Industrial       |                                                                                                                                                                                                                                                             |                                      |                    |
| DSP 01                                                                                                                                                     | copolymer      | 40                 | Aromatic solvent 100       | 10 to 18                            | 10                         | •                                                 | •                       |                     | •                   | •                        | Versatile acrylic resin for decorative & industrial coatings, good durability, glass & color retention. Can also be used as modifier for chlorinated rubber paint. Very high quality flexible air drying finishes with excellent colour, gloss & durability | Synocryl 874 N - 40%                 |                    |
| DSP 02                                                                                                                                                     | copolymer      | 55                 | Xylene                     | 80 to 100                           | 10                         |                                                   | V / R                   |                     |                     | •                        | It has very good CAB Compatibility gloss and exterior durability characteristics.                                                                                                                                                                           | Synocryl 874 x - 45%                 |                    |
| DSP 03                                                                                                                                                     | copolymer      | 50                 | Xylene                     | 40 - 60                             | 10                         | •                                                 | •                       | •                   |                     | Aerosol                  | Main application is for general purpose masonry,decorative coatings, aerosol paints.TPA exhibit good gloss, color retention,setting properties, good outdoor durability, excellent soap and detergent resistant.                                            | HiTech A4010 x - 50%                 |                    |
| DSP 04                                                                                                                                                     | copolymer      | 60                 | Xylene                     | 200 TO 230                          | 10                         | •                                                 | •                       | •                   | •                   | •                        | Excellent flexibility, pigment dispersion and plasticizer. High gloss and gloss retention. Good around weathering properties. Good for exterior concrete applications.                                                                                      |                                      |                    |

Ideal 1069

UNICRYL 5007