

		CONSTRUCTION CHEMICALS, ADHESIVES & SPECIALTY PRODUCTS.						
STANDARD EPOXY ADHESIVES - (FIX - TITE)								
PRODUCT CODE	POLYMER TYPE	Colour (G)	SOLVENT	% Non-volatile @ 110° c	RESIN Viscosity @25° (Poise)	HARDENER Viscosity @25° (Poise)	APPLICATION RATIO	Recommended Usages
DSP FIX - TITE	EPOXY ADHESIVES	WATER WHITE & PALE YELLOW	SOLVENT FREE	100%	80 to 120	300 TO 340 POISE	1: 8 (By weight)	FIX - TITE is RAPID, CLEAR, HIGH-STRENGTH EPOXY ADHESIVE. Epoxy Resin and Epoxy Hardener is a rapid-setting, two-component epoxy adhesive with a convenient 1:1 Resin-to-Hardener Mix Ratio. The product generates strong bonds on a wide variety of substrates in a short period of time. No special handling or application techniques are required.
TILE ADHESIVES								
PRODUCT CODE	POLYMER TYPE	Colour (G)	Water Ratio / 20 Kg Bag	Covrage Area ft/kg	Tiles size	Recommended Usages		
TILE ADHESIVE COPPER	Polymer Modified cement based	Greay/white	4 - 5 LTR / 20 KG BAG	2.85 to 3 sq.ft /kg	1 ft x 1 ft max.	Used for fixing high porosity tiles like ceramic/clay. Terracotta and quarry tiles of regular size on cementitious surfaces like plaster or concrete.		
TILE ADHESIVE SILVER	Polymer Modified cement based	Greay/white	4 - 5 LTR / 20 KG BAG	2.85 to 3 sq.ft /kg	2 ft x 2 ft max.	Used for fixing all types of vitrified/fully vitrified tiles, glass mosaic tiles, stone tiles & slab of regular size. It is suitable for both vertical & horizontal surfaces, over the cementitious substrate for indoor application, in dry & wet areas. It is also recommended to tile-on-tile application.		
TILE ADHESIVE GOLD	Polymer Modified cement based	Greay/white	4 - 5 LTR / 20 KG BAG	2.85 to 3 sq.ft /kg	Any Size	Low VOC Polymer modified cementitious adhesive, used for fixing ceramic, vitrified, glass mosaic, glass tiles, and natural stones on interior floors and walls, suitable for tile-on-tile installations. High bond strength, high grab & non sag property, better workability.		
TILE ADHESIVE PLATINUM	Polymer Modified cement based	Greay/white	4 - 5 LTR / 20 KG BAG	2.85 to 3 sq.ft /kg	Any Size	Used for fixing large-format vitrified/porcelain tiles, natural stone, marbale and exterior facades, it offers high flexibility, strong bond strength, and is suitable for wet areas & heavy-traffic zones, granite, marble & artificial stones on both floors and walls.		
BLOCK JOINT MORTAR								
PRODUCT CODE	POLYMER TYPE	Colour (G)	Water Ratio / 30 Kg Bag	Covrage Area ft/kg	Pot Life	Recommended Usages		
BLOCK JOINT MORTAR	Polymer Modified cement based	Greay	6.5 To 8 Ltrs / 30 kg bag	3 to 4 sq.ft /kg	30 to 1 Hrs	Ready to use grey cement based non-shrink, self-curing mortar for fixing AAC blocks, concrete blocks, fly ash bricks etc.		
READY MIX PLASTER (RMP)								
PRODUCT CODE	POLYMER TYPE	Colour (G)	Water Ratio / 40 Kg Bag	Covrage Area ft/kg	Pot Life	Recommended Usages		
READY MIX PLASTER (RMP)	cement, sand and polymers mixture	Greay	6 to 7 ltrs/ 40 kg bag	4.5 to 5.5 sq.ft/kg	60 to 90 min	RMP is a polymer-modified, pre-mixed mortar requiring only water to be applied on prepared, clean surfaces via trowel or spray at 12 to 15 mm thickness. It offers superior adhesion, minimal shrinkage and fast curing in 3 -4 days, significantly reducing on site work and material wastage compared to traditional sand-cement mixes.		
WHITE CEMENT BASE WALL PUTTY								
PRODUCT CODE	POLYMER TYPE	Colour (G)	Water Ratio / 40 Kg Bag	Covrage Area ft/kg	Pot Life	Recommended Usages		
DSP PREMIUM WALLCARE PUTTY	Polymer Modified White cement based	White	14 to 18 ltrs/ 40 kg bag	14 to 16 sq.ft/kg(2 coats)	2 to 3 hrs after mixing with water	wall putty is a white cement based, polymer-modified material primarily used to create a smooth, level and durable base on interior or exterior walls before painting. It fills cracks, dents and pores, enhances paint adhesion, prevents dampness and boosts paint longevity, ensuring a professional, premium finish.		
CONCRETE MASTER LW+100								
PRODUCT CODE	POLYMER TYPE	Colour (G)	PH Value	Dosage/50 kg bag	Non volatile %	Recommended Usages		
CONCRETE MASTER LW+100	Integral Waterproofing Liquid admixture	Wine red	11 to 14	200 to 250 ml	13.5 to 14.5%	It is specially formulated integral waterproofing liquid admixture composed of surfaces active plasticizing agents, polymers & additives. It is used as an additive for cement concrete, mortar & plasters.it makes concrete cohesive & prevents segregation.		
1K & 2K CLEARS FOR MIVAN COATING (Steel, Metal, Wood coating)								
PRODUCT CODE	COLOR (Gardener)	Viscosity @30° (FCB4)	Solids %	Tack free	Hard dry	Application Ratio	Recommended Usages	
DSP 1K Antitar clear coat	water white	40 TO 60 Sec	38 to 40%	40 to 60 min	over Night	As such with 4 to 6% thinner	This is single pack product is having good corrosion resistance & fast drying properties. It is mainly recommended to use for various application like Copper Bottles, Copper Tubes, Aluminium Formwork, Industrial machined components, Industrial coated surface where gloss improvement is required etc	
DSP 2K ALU clear coat	water white	40 TO 60 Sec	38 ± 2%	40 to 60 min	over Night	04:01, (use thinner upto 10%)	This is 2 pack product is having good corrosion resistance & fast drying properties. It is mainly recommended to use for various application like Copper Bottles, Copper Tubes, Aluminium Formwork, Industrial machined components, Industrial coated surface where gloss improvement is required etc	
SHUTTERING OIL FOR MIVAN COATING								
PRODUCT CODE	COLOR (Gardener)	Viscosity @30° (FCB4)	Solids %	Covrage Area sq. mtr /ltr	Specific Gravity	Recommended Usages		
MIVAN SHUTTERING OIL	Pale yellow liquid	17 to 25 sec	100%	20 -40 sq. mtr/ltr	0.86 to 0.91	Mivan shuttering oil is a specialized, low viscosity release agent -often a blend of mineral oils & additives designed for aluminium formwork to ensure easy stripping , reduce surface defects(blowholes) and protect metal from corrosion. It provide high coverage and produces a non- staining , smooth, fair-faced concrete finish.		
PAVOUR BLOCK LAQUERS & HARDENER.								
PRODUCT CODE	COLOR (Gardener)	Viscosity @30° (FCB4)	Solids %	Tack free	Hard dry	Application Ratio	Recommended Usages	
DSP TPA 04-30%	Water white	40 TO 60 Sec	28 to 30%	40 to 60 min	over Night	As such with 4 to 6% thinner	Clear Coating on paver blocks and concrete flooring. Used for polishing to pavour blocks.	
DSP PREMIUM HARDENER 100	Brawn	40 TO 60 Sec	37 ± 2%	NA	2 HRS	200 to 250 ml	Paver block hardener is a liquid admixture added to concrete during mixing to increase compressive strength, accelerate curing, it accelerating setting times for faster demolding.	
ADMIXTURE FOR READY MIX CONCRETE (RMC)								
PRODUCT CODE	COLOR (Gardener)	PH Value	Solids %	chloride Content	Density	Dosage/50 kg bag	Recommended Usages	
DSP ADMIXTURE 300	Brawn	7+	69 ± 2%	Nil	1.07 ± 0.02.	200 to 250 ml	DSP ADMIXTURE 300 is a high performance super plasticizer designed to achieve a low water/cement ratio and extended workability. It enhances concrete strength, achieves high workability, reduces the cement content, makes it a versatile choice for a range of concrete application because of its ability to disperse cement particle effectively which increases the surface area available for hydration.	