



AMRITLAL CHEMAUX PVT. LTD.

ALKYD RESINS

LONG OIL ALKYDS

PRODUCT CODE	Oil / Fatty Acid Type	Oil Length %	Nob Volatile % $\pm$ 2 %	Volatile	Viscosity		Acid value(Max) (Mg koh/gm)	Color (Gardner) Max	Main Application Fields - Architectural / General industrials wood & metal				Application / Features	Equivalent to
					Seconds @ 30° c	Poise @ 25° c			Primer / Undercoat	Gloss Enamel	wood varnish	Protective & Marine		
ACKYD 5034-70%	Soyabean	58	70	MTO	100 - 120 (50%MTO)	NA	15	6	•	•		•	Long Oil, Penta Erithritol esterified Alkyd Resin modified with Soya Bean Oil. Good brush ability. Good drying properties. Good durability and very good yellowing resistance in light and darkness. Used for Air drying & Enamel Paints.	Macro S - 5060

SHORT OIL ALKYDS

ACKYD 5025	COFA	31	70	xylene	40 - 60(40% xylene)	1 - 2 (40% xylene)	15	1	•	•	•		white baking enamels for refrigerators, washing machines, water filter and hospital appliances and as plasticizer for Nc Lacquers wood coating, bukkle clear, Nc, Sanding sealers.	Macro C - 1032
ACKYD 5030	DCO	42	70	MTO		15 - 20 (50% XL)	20	8		Baking Paint			General purpose alkyd for stoving enamels, Primers & NC lacquers.	Synolac - 4004 - 70

ROSINATED ALKYDS

ACKYD 5031 - LC 70%	SOFA	30	70	xylene	180 - 220 (50%MTO)	6.5 - 8 (50%MTO)	15 max	6	•	•		•	Low cost air drying and stoving enamels and undercoats	Synolac - 6003 / RDCO - 50%
ACKYD 5032 - 70%	SOFA	42	70	MTO	140 - 160 (50%MTO)	4.5 - 5.5 (50%MTO)	20 max	6	•	•		•	Low cost air drying and stoving enamels and undercoats	Synolac - 6003 / RDCO - 70%
ACKYD - 7070	SOFA	40	70	MTO	60 - 80 (40%MTO)	2 - 2.5 (40%MTO)	15 max	6	•	•		•	Low cost air drying and stoving enamels and undercoats	Synolac - 6003 / RDCO - 70% (Low viscosity)

CHAIN TERMINATED ALKYDS

ACKYD - 5021	SOFA	42	55	MTO / xylene	NA	40 - 50	10	8		OEM / VR		GI	High quality vehicle refinishes, fast drying industrial finishes and Low bake finishes.	Synolac 72 S - 55
ACKYD 5022 - 55%	SOFA	38	55	Xylene	140 - 160 (50% XL)	4.5 - 5.5 (50% XL)	12	8		OEM / VR	2K PU	GI	Air drying refinishes, low bake industrial stoving enamels, two pack polyurethane based coating	Synolac 82 x - 55%
ACKYD 5022 - 70%	SOFA	38	55	Xylene	140 - 160 (50% XL)	4.5 - 5.5 (50% XL)	12	8		OEM / VR	2K PU	GI	Air drying refinishes, low bake industrial stoving enamels, two pack polyurethane based coating	Synolac 82 x - 70%
ACKYD 5023 - 55%	SOFA	26	55	Xylene	200 - 250 (50% XL)	7 - 10 (50% XL)	15	8		OEM / VR		GI	High quality, Non-yellowing quick drying Primers and top coats.	Synolac 92 x - 55
ACKYD 5023 - 70%	SOFA	26	70	Xylene	200 - 250 (50% XL)	7 - 10 (50% XL)	15	8		OEM / VR		GI	High quality, Non-yellowing quick drying Primers and top coats.	Synolac 92 x - 70
ACKYD 6023	SOFA	32	70	Xylene	200 - 250 (50% xylene)	7 - 10 (50% XL)	7 - 12	6		OEM / VR		GI	High quality, Non-yellowing quick drying Primers and top coats.	
ACKYD 6025	SOFA	30	70	Xylene	250 - 300 (46.5% xylene)	10 - 11 (50% XL)	7 - 12	6		OEM / VR		GI	High quality, Non-yellowing quick drying Primers and top coats.	
ACKYD 6026	SOFA	26	70	Xylene	170 - 210 (46.5% xylene)	6 - 8 (46.5% xylene)	7 - 12	6		OEM / VR		GI	High quality, Non-yellowing quick drying Primers and top coats.	
ACKYD 6027	SOFA	25	70	Xylene	170 - 210 (46.5% xylene)	6 - 8 (46.5% xylene)	7 - 12	6		OEM / VR		GI	High quality, Non-yellowing quick drying Primers and top coats.	RPL 536

ACRYLATED / STYRENETED ALKYD RESIN - QUICK DRYING RESIN / SPECIALITY ALKYDS RESIN

CACRYALKYD 5035	SOFA	45	55	XL / Toulene	NA	5 - 7	8	2	Roller coating enamels and varnishes with excellent tooling, decorative & metal finishes, quick drying chemical resistant paints, quick drying machinery paints.					Syn 9006
CACRYALKYD 5036	SOFA	45	60	Xylene	NA	25 - 35	10	2	Roller coating enamels and varnishes with excellent tooling, decorative & metal finishes, quick drying chemical resistant paints, quick drying machinery paints.					Hitech 30601 - 60%