

**DSP TPA 04 - 60%****DIVIJA SPECIALTY POLYMERS**

Product Description: DSP TPA 04-60% Thermoplastic acrylic copolymers are having excellent flexibility, pigment dispersion properties and plasticizer resistance. High gloss and good gloss retention. Excellent yellowing resistance. Very suitable binder for metallic shades. Excellent hardness. Very good durability. Low odour type.

Applications:

- Used for concrete & other outdoor construction.
- Concrete flooring
- Paver blocks
- Air drying Decorative & industrial coatings
- Very suitable for metallic shades

Advantage:

- Excellent flexibility
- Good pigment dispersion & plasticizer resistance
- High gloss & good gloss retention
- Excellent yellowing resistance
- Excellent hardness
- Very good durability
- Low odor type.

Technical Specification:

Property	Unit	Value
Appearance	---	Clear Water White Viscous Liquid
Color	CGS	1 Max
Solid	%	60 ± 2%
Volatile	---	Mix- Xylene
Viscosity @ 25°C	Poise	200 to 230
Acid value	Mg KOH/gm	15.0 Max.

Solubility: DSP TPA 04-60% is supplied in solvent Xylene, which is soluble in butyl acetate, MEK, Ethyl glycol acetate.

Shelf Life: Under the above mentioned storage conditions the shelf life of the resin will be 12 months.

Packing: 200 Liter MS Drums.

Storage: DSP TPA 04-60% should be stored indoors in the original containers in a dry place at temperature between 5°C and 30°C. Avoid exposure to direct sunlight or frost.

DISCLAIMER: The information contained in this sheet is accurate to the best of our knowledge .In View of conditions of use being totally beyond our control, customers should evaluate the data and make their own tests to determine the suitability of our product for their special use All our products are sold without warranty express or implied, and no liability can be accepted in respect of information and products.

Date: 23.02.2021

DIVIJA SPECIALTY POLYMERS , OFFICE ADDRESS – FLAT NO-D301, D BUILDING, GRAND ORCHID APARTMENT , OPPOSITE KIRLOSKER CHILLER,
SASWAD, TAL –PURANDER , DIST –PUNE , PIN 412301..

Page1 of 1